
**Pneumatic fluid power —
Compressed-air lubricators —**

Part 2:

**Test methods to determine the main
characteristics to be included in
supplier's literature**

Transmissions pneumatiques — Lubrificateurs pour air comprimé —

*Partie 2: Méthodes d'essai pour déterminer les principales
caractéristiques à inclure dans la documentation du fournisseur*



STANDARDSISO.COM : Click to view the full PDF of ISO 6301-2:2018



COPYRIGHT PROTECTED DOCUMENT

© ISO 2018

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Fax: +41 22 749 09 47
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

	Page
Foreword.....	iv
Introduction.....	v
1 Scope.....	1
2 Normative references.....	1
3 Terms and definitions.....	1
4 Units and symbols.....	2
5 Test conditions and samples.....	2
5.1 Temperature.....	2
5.2 Pressures.....	2
5.3 Test samples.....	2
6 Test procedure to verify rated pressure.....	2
7 Air flow rate tests.....	3
8 Test procedure to establish the minimum operating air flow rate.....	4
8.1 Option 1.....	4
8.2 Option 2.....	5
9 Measurement of reservoir capacity.....	5
10 Identification statement.....	5
Bibliography.....	6

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 131, *Fluid power systems*, Subcommittee SC 5, *Control products and components*.

This third edition cancels and replaces the second edition (ISO 6301-2:2006), which has been technically revised.

The main changes compared to the previous edition are as follows:

— the normative references have been updated.

A list of all parts in the ISO 6301 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

In pneumatic fluid power systems, power is transmitted and controlled through air under pressure within a circuit. Where lubrication of the air media is desired, compressed air lubricators are components designed to introduce the required quantity of lubricant into the air stream.

STANDARDSISO.COM : Click to view the full PDF of ISO 6301-2:2018

STANDARDSISO.COM : Click to view the full PDF of ISO 6301-2:2018

Pneumatic fluid power — Compressed-air lubricators —

Part 2:

Test methods to determine the main characteristics to be included in supplier's literature

1 Scope

This document specifies tests, procedures and a method of presenting the results concerning the parameters that define the main characteristics to be included in the supplier's literature of lubricators conforming to ISO 6301-1.

This document can be applied:

- to facilitate the comparison of lubricators by standardizing test methods and presentation of test data;
- to assist in the proper application of lubricators in compressed-air systems.

The tests specified are intended to allow comparison between the different types of lubricators; they are not production tests to be carried out on each lubricator manufactured.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 3, *Preferred numbers — Series of preferred numbers*

ISO 1219-1, *Fluid power systems and components — Graphical symbols and circuit diagrams — Part 1: Graphical symbols for conventional use and data-processing applications*

ISO 2944, *Fluid power systems and components — Nominal pressures*

ISO 3448, *Industrial liquid lubricants — ISO viscosity classification*

ISO 5598, *Fluid power systems and components — Vocabulary*

ISO 6301-1:2017, *Pneumatic fluid power — Compressed-air lubricators — Part 1: Main characteristics to be included in supplier's literature and product-marking requirements*

ISO 6358-1:2013, *Pneumatic fluid power — Determination of flow-rate characteristics of components using compressible fluids — Part 1: General rules and test methods for steady-state flow*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 5598 and ISO 6301-1 apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <https://www.iso.org/obp>

4 Units and symbols

Units from ISO 80000-1 are generally used in pneumatic fluid power systems, in particular:

- gauge pressure, expressed in kilopascal (bar);
- temperature, expressed in degrees Celsius;
- air flow rate, expressed in litres per second or cubic decimetres per second (in Standard Reference Atmosphere, ANR) (see ISO 8778).

The graphical symbols used in [Figure 1](#) are in accordance with ISO 1219-1.

5 Test conditions and samples

5.1 Temperature

The temperature of the processed air, the equipment and the ambient air shall be maintained at $23\text{ °C} \pm 5\text{ °C}$ for all tests.

5.2 Pressures

The specified pressures shall be held to within a tolerance of $\pm 2\%$. The preferred test pressures are those given in ISO 6301-1:2017, 4.2.1 or ISO 2944. Where other test pressures are required, the value shall be selected from the series R 5 of preferred numbers, according to ISO 3.

5.3 Test samples

Test a minimum of three random samples in each of [Clauses 6, 7, 8, 9](#) and use the average of the results.

6 Test procedure to verify rated pressure

6.1 Perform this test with a proposed rated pressure for the product.

6.2 In this test, the product-sealing means may be modified to prevent leakage and allow structural failure to occur, but modifications shall not increase the structural strength of the pressure-containing envelope.

6.3 Fill samples with liquid whose viscosity does not exceed ISO VG 32, in accordance with ISO 3448, and install them in the temperature environment described in [5.1](#).

6.4 After stabilizing the temperature, pressurise slowly to a level of 1,5 times the proposed rated pressure. Hold at this level for 2 min and observe the sample for leakage or failure (as defined in [6.6](#)).

6.5 If there is no leakage or failure, increase the pressure by approximately half of its proposed rated pressure. Hold at this pressure for 2 min and observe the sample for leakage or failure (as defined in [6.6](#)).

If there is still no leakage or failure, in terms of the following units:

- a) for products constructed of light alloys, brass and steel: continue raising the pressure as above until a level of four times the proposed rated pressure has been reached;
- b) for products constructed of zinc die cast alloys or plastics:
 - used at operating temperatures up to 50 °C , continue raising the pressure as above until a level of four times the proposed rated pressure has been reached;

- used at operating temperatures between 50 °C and 80 °C, continue raising the pressure as above until a level of five times the proposed rated pressure has been reached.

6.6 Criteria for failure are a fracture, a separation of parts or a crack or any phenomenon that can pass liquid across the pressure-containing envelope sufficiently to wet the outer surface. Leakage across port threads shall not constitute a failure unless caused by a fracture or crack.

6.7 The proposed rated pressure is verified if all three samples pass the test.

6.8 Where a unit or sub-assembly in the unit (e.g. reservoir or sight glass) is constructed of different materials, the highest appropriate ratio between the test pressure and rated pressure should be used. The application of pressure may be restricted to the area of the interface between the different materials.

6.9 Where the design of the pressure-containing envelope is covered by a pressure vessel code in the country of sale, the requirements of that code take precedence over the requirements stated in this document.

7 Air flow rate tests

7.1 The test circuit for constant upstream pressure test shall be in accordance with ISO 6358-1:2013, Figure 1, Table 4 and 5.1.

7.2 The pressure-measuring tubes shall be in accordance with ISO 6358-1:2013, Figure 3, Table 4 and 5.4. The transition connectors shall be in accordance with ISO 6358-1:2013, 5.5.

7.3 The oil-feed control shall be set to zero and there shall be no oil in the reservoir.

NOTE The purpose of this operation is to reduce the chance of contamination of the flow rate measuring device.

7.4 Each series of results obtained for a specified test condition shall be recorded as soon as a steady-state condition has been reached. Recording shall be carried out with care making sure that the conditions would be modified slowly enough to avoid a drift in the steady-state characteristic. A periodic check shall be made to verify that no pressure intakes of measuring instruments are blocked by solid or liquid particles.

7.5 Set the inlet pressure to test levels of 250 kPa (2,5 bar), 630 kPa (6,3 bar), 1 000 kPa (10 bar) or at the rated pressure, if different from 1 000 kPa (10 bar). Adjust the pressure regulator as required to maintain the selected inlet pressure at a constant value throughout the test.

7.6 Begin circulating air through the test circuit, recording air flow rate and pressure drop, up to a maximum air flow rate corresponding to a pressure drop equal to the lesser of 80 kPa (0,8 bar) or 20 % of the inlet pressure. Then record air-flow rate and pressure drop with air-flow rate decreasing to zero.


7.7 Results shall be taken from the mean of the increasing or decreasing air flow rate data and presented in accordance with ISO 6301-1:2017, Figure 2, recording the port size and type of lubricator, or in accordance with ISO 6301-1:2017, Table 1, where the air-flow rate at which the pressure drop is 5 % of the inlet pressure is tabulated.

8 Test procedure to establish the minimum operating air flow rate

NOTE Non-recirculating lubricators dispense all the oil drops observed in the sight dome into the downstream air flow and measurement of the drop rate is a direct indication of the quantity of oil being carried in the downstream air. Recirculating lubricators direct the oil drops passing through the sight dome to a venturi in which the oil is sheared to form a mist of oil particles in the lubricator reservoir. A significant quantity of these particles settle in the reservoir and only a fraction of the generated particles are carried into the downstream air flow. The drop rate visible in the sight dome is not a direct measure of the quantity of oil delivered.

8.1 Option 1

8.1.1 Install the lubricator into the test circuit as described in [Figure 1](#).



Key

1	pressure regulator	5	general purpose filter
2	pressure gauge	6	coalescing filter
3	couplings	7	flow control valve
4	test lubricator	8	flowmeter

Figure 1 — Test circuit

8.1.2 The reservoir shall be partially filled with a liquid of viscosity equal to that of ISO VG 32, according to ISO 3448, to a liquid level approximately 25 % of the reservoir capacity as determined in [Clause 9](#).

8.1.3 Set the oil-feed mechanism to its maximum open position and maintain this throughout the test.

8.1.4 With the supply pressure held constant at 630 kPa (6,3 bar) or the rated pressure, if lower, open the flow control valve in the test circuit to generate an oil delivery of at least

- 1 drop per minute per 5 dm³/s (ANR) of flow for non-recirculating lubricators, or
- 10 drops per minute per 5 dm³/s (ANR) of flow for recirculating lubricators.

8.1.5 Remove and weigh the lubricator.

8.1.6 Install the lubricator and, without adjusting the flow control valve or lubricator drip setting, reapply the test pressure. Note the air-flow rate, and run the test for at least 30 min. Record the elapsed time. Stop the air flow and depressurize the test circuit.

NOTE At low air-flow rates, it can be necessary to extend the test period in order to deliver a significant amount of oil output.

8.1.7 Remove the lubricator and reweigh it. The difference between this mass and the mass determined in [8.1.5](#) is the amount of oil delivered over the test period. Use this mass to establish the oil output density in milligrams per cubic metre (ANR).

8.1.8 Repeat the test described in [8.1.6](#) with the air flow adjusted as necessary to achieve a nominal oil output density of 60 mg/m³ (ANR).

8.1.9 The minimum operating air flow rate can be established by interpolation or extrapolation of three results.

NOTE If the oil drop mass in a sight dome of a non-recirculating lubricator is known, the oil output can be established by noting the number of drops delivered over a test period.

8.2 Option 2

8.2.1 Install the lubricator into the test circuit as described in [7.1](#) and [7.2](#), with the exceptions that the downstream pressure-measuring tube is removed and the flowmeter is located only in the upstream part of the circuit.

8.2.2 The reservoir shall be partially filled with a liquid of viscosity equal to that of ISO VG 32, according to ISO 3448, to a liquid level approximately 25 % of the reservoir capacity as determined in [Clause 9](#).

8.2.3 Set the oil feed mechanism to its maximum open position and maintain this throughout the test.

8.2.4 With the supply pressure held constant at 630 kPa (6,3 bar) or the rated pressure, if lower, sufficiently open the flow control valve in the test circuit to generate an oil delivery of at least 5 drops per minute, as observed in the sight dome. Record the corresponding air-flow rate as the minimum operating air-flow rate.

9 Measurement of reservoir capacity

9.1 With the lubricator completely assembled, measure the amount of liquid necessary to fill the reservoir from the level 2 mm above the bottom of the pick-up tube to the maximum fill level marked by the manufacturer.

9.2 Determine the average for each group of samples. This value shall be the rated reservoir capacity for a given reservoir size.

10 Identification statement

Manufacturers who have chosen to conform to this document should use the following statement in test reports, catalogues and sales literature:

"Main characteristics of compressed-air lubricators determined in accordance with ISO 6301-2:2018, Pneumatic fluid power — Compressed-air lubricators — Part 2: Test methods to determine the main characteristics to be included in supplier's literature."