
**Earth-moving machinery —
Determination of emission sound
pressure level at operator's position —
Stationary test conditions**

*Engins de terrassement — Détermination du niveau de pression
acoustique d'émission au poste de conduite — Conditions d'essai
statique*



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

STANDARDSISO.COM : Click to view the full PDF of ISO 6394:2008



COPYRIGHT PROTECTED DOCUMENT

© ISO 2008

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 6394 was prepared by Technical Committee ISO/TC 127, *Earth-moving machinery*, Subcommittee SC 2, *Safety requirements and human factors*, in collaboration with Technical Committee ISO/TC 43, *Acoustics*, Subcommittee SC 1, *Noise*.

This third edition cancels and replaces the second edition (ISO 6394:1998), which has been technically revised.

Introduction

This International Standard is a specific test code for earth-moving machinery as defined in ISO 6165. It is an extension of ISO 11201, which contains the general requirements of many types of machinery and equipment.

Specific procedures are described in this International Standard to enable the time-averaged A-weighted emission sound pressure level in stationary test conditions to be determined in a manner which is repeatable. Attachments (bucket, dozer, etc.) for the manufacturer's production version are intended to be fitted since this is the configuration most likely to exist when the machine is in actual use.

This International Standard enables compliance with noise limits to be determined, if applicable. It can also be used for evaluation purposes in noise reduction investigations.

A complementary test code is given in ISO 6393. This other specific test code is intended to be used to determine the noise emitted by earth-moving machinery in terms of the A-weighted sound power level with the machine under stationary test conditions.

Corresponding measurements of noise emitted to the environment and noise at the operator's position under dynamic test conditions are described in ISO 6395 and ISO 6396, respectively.

STANDARDSISO.COM : Click to view the full PDF of ISO 6394:2008

Earth-moving machinery — Determination of emission sound pressure level at operator's position — Stationary test conditions

1 Scope

This International Standard specifies a method for determining the emission sound pressure level of earth-moving machinery at the operator's position, measured in terms of the time-averaged A-weighted emission sound pressure level while the machine is stationary with the engine operating at the rated speed under no-load conditions.

It is applicable to earth-moving machinery as defined in ISO 6165 and specified in ISO 6393:2008, Annex A.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 3411, *Earth-moving machinery — Physical dimensions of operators and minimum operator space envelope*

ISO 6165, *Earth-moving machinery — Basic types — Identification and terms and definitions*

ISO 6393:2008, *Earth-moving machinery — Determination of sound power level — Stationary test conditions*

ISO 9249, *Earth-moving machinery — Engine test code — Net power*¹⁾

ISO 11201, *Acoustics — Noise emitted by machinery and equipment — Measurement of emission sound pressure levels at a work station and at other specified positions — Engineering method in an essentially free field over a reflecting plane*²⁾

IEC 61672-1, *Electroacoustics — Sound level meters — Part 1: Specifications*

1) To be published. (Revision of ISO 9249:1997)

2) To be published. (Revision of ISO 11201:1995)

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 11201, ISO 6165 and the following apply.

3.1 time-averaged A-weighted sound pressure level

$L_{pA,T}$
A-weighted sound pressure level averaged on an energy basis over the whole measurement period, T

4 Instrumentation

The instrumentation shall be capable of carrying out measurements as described in Clause 8. The preferred instrumentation system for acquiring the data is an integrating-averaging sound level meter complying with the requirements of IEC 61672-1 for a class 1 instrument.

5 Test environment

For the purposes of this International Standard, the test environment specified in ISO 6393 applies.

6 Measurement of time-averaged A-weighted sound pressure levels

6.1 Operator stature

The operator shall have a stature between the small operator and the large operator as defined in ISO 3411. See also 6.2.2.2.

6.2 Operator presence

6.2.1 Ride-on machines

6.2.1.1 Operator's position

The operator shall be in the driving position and observers shall not be in close proximity or in the cab during sound measurement. The operator shall wear neither abnormally sound-absorptive clothing nor any hat or scarf (other than a protective helmet used for safety reasons, or a helmet or frame used to support a microphone) which might influence the noise measurement.

6.2.1.2 Seat adjustment

The seat shall be set at, or as near as possible to, the midpoint of its horizontal and vertical adjustment. Any seat suspension shall be adjusted to the operator's weight.

6.2.2 Pedestrian-controlled machines

6.2.2.1 Operator's position

The operator shall be in the usual working position specified by the manufacturer and observers shall not be in close proximity to the operator during sound measurement. The operator shall wear neither abnormally sound-absorptive clothing nor any hat or scarf (other than a protective helmet used for safety reasons, or a helmet or frame used to support a microphone) which might influence the noise measurement.

6.2.2.2 Standing operator

The standing operator shall have a stature of $1\,715\text{ mm} \pm 50\text{ mm}$.

6.3 Microphone

6.3.1 Microphone orientation

The microphone shall be oriented horizontally, with its reference direction — as specified by the microphone manufacturer — pointing in the direction in which a person occupying the operator's position would normally look.

6.3.2 Microphone position

The microphone shall be located $200\text{ mm} \pm 20\text{ mm}$ from the median plane of the head of the operator and in line with the eyes and to the side of the head of the operator where the time-averaged A-weighted sound pressure level is the highest.

6.3.3 Microphone mounting

The microphone can conveniently be mounted on a frame or on the helmet, or on a shoulder harness worn by the operator.

6.3.4 Microphone vibration precautions

Care shall be taken to isolate the microphone from vibrations which could affect the measurements. If the microphone is moved during the measurements, care shall be exercised to avoid introducing acoustical noise (for example, noise due to the microphone rubbing against the operator's clothing) or electrical noise (for example, due to a flexible cable) that could interfere with the measurements.

6.3.5 Precautions against microphone-reflected noise

6.3.5.1 Care shall be taken to minimize the effect of reflected noise which could affect microphone measurements. The recommendations given in 6.3.5.2 and 6.3.5.3 will minimize the effect of reflected noise.

6.3.5.2 Once the microphone location has been determined, a positional tolerance should be maintained of $\pm 50\text{ mm}$ from this location in any direction during the test.

6.3.5.3 The microphone should be placed a minimum of 100 mm from the side of the head and a minimum of 50 mm above the clothing on the shoulder during the test.

6.4 Positioning of the machine

The machine shall be positioned at the centre of the test site surface.

6.5 Measurement time

The total measurement time for each reading in a stabilized operating mode shall be in the range of 15 s to 30 s .

7 Set-up and operation of machine, and operator's position set-up

7.1 Set-up and operation of machine

The set-up and operation of the machine shall be as specified in ISO 6393:2008, Clause 7.

7.2 Setting-up operator's position for machines with cab

7.2.1 Cab with air-conditioning and/or pressurized ventilation system(s)

Measurements shall be taken with the doors and windows closed and the air-conditioning and/or ventilation system(s) in operation. If there is more than one operating speed available, the air conditioning and/or the pressurized ventilation system(s) shall be operated at the second speed for systems with up to four speeds.

For systems with more than four speeds, the third speed shall be used and, for systems with infinitely variable speeds, the mid-range speed.

If the air-conditioning and/or ventilation systems have a recirculate and outside air position control, the control shall be set for outside air.

7.2.2 Cab without air-conditioning or pressurized ventilation system(s)

Measurements shall be taken with the doors and windows closed, then repeated with the doors and windows open. The higher measurement result from the two sets of data obtained shall be used as the reported value.

8 Acoustic measurements

8.1 Measurement procedure

The time-averaged A-weighted emission sound pressure level at the operator's position shall be determined in accordance with ISO 11201.

At least three series of measurements shall be made. In order to meet the requirements laid down in 8.2, additional readings shall be taken.

8.2 Determination of measurement result

If two of the three A-weighted values so obtained do not differ by more than 1 dB, further measurements are unnecessary. If this is not the case, continue taking measurements until two values within 1 dB of one another are obtained. The time-averaged A-weighted emission sound pressure level to be reported is the arithmetic mean of the two highest values that are within 1 dB of each other.

9 Information to be recorded

The following information shall be recorded:

a) Machinery under test:

- machine manufacturer;
- machine model number;
- machine serial number;
- type of fan-drive system(s), test method(s) used, as specified in ISO 6393:2008, 7.3 a), b) or c), including corresponding system maximum fan speed and fan speed(s) used during the test for each fan;
- machine arrangement, including major equipment and attachments, and engine speed specified by the manufacturer, corresponding to the speed at which the engine develops its net power in accordance with ISO 9249;
- set-up configuration and fan speed setting used as specified in 7.2 for machines with cabs;
- engine net power, in kilowatts, at the corresponding speed, as defined in ISO 9249.

b) Acoustic environment:

- description of the test site and the type of test site measurement ground surface used, including a sketch showing the position of the machine;
- air temperature, barometric pressure, relative humidity and wind velocity at the test site.

c) Instrumentation:

- instrumentation used for the acoustical measurements, including name, type, serial number and manufacturer;
- method used to calibrate the instrumentation system;
- date and place of calibration of the acoustical calibrator.

d) Acoustical data:

- location of the microphone in relation to the operator's ear, and presence or absence of any object which could influence the operator's noise exposure (such as a protective helmet);
- time-averaged A-weighted sound pressure level at the microphone position for each measurement conducted in accordance with 8.1;
- time-averaged A-weighted sound pressure level of the background noise at the microphone position;
- final value of the time-averaged A-weighted emission sound pressure level at the operator's position, determined in accordance with 8.2.

10 Information to be reported**10.1 Information**

The following information shall be reported:

- a) machine manufacturer, model number, serial number, engine net power and corresponding speed (in kilowatts, as defined in ISO 9249), machine arrangement, including major attachments, and the type of test site measurement ground surface used;
- b) time-averaged A-weighted emission sound pressure level at the operator's position, determined in accordance with 8.2, rounded to the nearest whole number (use the lower number for values $< 0,5$; use the higher number for values $\geq 0,5$) for the selected configuration(s) of operator's position(s);
- c) manufacturer's specified engine speed, corresponding to the speed at which the engine develops its net power, in accordance with ISO 9249;
- d) type of fan-drive system(s), test method(s) used as specified in ISO 6393:2008, 7.3 a), b) or c); including the corresponding system maximum fan speed and fan speed(s) used during the test for each fan;
- e) set-up of air-conditioning and/or pressurized ventilation system.

10.2 Declaration of sound emission data and uncertainty

In some markets, the additional requirements listed in the normative Annex A apply. The declaration of sound emission data and uncertainty shall be made in accordance with Annex A, if relevant.