
**Diesel engines — Fuel injection pumps —
Tapers for shaft ends and hubs**

*Moteurs diesels — Pompes d'injection de combustible — Cônes pour
bouts d'arbre et moyeux*

STANDARDSISO.COM : Click to view the full PDF of ISO 6519:2004



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

STANDARDSISO.COM : Click to view the full PDF of ISO 6519:2004

© ISO 2004

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 6519 was prepared by Technical Committee ISO/TC 22, *Road vehicles*, Subcommittee SC 7, *Injection equipment and filters for use on road vehicles*.

This third edition cancels and replaces the second edition (ISO 6519:1993), which has been technically revised by the addition of nominal diameter 40 and dimensions for nominal diameter types 25 and 35.

[STANDARDSISO.COM](https://standardsiso.com) : Click to view the full PDF of ISO 6519:2004

Diesel engines — Fuel injection pumps — Tapers for shaft ends and hubs

1 Scope

This International Standard specifies the dimensions, necessary for interchangeability, of tapers for the shaft ends and hubs of fuel injection pumps on diesel (compression-ignition) engines. The shaft ends and hubs specified can be used either with or without woodruff keys, and for other applications for which no specific standards exist.

2 Dimensions and tolerances

2.1 General

To ensure satisfactory operation of the taper drive, it is necessary for manufacturers to provide such cone angle tolerances that the contact between the male and female cones commences at the major diameter.


2.2 Shaft ends with taper

Shaft ends shall be as shown in Figure 1 and in accordance with Table 1. The shaft ends may be made optionally according to Type 1 or 2. However, it shall be possible to screw the Go gauge for the thread up to the XX line.


2.3 Keyways of hub with taper

Hub keyways shall be as shown in Figure 2 and in accordance with Table 2. The length of the hub cone shall be such that, after assembling, the face at the smaller diameter of the hub cone lies far enough in front of the XX line (see Figures 1 and 2) that the fixing nut can be correctly screwed to this line.

Dimensions in millimetres



a) Type 1



b) Type 2

a Nominal.

Figure 1 — Shaft ends

Table 1 — Shaft ends

Dimensions in millimetres

d^a nom.	d_1	l_1 max.	l_2 $\begin{smallmatrix} 0 \\ -1 \end{smallmatrix}$	t_1 max.	b (h9)
17	M12	14,5	18	1,6	$3 \begin{smallmatrix} 0 \\ -0,025 \end{smallmatrix}$
20	M14 × 1,5	16,5	20	2	$4 \begin{smallmatrix} 0 \\ -0,03 \end{smallmatrix}$
22	M14 × 1,5	16,5			
	M16 × 1,5 ^b	18			
23	M16 × 1,5	18	23		
25	M18 × 1,5	20	25	2,6	$5 \begin{smallmatrix} 0 \\ -0,03 \end{smallmatrix}$
		14			
30	M20 × 1,5	23	30		
35	M24 × 1,5	27	35		
			27		
40	M30 × 1,5	27	40		
			27		

^a The tolerance for dimension d depends on the type of shaft bearing.

^b The thread M16 × 1,5 is preferred for shaft ends with 22 mm diameter.

Dimensions in millimetres


^a Nominal.

Figure 2 — Hub

Table 2 — Hub

Dimensions in millimetres

d^a nom.	t_2 min.	b (D10)
17	1,8	3 ^{+0,06} _{+0,02}
20	2,2	4 ^{+0,078} _{+0,030}
22		
23		
25	2,8	5 ^{+0,078} _{+0,030}
30		
35		
40		
^a d is the nominal diameter of the shaft.		