

Third edition
2019-07

AMENDMENT 5
2022-01

**Graphical symbols — Safety colours
and safety signs — Registered safety
signs**

AMENDMENT 5

*Symboles graphiques — Couleurs de sécurité et signaux de sécurité —
Signaux de sécurité enregistrés*

AMENDEMENT 5

STANDARDSISO.COM : Click to view the full PDF of ISO 7010:2019/Amd 5:2022



Reference number
ISO 7010:2019/Amd.5:2022(E)

© ISO 2022

STANDARDSISO.COM : Click to view the full PDF of ISO 7010:2019/Amd 5:2022



COPYRIGHT PROTECTED DOCUMENT

© ISO 2022

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 145, *Graphical symbols*, Subcommittee SC 2, *Safety identification, signs, shapes, symbols and colours*.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

STANDARDSISO.COM : Click to view the full PDF of ISO 7010:2019/Amd 5:2022

Graphical symbols — Safety colours and safety signs — Registered safety signs

AMENDMENT 5

IMPORTANT — The colours represented in the electronic file of this document can be neither viewed on screen nor printed as true representations. For the purposes of colour matching see ISO 3864-4, which provides colorimetric and photometric properties together with, as a guideline, references from colour order systems.

Add the following safety signs:

- M056: Ventilate before and during entering,
- M057: Ensure continuous ventilation,
- M058: Entry only with supervisor outside.

All safety signs are available on the ISO Online browsing platform at <https://www.iso.org/obp/ui>.

STANDARDSISO.COM : Click to view the full PDF of ISO 7010:2019/Amd.5:2022

Safety sign M056: Ventilate before and during entering

	Reference No. ISO 7010-M056
	Referent Ventilate before and during entering
	Function To signify that a space (e.g. room, tank, container) must be ventilated before and during entering
	Image content Upper human figure and two (air) arrows in opposite directions through an opening (open door, window or cover)
Hazard Hazardous concentrations of toxic gases or oxygen depletion.	
Human behaviour that is intended to be caused after understanding the safety sign's meaning Ensuring that the space (e.g. room, tank, container) is sufficiently ventilated before entering, for example by opening a door, window or cover for enough time before entering for there to be no hazardous concentrations of toxic gases or oxygen depletion. Also ensuring that the space continues to be sufficiently ventilated while a person is within that space.	
Additional information Test data obtained according to ISO 9186-1 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training. A supplementary sign shall be used to specify ventilation procedures (e.g. minimum opening time, if mechanical ventilation is required) except when this information is provided by manuals, instructions or training.	

Safety sign M057: Ensure continuous ventilation

	Reference No. ISO 7010-M057
	Referent Ensure continuous ventilation
	Function To signify that continuous ventilation must be ensured
	Image content Space (e.g. room, tank, container) shown as a box and two (air) arrows in opposite directions through an opening in the box
Hazard Emissions might accumulate in dangerous quantities.	
Human behaviour that is intended to be caused after understanding the safety sign's meaning Ensuring continuous ventilation to remove harmful concentrations of emissions or polluted air, for example by controlling and keeping ventilation openings continuously open and clear of obstructions.	
Additional information Test data obtained according to ISO 9186-1 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Safety sign M058: Entry only with supervisor outside

	Reference No. ISO 7010-M058
	Referent Entry only with supervisor outside
	Function To signify that a space (e.g. room, tank, container) must be entered only if a supervisor is placed outside, ready to give first aid and call for help in case of an accident
	Image content Space shown as a box with one human figure inside (right hand profile) and an upper human figure outside; telephone receiver
Hazard In case of an accident the person concerned might not be able to leave the space independently and/or call for help. Human behaviour that is intended to be caused after understanding the safety sign's meaning Ensuring that a person only enters the space (e.g. room, tank, container) when a supervisor is on the outside with a phone to be able to call emergency services, if necessary. Additional information Test data obtained according to ISO 9186-1 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	