

Second edition
2011-07-01

AMENDMENT 2
2020-06

**Implants for surgery — Components
for partial and total knee joint
prostheses —**

**Part 2:
Articulating surfaces made of metal,
ceramic and plastics materials**

AMENDMENT 2

*Implants chirurgicaux — Éléments de prothèses partielle et totale de
l'articulation du genou —*

*Partie 2: Surfaces articulaires constituées de matériaux métalliques,
céramiques et plastiques*

AMENDEMENT 2



Reference number
ISO 7207-2:2011/Amd.2:2020(E)

© ISO 2020



COPYRIGHT PROTECTED DOCUMENT

© ISO 2020

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 150, *Implants for surgery*, Subcommittee SC 4, *Bone and joint replacements*.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

STANDARDSISO.COM : Click to view the full PDF of ISO 7207-2:2011/Amd 2:2020

Implants for surgery — Components for partial and total knee joint prostheses —

Part 2:

Articulating surfaces made of metal, ceramic and plastics materials

AMENDMENT 2

3.2.1, first paragraph

Replace the paragraph with the following:

When measured in accordance with ISO 4288, all articulating surfaces of a metallic or ceramic femoral component shall be measured across the articulating surface at characteristic locations. The component shall have a $Ra_{\max}$ value of $\leq 0,1 \mu\text{m}$, using a cut-off value of 0,25 mm.

When analysing a bi- or tri- compartmental knee joint prosthesis, the roughness of the lateral and medial condyle of the femoral component each shall be measured

- a) at a location on the articulating surface in contact at 0° flexion,
- b) at a location on the articulating surface in contact at 30° flexion, and
- c) at a location on the articulating surface in contact at 60° flexion or higher angulation.

When analysing a tri-compartmental knee joint prosthesis, the patellar flange of the femoral component shall be measured at three evenly distributed locations at the articulating surface.

When analysing a uni-compartmental knee joint prosthesis, the roughness of the femoral component condyle shall be measured

- a) at a location on the articulating surface in contact at 0° flexion,
- b) at a location on the articulating surface in contact at 30° flexion, and
- c) at a location on the articulating surface in contact at 60° flexion.

When analysing a patello-femoral knee joint prosthesis, the patellar flange of the femoral component shall be measured at three evenly distributed locations at the articulating surface.

3.2.1, NOTE

Delete the NOTE.

3.2.2, first paragraph

Replace the paragraph with the following:

When measured in accordance with ISO 4288, all articulating surfaces of a metallic or ceramic tibial component shall be measured across the articulating surface at characteristic locations. The component shall have a $Ra_{\max}$ value of $\leq 0,1 \mu\text{m}$, using a cut-off value of $0,25 \text{ mm}$.

When analysing a bi- or tri compartmental knee joint prosthesis, the roughness at six evenly distributed locations at the articulating surface of the tibial component (three locations at the medial side and three locations at the lateral side) shall be measured.

When analysing a uni-compartmental knee joint prosthesis, the roughness at three evenly distributed locations at the articulating surface of the tibial component shall be measured.

3.2.3, first paragraph

Replace the paragraph with the following:

When measured in accordance with ISO 4288, all articulating surfaces of a tibial and patella component shall be measured across the articulating surface at characteristic locations. The component shall have a $Ra_{\max}$ value $\leq 2 \mu\text{m}$, using a cut-off value of $0,8 \text{ mm}$.

When analysing a bi- or tri compartmental knee joint prosthesis, the roughness at six evenly distributed locations at the articulating surface of the plastic tibial component (three locations at the medial side and three locations at the lateral side) shall be measured. The measurement direction shall be oriented approximately perpendicular to any machining marks that are present. If the tibial component allows for articulation at the tibial side (e.g. mobile bearing), measurements at the femoral side as well as at the tibial side shall be performed (six locations at the femoral side and six locations at the tibial side of the tibial component). If the tibial component provides a post, measurements at the post shall be performed as well. The measurements shall be taken at three evenly distributed locations at the intended articulating surface.

When analysing a uni-compartmental knee joint prosthesis, the roughness at three evenly distributed locations at the articulating surface of the plastic tibial component shall be measured. The measurement direction shall be oriented approximately perpendicular to any machining marks that are present. If the tibial component allows for articulation at the tibial side (e.g. mobile bearing), measurements at the femoral side as well as at the tibial side shall be performed (three locations at the femoral side and three locations at the tibial side of the tibial component).

When analysing a patello-femoral knee joint prosthesis, the roughness at three evenly distributed locations at the articulating surface of the plastic patella component shall be measured. The measurement direction shall be oriented approximately perpendicular to any machining marks that are present.

The following details should be reported along with the measured surface roughness, Ra , values: