

INTERNATIONAL STANDARD

22
**ISO
7654**

Second edition
1991-11-01

Road vehicles — Spin-on fuel filters for compression-ignition engines — Mounting and connecting dimensions

*Véhicules routiers — Filtres à combustible vissés pour moteurs à
combustion interne à allumage par compression — Dimensions de
montage et de raccordement*



Reference number
ISO 7654:1991(E)

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

International Standard ISO 7654 was prepared by Technical Committee ISO/TC 22, *Road vehicles*, Sub-Committee SC 7, *Injection equipment and filters for use on road vehicles*.

This second edition cancels and replaces the first edition (ISO 7654:1983). The filter without an inner sealing is the preferred design, but the alternative filter design in annex A may be used.

Annex A forms an integral part of this International Standard. Annex B is for information only.

© ISO 1991

All rights reserved. No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Organization for Standardization
Case Postale 56 • CH-1211 Genève 20 • Switzerland

Printed in Switzerland

Road vehicles — Spin-on fuel filters for compression-ignition engines — Mounting and connecting dimensions

1 Scope

This International Standard specifies the mounting and connecting dimensions for spin-on fuel filters, with and without an inner sealing, to be used with compression-ignition (diesel) engines.

The preferred design of spin-on fuel filters are those without an inner sealing, and they are specified in clause 2. The alternative filter design is specified in annex A and should be used if an inner sealing is required.

The corresponding filter heads are specified in ISO 7310, ISO 7311 and ISO 7577 (see annex B).

2 Dimensions and tolerances

Details not specified in this International Standard are left to the manufacturer's choice.

2.1 The dimensions and tolerances of the filter shall be in accordance with figure 1.

The shape of the sealing ring shown in X shall be

such that effective sealing is ensured. The dimensions of the compressed sealing ring shall be within the sealing surface shown in figure 2.

The dimension 0,5 min. shown in X shall be measured after tightening the filter in accordance with the filter manufacturer's recommendations. In cases where moulded sealing rings are used, this dimension may be 0; i.e., metal contact between the sealing surface to which the filter is attached and the face of the spin-on filter is allowed. This special design shall be identified on the filter with necessary fitting instructions.

2.2 The dimensions and tolerances of the sealing surface and connecting thread shall be in accordance with figure 2.

Z₁ shows the main design for the sealing surface; Z₂ shows a secondary design for the sealing surface with circular peaks, which shall be avoided for future applications.

3 Marking


Spin-on fuel filters may optionally be marked as follows:

a) designation of filter type: diesel fuel filter;

b) size of connecting thread, for example, M16 × 1,5;

c) instructions for installation.

The appearance and position of this marking on the filter body are left to the discretion of the manufacturer.



Size	D	d
1	$D \leq 80$	M16 × 1,5
2	$80 < D \leq 88$	
3	$88 < D \leq 100$	M16 × 1,5 or
4	$100 < D \leq 112$	M24 × 1,5

Figure 1 — Dimensions of filter

Technical drawing of a flange joint showing dimensions and tolerances. The drawing includes the following labels and dimensions:

- Inlet** and **Outlet** labels at the top.
- h ≥ 0** dimension on the left.
- Z₁/Z₂** label inside the flange.
- 0,3 A** tolerance zone label.
- φ d (see figure 1)** label for the central hole.
- φ 58 max.**, **φ 60 max.**, **φ 74 min.**, and **φ 76 min.** dimensions for the outer hole.
- A** tolerance zone label.
- 11 to 20°** angle dimension on the right.
- 2 min.** dimension on the right.
- Radius or chamfer optional** label on the left.
- Minimum sealing surface** label at the bottom left.
- 9 φ 1 A** label at the bottom right.

3,2/4 cut-off $r_B = 0,8$

Figure 2 — Dimensions of sealing surface and connecting thread

Annex A (normative)

Spin-on filters with inner sealing

In cases where an additional sealing ring (inner sealing) at the connecting thread is required, the alternative design shown in figures A.1 and A.2 should be used by mutual agreement between manufacturer and user.

All other dimensions and specifications not shown in figures A.1 and A.2 are in accordance with figures 1 and 2 respectively.

The free height of sealing ring shown in figure A.1 shall be at the discretion of the manufacturer, depending on material and shape.

The shape of the sealing rings shall be such that effective sealing is ensured. The dimensions of the compressed inner sealing ring shall be within the sealing surface shown in figure A.2.

Filter and sealing rings shall be so joined as to necessitate the replacement of all three parts simultaneously.




Figure A.1 — Dimensions of filter with inner sealing

STANDARDSISO.COM : Click to view the full PDF of ISO 7654:1991

Dimensions in millimetres




Figure A.2 — Dimensions of sealing surface and connecting thread with inner sealing