
International Standard



8177

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION • МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ • ORGANISATION INTERNATIONALE DE NORMALISATION

Aerospace — Omega clamps (saddle clamps) for fluid tubing installations — Dimensions

Aéronautique et espace — Colliers de fixation en oméga pour tuyauteries de fluides — Dimensions

First edition — 1985-11-15

STANDARDSISO.COM : Click to view the full PDF of ISO 8177:1985

UDC 621.881.24 : 629.7

Ref. No. ISO 8177-1985 (E)

Descriptors: aircraft, aircraft equipment, hydraulic systems, fluid pipelines, pipe clips, dimensions.

Price based on 2 pages

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work.

Draft International Standards adopted by the technical committees are circulated to the member bodies for approval before their acceptance as International Standards by the ISO Council. They are approved in accordance with ISO procedures requiring at least 75 % approval by the member bodies voting.

International Standard ISO 8177 was prepared by Technical Committee ISO/TC 20, *Aircraft and space vehicles*.

Users should note that all International Standards undergo revision from time to time and that any reference made herein to any other International Standard implies its latest edition, unless otherwise stated.

STANDARDSISO.COM : Click to view the full PDF of ISO 8177:1985

Aerospace — Omega clamps (saddle clamps) for fluid tubing installations — Dimensions

1 Scope

This International Standard specifies maximum and minimum dimensions for omega clamps (also known as "saddle clamps") installed by means of two bolts with a nominal diameter of 5 mm.

This International Standard shall not be considered as an interchangeability standard. The tolerances for each type of clamp are to be defined in the parts standards drawings.

2 Field of application

These clamps are intended for the installation, support and guiding of rigid tubing or hose assemblies used in aerospace equipment.

3 Reference

ISO 6771, *Aerospace construction — Fluid systems and components — Pressure and temperature classifications.*

4 Field of use

Omega clamps (saddle clamps) are classified into six types, according to the temperature range in which they are intended to be used (see table 1).

Table 1

Temperatures in degrees Celsius

Clamp type	Temperature range ¹⁾	
	min.	max.
1	− 55	+ 70
2	− 55	+ 135
3	− 55	+ 200
4	− 55	+ 320
5	− 55	+ 400
6	− 55	+ 650

1) See ISO 6771.

5 Description

The omega clamp (saddle clamp) is a "multi-component"-type clamp. It consists of a top band and a base contoured to the tubing. Mounting holes in the top band align with holes in the base on installation. This clamp is designed for single tubing installation, and can be provided as a metallic support only or with a plastomer or elastomer cushion or sheathing, as specified in the parts standard.

6 Dimensions

The omega clamp (saddle clamp) shall be in accordance with the figure and table 2.

The shape of clamp illustrated in the figure does not purport to be the exact shape of the manufactured clamp. Table 2 only specifies those dimensions required to define the maximum envelope and the proper location of the tube relative to the mounting plane and fastening points.