

First edition
1999-09-15

AMENDMENT 1
2012-01-15

**Fire-resistance tests — Elements of
building construction —**

**Part 1:
General requirements**

AMENDMENT 1

Essai de résistance au feu — Éléments de construction —

Partie 1: Exigences générales

AMENDEMENT 1



Reference number
ISO 834-1:1999/Amd.1:2012(E)

© ISO 2012

STANDARDSISO.COM : Click to view the full PDF of ISO 834-1:1999/Amd 1:2012



COPYRIGHT PROTECTED DOCUMENT

© ISO 2012

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

Amendment 1 to ISO 834-1:1999 was prepared by Technical Committee ISO/TC 92, *Fire safety*, Subcommittee SC 2, *Fire containment*.

STANDARDSISO.COM : Click to view the full PDF of ISO 834-1:1999/Amd.1:2012

STANDARDSISO.COM : Click to view the full PDF of ISO 834-1:1999/Amd 1:2012

Fire-resistance tests — Elements of building construction —

Part 1: General requirements

AMENDMENT 1

Page iii, Foreword

Add ISO/TR 834-2 to the list of parts:

Part 2: Guidance on measuring uniformity of furnace exposure on test samples [Technical Report]

Page 4, 5.5.1.1

Replace the subheading with the following:

5.5.1.1 Furnace temperature thermocouples

Replace the first paragraph with the following:

The furnace ~~thermocouples~~ temperature shall be measured with plate thermometers which comprise an assembly of a folded ~~steel~~ nickel alloy plate, the thermocouple fixed to it and ~~containing~~ insulation material. The measuring and recording equipment shall be capable of operating within the limits specified in 5.6.

Page 5, 5.5.1.1

Replace the second paragraph with the following:

~~The plate part shall be constructed from (150 ± 1) mm long by (100 ± 1) mm wide by (0,7 ± 0,1) mm thick nickel alloy sheet strips folded to the design as shown in figure 1. The folded metal plate shall be constructed from a strip of austenitic nickel based superalloy for high temperature oxidation resistance measuring (150 ± 1) mm long by (100 ± 1) mm wide by (0,7 ± 0,1) mm folded to the design as shown in Figure 1.~~

Replace the third paragraph with the following:

The measuring junction shall consist of nickel chromium/nickel aluminium (type K) wire as defined in IEC 60584-1, contained within mineral insulation in a heat-resisting steel alloy sheath of nominal diameter 1 mm to 3 mm, the hot junctions being electrically insulated from the sheath. The thermocouple hot junction shall be fixed to the geometric centre of the plate in the position shown in Figure 1 by a small steel strip made from the same material as the plate. The steel strip can be welded to the plate or may be screwed to it to facilitate replacement of the thermocouple. The strip shall be approximately 18 mm by 6 mm if it is spot welded to the plate, and nominally 25 mm by 6 mm if it is to be screwed to the plate. The screw shall be 2 mm in diameter.

Page 5, 5.5.1.2

Replace the subheading with the following:

Unexposed surface temperature thermocouples

Page 8, 5.5.1.4

Replace the subheading with the following:

Internal temperature thermocouples

Page 8, 5.5.1.5

Replace the subheading with the following:

Ambient-temperature thermocouples

Replace the first paragraph with the following:

A thermocouple shall be used to indicate the ambient temperature within the laboratory shall be measured with a thermocouple in the vicinity of the test specimen both prior to and during the test period. The thermocouple shall be nominally of 3 mm diameter, mineral insulated, stainless-steel sheathed type K, as defined in IEC 60584-1. The measuring junction shall be protected from radiated heat and draughts.

Page 15, 6.5

Replace the first paragraph with the following:

The furnace should be installed in a laboratory of sufficient size to prevent the ambient air temperature in the vicinity of a separating element increasing by more than 10 °C above the initial temperature whilst the test specimen is complying with the insulation criterion. The laboratory atmosphere shall be virtually draught-free. The ambient air temperature shall be 20 °C ± 150 °C at the commencement of the test and it shall be monitored at a distance of 1,0 m ± 0,5 m from the unexposed face under conditions such that the sensor is not affected by thermal radiation from the test specimen and/or furnace (particularly in the case of an element which only needs to satisfy the integrity criteria).

Page 15

Add new subclause after 6.7:

6.8 Furnace atmosphere

The fuel/air ratio to the burners and the introduction of any secondary air shall be set to give a minimum oxygen content of furnace atmosphere of 4 % when testing specimens with no combustible content such as described in ISO/TR 834-2. This fuel/air ratio setting of the burners including secondary air shall not be changed after the last verification of furnace performance.

Page 20, 9.3

Replace the second paragraph with the following:

At the time of the test, the initial average internal temperature, if used, and unexposed surface temperature of the test specimen shall be 20 °C ± 150 °C and shall be within 5 °C of the initial ambient temperature (see 6.6).