
INTERNATIONAL STANDARD



840

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION • МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ • ORGANISATION INTERNATIONALE DE NORMALISATION

Numerical control of machines — 7-bit coded character set

First edition — 1973-12-01

STANDARDSISO.COM : Click to view the full PDF of ISO 840:1973

UDC 681.3.042 : 003.62 : 62-05

Ref. No. ISO 840-1973 (E)

Descriptors : machinery, numerical control, coding.

Price based on 4 pages

FOREWORD

ISO (the International Organization for Standardization) is a worldwide federation of national standards institutes (ISO Member Bodies). The work of developing International Standards is carried out through ISO Technical Committees. Every Member Body interested in a subject for which a Technical Committee has been set up has the right to be represented on that Committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work.

Draft International Standards adopted by the Technical Committees are circulated to the Member Bodies for approval before their acceptance as International Standards by the ISO Council.

Prior to 1972, the results of the work of the Technical Committees were published as ISO Recommendations; these documents are now in the process of being transformed into International Standards. As part of this process, Technical Committee ISO/TC 97, *Computers and information processing*, has reviewed ISO Recommendation R 840-1968 and found it technically suitable for transformation. International Standard ISO 840 therefore replaces ISO Recommendation R 840-1968, which was approved by the Member Bodies of the following countries :

Belgium	Italy	Sweden
Czechoslovakia	Japan	Switzerland
Denmark	Netherlands	Turkey
Egypt, Arab Rep. of	New Zealand	United Kingdom
France	Poland	U.S.A.
Germany	Portugal	
Iran	Spain	

No Member Body expressed disapproval of the Recommendation.

Numerical control of machines – 7-bit coded character set

1 SCOPE AND FIELD OF APPLICATION

This International Standard specifies a 7-bit coded character set for the numerical control of machines and associated equipment (printers, punchers); it is to be implemented on 8-track punched tape.

The code is specified by means of a table, notes and a key. An annex gives the meanings assigned to the symbols in the International Standards on punched tape block formats.

2 REFERENCES

2.1 The recommended character set is based upon and compatible with the 7-bit coded character set, which is the

subject of ISO 646, *7-bit coded character set for information processing interchange*.

2.2 The implementation of this coded character set on punched tapes is in accordance with ISO 1113, *Information processing – Representation of 6- and 7-bit coded character sets on punched tape*; it includes a parity check (even parity); the parity bit is on track 8.

2.3 The technical terms used in this International Standard are based on the ISO data processing vocabulary¹⁾.

1) In preparation.

3 TABLE, NOTES AND KEY

3.1 Table

					b ₇				b ₆				
					0				1				
					b ₅				b ₄				
					0				1				
					column				row				
b ₃	b ₂	b ₁	b ₀	row	0	1	2	3	4	5	6	7	
0	0	0	0	0	NUL		SP	0		P			
0	0	0	1	1				1	A	Q			
0	0	1	0	2				2	B	R			
0	0	1	1	3				3	C	S			
0	1	0	0	4				4	D	T			
0	1	0	1	5			% [⊙]	5	E	U			
0	1	1	0	6				6	F	V			
0	1	1	1	7				7	G	W			
1	0	0	0	8	BS [⊙]		([⊙]	8	H	X			
1	0	0	1	9	HT		) [⊙]	9	I	Y			
1	0	1	0	10	LF [⊙]		:	10	J	Z			
1	0	1	1	11			+		K				
1	1	0	0	12					L				
1	1	0	1	13	CR [⊙]		-		M				
1	1	1	0	14					N				
1	1	1	1	15			/		O			DEL	