

INTERNATIONAL STANDARD

ISO/IEC
13719-2

First edition
1995-06-01

Information technology — Portable Common Tool Environment (PCTE) —

Part 2:

C programming language binding

*Technologies de l'information — Environnement d'outil courant portable
(PCTE) —*

Partie 2: Liant de langage de programmation C



Reference number
ISO/IEC 13719-2:1995(E)

Contents

	page
1 Scope	1
2 Conformance	1
3 Normative references	1
4 Definitions	2
5 Formal notations	2
6 Outline of the standard	2
7 Binding strategy	3
7.1 C Programming Language Standard	3
7.2 General Principles	3
7.3 Sets and Sequences	3
7.4 Character Strings	4
7.5 Memory Allocation	4
7.6 References and Names	5
7.7 Operation Return Values	5
7.8 Error Conditions	5
7.9 Identifiers	5
7.10 Implementation Limits.	6
8 Datatype mapping	6
8.1 Mapping of PCTE Datatypes to LI Datatypes	6

8.1.1	Mapping of Predefined PCTE Datatypes	6
8.1.2	Mapping of Private PCTE Datatypes	8
8.1.3	Mapping of Complex PCTE Datatypes	8
8.1.4	New LI Datatype Generators	8
8.2	Mapping of LI Datatypes to C Datatypes	10
8.2.1	LI Datatype: boolean	10
8.2.2	LI Datatype: pcte-integer	11
8.2.3	LI Datatype: pcte-natural	12
8.2.4	LI Datatype: pcte-float	13
8.2.5	LI Datatype: pcte-time	14
8.2.6	LI Datatype: pcte-text	15
8.2.7	LI Datatype: octet	16
8.2.8	LI Enumerated Datatype: pcte-xxx	16
8.2.9	LI Private Datatypes	16
8.2.10	LI Datatype Generator: pcte-sequence	17
8.2.11	LI Datatype: pcte-string	18
8.2.12	LI Datatype Generator: bounded-set	20
8.2.13	LI Datatype Generator: choice	21
8.2.14	LI Datatype: record	22
8.3	Private Datatypes	23
8.4	References and Names	23
8.5	C Private Type: Pcte_sequence	24
8.5.1	Operations on Sequences	27
8.5.2	Error Conditions for Sequence Operators	31
8.6	Deriving C Function Semantics From Abstract Specification.	32
8.7	Headers	32
8.7.1	The Global Pcte Header	33
8.7.2	The Pcte Basic Type Header	33
8.7.3	The Pcte Sequence Header	34
9	Object management	38
9.1	Object Management Datatypes	38
9.2	Link Operations	41
9.3	Object Operations	46
9.4	Version Operations	53
10	Schema management	55
10.1	Schema Management Datatypes	55
10.2	Update Operations	57
10.3	Usage Operations	65

10.4	Working Schema Operations	68
11	Volumes, devices and archives	72
11.1	Volume, Device, and Archive Datatypes	72
11.2	Volume, Device and Archive Operations	72
12	Files, pipes and devices	75
12.1	File, Pipe and Device Datatypes	75
12.2	File, Pipe and Device Operations	75
13	Process execution	78
13.1	Process Execution Datatypes	78
13.2	Process Execution Operations	79
13.3	Security Operations	83
13.4	Profiling Operations	84
13.5	Monitoring Operations	85
14	Message queues	86
14.1	Message Queue Datatypes	86
14.2	Message Queue Operations	87
15	Notification	89
15.1	Notification Datatypes	90
15.2	Notification Operations	90
16	Concurrency and integrity control	90
16.1	Concurrency and Integrity Control Datatypes	91
16.2	Concurrency and Integrity Control Operations	91
17	Replication	92
17.1	Replication Datatypes	92
17.2	Replication Operations	92
18	Network connection	94
18.1	Network Connection Datatypes	94
18.2	Network Connection Operations	95
18.3	Foreign System Operations	97
18.4	Time Operations	97

19	Discretionary security	97
19.1	Discretionary Security Datatypes	98
19.2	Discretionary Access Control Operations	100
19.3	Discretionary Security Administration Operations	100
20	Mandatory security	102
20.1	Mandatory Security Datatypes	102
20.2	Mandatory Security Operations	102
20.3	Mandatory Security Administration Operations	104
20.4	Mandatory Security Operations for Processes	105
21	Auditing	106
21.1	Auditing Datatypes	106
21.2	Auditing Operations	110
22	Accounting	112
22.1	Accounting Datatypes	112
22.2	Accounting Administration Operations	114
22.3	Consumer Identity Operations	116
23	References	116
23.1	Reference Datatypes	116
23.2	Object Reference Operations	117
23.3	Link Reference Operations	119
23.4	Type Reference Operations	121
24	Implementation limits	122
24.1	Implementation Limit Datatypes	122
24.2	Implementation Limit Operations	124
25	Error conditions	124
25.1	Error Condition Datatypes	124
25.2	Error Condition Operations	132
	Index of abstract operations	133
	Index of c subprograms	141
	Index of c datatypes	149

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

International Standard ISO/IEC 13719-2 was prepared by the European Computer Manufacturers Association (ECMA) (as Standard ECMA-158) and was adopted, under a special "fast-track procedure", by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, in parallel with its approval by national bodies of ISO and IEC.

ISO/IEC 13719 consists of the following parts, under the general title *Information technology — Portable Common Tool Environment (PCTE)*:

- Part 1: Abstract specification
- Part 2: C programming language binding
- Part 3: Ada programming language binding

Information technology — Portable Common Tool Environment (PCTE) —

Part 2: C programming language binding

1 Scope

This part of ISO/IEC 13719 defines the standard binding of the Portable Common Tool Environment (PCTE), as specified in ISO/IEC 13719-1, to the C Programming Language.

A number of features are not completely defined in ISO/IEC 13719-1, some freedom being allowed to the implementor. Some of these features are specified as implementation limits. Some constraints are placed on these implementation limits by this C Language Binding Standard. These constraints are specified in clause 24, Implementation Limits.

PCTE is an interface to a set of facilities that forms the basis for constructing environments supporting systems engineering projects. These facilities are designed particularly to provide an infrastructure for programs which may be part of such environments. Such programs, which are used as aids to system development, are often referred to as tools.

2 Conformance

An implementation of PCTE conforms to this part of ISO/IEC 13719 if it conforms to 2.2 of ISO/IEC 13719-1, where the binding referred to there is taken to be the C Language Binding defined in clauses 1 to 5 and 8 to 25 of this part of ISO/IEC 13719. All other clauses in this part of ISO/IEC 13719 are provided as assistance to the reader and are not normative.

The C Language Binding defined in this part of ISO/IEC 13719 conforms to 2.1 of ISO/IEC 13719-1.

3 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this part of ISO/IEC 13719. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this part of ISO/IEC 13719 are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO 8601:1988,	<i>Data elements and interchange formats — Information interchange — Representation of dates and times.</i>
ISO 8859-1:1987,	<i>Information processing — 8-bit single-byte coded graphic character sets — Part 1: Latin alphabet No. 1.</i>
ISO 9899:1990,	<i>Programming languages — C.</i>
ISO/IEC TR 10182:1993,	<i>Information technology — Programming languages, their environments and system software interfaces — Guidelines for language bindings.</i>
ISO/IEC 11404:— ¹⁾ ,	<i>Information technology — Programming languages their environments and system software interfaces — Language-independent datatypes.</i>
ISO/IEC 13719-1:1995,	<i>Information technology — Portable Common Tool Environment (PCTE) — Part 1: Abstract specification.</i>

4 Definitions

Definitions used in this part of ISO/IEC 13719 are those defined in ISO/IEC 13719-1.

5 Formal notations

Two formal notations are used in this part of ISO/IEC 13719. For each bound operation, the abstract specification is given using a subset of the Vienna Development Method Specification Language (or VDM-SL), exactly as it is specified in ISO/IEC 13719-1. For the C Language binding for each operation, the function prototype syntax is used as defined in ISO 9899.

6 Outline of the standard

Clause 7 describes the strategy used to develop this binding specification.

Clause 8 contains the mapping from the datatypes that are used in the Abstract Specification to C Language datatypes.

Clauses 9 to 22 define the binding of datatypes and operations in the corresponding clauses of ISO/IEC 13719-1.

Clause 23 defines the binding of object, attribute, link, and type references, as specified in 23.1.2 and 23.2 of ISO/IEC 13719-1.

Clause 24 defines the binding of the implementation limit functions described in ISO/IEC 13719-1, clause 24.

Clause 25 defines the binding of the error conditions specified in ISO/IEC 13719-1, appendix C, and defines binding-defined error conditions for the C Binding.

1) To be published

7 Binding strategy

7.1 C Programming Language Standard

This part of ISO/IEC 13719 is a conforming program according to ISO 9899.

7.2 General Principles

The following general principles were applied when generating the binding in this part of ISO/IEC 13719.

ISO/IEC TR 10182 should be followed as far as possible for binding method 1: provide a completely defined procedural interface.

Each operation in ISO/IEC 13719-1 should be represented by exactly one operation in this part of ISO/IEC 13719 except possibly when the abstract operation has distinct functionality depending on the values of one or more parameters.

Each operation in this part of ISO/IEC 13719 should have the same number of parameters as does the corresponding operation in ISO/IEC 13719-1.

All operations in this part of ISO/IEC 13719 should return an integer status value. All other values returned by the operation should be passed back to the caller via an output parameter. The return value of the operation should indicate success or failure only.

Operation and parameter names should be the same in this part of ISO/IEC 13719 as they are in ISO/IEC 13719-1, with the exception that identifiers with file scope should begin 'Pcte_' and otherwise consist of lowercase letters and underscores. The PCTE standard guarantees that there are no ambiguities in names prefixed by 'Pcte_'.

All additional names introduced in this part of ISO/IEC 13719 which are visible across the interface (except header names, see 8.5) should begin 'Pcte_' and otherwise consist of lowercase letters, underscores and digits, or begin 'PCTE_' and otherwise consist of uppercase letters, underscores and digits. The PCTE standard guarantees that there are no ambiguities in names prefixed by 'PCTE_' or 'Pcte_'.

Wherever practical, types introduced for passing complex data entities between caller and operation (and vice versa) should be private types defined by this part of ISO/IEC 13719. The principle should only be ignored for reasons of ease of use and efficiency of implementation.

Each simple datatype in ISO/IEC 13719-1 should be mapped to a corresponding type defined in this part of ISO/IEC 13719. Each implementation of the binding should then be free to map the binding-defined type to an efficient C Language basic type appropriate for the platform of the implementation, within the constraints specified in this part of ISO/IEC 13719.

A general policy of memory allocation should be adopted; see 7.5

7.3 Sets and Sequences

Some Complex data entities to be passed into or retrieved from an operation are defined as sets or sequences of a base type in ISO/IEC 13719-1. Bounded set types are mapped individually to bit-significant natural numbers; unbounded set and sequence types are

mapped to a private type, **Pcte_sequence** with operations for creation, population, retrieval and deletion. These operations allow multiple elements of sets and sequences to be set and read in a single operation, from or to an array object of an appropriate base type. Thus, the data for sets and sequences can be easily manipulated using standard C Language paradigms, while allowing the implementation to choose the best implementation for such sets and sequences.

7.4 Character Strings

In ISO/IEC 13719-1, two different types are used to represent sequences of characters. String is a sequence of Octets allowing all 8-bit values and Text is a sequence of latin 1 graphic characters. Contents, string attributes etc., are of type String; keys, type names etc., are of type Text.

In the C Bindings, String is mapped to **Pcte_string** (see 8.2.11). Text is mapped to the native C language string with a possibly fixed length, i.e. `char *` with operations depending on NUL ('\0') character termination (see 8.2.6).

7.5 Memory Allocation

Communication between caller and operation is effected by the transfer of data into an operation via an input parameter or back from an operation via an output parameter. There are two types of such parameters: public and private.

All instances of a public type are allocated and managed by the caller of the operation. All instances of a private type are allocated and managed by the implementation. However, the extraction of data from a private type is again by data transfer in instances of a public type via an operation on the private type. In these cases also, the caller of the operation is required to allocate and manage the instances of the public type. The caller is further required to allocate sufficient space to contain a handle to the private type, the type of which is always a pointer to an internal data structure of undefined form. Operations on the private type are provided to create and discard these internal data structures.

Data stored in an instance of a private type is owned by the implementation. The implementation is responsible for allocating, managing and deallocating the memory used to store this data. Furthermore, after a handle to an instance of a private type has been returned to the caller of an operation, via an output parameter, the implementation is responsible for maintaining the data stored therein, until the caller explicitly indicates that the data is no longer needed, by invoking the discard operation on that instance.

Data stored in an instance of a public type and passed into an operation via an input parameter, is owned by the caller of the operation. The caller is responsible for allocating, managing and deallocating the memory used to store this data. The caller is further responsible for maintaining the data stored therein for the duration of the operation. If the implementation needs to access the data after the operation has completed, the implementation is responsible for allocating additional memory and storing therein a copy of the data.

All the operations that have sequences as "out" parameters will allocate the sequence and return it as result of operation. The user does not need to allocate the sequence in

advance: the user only needs to declare a `Pcte_sequence` variable and pass the address of that variable.

7.6 References and Names

Objects, attributes, links, and types are referred to in this part of ISO/IEC 13719 using object references, attribute references, link references and type references, respectively. References are mapped to private datatypes encapsulating two ways of designating an object, attribute, link, or type: by an external and by an internal reference (see ISO/IEC 13719-1, clause 23).

Beside these references, in this part of ISO/IEC 13719 also attribute names, link names and type names are used to refer to attributes, links, or types. These names represent external references and they are mapped to the native C language string type.

Therefore two different interfaces are provided in this Binding for clauses 9 to 22:

- one interface using names for attributes, links, and types.
- one interface using references for attributes, links, and types. All operations of this interface begin '`Pcte_h_`'. These operations are defined if an operation of the previous interface uses attributes, links, or types. Whenever new datatypes are necessary, they also begin '`Pcte_h_`' (see 8.7).

7.7 Operation Return Values

All the operations are mapped to functions which return a `Pcte_error_type` value, which indicates success (`PCTE_NO_ERROR` equivalent to `PCTE_OK`) or failure (one of the other enumeration values of `Pcte_error_type`) of the operation. All other information that is passed between the caller and the operation is passed via "out" or "in-out" parameters.

The error code `PCTE_NO_ERROR` is equivalent to `PCTE_OK` (as both have the value zero).

Additionally the global variable `Pcte_error_number` is set to the same return value of the function after each `PCTE` call, but it should be noted that in case of multi-threading or queue handlers this global variable cannot be relied upon.

7.8 Error Conditions

Error conditions which are defined in ISO/IEC 13719-1 and which can be established and returned by the operations defined in this part of ISO/IEC 13719 are described in clause 25.

All binding defined errors are defined in 25.1(2).

7.9 Identifiers

Many of the identifiers in ISO/IEC 13719-1 are longer than 31 characters, but no two identifiers are exactly the same within the first 31 characters. The C Programming Language Standard requires that an internal name (i.e., a macro name or an identifier that does not have external linkage) be unique within the first 31 characters. Thus there is no need for any identifiers to be abbreviated in this Binding.

ISO 9899 requires all identifiers of enumeration values to be distinct. Where ISO/IEC 13719-1 uses the same identifier for values of enumeration types bound to different C Language enumeration types, new names have been invented.

In a few cases an abstract operation has been bound to more than one C Language function, to cater for optional parameters; in these cases also, new names have been invented.

7.10 Implementation Limits.

ISO/IEC 13719-1 defines a set of limits that must be honored by all implementations of the Language Bindings. Clause 24 describes the binding-defined identifiers for these limit values and the way in which these limits can be retrieved.

8 Datatype mapping

This clause defines the mapping of the parameter and result datatypes of the operations of ISO/IEC 13719-1 (*PCTE datatypes*) to the parameter and result datatypes of the operations of this part of ISO/IEC 13719 (*C datatypes*).

PCTE datatype names are printed in normal characters.

LI Datatypes names are printed in italics.

C datatype names are printed in bold except in displayed fragments of C.

The mapping from PCTE datatypes to C datatypes is done in two stages via LI datatypes defined in CD11404.2.

8.1 Mapping of PCTE Datatypes to LI Datatypes

As far as possible the names of PCTE datatypes are retained for the corresponding LI datatypes, but some new names are introduced.

The general strategy of this mapping is as follows.

- To select for each PCTE datatype a LI datatype definition which matches the requirements of the PCTE datatype defined in ISO/IEC 13719-1. The LI datatype definition is, where possible, a primitive LI datatype or otherwise a generated LI datatype.
- To define new datatype generators where needed.
- To map PCTE datatypes with the same properties to the same LI datatype.

8.1.1 Mapping of Predefined PCTE Datatypes

The mapping of these PCTE datatypes is as defined in ISO/IEC 13719-1, clause 23 and is summarized in table 1.

Table 1 - Mapping of predefined PCTE datatypes

PCTE datatype	LI datatype
Boolean	<i>boolean</i>
Integer	<i>pcte-integer = integer</i> range (<i>MIN_INTEGER_ATTRIBUTE..MAX_INTEGER_ATTRIBUTE</i>)
Natural	<i>pcte-natural = integer</i> range (<i>0..MAX_NATURAL_ATTRIBUTE</i>)
Float	<i>pcte-float =</i> <i>real</i> (<i>10, MAX_DIGITS_FLOAT_ATTRIBUTE</i>) range (<i>MIN_FLOAT_ATTRIBUTE..MAX_FLOAT_ATTRIBUTE</i>)
Time	<i>pcte-time =</i> <i>time</i> (<i>second, 10, Pcte_accuracy_factor</i>) range (<i>MIN_TIME_ATTRIBUTE..MAX_TIME_ATTRIBUTE</i>)
Octet	<i>octet</i>
Text	<i>pcte-text = character string</i> (<i>repertoire</i>)
Enumerated type xxx = VALUE1 VALUE2 ...	<i>pcte-xxx = enumerated</i> (<i>value1, value2, ...</i>)

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 13719-2:1995

8.1.2 Mapping of Private PCTE Datatypes

Table 2 - Mapping of private PCTE datatypes

PCTE datatype	LI datatype
Address	<i>address</i>
Attribute_reference	<i>attribute_reference</i>
Contents_handle	<i>contents_handle</i>
Handler	<i>handler</i>
Object_reference	<i>object_reference</i>
Link_reference	<i>link_reference</i>
Position_handle	<i>position_handle</i>
Profile_handle	<i>profile_handle</i>
Type_reference	<i>type_reference</i>

8.1.3 Mapping of Complex PCTE Datatypes

PCTE sequence datatypes are mapped to the new datatype generator *pcte-sequence* (see 8.1.4).

PCTE set datatypes are divided into bounded set types and unbounded set types. Bounded set types have values which are sets of enumeration values with at most 32 possible elements; all others are unbounded set types. Bounded set types are mapped via the new LI datatype generator *Bounded-set*. Unbounded set types are mapped via the new LI datatype generator *Sequence*, the order of elements being irrelevant.

When used as input parameter of an operation in clauses 9 to 22, a sequence which represents a PCTE unbounded set may contain repeated elements. The effect for the operation is as though each element occurred only once.

When returned as the result of an operation in clauses 9 to 22, an unbounded set has no repeated elements.

PCTE map are notionally mapped via a new LI datatype generator *Map*; their mappings to C datatypes are defined directly. The mapping of *Attribute_assignments* is defined in 9.1. The mapping of *Access_rights*, *Acl*, and *Atomic_access_rights* is defined in 19.1.

PCTE union datatypes other than enumerations are mapped via the datatype generator *Choice*.

PCTE composite and bracketed datatypes (except private PCTE datatypes, for which see 8.1.2) are mapped to the datatype generator *Record*.

8.1.4 New LI Datatype Generators

Pcte-Sequence

Description: *Pcte-sequence* is a datatype generator derived from *Sequence* by adding further characterizing operations. In some operations, an index of LI datatype *pcte-*

natural is used to identify elements in the sequence. The first element is always indexed from 0.

The characterizing operations are IsEmpty, Head, Tail, Equal, Empty, and Append from *Sequence* plus Get, Put, Copy, LengthOf, and IndexOf.

Get(s: sequence of *base*, index: Natural): *base* is undefined if InOrder(LengthOf(s), index) is true or is Head(s) if Equal(index, 0) is true; otherwise Get(Tail(s), Add(index, negate(1))).

Put(s: sequence of *base*, e: *base*, index: Natural): sequence of *base* is undefined if InOrder(Add(LengthOf(s), 1), index) is true or is Append(Create(e), s) if Equal(index, 0) is true; otherwise Append(Head(s), Put(Tail(s), e, Add(index, Negate(1)))).

Copy (s: sequence of *base*): sequence of *base* is Create() if IsEmpty(s) is true; otherwise Append(Head(s), Copy(Tail(s))).

LengthOf(s: sequence of *base*): Natural is 0 if IsEmpty(s); otherwise Add(LengthOf(Tail(s)), 1).

IndexOf(s: sequence of *base*, e: *base*): Natural is undefined if IsEmpty(s) is true or is 1 if Equal(Head(s), e) is true; otherwise Add(IndexOf(Tail(s), e), 1).

Bounded-set

Description: Bounded-set is a datatype generator derived from *Set* by restricting the cardinality of the values to 32 or less.

bounded-set of (*base*) = new set of (*base*) : size (0..32);

The characterizing operations are IsIn, Subset, Equal, Difference, Union, Intersection, Empty, SetOf, Select from *Set*.

8.2 Mapping of LI Datatypes to C Datatypes

8.2.1 LI Datatype: boolean

The LI datatype *boolean* is mapped to the C datatype **Pcte_boolean**.

typedef <boolean-type> Pcte_boolean;

where <boolean-type> is a C integer type.

TRUE is represented by PCTE_TRUE, FALSE is represented by PCTE_FALSE:

```
#define PCTE_TRUE (Pcte_boolean) 1
#define PCTE_FALSE (Pcte_boolean) 0
```

In addition, if a value of type **Pcte_boolean** is supplied as or as part of an input parameter, it is taken as TRUE if it is not 0.

Characterizing Operations

Operation	C Operation
Equal(b1,b2):b	if (b1 == b2) b = PCTE_TRUE; else b = PCTE_FALSE;
Not(b1):b	if (b1 == PCTE_FALSE) b = PCTE_TRUE; else b = PCTE_FALSE;
And(b1,b2):b	b = b1 && b2;
Or(b1,b2):b	b = b1 b2;

8.2.2 LI Datatype: *pcte-integer*

The LI datatype *pcte-integer* is mapped to the C datatype **Pcte_integer**.

typedef <integer-type> Pcte_integer;

where <integer-type> is a C integer type including the range MIN_INTEGER_ATTRIBUTE to MAX_INTEGER_ATTRIBUTE inclusive.

Characterizing Operations

Operation	C Operation
Equal(i1,i2):b	if (i1 == i2) b = PCTE_TRUE; else b = PCTE_FALSE;
InOrder(i1,i2):b	if (i1 <= i2) b = PCTE_TRUE; else b = PCTE_FALSE;
NonNegative(i):b	if (i >= 0) b = PCTE_TRUE; else b = PCTE_FALSE;
Negate(i1):i	i = -i1
Add(i1,i2):i	i = i1 + i2
Multiply(i1,i2):i	i = i1 * i2

8.2.3 LI Datatype: pcte-natural

The LI datatype *pcte-natural* is mapped to the C datatype **Pcte_natural**.

typedef <natural-type> Pcte_natural;

where <natural-type> is a C unsigned integer type including the range 0 to MAX_NATURAL_ATTRIBUTE inclusive.

Furthermore, the unsigned integral datatype in C Language operates under modular arithmetic rules; i.e. the result of any arithmetic operation is always reduced modulo the largest representable value. Therefore, $ULONG_MAX + 1 = 0$, where $ULONG_MAX$ is the largest value of the chosen base unsigned integer value.

Characterizing Operations

Operation	C Operation
Equal(n1,n2):b	if (n1 == n2) b = PCTE_TRUE; else b = PCTE_FALSE;
InOrder(n1,n2):b	if (n1 <= n2) b = PCTE_TRUE; else b = PCTE_FALSE;
Add(n1,n2):n	n = n1 + n2
Multiply(n1,n2):n	n = n1 * n2

8.2.4 LI Datatype: *pcte-float*

The LI datatype *pcte-float* is mapped to the C datatype **Pcte_float**.

typedef <float-type> Pcte_float;

where <float-type> is a C floating type including the range MIN_FLOAT_ATTRIBUTE to MAX_FLOAT_ATTRIBUTE inclusive, with an accuracy of at least MAX_DIGITS_FLOAT_ATTRIBUTE decimal digits, and able to represent SMALLEST_FLOAT_ATTRIBUTE.

Characterizing Operations

Operation	C Operation
Equal(f1,f2):b	if (f1 == f2) b = PCTE_TRUE; else b = PCTE_FALSE;
InOrder(f1,f2):b	if (f1 <= f2) b = PCTE_TRUE; else b = PCTE_FALSE;
NonNegative(i):b	if (f >= 0.0) b = PCTE_TRUE; else b = PCTE_FALSE;
Negate(f1):f	f = -f1
Add(f1,f2):f	f = f1 + f2
Multiply(f1,f2):f	f = f1 * f2
Reciprocal(f1):f	f = 1.0 / f1;

8.2.5 LI Datatype: *pcte-time*

The LI datatype *pcte-time* is mapped to the C datatype **Pcte_time**, where *Pcte_time_accuracy_factor* is an implementation-defined constant for the resolution of for time attributes.

```
typedef time_t Pcte_time;

#define Pcte_time_accuracy_factor (Pcte_natural) <implementation-defined>

#define Pcte_reference_time (Pcte_time) <implementation defined>
```

The datatype **time_t** is an arithmetic datatype that holds values representing time. The encoding of the calendar time within a value of type **time_t** is undefined. Functions on values of type **time_t** are provided to convert such a value into a meaningful and usable representation of calendar time.

The implementation shall provide a constant defining an optional time parameter in the operation *Pcte_object_set_time_attributes*.

```
#define Pcte_null_time (Pcte_time) <implementation defined>
```

Characterizing Operations

Operation	C Operation
Equal(t1,t2):b	if (difftime(t1,t2) < radix_factor) b = PCTE_TRUE; else b = PCTE_FALSE;
InOrder(t1,t2):b	if (difftime(t1,t2) >= 0) b = PCTE_TRUE; else b = PCTE_FALSE;
Difference(t1,t2):i	i = (Pcte_integer) difftime(t1,t2);
Extend.res1tores2(t1):t2	t2 = t1 * radix_factor;
Round.res1tores2(t1):t2	t2 = floor (t1 + radix_factor);

In this table radix_factor is 10^{-Pcte_time_accuracy_factor}

8.2.6 LI Datatype: pcte-text

The LI datatype *pcte-text* is mapped to the native C language null terminated string type with a fixed length. The character repertoire of the characters of such a sequence are the graphic characters of ISO 8859-1. **Pcte_octet** is used to represent this character repertoire. Attribute names, enumerals type images, exact identifier, keys, machine names, node names, link names, names, type names, and type names in SDSs are of type Text.

```
#define PCTE_MAX_XXX_SIZE <implementation-defined>
typedef Pcte_octet Pcte_XXX[PCTE_MAX_XXX_SIZE + 1];
```

XXX is one of the following PCTE datatypes: Attribute_name, Enumeral_type_image, Exact_identifier, Key, Link_name, Machine_name, Name, Node_name, and Type_name, or Type_name_in_sds. All values of PCTE XXX_SIZE defined in this Binding are minimum values, which have to be respected by an implementation.

Characterizing Operations

Operation	C Operation
Equal(s1,s2):b	if (strcmp(s1,s2) == 0) b = PCTE_TRUE; else b = PCTE_FALSE;
Empty():s	s[0] = '\0';
Head(s):c	c = s[0];
Tail(s1):s2	if (s1[0] != '\0') { s2 = malloc(strlen(s1)); (void) strncpy(s2,s1+1,strlen(s1)); }
Append(s1,e):s2	s2 = malloc(strlen(s1)+2); (void) strcpy(s2,s1); (void) strcat(s2,"e");
IsEmpty(s):b	if (s[0] == '\0') b = PCTE_TRUE; else b = PCTE_FALSE;

Note, that in this table memory errors like access at invalid addresses are not recognized.

8.2.7 LI Datatype: *octet*

The LI datatype *octet* is mapped to the C datatype **char**.

typedef char Pcte_octet;

Characterizing Operations

Operation	C Operation
Equal(o1,o2):b	if (o1 == o2) b = PCTE_TRUE; else b = PCTE_FALSE;

8.2.8 LI Enumerated Datatype: *pcte-xxx*

The LI datatype *pcte-xxx*, defined as *enumerated* (value1, value2, ...), corresponds to the PCTE enumeration datatype xxx (where the values of xxx are VALUE1, VALUE2, ...). It is mapped to the C datatype **Pcte_xxx**, defined as follows.

Case (1): if a bounded set of the enumeration type is not required the mapping is:

typedef enum {PCTE_VAL1, PCTE_VAL2, ...} Pcte_xxx;

Case (2): if a bounded set of the enumeration type is required the mapping is as defined in 8.2.12

Characterizing Operations

Operation	C Operation
Equal(e1,e2):b	if (e1 == e2) b = PCTE_TRUE; else b = PCTE_FALSE;
InOrder(e1,e2):b	if (e1 <= e2) b = PCTE_TRUE; else b = PCTE_FALSE;
Successor(e1):e2	e2 = e1+1;

8.2.9 LI Private Datatypes

Each LI private datatype xxx is mapped to an opaque C datatype *Pcte_xxx*.

typedef void *Pcte_xxx;

8.2.10 LI Datatype Generator: pcte-sequence

The LI datatypes of the family *pcte-sequence* are mapped to the C datatype **Pcte_sequence** (except for *pcte-sequence* of *octet*, see 8.2.7).

Since **Pcte_sequence** is an opaque type in the C Language, objects of this type may be manipulated only via the binding defined operations (see 8.5.1).

Characterizing Operations

Operation	C Operation
Equal(s1,s2):b	Pcte_sequences_are_equal (s1,s2,&b);
Empty():s	Pcte_sequence_create(-,NULL,0,&s);
Head(s):e	Pcte_sequence_get(s,0,&e);
Tail(s1):s2	Pcte_sequence_delete(s,0,1);
Append(s1,e):s2	Pcte_natural n; Pcte_sequence_get_length(s1,&n); Pcte_sequence_copy(s1,&s2,0,0,n); Pcte_sequence_put(s2,n+1,&e);
IsEmpty(s):b	Pcte_natural n; Pcte_sequence_get_length(s,&n); if (n == 0) b = PCTE_TRUE; else b = PCTE_FALSE;
Copy(s1):s2	Pcte_natural n; Pcte_sequence_get_length(s1,&n); Pcte_sequence_copy(s1,&s2,0,0,n);
Get(s,n):e	Pcte_sequence_get(s,n,&e);
Put(s1,e,n):s2	Pcte_natural n; Pcte_sequence_get_length(s1,&n); Pcte_sequence_copy(s1,&s2,0,0,n); Pcte_sequence_put(s2,n,&e);
LengthOf(s):n	Pcte_sequence_get_length(s,&n);
IndexOf(s,e):n	Pcte_sequence_get_index(s,&e,&n);

If a sequence is to be created using `Pcte_sequence_create`, a type of **Pcte_sequence_type** has to be supplied. In the table given above, this is indicated using '-'.
STANDARD ISO 13719-2:1995

The sequence operations, `Pcte_sequence_XXX`, which are used above are defined in 8.5.1.

8.2.11 LI Datatype: *pcte-string*

The LI datatype *pcte-string*, which is a *pcte-sequence* of *octets*, is mapped to the C datatype **Pcte_string**. Attribute values, contents, control data device characteristics, foreign devices, foreign names, foreign parameters, messages, pathnames, process data, relative pathnames, security labels, and volume characteristics are Strings.

```
typedef struct {
    Pcte_natural    size;
    Pcte_octet      *array;
} Pcte_string;
```

If a value of type **Pcte_string** is passed as or as part of an input parameter, **size** defines the valid number of octets given by **array**. If **size** is bigger than the number of octets allocated in **array**, the error PCTE_ACCESS_AT_INVALID_ADDRESS is raised.

If a value of type **Pcte_string** is passed as or as part of an output parameter, the space for the string can be either allocated by the caller or by the implementation:

- if the supplied **size** is set to 0, the space is allocated by the implementation; in this case it is in the responsibility of the caller to discard the space when the string is no longer needed, by using the operation **Pcte_string_discard**.
- if the supplied **size** is non-zero, it indicates the number of octets allocated by the user in **array**.

The implementation sets **size** to the number of returned octets, provided by the implementation in **array**. If there is not enough space in **array**, the implementation raises the error PCTE_STRING_TOO_SHORT or in case of a wrong set **size** PCTE_ACCESS_AT_INVALID_ADDRESS.

In order to improve usability, there are four exceptions to this rule: CONTENTS_READ, CONTENTS_WRITE, PROCESS_PEEK, and PROCESS_POKE. In all cases an array of **Pcte_octet** and an additional size parameter has to be supplied. For these two parameters the same rules apply for incoming and outgoing parameters as for *pcte-string*. In addition, pathname and relative pathname are mapped to the native C language string type (see 23.1). For these exceptions no characterizing operations are defined.

The following operations is provided.

Pcte_string_discard

```
Pcte_error_type Pcte_string_discard (
    Pcte_string    string
);
```

Pcte_string_discard discards the space allocated by the implementation for **string.array**

Characterizing Operations

Operation	C Operation
Equal(s1,s2):b	if ((s1.size == s2.size) && (memcmp(s1.array, s2.array, s1.size) == 0)) b = PCTE_TRUE; else b = PCTE_FALSE;
Empty():s	s.size == 0;
Head(s):c	c = s.array[0];
Tail(s1):s2	s2.size = s1.size - 1; s2.array = malloc(s2.size); memcpy(s2.array, s1.array, s2.size);
Append(s1,e):s2	s2.size = s1.size + 1; s2.array = malloc(s2.size); memcpy(s2.array, s1.array, s2.size); s2.array[s2.size] = e;
IsEmpty(s):b	if (s.size == 0) b = PCTE_TRUE; else b = PCTE_FALSE;
Copy(s1):s2	s2.size = s1.size; s2.array = malloc(s2.size); memcpy(s2.array, s1.array, s2.size);
Get(s,n):e	e = s.array[n];
Put(s1,e,n):s2	s2.size = s1.size; s2.array = malloc(s2.size); memcpy(s2.array, s1.array, s2.size); s2.array[n] = e;
LengthOf(s):n	n = s.size;
IndexOf(s,e):n	n = 0; while (s.array[n] != e) n++;

Note, that in this table memory errors like access at invalid addresses are not recognized.

8.2.12 LI Datatype Generator: bounded-set

Each LI datatype *bounded-set of (base)* is mapped to a different C datatype, defined as **Pcte_natural** (see 8.2.3), with an enumeration definition mapping the names of element values to bit positions. A natural value represents a set including an element value if the corresponding bit is 1. Thus a bounded set <bounded-set>, where <bounded-set> is either **Pcte_access_events**, **Pcte_categories**, **Pcte_definition_mode_values**, **Pcte_discretionary_access_modes**, or **Pcte_work_status**, with possible element values VALUE1, VALUE2, etc. is mapped as follows, making use of the corresponding enumerated types <enumerated-type>, where <enumerated-type> is either **Pcte_access_event**, **Pcte_category**, **Pcte_definition_mode_value**, **Pcte_discretionary_access_mode**, or **Pcte_work_status_item**, respectively:

```
enum {
    PCTE_VALUE1    =    1<<0,
    PCTE_VALUE2    =    1<<1,
    PCTE_VALUE3    =    1<<2,
    ...
} <enumerated-type>;

typedef Pcte_natural <bounded-set>;
```

Characterizing Operations

Operation	C Operation
Equal(s1,s2):b	if (s1 == s2) b = PCTE_TRUE; else b = PCTE_FALSE;
Empty ():s	s = 0;
IsIn (s,e):b	if (s & e) b = PCTE_TRUE; else b = PCTE_FALSE;
Subset(s1,s2):b	if (s2 == (s2 & s1)) b = PCTE_TRUE; else b = PCTE_FALSE;
Complement (s1):s2	s2 = ~s1;
Union (s1,s2):s3	s3 = s1 s2;
Intersection (s1,s2):s3	s3 = s1 & s2;
SetOf(e):s	s = e;
Select(s):e	for (e=1;;e<<1) if (s & e) break;

8.2.13 LI Datatype Generator: choice

The LI datatype *pcte-xxx = choice (alt-1, alt-2, ...)* is mapped to a C union datatype as follows:

Each value is discriminated by an enumeration, the discriminator, with its origin type. The position of the enumeration value of the discriminator corresponds to the position of the type of the choice, i.e. if the discriminator has the value PCTE_TYPE_1, the value of the choice is of type Pcte_type_1, etc.

```
typedef struct {
    enum {
        PCTE_TYPE_1,
        PCTE_TYPE_2,
        ...
    } union_type;
    union {
        Pcte_type_1 alt-1;
        Pcte_type_2 alt-2;
        ....;
    } choice;
} Pcte_xxx ;
```

Characterizing Operations

Operation	C Operation
Equal(c1,c2):b	if (c1 == c2) b = PCTE_TRUE; else b = PCTE_FALSE;
Tag.type-n(x,type-n):c	c.union_type = PCTE_TYPE_N; c.choice = x;
IsType.type-n(c):b	if (c.union_type == PCTE_TYPE_N) b = PCTE_TRUE; else b = PCTE_FALSE;
Case.type-n(c):x	x = c.choice;

8.2.14 LI Datatype: record

The LI datatype generator *Record* is mapped to the C language struct type as follows:

```
typedef struct {
    Pcte_type_1    component_1;
    Pcte_type_2    component_2;
    Pcte_type_3    component_3;
    ...;
} Pcte_xxx ;
```

Characterizing Operations

Operation	C Operation
Equal(r1,r2):b	if (r1 == r2) b = PCTE_TRUE; else b = PCTE_FALSE;
FieldSelect.c(r):c	c = r.c;
FieldReplace(r1,c):r2	r2 = r1; r2.c = c;

8.3 Private Datatypes

Private Datatypes are datatypes with a hidden representation, i.e. the implementation-defined representation of such a datatype is not defined in any header. These datatypes are denoted in the C language using **void ***. The table below shows all private types which are defined in this binding with the corresponding operations to create and discards instances of these types.

Datatypes	Create Operations	Discard Operations
Pcte_attribute_reference	Pcte_type_reference_copy Pcte_type_reference_set	Pcte_type_reference_unset
Pcte_contents_handle	Pcte_contents_open Pcte_contents_get_handle_- from_key Pcte_contents_handle_- duplicate Pcte_contents_handle_- duplicate_to_key	Pcte_contents_close
Pcte_link_reference	Pcte_link_reference_copy Pcte_link_reference_set	Pcte_link_reference_unset
Pcte_object_reference	Pcte_reference_copy Pcte_reference_set_absolute Pcte_reference_set_relative	Pcte_reference_unset
Pcte_position_handle	Pcte_contents_get_position	Pcte_position_handle_discard Pcte_contents_close
Pcte_profile_handle	Pcte_process_profiling_on	Pcte_process_profiling_off
Pcte_sequence	Pcte_sequence_create	Pcte_sequence_discard
Pcte_type_reference	Pcte_type_reference_copy Pcte_type_reference_set	Pcte_type_reference_unset

8.4 References and Names

The LI datatypes *attribute_reference*, *link_reference* and *type_reference* are mapped to the C datatypes **Pcte_attribute_name**, **Pcte_link_name**, and **Pcte_type_name**.

If an attribute reference, link reference, or type reference is passed as part of a parameter, the corresponding parts of the LI datatype of that parameter is also mapped to the C datatypes **Pcte_attribute_name**, **Pcte_link_name**, or **Pcte_type_name**.

Whenever a parameter of an operation in clause 9 to 22 is either an attribute reference, link reference or type reference, a second interface is defined beginning 'Pcte_h_' instead of 'Pcte_'. In this case, the LI datatypes *attribute_reference*, *link_reference* and *type_reference* are mapped to the C datatypes **Pcte_attribute_reference**, **Pcte_link_reference**, and **Pcte_type_reference** (see clause 23).

It may be necessary that if an attribute reference, link reference, or type reference is passed as part of a parameter of the C datatype **Pcte_xxx**, a new C datatype **Pcte_h_xxx** is defined using the C datatypes **Pcte_attribute_reference**, **Pcte_link_reference**, and **Pcte_type_reference**.

All definitions concerning operations beginning with 'Pcte_' also hold for 'Pcte_h_'.

8.5 C Private Type: Pcte_sequence

The new LI datatype *Sequence* is mapped to a family of C datatypes defined by the C datatype **Pcte_sequence**, defined as follows:

```
typedef void *Pcte_sequence;
```

```
#define Pcte_null_sequence (Pcte_sequence) NULL
```

In addition, there is for each LI datatype *xxx* which is a *sequence*, except *text* and *Pcte_string*, a C datatype with the corresponding name **Pcte_xxx**. Instead of **Pcte_h_attribute_references**, **Pcte_h_link_references**, and **Pcte_h_type_references**, the C datatypes **Pcte_attribute_names**, **Pcte_link_names**, and **Pcte_type_names** are used.

As ACL and attribute assignments are also defined as sequences (see 9.1, 19.1) corresponding C datatypes for these PCTE datatypes are also provided.

```
typedef Pcte_sequence Pcte_accounting_log;
```

```
typedef Pcte_sequence Pcte_acl;
```

```
typedef Pcte_sequence Pcte_audit_file;
```

```
typedef Pcte_sequence Pcte_attribute_assignments;
```

```
typedef Pcte_sequence Pcte_h_attribute_assignments;
```

```
typedef Pcte_sequence Pcte_attribute_names;
```

```
typedef Pcte_sequence Pcte_attribute_references;
```

```
typedef Pcte_sequence Pcte_buffer;
```

```
typedef Pcte_sequence Pcte_confidentiality_criteria;
```

```
typedef Pcte_sequence Pcte_enumeration_value_type;
```

```
typedef Pcte_sequence Pcte_h_enumeration_value_type;
```

```
typedef Pcte_sequence Pcte_enumeration_value_type_in_sds;
```

```
typedef Pcte_sequence Pcte_general_criteria;
```

```
typedef Pcte_sequence Pcte_integrity_criteria;
```

```
typedef Pcte_sequence Pcte_key_types;
```

```
typedef Pcte_sequence Pcte_h_key_types;
```

```

typedef Pcte_sequence Pcte_key_types_in_sds;
typedef Pcte_sequence Pcte_link_set_descriptors;
typedef Pcte_sequence Pcte_h_link_set_descriptors;
typedef Pcte_sequence Pcte_link_names;
typedef Pcte_sequence Pcte_link_references;
typedef Pcte_sequence Pcte_message_types;
typedef Pcte_sequence Pcte_name_sequence;
typedef Pcte_sequence Pcte_object_criteria;
typedef Pcte_sequence Pcte_object_references;
typedef Pcte_sequence Pcte_type_names;
typedef Pcte_sequence Pcte_type_names_in_sds;
typedef Pcte_sequence Pcte_type_references;
typedef Pcte_sequence Pcte_user_criteria;
typedef Pcte_sequence Pcte_volume_infos;

```

The following additional datatypes are used in the operational interfaces to these private types:

```

typedef enum {
    PCTE_ACCOUNTING_FILE, PCTE_ACL,
    PCTE_AUDIT_FILE, PCTE_ATTRIBUTE_ASSIGNMENTS,
    PCTE_H_ATTRIBUTE_ASSIGNMENTS,
    PCTE_ATTRIBUTE_NAMES, PCTE_ATTRIBUTE_REFERENCES,
    PCTE_BUFFER, PCTE_CONFIDENTIALITY_CRITERIA,
    PCTE_ENUMERATION_VALUE_TYPE,
    PCTE_H_ENUMERATION_VALUE_TYPE,
    PCTE_ENUMERATION_VALUE_TYPE_IN_SDS,
    PCTE_GENERAL_CRITERIA, PCTE_INTEGRITY_CRITERIA,
    PCTE_KEY_TYPES, PCTE_H_KEY_TYPES,
    PCTE_KEY_TYPES_IN_SDS, PCTE_LINK_NAMES,
    PCTE_LINK_SET_DESCRIPTOR, PCTE_H_LINK_SET_DESCRIPTOR,
    PCTE_LINK_REFERENCES, PCTE_MESSAGE_TYPES,
    PCTE_NAME_SEQUENCE, PCTE_OBJECT_CRITERIA,
    PCTE_OBJECT_REFERENCES, PCTE_TYPE_NAMES,
    PCTE_TYPE_NAMES_IN_SDS, PCTE_TYPE_REFERENCES,
    PCTE_USER_CRITERIA, PCTE_VOLUME_INFOS
} Pcte_sequence_type;

typedef void *Pcte_sequence_element;

typedef void *Pcte_array_of_sequence_elements;

```

Values of the type **Pcte_sequence_element** are used to set or retrieve a single element of a sequence using the operations **Pcte_put_element** or **Pcte_get_element**. In both cases, a pointer to a single value of the sequence element type has to be provided. For example, if the sequence is of type **Pcte_object_references**, a pointer to a value of type **Pcte_object_reference** has to be provided.

Pcte_array_of_sequence_elements is used to set or retrieve several elements to or from a sequence using the operations **Pcte_sequence_create**, **Pcte_sequence_insert_elements**, and **Pcte_sequence_get_elements**. In this case, a pointer to an array of the sequence element type has to be provided. For example, if the sequence is of type **Pcte_object_references**, a pointer to an array of **Pcte_object_reference** has to be provided.

The enumeration type **Pcte_sequence_type** is used to indicate the C element type of the sequence as follows:

enumeration value	C element type
PCTE_ACCOUNTING_FILE	Pcte_accounting_record
PCTE_ACL	Pcte_acl_entry
PCTE_AUDIT_FILE	Pcte_auditing_record
PCTE_ATTRIBUTE_ASSIGNMENTS	Pcte_attribute_assignment
PCTE_H_ATTRIBUTE_ASSIGNMENTS	Pcte_h_attribute_assignment
PCTE_ATTRIBUTE_NAMES	Pcte_attribute_name
PCTE_ATTRIBUTE_REFERENCES	Pcte_attribute_reference
PCTE_BUFFER	Pcte_natural
PCTE_CONFIDENTIALITY_CRITERIA	Pcte_confidentiality_criterion
PCTE_ENUMERATION_VALUE_TYPE	Pcte_type_name
PCTE_H_ENUMERATION_VALUE_TYPE	Pcte_type_reference
PCTE_ENUMERATION_VALUE_TYPE_IN_SDS	Pcte_type_name_in_sds
PCTE_GENERAL_CRITERIA	Pcte_general_criterion
PCTE_INTEGRITY_CRITERIA	Pcte_integrity_criterion
PCTE_KEY_TYPES	Pcte_type_name
PCTE_H_KEY_TYPES	Pcte_type_reference
PCTE_KEY_TYPES_IN_SDS	Pcte_type_name_in_sds
PCTE_LINK_NAMES	Pcte_link_name
PCTE_LINK_SET_DESCRIPTOR	Pcte_link_set_descriptor
PCTE_H_LINK_SET_DESCRIPTOR	Pcte_h_link_set_descriptor
PCTE_LINK_REFERENCES	Pcte_link_reference
PCTE_MESSAGE_TYPES	Pcte_message_type
PCTE_NAME_SEQUENCE	Pcte_name
PCTE_OBJECT_CRITERIA	Pcte_object_criterion
PCTE_OBJECT_REFERENCES	Pcte_object_reference
PCTE_TYPE_NAMES	Pcte_type_name
PCTE_TYPE_NAMES_IN_SDS	Pcte_type_name_in_sds
PCTE_TYPE_REFERENCES	Pcte_type_reference
PCTE_USER_CRITERIA	Pcte_user_criterion
PCTE_VOLUME_INFOS	Pcte_volume_info

8.5.1 Operations on Sequences

The following operations are defined on objects of type **Pcte_sequence**. Each operation returns a status via its return value, which indicates its success or failure. For an interpretation of returned status values, see clause 25, Error Conditions.

In some operations, elements of a sequence can be referenced using an index according to the positions of elements within the sequence. The first element of a

sequence has the position 0.

Pcte_sequence_create

```
Pcte_error_type Pcte_sequence_create (
    Pcte_sequence_type      type,
    Pcte_array_of_sequence_elements data,
    Pcte_natural             count,
    Pcte_sequence            *sequence
);
```

Pcte_sequence_create creates an instance of the sequence type specified by *type*, with *count* element values specified by *data*, and returns a pointer to it in *sequence*.

Pcte_sequence_discard

```
Pcte_error_type Pcte_sequence_discard (
    Pcte_sequence *sequence
);
```

Pcte_sequence_discard releases the contents of the sequence pointed to by *sequence* and discards any allocated data structures associated with it. The data structures allocated with each element are also discarded, even if they are themselves sequences. A null pointer is returned in *sequence*. When a sequence of types containing an object reference (i.e. *object_references*, *link_set* descriptors and *object_criterion*) is discarded, the object references contained in the sequence are unset as defined by the operation *object_reference_unset*.

Pcte_sequence_copy

```
Pcte_error_type Pcte_sequence_copy (
    Pcte_sequence source_list,
    Pcte_sequence destination_list,
    Pcte_natural index,
    Pcte_natural source_index,
    Pcte_natural count
);
```

Pcte_sequence_copy copies *count* subsequent elements of data from the sequence *source_list* from the position *source_index* to the sequence *destination_list* before the element at position *index*. If *index* is greater than the number of elements of *destination_list*, these elements are appended at the end of *destination_list*. Copying sequences is a deep copy operation, and object references are copied as they are with the status and evaluation point. Deallocating the source sequence or any of its elements will not affect the destination.

Pcte_sequence_insert_elements

```

Pcte_error_type Pcte_sequence_insert_elements (
    Pcte_sequence      sequence,
    Pcte_natural        index,
    Pcte_array_of_sequence_elements data,
    Pcte_natural        count
);

```

`Pcte_sequence_insert_elements` inserts the *count* elements specified by *data* into the sequence *sequence* before the element at position *index*.

Pcte_sequence_delete

```

Pcte_error_type Pcte_sequence_delete (
    Pcte_sequence      sequence,
    Pcte_natural        index,
    Pcte_natural        count
);

```

`Pcte_sequence_delete` removes the *count* subsequent elements from the sequence *sequence* starting with the element at position *index*.

Pcte_sequences_are_equal

```

Pcte_error_type Pcte_sequences_are_equal (
    Pcte_sequence      first_sequence,
    Pcte_sequence      second_sequence,
    Pcte_boolean        *equality
);

```

`Pcte_sequences_are_equal` returns in *equality* the value `PCTE_TRUE` if the two sequences *first_sequence* and *second_sequence* are equal, and the value `PCTE_FALSE` otherwise. Two sequences are equal if they contain the same number of elements and the values of corresponding elements are equal.

Pcte_sequence_get_index:

```

Pcte_error_type Pcte_sequence_get_index (
    Pcte_sequence      sequence,
    Pcte_sequence_element element,
    Pcte_integer        *index
);

```

`Pcte_sequence_get_index` returns in *index* the index of the first occurrence of the given element *element* in the sequence *sequence* if the element is a member of the sequence; otherwise -1 is returned.

Pcte_sequence_get_length

```

Pcte_error_type Pcte_sequence_get_length (
    Pcte_sequence    sequence,
    Pcte_natural      *length
);

```

Pcte_sequence_get_length returns in *length* the number of elements of the sequence *sequence*.

Pcte_sequence_get_elements

```

Pcte_error_type Pcte_sequence_get_elements (
    Pcte_sequence    sequence,
    Pcte_natural      index,
    Pcte_array_of_sequence_elements data,
    Pcte_natural      count
);

```

Pcte_sequence_get_elements returns *count* elements from the sequence *sequence* into *data*, starting from the element at position *index*.

Pcte_sequence_get

```

Pcte_error_type Pcte_sequence_get (
    Pcte_sequence    sequence,
    Pcte_natural      index,
    Pcte_sequence_element element
);

```

Pcte_sequence_get returns in *element* a copy of the element specified by *index* from the sequence *sequence*.

Pcte_sequence_insert

```

Pcte_error_type Pcte_sequence_insert (
    Pcte_sequence    sequence,
    Pcte_natural      index,
    Pcte_sequence_element element
);

```

Pcte_sequence_insert inserts in the sequence *sequence* the element *element* immediately before the element specified by *index*. If *index* is not less than the length of *sequence*, the element is appended to *sequence*.

Pcte_sequence_replace

```

Pcte_error_type Pcte_sequence_replace (
    Pcte_sequence      sequence,
    Pcte_natural        index,
    Pcte_sequence_element element
);

```

`Pcte_sequence_replace` replaces in the sequence *sequence* the element specified by *index* with the element *element*. If *index* is not less than the length of *sequence*, the element is appended to *sequence*.

Pcte_sequence_append

```

Pcte_error_type Pcte_sequence_append (
    Pcte_sequence      sequence,
    Pcte_sequence_element element
);

```

`Pcte_sequence_append` appends to the sequence *sequence* the element specified by *element*.

Pcte_sequence_normalize

```

Pcte_error_type Pcte_sequence_normalize (
    Pcte_sequence      sequence
);

```

`Pcte_sequence_normalize` reorganizes the sequence *sequence* so that each element value occurs once only, and elements are in an implementation-defined order. Two sequences containing the same element values (i.e. representing the same unbounded set) are equal after normalization.

8.5.2 Error Conditions for Sequence Operators

The following error conditions may be raised by operations on sequences.

- `PCTE_SEQUENCE_INVALID_TYPE`. Raised by any operation, if the type of a specified sequence does not match the required sequence type for that sequence.
- `PCTE_SEQUENCE_BAD_HANDLE`. Raised by any operation, if a specified sequence handle is not a valid sequence handle.
- `PCTE_SEQUENCE_OUT_OF_DATA`. Raised by `Pcte_sequence_get_elements`, if *sequence* does not contain *count* elements from position *index*. Similarly for `Pcte_sequence_copy`.
- `PCTE_SEQUENCE_INVALID_INDEX`. Raised by `Pcte_sequence_get`, if *sequence* does not contain an element at position *index*.

For further information on error conditions leading to an operational failure, see clause 25, Error Conditions.

8.6 Deriving C Function Semantics From Abstract Specification.

Each C function corresponds to the abstract operation in ISO/IEC 13719-1. The semantics of the C function are generally the same as those of the corresponding abstract operation and are derived as follows:

- C function parameters correspond to abstract operation parameters with the same names.
- C function parameter datatypes correspond to the abstract specification datatypes of the corresponding abstract parameters as defined in clause 8.
- Returned values corresponding to results of abstract operations are returned via parametric pointers to objects which contain the returned values. If the result is a mandatory single value of a simple type, the pointer parameter has the same name as the result. In more complicated cases an explanation is given.
- If the abstract operation contains optional parameters, an explanation of the mapping is given.
- If an operation fails, each operation returns `PCTE_ERROR` and `Pcte_error_number` holds the appropriate `Pcte_error_type` value. Otherwise, `PCTE_OK` is returned and `Pcte_error_number` is unchanged.

All exceptions to these general rules are defined in the appropriate clause.

Handlers execute as separate threads, subject to implementation-defined restrictions. Apart from that case, neither the C language, nor the PCTE operations provide mechanisms for a program to execute more than one thread; but an implementation may provide such mechanisms, which may be subject to implementation-defined rules.

8.7 Headers

Each implementation of this part of ISO/IEC 13719 must provide a header `<Pcte/sequences.h>` that contains the definitions of the constant values, datatypes and operation interface bindings for the manipulation of sequences as defined in 8.3.

Each implementation of this part of ISO/IEC 13719 must provide a set of clause-specific headers that contain the definitions of the constant values, data structures, and operation interface bindings for each clause 9 to 22 of ISO/IEC 13719-1.

Each implementation of this part of ISO/IEC 13719 must provide a header `<Pcte/references.h>` that contains the definitions of the constant values, datatypes and operation interface bindings for clause 23 of ISO/IEC 13719-1.

Each implementation of this part of ISO/IEC 13719 must provide a header `<Pcte/limits.h>` that contains the definitions of the constant values defined in clause 24.

Each implementation of this part of ISO/IEC 13719 must provide a header `<Pcte/errors.h>` that contains the definitions of the constant values and datatypes for errors defined in appendix C of ISO/IEC 13719-1.

In addition, each implementation must provide a single header `<Pcte/pcte.h>` which is used to include all other headers.

Each clause-specific header must provide all definitions necessary for the correct functioning of the operations of that clause. This may be achieved by including other headers.

The name of the headers are meant to be interpreted by the C processor as a directory 'Pcte' and files 'xxx.h'. If this does not map appropriately to a file naming convention then the implementation may change the #include directive appropriately.

8.7.1 The Global Pcte Header

```
/* The header <Pcte/pcte.h> */

#ifndef PCTE_INCLUDED
#define PCTE_INCLUDED 1

#include <Pcte/types.h>           /* clause 8.7.2 */
#include <Pcte/sequences.h>       /* clause 8.7.3 */
#include <Pcte/references.h>      /* clause 23 */
#include <Pcte/limits.h>         /* clause 24 */
#include <Pcte/errors.h>         /* clause 25 */

#include <Pcte/oms.h>             /* clause 9 */
#include <Pcte/sms.h>             /* clause 10 */
#include <Pcte/devices.h>        /* clause 11 */
#include <Pcte/contents.h>       /* clause 12 */
#include <Pcte/execution.h>      /* clause 13 */
#include <Pcte/messages.h>      /* clause 14 */
#include <Pcte/notification.h>   /* clause 15 */
#include <Pcte/activities.h>     /* clause 16 */
#include <Pcte/replication.h>    /* clause 17 */
#include <Pcte/network.h>        /* clause 18 */
#include <Pcte/discretionary.h>  /* clause 19 */
#include <Pcte/mandatory.h>     /* clause 20 */
#include <Pcte/auditing.h>      /* clause 21 */
#include <Pcte/accounting.h>     /* clause 22 */

#endif /* !PCTE_INCLUDED */
```

8.7.2 The Pcte Basic Type Header

```
/* The header <Pcte/types.h> */

#ifndef PCTE_TYPES_INCLUDED
#define PCTE_TYPES_INCLUDED 1

#include <time.h>
#include <Pcte/errors.h>

#define PCTE_OK 0
#define PCTE_ERROR 1
```

```

typedef <integer-type> Pcte_boolean;
#define PCTE_TRUE (Pcte_boolean) 1
#define PCTE_FALSE (Pcte_boolean) 0

typedef <integer-type> Pcte_integer;
typedef <natural-type> Pcte_natural;
typedef <float-type> Pcte_float;
typedef time_t Pcte_time;
#define Pcte_time_accuracy_factor (Pcte_natural) <implementation-defined>
#define Pcte_reference_time (Pcte_time) <implementation defined>
#define Pcte_null_time (Pcte_time) <implementation defined>
typedef unsigned char Pcte_octet;
typedef struct {
    Pcte_natural    size;
    Pcte_octet      *array;
} Pcte_string;

/*      Empty string can be used in all the operations that have a string as input      */
/*      parameters, where the user wants to pass a null value for a string.            */
#define PCTE_NULL_STRING "\0"
Pcte_error_type Pcte_string_discard (
    Pcte_string    string
);

#endif /* !PCTE_TYPES_INCLUDED */

```

8.7.3 The Pcte Sequence Header

```

/* The header <Pcte/sequences.h> */
#ifndef PCTE_SEQUENCES_INCLUDED
#define PCTE_SEQUENCES_INCLUDED 1
#include <Pcte/types.h>
typedef void *Pcte_sequence;
#define Pcte_null_sequence (Pcte_sequence) NULL
typedef Pcte_sequence Pcte_accounting_log;
typedef Pcte_sequence Pcte_audit_file;
typedef Pcte_sequence Pcte_attribute_names;

```

```
typedef Pcte_sequence Pcte_attribute_references;
typedef Pcte_sequence Pcte_buffer;
typedef Pcte_sequence Pcte_confidentiality_criteria;
typedef Pcte_sequence Pcte_enumeration_value_type;
typedef Pcte_sequence Pcte_h_enumeration_value_type;
typedef Pcte_sequence Pcte_enumeration_value_type_in_sds;
typedef Pcte_sequence Pcte_general_criteria;
typedef Pcte_sequence Pcte_integrity_criteria;
typedef Pcte_sequence Pcte_key_types;
typedef Pcte_sequence Pcte_h_key_types;
typedef Pcte_sequence Pcte_key_types_in_sds;
typedef Pcte_sequence Pcte_link_set_descriptors;
typedef Pcte_sequence Pcte_h_link_set_descriptors;
typedef Pcte_sequence Pcte_link_names;
typedef Pcte_sequence Pcte_link_references;
typedef Pcte_sequence Pcte_message_types;
typedef Pcte_sequence Pcte_name_sequence;
typedef Pcte_sequence Pcte_object_criteria;
typedef Pcte_sequence Pcte_object_references;
typedef Pcte_sequence Pcte_type_names;
typedef Pcte_sequence Pcte_type_names_in_sds;
typedef Pcte_sequence Pcte_type_references;
typedef Pcte_sequence Pcte_user_criteria;
typedef Pcte_sequence Pcte_volume_infos;
```

```

typedef enum {
    PCTE_ACCOUNTING_FILE, PCTE_ACL,
    PCTE_AUDIT_FILE, PCTE_ATTRIBUTE_ASSIGNMENTS,
    PCTE_H_ATTRIBUTE_ASSIGNMENTS,
    PCTE_ATTRIBUTE_NAMES, PCTE_ATTRIBUTE_REFERENCES,
    PCTE_BUFFER, PCTE_CONFIDENTIALITY_CRITERIA,
    PCTE_ENUMERATION_VALUE_TYPE,
    PCTE_H_ENUMERATION_VALUE_TYPE,
    PCTE_ENUMERATION_VALUE_TYPE_IN_SDS,
    PCTE_GENERAL_CRITERIA, PCTE_INTEGRITY_CRITERIA,
    PCTE_KEY_TYPES, PCTE_H_KEY_TYPES,
    PCTE_KEY_TYPES_IN_SDS, PCTE_LINK_NAMES,
    PCTE_LINK_SET_DESCRIPTOR, PCTE_H_LINK_SET_DESCRIPTOR,
    PCTE_LINK_REFERENCES, PCTE_MESSAGE_TYPES,
    PCTE_NAME_SEQUENCE, PCTE_OBJECT_CRITERIA,
    PCTE_OBJECT_REFERENCES, PCTE_TYPE_NAMES,
    PCTE_TYPE_NAMES_IN_SDS, PCTE_TYPE_REFERENCES,
    PCTE_USER_CRITERIA, PCTE_VOLUME_INFOS
} Pcte_sequence_type;

typedef void *Pcte_sequence_element;

typedef void *Pcte_array_of_sequence_elements;

Pcte_error_type Pcte_sequence_create (
    Pcte_sequence_type      type,
    Pcte_array_of_sequence_elements data,
    Pcte_natural            count,
    Pcte_sequence           *sequence
);

Pcte_error_type Pcte_sequence_discard (
    Pcte_sequence      *sequence
);

Pcte_error_type Pcte_sequence_copy (
    Pcte_sequence      source_list,
    Pcte_sequence      *destination_list,
    Pcte_natural       index,
    Pcte_natural       source_index,
    Pcte_natural       count
);

Pcte_error_type Pcte_sequence_insert_elements (
    Pcte_sequence      sequence,
    Pcte_natural       index,
    Pcte_array_of_sequence_elements data,
    Pcte_natural       count
);

```

```
Pcte_error_type Pcte_sequence_delete (
    Pcte_sequence    sequence,
    Pcte_natural     index,
    Pcte_natural     count
);

Pcte_error_type Pcte_sequences_are_equal (
    Pcte_sequence    first_sequence,
    Pcte_sequence    second_sequence,
    Pcte_boolean     *equality
);

Pcte_error_type Pcte_sequence_get_index (
    Pcte_sequence    sequence,
    Pcte_sequence_element element,
    Pcte_integer     *index
);

Pcte_error_type Pcte_sequence_get_length (
    Pcte_sequence    sequence,
    Pcte_natural     *length
);

Pcte_error_type Pcte_sequence_get_elements (
    Pcte_sequence    sequence,
    Pcte_natural     index,
    Pcte_array_of_sequence_elements data,
    Pcte_natural     count
);

Pcte_error_type Pcte_sequence_get (
    Pcte_sequence    sequence,
    Pcte_natural     index,
    Pcte_sequence_element element
);

Pcte_error_type Pcte_sequence_insert (
    Pcte_sequence    sequence,
    Pcte_natural     index,
    Pcte_sequence_element element
);

Pcte_error_type Pcte_sequence_replace (
    Pcte_sequence    sequence,
    Pcte_natural     index,
    Pcte_sequence_element element
);
```

```

Pcte_error_type Pcte_sequence_append (
    Pcte_sequence      sequence,
    Pcte_sequence_element element
);

Pcte_error_type Pcte_sequence_normalize (
    Pcte_sequence      sequence
);

#endif /* !PCTE_SEQUENCES_INCLUDED */

```

9 Object management

/* The header <Pcte/oms.h> */

```

#ifndef PCTE_OMS_INCLUDED
#define PCTE_OMS_INCLUDED 1

#include <Pcte/types.h>
#include <Pcte/references.h>

```

9.1 Object Management Datatypes

```

typedef enum {
    PCTE_COMPOSITION      = 1<<0,
    PCTE_EXISTENCE        = 1<<1,
    PCTE_REFERENCE         = 1<<2,
    PCTE_DESIGNATION      = 1<<3,
    PCTE_IMPLICIT          = 1<<4
} Pcte_category;

typedef Pcte_natural Pcte_categories;

#define PCTE_ALL_CATEGORIES (Pcte_natural) (PCTE_COMPOSITION | \
PCTE_EXISTENCE | \
PCTE_REFERENCE | \
PCTE_DESIGNATION | \
PCTE_IMPLICIT)

typedef enum {
    PCTE_BOOLEAN_ATTRIBUTE,
    PCTE_INTEGER_ATTRIBUTE,
    PCTE_NATURAL_ATTRIBUTE,
    PCTE_FLOAT_ATTRIBUTE,
    PCTE_STRING_ATTRIBUTE,
    PCTE_TIME_ATTRIBUTE,
    PCTE_ENUMERATION_ATTRIBUTE
} Pcte_value_type;

```

```

/*      The PCTE datatype Value_type is a union which also contains the      */
/*      constituent type Enumeration_value_type, which is a sequence of      */
/*      Enumeral_type_nominator. For convenience, in the operations          */
/*      SDS_GET_ATTRIBUTE_TYPE_PROPERTIES and                               */
/*      WS_GET_ATTRIBUTE_TYPE_PROPERTIES an additional parameter             */
/*      is used to return an enumeration value type if necessary. In all other */
/*      cases it is sufficient to use Pcte_value_type.                      */

```

```

typedef struct {
    Pcte_value_type    type;
    union {
        Pcte_boolean   v_boolean;
        Pcte_integer    v_integer;
        Pcte_natural    v_natural;
        Pcte_float      v_float;
        Pcte_string     v_string;
        Pcte_time       v_time;
        Pcte_natural    v_enumeral_type_position;
    } value;
} Pcte_attribute_value;

```

```

typedef struct {
    Pcte_attribute_name    attribute;
    Pcte_attribute_value   value;
} Pcte_attribute_assignment;

```

```

typedef struct {
    Pcte_attribute_reference    attribute;
    Pcte_attribute_value       value;
} Pcte_h_attribute_assignment;

```

```

#include <Pcte/sequences.h>

```

```

typedef Pcte_sequence Pcte_attribute_assignments;

```

```

typedef Pcte_sequence Pcte_h_attribute_assignments;

```

```

/*      The PCTE datatype attribute assignments, which is a map from attribute */
/*      reference to a value type, is mapped to the sequence                  */
/*      Pcte_attribute_assignments indicated by                               */
/*      PCTE_ATTRIBUTE_ASSIGNMENT with the C element datatype                */
/*      Pcte_attribute_assignment. The component attribute represents the     */
/*      domain of the map whereas the component value_type indicates the     */
/*      value of the map. If a parameter of type Pcte_attribute_assignments is */
/*      passed as an input parameter to an operation and if there is more than */
/*      one entry in the sequence with the same value of the component        */
/*      attribute, only the first of these entries is recognized in the operation. */

```

```

typedef enum {
    PCTE_INTERNAL_LINKS, PCTE_EXTERNAL_LINKS,
    PCTE_ALL_LINKS
} Pcte_link_scope;

typedef enum {
    PCTE_EQUAL_TYPE, PCTE_ANCESTOR_TYPE,
    PCTE_DESCENDANT_TYPE, PCTE_UNRELATED_TYPE
} Pcte_type_ancestry;

typedef enum {
    PCTE_ANCESTOR_VSN, PCTE_DESCENDANT_VSN,
    PCTE_SAME_VSN, PCTE_RELATED_VSN,
    PCTE_UNRELATED_VSN
} Pcte_version_relation;

typedef enum {
    PCTE_ATOMIC, PCTE_COMPOSITE
} Pcte_object_scope;

typedef enum {
    PCTE_ACCESSIBLE, PCTE_INACCESSIBLE, PCTE_UNKNOWN
} Pcte_volume_accessibility;

#include <Pcte/devices.h>

typedef struct {
    Pcte_volume_identifier    volume;
    Pcte_volume_accessibility    mounted;
} Pcte_volume_info;

typedef struct {
    Pcte_object_reference    origin;
    Pcte_link_names    links;
} Pcte_link_set_descriptor;

typedef struct {
    Pcte_object_reference    origin;
    Pcte_link_references    links;
} Pcte_h_link_set_descriptor;

#define PCTE_MAX_EXACT_IDENTIFIER_SIZE PCTE_MAX_KEY_SIZE

typedef Pcte_octet
    Pcte_exact_identifier[PCTE_MAX_EXACT_IDENTIFIER_SIZE + 1];

#include <Pcte/discretionary.h>

```

9.2 Link Operations

/* 9.2.1 LINK_CREATE */

```
Pcte_error_type Pcte_link_create (
    Pcte_object_reference  origin,
    Pcte_link_name        new_link,
    Pcte_object_reference  dest,
    Pcte_key              reverse_key
);
```

```
Pcte_error_type Pcte_h_link_create (
    Pcte_object_reference  origin,
    Pcte_link_reference    new_link,
    Pcte_object_reference  dest,
    Pcte_key              reverse_key
);
```

/* The effect of not providing the optional parameter *reverse_key* to the */
 /* abstract operation is achieved by specifying **reverse_key** as NULL. */

/* 9.2.2 LINK_DELETE */

```
Pcte_error_type Pcte_link_delete (
    Pcte_object_reference  origin,
    Pcte_link_name        link
);
```

```
Pcte_error_type Pcte_h_link_delete (
    Pcte_object_reference  origin,
    Pcte_link_reference    link
);
```

/* 9.2.3 LINK_DELETE_ATTRIBUTE */

```
Pcte_error_type Pcte_link_delete_attribute (
    Pcte_object_reference  origin,
    Pcte_link_name        link,
    Pcte_attribute_reference attribute
);
```

```
Pcte_error_type Pcte_h_link_delete_attribute (
    Pcte_object_reference  origin,
    Pcte_link_reference    link,
    Pcte_attribute_reference attribute
);
```

```
/* 9.2.4 LINK_GET_ATTRIBUTE */
```

```
Pcte_error_type Pcte_link_get_attribute (
    Pcte_object_reference  origin,
    Pcte_link_name        link,
    Pcte_attribute_name    attribute,
    Pcte_attribute_value   *value
);
```

```
Pcte_error_type Pcte_h_link_get_attribute (
    Pcte_object_reference  origin,
    Pcte_link_reference    link,
    Pcte_attribute_reference attribute,
    Pcte_attribute_value   *value
);
```

```
/* 9.2.5 LINK_GET_DESTINATION_VOLUME */
```

```
Pcte_error_type Pcte_link_get_destination_volume (
    Pcte_object_reference  origin,
    Pcte_link_name        link,
    Pcte_volume_info      *volume_info
);
```

```
Pcte_error_type Pcte_h_link_get_destination_volume (
    Pcte_object_reference  origin,
    Pcte_link_reference    link,
    Pcte_volume_info      *volume_info
);
```

```
/* 9.2.6 LINK_GET_KEY */
```

```
Pcte_error_type Pcte_link_get_key (
    Pcte_object_reference  origin,
    Pcte_link_name        link,
    Pcte_key               key
);
```

```
Pcte_error_type Pcte_h_link_get_key (
    Pcte_object_reference  origin,
    Pcte_link_reference    link,
    Pcte_key               key
);
```

```
/* 9.2.7 LINK_GET_REVERSE */
```

```
Pcte_error_type Pcte_link_get_reverse (
    Pcte_object_reference  origin,
    Pcte_link_name        link,
    Pcte_link_name        reverse_link,
    Pcte_object_reference  *dest
);
```

```

Pcte_error_type Pcte_h_link_get_reverse (
    Pcte_object_reference    origin,
    Pcte_link_reference      link,
    Pcte_link_reference      *reverse_link,
    Pcte_object_reference    *dest
);

/*      If the abstract operation returns no value in reverse_link then      */
/*      reverse_link is set to NULL for Pcte_h_link_get_reverse and is set to a      */
/*      string of zero length for Pcte_link_get_reverse.                      */
/* 9.2.8 LINK_GET_SEVERAL_ATTRIBUTES */

Pcte_error_type Pcte_link_get_attributes_in_working_schema (
    Pcte_object_reference    origin,
    Pcte_link_name          link,
    Pcte_attribute_assignments *values
);

Pcte_error_type Pcte_h_link_get_attributes_in_working_schema (
    Pcte_object_reference    origin,
    Pcte_link_reference      link,
    Pcte_h_attribute_assignments *values
);

Pcte_error_type Pcte_link_get_attributes_of_types (
    Pcte_object_reference    origin,
    Pcte_link_name          link,
    Pcte_attribute_names     attributes,
    Pcte_attribute_assignments *values
);

Pcte_error_type Pcte_h_link_get_attributes_of_types (
    Pcte_object_reference    origin,
    Pcte_link_reference      link,
    Pcte_attribute_references attributes,
    Pcte_h_attribute_assignments *values
);

/*      The effect of specifying attributes as VISIBLE_ATTRIBUTE_TYPES      */
/*      to the abstract operation is achieved by the operation                */
/*      Pcte_link_get_attributes_in_working_schema. The effect of specifying    */
/*      attributes as a set of attribute designators to the abstract operation is */
/*      achieved by the operation Pcte_link_get_attributes_of_types.            */

```

/* 9.2.9 LINK_REPLACE */

```
Pcte_error_type Pcte_link_replace (
    Pcte_object_reference    origin,
    Pcte_link_name           link,
    Pcte_object_reference    new_origin,
    Pcte_link_name           new_link,
    Pcte_key                 new_reverse_key
);
```

```
Pcte_error_type Pcte_h_link_replace (
    Pcte_object_reference    origin,
    Pcte_link_reference      link,
    Pcte_object_reference    new_origin,
    Pcte_link_reference      new_link,
    Pcte_key                 new_reverse_key
);
```

/* 9.2.10 LINK_RESET_ATTRIBUTE */

```
Pcte_error_type Pcte_link_reset_attribute (
    Pcte_object_reference    origin,
    Pcte_link_name           link,
    Pcte_attribute_name      attribute
);
```

```
Pcte_error_type Pcte_h_link_reset_attribute (
    Pcte_object_reference    origin,
    Pcte_link_reference      link,
    Pcte_attribute_reference  attribute
);
```

/* 9.2.11 LINK_SET_ATTRIBUTE */

```
Pcte_error_type Pcte_link_set_attribute (
    Pcte_object_reference    origin,
    Pcte_link_name           link,
    Pcte_attribute_name      attribute,
    Pcte_attribute_value     *value
);
```

```
Pcte_error_type Pcte_h_link_set_attribute (
    Pcte_object_reference    origin,
    Pcte_link_reference      link,
    Pcte_attribute_reference  attribute,
    Pcte_attribute_value     *value
);
```

/* 9.2.12 LINK_SET_SEVERAL_ATTRIBUTES */

```
Pcte_error_type Pcte_link_set_several_attributes (  
    Pcte_object_reference      origin,  
    Pcte_link_name            link,  
    Pcte_attribute_assignments attributes  
);
```

```
Pcte_error_type Pcte_h_link_set_several_attributes (  
    Pcte_object_reference      origin,  
    Pcte_link_reference        link,  
    Pcte_h_attribute_assignments attributes  
);
```

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 13719-2:1995

9.3 Object Operations

/* 9.3.1 OBJECT_CHECK_TYPE */

```
Pcte_error_type Pcte_object_check_type (
    Pcte_object_reference    object,
    Pcte_type_name          type2,
    Pcte_type_ancestry      *relation
);
```

```
Pcte_error_type Pcte_h_object_check_type (
    Pcte_object_reference    object,
    Pcte_type_reference      type2,
    Pcte_type_ancestry      *relation
);
```

/* 9.3.2 OBJECT_CONVERT */

```
Pcte_error_type Pcte_object_convert (
    Pcte_object_reference    object,
    Pcte_type_name          type
);
```

```
Pcte_error_type Pcte_h_object_convert (
    Pcte_object_reference    object,
    Pcte_type_reference      type
);
```

/* 9.3.3 OBJECT_COPY */

```
Pcte_error_type Pcte_object_copy (
    Pcte_object_reference    object,
    Pcte_object_reference    new_origin,
    Pcte_link_name          new_link,
    Pcte_key                reverse_key,
    Pcte_object_reference    on_same_volume_as,
    Pcte_atomic_access_rights *access_mask,
    Pcte_object_reference    *new_object
);
```

```
Pcte_error_type Pcte_h_object_copy (
    Pcte_object_reference    object,
    Pcte_object_reference    new_origin,
    Pcte_link_reference      new_link,
    Pcte_key                reverse_key,
    Pcte_object_reference    on_same_volume_as,
    Pcte_atomic_access_rights *access_mask,
    Pcte_object_reference    *new_object
);
```

```

/*      The effect of not providing the optional parameter reverse_key to the      */
/*      abstract operation is achieved by specifying reverse_key as NULL. The      */
/*      effect of not providing the optional parameter on_same_volume_as to      */
/*      the abstract operation is achieved by specifying on_same_volume_as as      */
/*      Pcte_null_object_reference.                                              */

```

```

/* 9.3.4 OBJECT_CREATE */

```

```

Pcte_error_type Pcte_object_create (
    Pcte_type_name          type,
    Pcte_object_reference    new_origin,
    Pcte_link_name          new_link,
    Pcte_key                reverse_key,
    Pcte_object_reference    on_same_volume_as,
    Pcte_atomic_access_rights *access_mask,
    Pcte_object_reference    *new_object
);

```

```

Pcte_error_type Pcte_h_object_create (
    Pcte_type_reference      type,
    Pcte_object_reference    new_origin,
    Pcte_link_reference      new_link,
    Pcte_key                reverse_key,
    Pcte_object_reference    on_same_volume_as,
    Pcte_atomic_access_rights *access_mask,
    Pcte_object_reference    *new_object
);

```

```

/*      The effect of not providing the optional parameter reverse_key to the      */
/*      abstract operation is achieved by specifying reverse_key as NULL. The      */
/*      effect of not providing the optional parameter on_same_volume_as to      */
/*      the abstract operation is achieved by specifying on_same_volume_as as      */
/*      Pcte_null_object_reference.                                              */

```

```

/* 9.3.5 OBJECT_DELETE */

```

```

Pcte_error_type Pcte_object_delete (
    Pcte_object_reference    origin,
    Pcte_link_name          link
);

```

```

Pcte_error_type Pcte_h_object_delete (
    Pcte_object_reference    origin,
    Pcte_link_reference      link
);

```

/* 9.3.6 OBJECT_DELETE_ATTRIBUTE */

```
Pcte_error_type Pcte_object_delete_attribute (
    Pcte_object_reference    object,
    Pcte_attribute_name      attribute
);
```

```
Pcte_error_type Pcte_h_object_delete_attribute (
    Pcte_object_reference    object,
    Pcte_attribute_reference attribute
);
```

/* 9.3.7 OBJECT_GET_ATTRIBUTE */

```
Pcte_error_type Pcte_object_get_attribute (
    Pcte_object_reference    object,
    Pcte_attribute_name      attribute,
    Pcte_attribute_value     *value
);
```

```
Pcte_error_type Pcte_h_object_get_attribute (
    Pcte_object_reference    object,
    Pcte_attribute_reference attribute,
    Pcte_attribute_value     *value
);
```

/* 9.3.8 OBJECT_GET_PREFERENCE */

```
Pcte_error_type Pcte_object_get_preference (
    Pcte_object_reference    object,
    Pcte_key                 key,
    Pcte_type_name           type
);
```

```
Pcte_error_type Pcte_h_object_get_preference (
    Pcte_object_reference    object,
    Pcte_key                 key,
    Pcte_type_reference      *type
);
```

```
/*      If the abstract operation returns no key, key is set as a string of zero */
/*      length. If the abstract operation returns no type, type is set to NULL for */
/*      Pcte_h_object_get_preference and to a string of zero length for */
/*      Pcte_object_get_preference. */
```

/* 9.3.9 OBJECT_GET_SEVERAL_ATTRIBUTES */

```
Pcte_error_type Pcte_object_get_attributes_in_working_schema (
    Pcte_object_reference    object,
    Pcte_attribute_assignments *values
);
```

```
Pcte_error_type Pcte_h_object_get_attributes_in_working_schema (
    Pcte_object_reference      object,
    Pcte_h_attribute_assignments *values
);
```

```
Pcte_error_type Pcte_object_get_attributes_of_types (
    Pcte_object_reference      object,
    Pcte_attribute_names      attributes,
    Pcte_attribute_assignments *values
);
```

```
Pcte_error_type Pcte_h_object_get_attributes_of_types (
    Pcte_object_reference      object,
    Pcte_attribute_references  attributes,
    Pcte_h_attribute_assignments *values
);
```

```
/*      The effect of specifying attributes as VISIBLE_ATTRIBUTE_TYPES      */
/*      to the abstract operation is achieved by the operation              */
/*      Pcte_object_get_attributes_in_working_schema. The effect of specifying */
/*      attributes as a set of attribute designators to the abstract operation */
/*      achieved by the operation Pcte_object_get_attributes_of_types.      */
```

```
/* 9.3.10 OBJECT_GET_TYPE */
```

```
Pcte_error_type Pcte_object_get_type (
    Pcte_object_reference      object,
    Pcte_type_name            type
);
```

```
Pcte_error_type Pcte_h_object_get_type (
    Pcte_object_reference      object,
    Pcte_type_reference        *type
);
```

```
/* 9.3.11 OBJECT_IS_COMPONENT */
```

```
Pcte_error_type Pcte_object_is_component (
    Pcte_object_reference      object1,
    Pcte_object_reference      object2,
    Pcte_boolean               *value
);
```

```
/* 9.3.12 OBJECT_LIST_LINKS */
```

```
Pcte_error_type Pcte_object_list_all_links (
    Pcte_object_reference      origin,
    Pcte_link_scope            extent,
    Pcte_object_scope          scope,
    Pcte_categories            categories,
    Pcte_link_set_descriptors  *links
);
```

```

Pcte_error_type Pcte_h_object_list_all_links (
    Pcte_object_reference    origin,
    Pcte_link_scope          extent,
    Pcte_object_scope        scope,
    Pcte_categories          categories,
    Pcte_h_link_set_descriptors *links
);

/*      The effect of specifying visibility as ALL_LINK_TYPES is achieved by */
/*      the operation Pcte_object_list_all_links. For Pcte_object_list_all_links, */
/*      all the link type names in the returned link names are type identifiers. */

Pcte_error_type Pcte_object_list_links_in_working_schema (
    Pcte_object_reference    origin,
    Pcte_link_scope          extent,
    Pcte_object_scope        scope,
    Pcte_categories          categories,
    Pcte_link_set_descriptors *links
);

Pcte_error_type Pcte_h_object_list_links_in_working_schema (
    Pcte_object_reference    origin,
    Pcte_link_scope          extent,
    Pcte_object_scope        scope,
    Pcte_categories          categories,
    Pcte_h_link_set_descriptors *links
);

/*      The effect of specifying visibility as VISIBLE_TYPES is achieved by */
/*      the operation Pcte_object_list_links_in_working_schema. */

Pcte_error_type Pcte_object_list_links_of_types (
    Pcte_object_reference    origin,
    Pcte_link_scope          extent,
    Pcte_object_scope        scope,
    Pcte_type_names          types,
    Pcte_link_set_descriptors *links
);

Pcte_error_type Pcte_h_object_list_links_of_types (
    Pcte_object_reference    origin,
    Pcte_link_scope          extent,
    Pcte_object_scope        scope,
    Pcte_type_references     types,
    Pcte_h_link_set_descriptors *links
);

/*      The effect of specifying visibility as link type nominators is achieved by */
/*      the operation Pcte_object_list_links_of_types. */

```

/* 9.3.13 OBJECT_LIST_VOLUMES */

```
Pcte_error_type Pcte_object_list_volumes (  
    Pcte_object_reference    object,  
    Pcte_volume_infos       *volumes  
);
```

/* 9.3.14 OBJECT_MOVE */

```
Pcte_error_type Pcte_object_move (  
    Pcte_object_reference    object,  
    Pcte_object_reference    on_same_volume_as,  
    Pcte_object_scope        scope  
);
```

/* 9.3.15 OBJECT_RESET_ATTRIBUTE */

```
Pcte_error_type Pcte_object_reset_attribute (  
    Pcte_object_reference    object,  
    Pcte_attribute_name      attribute  
);
```

```
Pcte_error_type Pcte_h_object_reset_attribute (  
    Pcte_object_reference    object,  
    Pcte_attribute_reference  attribute  
);
```

/* 9.3.16 OBJECT_SET_ATTRIBUTE */

```
Pcte_error_type Pcte_object_set_attribute (  
    Pcte_object_reference    object,  
    Pcte_attribute_name      attribute,  
    Pcte_attribute_value     *value  
);
```

```
Pcte_error_type Pcte_h_object_set_attribute (  
    Pcte_object_reference    object,  
    Pcte_attribute_reference  attribute,  
    Pcte_attribute_value     *value  
);
```

/* 9.3.17 OBJECT_SET_PREFERENCE */

```
Pcte_error_type Pcte_object_set_preference (  
    Pcte_object_reference    object,  
    Pcte_type_name           type,  
    Pcte_key                 key  
);
```

```

Pcte_error_type Pcte_h_object_set_preference (
    Pcte_object_reference    object,
    Pcte_type_reference      type,
    Pcte_key                 key
);

/*      The effect of not providing the optional parameter type to the abstract      */
/*      operation is achieved by specifying type as NULL. The effect of not      */
/*      providing the optional parameter key to the abstract operation is      */
/*      achieved by specifying key as NULL.                                     */

```

```

/* 9.3.18 OBJECT_SET_SEVERAL_ATTRIBUTES */

```

```

Pcte_error_type Pcte_object_set_several_attributes (
    Pcte_object_reference    object,
    Pcte_attribute_assignments attributes
);

```

```

Pcte_error_type Pcte_h_object_set_several_attributes (
    Pcte_object_reference    object,
    Pcte_h_attribute_assignments attributes
);

```

```

/* 9.3.19 OBJECT_SET_TIME_ATTRIBUTES */

```

```

Pcte_error_type Pcte_object_set_time_attributes (
    Pcte_object_reference    object,
    Pcte_time                last_access,
    Pcte_time                last_modification,
    Pcte_object_scope        scope
);

/*      The effect of not providing the optional parameters last_access or      */
/*      last_modification to the abstract operation is achieved by specifying      */
/*      last_access or last_modification as Pcte_null_time.                     */

```

```

/* 9.3.20 VOLUME_LIST_OBJECTS */

```

```

Pcte_error_type Pcte_volume_list_objects (
    Pcte_object_reference    volume,
    Pcte_type_names          types,
    Pcte_object_references    *objects
);

```

```

Pcte_error_type Pcte_h_volume_list_objects (
    Pcte_object_reference    volume,
    Pcte_type_references     types,
    Pcte_object_references    *objects
);

```

9.4 Version Operations

/* 9.4.1 VERSION_ADD_PREDECESSOR */

```
Pcte_error_type Pcte_version_add_predecessor (
    Pcte_object_reference    version,
    Pcte_object_reference    new_predecessor
);
```

/* 9.4.2 VERSION_IS_CHANGED */

```
Pcte_error_type Pcte_version_is_changed (
    Pcte_object_reference    version,
    Pcte_key                 predecessor,
    Pcte_boolean             *changed
);
```

/* 9.4.3 VERSION_REMOVE */

```
Pcte_error_type Pcte_version_remove (
    Pcte_object_reference    version
);
```

/* 9.4.4 VERSION_REMOVE_PREDECESSOR */

```
Pcte_error_type Pcte_version_remove_predecessor (
    Pcte_object_reference    version,
    Pcte_object_reference    predecessor
);
```

/* 9.4.5 VERSION_REVISE */

```
Pcte_error_type Pcte_version_revise (
    Pcte_object_reference    version,
    Pcte_object_reference    new_origin,
    Pcte_link_name           new_link,
    Pcte_object_reference    on_same_volume_as,
    Pcte_atomic_access_rights *access_mask,
    Pcte_object_reference    *new_version
);
```

```
Pcte_error_type Pcte_h_version_revise (
    Pcte_object_reference    version,
    Pcte_object_reference    new_origin,
    Pcte_link_reference      new_link,
    Pcte_object_reference    on_same_volume_as,
    Pcte_atomic_access_rights *access_mask,
    Pcte_object_reference    *new_version
);
```

```

/*      The effect of not providing the optional parameter on_same_volume_as      */
/*      to the abstract operation is achieved by specifying on_same_volume_as      */
/*      as Pcte_null_object_reference.                                           */

```

```

/* 9.4.6 VERSION_SNAPSHOT */

```

```

Pcte_error_type Pcte_version_snapshot (
    Pcte_object_reference    version,
    Pcte_object_reference    new_origin,
    Pcte_link_name           new_link,
    Pcte_object_reference    on_same_volume_as,
    Pcte_atomic_access_rights *access_mask,
    Pcte_object_reference    *new_version
);

```

```

Pcte_error_type Pcte_h_version_snapshot (
    Pcte_object_reference    version,
    Pcte_object_reference    new_origin,
    Pcte_link_reference       new_link,
    Pcte_object_reference    on_same_volume_as,
    Pcte_atomic_access_rights *access_mask,
    Pcte_object_reference    *new_version
);

```

```

/*      The effect of not providing the optional parameter new_link and origin      */
/*      to the abstract operation is achieved by specifying new_link as NULL      */
/*      and new_origin as Pcte_null_object_reference. The effect of not          */
/*      providing the optional parameter on_same_volume_as to the abstract        */
/*      operation is achieved by specifying on_same_volume_as as                */
/*      Pcte_null_object_reference.                                               */

```

```

/* 9.4.7 VERSION_TEST_ANCESTRY */

```

```

Pcte_error_type Pcte_version_test_ancestry (
    Pcte_object_reference    version1,
    Pcte_object_reference    version2,
    Pcte_version_relation     *ancestry
);

```

```

/* 9.4.8 VERSION_TEST_DESCENT */

```

```

Pcte_error_type Pcte_version_test_descent (
    Pcte_object_reference    version1,
    Pcte_object_reference    version2,
    Pcte_version_relation     *descent
);

```

```
#endif /* !PCTE_OMS_INCLUDED */
```

10 Schema management

```
/* The header <Pcte/sms.h> */
```

```
#ifndef PCTE_SMS_INCLUDED
```

```
#define PCTE_SMS_INCLUDED 1
```

```
#include <Pcte/types.h>
```

```
#include <Pcte/references.h>
```

```
#include <Pcte/sequences.h>
```

```
#include <Pcte/oms.h>
```

10.1 Schema Management Datatypes

```
typedef enum {
```

```
    PCTE_CREATE_MODE      =    1<<0,
```

```
    PCTE_DELETE_MODE      =    1<<1,
```

```
    PCTE_READ_MODE        =    1<<2,
```

```
    PCTE_WRITE_MODE       =    1<<3,
```

```
    PCTE_NAVIGATE_MODE    =    1<<4
```

```
} Pcte_definition_mode_value;
```

```
typedef Pcte_natural Pcte_definition_mode_values;
```

```
typedef enum {
```

```
    PCTE_DUPLICATED, PCTE_NOT_DUPLICATED
```

```
} Pcte_duplication ;
```

```
typedef enum {
```

```
    PCTE_SHARABLE, PCTE_EXCLUSIVE
```

```
} Pcte_exclusiveness;
```

```
typedef enum {
```

```
    PCTE_ATOMIC_STABLE, PCTE_COMPOSITE_STABLE,
```

```
    PCTE_NOT_STABLE
```

```
} Pcte_stability;
```

```
typedef enum {
```

```
    PCTE_NO_CONTENTS, PCTE_FILE_TYPE,
```

```
    PCTE_PIPE_TYPE, PCTE_DEVICE_TYPE,
```

```
    PCTE_AUDIT_FILE_TYPE, PCTE_ACCOUNTING_LOG_TYPE
```

```
} Pcte_contents_type;
```

```
/*      Pcte_contents_type corresponds to the PCTE datatype Contents_type.      */
```

```
/*      The value PCTE_NO_CONTENTS corresponds to absence of a      */
```

```
/*      Contents_type result from SDS_GET_OBJECT_TYPE_PROPERTIES      */
```

```
/*      and WS_GET_OBJECT_TYPE_PROPERTIES.      */
```

```

typedef struct {
    Pcte_category      category;
    Pcte_stability      stability;
    Pcte_exclusiveness  exclusiveness;
    Pcte_duplication    duplication;
} Pcte_link_flags;

typedef struct {
    Pcte_link_flags    link_type_flag;
    Pcte_natural        lower_bound, upper_bound;
} Pcte_link_type_properties;

/*      Pcte_link_type_properties corresponds to a number of parameter types      */
/*      in SDS_CREATE_RELATIONSHIP_TYPE, and to a number of result      */
/*      types      of      SDS_GET_LINK_TYPE_PROPERTIES      and      */
/*      WS_GET_LINK_TYPE_PROPERTIES.      */

typedef enum {
    PCTE_OBJECT, PCTE_OBJECT_ALL,
    PCTE_LINK_KEY, PCTE_LINK_NON_KEY
} Pcte_attribute_scan_kind;

typedef enum {
    PCTE_ORIGIN, PCTE_ORIGIN_ALL,
    PCTE_DESTINATION, PCTE_DESTINATION_ALL,
    PCTE_KEY, PCTE_NON_KEY
} Pcte_link_scan_kind;

typedef enum {
    PCTE_CHILD, PCTE_DESCENDANT,
    PCTE_PARENT, PCTE_ANCESTOR,
    PCTE_ATTRIBUTE, PCTE_ATTRIBUTE_ALL,
    PCTE_LINK_ORIGIN, PCTE_LINK_ORIGIN_ALL,
    PCTE_LINK_DESTINATION, PCTE_LINK_DESTINATION_ALL
} Pcte_object_scan_kind;

typedef enum {
    PCTE_OBJECT_TYPE, PCTE_LINK_TYPE,
    PCTE_ATTRIBUTE_TYPE, PCTE_ENUMERAL_TYPE
} Pcte_type_kind;

#define PCTE_MAX_ENUMERAL_TYPE_IMAGE_SIZE PCTE_MAX_NAME_SIZE

typedef Pcte_octet
Pcte_enumeral_type_image[PCTE_MAX_ENUMERAL_TYPE_IMAGE_SIZE + 1];

```

10.2 Update Operations

/* 10.2.1 SDS_ADD_DESTINATION */

```
Pcte_error_type Pcte_sds_add_destination (
    Pcte_object_reference    sds,
    Pcte_type_name_in_sds   link_type,
    Pcte_type_name_in_sds   object_type
);
```

/* 10.2.2 SDS_APPLY_ATTRIBUTE_TYPE */

```
Pcte_error_type Pcte_sds_apply_attribute_type (
    Pcte_object_reference    sds,
    Pcte_type_name_in_sds   attribute_type,
    Pcte_type_name_in_sds   type
);
```

/* 10.2.3 SDS_APPLY_LINK_TYPE */

```
Pcte_error_type Pcte_sds_apply_link_type (
    Pcte_object_reference    sds,
    Pcte_type_name_in_sds   link_type,
    Pcte_type_name_in_sds   object_type
);
```

/* 10.2.4 SDS_CREATE_BOOLEAN_ATTRIBUTE_TYPE */

```
Pcte_error_type Pcte_sds_create_boolean_attribute_type (
    Pcte_object_reference    sds,
    Pcte_name                local_name,
    Pcte_boolean             initial_value,
    Pcte_duplication          duplication,
    Pcte_type_name_in_sds    new_type
);
```

```
/*      The effect of not providing the optional parameter local_name to the */
/*      abstract operation is achieved by specifying local_name as NULL. The */
/*      effect of not providing the optional parameter initial_value to the */
/*      abstract operation is achieved by specifying initial_value as */
/*      PCTE_FALSE. */
```

/* 10.2.5 SDS_CREATE_DESIGNATION_LINK_TYPE */

Pcte_error_type Pcte_sds_create_designation_link_type (

 Pcte_object_reference object,
 Pcte_name local_name,
 Pcte_natural lower_bound,
 Pcte_natural upper_bound,
 Pcte_duplication duplication,
 Pcte_key_types_in_sds key_types,
 Pcte_type_name_in_sds new_type

);

/* The effect of not providing the optional parameter *local_name* to the */
/* abstract operation is achieved by specifying **local_name** as NULL. The */
/* effect of not providing the optional parameter *upper_bound* to the */
/* abstract operation is achieved by specifying **upper_bound** as 0. */

/* 10.2.6 SDS_CREATE_ENUMERAL_TYPE */

Pcte_error_type Pcte_sds_create_enumeral_type (

 Pcte_object_reference sds,
 Pcte_name local_name,
 Pcte_type_name_in_sds new_type

);

/* The effect of not providing the optional parameter *local_name* to the */
/* abstract operation is achieved by specifying **local_name** as NULL. */

/* 10.2.7 SDS_CREATE_ENUMERATION_ATTRIBUTE_TYPE */

Pcte_error_type Pcte_sds_create_enumeration_attribute_type (

 Pcte_object_reference sds,
 Pcte_name local_name,
 Pcte_type_names_in_sds values,
 Pcte_duplication duplication,
 Pcte_natural initial_value,
 Pcte_type_name_in_sds new_type

);

/* The effect of not providing the optional parameter *local_name* to the */
/* abstract operation is achieved by specifying **local_name** as NULL. The */
/* effect of not providing the optional parameter *initial_value* to the */
/* abstract operation is achieved by specifying **initial_value** as 0. */

/* 10.2.8 SDS_CREATE_FLOAT_ATTRIBUTE_TYPE */

Pcte_error_type Pcte_sds_create_float_attribute_type (

 Pcte_object_reference sds,
 Pcte_name local_name,
 Pcte_float initial_value,
 Pcte_duplication duplication,
 Pcte_type_name_in_sds new_type

);

/* The effect of not providing the optional parameter *local_name* to the */
/* abstract operation is achieved by specifying **local_name** as NULL. The */
/* effect of not providing the optional parameter *initial_value* to the */
/* abstract operation is achieved by specifying **initial_value** as 0.0. */

/* 10.2.9 SDS_CREATE_INTEGER_ATTRIBUTE_TYPE */

Pcte_error_type Pcte_sds_create_integer_attribute_type (

 Pcte_object_reference sds,
 Pcte_name local_name,
 Pcte_integer initial_value,
 Pcte_duplication duplication,
 Pcte_type_name_in_sds new_type

);

/* The effect of not providing the optional parameter *local_name* to the */
/* abstract operation is achieved by specifying **local_name** as NULL. The */
/* effect of not providing the optional parameter *initial_value* to the */
/* abstract operation is achieved by specifying **initial_value** as 0. */

/* 10.2.10 SDS_CREATE_NATURAL_ATTRIBUTE_TYPE */

Pcte_error_type Pcte_sds_create_natural_attribute_type (

 Pcte_object_reference sds,
 Pcte_name local_name,
 Pcte_natural initial_value,
 Pcte_duplication duplication,
 Pcte_type_name_in_sds new_type

);

/* The effect of not providing the optional parameter *local_name* to the */
/* abstract operation is achieved by specifying **local_name** as NULL. The */
/* effect of not providing the optional parameter *initial_value* to the */
/* abstract operation is achieved by specifying **initial_value** as 0. */

/* 10.2.11 SDS_CREATE_OBJECT_TYPE */

```
Pcte_error_type Pcte_sds_create_object_type (
    Pcte_object_reference    sds,
    Pcte_name                local_name,
    Pcte_type_names_in_sds  parents,
    Pcte_type_name_in_sds   new_type
);
```

/* The effect of not providing the optional parameter *local_name* to the */
 /* abstract operation is achieved by specifying **local_name** as NULL. */
 /* */

/* 10.2.12 SDS_CREATE_RELATIONSHIP_TYPE */

```
Pcte_error_type Pcte_sds_create_relationship_type (
    Pcte_object_reference    sds,
    Pcte_name                forward_local_name,
    Pcte_link_type_properties *forward_properties,
    Pcte_key_types_in_sds    forward_key_types,
    Pcte_name                reverse_local_name,
    Pcte_link_type_properties *reverse_properties,
    Pcte_key_types_in_sds    reverse_key_types,
    Pcte_type_name_in_sds    forward_type,
    Pcte_type_name_in_sds    reverse_type
);
```

/* The effect of not providing the optional parameter *forward_local_name* */
 /* to the abstract operation is achieved by specifying **forward_local_name** */
 /* as NULL. The effect of not providing the optional parameter */
 /* *reverse_local_name* to the abstract operation is achieved by specifying */
 /* **reverse_local_name** as NULL. The effect of not providing the optional */
 /* parameter *forward_upper_bound* to the abstract operation is achieved by */
 /* specifying **forward_properties.upper_bound** as 0. The effect of not */
 /* providing the optional parameter *reverse_upper_bound* to the abstract */
 /* operation is achieved by specifying **reverse_properties.upper_bound** */
 /* as 0. */

/* 10.2.13 SDS_CREATE_STRING_ATTRIBUTE_TYPE */

```
Pcte_error_type Pcte_sds_create_string_attribute_type (
    Pcte_object_reference    sds,
    Pcte_name                local_name,
    Pcte_string              *initial_value,
    Pcte_duplication          duplication,
    Pcte_type_name_in_sds    new_type
);
```

```

/*      The effect of not providing the optional parameter local_name to the      */
/*      abstract operation is achieved by specifying local_name as NULL. The      */
/*      effect of not providing the optional parameter initial_value to the      */
/*      abstract operation is achieved by specifying initial_value as NULL.      */

```

```

/* 10.2.14 SDS_CREATE_TIME_ATTRIBUTE_TYPE */

```

```

Pcte_error_type Pcte_sds_create_time_attribute_type (
    Pcte_object_reference    sds,
    Pcte_name                local_name,
    Pcte_time                initial_value,
    Pcte_duplication         duplication,
    Pcte_type_name_in_sds    new_type
);

```

```

/*      The effect of not providing the optional parameter local_name to the      */
/*      abstract operation is achieved by specifying local_name as NULL. The      */
/*      effect of not providing the optional parameter initial_value to the      */
/*      abstract operation is achieved by specifying initial_value as          */
/*      Pcte_reference_time.                                                       */

```

```

/* 10.2.15 SDS_IMPORT_ATTRIBUTE_TYPE */

```

```

Pcte_error_type Pcte_sds_import_attribute_type (
    Pcte_object_reference    to_sds,
    Pcte_object_reference    from_sds,
    Pcte_type_name_in_sds    type,
    Pcte_name                local_name
);

```

```

/*      The effect of not providing the optional parameter local_name to the      */
/*      abstract operation is achieved by specifying local_name as NULL.          */

```

```

/* 10.2.16 SDS_GET_NAME */

```

```

Pcte_error_type Pcte_sds_get_name (
    Pcte_object_reference    sds,
    Pcte_name                name
);

```

```

/* 10.2.17 SDS_IMPORT_ENUMERAL_TYPE */

```

```

Pcte_error_type Pcte_sds_import_enumeral_type (
    Pcte_object_reference    to_sds,
    Pcte_object_reference    from_sds,
    Pcte_type_name_in_sds    type,
    Pcte_name                local_name
);

```

```

/*      The effect of not providing the optional parameter local_name to the      */
/*      abstract operation is achieved by specifying local_name as NULL.          */

```

/* 10.2.18 SDS_IMPORT_LINK_TYPE */

```
Pcte_error_type Pcte_sds_import_link_type (
    Pcte_object_reference    to_sds,
    Pcte_object_reference    from_sds,
    Pcte_type_name_in_sds    type,
    Pcte_name                local_name
);
```

/* The effect of not providing the optional parameter *local_name* to the */
 /* abstract operation is achieved by specifying **local_name** as NULL. */

/* 10.2.19 SDS_IMPORT_OBJECT_TYPE */

```
Pcte_error_type Pcte_sds_import_object_type (
    Pcte_object_reference    to_sds,
    Pcte_object_reference    from_sds,
    Pcte_type_name_in_sds    type,
    Pcte_name                local_name
);
```

/* The effect of not providing the optional parameter *local_name* to the */
 /* abstract operation is achieved by specifying **local_name** as NULL. */

/* 10.2.20 SDS_INITIALIZE */

```
Pcte_error_type Pcte_sds_initialize (
    Pcte_object_reference    sds,
    Pcte_name                name
);
```

/* 10.2.21 SDS_REMOVE */

```
Pcte_error_type Pcte_sds_remove (
    Pcte_object_reference    sds
);
```

/* 10.2.22 SDS_REMOVE_DESTINATION */

```
Pcte_error_type Pcte_sds_remove_destination (
    Pcte_object_reference    sds,
    Pcte_type_name_in_sds    link_type,
    Pcte_type_name_in_sds    object_type
);
```

/* 10.2.23 SDS_REMOVE_TYPE */

```
Pcte_error_type Pcte_sds_remove_type (
    Pcte_object_reference    sds,
    Pcte_type_name_in_sds    type
);
```

/* 10.2.24 SDS_SET_ENUMERAL_TYPE_IMAGE */

```
Pcte_error_type Pcte_sds_set_enumeral_type_image (
    Pcte_object_reference    sds,
    Pcte_type_name_in_sds   type,
    Pcte_enumeral_type_image image
);
```

/* The effect of not providing the optional parameter *image* to the abstract */
 /* operation is achieved by specifying **image** as NULL. */

/* 10.2.25 SDS_SET_TYPE_MODES */

```
Pcte_error_type Pcte_sds_set_usage_mode (
    Pcte_object_reference    sds,
    Pcte_type_name_in_sds   type,
    Pcte_definition_mode_values usage_mode
);
```

```
Pcte_error_type Pcte_sds_set_export_mode (
    Pcte_object_reference    sds,
    Pcte_type_name_in_sds   type,
    Pcte_definition_mode_values export_mode
);
```

/* The effect of not providing the optional parameter *export_mode* is */
 /* obtained by calling Pcte_sds_set_usage_mode. The effect of not */
 /* providing the optional parameter *usage_mode* is obtained by calling */
 /* Pcte_sds_set_export_mode. The effect of providing both optional */
 /* parameters *usage_mode* and *export_mode* is obtained by calling */
 /* Pcte_sds_set_usage_mode and Pcte_sds_set_export_mode in sequence. */
 /* As an operation call with neither optional parameter has no effect, no */
 /* means for making such a call is provided. */

/* 10.2.26 SDS_SET_TYPE_NAME */

```
Pcte_error_type Pcte_sds_set_type_name (
    Pcte_object_reference    sds,
    Pcte_type_name_in_sds   type,
    Pcte_name                local_name
);
```

/* The effect of not providing the optional parameter *local_name* to the */
 /* abstract operation is achieved by specifying **local_name** as NULL. */

/* 10.2.27 SDS_UNAPPLY_ATTRIBUTE_TYPE */

```
Pcte_error_type Pcte_sds_unapply_attribute_type (
    Pcte_object_reference    sds,
    Pcte_type_name_in_sds   attribute_type,
    Pcte_type_name_in_sds   type
);
```

```
/* 10.2.28 SDS_UNAPPLY_LINK_TYPE */
```

```
Pcte_error_type Pcte_sds_unapply_link_type (  
    Pcte_object_reference    sds,  
    Pcte_type_name_in_sds    link_type,  
    Pcte_type_name_in_sds    object_type  
);
```

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 13719-2:1995

10.3 Usage Operations

/* 10.3.1 SDS_GET_ATTRIBUTE_TYPE_PROPERTIES */

```
Pcte_error_type Pcte_sds_get_attribute_type_properties (
    Pcte_object_reference      sds,
    Pcte_type_name_in_sds     type,
    Pcte_duplication           *duplication,
    Pcte_value_type            *value_type,
    Pcte_enumeration_value_type_in_sds *enumeration_value_type,
    Pcte_attribute_value       *initial_value
);
```

/* If the abstract operation returns an enumeration value type in *value_type* */
 /* then **value_type** is set to PCTE_ENUMERATION_VALUE_TYPE and */
 /* **enumeration_value_type** contains the sequence of enumeration value */
 /* type nominators. */

/* 10.3.2 SDS_GET_ENUMERAL_TYPE_IMAGE */

```
Pcte_error_type Pcte_sds_get_enumeral_type_image (
    Pcte_object_reference      sds,
    Pcte_type_name_in_sds     enumeral_type,
    Pcte_enumeral_type_image  image
);
```

/* If the abstract operation returns no value in *image*, **image** is returned as */
 /* a string of zero length. */

/* 10.3.3 SDS_GET_ENUMERAL_TYPE_POSITION */

```
Pcte_error_type Pcte_sds_get_enumeral_type_position (
    Pcte_object_reference      sds,
    Pcte_type_name_in_sds     enumeral_type,
    Pcte_type_name_in_sds     attribute_type,
    Pcte_natural               *position
);
```

/* 10.3.4 SDS_GET_LINK_TYPE_PROPERTIES */

```
Pcte_error_type Pcte_sds_get_link_type_properties (
    Pcte_object_reference      sds,
    Pcte_type_name_in_sds     type,
    Pcte_link_type_properties  *properties,
    Pcte_key_types_in_sds     *key_types,
    Pcte_type_name_in_sds     reverse
);
```

```

/* The category, lower_bound, upper_bound, exclusiveness, stability, */
/* duplication, key_types and reverse values are returned in the members */
/* of the same names of the Pcte_link_type_properties object pointed to */
/* by properties. If the abstract operation returns no value in reverse, */
/* reverse is set to a string of zero length. */

```

```

/* 10.3.5 SDS_GET_OBJECT_TYPE_PROPERTIES */

```

```

Pcte_error_type Pcte_sds_get_object_type_properties (
    Pcte_object_reference sds,
    Pcte_type_name_in_sds type,
    Pcte_contents_type *contents_type,
    Pcte_type_names_in_sds *parents,
    Pcte_type_names_in_sds *children
);

```

```

/* If the abstract operation returns no value in contents_type then */
/* contents_type is set to PCTE_NO_CONTENTS. */

```

```

/* 10.3.6 SDS_GET_TYPE_KIND */

```

```

Pcte_error_type Pcte_sds_get_type_kind (
    Pcte_object_reference sds,
    Pcte_type_name_in_sds type,
    Pcte_type_kind *type_kind
);

```

```

/* 10.3.7 SDS_GET_TYPE_MODES */

```

```

Pcte_error_type Pcte_sds_get_type_modes (
    Pcte_object_reference sds,
    Pcte_type_name_in_sds type,
    Pcte_definition_mode_values *usage_mode,
    Pcte_definition_mode_values *export_mode,
    Pcte_definition_mode_values *max_usage_mode
);

```

```

/* 10.3.8 SDS_GET_TYPE_NAME */

```

```

Pcte_error_type Pcte_sds_get_type_name (
    Pcte_object_reference sds,
    Pcte_type_name_in_sds type,
    Pcte_type_name name
);

```

```

/* If the abstract operation returns no value in name, name is returned as a */
/* string of zero length. */

```

/* 10.3.9 SDS_SCAN_ATTRIBUTE_TYPE */

```
Pcte_error_type Pcte_sds_scan_attribute_type (
    Pcte_object_reference    sds,
    Pcte_type_name_in_sds   type,
    Pcte_attribute_scan_kind scanning_kind,
    Pcte_type_names_in_sds  *types
);
```

/* 10.3.10 SDS_SCAN_ENUMERAL_TYPE */

```
Pcte_error_type Pcte_sds_scan_enumeral_type (
    Pcte_object_reference    sds,
    Pcte_type_name_in_sds   type,
    Pcte_type_names_in_sds  *types
);
```

/* 10.3.11 SDS_SCAN_LINK_TYPE */

```
Pcte_error_type Pcte_sds_scan_link_type (
    Pcte_object_reference    sds,
    Pcte_type_name_in_sds   type,
    Pcte_link_scan_kind     scanning_kind,
    Pcte_type_names_in_sds  *types
);
```

/* 10.3.12 SDS_SCAN_OBJECT_TYPE */

```
Pcte_error_type Pcte_sds_scan_object_type (
    Pcte_object_reference    sds,
    Pcte_type_name_in_sds   type,
    Pcte_object_scan_kind   scanning_kind,
    Pcte_type_names_in_sds  *types
);
```

/* 10.3.13 SDS_SCAN_TYPES */

```
Pcte_error_type Pcte_sds_scan_types (
    Pcte_object_reference    sds,
    Pcte_type_kind           kind,
    Pcte_type_names_in_sds  *types
);
```

```
Pcte_error_type Pcte_sds_scan_all_types (
    Pcte_object_reference    sds,
    Pcte_type_names_in_sds  *types
);
```

```
/*      The effect of not providing the optional parameter kind to the abstract      */
/*      operation is achieved by the operation Pcte_sds_scan_all_types.                */
```

10.4 Working Schema Operations

/* 10.4.1 WS_GET_ATTRIBUTE_TYPE_PROPERTIES */

```
Pcte_error_type Pcte_ws_get_attribute_type_properties (
    Pcte_type_name          type,
    Pcte_duplication        *duplication,
    Pcte_value_type         *value_type,
    Pcte_enumeration_value_type *enumeration_value_type,
    Pcte_attribute_value     *initial_value
);
```

```
Pcte_error_type Pcte_h_ws_get_attribute_type_properties (
    Pcte_type_reference      type,
    Pcte_duplication        *duplication,
    Pcte_value_type         *value_type,
    Pcte_h_enumeration_value_type *enumeration_value_type,
    Pcte_attribute_value     *initial_value
);
```

/* 10.4.2 WS_GET_ENUMERAL_TYPE_IMAGE */

```
Pcte_error_type Pcte_ws_get_enumeral_type_image (
    Pcte_type_name          enumeral_type,
    Pcte_enumeral_type_image image
);
```

```
Pcte_error_type Pcte_h_ws_get_enumeral_type_image (
    Pcte_type_reference      enumeral_type,
    Pcte_enumeral_type_image image
);
```

/* If the abstract operation returns no value in *image*, **image** is returned as */
 /* a string of zero length. */

/* 10.4.3 WS_GET_ENUMERAL_TYPE_POSITION */

```
Pcte_error_type Pcte_ws_get_enumeral_type_position (
    Pcte_type_name          enumeral_type,
    Pcte_type_name          attribute_type,
    Pcte_natural            *position
);
```

```
Pcte_error_type Pcte_h_ws_get_enumeral_type_position (
    Pcte_type_reference      enumeral_type,
    Pcte_type_reference      attribute_type,
    Pcte_natural            *position
);
```

/* 10.4.4 WS_GET_LINK_TYPE_PROPERTIES */

```
Pcte_error_type Pcte_ws_get_link_type_properties (
    Pcte_type_name      type,
    Pcte_link_type_properties *properties,
    Pcte_key_types      *key_types,
    Pcte_type_name      reverse
);
```

```
Pcte_error_type Pcte_h_ws_get_link_type_properties (
    Pcte_type_reference  type,
    Pcte_link_type_properties *properties,
    Pcte_h_key_types     *key_types,
    Pcte_type_reference  *reverse
);
```

/* If the abstract operation returns no value in *reverse*, **reverse** is returned */
 /* as a string of zero length for Pcte_ws_get_link_type_properties and as */
 /* NULL for Pcte_h_ws_get_link_type_properties. */

/* 10.4.5 WS_GET_OBJECT_TYPE_PROPERTIES */

```
Pcte_error_type Pcte_ws_get_object_type_properties (
    Pcte_type_name      type,
    Pcte_contents_type  *contents_type,
    Pcte_type_names     *parents,
    Pcte_type_names     *children
);
```

```
Pcte_error_type Pcte_h_ws_get_object_type_properties (
    Pcte_type_reference  type,
    Pcte_contents_type  *contents_type,
    Pcte_type_references *parents,
    Pcte_type_references *children
);
```

/* If the abstract operation returns no value in *contents_type* then */
 /* **contents_type** is set to PCTE_NO_CONTENTS. */

/* 10.4.6 WS_GET_TYPE_KIND */

```
Pcte_error_type Pcte_ws_get_type_kind (
    Pcte_type_name      type,
    Pcte_type_kind      *type_kind
);
```

```
Pcte_error_type Pcte_h_ws_get_type_kind (
    Pcte_type_reference  type,
    Pcte_type_kind      *type_kind
);
```

```
/* 10.4.7 WS_GET_TYPE_MODES */
```

```
Pcte_error_type Pcte_ws_get_type_modes (
    Pcte_type_name      type,
    Pcte_definition_mode_values *usage_modes
);
```

```
Pcte_error_type Pcte_h_ws_get_type_modes (
    Pcte_type_reference  type,
    Pcte_definition_mode_values *usage_modes
);
```

```
/* 10.4.8 WS_GET_TYPE_NAME */
```

```
Pcte_error_type Pcte_ws_get_type_name (
    Pcte_type_name      type,
    Pcte_type_name      name
);
```

```
Pcte_error_type Pcte_h_ws_get_type_name (
    Pcte_type_reference  type,
    Pcte_type_name      name
);
```

```
/*      If the abstract operation returns no value in name, name is returned as a      */
/*      string of zero length.                                                         */
```

```
/* 10.4.9 WS_SCAN_ATTRIBUTE_TYPE */
```

```
Pcte_error_type Pcte_ws_scan_attribute_type (
    Pcte_type_name      type,
    Pcte_attribute_scan_kind scanning_kind,
    Pcte_type_names     *types
);
```

```
Pcte_error_type Pcte_h_ws_scan_attribute_type (
    Pcte_type_reference  type,
    Pcte_attribute_scan_kind scanning_kind,
    Pcte_type_references *types
);
```

```
/* 10.4.10 WS_SCAN_ENUMERAL_TYPE */
```

```
Pcte_error_type Pcte_ws_scan_enumeral_type (
    Pcte_type_name      type,
    Pcte_type_names     *types
);
```

```
Pcte_error_type Pcte_h_ws_scan_enumeral_type (
    Pcte_type_reference  type,
    Pcte_type_references *types
);
```

```
/* 10.4.11 WS_SCAN_LINK_TYPE */
```

```
Pcte_error_type Pcte_ws_scan_link_type (  
    Pcte_type_name      type,  
    Pcte_link_scan_kind scanning_kind,  
    Pcte_type_names     *types  
);
```

```
Pcte_error_type Pcte_h_ws_scan_link_type (  
    Pcte_type_reference  type,  
    Pcte_link_scan_kind  scanning_kind,  
    Pcte_type_references *types  
);
```

```
/* 10.4.12 WS_SCAN_OBJECT_TYPE */
```

```
Pcte_error_type Pcte_ws_scan_object_type (  
    Pcte_type_name      type,  
    Pcte_object_scan_kind scanning_kind,  
    Pcte_type_names     *types  
);
```

```
Pcte_error_type Pcte_h_ws_scan_object_type (  
    Pcte_type_reference  type,  
    Pcte_object_scan_kind scanning_kind,  
    Pcte_type_references *types  
);
```

```
/* 10.4.13 WS_SCAN_TYPES */
```

```
Pcte_error_type Pcte_ws_scan_types (  
    Pcte_type_kind  kind,  
    Pcte_type_names *types  
);
```

```
Pcte_error_type Pcte_h_ws_scan_types (  
    Pcte_type_kind  kind,  
    Pcte_type_references *types  
);
```

```
Pcte_error_type Pcte_ws_scan_all_types (  
    Pcte_type_names *types  
);
```

```
Pcte_error_type Pcte_h_ws_scan_all_types (  
    Pcte_type_references *types  
);
```

```
#endif /* !PCTE_SMS_INCLUDED */
```

11 Volumes, devices and archives

```
/* The header <Pcte/devices.h> */

#ifndef PCTE_DEVICES_INCLUDED
#define PCTE_DEVICES_INCLUDED 1

#include <Pcte/types.h>
#include <Pcte/references.h>
#include <Pcte/sequences.h>
```

11.1 Volume, Device, and Archive Datatypes

```
typedef Pcte_natural Pcte_volume_identifier;

typedef struct {
    Pcte_natural    total_blocks;
    Pcte_natural    free_blocks;
    Pcte_natural    block_size;
    Pcte_natural    num_objects;
    Pcte_volume_identifier volume_identifier;
} Pcte_volume_status;

typedef Pcte_natural Pcte_device_identifier;

typedef enum {
    PCTE_PARTIAL, PCTE_COMPLETE
} Pcte_archive_status;

typedef Pcte_natural Pcte_archive_identifier;

#include <Pcte/discretionary.h>
```

11.2 Volume, Device and Archive Operations

```
/* 11.2.1 ARCHIVE_CREATE */

Pcte_error_type Pcte_archive_create (
    Pcte_natural    archive_identifier,
    Pcte_object_reference on_same_volume_as,
    Pcte_atomic_access_rights *access_mask,
    Pcte_object_reference *new_archive
);

/* 11.2.2 ARCHIVE_REMOVE */

Pcte_error_type Pcte_archive_remove (
    Pcte_object_reference archive
);
```

/* 11.2.3 ARCHIVE_RESTORE */

```
Pcte_error_type Pcte_archive_restore (
    Pcte_object_reference device,
    Pcte_object_reference archive,
    Pcte_object_references objects,
    Pcte_object_reference on_same_volume_as,
    Pcte_archive_status *restoring_status
);
```

```
Pcte_error_type Pcte_archive_restore_all (
    Pcte_object_reference device,
    Pcte_object_reference archive,
    Pcte_object_reference on_same_volume_as,
    Pcte_archive_status *restoring_status
);
```

```
/* The effect of specifying scope as a set of object designator to the */
/* abstract operation is achieved by the operation Pcte_archive_restore. The */
/* effect of specifying scope as ALL to the abstract operation is achieved */
/* by the operation Pcte_archive_restore_all. */
```

/* 11.2.4 ARCHIVE_SAVE */

```
Pcte_error_type Pcte_archive_save (
    Pcte_object_reference device,
    Pcte_object_reference archive,
    Pcte_object_references objects,
    Pcte_archive_status *archiving_status
);
```

/* 11.2.5 DEVICE_CREATE */

```
Pcte_error_type Pcte_device_create (
    Pcte_object_reference station,
    Pcte_type_name device_type,
    Pcte_atomic_access_rights *access_mask,
    Pcte_natural device_identifier,
    Pcte_string *device_characteristics,
    Pcte_object_reference *new_device
);
```

```
Pcte_error_type Pcte_h_device_create (
    Pcte_object_reference station,
    Pcte_type_reference device_type,
    Pcte_atomic_access_rights *access_mask,
    Pcte_natural device_identifier,
    Pcte_string *device_characteristics,
    Pcte_object_reference *new_device
);
```

/* 11.2.6 DEVICE_REMOVE */

```
Pcte_error_type Pcte_device_remove (  
    Pcte_object_reference    device  
);
```

/* 11.2.7 LINK_GET_DESTINATION_ARCHIVE */

```
Pcte_error_type Pcte_link_get_destination_archive (  
    Pcte_object_reference    origin,  
    Pcte_link_name          link,  
    Pcte_archive_identifier  *archive_identifier  
);
```

```
Pcte_error_type Pcte_h_link_get_destination_archive (  
    Pcte_object_reference    origin,  
    Pcte_link_reference      link,  
    Pcte_archive_identifier  *archive_identifier  
);
```

/* 11.2.8 VOLUME_CREATE */

```
Pcte_error_type Pcte_volume_create (  
    Pcte_object_reference    device,  
    Pcte_natural             volume_id,  
    Pcte_atomic_access_rights *access_mask,  
    Pcte_string              *volume_characteristics,  
    Pcte_object_reference    *new_volume  
);
```

/* 11.2.9 VOLUME_DELETE */

```
Pcte_error_type Pcte_volume_delete (  
    Pcte_object_reference    volume  
);
```

/* 11.2.10 VOLUME_GET_STATUS */

```
Pcte_error_type Pcte_volume_get_status (  
    Pcte_object_reference    volume,  
    Pcte_volume_status       *volume_status  
);
```

/* 11.2.11 VOLUME_MOUNT */

```
Pcte_error_type Pcte_volume_mount (  
    Pcte_object_reference    device,  
    Pcte_volume_identifier   volume_identifier,  
    Pcte_boolean             read_only  
);
```

```

/* 11.2.12 VOLUME_UNMOUNT */
Pcte_error_type Pcte_volume_unmount (
    Pcte_object_reference    volume
);
#endif /* !PCTE_DEVICES_INCLUDED */

```

12 Files, pipes and devices

```

/* The header <Pcte/contents.h> */
#ifndef PCTE_CONTENTS_INCLUDED
#define PCTE_CONTENTS_INCLUDED 1
#include <Pcte/types.h>
#include <Pcte/references.h>

```

12.1 File, Pipe and Device Datatypes

```

typedef void *Pcte_position_handle;

typedef enum {
    PCTE_READ_WRITE, PCTE_READ_ONLY,
    PCTE_WRITE_ONLY, PCTE_APPEND_ONLY
} Pcte_contents_access_mode;

typedef enum {
    PCTE_FROM_BEGINNING, PCTE_FROM_CURRENT, PCTE_FROM_END
} Pcte_seek_position;

typedef enum {
    PCTE_AT_BEGINNING, PCTE_AT_POSITION, PCTE_AT_END
} Pcte_set_position;

typedef void *Pcte_contents_handle;

typedef enum {
    PCTE_SEQUENTIAL, PCTE_DIRECT, PCTE_SEEK
} Pcte_positioning_style;

```

12.2 File, Pipe and Device Operations

```

/* 12.2.1 CONTENTS_CLOSE */
Pcte_error_type Pcte_contents_close (
    Pcte_contents_handle    contents
);

```

/* 12.2.2 CONTENTS_GET_HANDLE_FROM_KEY */

```
Pcte_error_type Pcte_contents_get_handle_from_key (
    Pcte_natural      open_object_key,
    Pcte_contents_handle *contents
);
```

/* 12.2.3 CONTENTS_GET_KEY_FROM_HANDLE */

```
Pcte_error_type Pcte_contents_get_key_from_handle (
    Pcte_contents_handle contents,
    Pcte_natural      *open_object_key
);
```

/* 12.2.4 CONTENTS_GET_POSITION */

```
Pcte_error_type Pcte_contents_get_position (
    Pcte_contents_handle contents,
    Pcte_position_handle *position
);
```

/* 12.2.5 CONTENTS_HANDLE_DUPLICATE */

```
Pcte_error_type Pcte_contents_handle_duplicate (
    Pcte_contents_handle contents,
    Pcte_boolean      inheritable,
    Pcte_contents_handle *new_contents
);
```

```
Pcte_error_type Pcte_contents_handle_duplicate_to_key (
    Pcte_contents_handle contents,
    Pcte_natural      new_key,
    Pcte_boolean      inheritable,
    Pcte_contents_handle *new_contents
);
```

```
/* The effect of not providing the optional parameter new_key to the */
/* abstract operation is achieved by the operation */
/* Pcte_contents_handle_duplicate. */
```

/* 12.2.6 CONTENTS_OPEN */

```
Pcte_error_type Pcte_contents_open (
    Pcte_object_reference object,
    Pcte_contents_access_mode opening_mode,
    Pcte_boolean      non_blocking_io,
    Pcte_boolean      inheritable,
    Pcte_contents_handle *contents
);
```

/* 12.2.7 CONTENTS_READ */

```
Pcte_error_type Pcte_contents_read (
    Pcte_contents_handle  contents,
    Pcte_natural          size,
    Pcte_octet            *data,
    Pcte_natural          *data_size
);
```

/* In *data* the read octets are returned and in *data_size* the number of read octets is returned. If there is not enough space in *data*, the error PCTE_STRING_TOO_SHORT is raised. */

/* 12.2.8 CONTENTS_SEEK */

```
Pcte_error_type Pcte_contents_seek (
    Pcte_contents_handle  contents,
    Pcte_integer          offset,
    Pcte_seek_position    whence,
    Pcte_natural          *new_position
);
```

/* 12.2.9 CONTENTS_SET_POSITION */

```
Pcte_error_type Pcte_contents_set_position (
    Pcte_contents_handle  contents,
    Pcte_position_handle  position_handle,
    Pcte_set_position     set_mode
);
```

/* 12.2.10 CONTENTS_SET_PROPERTIES */

```
Pcte_error_type Pcte_contents_set_properties (
    Pcte_contents_handle  contents,
    Pcte_positioning_style positioning
);
```

/* 12.2.11 CONTENTS_TRUNCATE */

```
Pcte_error_type Pcte_contents_truncate (
    Pcte_contents_handle  contents
);
```

/* 12.2.12 CONTENTS_WRITE */

```
Pcte_error_type Pcte_contents_write (
    Pcte_contents_handle  contents,
    Pcte_octet            *data,
    Pcte_natural          data_size,
    Pcte_natural          *actual_size
);
```

```

/*      In data the octets to be written have to be provided and in data_size the
/*      number of octets to be written has to be provided. If data_size is bigger
/*      than the number of octets allocated in data, the error
/*      PCTE_ACCESS_AT_INVALID_ADDRESS is raised.
*/

```

```

/* 12.2.13 DEVICE_GET_CONTROL */

```

```

Pcte_error_type Pcte_device_get_control (
    Pcte_contents_handle contents,
    Pcte_natural operation,
    Pcte_string *control_data
);

```

```

/* 12.2.14 DEVICE_SET_CONTROL */

```

```

Pcte_error_type Pcte_device_set_control (
    Pcte_contents_handle contents,
    Pcte_natural operation,
    Pcte_string *control_data
);

```

```

Pcte_error_type Pcte_position_handle_discard (
    Pcte_position_handle *position_handle
);

```

```

/*      Pcte_position_handle_discard discards position handles created by
/*      Pcte_contents_get_position.
*/

```

```

/*      Pcte_contents_handle does not correspond to an ISO/IEC 13719-1
/*      contents handle but rather references to it.
*/

```

```

#endif /* !PCTE_CONTENTS_INCLUDED */

```

13 Process execution

```

/* The header <Pcte/execution.h> */

```

```

#ifndef PCTE_EXECUTION_INCLUDED
#define PCTE_EXECUTION_INCLUDED 1

```

```

#include <Pcte/types.h>
#include <Pcte/references.h>
#include <Pcte/sequences.h>
#include <Pcte/discretionary.h>

```

13.1 Process Execution Datatypes

```

typedef <implementation-defined> Pcte_address;

```

```

/*      Pcte_address corresponds to the PCTE datatype Address which must be      */
/*      defined for each implementation.                                          */

```

```

typedef enum {
    PCTE_SUSPENDED, PCTE_RUNNING, PCTE_STOPPED
} Pcte_initial_status;

```

```

#define PCTE_EXIT_SUCCESS          <implementation-defined>
#define PCTE_EXIT_ERROR           <implementation-defined>
#define PCTE_SYSTEM_FAILURE       <implementation-defined>
#define PCTE_ACTIVITY_ABORTED     <implementation-defined>
#define PCTE_UNAVAILABLE          <implementation-defined>
#define PCTE_NULL_TERMINATION     <implementation-defined>

```

```

/*      An implementation may provide further values for the termination status  */
/*      of a process by extending this list of values.                          */

```

```

typedef void *Pcte_profile_handle;

#include <Pcte/mandatory.h>

```

13.2 Process Execution Operations

```

/* 13.2.1 PROCESS_CREATE */

```

```

Pcte_error_type Pcte_process_create (
    Pcte_object_reference    static_context,
    Pcte_type_name           process_type,
    Pcte_object_reference    parent,
    Pcte_object_reference    site,
    Pcte_boolean             implicit_deletion,
    Pcte_atomic_access_rights *access_mask,
    Pcte_object_reference    *new_process
);

```

```

Pcte_error_type Pcte_h_process_create (
    Pcte_object_reference    static_context,
    Pcte_type_reference      process_type,
    Pcte_object_reference    parent,
    Pcte_object_reference    site,
    Pcte_boolean             implicit_deletion,
    Pcte_atomic_access_rights *access_mask,
    Pcte_object_reference    *new_process
);

```

```

/*      The effect of not providing the optional parameter parent to the abstract      */
/*      operation is achieved by specifying parent as                                */
/*      Pcte_null_object_reference. The effect of not providing the optional          */
/*      parameter site to the abstract operation is achieved by specifying site as    */
/*      Pcte_null_object_reference.                                                  */

```

```

/* 13.2.2 PROCESS_CREATE_AND_START */

```

```

Pcte_error_type Pcte_process_create_and_start (
    Pcte_object_reference    static_context,
    Pcte_string              *arguments,
    Pcte_string              *environment,
    Pcte_object_reference    site,
    Pcte_boolean             implicit_deletion,
    Pcte_atomic_access_rights *access_mask,
    Pcte_object_reference    *new_process
);

```

```

/*      The effect of not providing the optional parameter site to the abstract      */
/*      operation is achieved by specifying site as Pcte_null_object_reference.      */

```

```

/* 13.2.3 PROCESS_GET_WORKING_SCHEMA */

```

```

Pcte_error_type Pcte_process_get_working_schema(
    Pcte_object_reference    process,
    Pcte_name_sequence       *sds_sequence
);

```

```

/*      The effect of not providing the optional parameter process to the          */
/*      abstract operation is achieved by specifying process as                      */
/*      Pcte_null_object_reference.                                                  */

```

```

/* 13.2.4 PROCESS_INTERRUPT_OPERATION */

```

```

Pcte_error_type Pcte_process_interrupt_operation (
    Pcte_object_reference    process
);

```

```

/* 13.2.5 PROCESS_RESUME */

```

```

Pcte_error_type Pcte_process_resume (
    Pcte_object_reference    process
);

```

```

/* 13.2.6 PROCESS_SET_ALARM */

```

```

Pcte_error_type Pcte_process_set_alarm (
    Pcte_natural    duration
);

```

/* 13.2.7 PROCESS_SET_FILE_SIZE_LIMIT */

```
Pcte_error_type Pcte_process_set_file_size_limit (
    Pcte_object_reference process,
    Pcte_natural          fslimit
);
```

/* The effect of not providing the optional parameter *process* to the */
 /* abstract operation is achieved by specifying **process** as */
 /* Pcte_null_object_reference. */

/* 13.2.8 PROCESS_SET_OPERATION_TIME_OUT */

```
Pcte_error_type Pcte_process_set_operation_time_out (
    Pcte_natural duration
);
```

/* 13.2.9 PROCESS_SET_PRIORITY */

```
Pcte_error_type Pcte_process_set_priority (
    Pcte_object_reference process,
    Pcte_natural          priority
);
```

/* The effect of not providing the optional parameter *process* to the */
 /* abstract operation is achieved by specifying **process** as */
 /* Pcte_null_object_reference. */

/* 13.2.10 PROCESS_SET_REFERENCED_OBJECT */

```
Pcte_error_type Pcte_process_set_referenced_object (
    Pcte_object_reference process,
    Pcte_key              reference_name,
    Pcte_object_reference object
);
```

/* The effect of not providing the optional parameter *process* to the */
 /* abstract operation is achieved by specifying **process** as */
 /* Pcte_null_object_reference. */

/* 13.2.11 PROCESS_SET_TERMINATION_STATUS */

```
Pcte_error_type Pcte_process_set_termination_status (
    Pcte_integer termination_status
);
```

/* 13.2.12 PROCESS_SET_WORKING_SCHEMA */

```
Pcte_error_type Pcte_process_set_working_schema (
    Pcte_object_reference process,
    Pcte_name_sequence   sds_sequence
);
```

```

/*      The effect of not providing the optional parameter process to the      */
/*      abstract operation is achieved by specifying process as                */
/*      Pcte_null_object_reference.                                           */

```

```

/* 13.2.13 PROCESS_START */

```

```

Pcte_error_type Pcte_process_start (
    Pcte_object_reference process,
    Pcte_string           *arguments,
    Pcte_string           *environment,
    Pcte_object_reference site,
    Pcte_initial_status   initial_status
);

```

```

/*      The effect of not providing the optional parameter site to the abstract */
/*      operation is obtained by specifying site as Pcte_null_object_reference. */

```

```

/* 13.2.14 PROCESS_SUSPEND */

```

```

Pcte_error_type Pcte_process_suspend (
    Pcte_object_reference process,
    Pcte_natural          alarm
);

```

```

Pcte_error_type Pcte_process_suspend_unlimited (
    Pcte_object_reference process
);

```

```

/*      The effect of not providing the optional parameter process to the      */
/*      abstract operation is achieved by specifying process as                */
/*      Pcte_null_object_reference. The effect of not providing the optional    */
/*      parameter alarm is achieved by the operation                        */
/*      Pcte_process_suspend_unlimited.                                         */

```

```

/* 13.2.15 PROCESS_TERMINATE */

```

```

Pcte_error_type Pcte_process_terminate (
    Pcte_object_reference process,
    Pcte_integer          termination_status
);

```

```

/*      The effect of not providing the optional parameter process to the      */
/*      abstract operation is achieved by specifying process as                */
/*      Pcte_null_object_reference. The effect of not providing the optional    */
/*      parameter termination_status to the abstract operation is achieved by */
/*      specifying termination_status as PCTE_NULL_TERMINATION.              */

```

```

/* 13.2.16 PROCESS_UNSET_REFERENCED_OBJECT */

```

```

Pcte_error_type Pcte_process_unset_referenced_object (
    Pcte_object_reference process,
    Pcte_key              reference_name
);

```

```

/*      The effect of not providing the optional parameter process to the      */
/*      abstract operation is achieved by specifying process as                */
/*      Pcte_null_object_reference.                                           */

```

```

/* 13.2.17 PROCESS_WAIT_FOR_ANY_CHILD */

```

```

Pcte_error_type Pcte_process_wait_for_any_child (
    Pcte_integer      *termination_status,
    Pcte_natural      *child
);

```

```

/* 13.2.18 PROCESS_WAIT_FOR_CHILD */

```

```

Pcte_error_type Pcte_process_wait_for_child (
    Pcte_object_reference child,
    Pcte_integer          *termination_status
);

```

13.3 Security Operations

```

/* 13.3.1 PROCESS_ADOPT_USER_GROUP */

```

```

Pcte_error_type Pcte_process_adopt_user_group (
    Pcte_object_reference process,
    Pcte_object_reference user_group
);

```

```

/*      The effect of not providing the optional parameter process to the      */
/*      abstract operation is achieved by specifying process as                */
/*      Pcte_null_object_reference.                                           */

```

```

/* 13.3.2 PROCESS_GET_DEFAULT_ACL */

```

```

Pcte_error_type Pcte_process_get_default_acl (
    Pcte_acl      *acl
);

```

```

/* 13.3.3 PROCESS_GET_DEFAULT_OWNER */

```

```

Pcte_error_type Pcte_process_get_default_owner (
    Pcte_group_identifier *group
);

```

```

/* 13.3.4 PROCESS_SET_ADOPTABLE_FOR_CHILD */

```

```

Pcte_error_type Pcte_process_set_adoptable_for_child (
    Pcte_object_reference process,
    Pcte_object_reference user_group,
    Pcte_boolean          adoptability
);

```

```

/*      The effect of not providing the optional parameter process to the      */
/*      abstract operation is achieved by specifying process as                */
/*      Pcte_null_object_reference.                                           */

```

```

/* 13.3.5 PROCESS_SET_DEFAULT_ACL_ENTRY */

```

```

Pcte_error_type Pcte_process_set_default_acl_entry (
    Pcte_object_reference    process,
    Pcte_group_identifier    group,
    Pcte_requested_access_rights *modes
);

```

```

/*      The effect of not providing the optional parameter process to the      */
/*      abstract operation is achieved by specifying process as                */
/*      Pcte_null_object_reference.                                           */

```

```

/* 13.3.6 PROCESS_SET_DEFAULT_OWNER */

```

```

Pcte_error_type Pcte_process_set_default_owner (
    Pcte_object_reference    process,
    Pcte_group_identifier    group
);

```

```

/*      The effect of not providing the optional parameter process to the      */
/*      abstract operation is achieved by specifying process as                */
/*      Pcte_null_object_reference.                                           */

```

```

/* 13.3.7 PROCESS_SET_USER */

```

```

Pcte_error_type Pcte_process_set_user (
    Pcte_object_reference    user,
    Pcte_object_reference    user_group
);

```

13.4 Profiling Operations

```

/* 13.4.1 PROCESS_PROFILING_OFF */

```

```

Pcte_error_type Pcte_process_profiling_off (
    Pcte_profile_handle    handle,
    Pcte_buffer            *buffer
);

```

```

/* 13.4.2 PROCESS_PROFILING_ON */

```

```

Pcte_error_type Pcte_process_profiling_on (
    Pcte_address    start,
    Pcte_address    end,
    Pcte_natural    count,
    Pcte_profile_handle *handle
);

```

13.5 Monitoring Operations

/* 13.5.1 PROCESS_ADD_BREAKPOINT */

```
Pcte_error_type Pcte_process_add_breakpoint (
    Pcte_object_reference process,
    Pcte_address          breakpoint
);
```

/* 13.5.2 PROCESS_CONTINUE */

```
Pcte_error_type Pcte_process_continue (
    Pcte_object_reference process
);
```

/* 13.5.3 PROCESS_PEEK */

```
Pcte_error_type Pcte_process_peek (
    Pcte_object_reference process,
    Pcte_address          address,
    Pcte_octet             *process_data,
    Pcte_natural           *process_data_size
);
```

/* In *process_data_size* the number of octets which are to be read has to be provided. In *process_data* the read octets are returned and in *process_data_size* the number of read octets is returned. If there is not enough space in *process_data*, the error PCTE_STRING_TOO_SHORT is raised. */

/* 13.5.4 PROCESS_POKE */

```
Pcte_error_type Pcte_process_poke (
    Pcte_object_reference process,
    Pcte_address          address,
    Pcte_octet             *process_data,
    Pcte_natural           process_data_size
);
```

/* In *process_data* the octets to be written have to be provided and in *process_data_size* the number of octets to be written has to be provided. If *process_data_size* is bigger than the number of octets allocated in *process_data*, the error PCTE_ACCESS_AT_INVALID_ADDRESS is raised. */

/* 13.5.5 PROCESS_REMOVE_BREAKPOINT */

```
Pcte_error_type Pcte_process_remove_breakpoint (
    Pcte_object_reference process,
    Pcte_address          breakpoint
);
```

```

/* 13.5.6 PROCESS_WAIT_FOR_BREAKPOINT */
Pcte_error_type Pcte_process_wait_for_breakpoint (
    Pcte_object reference    process,
    Pcte_address             *breakpoint
);
/*      If the abstract operation returns no value in breakpoint then breakpoint      */
/*      is set to NULL.                                                                */
#endif /* !PCTE_EXECUTION_INCLUDED */

```

14 Message queues

```

/* The header <Pcte/messages.h> */
#ifndef PCTE_MESSAGES_INCLUDED
#define PCTE_MESSAGES_INCLUDED 1

#include <Pcte/types.h>
#include <Pcte/references.h>
#include <Pcte/sequences.h>

```

14.1 Message Queue Datatypes

```

typedef enum {
    PCTE_INTERRUPT_MSG, PCTE_QUIT_MSG, PCTE_FINISH_MSG,
    PCTE_SUSPEND_MSG, PCTE_END_MSG, PCTE_ABORT_MSG,
    PCTE_DEADLOCK_MSG, PCTE_WAKE_MSG
} Pcte_standard_message_type;

typedef enum {
    PCTE_MODIFICATION_MSG, PCTE_CHANGE_MSG,
    PCTE_DELETE_MSG, PCTE_MOVE_MSG,
    PCTE_NOT_ACCESSIBLE_MSG, PCTE_LOST_MSG
} Pcte_notification_message_type;

typedef struct {
    enum {
        PCTE_STANDARD_MESSAGE, PCTE_NOTIFICATION_MESSAGE,
        PCTE_IMPLEMENTATION_MESSAGE, PCTE_UNDEFINED_MESSAGE
    } message_kind;
    union {
        Pcte_standard_message_type    standard;
        Pcte_notification_message_type notification;
        Pcte_natural                   implementation;
        Pcte_natural                   undefined;
    } type;
} Pcte_message_type;

#define Pcte_all_message_types (Pcte_message_types) NULL

```

```

typedef struct {
    Pcte_string      data;
    Pcte_message_type message_type;
} Pcte_message;

typedef struct {
    Pcte_message      message;
    Pcte_natural       position;
    Pcte_boolean       message_received;
} Pcte_received_message;

typedef void (* Pcte_handler)(Pcte_object_reference message_queue);

```

14.2 Message Queue Operations

/* 14.2.1 MESSAGE_DELETE */

```

Pcte_error_type Pcte_message_delete (
    Pcte_object_reference queue,
    Pcte_natural          position
);

```

/* 14.2.2 MESSAGE_PEEK */

```

Pcte_error_type Pcte_message_peek (
    Pcte_object_reference queue,
    Pcte_message_types   type,
    Pcte_natural          position,
    Pcte_received_message *message
);

```

/* The effect of specifying *types* as ALL_MESSAGE_TYPES to the
 /* abstract operation is achieved by specifying **types** as
 /* Pcte_all_message_types. The effect of not providing the optional
 /* parameter *position* to the abstract operation is achieved by specifying
 /* **position** as 0. If no message is returned, message_received is set to
 /* PCTE_FALSE. */

/* 14.2.3 MESSAGE_RECEIVE_NO_WAIT */

```

Pcte_error_type Pcte_message_receive_no_wait (
    Pcte_object_reference queue,
    Pcte_message_types   types,
    Pcte_natural          position,
    Pcte_received_message *message
);

```

```

/*      The effect of specifying types as ALL_MESSAGE_TYPES to the      */
/*      abstract operation is achieved by specifying types as          */
/*      Pcte_all_message_types. The effect of not providing the optional */
/*      parameter position to the abstract operation is achieved by specifying */
/*      position as 0. If no message is returned, message_received is set to */
/*      PCTE_FALSE.                                                    */

```

```

/* 14.2.4 MESSAGE_RECEIVE_WAIT */

```

```

Pcte_error_type Pcte_message_receive_wait (
    Pcte_object_reference    queue,
    Pcte_message_types      types,
    Pcte_natural             position,
    Pcte_received_message   *message
);

```

```

/*      The effect of not providing the optional parameter position to the      */
/*      abstract operation is achieved by specifying position as 0.          */
/*                                                                 */

```

```

/* 14.2.5 MESSAGE_SEND_NO_WAIT */

```

```

Pcte_error_type Pcte_message_send_no_wait (
    Pcte_object_reference    queue,
    Pcte_message             *message
);

```

```

/* 14.2.6 MESSAGE_SEND_WAIT */

```

```

Pcte_error_type Pcte_message_send_wait (
    Pcte_object_reference    queue,
    Pcte_message             *message
);

```

```

/* 14.2.7 QUEUE_EMPTY */

```

```

Pcte_error_type Pcte_queue_empty (
    Pcte_object_reference    queue
);

```

```

/* 14.2.8 QUEUE_HANDLER_DISABLE */

```

```

Pcte_error_type Pcte_queue_handler_disable (
    Pcte_object_reference    queue
);

```

```

/* 14.2.9 QUEUE_HANDLER_ENABLE */

```

```

Pcte_error_type Pcte_queue_handler_enable (
    Pcte_object_reference    queue,
    Pcte_message_types      types,
    Pcte_handler             handler
);

```

```

/*      The effect of specifying types as ALL_MESSAGE_TYPES to the      */
/*      abstract operation is achieved by specifying types as          */
/*      Pcte_all_message_types.                                          */
/* 14.2.10 QUEUE_RESERVE */
Pcte_error_type Pcte_queue_reserve (
    Pcte_object_reference queue
);
/* 14.2.11 QUEUE_RESTORE */
Pcte_error_type Pcte_queue_restore (
    Pcte_object_reference queue,
    Pcte_object_reference file
);
/* 14.2.12 QUEUE_SAVE */
Pcte_error_type Pcte_queue_save (
    Pcte_object_reference queue,
    Pcte_object_reference file
);
/* 14.2.13 QUEUE_SET_TOTAL_SPACE */
Pcte_error_type Pcte_queue_set_total_space (
    Pcte_object_reference queue,
    Pcte_natural total_space
);
/* 14.2.14 QUEUE_UNRESERVE */
Pcte_error_type Pcte_queue_unreserve (
    Pcte_object_reference queue
);
#endif /* !PCTE_MESSAGES_INCLUDED */

```

15 Notification

```

/* The header <Pcte/notification.h> */
#ifndef PCTE_NOTIFICATION_INCLUDED
#define PCTE_NOTIFICATION_INCLUDED 1

#include <Pcte/types.h>
#include <Pcte/references.h>
#include <Pcte/messages.h>

```

15.1 Notification Datatypes

```
typedef enum {
    PCTE_MODIFICATION_EVENT = 1<<0,
    PCTE_CHANGE_EVENT       = 1<<1,
    PCTE_DELETE_EVENT       = 1<<2,
    PCTE_MOVE_EVENT         = 1<<3
} Pcte_access_event;

typedef Pcte_natural Pcte_access_events;
```

15.2 Notification Operations

/* 15.2.1 NOTIFY_CREATE */

```
Pcte_error_type Pcte_notify_create (
    Pcte_natural      notifier_key,
    Pcte_object_reference queue,
    Pcte_object_reference object
);
```

/* 15.2.2 NOTIFY_DELETE */

```
Pcte_error_type Pcte_notify_delete (
    Pcte_natural      notifier_key,
    Pcte_object_reference queue
);
```

/* 15.2.3 NOTIFICATION_MESSAGE_GET_KEY */

```
Pcte_error_type Pcte_notification_message_get_key (
    Pcte_received_message message,
    Pcte_natural          *notifier_key
);
```

/* 15.2.4 NOTIFY_SWITCH_EVENTS */

```
Pcte_error_type Pcte_notify_switch_events (
    Pcte_natural      notifier_key,
    Pcte_object_reference queue,
    Pcte_access_events access_events
);
```

#endif /* !PCTE_NOTIFICATION_INCLUDED */

16 Concurrency and integrity control

/* The header <Pcte/activities.h> */

```
#ifndef PCTE_ACTIVITIES_INCLUDED
#define PCTE_ACTIVITIES_INCLUDED 1
```

```
#include <Pcte/types.h>
#include <Pcte/references.h>
#include <Pcte/oms.h>
```

16.1 Concurrency and Integrity Control Datatypes

```
typedef enum {
    PCTE_UNPROTECTED, PCTE_PROTECTED, PCTE_TRANSACTION
} Pcte_activity_class;

typedef enum {
    PCTE_READ_UNPROTECTED, PCTE_READ_SEMIPROTECTED,
    PCTE_WRITE_UNPROTECTED, PCTE_WRITE_SEMIPROTECTED,
    PCTE_DELETE_UNPROTECTED, PCTE_DELETE_SEMIPROTECTED,
    PCTE_READ_PROTECTED, PCTE_WRITE_PROTECTED,
    PCTE_DELETE_PROTECTED, PCTE_WRITE_TRANSACTIONED,
    PCTE_DELETE_TRANSACTIONED, PCTE_READ_DEFAULT,
    PCTE_WRITE_DEFAULT, PCTE_DELETE_DEFAULT
} Pcte_lock_set_mode;

typedef Pcte_lock_set_mode Pcte_lock_internal_mode;
```

16.2 Concurrency and Integrity Control Operations

```
/* 16.2.1 ACTIVITY_ABORT */
Pcte_error_type Pcte_activity_abort (
);

/* 16.2.2 ACTIVITY_END */
Pcte_error_type Pcte_activity_end (
);

/* 16.2.3 ACTIVITY_START */
Pcte_error_type Pcte_activity_start (
    Pcte_activity_class    activity_class
);

/* 16.2.4 LOCK_RESET_INTERNAL_MODE */
Pcte_error_type Pcte_lock_reset_internal_mode (
    Pcte_object_reference  object
);
```

```
/* 16.2.5 LOCK_SET_INTERNAL_MODE */
```

```
Pcte_error_type Pcte_lock_set_internal_mode (
    Pcte_object_reference    object,
    Pcte_lock_internal_mode  lock_mode,
    Pcte_boolean             wait_flag
);
```

```
/* If the value PCTE_READ_DEFAULT, PCTE_WRITE_DEFAULT, */
/* PCTE_DELETE_DEFAULT, PCTE_DELETE_PROTECTED, */
/* PCTE_WRITE_TRANSACTIONED, or */
/* PCTE_DELETE_TRANSACTIONED is passed to lock_mode, the error */
/* PCTE_VALUE_IS_OUT_OF_RANGE is raised. */
```

```
/* 16.2.6 LOCK_SET_OBJECT */
```

```
Pcte_error_type Pcte_lock_set_object (
    Pcte_object_reference    object,
    Pcte_lock_set_mode       lock_mode,
    Pcte_boolean             wait_flag,
    Pcte_object_scope        scope
);
```

```
/* 16.2.7 LOCK_UNSET_OBJECT */
```

```
Pcte_error_type Pcte_lock_unset_object (
    Pcte_object_reference    object,
    Pcte_object_scope        scope
);
```

```
#endif /* !PCTE_ACTIVITIES_INCLUDED */
```

17 Replication

```
/* The header <Pcte/replication.h> */
```

```
#ifndef PCTE_REPLICATION_INCLUDED
#define PCTE_REPLICATION_INCLUDED 1
```

```
#include <Pcte/types.h>
#include <Pcte/references.h>
```

17.1 Replication Datatypes

```
/* None. */
```

17.2 Replication Operations

/* 17.2.1 REPLICA_SET_ADD_COPY_VOLUME */

```
Pcte_error_type Pcte_replica_set_add_copy_volume (  
    Pcte_object_reference    replica_set,  
    Pcte_object_reference    copy_volume  
);
```

/* 17.2.2 REPLICA_SET_CREATE */

```
Pcte_error_type Pcte_replica_set_create (  
    Pcte_object_reference    master_volume,  
    Pcte_natural             identifier,  
    Pcte_object_reference    *replica_set  
);
```

/* 17.2.3 REPLICA_SET_REMOVE */

```
Pcte_error_type Pcte_replica_set_remove (  
    Pcte_object_reference    replica_set  
);
```

/* 17.2.4 REPLICA_SET_REMOVE_COPY_VOLUME */

```
Pcte_error_type Pcte_replica_set_remove_copy_volume (  
    Pcte_object_reference    replica_set,  
    Pcte_object_reference    copy_volume  
);
```

/* 17.2.5 REPLICATED_OBJECT_CREATE */

```
Pcte_error_type Pcte_replicated_object_create (  
    Pcte_object_reference    replica_set,  
    Pcte_object_reference    object  
);
```

/* 17.2.6 REPLICATED_OBJECT_DELETE_REPLICA */

```
Pcte_error_type Pcte_replicated_object_delete_replica (  
    Pcte_object_reference    object,  
    Pcte_object_reference    copy_volume  
);
```

/* 17.2.7 REPLICATED_OBJECT_DUPLICATE */

```
Pcte_error_type Pcte_replicated_object_duplicate (  
    Pcte_object_reference    object,  
    Pcte_object_reference    volume,  
    Pcte_object_reference    copy_volume  
);
```

```

/* 17.2.8 REPLICATED_OBJECT_REMOVE */
Pcte_error_type Pcte_replicated_object_remove (
    Pcte_object_reference    object
);

/* 17.2.9 WORKSTATION_SELECT_REPLICA_SET_VOLUME */
Pcte_error_type Pcte_workstation_select_replica_set_volume (
    Pcte_object_reference    workstation,
    Pcte_object_reference    replica_set,
    Pcte_object_reference    volume
);

/* 17.2.10 WORKSTATION_UNSELECT_REPLICA_SET_VOLUME */
Pcte_error_type Pcte_workstation_unselect_replica_set_volume (
    Pcte_object_reference    workstation,
    Pcte_object_reference    replica_set
);

#endif /* !PCTE_REPLICATION_INCLUDED */

```

18 Network connection

```

/* The header <Pcte/network.h> */

#ifndef PCTE_NETWORK_INCLUDED
#define PCTE_NETWORK_INCLUDED 1

#include <Pcte/types.h>
#include <Pcte/references.h>
#include <Pcte/devices.h>

```

18.1 Network Connection Datatypes

```

typedef enum {
    PCTE_ACTIVITY_REMOTE_LOCKS      = 1<<0,
    PCTE_ACTIVITY_LOCAL_LOCKS       = 1<<1,
    PCTE_TRANSACTION_REMOTE_LOCKS   = 1<<2,
    PCTE_TRANSACTION_LOCAL_LOCKS    = 1<<3,
    PCTE_QUEUE_REMOTE               = 1<<4,
    PCTE_QUEUE_LOCAL                = 1<<5,
    PCTE_RECEIVE_REMOTE             = 1<<6,
    PCTE_RECEIVE_LOCAL              = 1<<7,
    PCTE_CHILD_REMOTE               = 1<<8,
    PCTE_CHILD_LOCAL                = 1<<9
} Pcte_work_status_item;

typedef Pcte_natural Pcte_work_status;

```

```

typedef enum {
    PCTE_LOCAL, PCTE_CLIENT, PCTE_CONNECTED,
    PCTE_AVAILABLE
} Pcte_connection_status;

typedef Pcte_connection_status Pcte_requested_connection_status;

typedef struct {
    Pcte_string          foreign_device;
    Pcte_volume_identifier administration_volume;
    Pcte_string          volume_characteristics;
    Pcte_device_identifier device;
    Pcte_string          device_characteristics;
} Pcte_new_administration_volume;

typedef struct {
    Pcte_connection_status connection;
    Pcte_work_status       work;
} Pcte_workstation_status;

#define PCTE_MAX_MACHINE_NAME_SIZE PCTE_MAX_NAME_SIZE
typedef Pcte_octet Pcte_machine_name[PCTE_MAX_MACHINE_NAME_SIZE + 1];

#define PCTE_MAX_NODE_NAME_SIZE PCTE_MAX_NAME_SIZE
typedef Pcte_octet Pcte_node_name[PCTE_MAX_NODE_NAME_SIZE + 1];

```

18.2 Network Connection Operations

/* 18.2.1 WORKSTATION_CONNECT */

```

Pcte_error_type Pcte_workstation_connect (
    Pcte_requested_connection_status status
);

```

/* If the value PCTE_AVAILABLE is passed to the parameter **status** the
 /* error PCTE_VALUE_OUT_OF_RANGE is raised. */

/* 18.2.2 WORKSTATION_CREATE */

```

Pcte_error_type Pcte_workstation_create (
    Pcte_natural          execution_site_identifier,
    Pcte_new_administration_volume *administration_volume,
    Pcte_atomic_access_rights *access_mask,
    Pcte_node_name        node_name,
    Pcte_machine_name     machine_name
);

```

```

Pcte_error_type Pcte_workstation_create_with_existing_admin_volume (
    Pcte_natural          execution_site_identifier,
    Pcte_object_reference existing_administration_volume,
    Pcte_atomic_access_rights *access_mask,
    Pcte_node_name        node_name,
    Pcte_machine_name      machine_name
);

/* The effect of specifying administration_volume as a new administration */
/* volume to the abstract operation is achieved by the operation */
/* Pcte_workstation_create_with_existing_admin_volume. The effect of */
/* specifying administration_volume as a volume designator to the abstract */
/* operation is achieved by the operation Pcte_workstation_create. */

/* 18.2.3 WORKSTATION_DELETE */

Pcte_error_type Pcte_workstation_delete (
    Pcte_object_reference station
);

/* 18.2.4 WORKSTATION_DISCONNECT */

Pcte_error_type Pcte_workstation_disconnect (
);

/* 18.2.5 WORKSTATION_GET_STATUS */

Pcte_error_type Pcte_workstation_get_status (
    Pcte_object_reference station,
    Pcte_workstation_status *status
);

/* The effect of not providing the optional parameter station to the abstract */
/* operation is achieved by specifying station as */
/* Pcte_null_object reference. */

/* 18.2.6 WORKSTATION_REDUCE_CONNECTION */

Pcte_error_type Pcte_workstation_reduce_connection (
    Pcte_object_reference station,
    Pcte_requested_connection_status status,
    Pcte_boolean force
);

/* The effect of not providing the optional parameter station to the abstract */
/* operation is achieved by specifying station as */
/* Pcte_null_object reference. If the value PCTE_AVAILABLE is passed */
/* to the parameter status the error PCTE_VALUE_OUT_OF_RANGE is */
/* raised. */

```

18.3 Foreign System Operations

/* 18.3.1 CONTENTS_COPY_FROM_FOREIGN_SYSTEM */

```
Pcte_error_type Pcte_contents_copy_from_foreign_system (
    Pcte_object_reference file,
    Pcte_object_reference foreign_system,
    Pcte_string           *foreign_name,
    Pcte_string           *foreign_parameters
);
```

/* The effect of not providing the optional parameter *foreign_parameters* */
 /* to the abstract operation is achieved by specifying **foreign_parameters** */
 /* as NULL. */

/* 18.3.2 CONTENTS_COPY_TO_FOREIGN_SYSTEM */

```
Pcte_error_type Pcte_contents_copy_to_foreign_system (
    Pcte_object_reference file,
    Pcte_object_reference foreign_system,
    Pcte_string           *foreign_name,
    Pcte_string           *foreign_parameters
);
```

/* The effect of not providing the optional parameter *foreign_parameters* */
 /* to the abstract operation is achieved by specifying **foreign_parameters** */
 /* as NULL. */

18.4 Time Operations

/* 18.4.1 TIME_GET */

```
Pcte_error_type Pcte_time_get (
    Pcte_time *time
);
```

/* 18.4.2 TIME_SET */

```
Pcte_error_type Pcte_time_set (
    Pcte_time time
);
```

#endif /* !PCTE_NETWORK_INCLUDED */

19 Discretionary security

/* The header <Pcte/discretionary.h> */

```
#ifndef PCTE_DISCRETIONARY_INCLUDED
#define PCTE_DISCRETIONARY_INCLUDED 1
```

```
#include <Pcte/types.h>
```

```
#include <Pcte/references.h>
```

```
#include <Pcte/sequences.h>
```

19.1 Discretionary Security Datatypes

```
#define PCTE_ALL_USERS (Pcte_natural) 1
#define PCTE_SECURITY (Pcte_natural) 2
#define PCTE_AUDIT (Pcte_natural) 3
#define PCTE_EXECUTION (Pcte_natural) 4
#define PCTE_REPLICATION (Pcte_natural) 5
#define PCTE_CONFIGURATION (Pcte_natural) 6
#define PCTE_HISTORY (Pcte_natural) 7
#define PCTE_SCHEMA_UPDATE (Pcte_natural) 8

typedef enum {
    PCTE_NAVIGATE = 1<<0,
    PCTE_READ_ATTRIBUTES = 1<<1,
    PCTE_READ_LINKS = 1<<2,
    PCTE_READ_CONTENTS = 1<<3,
    PCTE_APPEND_LINKS = 1<<4,
    PCTE_APPEND_IMPLICIT = 1<<5,
    PCTE_APPEND_CONTENTS = 1<<6,
    PCTE_WRITE_IMPLICIT = 1<<7,
    PCTE_WRITE_ATTRIBUTES = 1<<8,
    PCTE_WRITE_LINKS = 1<<9,
    PCTE_WRITE_CONTENTS = 1<<10,
    PCTE_DELETE = 1<<11,
    PCTE_EXECUTE = 1<<12,
    PCTE_EXPLOIT_DEVICE = 1<<13,
    PCTE_EXPLOIT_SCHEMA = 1<<14,
    PCTE_EXPLOIT_CONSUMER_IDENTITY = 1<<15,
    PCTE_CONTROL_DISCRETIONARY = 1<<16,
    PCTE_CONTROL_MANDATORY = 1<<17,
    PCTE_CONTROL_OBJECT = 1<<18,
    PCTE_OWNER = 1<<19,
    PCTE_STABILIZE = 1<<20
} Pcte_discretionary_access_mode;

typedef Pcte_natural Pcte_discretionary_access_modes;

typedef struct {
    Pcte_discretionary_access_modes denied_rights;
    Pcte_discretionary_access_modes granted_rights;
} Pcte_access_rights;

typedef Pcte_access_rights Pcte_atomic_access_rights;

typedef Pcte_access_rights Pcte_requested_access_rights;
```

/* **Pcte_access_rights** corresponds to the PCTE datatype **Access_rights**. */
 /* Consider a particular access mode, A. A is represented by an entry E */
 /* within the bounded set of access mode. Let DR indicate "denied rights" */
 /* and GR indicate "granted rights". The following table shows how the */
 /* entry E is set or not set to specify any given access mode value: */

	GR	DR
partially-denied	0	0
denied	0	1
granted	1	0
undefined	1	1

/* In the same way, **Pcte_atomic_access_rights** and */
 /* **Pcte_requested_access_rights** are defined using the following tables: */

Pcte_atomic_access_rights		
	GR	DR
denied	0	1
granted	1	0
undefined	1	1

Pcte_requested_access_rights		
	GR	DR
unchanged	0	0
denied	0	1
granted	1	0
undefined	1	1

typedef Pcte_natural Pcte_group_identifier;

```
typedef struct {
    Pcte_group_identifier group;
    Pcte_access_rights access_rights;
} Pcte_acl_entry;
```

typedef Pcte_sequence Pcte_acl;

/* The PCTE datatype Acl which is a map from security group identifier to */
 /* access rights is mapped to the C datatype **Pcte_acl**. **Pcte_acl** is a */
 /* sequence indicated by PCTE_ACL with the C element datatype */
 /* **Pcte_acl_entry**. The component **security_group** represents the domain */
 /* of the map whereas the component **access_rights** indicates the value of */
 /* the map. */

#include <Pcte/oms.h>

19.2 Discretionary Access Control Operations

/* 19.2.1 GROUP_GET_IDENTIFIER */

```
Pcte_error_type Pcte_group_get_identifier (
    Pcte_object_reference    group,
    Pcte_group_identifier    *identifier
);
```

/* 19.2.2 OBJECT_CHECK_PERMISSION */

```
Pcte_error_type Pcte_object_check_permission (
    Pcte_object_reference    object,
    Pcte_discretionary_access_modes    modes,
    Pcte_object_scope        scope,
    Pcte_boolean             *accessible
);
```

/* 19.2.3 OBJECT_GET_ACL */

```
Pcte_error_type Pcte_object_get_acl (
    Pcte_object_reference    object,
    Pcte_object_scope        scope,
    Pcte_acl                 *acl
);
```

/* 19.2.4 OBJECT_SET_ACL_ENTRY */

```
Pcte_error_type Pcte_object_set_acl_entry (
    Pcte_object_reference    object,
    Pcte_group_identifier    group,
    Pcte_requested_access_rights    *modes,
    Pcte_object_scope        scope
);
```

19.3 Discretionary Security Administration Operations

/* 19.3.1 GROUP_INITIALIZE */

```
Pcte_error_type Pcte_group_initialize (
    Pcte_object_reference    group,
    Pcte_group_identifier    *identifier
);
```

/* 19.3.2 GROUP_REMOVE */

```
Pcte_error_type Pcte_group_remove (
    Pcte_object_reference    group
);
```

/* 19.3.3 GROUP_RESTORE */

```
Pcte_error_type Pcte_group_restore (  
    Pcte_object_reference    group,  
    Pcte_group_identifier    identifier  
);
```

/* 19.3.4 PROGRAM_GROUP_ADD_MEMBER */

```
Pcte_error_type Pcte_program_group_add_member (  
    Pcte_object_reference    group,  
    Pcte_object_reference    program  
);
```

/* 19.3.5 PROGRAM_GROUP_ADD_SUBGROUP */

```
Pcte_error_type Pcte_program_group_add_subgroup (  
    Pcte_object_reference    group,  
    Pcte_object_reference    subgroup  
);
```

/* 19.3.6 PROGRAM_GROUP_REMOVE_MEMBER */

```
Pcte_error_type Pcte_program_group_remove_member (  
    Pcte_object_reference    group,  
    Pcte_object_reference    program  
);
```

/* 19.3.7 PROGRAM_GROUP_REMOVE_SUBGROUP */

```
Pcte_error_type Pcte_program_group_remove_subgroup (  
    Pcte_object_reference    group,  
    Pcte_object_reference    subgroup  
);
```

/* 19.3.8 USER_GROUP_ADD_MEMBER */

```
Pcte_error_type Pcte_user_group_add_member (  
    Pcte_object_reference    group,  
    Pcte_object_reference    user  
);
```

/* 19.3.9 USER_GROUP_ADD_SUBGROUP */

```
Pcte_error_type Pcte_user_group_add_subgroup (  
    Pcte_object_reference    group,  
    Pcte_object_reference    subgroup  
);
```

```
/* 19.3.10 USER_GROUP_REMOVE_MEMBER */
```

```
Pcte_error_type Pcte_user_group_remove_member (
    Pcte_object_reference    group,
    Pcte_object_reference    user
);
```

```
/* 19.3.11 USER_GROUP_REMOVE_SUBGROUP */
```

```
Pcte_error_type Pcte_user_group_remove_subgroup (
    Pcte_object_reference    group,
    Pcte_object_reference    subgroup
);
```

```
#endif /* !PCTE_DISCRETIONARY_INCLUDED */
```

20 Mandatory security

```
/* The header <Pcte/mandatory.h> */
```

```
#ifndef PCTE_MANDATORY_INCLUDED
#define PCTE_MANDATORY_INCLUDED 1
```

```
#include <Pcte/types.h>
#include <Pcte/references.h>
```

20.1 Mandatory Security Datatypes

```
typedef Pcte_string Pcte_security_label;
```

```
/* The PCTE datatype Pcte_security_label_string (see ISO/IEC 13719-1, */
/* 23.1.3.1) is mapped to the C datatype Pcte_security_label. */
```

```
typedef enum {
    PCTE_NO_FLOAT, PCTE_FLOAT_IN,
    PCTE_FLOAT_OUT, PCTE_FLOAT_IN_OUT
} Pcte_floating_level;
```

20.2 Mandatory Security Operations

```
/* 20.2.1 DEVICE_SET_CONFIDENTIALITY_RANGE */
```

```
Pcte_error_type Pcte_device_set_confidentiality_range (
    Pcte_object_reference    object,
    Pcte_security_label      *high_label,
    Pcte_security_label      *low_label
);
```

/* 20.2.2 DEVICE_SET_INTEGRITY_RANGE */

```
Pcte_error_type Pcte_device_set_integrity_range (  
    Pcte_object_reference    object,  
    Pcte_security_label      *high_label,  
    Pcte_security_label      *low_label  
);
```

/* 20.2.3 EXECUTION_SITE_SET_CONFIDENTIALITY_RANGE */

```
Pcte_error_type Pcte_execution_site_set_confidentiality_range (  
    Pcte_object_reference    execution_site,  
    Pcte_security_label      *high_label,  
    Pcte_security_label      *low_label  
);
```

/* 20.2.4 EXECUTION_SITE_SET_INTEGRITY_RANGE */

```
Pcte_error_type Pcte_execution_site_set_integrity_range (  
    Pcte_object_reference    execution_site,  
    Pcte_security_label      *high_label,  
    Pcte_security_label      *low_label  
);
```

/* 20.2.5 OBJECT_SET_CONFIDENTIALITY_LABEL */

```
Pcte_error_type Pcte_object_set_confidentiality_label (  
    Pcte_object_reference    object,  
    Pcte_security_label      *label  
);
```

/* 20.2.6 OBJECT_SET_INTEGRITY_LABEL */

```
Pcte_error_type Pcte_object_set_integrity_label (  
    Pcte_object_reference    object,  
    Pcte_security_label      *label  
);
```

/* 20.2.7 VOLUME_SET_CONFIDENTIALITY_RANGE */

```
Pcte_error_type Pcte_volume_set_confidentiality_range (  
    Pcte_object_reference    volume,  
    Pcte_security_label      *high_label,  
    Pcte_security_label      *low_label  
);
```

/* 20.2.8 VOLUME_SET_INTEGRITY_RANGE */

```
Pcte_error_type Pcte_volume_set_integrity_range (  
    Pcte_object_reference    volume,  
    Pcte_security_label      *high_label,  
    Pcte_security_label      *low_label  
);
```

20.3 Mandatory Security Administration Operations

/* 20.3.1 CONFIDENTIALITY_CLASS_INITIALIZE */

```
Pcte_error_type Pcte_confidentiality_class_initialize (
    Pcte_object_reference    object,
    Pcte_name                class_name,
    Pcte_object_reference    to_be_dominated
);
```

/* The effect of not providing the optional parameter *to_be_dominated* to
 /* the abstract operation is achieved by specifying **to_be_dominated** as
 /* Pcte_null_object_reference. */

/* 20.3.2 GROUP_DISABLE_FOR_CONFIDENTIALITY_DOWNGRADE */

```
Pcte_error_type Pcte_group_disable_for_confidentiality_downgrade (
    Pcte_object_reference    group,
    Pcte_object_reference    confidentiality_class
);
```

/* 20.3.3 GROUP_DISABLE_FOR_INTEGRITY_UPGRADE */

```
Pcte_error_type Pcte_group_disable_for_integrity_upgrade (
    Pcte_object_reference    group,
    Pcte_object_reference    integrity_class
);
```

/* 20.3.4 GROUP_ENABLE_FOR_CONFIDENTIALITY_DOWNGRADE */

```
Pcte_error_type Pcte_group_enable_for_confidentiality_downgrade (
    Pcte_object_reference    group,
    Pcte_object_reference    confidentiality_class
);
```

/* 20.3.5 GROUP_ENABLE_FOR_INTEGRITY_UPGRADE */

```
Pcte_error_type Pcte_group_enable_for_integrity_upgrade (
    Pcte_object_reference    group,
    Pcte_object_reference    integrity_class
);
```

/* 20.3.6 INTEGRITY_CLASS_INITIALIZE */

```
Pcte_error_type Pcte_integrity_class_initialize (
    Pcte_object_reference    object,
    Pcte_name                class_name,
    Pcte_object_reference    to_be_dominated
);
```

```

/*      The effect of not providing the optional parameter to_be_dominated to      */
/*      the abstract operation is achieved by specifying to_be_dominated as      */
/*      Pcte_null_object_reference.                                             */

```

```

/* 20.3.7 USER_EXTEND_CONFIDENTIALITY_CLEARANCE */

```

```

Pcte_error_type Pcte_user_extend_confidentiality_clearance (
    Pcte_object_reference    user,
    Pcte_object_reference    confidentiality_class
);

```

```

/* 20.3.8 USER_EXTEND_INTEGRITY_CLEARANCE */

```

```

Pcte_error_type Pcte_user_extend_integrity_clearance (
    Pcte_object_reference    user,
    Pcte_object_reference    integrity_class
);

```

```

/* 20.3.9 USER_REDUCE_CONFIDENTIALITY_CLEARANCE */

```

```

Pcte_error_type Pcte_user_reduce_confidentiality_clearance (
    Pcte_object_reference    user,
    Pcte_object_reference    confidentiality_class
);

```

```

/* 20.3.10 USER_REDUCE_INTEGRITY_CLEARANCE */

```

```

Pcte_error_type Pcte_user_reduce_integrity_clearance (
    Pcte_object_reference    user,
    Pcte_object_reference    integrity_class
);

```

20.4 Mandatory Security Operations for Processes

```

/* 20.4.1 PROCESS_SET_CONFIDENTIALITY_LABEL */

```

```

Pcte_error_type Pcte_process_set_confidentiality_label (
    Pcte_object_reference    process,
    Pcte_security_label      *confidentiality_label
);

```

```

/*      The effect of not providing the optional parameter process to the      */
/*      abstract operation is achieved by specifying process as                */
/*      Pcte_null_object_reference.                                             */

```

```

/* 20.4.2 PROCESS_SET_FLOATING_CONFIDENTIALITY_LEVEL */

```

```

Pcte_error_type Pcte_process_set_floating_confidentiality_level (
    Pcte_object_reference    process,
    Pcte_floating_level      floating_mode
);

```

```

/*      The effect of not providing the optional parameter process to the      */
/*      abstract operation is achieved by specifying process as                */
/*      Pcte_null_object_reference.                                           */
/* 20.4.3 PROCESS_SET_FLOATING_INTEGRITY_LEVEL */
Pcte_error_type Pcte_process_set_floating_integrity_level (
    Pcte_object_reference    process,
    Pcte_floating_level      floating_mode
);
/*      The effect of not providing the optional parameter process to the      */
/*      abstract operation is achieved by specifying process as                */
/*      Pcte_null_object_reference.                                           */
/* 20.4.4 PROCESS_SET_INTEGRITY_LABEL */
Pcte_error_type Pcte_process_set_integrity_label (
    Pcte_object_reference    process,
    Pcte_security_label      *integrity_label
);
/*      The effect of not providing the optional parameter process to the      */
/*      abstract operation is achieved by specifying process as                */
/*      Pcte_null_object_reference.                                           */
#endif /* !PCTE_MANDATORY_INCLUDED */

```

21 Auditing

```

/* The header <Pcte/auditing.h> */
#ifndef PCTE_AUDITING_INCLUDED
#define PCTE_AUDITING_INCLUDED 1

#include <Pcte/types.h>
#include <Pcte/references.h>
#include <Pcte/sequences.h>
#include <Pcte/discretionary.h>
#include <Pcte/mandatory.h>

```

21.1 Auditing Datatypes

```
typedef enum {
    PCTE_WRITE, PCTE_READ, PCTE_COPY, PCTE_ACCESS_CONTENTS,
    PCTE_EXPLOIT, PCTE_CHANGE_ACCESS_CONTROL_LIST,
    PCTE_CHANGE_LABEL, PCTE_USE_PREDEFINED_GROUP,
    PCTE_SET_USER_IDENTITY,
    PCTE_WRITE_CONFIDENTIALITY_VIOLATION,
    PCTE_READ_CONFIDENTIALITY_VIOLATION,
    PCTE_WRITE_INTEGRITY_VIOLATION,
    PCTE_READ_INTEGRITY_VIOLATION,
    PCTE_COVERT_CHANNEL, PCTE_INFORMATION_EVENT
} Pcte_selectable_event_type;
```

```
typedef enum {
    PCTE_CHANGE_IDENTIFICATION, PCTE_SELECT_AUDIT_EVENT,
    PCTE_SECURITY_ADMINISTRATION
} Pcte_mandatory_event_type;
```

```
typedef struct {
    enum {
        PCTE_SELECTABLE, PCTE_MANDATORY
    } event_kind;
    union {
        Pcte_selectable_event_type selectable_event_type;
        Pcte_mandatory_event_type mandatory_event_type;
    } event_type;
} Pcte_event_type;
```

```
/* Pcte_event_type corresponds to the PCTE datatypes */
/* Selectable_event_type and Mandatory_event_type. */
```

```
typedef enum {
    PCTE_FAILURE, PCTE_SUCCESS, PCTE_ANY_CODE
} Pcte_selected_return_code;
```

```
typedef Pcte_selected_return_code Pcte_return_code;
```

```
typedef struct {
    Pcte_group_identifier user;
    Pcte_time time;
    Pcte_exact_identifier workstation;
    Pcte_event_type type;
    Pcte_return_code return_code;
    Pcte_exact_identifier process;
    Pcte_exact_identifier object;
} Pcte_object_auditing_record;
```

```
typedef struct {
    Pcte_group_identifier    user;
    Pcte_time                time;
    Pcte_exact_identifier    workstation;
    Pcte_event_type          type;
    Pcte_return_code          return_code;
    Pcte_exact_identifier    process;
    Pcte_exact_identifier    new_process;
    Pcte_exact_identifier    exploited_object;
} Pcte_exploit_auditing_record;
```

```
typedef struct {
    Pcte_group_identifier    user;
    Pcte_time                time;
    Pcte_exact_identifier    workstation;
    Pcte_event_type          type;
    Pcte_return_code          return_code;
    Pcte_exact_identifier    process;
    Pcte_string              text;
} Pcte_information_auditing_record;
```

```
typedef struct {
    Pcte_group_identifier    user;
    Pcte_time                time;
    Pcte_exact_identifier    workstation;
    Pcte_event_type          type;
    Pcte_return_code          return_code;
    Pcte_exact_identifier    process;
    Pcte_exact_identifier    source;
    Pcte_exact_identifier    destination;
} Pcte_copy_auditing_record;
```

```
typedef struct {
    Pcte_group_identifier    user;
    Pcte_time                time;
    Pcte_exact_identifier    workstation;
    Pcte_event_type          type;
    Pcte_return_code          return_code;
    Pcte_exact_identifier    process;
    Pcte_exact_identifier    group;
} Pcte_security_auditing_record;
```

```

typedef struct {
    enum {
        PCTE_OBJECT_RECORD, PCTE_EXPLOIT_RECORD,
        PCTE_INFORMATION_RECORD, PCTE_COPY_RECORD,
        PCTE_SECURITY_RECORD
    } type;
    union {
        Pcte_object_auditing_record      object;
        Pcte_exploit_auditing_record      exploit;
        Pcte_information_auditing_record  information;
        Pcte_copy_auditing_record         copy;
        Pcte_security_auditing_record     security;
    } record;
} Pcte_auditing_record;

typedef enum {
    PCTE_ENABLED, PCTE_DISABLED
} Pcte_audit_status;

typedef struct {
    Pcte_selectable_event_type  selectable_event_type;
    Pcte_selected_return_code   return_code;
} Pcte_general_criterion;

typedef struct {
    Pcte_selectable_event_type  selectable_event_type;
    Pcte_group_identifier       user;
} Pcte_user_criterion;

typedef struct {
    Pcte_selectable_event_type  selectable_event_type;
    Pcte_security_label         security_label;
} Pcte_confidentiality_criterion;

typedef Pcte_confidentiality_criterion Pcte_integrity_criterion;

typedef struct {
    Pcte_selectable_event_type  selectable_event_type;
    Pcte_object_reference       object;
} Pcte_object_criterion;

typedef enum {
    PCTE_GENERAL, PCTE_USER_DEPENDENT,
    PCTE_CONFIDENTIALITY_DEPENDENT,
    PCTE_INTEGRITY_DEPENDENT, PCTE_OBJECT_DEPENDENT
} Pcte_criterion_type;

```

```
typedef struct {
    Pcte_criterion_type type;
    union {
        Pcte_general_criterion      general;
        Pcte_user_criterion          user;
        Pcte_confidentiality_criterion confidentiality;
        Pcte_integrity_criterion     integrity;
        Pcte_object_criterion        object;
    } criterion;
} Pcte_selection_criterion;

typedef Pcte_selection_criterion Pcte_specific_criterion;

typedef struct {
    Pcte_criterion_type type;
    union {
        Pcte_general_criteria      general;
        Pcte_user_criteria          user;
        Pcte_confidentiality_criteria confidentiality;
        Pcte_integrity_criteria     integrity;
        Pcte_object_criteria        object;
    } criteria;
} Pcte_criteria;
```

21.2 Auditing Operations

```
/* 21.2.1 AUDIT_ADD_CRITERION */
Pcte_error_type Pcte_audit_add_criterion (
    Pcte_object_reference    station,
    Pcte_selection_criterion *criterion
);

/* 21.2.2 AUDIT_FILE_COPY_AND_RESET */
Pcte_error_type Pcte_audit_file_copy_and_reset (
    Pcte_object_reference    source,
    Pcte_object_reference    destination
);

/* 21.2.3 AUDIT_FILE_READ */
Pcte_error_type Pcte_audit_file_read (
    Pcte_object_reference    audit_file,
    Pcte_audit_file          *records
);
```

/* 21.2.4 AUDIT_GET_CRITERIA */

```
Pcte_error_type Pcte_audit_get_criteria (
    Pcte_object_reference    station,
    Pcte_criterion_type      criterion_type,
    Pcte_criteria            *criteria
);
```

/* 21.2.5 AUDIT_GET_STATUS */

```
Pcte_error_type Pcte_audit_get_status (
    Pcte_object_reference    station,
    Pcte_audit_status        *status
);
```

/* 21.2.6 AUDIT_RECORD_WRITE */

```
Pcte_error_type Pcte_auditing_record_write (
    Pcte_string              *text
);
```

/* 21.2.7 AUDIT_REMOVE_CRITERION */

```
Pcte_error_type Pcte_audit_remove_criterion (
    Pcte_object_reference    station,
    Pcte_specific_criterion  *criterion
);
```

```
/*      If a value of type general criterion is passed to criterion then the error */
/*      PCTE_VALUE_OUT_OF_RANGE is raised. */
/* */
```

```
Pcte_error_type Pcte_audit_remove_criterion_of_event_type (
    Pcte_object_reference    station,
    Pcte_selectable_event_type criterion
);
```

```
/*      The effect specifying criterion as a specific criterion to the abstract */
/*      operation is achieved by the operation Pcte_audit_remove_criterion. The */
/*      effect specifying criterion as a selectable event type to the abstract */
/*      operation is achieved by the operation */
/*      Pcte_audit_remove_criterion_of_event_type. */
```

/* 21.2.8 AUDIT_SELECTION_CLEAR */

```
Pcte_error_type Pcte_audit_selection_clear (
    Pcte_object_reference    station
);
```

/* 21.2.9 AUDIT_SWITCH_OFF_SELECTION */

```
Pcte_error_type Pcte_audit_switch_off_selection (
    Pcte_object_reference    station
);
```

```

/* 21.2.10 AUDIT_SWITCH_ON_SELECTION */

Pcte_error_type Pcte_audit_switch_on_selection (
    Pcte_object_reference    station
);

#endif /* !PCTE_AUDITING_INCLUDED */

```

22 Accounting

```

/* The header <Pcte/accounting.h> */

#ifndef PCTE_ACCOUNTING_INCLUDED
#define PCTE_ACCOUNTING_INCLUDED 1

#include <Pcte/types.h>
#include <Pcte/references.h>
#include <Pcte/sequences.h>
#include <Pcte/discretionary.h>

```

22.1 Accounting Datatypes

```

typedef Pcte_natural Pcte_consumer_identifier;

typedef Pcte_natural Pcte_resource_identifier;

typedef enum {
    PCTE_WORKSTATION, PCTE_FILE, PCTE_PIPE, PCTE_DEVICE,
    PCTE_STATIC_CONTEXT, PCTE_SDS, PCTE_MESSAGE_QUEUE,
    PCTE_INFORMATION
} Pcte_resource_kind;

typedef struct {
    Pcte_group_identifier    security_user;
    Pcte_group_identifier    adopted_user_group;
    Pcte_exact_identifier    consumer_group;
    Pcte_exact_identifier    resource_group;
    Pcte_resource_kind        resource_kind;
    Pcte_time                start_time;
    Pcte_float               duration;
    Pcte_float               cpu_time;
    Pcte_float               sys_time;
} Pcte_workstation_accounting_record;

typedef Pcte_workstation_accounting_record
    Pcte_static_context_accounting_record;

```

```
typedef struct {
    Pcte_group_identifier security_user;
    Pcte_group_identifier adopted_user_group;
    Pcte_exact_identifier consumer_group;
    Pcte_exact_identifier resource_group;
    Pcte_resource_kind resource_kind;
    Pcte_time start_time;
} Pcte_sds_accounting_record;
```

```
typedef struct {
    Pcte_group_identifier security_user;
    Pcte_group_identifier adopted_user_group;
    Pcte_exact_identifier consumer_group;
    Pcte_exact_identifier resource_group;
    Pcte_resource_kind resource_kind;
    Pcte_time start_time;
    Pcte_float duration;
    Pcte_natural read_count;
    Pcte_natural write_count;
    Pcte_natural read_size;
    Pcte_natural write_size;
} Pcte_device_accounting_record;
```

```
typedef Pcte_device_accounting_record Pcte_file_accounting_record;
```

```
typedef Pcte_device_accounting_record Pcte_pipe_accounting_record;
```

```
typedef enum {
    PCTE_SEND, PCTE_RECEIVE, PCTE_RESERVE
} Pcte_operation_kind;
```

```
typedef struct {
    Pcte_group_identifier security_user;
    Pcte_group_identifier adopted_user_group;
    Pcte_exact_identifier consumer_group;
    Pcte_exact_identifier resource_group;
    Pcte_resource_kind resource_kind;
    Pcte_time start_time;
    Pcte_operation_kind operation;
    Pcte_natural message_size;
} Pcte_message_queue_accounting_record;
```

```

typedef struct {
    Pcte_group_identifier security_user;
    Pcte_group_identifier adopted_user_group;
    Pcte_exact_identifier consumer_group;
    Pcte_exact_identifier resource_group;
    Pcte_resource_kind resource_kind;
    Pcte_time start_time;
    Pcte_string information;
} Pcte_information_accounting_record;

typedef struct {
    Pcte_resource_kind resource_kind;
    union {
        Pcte_workstation_accounting_record workstation;
        Pcte_static_context_accounting_record static_context;
        Pcte_sds_accounting_record sds;
        Pcte_device_accounting_record device;
        Pcte_file_accounting_record file;
        Pcte_pipe_accounting_record pipe;
        Pcte_message_queue_accounting_record message_queue;
        Pcte_information_accounting_record information;
    } resource;
} Pcte_accounting_record;

```

22.2 Accounting Administration Operations

/* 22.2.1 ACCOUNTING_LOG_COPY_AND_RESET */

```

Pcte_error_type Pcte_accounting_log_copy_and_reset (
    Pcte_object_reference source_log,
    Pcte_object_reference destination_log
);

```

/* 22.2.2 ACCOUNTING_LOG_READ */

```

Pcte_error_type Pcte_accounting_log_read (
    Pcte_object_reference log,
    Pcte_accounting_log *records
);

```

/* 22.2.3 ACCOUNTING_OFF */

```

Pcte_error_type Pcte_accounting_off (
    Pcte_object_reference station
);

```

/* 22.2.4 ACCOUNTING_ON */

```
Pcte_error_type Pcte_accounting_on (  
    Pcte_object_reference    log,  
    Pcte_object_reference    station  
);
```

/* 22.2.5 ACCOUNTING_RECORD_WRITE */

```
Pcte_error_type Pcte_accounting_record_write (  
    Pcte_object_reference    log,  
    Pcte_string              *information  
);
```

/* 22.2.6 CONSUMER_GROUP_INITIALIZE */

```
Pcte_error_type Pcte_consumer_group_initialize (  
    Pcte_object_reference    group,  
    Pcte_consumer_identifier *identifier  
);
```

/* 22.2.7 CONSUMER_GROUP_REMOVE */

```
Pcte_error_type Pcte_consumer_group_remove (  
    Pcte_object_reference    group  
);
```

/* 22.2.8 RESOURCE_GROUP_ADD_OBJECT */

```
Pcte_error_type Pcte_resource_group_add_object (  
    Pcte_object_reference    object,  
    Pcte_object_reference    group  
);
```

/* 22.2.9 RESOURCE_GROUP_INITIALIZE */

```
Pcte_error_type Pcte_resource_group_initialize (  
    Pcte_object_reference    group,  
    Pcte_resource_identifier *identifier  
);
```

/* 22.2.10 RESOURCE_GROUP_REMOVE */

```
Pcte_error_type Pcte_resource_group_remove (  
    Pcte_object_reference    group  
);
```

/* 22.2.11 RESOURCE_GROUP_REMOVE_OBJECT */

```
Pcte_error_type Pcte_resource_group_remove_object (  
    Pcte_object_reference    object,  
    Pcte_object_reference    group  
);
```

22.3 Consumer Identity Operations

```

/* 22.3.1 PROCESS_SET_CONSUMER_IDENTITY */
Pcte_error_type Pcte_process_set_consumer_identity (
    Pcte_object_reference    group
);

/* 22.3.2 PROCESS_UNSET_CONSUMER_IDENTITY */
Pcte_error_type Pcte_process_unset_consumer_identity (
);

#endif /* !PCTE_ACCOUNTING_INCLUDED */

```

23 References

```

/* The header <Pcte/references.h> */

#ifndef PCTE_REFERENCES_INCLUDED
#define PCTE_REFERENCES_INCLUDED 1

#include <stdio.h>
#include <Pcte/types.h>

```

23.1 Reference Datatypes

```

typedef void *Pcte_object_reference;
#define Pcte_null_object_reference (Pcte_object_reference) NULL

typedef void *Pcte_type_reference;
#define Pcte_null_type_reference (Pcte_type_reference) NULL

typedef Pcte_type_reference Pcte_attribute_reference;

typedef void *Pcte_link_reference;
#define Pcte_null_link_reference (Pcte_link_reference) NULL

typedef enum {
    PCTE_NOW, PCTE_FIRST_USE, PCTE EVERY_USE
} Pcte_evaluation_point;

typedef enum {
    PCTE_INTERNAL, PCTE_EXTERNAL
} Pcte_evaluation_status;

typedef enum {
    PCTE_EQUAL_REF, PCTE_UNEQUAL_REF, PCTE_EXTERNAL_REF
} Pcte_reference_equality;

#define PCTE_MAX_NAME_SIZE <implementation-defined>

typedef Pcte_octet Pcte_name [PCTE_MAX_NAME_SIZE + 1];

```

```

#define PCTE_MAX_TYPE_NAME_SIZE <implementation-defined>
typedef Pcte_octet Pcte_type_name [PCTE_MAX_TYPE_NAME_SIZE + 1];
typedef Pcte_type_name Pcte_attribute_name;
typedef Pcte_type_name Pcte_type_name_in_sds;
#define PCTE_MAX_KEY_SIZE <implementation-defined>
typedef Pcte_octet Pcte_key [PCTE_MAX_KEY_SIZE + 1];
#define PCTE_MAX_LINK_NAME_SIZE <implementation-defined>
typedef Pcte_octet Pcte_link_name [PCTE_MAX_LINK_NAME_SIZE + 1];
typedef Pcte_octet *Pcte_pathname;
typedef Pcte_octet *Pcte_relative_pathname;
typedef struct {
    enum {
        PCTE_NATURAL_KEY, PCTE_STRING_KEY
    } type;
    union {
        Pcte_natural    natural;
        Pcte_key         string;
    } value;
} Pcte_key_value;

```

23.2 Object Reference Operations

```

Pcte_error_type Pcte_pathname_discard (
    Pcte_pathname *pathname
);

/*      Pcte_pathname_discard is used to discard a pathname obtained by      */
/*      Pcte_object_reference_get_path.                                         */

/* 23.2.1 OBJECT_REFERENCE_COPY */

Pcte_error_type Pcte_object_reference_copy (
    Pcte_object_reference    reference,
    Pcte_evaluation_point    point,
    Pcte_object_reference    *new_reference
);

/* 23.2.2 OBJECT_REFERENCE_GET_EVALUATION_POINT */

Pcte_error_type Pcte_object_reference_get_evaluation_point (
    Pcte_object_reference    reference,
    Pcte_evaluation_point    *point
);

```

/* 23.2.3 OBJECT_REFERENCE_GET_PATH */

```
Pcte_error_type Pcte_object_reference_get_path (
    Pcte_object_reference    reference,
    Pcte_pathname            *pathname
);
```

```
/*    As it is not possible to determine the size of the returned pathname    */
/*    before executing this operation, in this case the implementation allocates */
/*    memory for the returned pathname, which is a native C language string    */
/*    terminated with a NUL character. The returned pathname can be            */
/*    discarded using Pcte_pathname_discard.                                    */
```

/* 23.2.4 OBJECT_REFERENCE_GET_STATUS */

```
Pcte_error_type Pcte_object_reference_get_status (
    Pcte_object_reference    reference,
    Pcte_evaluation_status   *status
);
```

/* 23.2.5 OBJECT_REFERENCE_SET_ABSOLUTE */

```
Pcte_error_type Pcte_object_reference_set_absolute (
    Pcte_pathname            pathname,
    Pcte_evaluation_point    point,
    Pcte_object_reference    *new_reference
);
```

/* 23.2.6 OBJECT_REFERENCE_SET_RELATIVE */

```
Pcte_error_type Pcte_object_reference_set_relative (
    Pcte_object_reference    reference,
    Pcte_relative_pathname   pathname,
    Pcte_evaluation_point    point,
    Pcte_object_reference    *new_reference
);
```

/* 23.2.7 OBJECT_REFERENCE_UNSET */

```
Pcte_error_type Pcte_object_reference_unset (
    Pcte_object_reference    *reference
);
```

```
/*    A null pointer is returned in reference.                                */
```

/* 23.2.8 OBJECT_REFERENCES_ARE_EQUAL */

```
Pcte_error_type Pcte_object_references_are_equal (
    Pcte_object_reference    first_reference,
    Pcte_object_reference    second_reference,
    Pcte_reference_equality   *equal
);
```

23.3 Link Reference Operations

/* 23.3.1 LINK_REFERENCE_COPY */

```
Pcte_error_type Pcte_link_reference_copy (
    Pcte_link_reference    link_reference,
    Pcte_evaluation_point  point,
    Pcte_link_reference    *new_link_reference
);
```

/* 23.3.2 LINK_REFERENCE_GET_EVALUATION_POINT */

```
Pcte_error_type Pcte_link_reference_get_evaluation_point (
    Pcte_link_reference    link_reference,
    Pcte_evaluation_point  *point
);
```

/* 23.3.3 LINK_REFERENCE_GET_KEY */

```
Pcte_error_type Pcte_link_reference_get_key (
    Pcte_link_reference    link_reference,
    Pcte_key               key
);
```

/* 23.3.4 LINK_REFERENCE_GET_KEY_VALUE */

```
Pcte_error_type Pcte_link_reference_get_key_value (
    Pcte_link_reference    link_reference,
    Pcte_natural           index,
    Pcte_key_value         *key_value
);
```

```
/* If the abstract operations returns a value of type Natural, */
/* key_value.type is set to PCTE_NATURAL_KEY and */
/* key_value.natural contains the value of that key attribute. Otherwise */
/* key_value.type is set to PCTE_STRING_KEY and key_value.string */
/* contains the value of that key attribute. */
```

/* 23.3.5 LINK_REFERENCE_GET_NAME */

```
Pcte_error_type Pcte_link_reference_get_name (
    Pcte_link_reference    link_reference,
    Pcte_link_name         link_name
);
```

/* 23.3.6 LINK_REFERENCE_GET_STATUS */

```
Pcte_error_type Pcte_link_reference_get_status (
    Pcte_link_reference    link_reference,
    Pcte_evaluation_status *status
);
```

```
/* 23.3.7 LINK_REFERENCE_GET_TYPE */
```

```
Pcte_error_type Pcte_link_reference_get_type (
    Pcte_link_reference    link_reference,
    Pcte_type_reference    *type_reference
);
```

```
/* 23.3.8 LINK_REFERENCE_SET */
```

```
Pcte_error_type Pcte_link_reference_set_from_name (
    Pcte_link_name        link_name,
    Pcte_evaluation_point point,
    Pcte_link_reference    *new_link_reference
);
```

```
Pcte_error_type Pcte_link_reference_set_from_type (
    Pcte_type_reference    type,
    Pcte_evaluation_point point,
    Pcte_link_reference    *new_link_reference
);
```

```
Pcte_error_type Pcte_link_reference_set (
    Pcte_key              key,
    Pcte_type_reference    type,
    Pcte_evaluation_point point,
    Pcte_link_reference    *new_link_reference
);
```

```
/* The effect of providing a value of type Link_name to link_name in the */
/* abstract operation is achieved by the operation */
/* Pcte_link_reference_set_from_name. The effect of providing a value of */
/* type Type_reference to link_name in the abstract operation is achieved */
/* by the operation Pcte_link_reference_set_from_type. The effect of */
/* providing a value of type (Key * Type_reference) to link_name in the */
/* abstract operation is achieved by the operation Pcte_link_reference_set. */
/* */
```

```
/* 23.3.9 LINK_REFERENCE_UNSET */
```

```
Pcte_error_type Pcte_link_reference_unset (
    Pcte_link_reference    *link_reference
);
```

```
/* A null pointer is returned in link_reference. */
```

```
/* 23.3.10 LINK_REFERENCES_ARE_EQUAL */
```

```
Pcte_error_type Pcte_link_references_are_equal (
    Pcte_link_reference    first_link_reference,
    Pcte_link_reference    second_link_reference,
    Pcte_reference_equality *equal
);
```

23.4 Type Reference Operations

/* 23.4.1 TYPE_REFERENCE_COPY */

```
Pcte_error_type Pcte_type_reference_copy (
    Pcte_type_reference    type_reference,
    Pcte_evaluation_point  point,
    Pcte_type_reference    *new_type_reference
);
```

/* 23.4.2 TYPE_REFERENCE_GET_EVALUATION_POINT */

```
Pcte_error_type Pcte_type_reference_get_evaluation_point (
    Pcte_type_reference    type_reference,
    Pcte_evaluation_point  *point
);
```

/* 23.4.3 TYPE_REFERENCE_GET_IDENTIFIER */

```
Pcte_error_type Pcte_type_reference_get_identifier (
    Pcte_type_reference    type_reference,
    Pcte_type_name        type_identifier
);
```

/* 23.4.4 TYPE_REFERENCE_GET_NAME */

```
Pcte_error_type Pcte_type_reference_get_name (
    Pcte_object_reference  sds,
    Pcte_type_reference    type_reference,
    Pcte_type_name        type_name
);
```

/* The effect of not providing the optional parameter *sds* to the abstract operation is achieved by specifying *sds* as *Pcte_null_object_reference*. */

/* 23.4.5 TYPE_REFERENCE_GET_STATUS */

```
Pcte_error_type Pcte_type_reference_get_status (
    Pcte_type_reference    type_reference,
    Pcte_evaluation_status *status
);
```

/* 23.4.6 TYPE_REFERENCE_SET */

```
Pcte_error_type Pcte_type_reference_set (
    Pcte_type_name        type_name,
    Pcte_evaluation_point  point,
    Pcte_type_reference    *new_type_reference
);
```

```

/* 23.4.7 TYPE_REFERENCE_UNSET */
Pcte_error_type Pcte_type_reference_unset (
    Pcte_type_reference    *type_reference
);
/*      A null pointer is returned in type_reference. */
/* 23.4.8 TYPE_REFERENCES_ARE_EQUAL */
Pcte_error_type Pcte_type_references_are_equal (
    Pcte_type_reference    first_type_reference,
    Pcte_type_reference    second_type_reference,
    Pcte_reference_equality *equal
);
#endif /* !PCTE_REFERENCES_INCLUDED */

```

24 Implementation limits

```

/* The header <Pcte/limits.h> */
#ifndef PCTE_LIMITS_INCLUDED
#define PCTE_LIMITS_INCLUDED 1
#include <Pcte/types.h>

```

24.1 Implementation Limit Datatypes

```

/*      The implementation limits MAX_NAME_SIZE, MAX_KEY_SIZE, and
/*      MAX_LINK_NAME_SIZE, which define the maximum size of the
/*      corresponding texts Pcte_name, Pcte_key, and Pcte_link_name, are
/*      defined in 23.1. All other implementation limits are defined in this
/*      clause.
/*
/*
typedef enum {
    PCTE_STANDARD, PCTE_IMPLEMENTATION, PCTE_REMAINING
} Pcte_limit_category;

/*      An implementation of this binding must return three sets of those
/*      implementation limits which are defined in this clause:
/*
/*      • STANDARD: The value specified in ISO/IEC 13719-1
/*
/*      • IMPLEMENTATION: The value supported by the implementation
/*
/*      • REMAINING: Where appropriate, the value remaining at the
/*      current time (after the usage of some resources).
/*

```