
**Information technology — Generic coding
of moving pictures and associated audio
information: Video**

AMENDMENT 2: Support for colour spaces

*Technologies de l'information — Codage générique des images
animées et du son associé: Données vidéo*

AMENDEMENT 2: Prise en charge des espaces chromatiques

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

© ISO/IEC 2007

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of the joint technical committee is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

Amendment 2 to ISO/IEC 13818-2:2000 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 29, *Coding of audio, picture, multimedia and hypermedia information*, in collaboration with ITU-T. The identical text is published as ITU-T Rec. H.262 (2000)/Amd.2 (01/2007).

This corrected version incorporates a correction to the edition number on the cover page, replacing "First edition" with "Second edition".

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 13818-2:2000/AMD2:2007

INTERNATIONAL STANDARD
ITU-T RECOMMENDATION

Information technology – Generic coding of moving pictures and
associated audio information: Video

Amendment 2

Support for colour spaces

1) Subclause 4.1

Add the following definitions at the end of subclause 4.1:

Floor() the largest integer less than or equal to the argument.

Round() $\text{Sign}(x) * \text{Floor}(\text{Abs}(x) + 0.5)$, for an argument x

2) Table 6-7

Replace Table 6-7 with:

Table 6-7 – Colour primaries

Value	Primaries			Informative remarks
0	Forbidden			
1	primary	x	y	ITU-R Rec. BT.709-5
	green	0.300	0.600	ITU-R Rec. BT.1361 conventional colour gamut system or extended colour gamut system
	blue	0.150	0.060	IEC 61966-2-4
	red	0.640	0.330	Society of Motion Picture and Television Engineers
	white D65	0.3127	0.3290	RP 177 Annex B
2	Unspecified			Image characteristics are unknown or are determined by the application
3	Reserved			For future use by ITU-T ISO/IEC
4	primary	x	y	ITU-R Rec. BT.470-6 System M (historical)
	green	0.21	0.71	United States National Television System Committee 1953
	blue	0.14	0.08	Recommendation for transmission standards for colour television
	red	0.67	0.33	United States Federal Communications Commission Title 47 Code of Federal Regulations (2004) 73.682 (a) (20)
	white C	0.310	0.316	
5	primary	x	y	ITU-R Rec. BT.1700 625 PAL or 625 SECAM
	green	0.29	0.60	ITU-R Rec. BT.1358 625
	blue	0.15	0.06	ITU-R Rec. BT.470-6 System B, G (historical)
	red	0.64	0.33	ITU-R Rec. BT.601-6 625
	white D65	0.3127	0.3290	
6	primary	x	y	ITU-R Rec. BT.1700 NTSC
	green	0.310	0.595	ITU-R Rec. BT.1358 525
	blue	0.155	0.070	Society of Motion Picture and Television Engineers 170M
	red	0.630	0.340	(functionally the same as the value 7)
	white D65	0.3127	0.3290	ITU-R Rec. BT.601-6 525

Table 6-7 – Colour primaries

Value	Primaries	Informative remarks
7	primary x y green 0.310 0.595 blue 0.155 0.070 red 0.630 0.340 white D65 0.3127 0.3290	Society of Motion Picture and Television Engineers 240M (functionally the same as the value 6)
8-255	Reserved	For future use by ITU-T ISO/IEC

3) Table 6-8

Replace Table 6-8 with:

Table 6-8 – Transfer characteristics

Value	Transfer characteristic	Informative remarks
0	Forbidden	
1	$V = 1.099 L_c^{0.45} - 0.099$ for $1 \geq L_c \geq 0.018$ $V = 4.500 L_c$ for $0.018 > L_c \geq 0$	ITU-R Rec. BT.709-5 ITU-R Rec. BT.1361 conventional colour gamut system (functionally the same as the value 6)
2	Unspecified	Image characteristics are unknown or are determined by the application.
3	Reserved	For future use by ITU-T ISO/IEC
4	Assumed display gamma 2.2	ITU-R Rec. BT.470-6 System M (historical) United States National Television System Committee 1953 Recommendation for transmission standards for colour television United States Federal Communications Commission Title 47 Code of Federal Regulations (2004) 73.682 (a) (20)
5	Assumed display gamma 2.8	ITU-R Rec. BT.1700 (2007 Revision) 625 PAL or 625 SECAM ITU-R Rec. BT.470-6 System B, G (historical)
6	$V = 1.099 L_c^{0.45} - 0.099$ for $1 \geq L_c \geq 0.018$ $V = 4.500 L_c$ for $0.018 > L_c \geq 0$	ITU-R Rec. BT.1700 NTSC ITU-R Rec. BT.1358 525 or 625 Society of Motion Picture and Television Engineers 170M (functionally the same as the value 1) ITU-R Rec. BT.601-6 525 or 625
7	$V = 1.1115 L_c^{0.45} - 0.1115$ for $L_c \geq 0.0228$ $V = 4.0 L_c$ for $0.0228 > L_c$	Society of Motion Picture and Television Engineers 240M
8	$V = L_c$	Linear transfer characteristics
9	$V = 1.0 - \log_{10}(L_c) + 2$ for $1 \geq L_c \geq 0.01$ $V = 0.0$ for $0.01 > L_c \geq 0$	Logarithmic transfer characteristic (100:1 range)
10	$V = 1.0 - \log_{10}(L_c) + 2.5$ for $1 \geq L_c \geq 0.0031622777$ $V = 0.0$ for $0.0031622777 > L_c \geq 0$	Logarithmic transfer characteristic (316.22777:1 range)

Table 6-8 – Transfer characteristics

Value	Transfer characteristic	Informative remarks
11	$V = 1.099 L_c^{0.45} - 0.099$ for $L_c \geq 0.018$ $V = 4.500 L_c$ for $0.018 > L_c > -0.018$ $V = -(1.099 (-L_c)^{0.45} - 0.099)$ for $-0.018 \geq L_c$	IEC 61966-2-4
12	$V = 1.099 L_c^{0.45} - 0.099$ for $1.33 > L_c \geq 0.018$ $V = 4.500 L_c$ for $0.018 > L_c \geq -0.0045$ $V = -(1.099 (-4 * L_c)^{0.45} - 0.099) \div 4$ for $-0.0045 > L_c \geq -0.25$	ITU-R Rec. BT.1361 extended colour gamut system
13-255	Reserved	For future use by ITU-T ISO/IEC

4) Subclause 6.3.6 semantics of matrix_coefficients and Table 6-9

Replace semantics of matrix_coefficients and Table 6-9 with:

matrix_coefficients – This 8-bit integer describes the matrix coefficients used in deriving luminance and chrominance signals from the green, blue, and red primaries, and is defined in Table 6-9.

Table 6-9 – Matrix coefficients

Value	Matrix	Informative remarks
0	Forbidden	
1	$E'_Y = 0.7152 E'_G + 0.0722 E'_B + 0.2126 E'_R$ $E'_{PB} = -0.3854 E'_G + 0.5000 E'_B - 0.1146 E'_R$ $E'_{PR} = -0.4542 E'_G - 0.0458 E'_B + 0.5000 E'_R$	ITU-R Rec. BT.709-5 ITU-R Rec. BT.1361 conventional colour gamut system and extended colour gamut system IEC 61966-2-4 xvYCC ₇₀₉ Society of Motion Picture and Television Engineers RP 177 Annex B
2	Unspecified	Image characteristics are unknown or are determined by the application
3	Reserved	For future use by ITU-T ISO/IEC
4	$E'_Y = 0.59 E'_G + 0.11 E'_B + 0.30 E'_R$ $E'_{PB} = -0.331 E'_G + 0.500 E'_B - 0.169 E'_R$ $E'_{PR} = -0.421 E'_G - 0.079 E'_B + 0.500 E'_R$	United States National Television System Committee 1953 Recommendation for transmission standards for colour television United States Federal Communications Commission Title 47 Code of Federal Regulations (2004) 73.682 (a) (20)
5	$E'_Y = 0.5870 E'_G + 0.1140 E'_B + 0.2990 E'_R$ $E'_{PB} = -0.3313 E'_G + 0.5000 E'_B - 0.1687 E'_R$ $E'_{PR} = -0.4187 E'_G - 0.0813 E'_B + 0.5000 E'_R$	ITU-R Rec. BT.1700 625 PAL or 625 SECAM ITU-R Rec. BT.1358 625 IEC 61966-2-4 xvYCC ₆₀₁ ITU-R Rec. BT.470-6 System B, G (historical) (functionally the same as the value 6) ITU-R Rec. BT.601-6 625
6	$E'_Y = 0.5870 E'_G + 0.1140 E'_B + 0.2990 E'_R$ $E'_{PB} = -0.3313 E'_G + 0.5000 E'_B - 0.1687 E'_R$ $E'_{PR} = -0.4187 E'_G - 0.0813 E'_B + 0.5000 E'_R$	ITU-R Rec. BT.1700 NTSC ITU-R Rec. BT.1358 525 Society of Motion Picture and Television Engineers 170M IEC 61966-2-4 xvYCC ₆₀₁ (functionally the same as the value 5) ITU-R Rec. BT.601-6 525

Table 6-9 – Matrix coefficients

Value	Matrix	Informative remarks
7	$E'_Y = 0.701 E'_G + 0.087 E'_B + 0.212 E'_R$ $E'_{PB} = -0.384 E'_G + 0.500 E'_B - 0.116 E'_R$ $E'_{PR} = -0.445 E'_G - 0.055 E'_B + 0.500 E'_R$	Society of Motion Picture and Television Engineers 240M
8	YCgCo	Defined as specified below
9-255	Reserved	For future use by ITU-T ISO/IEC

In Table 6-9:

- When transfer_characteristics is not equal to 11 or 12, E'_R , E'_G and E'_B are analog with values between 0 and 1;
- When transfer_characteristics is equal to 11 (IEC 61966-2-4) or 12 (ITU-R Rec. BT.1361 extended colour gamut system), E'_R , E'_G and E'_B are analog with a larger range not specified in this Recommendation | International Standard;
- Nominal black is considered to have the property $E'_R = 0$, $E'_G = 0$ and $E'_B = 0$;
- Nominal white is considered to have the property $E'_R = 1$, $E'_G = 1$ and $E'_B = 1$;
- If matrix_coefficients is not equal to 8, the following applies:
 - E'_Y is analog with the value 0 associated with nominal black and the value 1 associated with nominal white;
 - E'_{PB} and E'_{PR} are analog with the value 0 associated with both nominal black and nominal white;
 - When transfer_characteristics is not equal to 11 or 12, E'_Y has values between 0 and 1;
 - When transfer_characteristics is not equal to 11 or 12, E'_{PB} and E'_{PR} have values between -0.5 and 0.5;
 - When transfer_characteristics is equal to 11 (IEC 61966-2-4), or 12 (ITU-R Rec. BT.1361 extended colour gamut system), E'_Y , E'_{PB} and E'_{PR} are analog with a larger range not specified in this Recommendation | International Standard;
 - Y , C_b and C_r are related to E'_Y , E'_{PB} and E'_{PR} by the following formulae:

$$\begin{aligned}
 Y &= \max[0, \min[255, \text{Round}((219 * E'_Y)) + 16]] \\
 C_b &= \max[0, \min[255, \text{Round}((224 * E'_{PB})) + 128]] \\
 C_r &= \max[0, \min[255, \text{Round}((224 * E'_{PR})) + 128]]
 \end{aligned}$$

- Otherwise (matrix_coefficients is equal to 8 (YCgCo)), the following applies:

$$\begin{aligned}
 R &= 219 * E'_R + 16 \\
 G &= 219 * E'_G + 16 \\
 B &= 219 * E'_B + 16
 \end{aligned}$$

$$\begin{aligned}
 Y &= \max[0, \min[255, \text{Round}(0.5 * G + 0.25 * (R + B))]] \\
 C_b &= \max[0, \min[255, \text{Round}(0.5 * G - 0.25 * (R + B)) + 128]] \\
 C_r &= \max[0, \min[255, \text{Round}(0.5 * (R - B)) + 128]]
 \end{aligned}$$

NOTE 1 – For purposes of the YCgCo nomenclature used in Table 6-9, C_b and C_r of the above equations may be referred to as C_g and C_o , respectively. The inverse conversion for the above three equations should be computed as:

$$\begin{aligned}
 t &= Y - (C_b - 128) \\
 G &= Y + (C_b - 128) \\
 B &= t - (C_r - 128) \\
 R &= t + (C_r - 128)
 \end{aligned}$$

NOTE 2 – The decoding process given by this Recommendation | International Standard limits output sample values for Y , C_r and C_b to the range [0:255]. Thus, sample values outside the range implied by the above equations may occasionally occur at the output of the decoding process. In particular the sample values 0 and 255 may occur.