INTERNATIONAL STANDARD

ISO/IEC 24709-1

Second edition
2017-11

Information technology — Conformance testing for the biometric application programming interface (BioAPI) —

Part 1: Methods and procedures

Technologies de l'information — Test de conformité pour l'interface de programmation d'applications biométriques (BioAPI) —

Partie 1: Méthodes et procédures

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

Reference number
ISO/IEC 24709-1:2017(E)

© ISO/IEC 2017

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2017, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

© ISO/IEC 2017 – All rights reserved

Contents

Page

Foreword ... **xix**
Introduction ... **xx**
1 Scope ... **1**
2 Normative references ... **1**
3 Terms and definitions ... **1**
4 Abbreviated terms ... **3**
5 Conformance ... **3**
6 Conformance testing methodology ... **4**
6.1 General ... 4
6.1.1 Implementation under test ... 4
6.1.2 Test method ... 5
6.1.3 Standard BioAPI components and standard BioAPI interfaces ... 6
6.1.4 Physical architectures ... 7
6.2 Conformance testing models ... 8
6.3 Abstract test engine ... 13
7 General properties of the assertion language ... **14**
7.1 General ... 14
7.2 Variables ... 17
7.3 Built-in variables ... 18
7.4 Representation of integers ... 18
7.5 Representation of Booleans ... 19
7.6 Representation of universally unique identifiers (UUIDs) ... 19
7.7 Representation of octet strings ... 19
7.8 XML documents ... 20
8 Elements of the assertion language ... **20**
8.1 Element <package> ... 20
8.1.1 Syntax ... 20
8.1.2 Semantics ... 20
8.1.3 Example (non-normative) ... 21
8.2 Element <assertion> (child of <package>) ... 21
8.2.1 Syntax ... 21
8.2.2 Semantics ... 22
8.2.3 Example (non-normative) ... 22
8.3 Element <input> (child of <assertion>) ... 23
8.3.1 Syntax ... 23
8.3.2 Semantics ... 23
8.3.3 Example (non-normative) ... 23
8.4 Element <invoke> (child of <assertion>) ... 23
8.4.1 Syntax ... 23
8.4.2 Semantics ... 24
8.4.3 Example (non-normative) ... 24
8.5 Element <input> (child of <invoke>) ... 24
8.5.1 Syntax ... 24
8.5.2 Semantics ... 25
8.5.3 Example (non-normative) ... 25
8.6 Element <output> (child of <invoke>) ... 25
8.6.1 Syntax ... 25
8.6.2 Semantics ... 26
8.7 Element <return> (child of <invoke>) ... 26
8.7.1 Syntax ... 26
8.7.2 Semantics ... 27

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

8.8 Element <bind> (child of <assertion>) 27
8.8.1 Syntax 27
8.8.2 Semantics 27
8.9 Element <activity> (child of <package>) 28
8.9.1 Syntax 28
8.9.2 Semantics 29
8.9.3 Example (non-normative) 32
8.10 Element <input> (child of <activity>) 35
8.10.1 Syntax 35
8.10.2 Semantics 35
8.11 Element <output> (child of <activity>) 35
8.11.1 Syntax 35
8.11.2 Semantics 35
8.12 Element <set> 36
8.12.1 Syntax 36
8.12.2 Semantics 36
8.13 Element <add> 37
8.13.1 Syntax 37
8.13.2 Semantics 37
8.14 Element <subtract> 38
8.14.1 Syntax 38
8.14.2 Semantics 38
8.15 Element <invoke> (child of <activity>) 39
8.15.1 Syntax 39
8.15.2 Semantics 39
8.15.3 Example (non-normative) 42
8.16 Element <only_if> 42
8.16.1 Syntax 42
8.16.2 Semantics 43
8.17 Element <wait_until> 43
8.17.1 Syntax 43
8.17.2 Semantics 44
8.18 Element <assert_condition> 45
8.18.1 Syntax 45
8.18.2 Semantics 45
8.19 Element <and> 46
8.19.1 Syntax 46
8.19.2 Semantics 46
8.20 Element <or> 47
8.20.1 Syntax 47
8.20.2 Semantics 47
8.21 Element <xor> 47
8.21.1 Syntax 47
8.21.2 Semantics 48
8.22 Element <not> 48
8.22.1 Syntax 48
8.22.2 Semantics 48
8.23 Element <equal_to> 49
8.23.1 Syntax 49
8.23.2 Semantics 49
8.24 Element <not_equal_to> 50
8.24.1 Syntax 50
8.24.2 Semantics 50
8.25 Element <greater_than> 50
8.25.1 Syntax 50
8.25.2 Semantics 50
8.26 Element <greater_than_or_equal_to> 50
8.26.1 Syntax 50

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

8.26.2 Semantics 50
8.27 Element <less_than> 50
8.27.1 Syntax 50
8.27.2 Semantics 50
8.28 Element <less_than_or_equal_to> 51
8.28.1 Syntax 51
8.28.2 Semantics 51
8.29 Element <same_as> 51
8.29.1 Syntax 51
8.29.2 Semantics 51
8.30 Element <not_same_as> 52
8.30.1 Syntax 52
8.30.2 Semantics 52
8.31 Element <existing> 52
8.31.1 Syntax 52
8.31.2 Semantics 52
8.32 Element <not_existing> 53
8.32.1 Syntax 53
8.32.2 Semantics 53

9 Standard interface functions 53
9.1 General 53
9.2 Parameter groups 60
9.2.1 General 60
9.2.2 Parameter group “Biometric type” 60
9.2.3 Parameter group “Operations” 62
9.2.4 Parameter group “Options” 64
9.2.5 Parameter group “Events” 66
9.2.6 Parameter group “Biometric data type” 67
9.2.7 Parameter group “Biometric subtype” 68
9.2.8 Parameter group “Date” 69
9.2.9 Parameter group “Date and time” 70
9.2.10 Parameter group “Framework schema” 71
9.2.11 Parameter group “BSP schema” 72
9.2.12 Parameter group “BFP schema” 76
9.2.13 Parameter group “Unit schema” 78
9.2.14 Parameter group “BIR header” 81
9.2.15 Parameter group “BIR” 84
9.2.16 Parameter group “Input BIR” 85
9.2.17 Parameter group “Identify population” 86
9.2.18 Parameter group “Candidate” 88
9.2.19 Parameter group “GUI state” 90
9.2.20 Parameter group “Access type” 90
9.2.21 Parameter group “GUI Event Subscription” 91
9.2.22 Parameter group “Key Information” 92
9.2.23 Parameter group “Key Transport” 93
9.2.24 Parameter group “MAC Algorithm Information” 93
9.2.25 Parameter group “Security Options Mask” 94
9.2.26 Parameter group “Security Profile” 95
9.2.27 Parameter group “ACBio parameters” 97
9.2.28 Parameter group “BFP List Element parameters” 98
9.2.29 Parameter group “Biometric subtype mask” 98
9.2.30 Parameter group “ENCRYPTION INFO” 100
9.3 BioAPI_Init 101
9.3.1 Function invocation scheme 101
9.3.2 Constraints on the parameters 101
9.3.3 Function invocation input 101
9.3.4 Function invocation output 101
9.3.5 Bound activity invocation input 101

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.3.6 Bound activity invocation output 102
9.4 BioAPI_Terminate 102
9.4.1 Function invocation scheme 102
9.4.2 Constraints on the parameters 102
9.4.3 Function invocation input 102
9.4.4 Function invocation output 102
9.4.5 Bound activity invocation input 102
9.4.6 Bound activity invocation output 102
9.5 BioAPI_GetFrameworkInfo 103
9.5.1 Function invocation scheme 103
9.5.2 Constraints on the parameters 103
9.5.3 Function invocation input 103
9.5.4 Function invocation output 103
9.5.5 Bound activity invocation input 104
9.5.6 Bound activity invocation output 104
9.6 BioAPI_EnumBSPs 104
9.6.1 Function invocation scheme 104
9.6.2 Constraints on the parameters 105
9.6.3 Function invocation input 105
9.6.4 Function invocation output 105
9.6.5 Bound activity invocation input 105
9.6.6 Bound activity invocation output 106
9.7 BioAPI_BSPLoad 106
9.7.1 Function invocation scheme 106
9.7.2 Constraints on the parameters 106
9.7.3 Function invocation input 106
9.7.4 Function invocation output 107
9.7.5 Bound activity invocation input 107
9.7.6 Bound activity invocation output 107
9.8 BioAPI_BSPUnload 107
9.8.1 Function invocation scheme 107
9.8.2 Constraints on the parameters 108
9.8.3 Function invocation input 108
9.8.4 Function invocation output 108
9.8.5 Bound activity invocation input 108
9.8.6 Bound activity invocation output 109
9.9 BioAPI_BSPAttach 109
9.9.1 Function invocation scheme 109
9.9.2 Constraints on the parameters 109
9.9.3 Function invocation input 110
9.9.4 Function invocation output 110
9.9.5 Bound activity invocation input 110
9.9.6 Bound activity invocation output 111
9.10 BioAPI_BSPDetach 111
9.10.1 Function invocation scheme 111
9.10.2 Constraints on the parameters 111
9.10.3 Function invocation input 111
9.10.4 Function invocation output 112
9.10.5 Bound activity invocation input 112
9.10.6 Bound activity invocation output 112
9.11 BioAPI_QueryUnits 112
9.11.1 Function invocation scheme 112
9.11.2 Constraints on the parameters 113
9.11.3 Function invocation input 113
9.11.4 Function invocation output 114
9.11.5 Bound activity invocation input 114
9.11.6 Bound activity invocation output 114
9.12 BioAPI_EnumBFPs 114

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.12.1 Function invocation scheme 114
9.12.2 Constraints on the parameters 115
9.12.3 Function invocation input 115
9.12.4 Function invocation output 116
9.12.5 Bound activity invocation input 116
9.12.6 Bound activity invocation output 116
9.13 BioAPI_QueryBFPs 116
9.13.1 Function invocation scheme 116
9.13.2 Constraints on the parameters 117
9.13.3 Function invocation input 117
9.13.4 Function invocation output 118
9.13.5 Bound activity invocation input 118
9.13.6 Bound activity invocation output 118
9.14 BioAPI_ControlUnit 118
9.14.1 Function invocation scheme 118
9.14.2 Constraints on the parameters 119
9.14.3 Function invocation input 119
9.14.4 Function invocation output 119
9.14.5 Bound activity invocation input 120
9.14.6 Bound activity invocation output 120
9.15 BioAPI_LinkToEndpoint 120
9.15.1 Function invocation scheme 120
9.15.2 Constraints on the parameter 120
9.15.3 Function invocation input 121
9.15.4 Function invocation output 121
9.15.5 Bound activity invocation input 121
9.15.6 Bound activity invocation output 121
9.16 BioAPI_UnlinkFromEndpoint 121
9.16.1 Function invocation scheme 121
9.16.2 Constraints on the parameter 121
9.16.3 Function invocation input 122
9.16.4 Function invocation output 122
9.16.5 Bound activity invocation input 122
9.16.6 Bound activity invocation output 122
9.17 BioAPI_EnumFrameworks 122
9.17.1 Function invocation scheme 122
9.17.2 Constraints on the parameters 123
9.17.3 Function invocation input 123
9.17.4 Function invocation output 123
9.17.5 Bound activity invocation input 123
9.17.6 Bound activity invocation output 123
9.18 BioAPI_FreeBIRHandle 124
9.18.1 Function invocation scheme 124
9.18.2 Constraints on the parameters 124
9.18.3 Function invocation input 124
9.18.4 Function invocation output 124
9.18.5 Bound activity invocation input 124
9.18.6 Bound activity invocation output 125
9.19 BioAPI_GetBIRFromHandle 125
9.19.1 Function invocation scheme 125
9.19.2 Constraints on the parameters 125
9.19.3 Function invocation input 126
9.19.4 Function invocation output 126
9.19.5 Bound activity invocation input 126
9.19.6 Bound activity invocation output 126
9.20 BioAPI_GetHeaderFromHandle 126
9.20.1 Function invocation scheme 126
9.20.2 Constraints on the parameters 127

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.20.3 Function invocation input 127
9.20.4 Function invocation output 127
9.20.5 Bound activity invocation input 128
9.20.6 Bound activity invocation output 128
9.21 BioAPI_EnableEvents 128
9.21.1 Function invocation scheme 128
9.21.2 Constraints on the parameters 128
9.21.3 Function invocation input 129
9.21.4 Function invocation output 129
9.21.5 Bound activity invocation input 129
9.21.6 Bound activity invocation output 129
9.22 BioAPI_NotifyGUIProgressEvent 130
9.22.1 Function invocation scheme 130
9.22.2 Constraints on the parameters 131
9.22.3 Function invocation input 131
9.22.4 Function invocation output 131
9.22.5 Bound activity invocation input 132
9.22.6 Bound activity invocation output 132
9.23 BioAPI_NotifyGUISelectEvent 132
9.23.1 Function invocation scheme 132
9.23.2 Constraints on the parameters 133
9.23.3 Function invocation input 134
9.23.4 Function invocation output 134
9.23.5 Bound activity invocation input 134
9.23.6 Bound activity invocation output 135
9.24 BioAPI_NotifyGUIStateEvent 135
9.24.1 Function invocation scheme 135
9.24.2 Constraints on the parameters 136
9.24.3 Function invocation input 137
9.24.4 Function invocation output 137
9.24.5 Bound activity invocation input 137
9.24.6 Bound activity invocation output 138
9.25 BioAPI_QueryGUIEventSubscriptions 138
9.25.1 Function invocation scheme 138
9.25.2 Constraints on the parameters 139
9.25.3 Function invocation input 139
9.25.4 Function invocation output 139
9.25.5 Bound activity invocation input 139
9.25.6 Bound activity invocation output 139
9.26 BioAPI_RedirectGUIEvents 140
9.26.1 Function invocation scheme 140
9.26.2 Constraints on the parameters 140
9.26.3 Function invocation input 141
9.26.4 Function invocation output 141
9.26.5 Bound activity invocation input 141
9.26.6 Bound activity invocation output 141
9.27 BioAPI_SubscribeToGUIEvents 142
9.27.1 Function invocation scheme 142
9.27.2 Constraints on the parameters 142
9.27.3 Function invocation input 143
9.27.4 Function invocation output 143
9.27.5 Bound activity invocation input 143
9.27.6 Bound activity invocation output 144
9.28 BioAPI_UnredirctGUIEvents 144
9.28.1 Function invocation scheme 144
9.28.2 Constraints on the parameters 144
9.28.3 Function invocation input 145
9.28.4 Function invocation output 145

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.28.5 Bound activity invocation input 145
9.28.6 Bound activity invocation output 145
9.29 BioAPI_UnsubscribeFromGUIEvents 146
9.29.1 Function invocation scheme 146
9.29.2 Constraints on the parameters 146
9.29.3 Function invocation input 147
9.29.4 Function invocation output 147
9.29.5 Bound activity invocation input 147
9.29.6 Bound activity invocation output 147
9.30 BioAPI_SetGUICallbacks 148
9.30.1 Function invocation scheme 148
9.30.2 Constraints on the parameters 148
9.30.3 Function invocation input 148
9.30.4 Function invocation output 149
9.30.5 Bound activity invocation input 149
9.30.6 Bound activity invocation output 149
9.31 BioAPI_Capture 150
9.31.1 Function invocation scheme 150
9.31.2 Constraints on the parameters 150
9.31.3 Function invocation input 151
9.31.4 Function invocation output 151
9.31.5 Bound activity invocation input 151
9.31.6 Bound activity invocation output 152
9.32 BioAPI_CreateTemplate 152
9.32.1 Function invocation scheme 152
9.32.2 Constraints on the parameters 153
9.32.3 Function invocation input 154
9.32.4 Function invocation output 154
9.32.5 Bound activity invocation input 155
9.32.6 Bound activity invocation output 155
9.33 BioAPI_Process 155
9.33.1 Function invocation scheme 155
9.33.2 Constraints on the parameters 156
9.33.3 Function invocation input 156
9.33.4 Function invocation output 157
9.33.5 Bound activity invocation input 157
9.33.6 Bound activity invocation output 157
9.34 BioAPI_ProcessUsingAuxBIRs 158
9.34.1 Function invocation scheme 158
9.34.2 Constraints on the parameters 158
9.34.3 Function invocation input 159
9.34.4 Function invocation output 159
9.34.5 Bound activity invocation input 159
9.34.6 Bound activity invocation output 160
9.35 BioAPI_VerifyMatch 160
9.35.1 Function invocation scheme 160
9.35.2 Constraints on the parameters 161
9.35.3 Function invocation input 162
9.35.4 Function invocation output 162
9.35.5 Bound activity invocation input 163
9.35.6 Bound activity invocation output 163
9.36 BioAPI_VerifyMatchUsingAuxBIRs 163
9.36.1 Function invocation scheme 163
9.36.2 Constraints on the parameters 164
9.36.3 Function invocation input 165
9.36.4 Function invocation output 165
9.36.5 Bound activity invocation input 166
9.36.6 Bound activity invocation output 166

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.37 BioAPI_IdentifyMatch 167
9.37.1 Function invocation scheme 167
9.37.2 Constraints on the parameters 168
9.37.3 Function invocation input 169
9.37.4 Function invocation output 169
9.37.5 Bound activity invocation input 170
9.37.6 Bound activity invocation output 170
9.38 BioAPI_Decide 170
9.38.1 Function invocation scheme 170
9.38.2 Constraints on the parameters 171
9.38.3 Function invocation input 171
9.38.4 Function invocation output 171
9.38.5 Bound activity invocation input 172
9.38.6 Bound activity invocation output 172
9.39 BioAPI_Fuse 172
9.39.1 Function invocation scheme 172
9.39.2 Constraints on the parameters 173
9.39.3 Function invocation input 173
9.39.4 Function invocation output 173
9.39.5 Bound activity invocation input 173
9.39.6 Bound activity invocation output 174
9.40 BioAPI_Enroll 174
9.40.1 Function invocation scheme 174
9.40.2 Constraints on the parameters 175
9.40.3 Function invocation input 176
9.40.4 Function invocation output 176
9.40.5 Bound activity invocation input 177
9.40.6 Bound activity invocation output 177
9.41 BioAPI_Verify 177
9.41.1 Function invocation scheme 177
9.41.2 Constraints on the parameters 178
9.41.3 Function invocation input 179
9.41.4 Function invocation output 179
9.41.5 Bound activity invocation input 180
9.41.6 Bound activity invocation output 181
9.42 BioAPI_Identify 181
9.42.1 Function invocation scheme 181
9.42.2 Constraints on the parameters 182
9.42.3 Function invocation input 183
9.42.4 Function invocation output 183
9.42.5 Bound activity invocation input 184
9.42.6 Bound activity invocation output 184
9.43 BioAPI_Import 184
9.43.1 Function invocation scheme 184
9.43.2 Constraints on the parameters 185
9.43.3 Function invocation input 185
9.43.4 Function invocation output 186
9.43.5 Bound activity invocation input 186
9.43.6 Bound activity invocation output 187
9.44 BioAPI_Export 187
9.44.1 Function invocation scheme 187
9.44.2 Constraints on the parameters 187
9.44.3 Function invocation input 188
9.44.4 Function invocation output 188
9.44.5 Bound activity invocation input 188
9.44.6 Bound activity invocation output 189
9.45 BioAPI_PresetIdentifyPopulation 189
9.45.1 Function invocation scheme 189

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

 © ISO/IEC 2017 – All rights reserved

9.45.2 Constraints on the parameters 189
9.45.3 Function invocation input 189
9.45.4 Function invocation output 190
9.45.5 Bound activity invocation input 190
9.45.6 Bound activity invocation output 190
9.46 BioAPI_Transform 190
9.46.1 Function invocation scheme 190
9.46.2 Constraints on the parameters 191
9.46.3 Function invocation input 191
9.46.4 Function invocation output 192
9.46.5 Bound activity invocation input 192
9.46.6 Bound activity invocation output 192
9.47 BioAPI_DbOpen 192
9.47.1 Function invocation scheme 192
9.47.2 Constraints on the parameters 193
9.47.3 Function invocation input 193
9.47.4 Function invocation output 194
9.47.5 Bound activity invocation input 194
9.47.6 Bound activity invocation output 194
9.48 BioAPI_DbClose 195
9.48.1 Function invocation scheme 195
9.48.2 Constraints on the parameters 195
9.48.3 Function invocation input 195
9.48.4 Function invocation output 195
9.48.5 Bound activity invocation input 195
9.48.6 Bound activity invocation output 196
9.49 BioAPI_DbCreate 196
9.49.1 Function invocation scheme 196
9.49.2 Constraints on the parameters 196
9.49.3 Function invocation input 197
9.49.4 Function invocation output 197
9.49.5 Bound activity invocation input 197
9.49.6 Bound activity invocation output 197
9.50 BioAPI_DbDelete 198
9.50.1 Function invocation scheme 198
9.50.2 Constraints on the parameters 198
9.50.3 Function invocation input 198
9.50.4 Function invocation output 198
9.50.5 Bound activity invocation input 198
9.50.6 Bound activity invocation output 199
9.51 BioAPI_DbSetMarker 199
9.51.1 Function invocation scheme 199
9.51.2 Constraints on the parameters 199
9.51.3 Function invocation input 200
9.51.4 Function invocation output 200
9.51.5 Bound activity invocation input 200
9.51.6 Bound activity invocation output 200
9.52 BioAPI_DbFreeMarker 200
9.52.1 Function invocation scheme 200
9.52.2 Constraints on the parameters 201
9.52.3 Function invocation input 201
9.52.4 Function invocation output 201
9.52.5 Bound activity invocation input 201
9.52.6 Bound activity invocation output 201
9.53 BioAPI_DbStoreBIR 202
9.53.1 Function invocation scheme 202
9.53.2 Constraints on the parameters 202
9.53.3 Function invocation input 203

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.53.4 Function invocation output 203
9.53.5 Bound activity invocation input 203
9.53.6 Bound activity invocation output 203
9.54 BioAPI_DbGetBIR 204
9.54.1 Function invocation scheme 204
9.54.2 Constraints on the parameters 204
9.54.3 Function invocation input 205
9.54.4 Function invocation output 205
9.54.5 Bound activity invocation input 205
9.54.6 Bound activity invocation output 206
9.55 BioAPI_DbGetNextBIR 206
9.55.1 Function invocation scheme 206
9.55.2 Constraints on the parameters 206
9.55.3 Function invocation input 207
9.55.4 Function invocation output 207
9.55.5 Bound activity invocation input 207
9.55.6 Bound activity invocation output 208
9.56 BioAPI_DbDeleteBIR 208
9.56.1 Function invocation scheme 208
9.56.2 Constraints on the parameters 208
9.56.3 Function invocation input 209
9.56.4 Function invocation output 209
9.56.5 Bound activity invocation input 209
9.56.6 Bound activity invocation output 209
9.57 BioAPI_SetPowerMode 209
9.57.1 Function invocation scheme 209
9.57.2 Constraints on the parameters 210
9.57.3 Function invocation input 210
9.57.4 Function invocation output 210
9.57.5 Bound activity invocation input 210
9.57.6 Bound activity invocation output 210
9.58 BioAPI_SetIndicatorStatus 211
9.58.1 Function invocation scheme 211
9.58.2 Constraints on the parameters 211
9.58.3 Function invocation input 211
9.58.4 Function invocation output 211
9.58.5 Bound activity invocation input 211
9.58.6 Bound activity invocation output 212
9.59 BioAPI_GetIndicatorStatus 212
9.59.1 Function invocation scheme 212
9.59.2 Constraints on the parameters 212
9.59.3 Function invocation input 213
9.59.4 Function invocation output 213
9.59.5 Bound activity invocation input 213
9.59.6 Bound activity invocation output 213
9.60 BioAPI_CalibrateSensor 213
9.60.1 Function invocation scheme 213
9.60.2 Constraints on the parameters 214
9.60.3 Function invocation input 214
9.60.4 Function invocation output 214
9.60.5 Bound activity invocation input 214
9.60.6 Bound activity invocation output 214
9.61 BioAPI_Cancel 215
9.61.1 Function invocation scheme 215
9.61.2 Constraints on the parameters 215
9.61.3 Function invocation input 215
9.61.4 Function invocation output 215
9.61.5 Bound activity invocation input 215

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.61.6 Bound activity invocation output 215
9.62 BioAPI_Free 216
9.62.1 Function invocation scheme 216
9.62.2 Constraints on the parameters 216
9.62.3 Function invocation input 216
9.62.4 Function invocation output 216
9.62.5 Bound activity invocation input 216
9.62.6 Bound activity invocation output 216
9.63 BioAPI_Util_InstallBSP 217
9.63.1 Function invocation scheme 217
9.63.2 Constraints on the parameters 217
9.63.3 Function invocation input 218
9.63.4 Function invocation output 218
9.63.5 Bound activity invocation input 218
9.63.6 Bound activity invocation output 218
9.64 BioAPI_Util_InstallBFP 219
9.64.1 Function invocation scheme 219
9.64.2 Constraints on the parameters 219
9.64.3 Function invocation input 220
9.64.4 Function invocation output 220
9.64.5 Bound activity invocation input 220
9.64.6 Bound activity invocation output 220
9.65 BioSPI_BSPLoad 220
9.65.1 Function invocation scheme 220
9.65.2 Constraints on the parameters 221
9.65.3 Function invocation input 221
9.65.4 Function invocation output 222
9.65.5 Bound activity invocation input 222
9.65.6 Bound activity invocation output 222
9.65.7 Default output 222
9.66 BioSPI_BSPUnload 222
9.66.1 Function invocation scheme 222
9.66.2 Constraints on the parameters 222
9.66.3 Function invocation input 223
9.66.4 Function invocation output 223
9.66.5 Bound activity invocation input 223
9.66.6 Bound activity invocation output 223
9.66.7 Default output 223
9.67 BioSPI_BSPAttach 223
9.67.1 Function invocation scheme 223
9.67.2 Constraints on the parameters 224
9.67.3 Function invocation input 224
9.67.4 Function invocation output 225
9.67.5 Bound activity invocation input 225
9.67.6 Bound activity invocation output 225
9.67.7 Default output 225
9.68 BioSPI_BSPDetach 225
9.68.1 Function invocation scheme 225
9.68.2 Constraints on the parameters 226
9.68.3 Function invocation input 226
9.68.4 Function invocation output 226
9.68.5 Bound activity invocation input 226
9.68.6 Bound activity invocation output 226
9.68.7 Default output 226
9.69 BioSPI_QueryUnits 226
9.69.1 Function invocation scheme 226
9.69.2 Bound activity invocation output 227
9.69.3 Default output 228

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.70 BioSPI_QueryBFPs ... 228
9.70.1 Function invocation scheme ... 228
9.70.2 Bound activity invocation output ... 229
9.70.3 Default output ... 229
9.71 BioSPI_ControlUnit ... 229
9.71.1 Function invocation scheme ... 229
9.71.2 Bound activity invocation output ... 230
9.71.3 Default output ... 230
9.72 BioSPI_SetConfiguration ... 231
9.72.1 Function invocation scheme ... 231
9.72.2 Bound activity invocation output ... 231
9.72.3 Default output ... 231
9.73 BioSPI_FreeBIRHandle ... 232
9.73.1 Function invocation scheme ... 232
9.73.2 Bound activity invocation output ... 232
9.73.3 Default output ... 232
9.74 BioSPI_GetBIRFromHandle ... 232
9.74.1 Function invocation scheme ... 232
9.74.2 Bound activity invocation output ... 233
9.74.3 Default output ... 233
9.75 BioSPI_GetHeaderFromHandle ... 233
9.75.1 Function invocation scheme ... 233
9.75.2 Bound activity invocation output ... 234
9.75.3 Default output ... 234
9.76 BioSPI_SubscribeToGUIEvents ... 234
9.76.1 Function invocation scheme ... 234
9.76.2 Bound activity invocation output ... 235
9.76.3 Default output ... 235
9.77 BioSPI_UnsubscribeFromGUIEvents ... 235
9.77.1 Function invocation scheme ... 235
9.77.2 Bound activity invocation output ... 235
9.77.3 Default output ... 236
9.78 BioSPI_EnableEvents ... 236
9.78.1 Function invocation scheme ... 236
9.78.2 Bound activity invocation output ... 236
9.78.3 Default output ... 236
9.79 BioSPI_SetGUICallbacks ... 237
9.79.1 Function invocation scheme ... 237
9.79.2 Bound activity invocation output ... 237
9.79.3 Default output ... 237
9.80 BioSPI_Capture ... 238
9.80.1 Function invocation scheme ... 238
9.80.2 Bound activity invocation output ... 238
9.80.3 Default output ... 239
9.81 BioSPI_CreateTemplate ... 239
9.81.1 Function invocation scheme ... 239
9.81.2 Bound activity invocation output ... 240
9.81.3 Default output ... 240
9.82 BioSPI_Process ... 241
9.82.1 Function invocation scheme ... 241
9.82.2 Bound activity invocation output ... 241
9.82.3 Default output ... 242
9.83 BioSPI_ProcessUsingAuxBIRs ... 242
9.83.1 Function invocation scheme ... 242
9.83.2 Bound activity invocation output ... 243
9.83.3 Default output ... 243
9.84 BioSPI_VerifyMatch ... 243
9.84.1 Function invocation scheme ... 243

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.84.2 Bound activity invocation output 244
9.84.3 Default output 245
9.85 BioSPI_VerifyMatchUsingAuxBIRs 245
9.85.1 Function invocation scheme 245
9.85.2 Bound activity invocation output 246
9.85.3 Default output 247
9.86 BioSPI_IdentifyMatch 247
9.86.1 Function invocation scheme 247
9.86.2 Bound activity invocation output 248
9.86.3 Default output 249
9.87 BioSPI_Decide 249
9.87.1 Function invocation scheme 249
9.87.2 Bound activity invocation output 250
9.87.3 Default output 250
9.88 BioSPI_Fuse 251
9.88.1 Function invocation scheme 251
9.88.2 Bound activity invocation output 251
9.88.3 Default output 252
9.89 BioSPI_Enroll 252
9.89.1 Function invocation scheme 252
9.89.2 Bound activity invocation output 253
9.89.3 Default output 254
9.90 BioSPI_Verify 254
9.90.1 Function invocation scheme 254
9.90.2 Bound activity invocation output 255
9.90.3 Default output 256
9.91 BioSPI_Identify 256
9.91.1 Function invocation scheme 256
9.91.2 Bound activity invocation output 257
9.91.3 Default output 258
9.92 BioSPI_Import 258
9.92.1 Function invocation scheme 258
9.92.2 Bound activity invocation output 259
9.92.3 Default output 259
9.93 BioSPI_Export 260
9.93.1 Function invocation scheme 260
9.93.2 Bound activity invocation output 260
9.93.3 Default output 261
9.94 BioSPI_PresetIdentifyPopulation 261
9.94.1 Function invocation scheme 261
9.94.2 Bound activity invocation output 261
9.94.3 Default output 262
9.95 BioSPI_Transform 262
9.95.1 Function invocation scheme 262
9.95.2 Bound activity invocation output 262
9.95.3 Default output 263
9.96 BioSPI_DbOpen 263
9.96.1 Function invocation scheme 263
9.96.2 Bound activity invocation output 264
9.96.3 Default output 264
9.97 BioSPI_DbClose 265
9.97.1 Function invocation scheme 265
9.97.2 Bound activity invocation output 265
9.97.3 Default output 265
9.98 BioSPI_DbCreate 265
9.98.1 Function invocation scheme 265
9.98.2 Bound activity invocation output 266
9.98.3 Default output 266

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.99 BioSPI_DbDelete ... 267
9.99.1 Function invocation scheme ... 267
9.99.2 Bound activity invocation output ... 267
9.99.3 Default output ... 267
9.100 BioSPI_DbSetMarker ... 267
9.100.1 Function invocation scheme ... 267
9.100.2 Bound activity invocation output ... 268
9.100.3 Default output ... 268
9.101 BioSPI_DbFreeMarker ... 268
9.101.1 Function invocation scheme ... 268
9.101.2 Bound activity invocation output ... 269
9.101.3 Default output ... 269
9.102 BioSPI_DbStoreBIR ... 269
9.102.1 Function invocation scheme ... 269
9.102.2 Bound activity invocation output ... 269
9.102.3 Default output ... 270
9.103 BioSPI_DbGetBIR ... 270
9.103.1 Function invocation scheme ... 270
9.103.2 Bound activity invocation output ... 271
9.103.3 Default output ... 271
9.104 BioSPI_DbGetNextBIR ... 271
9.104.1 Function invocation scheme ... 271
9.104.2 Bound activity invocation output ... 272
9.104.3 Default output ... 272
9.105 BioSPI_DbDeleteBIR ... 273
9.105.1 Function invocation scheme ... 273
9.105.2 Bound activity invocation output ... 273
9.105.3 Default output ... 273
9.106 BioSPI_SetPowerMode ... 273
9.106.1 Function invocation scheme ... 273
9.106.2 Bound activity invocation output ... 274
9.106.3 Default output ... 274
9.107 BioSPI_SetIndicatorStatus ... 274
9.107.1 Function invocation scheme ... 274
9.107.2 Bound activity invocation output ... 275
9.107.3 Default output ... 275
9.108 BioSPI_GetIndicatorStatus ... 275
9.108.1 Function invocation scheme ... 275
9.108.2 Bound activity invocation output ... 275
9.108.3 Default output ... 276
9.109 BioSPI_CalibrateSensor ... 276
9.109.1 Function invocation scheme ... 276
9.109.2 Bound activity invocation output ... 276
9.109.3 Default output ... 276
9.110 BioSPI_Cancel ... 277
9.110.1 Function invocation scheme ... 277
9.110.2 Bound activity invocation output ... 277
9.110.3 Default output ... 277
9.111 BioSPI_Free ... 277
9.111.1 Function invocation scheme ... 277
9.111.2 Bound activity invocation output ... 278
9.111.3 Default output ... 278
9.112 BioAPI_GUI_STATE_EVENT_HANDLER ... 278
9.112.1 Function invocation scheme ... 278
9.112.2 Bound activity invocation output ... 279
9.112.3 Default output ... 280
9.113 BioSPI_EventHandler ... 280
9.113.1 Function invocation scheme ... 280

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.113.2 Constraints on the parameters 281
9.113.3 Function invocation input 281
9.113.4 Function invocation output 281
9.113.5 Bound activity invocation input 282
9.113.6 Bound activity invocation output 282
9.113.7 Default output 282
9.114 BioAPI_GUI_STATE_CALLBACK 282
9.114.1 Function invocation scheme 282
9.114.2 Constraints on the parameters 283
9.114.3 Bound activity invocation input 284
9.114.4 Bound activity invocation output 284
9.114.5 Default output 284
9.115 BioAPI_GUI_STREAMING_CALLBACK 285
9.115.1 Function invocation scheme 285
9.115.2 Constraints on the parameters 285
9.115.3 Bound activity invocation input 285
9.115.4 Bound activity invocation output 286
9.115.5 Default output 286
9.116 BioSPI_EventHandler 286
9.116.1 Function invocation scheme 286
9.116.2 Constraints on the parameters 286
9.116.3 Function invocation input 287
9.116.4 Function invocation output 287
9.116.5 Bound activity invocation input 287
9.116.6 Bound activity invocation output 287
9.116.7 Default output 287
9.117 BioSPI_GUI_STATE_CALLBACK 288
9.117.1 Function invocation scheme 288
9.117.2 Function invocation input 288
9.117.3 Function invocation output 289
9.118 BioSPI_GUI_STREAMING_CALLBACK 289
9.118.1 Function invocation scheme 289
9.118.2 Function invocation input 290
9.118.3 Function invocation output 290
9.119 BioSPI_BFP_ENUMERATION_HANDLER 290
9.119.1 Function invocation scheme 290
9.119.2 Constraints on the parameters 291
9.119.3 Function invocation input 291
9.119.4 Function invocation output 291
9.119.5 Bound activity invocation input 292
9.119.6 Bound activity invocation output 292
9.119.7 Default output 292
9.120 BioSPI_MEMORY_FREE_HANDLER 292
9.120.1 Function invocation scheme 292
9.120.2 Constraints on the parameters 293
9.120.3 Function invocation input 293
9.120.4 Function invocation output 293
9.120.5 Bound activity invocation input 293
9.120.6 Bound activity invocation output 293
9.120.7 Default output 293
9.121 BioSPI_GUI_PROGRESS_EVENT_HANDLER 293
9.121.1 Function invocation scheme 293
9.121.2 Bound activity invocation output 294
9.121.3 Default output 294
9.122 BioSPI_GUI_SELECT_EVENT_HANDLER 295
9.122.1 Function invocation scheme 295
9.122.2 Bound activity invocation output 296
9.122.3 Default output 296

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.123 BioSPI_GUI_STATE_EVENT_HANDLER ... 296
9.123.1 Function invocation scheme ... 296
9.123.2 Bound activity invocation output ... 297
9.123.3 Default output ... 297

10 Built-in variables ... 297
10.1 Variables whose value never changes ... 297
10.2 Variables whose value may change ... 309

11 Test log ... 310

12 Test report ... 312

13 BioAPI conformance test suite ... 313
13.1 General concepts ... 313
13.2 BioAPI conformance test suite structure ... 314

Annex A (normative) **XML schema of the assertion language ... 316**

Annex B (normative) **ASN.1 schema of the assertion language ... 320**

Annex C (normative) **XML schema for the test log ... 323**

Annex D (informative) **Test method implementation guidelines ... 325**

Annex E (informative) **XML diagrams of the assertion language ... 331**

Bibliography ... 352

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 37, *Biometrics*.

This second edition cancels and replaces the first edition (ISO/IEC 24709-1:2007), which has been technically revised.

A list of all parts in the ISO/IEC 24709 series can be found on the ISO website.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

Introduction

This document defines a conformance testing methodology for ISO/IEC 19784-1. It specifies three conformance testing models that enable conformance testing of each of the following BioAPI components: an application, a framework, or a BSP. It also specifies an assertion language that is used for the definition of test assertions. Actual test assertions for each of the BioAPI components are defined in the subsequent parts of the ISO/IEC 24709 series.

This document also contains informative guidelines regarding general concepts related to establishing and administering a BioAPI conformance assessment and certification program. These informative guidelines identify the types of activities, responsibilities, services, and documentation recommended for conducting conformity assessment and certification of BioAPI-conformant implementations. Further, this document provides informative guidelines for establishing a complete conformity assessment methodology for BioAPI specification.

Clause 6 describes the general test method and conformance testing models for BioAPI.

Clause 7 defines the assertion language, based on XML, used for definition of conformance test assertion.

Clause 8 defines the elements of the assertion language.

Clause 9 specifies the use of the standard BioAPI interface functions of BioAPI in conformance testing.

Clause 10 defines the built-in variables of the assertion language.

Clause 11 defines the test log using XML syntax.

Clause 12 defines the test report using XML syntax.

Clause 13 describes the general concept and structure of a BioAPI conformance test suite.

Annex A defines the XML schema of the assertion language.

Annex B defines the ASN.1 schema of the assertion language.

Annex C defines the XML schema for the test log.

Annex D describes a primer of a BioAPI test method implementation, including elements of the conformance test process and description of the test categories.

Annex E provides the relationship diagrams for the assertion language.

The Bibliography references a number of standards organizations, including ISO, IEC, NIST, IEEE and other organizations, that have published a number of documents and white papers related to conformity assessment in general and conformance testing in particular.

NOTE Rather than make normative references to these documents, this document incorporates appropriate excerpts of their text, in some cases paraphrasing the text or adapting the provisions to the specific circumstances. Therefore, these documents are listed in the Bibliography or are referred in the body text explicitly as appropriate.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

 © ISO/IEC 2017 – All rights reserved

Information technology — Conformance testing for the biometric application programming interface (BioAPI) —

Part 1: Methods and procedures

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

1 Scope

This document specifies the concepts, framework, test methods, and criteria required to test conformity of biometric products claiming conformance to BioAPI (see ISO/IEC 19784-1). Guidelines for specifying BioAPI conformance test suites, writing test assertions, and defining procedures to be followed during the conformance testing are provided.

This document is concerned with conformance testing of biometric products claiming conformance to BioAPI (see ISO/IEC 19784-1). It is not concerned with testing other characteristics of biometric products or other types of testing of biometric products (i.e. acceptance, performance, robustness, security, etc.) Testing by means of test methods, which are specific to particular biometric products, are not the subject of this document.

This document is applicable to the development and use of conformance test method specifications, BioAPI conformance test suites, and conformance testing programs for BioAPI-conformant products. It is intended primarily for use by testing organizations, but can be applied by developers and users of test assertions and test method implementations.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 8601, *Data elements and interchange formats — Information interchange — Representation of dates and times*

ISO/IEC 19784-1, *Information technology — Biometric application program interface — Part 1: BioAPI specification*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO/IEC 19784-1 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

— IEC Electropedia: available at http://www.electropedia.org/

— ISO Online browsing platform: available at http://www.iso.org/obp

3.1
abstract test engine
conceptual machine capable of performing conformance tests on an instance of a standard BioAPI component

© ISO/IEC 2017 – All rights reserved

3.2
base standard
standard for which a *test method specification* (3.13) is written and/or a *test method implementation* (3.12) is developed

3.3
BioAPI conformity statement
statement that describes conformity of an IUT against relevant BioAPI requirements

3.4
BioAPI conformance test suite
test software used to ascertain *conformance* (3.6) to a specification or a standard that is in conformance to ISO/IEC 19784-1

3.5
certification
acknowledgement that a *validation* (3.17) has been completed and the criteria established by the certifying organization have been met

3.6
conformance
fulfillment by a product, process, or service of all relevant specified conformance requirements

3.7
conformity assessment
any activity concerned with determining directly or indirectly that relevant requirements are fulfilled

Note 1 to entry: See ISO/IEC Guide 2.

3.8
implementation under test
software and hardware, located on one or more system, which implement the standard(s) being tested

3.9
standard BioAPI interface
one of the interfaces specified in ISO/IEC 19784-1, which one standard BioAPI component exposes to another standard BioAPI component

Note 1 to entry: See 6.1.3.8.

3.10
test assertion
assertion
specification for testing a conformance requirement in an *implementation under test* (3.8) in the form of software or procedural methods that generate the test results (also named test outcomes or test verdicts) used for assessment of the conformance requirement

3.11
test case
specification of the actions required to achieve a specific *test purpose* (3.14) or combination of test purposes

[SOURCE: ISO/IEC 9646-1:1994, 3.3.3, modified — The definition has been revised.]

3.12
test method implementation
software, procedures, or other means used to measure *conformance* (3.6)

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

3.13
test method specification
document that expresses the required functionality and behaviour of a *base standard* (3.2) as *assertions* (3.10) and provides the complete set of conforming *test result codes* (3.15)

[SOURCE: ISO/IEC 13210:1999, 2.2.2.30]

3.14
test purpose
prose description of a narrowly defined objective of testing, focusing on a single conformance requirement, as specified in the appropriate product specification

[SOURCE: ISO/IEC 13210:1999, 2.2.2.32, modified — The definition has been revised.]

3.15
test result code
value that describes the result of a test

3.16
test report
document that presents test results and other information relevant to the execution of the test methods against an *implementation under test* (3.8)

3.17
validation
process of testing software for *conformance* (3.6) to a specific specification

4 Abbreviated terms

API Application Programming Interface

BCS BioAPI Conformity Statement

BIR Biometric Information Record

BSP Biometric Service Provider

CBEFF Common Biometric Exchange Formats Framework

CTS BioAPI Conformance Test Suite

IUT Implementation Under Test

SPI Service Provider Interface

UUID Universally Unique Indentifier

5 Conformance

5.1 A BioAPI conformance test suite conforming to this document shall support one or more conformance testing models (see 6.2) and shall be able to execute any valid test assertion for the testing model(s) that it supports, and that are written in the assertion language specified in Clause 7 to Clause 10.

NOTE There is no restriction on the form or structure of a BioAPI conformance test suite, in terms of the number of software components, the tasks performed by each software component, or the content and form of the information exchanged between software components.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

5.2 A BioAPI conformance test suite shall be able to verify the syntactic correctness of any package (see 7.1.6) containing assertions or activities (or both) for any conformance testing model, including the testing models that the implementation does not support (if any).

5.3 For each supported conformance testing model, a BioAPI conformance test suite shall be able to perform the actions (specific to a computing platform) necessary to interact with an implementation under test, making function calls to the standard BioAPI interface functions exposed by the implementation under test and receiving function calls from it.

In the conformance testing model for BioAPI applications, it is not required that the BioAPI conformance test suite be able to start or stop the execution of the implementation under test, but needs a mechanism to detect the starting or ending of the application under test.

NOTE It is not required that a BioAPI conformance test suite be able to test all implementations of the base standard that claim conformance to the base standard. This includes, but is not limited to, the case when the implementation of the base standard was created for a computing platform different from the one for which the BioAPI conformance test suite was created, and the case where the implementation of the base standard depends on a hardware device that is not available on the computing system where the test is to be run.

5.4 A BioAPI conformance test suite shall produce a test log (see Clause 11) and test report (see Clause 12) for each implementation tested.

5.5 If a BioAPI conformance test suite is unable to perform the test of an implementation of the base standard, this shall be recorded in the test report in these terms rather than as non-conformance of the implementation under test.

5.6 A BioAPI conformance test suite shall provide a means for a user to enter all the data necessary as input to a test.

NOTE This includes the identification of the assertion to be processed (package name and assertion name), the list of all the input parameters of the assertion, and all the other information that is to be included in a test report (see Clause 12).

6 Conformance testing methodology

6.1 General

6.1.1 Implementation under test

6.1.1.1 The implementation under test (IUT) is the object that is being tested for conformity. For BioAPI specifications, it is the software that has "implemented" the specification. The software and supporting hardware constitute the IUT and shall be listed in both the test report and certificate of conformity.

6.1.1.2 Biometric products claiming to conform to the BioAPI specification are expected to conform to all the applicable conformity requirements in the conformity clause of the BioAPI specification (see Clause 5). These requirements can be:

a) mandatory requirements: these are to be observed in all cases;

b) conditional requirements: these are to be observed if the conditions set out in the specification apply;

c) optional requirements: these can be selected to suit the implementation and are to be observed if selected.

6.1.1.3 To evaluate the conformity of a biometric product, it is necessary to have a statement of the capabilities that have been implemented in conformance with the BioAPI specification, so that the implementation can be tested for conformity against relevant requirements and against those

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

 © ISO/IEC 2017 – All rights reserved

requirements only. Such a statement is called a BioAPI Conformity Statement (BCS, and shall be prepared by the IUT supplier prior to the beginning of the conformance testing. At a minimum, the BCS shall contain an itemized list of all mandatory, optional, and conditional conformity requirements of the BioAPI specification included in the IUT.

6.1.2 Test method

6.1.2.1 For conformance testing to be meaningful, all BioAPI implementations shall be tested in the same manner. Conformance testing reflects the essence of technical requirements of BioAPI specifications and measures whether a biometric product faithfully implements the specification.

6.1.2.2 For the purpose of this document, conformance testing is "black box" testing of the functionality of a BioAPI implementation. Neither the internal structure nor source code of a candidate implementation is examined.

6.1.2.3 Considering the complexity of the BioAPI specification, and many possible ways of implementing BioAPI-conformant products, the feasible strategy is to use falsification testing methodology. This strategy as implemented in this document includes the following steps.

a) Analyse the BioAPI specification and develop documented test cases in form of test assertions. Test cases may be further grouped to form test scenarios. The test assertions are documented in other parts of ISO/IEC 24709.

b) The test assertions may be realized in the form of executable test scripts, which, in combination with applicable data files, will constitute a BioAPI conformance test suite (CTS).

c) An IUT will be subjected to various combinations of legal and illegal inputs, and compare the resulting output to a set of corresponding "expected results."

d) Test results will be evaluated using pass/fail criteria.

6.1.2.4 Falsification testing can only demonstrate non-conformity, i.e. if errors are found, non-conformance of the IUT shall be proven, but the absence of errors does not necessarily imply the converse. This test method is intended to provide a reasonable level of confidence and practical assurance that the IUT conforms to the standard. Use of this test method will not guarantee conformity of an implementation to the standard; that normally would require exhaustive testing, which is impractical for both technical and economic reasons.

6.1.2.5 A test method implementation shall document that it conforms to this document and shall document any other test method specifications to which it claims to conform. Each test method implementation shall include the following:

a) BioAPI conformance test suite (CTS), including documentation of the test suite, describing test categories, test objectives for each individual test, instructions on how to execute the test suite, and the expected results of executing the individual tests. The CTS shall be capable of executing the test script sets, capturing the returned results, evaluating the results, and reporting them in a human-readable form;

b) documented test cases, which will sufficiently assure conformity to this document. The test cases shall be formally represented in the form of test assertions using the assertion language, which can be submitted to the BioAPI conformance test suite;

c) conformance testing procedure, which shall identify and define all the activities necessary to prepare for conformance testing, perform the conformance testing, and report the test results. The procedure shall be detailed enough so that testing of a given IUT can be repeated with no significant change in test results. The procedure shall identify the administrative, as well as testing processes.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

6.1.2.6 A test method implementation shall use the required assertion definitions, types, syntax, and constructs specified in the ISO/IEC 24709 series as applicable. It shall use test result codes specified in this document for test results defined by this document.

6.1.2.7 The conformance testing process is the complete process of accomplishing all conformance testing activities necessary to assess the conformity of an IUT to the BioAPI specification standard. The conformance testing process involves three phases:

a) preparation for testing, which includes analysis of the BCS, preparation of the Conformance Test Plan, selection and configuration of the CTS, and preparation of the IUT and corresponding test environment (means of testing);

b) test execution, which includes execution of the CTS and recording the observed test results in conformity test log(s). The results of conformance testing shall apply only to the IUT and test environment for which the tests are run;

c) test report production, which includes recording of all events occurred during the execution of each test case, including all test outcomes and test verdicts, as well as description of the test environment (operating system, hardware configuration, etc.).

6.1.2.8 In order to achieve the objective of credible conformance testing, the result of executing a test case on an IUT should be the same whenever it is performed. While it may not be possible to execute a complete BioAPI conformance test suite and observe test outcomes that are identical to those obtained on another occasion, every effort should be made to ensure repeatability of test results and to minimize the possibility that a test case produces different outcomes on different occasions.

6.1.2.9 It may be necessary to review the observed test outcomes in order to make sure that all procedures have been correctly followed. It is essential that all inputs, outputs, and other test events, as well as test environment and IUT configuration, be logged for each test case being executed, with sufficient information to produce a conformity log for each test execution, for future reference.

6.1.3 Standard BioAPI components and standard BioAPI interfaces

6.1.3.1 This document specifies a methodology for assessing conformance of implementations of ISO/IEC 19784-1. Three types of implementations of ISO/IEC 19784-1 are distinguished (see Figure 1):

a) BioAPI application;

b) BioAPI framework;

c) BioAPI biometric service provider (BSP).

6.1.3.2 A BioAPI application is a software component (or set of software components) that uses the BioAPI interface specified in ISO/IEC 19784-1, making one or more function calls to the BioAPI interface in the course of its execution.

6.1.3.3 A BioAPI framework is a software component (or set of software components) that implements the BioAPI interface specified in ISO/IEC 19784-1 and realizes its prescribed behaviour, making one or more function calls to the BioSPI interface specified in ISO/IEC 19784-1 in the course of its execution.

6.1.3.4 A BioAPI biometric service provider is a software component (or set of software components) that implements the BioSPI interface specified in ISO/IEC 19784-1 and realizes its prescribed behaviour.

6.1.3.5 A BioAPI biometric function provider (BFP) is another component of the BioAPI architecture, but its interface is not specified in ISO/IEC 19784-1. Therefore, this document contains no provisions relative to that component.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

 © ISO/IEC 2017 – All rights reserved

6.1.3.6 Besides the two main interfaces BioAPI and BioSPI, two other interfaces are specified in ISO/IEC 19784-1 as indicated in the five following subclauses.

6.1.3.6.1 BioAPI frameworks implement an auxiliary interface that supports the reception of the following information from BSPs:

a) notifications of events related to BioAPI units;

b) streaming data (grayscale bitmaps) sent during an operation performed by a BSP or by a BFP (on behalf of a BSP);

c) GUI state information sent during an operation performed by a BSP or by a BFP (on behalf of a BSP).

6.1.3.6.2 In this document, the interface mentioned in the previous subclause, implemented by BioAPI frameworks, is called the "framework callback interface".

6.1.3.6.3 BioAPI applications may implement an auxiliary interface that supports the reception of some, or all, of the following information from the BioAPI framework:

a) notifications of events related to BioAPI units, originating in a BSP or in a BFP and relayed by the framework to the application;

b) streaming data (grayscale bitmaps) sent during an operation performed by a BSP or by a BFP (on behalf of a BSP) and relayed by the framework to the application;

c) GUI state information sent during an operation performed by a BSP or by a BFP (on behalf of a BSP) and relayed by the framework to the application.

The BioAPI framework relays to the application(s) the information it receives from the BSPs, depending on which functions are supported by each application, and depending on whether the application is currently using the BSP that sends the information to the BioAPI framework.

6.1.3.6.4 In this document, the interface mentioned in the previous subclause, optionally implemented by BioAPI applications, is called the "application callback interface".

6.1.3.6.5 In addition, BioAPI frameworks include functions that support installation and deinstallation of BSPs, and installation and deinstallaton of BFPs. In this document, those functions are included in the BioAPI interface.

6.1.3.7 BioAPI BSPs may implement an auxiliary interface that supports the reception of information from BFPs, but this interface is not specified in ISO/IEC 19784-1. Therefore, this document contains no provisions relative to that interface.

6.1.3.8 In this document, the three types of implementations of the BioAPI standard listed above are called the standard BioAPI components. The BioAPI interface, the BioSPI interface, the application callback interface, and the framework callback interface mentioned above are called the standard BioAPI interfaces. For the purposes of this document, each standard BioAPI component interacts with other standard BioAPI components by making function calls to their standard BioAPI interfaces (and in no other way).

6.1.3.9 This document specifies a BioAPI conformance testing methodology in terms of the three standard BioAPI components and of the four standard BioAPI interfaces.

6.1.4 Physical architectures

6.1.4.1 ISO/IEC 19784-1 does not specify the details of loading in memory for any of the standard BioAPI components, nor does it specify a physical association between standard BioAPI components and

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

nodes, nor does it limit the number of instances of each standard BioAPI component within a node. All this information is therefore platform-specific or implementation-specific.

6.1.4.2 Typically, BioAPI BSPs are implemented as dynamic libraries on the platforms that support this feature.

6.1.4.3 In one typical physical BioAPI architecture, the BioAPI framework is a dynamic library as well, and BioAPI applications are executable programs that load the BioAPI framework dynamic library in memory. In this architecture, there can only be one BioAPI application using an instance of the BioAPI framework at any given time. If multiple BioAPI applications are running concurrently in a node, each of them owns a separate instance of the BioAPI framework and a separate instance of each BSP that is loaded by more than one of them.

6.1.4.4 In another typical physical BioAPI architecture, the BioAPI framework is an independent executable program (e.g. an operating system service) and any number of BioAPI applications may be launched and terminated at any time during the execution of the BioAPI framework, all of them using the same instance of the framework and the same instance of each BSP that is loaded by more than one of them simultaneously.

6.1.4.5 Given the abstractness of the BioAPI architecture specified in ISO/IEC 19784-1, the conformance testing methodology specified in this document does not depend on any particular physical BioAPI architecture. The conformance testing methodology treats the standard BioAPI components as abstract components implementing the interfaces and the behaviour specified in ISO/IEC 19784-1, with no assumptions being made on their physical realization.

6.1.4.6 However, specific implementations of the conformance testing methodology (BioAPI conformance test suites) run on specific platforms and are designed for particular physical BioAPI architectures. Therefore, each BioAPI conformance test suite may be designed for testing only a subset of the possible implementations of the standard BioAPI components. In Annex E, recommendations are provided in order to increase the level of consistency between different implementations of the conformance testing methodology created for different platforms or for different physical BioAPI architectures on the same platform.

6.2 Conformance testing models

6.2.1 The conformance testing methodology specified in this document addresses each of the standard BioAPI components separately. Three conformance testing models are defined within the methodology, one for the testing of each standard BioAPI component.

6.2.2 The three conformance testing models are independent from one another, although they have many properties in common.

6.2.3 Implementations of the conformance testing methodology reflect the separation between these three testing models, resulting in testing procedures that are specialized for testing the conformance of only one of the following at a time:

a) a given implementation of the BioAPI application standard BioAPI component;

b) a given implementation of the BioAPI framework standard BioAPI component;

c) a given implementation of the BioAPI BSP standard BioAPI component.

6.2.4 Each testing model is based on a variation to the basic BioAPI architecture.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

 © ISO/IEC 2017 – All rights reserved

6.2.5 For the purposes of this subclause, the basic BioAPI architecture is described as comprising a normal BioAPI application, a normal BioAPI framework, and one or more normal BioAPI BSPs. Each testing model makes additions and replacements to the basic architecture as specified in the three following subclauses.

6.2.5.1 In the conformance testing model for BioAPI applications, a special testing component (called the "application-testing framework") shall be inserted between the application under test and the normal framework (see Figure 2). This testing component shall implement the standard BioAPI interface on one side and the application callback interface on the other side. As a result, it shall appear to the application under test as a framework, and to a framework as an application. This testing component shall have the ability to relay application calls to the normal framework and framework calls to the application under test, and the ability to observe, analyse, and log the flow of incoming calls and to generate extra calls for testing purposes.

6.2.5.2 In the conformance testing model for BioAPI frameworks, a special testing component (called the "framework-testing application") shall replace the normal application, and another special testing component (called the "framework-testing BSP") shall replace the normal BSP (see Figure 3). Between these two testing components shall lie the framework under test. The framework-testing application shall implement the application callback interface and the framework-testing BSP shall implement the BioSPI interface. Therefore, the framework under test cannot distinguish between them and the corresponding normal BioAPI components. In addition, each testing component shall have a special testing interface enabling them to interact with each other for the purpose of performing the tests.

6.2.5.3 In the conformance testing model for BioAPI BSPs, a special testing component (called the "BSP-testing application") shall replace the normal application and the normal framework (see Figure 4). This testing component shall act both as a BioAPI application and as a BioAPI framework, and shall implement the framework callback interface. As a result, it shall appear to the BSP under test as a framework. The testing component shall be able to make calls to the BioSPI interface of the BSP under test.

6.2.6 When a BioAPI implementation that comprises two or more standard BioAPI components is submitted to conformance testing, the procedures for each component shall be followed separately for each component, producing separate reports (see Clause 12).

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved





Figure 1 — Normal BioAPI component model

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved



STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

Figure 2 — Conformance testing model for BioAPI applications

© ISO/IEC 2017 – All rights reserved




Figure 3 — Conformance testing model for BioAPI frameworks

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved




Figure 4 — Conformance testing model for BioAPI BSPs

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

6.3 Abstract test engine

6.3.1 The semantics of the assertion language is specified in terms of an abstract test engine.

6.3.2 The abstract test engine is a conceptual machine capable of performing conformance tests on an instance of a standard BioAPI component (application, framework, or BSP). The abstract test engine shall be able to do so by processing a formal assertion written in the assertion language specified in Clause 7).

6.3.3 The abstract test engine shall have the ability to operate according to any of the three conformance testing models (see 6.2) depending on the type of the standard BioAPI component under test. In each testing model, the abstract test engine shall be associated with the special testing components in the model as follows.

a) In the conformance testing model for BioAPI applications (see 6.2.5.1), the abstract test engine shall be associated with the application-testing framework.

b) In the conformance testing model for BioAPI frameworks (see 6.2.5.2), the abstract test engine shall be associated both with the framework-testing application and with the framework-testing BSP at the same time.

c) In the conformance testing model for BioAPI BSPs (see 6.2.5.3), the abstract test engine shall be associated with the BSP-testing application.

© ISO/IEC 2017 – All rights reserved

6.3.4 During the processing of a test assertion, the special testing component(s) associated with the abstract test engine shall be able to make calls to the standard BioAPI interfaces of the component under test and of other components present in the testing model. The testing component(s) shall also be able to process incoming calls made by the other components to the standard BioAPI interfaces implemented by the testing components themselves.

6.3.5 The type of outgoing calls being made and of incoming calls being processed by the testing component(s) shall depend on the type of standard BioAPI component under test (and thus on the conformance testing model being used), while the actual calls being made and the way of processing the incoming calls shall depend on the content of the assertion being processed.

6.3.6 In the conformance testing model that contains two special testing components (the testing model for BioAPI frameworks), the testing components associated with the abstract test engine shall communicate with each other by using the special testing interfaces, so that the abstract test engine controls the behaviour of both components at the same time. The communication between the two testing components is not standardized and the special testing interfaces are not directly represented in the language.

6.3.7 The structure and operation of the abstract test engine shall not depend on platforms, physical BioAPI architecture, or the internal architecture of the BioAPI components. From the point of view of the abstract test engine, each component shall be a black box whose behaviour depends solely on

a) the calls being made to the entry points of its standard BioAPI interfaces, and

b) the passing of time or interaction with other actors (invisible to the abstract test engine) as they can cause well-defined activities to take place inside the component at undefined instants.

6.3.8 The activities described in 6.3.7 b) may be indirectly observed by the abstract test engine as they may affect

a) one or more subsequent calls that the component will make to other components, or

b) the component's responses to one or more subsequent calls that other components will make to it.

6.3.9 BioAPI conformance test suites shall include a concrete implementation of the abstract test engine. The structure of the abstract test engine does not have to be mirrored in such implementations, but its specified behaviour shall be reflected in the implementation, so that the semantics of the assertion language is preserved.

6.3.10 Concrete activities such as loading and running an executable program, locating and loading a dynamic library, and so on, fall below the level of abstraction of the conformance testing models and of the abstract test engine. Therefore, they are not formally described in this document.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

7 General properties of the assertion language

7.1 General

7.1.1 Clause 7 to Clause 10 specify a language whose purpose is to express assertions to be used in BioAPI conformance testing. The assertion language is an integral part of the BioAPI conformance testing methodology.

7.1.2 Other parts of ISO/IEC 24709 contain a set of assertions written in the assertion language. Implementations of the BioAPI conformance testing methodology (BioAPI conformance test suites) that claim conformance to ISO/IEC 24709 need to use (or implement) all the assertions provided in these parts and only those assertions.

© ISO/IEC 2017 – All rights reserved

7.1.3 The above does not preclude particular implementations of the conformance testing methodology from using a different set of assertions (be they derived or not from the assertions in other parts of ISO/IEC 24709), while still claiming conformance to this document. However, such implementations cannot also claim conformance to other parts of ISO/IEC 24709.

7.1.4 The assertion language has a syntax based on W3C XML 1.0. In the rest of this subclause, the terms "element" and "attribute" are used with the meaning of "XML element" and "XML attribute", respectively.

7.1.5 Assertions are represented as `<assertion>` elements (see 8.2). Each assertion has a number of properties represented as attributes and as child elements of the `<assertion>` element. Among the properties of an assertion are its name (`name` attribute), its conformance testing model (`model` attribute), and its primary activity reference (`<invoke>` child element).

EXAMPLE (non-normative)

```
<assertion name="CreateTemplate1" model="BSPTesting">
   <description>
      Test the BioSPI_CreateTemplate function of a BSP.
      The UUID and version of the BSP must be provided
      as input to the test.
   </description>
   <input name="_uuid"/>
   <input name="_version"/>
   <invoke activity="CreateTemplate"
      package="7346D660-1583-13D0-A3A5-00C0FFD756E3">
      <input name="BSPUuid" var="_uuid"/>
      <input name="BSPVersion" var="_version"/>
      <input name="deviceIDOrNull" value="0"/>
      <input name="inserttimeouttime" value="15000"/>
      <input name="sourcepresenttimeouttime" value="10000"/>
      <input name="capturetimeouttime" value="20000"/>
   </invoke>
   <bind activity="EventHandler" function="BioAPI_EventHandler"/>
</assertion>
```

7.1.6 Assertions are grouped into packages. Each package, represented as a `<package>` element that is always the root element of an XML document, has a name (`name` attribute) and other identification properties. A package contains zero or more assertions (`<assertion>` elements) followed by zero or more activities (`<activity>` elements). Empty packages are permitted, as well as packages containing only assertions, or only activities, or both assertions and activities (where all the assertions precede the first activity in the package). Neither the `<assertion>` element nor the `<activity>` element can be the root element of an XML document.

EXAMPLE (non-normative)

```
<?xml version='1.0' encoding="utf-8"?>
<package name="73668660-1583-1AD0-A3A5-09C0FF4756E3">
   <author>
      ISO/IEC SC37
   </author>
   <description>
      Abcde abcde abcde
   </description>

   <assertion name="Capture2" model="BSPTesting">
      <description>
         Test the BioSPI_Capture function of a BSP.
      </description>
      <invoke activity="Capture"
         package="7346D660-1583-13D0-A3A5-00C0FFD756E3">
         <input name="BSPUuid" value=""/>
         <input name="BSPVersion" value="0"/>
         <input name="deviceIDOrNull" value="0"/>
         <input name="inserttimeouttime" value="15000"/>
         <input name="sourcepresenttimeouttime" value="10000"/>
```

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

```
         <input name="capturetimeouttime" value="20000"/>
      </invoke>
      <bind activity="EventHandler" function="BioAPI_EventHandler"/>
   </assertion>

   <assertion name="Capture5" model="BSPTesting">
      <description>
         Test the BioSPI_Capture function of a BSP
         with abcde abcde abcde.
      </description>
      <invoke activity="Capture"
         package="7346D660-1583-13D0-A3A5-00C0FFD756E3">
         <input name="BSPUuid" value=""/>
         <input name="BSPVersion" value="0"/>
         <input name="deviceIDOrNull" value="-1"/>
         <input name="inserttimeouttime" value="15000"/>
         <input name="sourcepresenttimeouttime" value="10000"/>
         <input name="capturetimeouttime" value="20000"/>
      </invoke>
      <bind activity="EventHandler" function="BioAPI_EventHandler"/>
   </assertion>
</package>
```

7.1.7 Assertions may have input parameters (but not output parameters). The input parameters are represented by <input> elements. At the time of testing, they are assigned actual values during the preparation of a test. For an assertion with parameters, the results of a test may depend on the values assigned to the parameters; therefore, those values are an important part of the test being performed.

7.1.8 The means of assigning values to the input parameters of assertions is outside the scope of this document, but the values used in a test are documented in the standard test report (see Clause 12).

7.1.9 Every assertion contains a primary activity reference. The primary activity of an assertion specifies the actions to be executed when the assertion is processed.

7.1.10 Activities are represented as <activity> elements (see 8.9). An activity is a sequence, usually parameterized, of actions that may include invocation of functions of the standard BioAPI interfaces (see Clause 9). An activity may invoke other activities.

EXAMPLE (non-normative)

```
<?xml version='1.0' encoding="utf-8"?>
<package name="734ED660-1183-13D0-A3A5-0410FFD77AE9">
   <author>
      ISO/IEC SC37
   </author>
   <description>
      Abcde abcde abcde
   </description>

   <activity name="CreateTemplate">
       <input name="BSPUuid"/>
       <input name="BSPVersion"/>
       <input name="deviceIDOrNull"/>
       <input name="inserttimeouttime"/>
       <input name="sourcepresenttimeouttime"/>
       <input name="capturetimeouttime"/>


       <invoke activity="LoadAndAttach" break_on_break="true">
           <input name="BSPUuid" var="BSPUuid"/>
           <input name="BSPVersion" var="BSPVersion"/>
           <input name="deviceIDOrNull" var="deviceIDOrNull"/>
           <input name="BSP" value="1"/>
           <input name="eventtimeouttime"
              var="inserttimeouttime"/>
       </invoke>
```

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

```
        <wait_until
           timeout_var="sourcepresenttimeouttime"
           setvar="eventtimeoutflag"
           var="_sourcePresent"/>


        <assert_condition
               response_if_true="undecided"
               break_if_false="true">
           <description>
               We are testing
           </description>
           <not var="eventtimeoutflag"/>
        </assert_condition>


        <invoke function="BioSPI_Capture">
            <input name="BSPHandle" value="1"/>
            <input name="Purpose" var="__BioAPI_PURPOSE_ENROLL"/>
            <input name="Timeout" var="capturetimeouttime"/>
            <output name="CapturedBIR" setvar="bir"/>
            <output name="AuditData" setvar="auditbir"/>
            <return setvar="return"/>
        </invoke>
    </activity>


    <activity name="LoadAndAttach">
        ...
    </activity>


</package>
```

7.2 Variables

7.2.1 The names of variables in the assertion language shall consist of strings of ISO/IEC 10646 characters that match the "NCName" production in W3C XML Namespaces.

7.2.2 Variables whose name begins with a LOW LINE character ("_") are global variables. Any other variables are local variables.

7.2.3 Global variables shall have a lifetime that extends over the processing of an entire assertion. They may be created within any activity (see 8.6.2.3, 8.7.2.3, 8.12.2.5.1 and 8.17.2.9) but shall be associated with the entire assertion and shall not be destroyed until the processig of the assertion terminates. Global variables may also be created as input parameters of assertions (see 8.3.2.4).

7.2.4 Local variables may be created within any activity (see 8.5.2.5, 8.6.2.3, 8.7.2.3, 8.12.2.5.1 and 8.17.2.9), shall be associated with that activity, and shall be destroyed as soon as that activity terminates.

7.2.5 Input and output parameters of activities are local variables of the activities. The only difference between input parameters (of assertions and activities) and ordinary variables is in the way they are created and acquire their initial value. The only difference between output parameters of activities and ordinary variables is in the way they are destroyed and in the disposition of their final value.

7.2.6 In the assertion language, variables do not have a data type. The values of all variables are ISO/IEC 10646 character strings of unlimited length.

7.2.7 A value shall be interpreted as an integer in two cases

a) when it is evaluated by a numeric operation (see 8.23 to 8.28), or

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

b) when it is passed to a standard BioAPI interface function that accepts an integer as input.

7.2.8 In case 7.2.7 a), a typical numeric operation gets one or more values (character strings representing integers) as input and returns a value. Although the values may exist in some native numeric representation for some time during the execution of the operation, this fact is never reflected outside the operation.

7.2.9 In case 7.2.7 b), the conversion from character string to integer is performed as part of the invocation of the function and does not manifest itself in the syntax of the assertion language.

7.2.10 Likewise, a variable may be set to a (character string) value resulting from a conversion of an integer to a character string. This happens when the variable is set from an output parameter of a standard BioAPI interface function or from its return value.

7.2.11 The conversion from integer to character string is performed as part of the invocation of the function and does not manifest itself in the syntax of the assertion language.

7.2.12 The same is true of data types other than integers, which are used on the standard BioAPI interfaces. These native data types are enumerations, handles, addresses of functions, and addresses of data (see Clause 9), and are all represented as character strings in the assertion language.

7.3 Built-in variables

7.3.1 A number of global variables are built into the assertion language. Their names all begin with two consecutive LOW LINE characters ("_"). These variables are specified in Clause 10.

7.3.2 The abstract test engine shall create and assign all built-in variables before starting execution of the primary activity of an assertion and shall not destroy them until the execution of that activity terminates. Most of the built-in variables have a value that never changes and is specified in 10.1. The value of the other built-in variables may change as specified in 10.2.

NOTE Names of global variables beginning with two consecutive LOW LINE characters ("_") cannot appear as the value of the `setvar` attribute of the elements `<output>`, `<return>`, and `<wait_until>` (see 8.6.2.3, 8.7.2.3 and 8.17.2.9.1, respectively) or as the value of the `name` attribute of the elements `<input>`, `<set>`, `<add>`, and `<subtract>` (see 8.3.2.3, 8.12.2.2, 8.13.2.2 and 8.14.2.2, respectively). Therefore, it is not possible to explicitly modify the value of a built-in variable.

7.3.3 In the execution of any activity, built-in variables shall only be updated during the time intervals in which the activity is interruptible (see 8.9.2.21). At the end of any such interval, the values of all related built-in variables shall be consistent with one another.

It is always safe to reference two or more related built-in variables in a condition within an `<only_if>`, `<wait_until>`, and so on. If one wants to reference multiple built-in variables in a series of elements (e.g. to copy two or more variables to ordinary variables using `<set>`), the elements need to be placed in an activity with the attribute `atomic="true"`.

7.4 Representation of integers

7.4.1 Non-negative integers shall be represented as strings of one or more ISO/IEC 10646 characters in the range DIGIT ZERO to DIGIT NINE ("0" to "9").

7.4.2 Negative integers shall be represented as the corresponding positive integer, preceded by a HYPHEN-MINUS character ("-").

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

 © ISO/IEC 2017 – All rights reserved

7.4.3 The canonical representation of a positive integer is the one that contains no leading DIGIT ZERO characters. The canonical representation of the integer zero is the one consisting of a single DIGIT ZERO character. The canonical representation of a negative integer is the one consisting of a HYPHEN-MINUS character followed by the canonical representation of the corresponding positive integer.

7.5 Representation of Booleans

7.5.1 The Boolean TRUE shall be represented as the string of ISO/IEC 10646 characters "`true`". The Boolean FALSE shall be represented as the string of ISO/IEC 10646 characters "`false`".

7.5.2 This representation is canonical.

7.6 Representation of universally unique identifiers (UUIDs)

7.6.1 Universally unique identifiers (UUIDs) shall be represented as strings of ISO/IEC 10646 characters. Each string shall contain characters from the union of the following sets:

a) DIGIT ZERO to DIGIT NINE ("`0`" to "`9`"), each representing a hexadecimal digit 0 to 9;

b) LATIN CAPITAL LETTER A to LATIN CAPITAL LETTER F ("`A`" to "`F`"), each representing a hexadecimal digit A to F;

c) LATIN SMALL LETTER A to LATIN SMALL LETTER F ("`a`" to "`f`"), each representing a hexadecimal digit A to F;

d) HYPHEN-MINUS ("-").

7.6.2 There shall be exactly 32 hexadecimal digits. There shall also be four HYPHEN-MINUS characters inserted at the following positions:

a) between the 8th and the 9th hexadecimal digit;

b) between the 12th and the 13th hexadecimal digit;

c) between the 16th and the 17th hexadecimal digit;

d) between the 20th and the 21st hexadecimal digit.

7.6.3 The canonical representation of a UUID is the one in which the characters listed in 7.6.1 b) are not used.

7.7 Representation of octet strings

7.7.1 Octet strings shall be represented as strings of ISO/IEC 10646 characters. Each string shall contain an even number (possibly zero) of characters from the union of the following sets:

a) DIGIT ZERO to DIGIT NINE ("`0`" to "`9`"), each representing a hexadecimal digit 0 through 9;

b) LATIN CAPITAL LETTER A to LATIN CAPITAL LETTER F ("`A`" to "`F`"), each representing a hexadecimal digit A through F;

c) LATIN SMALL LETTER A to LATIN SMALL LETTER F ("`a`" to "`f`"), each representing a hexadecimal digit A through F.

7.7.2 The canonical representation of an octet string is the one in which the characters listed in 7.7.1 b) are not used.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

7.8 XML documents

7.8.1 Assertions and activities shall be contained in W3C XML 1.0 documents. The version of XML shall be "`1.0`". The character encoding shall be either "`utf-8`" or "`utf-16`".

7.8.2 The root element of all such XML documents shall be the `<package>` element (see 8.1).

7.8.3 The XML documents shall be valid according to the XML schema specified in Annex A and according to the ASN.1 module specified in Annex B.

NOTE An implementation can use either the XML Schema or the ASN.1 Schema for validating assertions because the two schemas are equivalent.

8 Elements of the assertion language

8.1 Element `<package>`

8.1.1 Syntax

8.1.1.1 This element shall have the following attribute:

`name` (required) — the value of this attribute shall be a valid package name (see 8.1.2.5).

8.1.1.2 This element shall have a content consisting of the following (in order):

a) one `<author>` element — this element shall contain the name or description of the author of the package (a character string);

b) one `<description>` element — this element shall contain the description of the package (a character string);

c) zero or more `<assertion>` elements — this element represents an assertion and is specified in 8.2;

d) zero or more `<activity>` elements — this element represents an activity and is specified in 8.9.

8.1.2 Semantics

8.1.2.1 A package is a named container for assertions and activities.

8.1.2.2 Both assertions and activities may be referenced from a context outside their package.

8.1.2.3 Assertions are not referenced from any package, but may be referenced from contexts external to the assertion language. In particular, they are referenced when setting up a test and within test reports (see Clause 12).

8.1.2.4 Activities are normally referenced from assertions (either in an `<invoke>` element or in a `<bind>` element) or from other activities. In both cases, they may be referenced from either the same package or a different package.

8.1.2.5 The names of packages shall consist of strings of ISO/IEC 10646 characters that represent UUIDs (see 7.6). Each package name shall be globally unique.

8.1.2.6 Two package names shall be considered equal if and only if they contain the same sequence of digits and letters regardless of case.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

 © ISO/IEC 2017 – All rights reserved

8.1.2.7 The assertions in a package shall have distinct names. The activities in a package shall also have distinct names.

NOTE An assertion and an activity in a package can have identical names.

8.1.3 Example (non-normative)

```
<?xml version='1.0' encoding="utf-8"?>
<package name="734ED660-1183-13D0-A3A5-0410FFD77AE9">
   <author>
      ISO/IEC SC37
   </author>
   <description>
      Abcde abcde abcde
   </description>


   <assertion name="Capture2" model="BSPTesting">
      <description>
         Test the BioSPI_Capture function of a BSP.
      </description>
      <invoke activity="Capture"
         package="7346D660-1583-13D0-A3A5-00C0FFD756E3">
         <input name="BSPUuid" value=""/>
         <input name="BSPVersion" value="0"/>
         <input name="deviceIDOrNull" value="0"/>
         <input name="inserttimeouttime" value="15000"/>
         <input name="sourcepresenttimeouttime" value="10000"/>
         <input name="capturetimeouttime" value="20000"/>
      </invoke>
      <bind activity="EventHandler" function="BioAPI_EventHandler"/>
   </assertion>
</package>
```

8.2 Element <assertion> (child of <package>)

8.2.1 Syntax

8.2.1.1 This element shall have the following attributes:

a) `name` (required) — the value of this attribute shall be a valid assertion name (see 8.2.2.7);

b) `model` (required) — this attribute shall have one of the values "`applicationTesting`", "`frameworkTesting`", "`BSPTesting`"; it shall indicate the conformance testing model of the assertion.

8.2.1.2 This element shall have a content consisting of the following (in order):

a) one <description> element — this element shall contain a description of the assertion (a character string);

b) zero or more <input> elements — this element represents an input parameter of the assertion and is specified in 8.3;

c) one <invoke> element — this element represents the invocation of the primary activity of the assertion and is specified in 8.4;

d) zero or more <bind> elements — this element represents a binding between a standard BioAPI interface function and an activity and is specified in 8.8.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

8.2.2 Semantics

8.2.2.1 The `model` indicates which conformance testing model (see 6.2) shall be selected for the processing of the assertion, and thus, determines which component(s) of the model shall be associated with the abstract test engine.

8.2.2.2 If there is only one testing component, all calls required to be made to standard BioAPI interface functions of other standard BioAPI components as a result of processing the assertion shall be made by this component and all incoming calls to this component shall be processed according to the content of the assertion.

8.2.2.3 If there are two testing components, either component can make calls to standard BioAPI interface functions of other components and all incoming calls to either testing component shall be processed according to the content of the assertion.

8.2.2.4 If `model` is "`applicationTesting`", the testing model for BioAPI applications (see 6.2.5.1) shall be selected for this assertion, and the abstract test engine shall be associated with the application-testing framework.

8.2.2.5 If `model` is "`frameworkTesting`", the testing model for BioAPI frameworks (see 6.2.5.2) shall be selected for this assertion, and the abstract test engine shall be associated with both the framework-testing application and the framework-testing BSP at the same time.

8.2.2.6 If `model` is "`BSPTesting`", the testing model for BioAPI BSPs (see 6.2.5.3) shall be selected for this assertion, and the abstract test engine shall be associated with the BSP-testing application.

8.2.2.7 The names of assertions shall consist of strings of ISO/IEC 10646 characters that match the "NCName" production in W3C XML Namespaces.

8.2.2.8 The names of assertions shall be unique within a package.

8.2.3 Example (non-normative)

```
<assertion name="CreateTemplate1" model="BSPTesting">
   <description>
      Test the BioSPI_CreateTemplate function of a BSP.
      The UUID and version of the BSP must be provided
      as input to the test.
   </description>
   <input name="_uuid"/>
   <input name="_version"/>
   <invoke activity="CreateTemplate"
      package="7346D660-1583-13D0-A3A5-00C0FFD756E3">
      <input name="BSPUuid" var="_uuid"/>
      <input name="BSPVersion" var="_version"/>
      <input name="deviceIDOrNull" value="0"/>
      <input name="inserttimeouttime" value="15000"/>
      <input name="sourcepresenttimeouttime" value="10000"/>
      <input name="capturetimeouttime" value="20000"/>
   </invoke>
   <bind activity="EventHandler" function="BioAPI_EventHandler"/>
</assertion>
```

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

8.3 Element <input> (child of <assertion>)

8.3.1 Syntax

8.3.1.1 This element shall have the following attribute:

name (required) — the value of this attribute shall be a valid global variable name (see 7.2), which is to be the name of an input parameter of the assertion.

8.3.1.2 The content of this element shall be empty.

8.3.2 Semantics

8.3.2.1 This element represents an input parameter of an assertion.

Assertions cannot have output parameters.

8.3.2.2 Assertions with parameters cannot be processed unless a value is assigned to each parameter. The means of assigning values to input parameters of assertions is outside the scope of this document.

8.3.2.3 The value of the name attribute shall be a valid global variable name (see 7.2) and shall not begin with two consecutive LOW LINE characters ("_").

8.3.2.4 Input parameters of assertions shall be created and set to the values provided as input to the test.

8.3.2.5 Assigning values to assertion parameters is an essential part of the preparation of a test. For some implementations under test, the results of a test may depend on the values assigned to the parameters. The values used in a given test are documented in the standard test report (see Clause 12).

8.3.2.6 The names of the input parameters of an assertion shall be valid global variable names (see 7.2). The names of all global variables (including input parameters) shall be distinct.

The values assigned to assertion parameters cannot be changed during the processing of an assertion because all the language elements that assign or modify a global variable (see 8.6.2.3, 8.7.2.3, 8.12.2.2, 8.13.2.2, 8.14.2.2 and 8.17.2.9.1) do not permit the use of an assertion parameter as the variable to be modified.

8.3.3 Example (non-normative)

```
<input name="_uuid"/>
```

8.4 Element <invoke> (child of <assertion>)

8.4.1 Syntax

8.4.1.1 This element shall have the following attributes:

a) activity (required) — the value of this attriFbute shall be the name of an activity;

b) package (optional) — if this attribute is present, its value shall be the name of the package that contains the activity named in a).

8.4.1.2 This element shall have a content consisting of the following:

zero or more <input> elements — this element provides a value for an input parameter of the activity and is specified in 8.5.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

8.4.2 Semantics

8.4.2.1 This element designates the primary activity of the assertion and specifies the actual input parameters of its invocation. The processing of the assertion shall result in the execution of that activity with the provided input parameters. There shall be exactly one such activity for each assertion.

8.4.2.2 The activity may contain `<assert_condition>` elements with a `break_if_false` attribute (see 8.18.2.3). If a break occurs during the execution of the activity, the processing of the entire assertion shall terminate.

8.4.2.3 The set of `<input>` elements of the invocation shall match the input parameters of the activity as specified in 8.5.2.2.

8.4.2.4 The `package` attribute is mandatory if the activity is in a different package from the one that contains the assertion and is optional otherwise.

8.4.2.5 The activity may or may not have output parameters. If the primary activity of an assertion has output parameters, the values of all the output parameters are discarded when the invoked activity terminates.

NOTE This is similar to invoking an activity with output parameters from another activity without providing any `<output>` elements matching the output parameters. That is allowed, and is useful when the invoking activity is not interested in the values of the output parameters of the invoked activity.

8.4.2.6 The `<invoke>` element of assertions shall not have a `break_on_break` attribute (see 8.15.2.6.5) and shall not have an `<only_if>` child element (see 8.16).

8.4.3 Example (non-normative)

```
<invoke activity="CreateTemplate"
    package="7346D660-1583-13D0-A3A5-00C0FFD756E3">
    <input name="BSPUuid" var="_uuid"/>
    <input name="BSPVersion" var="_version"/>
    <input name="deviceIDOrNull" value="0"/>
    <input name="inserttimeouttime" value="15000"/>
    <input name="sourcepresenttimeouttime" value="10000"/>
    <input name="capturetimeouttime" value="20000"/>
</invoke>
```

8.5 Element `<input>` (child of `<invoke>`)

8.5.1 Syntax

8.5.1.1 This element shall have the following attributes:

a) `name` (required) — the value of this attribute shall be the name of an input parameter of the activity or standard BioAPI interface function being invoked;

b) `value` (optional) — if this attribute is present, its value shall be the value to be assigned to the input parameter named in a);

c) `var` (optional) — if this attribute is present, its value shall be a valid name of a variable (see 7.2), whose value is to be assigned to the input parameter.

8.5.1.2 Exactly one of the attributes `value` and `var` shall be present.

8.5.1.3 The content of this element shall be empty.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

 © ISO/IEC 2017 – All rights reserved

8.5.2 Semantics

8.5.2.1 This element represents the assignment of a value to an input parameter of an activity or a standard BioAPI interface function (see Clause 9) in an invocation.

8.5.2.2 The set of `<input>` elements of an invocation shall match the input parameters of the activity or of the standard BioAPI interface function being invoked as specified in the two following subclauses.

8.5.2.2.1 In the case of activity invocation, for each `<input>` element of the activity, there shall be at most one `<input>` element in the invocation whose `name` attribute equals the `name` attribute of the former and vice versa. For each `<input>` element in the invocation, there shall be an `<input>` element of the activity whose `name` attribute equals the `name` attribute of the former. The order of the `<input>` elements in the activity and in the invocation need not be the same.

8.5.2.2.2 In the case of function invocation, for each input parameter of the function, there shall be at most one `<input>` element in the invocation whose `name` attribute equals the name of the input parameter of the function and vice versa. For each `<input>` element in the invocation, there shall be an input parameter of the function whose `name` equals the `name` attribute of the former. The `<input>` elements in the invocation may appear in any order.

NOTE Clause 9 specifies the names of all standard BioAPI interface functions and the names of their input and output parameters as they are to appear in the invocation of those functions.

8.5.2.3 If the `var` attribute is present, its value shall be the name of a variable (see 7.2) that already exists prior to the invocation. The value of the variable shall be assigned to the input parameter. The variable may be either global or local.

8.5.2.4 If the `value` attribute is present, its value shall be assigned to the input parameter.

8.5.2.5 In the case of activity invocation, the input parameter shall be created as a local variable of the activity being invoked and shall be set to the specified value.

8.5.2.6 In the case of function invocation, the specified value shall be converted into a native form suitable for the corresponding parameter of the underlying standard BioAPI interface function as specified in Clause 9 and its individual subclauses.

8.5.3 Example (non-normative)

```
<input name="BSPUuid" var="_uuid"/>
```

8.6 Element `<output>` (child of `<invoke>`)

8.6.1 Syntax

8.6.1.1 This element shall have the following attributes:

a) `name` (required) — the value of this attribute shall be the name of an output parameter of the activity or standard BioAPI interface function being invoked;

b) `setvar` (required) — the value of this attribute shall be a valid name of a variable (see 7.2) to which the value of the output parameter is to be assigned.

8.6.1.2 The content of this element shall be empty.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

8.6.2 Semantics

8.6.2.1 This element represents the assignment of the value of an output parameter of an activity or standard BioAPI interface function to a variable (see Clause 9) in an invocation.

8.6.2.2 The set of `<output>` elements of an invocation shall match the output parameters of the activity or standard BioAPI interface function being invoked as specified in the two following subclauses.

8.6.2.2.1 In the case of activity invocation, for each `<output>` element of the activity, there shall be at most one `<output>` element in the invocation whose `name` attribute equals the `name` attribute of the former. For each `<output>` element in the invocation, there shall be an `<output>` element of the activity whose `name` attribute equals the `name` attribute of the former. The order of the `<output>` elements in the activity and in the invocation need not be the same.

8.6.2.2.2 In the case of function invocation, for each output parameter of the function, there shall be at most one `<output>` element in the invocation whose `name` attribute equals the `name` of the output parameter of the function. For each `<output>` element in the invocation, there shall be an output parameter of the function whose `name` equals the `name` attribute of the former. The `<output>` elements in the invocation may appear in any order.

NOTE Clause 9 specifies the names of all standard BioAPI interface functions and the names of their input and output parameters as they are to appear in the invocation of those functions.

8.6.2.3 The value of the `setvar` attribute shall be a valid global or local variable name (see 7.2), shall not be an input parameter of the assertion being processed (see 8.3), and shall not begin with two consecutive LOW LINE characters ("_"). The variable may already exist prior to the invocation or may be a new variable that is to be created when the invoked activity or function terminates.

8.6.2.4 The values of the setvar attributes of the `<output>` elements in an invocation shall all be distinct.

8.6.2.5 When the invoked activity or function terminates, if the variable does not exist, it shall be created. If the variable is local, it shall be associated with the current (invoking) activity, so that it will be destroyed when that activity terminates.

8.6.2.6 In the case of activity invocation, the variable shall be set to the final value of the output parameter of the invoked activity, which is the value that the parameter has immediately before being destroyed. The output parameter shall exist when the invoked activity terminates.

NOTE The output parameter (as a local variable) can be created at any time during the execution of the invoked activity.

8.6.2.7 In the case of function invocation, the value of the corresponding output parameter of the underlying standard BioAPI interface function shall be converted from its native form into a character string as specified in the individual subclauses of Clause 9 and the variable shall be set to the resulting character string.

8.7 Element `<return>` (child of `<invoke>`)

8.7.1 Syntax

8.7.1.1 This element shall have the following attribute:

`setvar` (required) — the value of this attribute shall be a valid name of a variable (see 7.2) to which the return value is to be assigned.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

 © ISO/IEC 2017 – All rights reserved

8.7.1.2 The content of this element shall be empty.

8.7.2 Semantics

8.7.2.1 This element represents the assignment of the return value of a standard BioAPI interface function to a variable (see Clause 9 and its individual subclauses) in an invocation.

8.7.2.2 There shall be at most one `<return>` element in the invocation of any standard BioAPI interface function.

8.7.2.3 The value of the `setvar` attribute shall be a valid global or local variable name (see 7.2), shall not be an input parameter of the assertion being processed (see 8.3), and shall not begin with two consecutive LOW LINE characters ("_"). This variable may already exist prior to the invocation or may be a new variable that is to be created when the invoked activity or function terminates.

8.7.2.4 When the invoked function terminates, if the variable does not exist, it shall be created. If the variable is local, it shall be associated with the current (invoking) activity, so that it will be destroyed when the current activity terminates.

8.7.2.5 The return value of the standard BioAPI interface function shall be converted from its native form into a character string as specified in Clause 9 and the variable shall be set to the resulting character string.

8.8 Element `<bind>` (child of `<assertion>`)

8.8.1 Syntax

8.8.1.1 This element shall have the following attributes:

a) `function` (required) — the value of this attribute shall be the name of a standard BioAPI interface function (see Clause 9);

b) `activity` (required) — the value of this attribute shall be the name of an activity;

c) `package` (optional) — if this attribute is present, its value shall be the name of the package that contains the activity named in b).

8.8.1.2 The content of this element shall be empty.

8.8.2 Semantics

8.8.2.1 This element represents an association between a standard BioAPI interface function (exposed by a testing component) and an activity, whereby the activity is automatically invoked in response to an incoming call to the standard BioAPI interface function.

8.8.2.2 The association (binding) shall be in effect through the processing of the assertion.

NOTE Bindings are established before the primary activity of the assertion starts execution and cannot be disabled or changed.

8.8.2.3 The standard BioAPI interface function identified by the `function` attribute shall be one of the functions exposed by the testing component(s).

NOTE The conformance testing model of an assertion, specified by the `model` attribute of the assertion, determines which testing component(s) exist for that assertion (see 6.2), and thus which functions can be referenced in a binding.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

8.8.2.4 The same standard BioAPI interface function shall not be referenced in two different <bind> elements in the same assertion.

8.8.2.5 The bound activity shall have input and output parameters determined from the input and output parameters of the function invocation scheme (specified in Clause 9) of the standard BioAPI interface function to which it is bound as follows.

a) In the conformance testing model for BioAPI applications, all the input and output parameters of the function invocation shall be input parameters of the bound activity. In addition, there shall be an input parameter named return.

b) In the conformance testing model for BioAPI frameworks and in the conformance testing model for BioAPI BSPs, all the input parameters of the function invocation shall be output parameters of the bound activity and all the output parameters of the function invocation shall be input parameters of the bound activity. In addition, there shall be an output parameter named return.

8.8.2.6 The bound activity shall be invoked each time a testing component receives an incoming call to the standard BioAPI interface function to which the activity is bound as specified in 8.9.2.7 and 8.9.2.8.

8.9 Element <activity> (child of <package>)

8.9.1 Syntax

8.9.1.1 This element shall have the following attributes:

a) name (required) — the value of this attribute shall be a valid activity name (see 8.9.2.22);

b) atomic (optional) — this attribute shall indicate whether the execution of the activity is not interruptible (the default is "false").

8.9.1.2 This element shall have a content consisting of the following (in order):

a) zero or more <input> elements — this element represents an input parameter of the activity and is specified in 8.10;

b) zero or more <output> elements — this element represents an output parameter of the activity and is specified in 8.11;

c) zero or more occurrences of any of the following elements in any order:

1) <set> — this element represents the assignment of a value to a new variable or to an existing variable and is specified in 8.12;

2) <add> — this element represents the addition of an integer to the value (representing an integer) of an existing variable and is specified in 8.13;

3) <subtract> — this element represents the subtraction of an integer from the value (representing an integer) of an existing variable and is specified in 8.14;

4) <wait_until> — this element represents a suspension of the execution of the current activity until a condition is verified and is specified in 8.17;

5) <assert_condition> — this element represents the issuance of a conformity response based on a given condition and is specified in 8.18;

6) <invoke> — this element represents the invocation of an activity or of a standard BioAPI interface function and is specified in 8.15.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

8.9.2 Semantics

8.9.2.1 Activities are the executable units of the assertion language and consist of ordered sequences of zero or more elements representing the following actions:

a) assigning a variable;

b) suspending execution of the activity until a condition is verified;

c) invoking a standard BioAPI interface function;

d) issuing a conformity response based on a condition;

e) invoking an activity.

8.9.2.2 The abstract test engine shall perform the actions of an activity in order.

8.9.2.3 An activity shall have a priority, which can be low, medium, or high. At most, one activity may be in execution at any given time during the processing of an assertion. The abstract test engine shall have the ability to interrupt the execution of an activity in order to execute an activity with a higher priority (see 8.9.2.21).

8.9.2.4 When an assertion is submitted for processing, the abstract test engine shall invoke the primary activity of the assertion as a high-priority activity.

8.9.2.5 When an activity invokes another activity, the invoked activity shall be given the same priority as the invoking activity.

8.9.2.6 When one of the following elements

a) a `<wait_until>` element, or

b) an `<invoke>` element invoking a standard BioAPI interface function

occurs for the first time in the primary activity of an assertion or in an activity that has been (directly or indirectly) invoked by it, the priority of the activity in which the element occurs shall be changed from high to low immediately before the element is processed. If the activity in which the element occurs is not the primary activity of an assertion, the priority of every activity (including the primary activity) that has (directly or indirectly) invoked that activity shall be changed to low as well.

8.9.2.7 In the conformance testing model for BioAPI applications (see 6.2.5.1), when the testing component receives an incoming call to a standard BioAPI interface function, the actions specified in the four following subclauses shall be performed.

8.9.2.7.1 If the function being called belongs to the BioAPI interface, the incoming call shall be relayed to the same standard BioAPI interface function exposed by the normal framework. The new (relayed) call shall have the same native parameter values as the original incoming call.

8.9.2.7.2 If the function being called belongs to the application callback interface, the incoming call shall be relayed to the same standard BioAPI interface function exposed by the application under test. The new (relayed) call shall have the same native parameter values as the original incoming call.

8.9.2.7.3 When the relayed call returns but before returning from the original incoming call, if there is an activity bound to the standard BioAPI interface function being called (see 8.8), the abstract test engine shall interrupt the execution of the current low-priority activity and shall invoke the bound activity as a high-priority activity (but see 8.9.2.9).

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

8.9.2.7.4 The input parameters of the bound activity invocation shall be set from the native input parameters of the incoming call and from the native output parameters and return value of the relayed call that has just returned, as specified in the subclauses of Clause 9 with the heading titled "Bound activity invocation input", relative to the standard BioAPI interface function.

8.9.2.8 In the conformance testing model for BioAPI frameworks (see 6.2.5.2) and in the conformance testing model for BioAPI BSPs (see 6.2.5.3), when the testing component receives an incoming call, the actions specified in the four following subclauses shall be performed.

8.9.2.8.1 If there is an activity bound to the function being called (see 8.8), the abstract test engine shall interrupt the execution of the current low-priority activity and shall invoke the bound activity (but see 8.9.2.9) with its priority set as follows:

a) if the function is `BioSPI_Cancel`, the priority shall be high;

b) if the function belongs to the BioSPI interface but is not `BioSPI_Cancel`, the priority shall be medium;

c) otherwise, the priority shall be high.

8.9.2.8.2 The input parameters of the bound activity invocation shall be set from the native input parameters of the incoming call as specified in the subclauses of Clause 9 with the heading titled "Bound activity invocation input" relative to the standard BioAPI interface function.

8.9.2.8.3 When the bound activity terminates, the native output parameters and the return value of the incoming call shall be set from the output parameters of the activity as specified in the subclauses of Clause 9 with the heading titled "Bound activity invocation output" relative to the standard BioAPI interface function.

8.9.2.8.4 If there is no activity bound to the function being called, then the abstract test engine shall set the native output parameters and return value of the incoming call as specified in the individual subclauses of Clause 9 with the heading titled "Default output".

8.9.2.9 If an incoming call to a function that has a bound activity (with a given priority) is received while the abstract test engine is executing another activity with the same or a higher priority, the new activity invocation shall be added to a queue using a separate queue for each priority.

8.9.2.10 Each time an activity terminates or the priority of the current activity is changed from high to low, the abstract test engine shall determine which queue, among those that are not empty, holds the activity invocations with the highest priority. The oldest activity invocation in that queue shall be removed from the queue and processed.

8.9.2.11 The execution of any activity shall start with the creation of an execution context that is relative to one particular invocation of the activity. The execution context shall act as a container for the local variables of the activity (including its input and output parameters) and shall include an indication of the current execution position within the activity.

8.9.2.12 After the execution context is created, each of the input parameters of the activity shall be created (as a local variable) in the execution context and shall be set to the following value:

a) if the invocation of the activity provides an `<input>` element for that output parameter, the provided value (see 8.5.2.5);

b) otherwise, an empty string.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

8.9.2.13 The elements of the activity shall then be processed in order, from the first element to the last element, unless a break occurs as specified in 8.9.2.17.

8.9.2.14 If no break occurs, then after the last element of the activity has been processed, one of the following actions shall be performed for each output parameter of the activity:

a) if the invocation of the activity provides an `<output>` element for that output parameter, the final value of the output parameter shall be assigned to the variable referenced in the `<output>` element as specified in 8.6.2.3;

b) otherwise, the final value of the output parameter shall be discarded.

8.9.2.15 The execution context relative to the present invocation of the activity shall then be destroyed.

8.9.2.16 If the activity was invoked by an activity, the execution of the invoking activity shall resume. If the activity was the primary activity of an assertion, the processing of the entire assertion shall terminate.

8.9.2.17 A break is said to occur within the execution of an activity in the following two cases:

a) if an activity contains an `<assert_condition>` element with a `break_if_false` attribute with a value of "`true`", when the condition in the `<assert_condition>` element evaluates to "`false`", a break is said to occur within that activity;

b) if an activity contains an `<invoke>` element with a `break_on_break` attribute with a value of "`true`", when the invoked activity terminates because of a break (see 8.9.2.18), a break is said to occur within the invoking activity.

8.9.2.18 When a break occurs within an activity [because of either 8.9.2.17 a) or b)], the abstract test engine shall:

a) skip the processing of the remaining elements of the activity;

b) skip the assignment of the values of the output parameters to the variables referenced in the corresponding `<output>` elements in the invocation of the activity (if any);

c) proceed with the destruction of the execution context and resume execution of the invoking activity (if any).

NOTE Item b) implies that, if a variable corresponding to an output parameter did not exist before the invocation, it is not created when the invoking activity is resumed.

If 8.9.2.17 b) applies to the invoking activity, the execution of the invoking activity will be abandoned immediately after being resumed.

8.9.2.19 Activities may create new global variables or change the value of existing ones.

8.9.2.20 An activity may not be interrupted by another activity with the same or a lower priority (see 8.9.2.9).

8.9.2.21 An activity may be interrupted by an activity with a higher priority. Interruptions may occur at any time, either before or after each element of the activity or during the processing of an element of the activity, with the following exceptions:

a) no interruption shall occur during the processing of a `<set>`, `<add>`, `<subtract>` or `<assert_condition>` element;

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

b) during the processing of an <invoke> of a standard BioAPI interface function, no interruption shall occur during the evaluation of the condition (if any) and the assignment of the input parameters, and during the disposition of the output parameters and return value;

NOTE 1 Interruptions are allowed while the function is in execution.

c) during the processing of a <wait_until>, no interruption shall occur during each evaluation of the condition;

NOTE 2 Interruptions are allowed between two consecutive evaluations of the condition.

d) an activity that has an atomic attribute with the value "true" shall not be interrupted at any time (from the creation of the input parameters until after the destruction of the output parameters).

8.9.2.22 The names of activities shall consist of strings of ISO/IEC 10646 characters that match the "NCName" production in W3C XML Namespaces.

8.9.2.23 The names of activities shall be unique within a package.

8.9.3 Example (non-normative)

```
<?xml version='1.0' encoding="utf-8"?>
<package name="73668660-1583-1AD0-A3A5-09C0FF4756E3">
   <author>
      ISO/IEC SC37
   </author>
   <description>
      Abcde abcde abcde
   </description>


<activity name="LoadAndAttach">
 <input name="BSPUuid"/>
 <input name="BSPVersion"/>
 <input name="deviceIDOrNull"/>
 <input name="BSP"/>
 <input name="eventtimeouttime"/>


 <set name="_deviceIDOrNull" var="deviceIDOrNull"/>


<invoke function="BioSPI_BSPLoad">
 <input name="Reserved" value=""/>
 <input name="BSPUuid" var="BSPUuid"/>
 <input name="eventHandler" value="1"/>
 <input name="context" value="1"/>
 <return setvar="return"/>
</invoke>


<assert_condition
      response_if_true="undecided"
      break_if_false="true">
  <equal_to var1="return" var2="__BioAPI_OK"/>
</assert_condition>


<wait_until
      timeout_var="eventtimeouttime"
      setvar="eventtimeoutflag"
      var="_insert"/>


<assert_condition
      response_if_true="undecided"
      break_if_false="true">
```

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

```
      <not var="eventtimeoutflag"/>
</assert_condition>


<invoke function="BioSPI_BSPAttach">
  <input name="BSPUuid" var="BSPUuid"/>
  <input name="Version" var="BSPVersion"/>
  <input name="DeviceID" var="_deviceID"/>
  <input name="Reserved1" value="0"/>
  <input name="Reserved2" value="0"/>
  <input name="BSPHandle" var="BSP"/>
  <input name="Reserved3" value="0"/>
  <input name="Reserved4" value=""/>
  <input name="Reserved5" value=""/>
  <input name="Reserved6" value=""/>
  <return setvar="return"/>
</invoke>


<assert_condition
      response_if_true="undecided"
      break_if_false="true">
  <equal_to var1="return" var2="__BioAPI_OK"/>
</assert_condition>


</activity>



<activity name="EventHandler">
 <input name="BSPUuid"/>
 <input name="context"/>
 <input name="deviceID"/>
 <input name="reserved"/>
 <input name="eventType"/>


 <set name="_BSPUuid" var="BSPUuid"/>
 <set name="_context" var="context"/>


 <set name="_deviceID" var="deviceID">
  <only_if>
   <not>
    <existing var="_deviceID"/>
   </not>
   <or>
    <equal_to var1="eventType" var2="__BioAPI_NOTIFY_INSERT"/>
    <equal_to var1="eventType"
              var2="__BioAPI_NOTIFY_SOURCE_PRESENT"/>
   </or>
   <or>
    <equal_to var1="_deviceIDOrNull" value2="0"/>
    <equal_to var1="_deviceIDOrNull" var2="deviceID"/>
   </or>
  </only_if>
 </set>


 <set name="_insert" value="true">
  <only_if>
   <equal_to var1="eventType" var2="__BioAPI_NOTIFY_INSERT"/>
   <equal_to var1="_deviceID" var2="deviceID"/>
  </only_if>
 </set>


 <set name="_insert" value="false">
  <only_if>
   <equal_to var1="eventType" var2="__BioAPI_NOTIFY_REMOVE"/>
```

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

```
   <equal_to var1="_deviceID" var2="deviceID"/>
  </only_if>
 </set>


 <set name="_sourcePresent" value="true">
  <only_if>
   <equal_to var1="eventType"
              var2="__BioAPI_NOTIFY_SOURCE_PRESENT"/>
   <equal_to var1="_deviceID" var2="deviceID"/>
  </only_if>
 </set>


 <set name="_sourcePresent" value="false">
  <only_if>
   <equal_to var1="eventType"
              var2="__BioAPI_NOTIFY_SOURCE_REMOVED"/>
   <equal_to var1="_deviceID" var2="deviceID"/>
  </only_if>
 </set>


 <set name="_eventtype" var="eventType">
  <only_if>
   <equal_to var1="_deviceID" var2="deviceID"/>
  </only_if>
 </set>


 <assert_condition
      response_if_false="fail">
  <equal_to var1="reserved" value2="0"/>
 </assert_condition>


</activity>



<activity name="CreateTemplate">
  <input name="BSPUuid"/>
  <input name="BSPVersion"/>
  <input name="deviceIDOrNull"/>
  <input name="inserttimeouttime"/>
  <input name="sourcepresenttimeouttime"/>
  <input name="capturetimeouttime"/>


  <invoke activity="LoadAndAttach" break_on_break="true">
    <input name="BSPUuid" var="BSPUuid"/>
    <input name="BSPVersion" var="BSPVersion"/>
    <input name="deviceIDOrNull" var="deviceIDOrNull"/>
    <input name="BSP" value="1"/>
    <input name="eventtimeouttime" var="inserttimeouttime"/>
  </invoke>


  <wait_until
        timeout_var="sourcepresenttimeouttime"
        setvar="eventtimeoutflag"
        var="_sourcePresent"/>


  <assert_condition
        response_if_true="undecided"
        break_if_false="true">
    <not var="eventtimeoutflag"/>
  </assert_condition>
```

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

```
  <invoke function="BioSPI_Capture">
    <input name="BSPHandle" value="1"/>
    <input name="Purpose" var="__BioAPI_PURPOSE_ENROLL"/>
    <input name="Timeout" var="capturetimeouttime"/>
    <output name="CapturedBIR" setvar="bir"/>
    <output name="AuditData" setvar="auditbir"/>
    <return setvar="return"/>
  </invoke>


 ...
</activity>


</package>
```

8.10 Element <input> (child of <activity>)

8.10.1 Syntax

8.10.1.1 This element shall have the following attribute:

name (required) — the value of this attribute shall be a valid local variable name (see 7.2), which is to be the name of an input parameter of the activity.

8.10.1.2 The content of this element shall be empty.

8.10.2 Semantics

8.10.2.1 This element represents an input parameter of an activity.

8.10.2.2 Input parameters of activities are local variables (see 7.2).

8.10.2.3 The names of the input parameters of an activity shall be valid local variable names (see 7.2).

8.10.2.4 The names of all local variables of an activity (including the input and output parameters of the activity) shall be distinct.

8.11 Element <output> (child of <activity>)

8.11.1 Syntax

8.11.1.1 This element shall have the following attribute:

name (required) — the value of this attribute shall be a valid local variable name (see 7.2), which is to be the name of an output parameter of the activity.

8.11.1.2 The content of this element shall be empty.

8.11.2 Semantics

8.11.2.1 This element represents an output parameter of an activity.

8.11.2.2 Output parameters of activities are local variables (see 7.2).

8.11.2.3 The names of the output parameters of an activity shall be valid local variable names.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

8.11.2.4 The names of all local variables of an activity (including the input and output parameters of the activity) shall be distinct.

8.12 Element `<set>`

8.12.1 Syntax

8.12.1.1 This element shall have the following attributes:

a) `name` (required) — the value of this attribute shall be a valid name of a variable (see 7.2), which is to be assigned a value (or created and then assigned a value);

b) `value` (optional) — if this attribute is present, its value shall be the value to be assigned to the variable referenced in a);

c) `var` (optional) — if this attribute is present, its value shall be a valid name of a variable (see 7.2), whose value is to be assigned to the variable referenced in a).

8.12.1.2 One and only one of the attributes value and var shall be present.

8.12.1.3 This element shall have a content consisting of the following:

an optional `<only_if>` element — this element represents a condition and is specified in 8.16.

8.12.2 Semantics

8.12.2.1 This element represents the assignment of a value to a variable, possibly subject to a condition.

8.12.2.2 The value of the `name` attribute shall be a valid global or local variable name (see 7.2), shall not be an input parameter of the assertion being processed (see 8.3), and shall not begin with two consecutive LOW LINE characters ("_"). The variable may exist prior to the assignment or may be a new variable created by the assignment.

8.12.2.3 If there is an `<only_if>` child element, the condition shall be evaluated (see 8.16).

8.12.2.4 The result of the evaluation shall be a valid representation of a Boolean (see 7.5).

8.12.2.5 If the result of the evaluation is "`true`", the variable whose name is the value of the name attribute shall be set as specified in the three following subclauses.

8.12.2.5.1 If the variable does not exist, it shall be created.

8.12.2.5.2 If the `var` attribute is present, its value shall be the name of an existing variable. The value of that variable shall be assigned to the variable whose name is the value of the `name` attribute.

8.12.2.5.3 If the `value` attribute is present, its value shall be assigned to the variable whose name is the value of the `name` attribute.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

8.13 Element <add>

8.13.1 Syntax

8.13.1.1 This element shall have the following attributes:

a) name (required) — the value of this attribute shall be a valid name of a variable (see 7.2) whose value is to be modified;

b) value (optional) — if this attribute is present, its value shall represent an integer to be added to the current value (representing an integer) of the variable referenced in a);

c) var (optional) — if this attribute is present, its value shall be a valid name of a variable (see 7.2) whose value represents an integer to be added to the current value of the variable referenced in a).

8.13.1.2 One and only one of the attributes value and var shall be present.

8.13.1.3 This element shall have a content consisting of the following:

An optional <only_if> element — this element represents a condition and is specified in 8.16.

8.13.2 Semantics

8.13.2.1 This element represents the addition of an integer to the value (representing an integer) of a variable (see 7.4), possibly subject to a condition.

8.13.2.2 The value of the name attribute shall be a valid global or local variable name (see 7.2), shall not be an input parameter of the assertion being processed (see 8.3), and shall not begin with two consecutive LOW LINE characters ("_"). The variable shall exist prior to the assignment and its value shall be a valid representation of an integer (see 7.4).

8.13.2.3 If there is an <only_if> child element, the condition shall be evaluated (see 8.16).

8.13.2.4 The result of the evaluation shall be a valid representation of a Boolean (see 7.5).

8.13.2.5 If the result of the evaluation is "true", the variable whose name is the value of the name attribute shall be set as specified in the three following subclauses.

8.13.2.5.1 The variable shall be set to the canonical representation of an integer which is the sum of two operands. The first operand is the integer represented by the current value of the variable. The second operand shall be determined as follows.

8.13.2.5.2 If the var attribute is present, its value shall be the name of an existing variable. The value of that variable shall be a valid representation of an integer (see 7.4). This integer is the second operand.

8.13.2.5.3 If the value attribute is present, its value shall be a valid representation of an integer (see 7.4). This integer is the second operand.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

8.14 Element <subtract>

8.14.1 Syntax

8.14.1.1 This element shall have the following attributes:

a) name (required) — the value of this attribute shall be a valid name of a variable (see 7.2) whose value is to be modified;

b) value (optional) — if this attribute is present, its value shall represent an integer to be subtracted from the current value of the variable referenced in a);

c) var (optional) — if this attribute is present, its value shall be a valid name of a variable (see 7.2) whose value represents an integer to be subtracted from the current value of the variable referenced in a).

8.14.1.2 One and only one of the attributes value and var shall be present.

8.14.1.3 This element shall have a content consisting of the following:

An optional <only_if> element — this element represents a condition and is specified in 8.16.

8.14.2 Semantics

8.14.2.1 This element represents the subtraction of an integer from the value (representing an integer) of a variable (see 7.4), possibly subject to a condition.

8.14.2.2 The value of the name attribute shall be a valid global or local variable name (see 7.2), shall not be an input parameter of the assertion being processed (see 8.3), and shall not begin with two consecutive LOW LINE characters ("_"). The variable shall exist prior to the assignment and its value shall be a valid representation of an integer (see 7.4).

8.14.2.3 If there is an <only_if> child element, the condition shall be evaluated (see 8.16).

8.14.2.4 The result of the evaluation shall be a valid representation of a Boolean (see 7.5).

8.14.2.5 If the result of the evaluation is "true", the variable whose name is the value of the name attribute shall be set as specified in the three following subclauses.

8.14.2.5.1 The variable shall be set to the canonical representation of an integer which is the difference between two operands. The first operand is the integer represented by the current value of the variable. The second operand shall be determined as follows.

8.14.2.5.2 If the var attribute is present, its value shall be the name of an existing variable. The value of that variable shall be a valid representation of an integer (see 7.4). This integer is the second operand.

8.14.2.5.3 If the value attribute is present, its value shall be a valid representation of an integer (see 7.4). This integer is the second operand.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

8.15 Element <invoke> (child of <activity>)

8.15.1 Syntax

8.15.1.1 This element shall have the following attributes:

a) activity (optional) — the value of this attribute shall be the name of an activity;

b) package (optional) — if this attribute is present, its value shall be the name of the package that contains the activity named in a);

c) break_on_break (optional) — if this attribute is present, it shall have one of the values "false" or "true". It indicates whether a break occurring in the invoked activity shall cause the current activity to be abandoned as well. The default is "false";

d) function (optional) — the value of this attribute shall be the name of a standard BioAPI interface function;

e) timeout_value (optional) — if this attribute is present, its value indicates the maximum duration of time (in milliseconds) allowed for the invocation;

f) timeout_var (optional) — if this attribute is present, its value shall be a valid name of a variable (see 7.2), whose value indicates the maximum duration of time (in milliseconds) allowed for the invocation;

g) setvar (optional) — if this attribute is present, its value shall be a valid variable name (see 7.2).

8.15.1.2 Exactly one of the attributes activity and function shall be present.

8.15.1.3 The attributes package and break_on_break shall not be present unless the attribute activity is present.

8.15.1.4 The attributes timeout_var, timeout_value, and setvar shall not be present unless the attribute function is present.

8.15.1.5 At most, one of the attributes timeout_var and timeout_value shall be present.

8.15.1.6 The setvar attribute shall not be present unless either the timeout_value attribute or the timeout_var attribute is present.

8.15.1.7 This element shall have a content consisting of the following (in order):

a) an optional <only_if> element — this element represents a condition and is specified in 8.16;

b) zero or more <input> elements — this element provides a value for an input parameter of the activity or standard BioAPI interface function being invoked and is specified in 8.5;

c) zero or more <output> elements — this element references a variable which is to be assigned from an output parameter of the activity or function being invoked and is specified in 8.6;

d) an optional <return> element — this element references a variable which is to be assigned from the return value of the function being invoked and is specified in 8.7.

8.15.2 Semantics

8.15.2.1 This element represents an invocation of an activity or of a standard BioAPI interface function from an activity.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

8.15.2.2 If there is an `<only_if>` child element, the condition shall be evaluated (see 8.16).

8.15.2.3 The result of the evaluation shall be a valid representation of a Boolean (see 7.5).

8.15.2.4 If the result of the evaluation is "`true`", the invocation shall be performed as specified in the following subclauses; otherwise, no further action shall be performed for this `<invoke>` element.

8.15.2.5 In case of activity invocation, the activity being invoked shall be an existing activity that may be either in the same package as the invoking activity or in a different package (see 8.15.2.6.4). In case of function invocation, the function being invoked shall be one of the standard BioAPI interface functions specified in Clause 9.

8.15.2.6 In the case of activity invocation, the five following subclauses apply.

8.15.2.6.1 The set of `<input>` elements of the invocation shall match the input parameters of the activity as specified in 8.5.2.2.

8.15.2.6.2 The set of `<output>` elements of the invocation shall match the output parameters of the activity as specified in 8.6.2.2.

8.15.2.6.3 The `<return>` element shall not be present.

8.15.2.6.4 The `package` attribute, if present, shall indicate the package in which the activity being invoked is. This attribute is mandatory if the activity being invoked is in a different package from the one that contains the invoking activity and is optional otherwise.

8.15.2.6.5 If the attribute `break_on_break` is present and its value is "`true`", then if the activity being invoked is abandoned because of a break (see 8.9.2.17), the current activity shall be abandoned as well.

8.15.2.7 In the case of function invocation, the three following subclauses apply.

8.15.2.7.1 The set of `<input>` elements of the invocation shall match the input parameters of the function as specified in 8.5.2.2.

8.15.2.7.2 The set of `<output>` elements of the invocation shall match the output parameters of the function as specified in 8.6.2.2.

8.15.2.7.3 The `<return>` element may be present (see 8.7.2.2).

8.15.2.8 If the `timeout_value` attribute is present, its value shall be a valid representation of an integer (see 7.4) that specifies the maximum duration allowed for the invocation (in milliseconds). If the `timeout_var` attribute is present, its value shall be the name of an existing variable and the value of that variable shall be a valid representation of an integer (see 7.4) that specifies the maximum duration. Otherwise, there shall be no maximum duration.

An implementation of this document may abandon the execution of a test that has lasted beyond a reasonable amount of time. Such a behaviour would not be in violation of 8.15.2.8.

8.15.2.9 The invocation shall proceed regardless of the specified maximum duration, even if this is zero or negative. If it is zero or negative, the abstract test engine shall immediately determine that the maximum duration has been exceeded.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

 © ISO/IEC 2017 – All rights reserved

8.15.2.10 If the `setvar` attribute is present, the four following subclauses apply.

8.15.2.10.1 The value of the `setvar` attribute shall be a valid global or local variable name (see 7.2), shall not be an input parameter of the assertion being processed (see 8.3), and shall not begin with two consecutive LOW LINE characters ("_"). The variable may exist prior to the assignment or may be a new variable created by the assignment.

8.15.2.10.2 If the maximum duration is exceeded before the invocation returns, the variable shall be created (if it does not exist) and shall be set to "`true`".

8.15.2.10.3 If the invocation returns before the maximum duration is exceeded, then the variable shall be created (if it does not exist) and shall be set to "`false`".

8.15.2.10.4 The variable shall not be created (if it does not exist before the invocation) and shall not be assigned except as specified in the two previous subclauses.

8.15.2.11 When an activity or a function is invoked, the execution of the current activity shall be suspended until the invoked activity or function terminates or until the maximum duration has been exceeded.

8.15.2.12 Before the activity or function being invoked starts, all input parameters for which an `<input>` element was provided in the invocation (if any) shall be set from the variables or values provided in those `<input>` elements as specified in 8.5.2.5. The remaining input parameters shall be assigned from an empty string.

8.15.2.13 If the invoked activity or function terminates without exceeding the maximum duration, the two following subclauses apply.

8.15.2.13.1 The values of each output parameter for which an `<output>` element was provided in the invocation (if any) shall be assigned to the variable referenced in the `<output>` element as specified in 8.6.2.3.

8.15.2.13.2 In case of function invocation, if there is a `<return>` element in the invocation, the return value shall be assigned to the variable referenced in the `<return>` element as specified in 8.7.2.3.

8.15.2.14 If the maximum duration is exceeded before the invoked function returns, the two following subclauses apply.

8.15.2.14.1 No assignment of output parameters and return value to variables shall be performed. In addition, if a variable corresponding to an output parameter or return value did not exist before the invocation, it shall not be created when the invoking activity resumes.

8.15.2.14.2 An implementation shall not (attempt to) interrupt the execution of the native function, even if it determines that the execution of the native function may last forever.

8.15.2.15 The execution of the invoking activity (if any) shall then resume (but see 8.9.2.17).

8.15.2.16 A native function that has exceeded the maximum duration may eventually return. When it returns, its native output parameters (if any) and return value shall be discarded.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

8.15.3 Example (non-normative)

```
<invoke activity="LoadAndAttach">
    <only_if var="myflag"/>
    <output name="BSP" setvar="BSP"/>
</invoke>


<invoke function="BioSPI_CreateTemplate">
    <input name="BSPHandle" var="BSP"/>
    <input name="CapturedBIR" var="inputbir"/>
    <input name="StoredTemplate" value=""/>
    <input name="Payload" value=""/>
    <output name="NewTemplate" setvar="template"/>
    <return setvar="return"/>
</invoke>
```

8.16 Element <only_if>

8.16.1 Syntax

8.16.1.1 This element shall have the following attribute:

`var` (optional) — if this attribute is present, its value shall be a valid variable name (see 7.2).

8.16.1.2 This element shall have a content consisting of the following:

a) an optional <description> element — this element (if present) shall contain a description of the condition (a character string);

b) zero or more occurrences of any of the following elements in any order:

1) <and> — this element represents the logical operator AND and is specified in 8.19;

2) <or> — this element represents the logical operator OR and is specified in 8.20;

3) <xor> — this element represents the logical operator XOR and is specified in 8.21;

4) <not> — this element represents the logical operator NOT and is specified in 8.22;

5) <equal_to> — this element represents the numeric operator “equal_to” and is specified in 8.23;

6) <not_equal_to> — this element represents the numeric operator “not equal to” and is specified in 8.24;

7) <greater_than> — this element represents the numeric operator “greater than” and is specified in 8.25;

8) <greater_than_or_equal_to> — this element represents the numeric operator “greater than or equal to” and is specified in 8.26;

9) <less_than> — this element represents the numeric operator “less than” and is specified in 8.27;

10) <less_than_or_equal_to> — this element represents the numeric operator “less than or equal to” and is specified in 8.28;

11) <same_as> — this element represents the character-string operator “equals” and is specified in 8.29;

12) <not_same_as> — this element represents the character-string operator “not equal to” and is specified in 8.30;

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

13) <existing> — this element expresses the condition that a variable exists and is specified in 8.31;

14) <not_existing> — this element expresses the condition that a variable does not exist and is specified in 8.32.

8.16.1.3 If the var attribute is present, the content of the element shall be empty.

8.16.2 Semantics

8.16.2.1 This element represents a condition based on either a single variable or a combination of variables, values, logical operators, numeric operators, and other operators.

8.16.2.2 If the var attribute is present, its value shall be the name of an existing variable and the value of that variable shall be a valid representation of a Boolean (see 7.5). The result of the evaluation shall be the same as the value of the variable.

8.16.2.3 If there is no var attribute and there are no child elements, the result of the evaluation shall be "true".

8.16.2.4 If there are child elements, the result of the evaluation of each child element shall be a valid representation of a Boolean (see 7.5). The result of the evaluation of the condition shall be "true" if all the child elements evaluate to "true" and shall be "false" otherwise.

8.16.2.5 The condition is evaluated during the processing of the parent element (see 8.12.2.3 and 8.15.2.2). If the condition evaluates to "true", then the containing element is processed normally (as though it did not have an <only_if> child element); otherwise, its processing has no effect.

8.17 Element <wait_until>

8.17.1 Syntax

8.17.1.1 This element shall have the following attributes:

a) timeout_value (optional) — if this attribute is present, its value indicates the maximum duration of time (in milliseconds) allowed for the wait;

b) timeout_var (optional) — if this attribute is present, its value shall be a valid name of a variable (see 7.2), whose value indicates the maximum duration of time (in milliseconds) allowed for the wait;

c) setvar (optional) — if this attribute is present, its value shall be a valid variable name (see 7.2);

d) var (optional) — if this attribute is present, its value shall be a valid variable name (see 7.2).

8.17.1.2 At most, one of the attributes timeout_var and timeout_value shall be present.

8.17.1.3 The setvar attribute shall not be present unless either the timeout_value attribute or the timeout_var attribute is present.

8.17.1.4 This element shall have a content consisting of the same child elements as specified for the element <only_if> (see 8.16).

8.17.1.5 If the var attribute is present, the content of the element shall be empty.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

8.17.2 Semantics

8.17.2.1 This element specifies a suspension of the execution of the current activity until a certain condition is verified or until a certain maximum duration of time has been reached.

8.17.2.2 The condition in the `<wait_until>` element is based on either a single variable or a combination of variables, values, logical operators, numeric operators, and other operators.

8.17.2.3 If the `var` attribute is present, its value shall be the name of an existing variable and the value of that variable shall be a valid representation of a Boolean (see 7.5). The result of the evaluation shall be the same as the value of the variable.

8.17.2.4 If there is no `var` attribute and there are no child elements, the result of the evaluation shall be "`true`".

8.17.2.5 If there are child elements, the result of the evaluation of each child element shall be a valid representation of a Boolean (see 7.5). The result of the evaluation of the condition shall be "`true`" if all the child elements evaluate to "`true`" and shall be "`false`" otherwise.

8.17.2.6 If the `timeout_value` attribute is present, its value shall be a valid representation of an integer (see 7.4) that specifies the maximum duration allowed for the wait (in milliseconds). If the `timeout_var` attribute is present, its value shall be the name of an existing variable and the value of that variable shall be a valid representation of an integer (see 7.4) that specifies the maximum duration. Otherwise, the wait shall last (conceptually) for an indefinite time.

NOTE The Note in 8.15.2.8 applies.

8.17.2.7 Conceptually, the condition shall be evaluated repeatedly and continuously during the wait until its result becomes "`true`" or until the maximum duration (if any) has been reached.

In practice, it is only necessary to evaluate the condition at discrete points in time, whenever there is a possibility that an incoming call made to the testing component, or even the passing of time, have affected the value of the condition. Implementors of this document shall ensure that any transition of the condition from "`false`" to "`true`" during a wait is detected, even if the condition remains "`true`" for a very short time and then becomes "`false`" again.

8.17.2.8 The condition shall be evaluated at least once. If the first evaluation produces a value of "`true`", then the maximum duration shall not be considered exceeded.

This is required even if the maximum duration is zero or negative.

8.17.2.9 If the `setvar` attribute is present, the four following subclauses apply.

8.17.2.9.1 The value of the `setvar` attribute shall be a valid global or local variable name (see 7.2), shall not be an input parameter of the assertion being processed (see 8.3), and shall not begin with two consecutive LOW LINE characters ("_"). The variable may exist prior to the assignment or may be a new variable created by the assignment.

8.17.2.9.2 If the maximum duration is exceeded while the condition is still "`false`", the variable shall be created (if it does not exist) and shall be set to "`true`".

8.17.2.9.3 If the condition is already "`true`" at the beginning of the wait or becomes "`true`" during the wait, then the variable shall be created (if it does not exist) and shall be set to "`false`".

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

 © ISO/IEC 2017 – All rights reserved

8.17.2.9.4 The variable shall not be created (if it does not exist before the wait) and shall not be assigned except as specified in the two previous subclauses.

NOTE This implies that the variable cannot be initialized at the beginning of the wait.

8.18 Element `<assert_condition>`

8.18.1 Syntax

8.18.1.1 This element shall have the following attributes:

a) `response_if_true` (optional) — if this attribute is present, it shall have one of the values "`pass`", "`undecided`". It indicates which conformity response shall be issued when the condition is "`true`". The default is "`pass`";

b) `response_if_false` (optional) — if this attribute is present, it shall have one of the values "`fail`", "`undecided`". It shall indicate which conformity response shall be issued when the condition is "`false`". The default is "`fail`";

c) `break_if_false` (optional) — if this attribute is present, it shall have one of the values "`false`" or "`true`". It indicates whether the execution of the current activity shall be abandoned in case the condition is "`false`". The default is "`false`";

d) `var` (optional) — if this attribute is present, its value shall be a valid variable name (see 7.2).

8.18.1.2 This element shall have a content consisting of the same child elements as specified for the element `<only_if>` (see 8.16).

8.18.1.3 If the `var` attribute is present, the content of the element shall be empty.

8.18.2 Semantics

8.18.2.1 This element specifies

a) a condition relative to an aspect of the behaviour of the IUT,

b) the conformity response ("`pass`", "`undecided`") to be issued when the condition is verified, and

c) the conformity response ("`fail`", "`undecided`") to be issued when the condition is not verified.

8.18.2.2 This feature enables the specification of conformance criteria by which one wants to state that a certain condition shall produce, say, a "`pass`" response but the opposite condition shall produce "`undecided`", or by which one wants to state that a certain condition shall produce, say, a "`fail`" response but the opposite condition shall produce "`undecided`".

8.18.2.3 The `break_if_false` attribute indicates whether a result of "`false`" for the condition shall cause the abstract test engine to abandon (break) the execution of the current activity (see 8.9.2.18). It supports those common cases in which a series of actions, following the issuance of a certain conformity response, are meaningless or inappropriate.

8.18.2.4 The condition in the `<assert_condition>` element is based on either a single variable or a combination of variables, values, logical operators, numeric operators, and other operators.

8.18.2.5 If the `var` attribute is present, its value shall be the name of an existing variable and the value of that variable shall be a valid representation of a Boolean (see 7.5). The result of the evaluation shall be the same as the value of the variable.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

8.18.2.6 If there is no `var` attribute and there are no child elements, the result of the evaluation shall be "`true`".

8.18.2.7 If there are child elements, the result of the evaluation of each child element shall be a valid representation of a Boolean (see 7.5). The result of the evaluation of the condition shall be "`true`" if all the child elements evaluate to "`true`" and shall be "`false`" otherwise.

8.18.2.8 If the condition evaluates to "`true`", then the corresponding conformity response [see 8.18.2.1 b)] shall be issued as specified in Clause 11.

8.18.2.9 If the condition evaluates to "`false`", then the corresponding conformity response [see 8.18.2.1 c)] shall be issued as specified in Clause 11. In addition, if the `break_if_false` attribute is "`true`", the current activity shall be abandoned (see 8.9.2.18).

8.19 Element `<and>`

8.19.1 Syntax

8.19.1.1 This element shall have the following attributes:

a) `var1` (optional) — if this attribute is present, its value shall be a valid variable name (see 7.2);

b) `var2` (optional) — if this attribute is present, its value shall be a valid variable name (see 7.2).

8.19.1.2 This element shall have a content consisting of the same child elements as specified for the element `<only_if>` (see 8.16), but with the following constraint.

8.19.1.3 If either the `var1` attribute or the `var2` attribute is present, then both shall be present and the content of the element shall be empty; otherwise, there shall be two or more child elements.

8.19.2 Semantics

8.19.2.1 This element represents a condition based on either two variables or a combination of variables, values, logical operators, numeric operators, and other operators. The condition is evaluated during the processing of the parent element.

8.19.2.2 This element represents a logical AND operator, whose operands may be provided either as attributes of this element or as child elements. If attributes are used, the number of operands shall be two; otherwise, it can be two or more.

8.19.2.3 If the `var1` attribute is present, its value shall be the name of an existing variable and the value of that variable shall be a valid representation of a Boolean (see 7.5).

8.19.2.4 If the `var2` attribute is present, its value shall be the name of an existing variable and the value of that variable shall be a valid representation of a Boolean (see 7.5).

8.19.2.5 If the attributes `var1` and `var2` are present, the operands shall be the values of the two variables specified in these attributes in order. Otherwise, the operands shall be the result of the evaluation of each child element in order.

8.19.2.6 Each operand shall be a valid representation of a Boolean (see 7.5). The result of the evaluation shall be "`true`" if the operands are all "`true`"; otherwise, it shall be "`false`".

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

8.20 Element <or>

8.20.1 Syntax

8.20.1.1 This element shall have the following attributes:

a) var1 (optional) — if this attribute is present, its value shall be a valid variable name (see 7.2);

b) var2 (optional) — if this attribute is present, its value shall be a valid variable name (see 7.2).

8.20.1.2 This element shall have a content consisting of the same child elements as specified for the element <only_if> (see 8.16), but with the following constraint.

8.20.1.3 If either the var1 attribute or the var2 attribute is present, then both shall be present and the content of the element shall be empty; otherwise, there shall be two or more child elements.

8.20.2 Semantics

8.20.2.1 This element represents a condition based on either two variables or a combination of variables, values, logical operators, numeric operators, and other operators. The condition is evaluated during the processing of the parent element.

8.20.2.2 This element represents a logical OR operator, whose operands may be provided either as attributes of this element or as child elements. If attributes are used, the number of operands shall be two; otherwise, it can be two or more.

8.20.2.3 If the var1 attribute is present, its value shall be the name of an existing variable and the value of that variable shall be a valid representation of a Boolean (see 7.5).

8.20.2.4 If the var2 attribute is present, its value shall be the name of an existing variable and the value of that variable shall be a valid representation of a Boolean (see 7.5).

8.20.2.5 If the attributes var1 and var2 are present, the operands shall be the values of the two variables specified in these attributes in order. Otherwise, the operands shall be the result of the evaluation of each child element in order.

8.20.2.6 Each operand shall be a valid representation of a Boolean (see 7.5). The result of the evaluation shall be "false" if the operands are all "false"; otherwise, it shall be "true".

8.21 Element <xor>

8.21.1 Syntax

8.21.1.1 This element shall have the following attributes:

a) var1 (optional) — if this attribute is present, its value shall be a valid variable name (see 7.2);

b) var2 (optional) — if this attribute is present, its value shall be a valid variable name (see 7.2).

8.21.1.2 This element shall have a content consisting of the same child elements as specified for the element <only_if> (see 8.16), but with the following constraint.

8.21.1.3 If either the var1 attribute or the var2 attribute is present, then both shall be present and the content of the element shall be empty; otherwise, there shall be exactly two child elements.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

8.21.2 Semantics

8.21.2.1 This element represents a condition based on either two variables or a combination of variables, values, logical operators, numeric operators, and other operators. The condition is evaluated during the processing of the parent element.

8.21.2.2 This element represents a logical XOR operator, whose operands may be provided either as attributes of this element or as child elements. The number of operands shall be two.

8.21.2.3 If the `var1` attribute is present, its value shall be the name of an existing variable and the value of that variable shall be a valid representation of a Boolean (see 7.5).

8.21.2.4 If the `var2` attribute is present, its value shall be the name of an existing variable and the value of that variable shall be a valid representation of a Boolean (see 7.5).

8.21.2.5 If the attributes `var1` and `var2` are present, the operands shall be the values of the two variables specified in these attributes in order. Otherwise, the operands shall be the result of the evaluation of each child element in order.

8.21.2.6 Each operand shall be a valid representation of a Boolean (see 7.5). The result of the evaluation shall be "`true`" if the two operands are different; otherwise, it shall be "`false`".

8.22 Element `<not>`

8.22.1 Syntax

8.22.1.1 This element shall have the following attribute:

`var` (optional) — if this attribute is present, its value shall be a valid variable name (see 7.2).

8.22.1.2 This element shall have a content consisting of the same child elements as specified for the element `<only_if>` (see 8.16), but with the following constraint.

8.22.1.3 If the `var` attribute is present, then the content of the element shall be empty; otherwise, there shall be exactly one child element.

8.22.2 Semantics

8.22.2.1 This element represents a condition based on either a single variable or a combination of variables, values, logical operators, numeric operators, and other operators. The condition is evaluated during the processing of the parent element.

8.22.2.2 This element represents a logical NOT operator, whose operand may be provided either as an attribute of this element or as a child element. The number of operands shall be exactly one.

8.22.2.3 If the `var` attribute is present, its value shall be the name of an existing variable and the value of that variable shall be a valid representation of a Boolean (see 7.5).

8.22.2.4 If the `var` attribute is present, the operand shall be the value of the variable specified in this attribute. Otherwise, the operand shall be the result of the evaluation of the child element.

8.22.2.5 The operand shall be a valid representation of a Boolean (see 7.5). The result of the evaluation shall be "`false`" if the operand is "`true`" and shall be "`true`" otherwise.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

 © ISO/IEC 2017 – All rights reserved

8.23 Element <equal_to>

8.23.1 Syntax

8.23.1.1 This element shall have the following attributes:

a) var1 (optional) — if this attribute is present, its value shall be a valid variable name (see 7.2);

b) var2 (optional) — if this attribute is present, its value shall be a valid variable name (see 7.2);

c) value1 (optional) — if this attribute is present, its value shall be a valid representation of an integer;

d) value2 (optional) — if this attribute is present, its value shall be a valid representation of an integer.

8.23.1.2 This element shall have a content consisting of the same child elements as specified for the element <only_if> (see 8.16), but with the following constraints.

8.23.1.3 At most, one of the attributes var1 and value1 shall be present.

8.23.1.4 At most, one of the attributes var2 and value2 shall be present.

8.23.1.5 If either var1 or value1 is present and either var2 or value2 is also present, then the content of the element shall be empty. If no attribute is present, then there shall be exactly two child elements. Otherwise, there shall be exactly one child element.

8.23.2 Semantics

8.23.2.1 This element represents a condition based on either two variables or a combination of variables, values, logical operators, numeric operators, and other operators. The condition is evaluated during the processing of the parent element.

8.23.2.2 This element represents an "equals" numeric operation, whose operands may be provided either as attributes of this element or as child elements. The number of operands shall be two.

8.23.2.3 If the var1 attribute is present, its value shall be the name of an existing variable and the value of that variable shall be a valid representation of an integer (see 7.4).

8.23.2.4 If the var2 attribute is present, its value shall be the name of an existing variable and the value of that variable shall be a valid representation of an integer (see 7.4).

8.23.2.5 If the var1 attribute is present, then the first operand shall be the value of the variable specified in this attribute. If the attribute value1 is present, then the first operand shall be the value of this attribute. Otherwise, the first operand shall be the result of the evaluation of the first (or only) child element.

8.23.2.6 If the var2 attribute is present, then the second operand shall be the value of the variable specified in this attribute. If the attribute value2 is present, then the second operand shall be the value of this attribute. Otherwise, the second operand shall be the result of the evaluation of the second (or only) child element.

8.23.2.7 Each operand shall be a valid representation of an integer (see 7.4). The result of the evaluation shall be "true" if the integer represented by the first operand is equal to the integer represented by the second; otherwise, it shall be "false".

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

8.24 Element <not_equal_to>

8.24.1 Syntax

This element has the same syntax as the element <equal_to> (see 8.23).

8.24.2 Semantics

8.24.2.1 This element has the same semantics as the element <equal_to> except for the following.

8.24.2.2 This element represents a "not equal to" numeric operation. The result of the evaluation shall be "true" if the integer represented by the first operand is not equal to the integer represented by the second; otherwise, it shall be "false".

8.25 Element <greater_than>

8.25.1 Syntax

This element has the same syntax as the element <equal_to> (see 8.23).

8.25.2 Semantics

8.25.2.1 This element has the same semantics as the element <equal_to> except for the following.

8.25.2.2 This element represents a "greater than" numeric operation. The result of the evaluation shall be "true" if the integer represented by the first operand is greater than the integer represented by the second; otherwise, it shall be "false".

8.26 Element <greater_than_or_equal_to>

8.26.1 Syntax

This element has the same syntax as the element <equal_to> (see 8.23).

8.26.2 Semantics

8.26.2.1 This element has the same semantics as the element <equal_to> except for the following.

8.26.2.2 This element represents a "greater than or equal to" numeric operation. The result of the evaluation shall be "true" if the integer represented by the first operand is greater than or equal to the integer represented by the second; otherwise, it shall be "false".

8.27 Element <less_than>

8.27.1 Syntax

This element has the same syntax as the element <equal_to> (see 8.23).

8.27.2 Semantics

8.27.2.1 This element has the same semantics as the element <equal_to> except for the following.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

8.27.2.2 This element represents a "less than" numeric operation. The result of the evaluation shall be "`true`" if the integer represented by the first operand is less than the integer represented by the second; otherwise, it shall be "`false`".

8.28 Element `<less_than_or_equal_to>`

8.28.1 Syntax

This element has the same syntax as the element `<equal_to>` (see 8.23).

8.28.2 Semantics

8.28.2.1 This element has the same semantics as the element `<equal_to>` except for the following.

8.28.2.2 This element represents a "less than or equal to" numeric operation. The result of the evaluation shall be "`true`" if the integer represented by the first operand is less than or equal to the integer represented by the second; otherwise, it shall be "`false`".

8.29 Element `<same_as>`

8.29.1 Syntax

8.29.1.1 This element shall have the following attributes:

a) `var1` (optional) — if this attribute is present, its value shall be a valid variable name (see 7.2);

b) `var2` (optional) — if this attribute is present, its value shall be a valid variable name (see 7.2);

c) `value1` (optional);

d) `value2` (optional).

8.29.1.2 This element shall have a content consisting of the same child elements as specified for the element `<only_if>` (see 8.16), but with the following constraints.

8.29.1.3 At most, one of the attributes `var1` and `value1` shall be present.

8.29.1.4 At most one of the attributes `var2` and `value2` shall be present.

8.29.1.5 If either `var1` or `value1` is present and either `var2` or `value2` is also present, then the content of the element shall be empty. If no attribute is present, then there shall be exactly two child elements. Otherwise, there shall be exactly one child element.

8.29.2 Semantics

8.29.2.1 This element represents a condition based on either two variables or a combination of variables, values, logical operators, numeric operators, and other operators. The condition is evaluated during the processing of the parent element.

8.29.2.2 This element represents a character-string "equals" operation, whose operands may be provided either as attributes of this element or as child elements. The number of operands shall be two.

8.29.2.3 If the `var1` attribute is present, its value shall be the name of an existing variable.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

8.29.2.4 If the `var2` attribute is present, its value shall be the name of an existing variable.

8.29.2.5 If the `var1` attribute is present, then the first operand shall be the value of the variable specified in this attribute. If the attribute `value1` is present, then the first operand shall be the value of this attribute. Otherwise, the first operand shall be the result of the evaluation of the first (or only) child element.

8.29.2.6 If the `var2` attribute is present, then the second operand shall be the value of the variable specified in this attribute. If the attribute `value2` is present, then the second operand shall be the value of this attribute. Otherwise, the second operand shall be the result of the evaluation of the second (or only) child element.

8.29.2.7 The result of the evaluation shall be "`true`" if the first operand is equal to the second operand character-by-character; otherwise, it shall be "`false`".

NOTE This element is normally used to compare two character strings or two Booleans.

8.30 Element `<not_same_as>`

8.30.1 Syntax

This element has the same syntax as the element `<same_as>` (see 8.29).

8.30.2 Semantics

8.30.2.1 This element has the same semantics as the element `<same_as>` except for the following.

8.30.2.2 This element represents a "not equal to" character-string operation. The result of the evaluation shall be "`true`" if the first operand is not equal to the second operand character-by-character; otherwise, it shall be "`false`".

8.31 Element `<existing>`

8.31.1 Syntax

8.31.1.1 This element shall have the following attribute:

`var` (mandatory) — the value of this attribute shall be a valid variable name (see 7.2).

8.31.1.2 The content of this element shall be empty.

8.31.2 Semantics

8.31.2.1 This element represents a condition based on a variable. The condition is evaluated during the processing of the parent element.

8.31.2.2 If the value of the `var` attribute is the name of an existing global or local variable, the result of the evaluation shall be "`true`"; otherwise, it shall be "`false`".

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

8.32 Element <not_existing>

8.32.1 Syntax

This element has the same syntax as the element <existing> (see 8.31).

8.32.2 Semantics

8.32.2.1 This element has the same semantics as the element <existing> except for the following.

8.32.2.2 If the value of the var attribute is the name of an existing global or local variable, the result of the evaluation shall be "false"; otherwise, it shall be "true".

9 Standard interface functions

9.1 General

9.1.1 Clause 9 specifies the use of the standard BioAPI interface functions of BioAPI in conformance testing. 9.2 specifies parameter groups with more specific restrictions which are to be considered in addition to the parameter constraints specified in the subsequent subcluases. Each major subclause of Clause 9 (from 9.3 to the end of the clause) specifies the following properties of a standard BioAPI interface function:

a) function invocation scheme — the name of the standard BioAPI interface function and the names of its input and output parameters to be used in an invocation of the function;

b) constraints on the parameters;

c) function invocation input — setting of the native input parameters of the underlying function from the input parameters of a function invocation;

d) function invocation output — setting of the output parameters and return value of a function invocation from the native output parameters and return value of the underlying function;

e) bound activity invocation input — setting of the input parameters of an activity bound to the standard BioAPI interface function from the native input parameters of an incoming call;

f) bound activity invocation output — setting of the native output parameters and return value of the incoming call from the output parameters of an activity bound to the standard BioAPI interface function;

g) default output — setting of the native output parameters and return value of an incoming call when there is no activity bound to a standard BioAPI interface function.

NOTE Some variables and parameter groups of the assertion language support a wider range of values than are permitted by BioAPI for the corresponding native variables and function parameters. The purpose of this is to allow the creation of assertions that assess the response of the IUT to values outside the permitted range and assess the validity of the responses from the IUT.

9.1.2 The "outbound value" (for an input parameter of a function) is:

a) if the corresponding <input> element contains a value attribute, the value of that attribute;

b) if the corresponding <input> element contains a var attribute, the value of the variable whose name is the value of that attribute.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.1.3 The “inbound value” (for an output parameter of a function) is the value to be assigned to the variable whose name is the value of the `setvar` attribute of the corresponding `<output>` element (if this element is provided in the invocation).

9.1.4 The “return value” of a function is the value to be assigned to the variable whose name is the value of the `setvar` attribute of the `<return>` element (if this element is provided in the invocation).

9.1.5 The “inbound value” (for an input parameter of a bound activity) is:

a) if the corresponding `<input>` element contains a `value` attribute, the value of that attribute;

b) if the corresponding `<input>` element contains a `var` attribute, the value of the variable whose name is the value of that attribute.

9.16 The “outbound value” (for an output parameter of a bound activity) is the value to be assigned to the variable whose name is the value of the `setvar` attribute of the corresponding `<output>` element (if this element is provided in the invocation).

9.1.7 In all function invocations, the return (inbound) value shall be set to the canonical representation of the integer in the range 0 to 4294967295 returned by the underlying function (see 7.4.3).

9.1.8 In each conformance testing model, standard BioAPI interface functions shall be used as specified in Table 1.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

Table 1 — Use of standard BioAPI interface functions in conformance testing models

	Conformance testing model for BioAPI applications (see 6.2.5.1)	Conformance testing model for BioAPI frameworks (see 6.2.5.2)	Conformance testing model for BioAPI BSPs (see 6.2.5.3)
Standard BioAPI interface functions of the BioAPI interface	the application-testing framework shall expose the function the normal framework exposes the function the application under test may call the function exposed by the application-testing framework any incoming calls to the function exposed by the application-testing framework shall be relayed to the same function exposed by the normal framework no other ways of calling the function are supported	the framework under test exposes the function neither the framework-testing application nor the framework-testing BSP shall expose the function the framework-testing application is able to call the function exposed by the framework under test no other ways of calling the function are supported	the BSP-testing application shall not expose the function no ways of calling the function are supported
Standard BioAPI interface functions of the application callback interface	the application under test may expose the function the application-testing framework shall expose the function the normal framework may call the function exposed by the application-testing framework any incoming calls to the function exposed by the application-testing framework shall be relayed to the same function exposed by the application under test (if any) no other ways of calling the function are supported	the framework-testing application shall expose the function the framework under test may call the function exposed by the framework-testing application no other ways of calling the function are supported	the BSP-testing application shall not expose the function no ways of calling the function are supported

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

Table 1 *(continued)*

	Conformance testing model for BioAPI applications (see 6.2.5.1)	Conformance testing model for BioAPI frameworks (see 6.2.5.2)	Conformance testing model for BioAPI BSPs (see 6.2.5.3)
Framework callback interface	the normal framework exposes the function the application-testing framework shall not expose the function the normal BSP may call the function exposed by the normal framework no other ways of calling the function are supported	the framework under test exposes the function neither the framework-testing application nor the framework-testing BSP shall expose the function the framework-testing BSP is able to call the function exposed by the framework under test no other ways of calling the function are supported	the BSP-testing application shall expose the function the BSP under test may call the function exposed by the BSP-testing application no other ways of calling the function are supported
Standard BioAPI interface functions of the BioSPI interface	the normal BSP may expose the function the application-testing framework shall not expose the function the normal framework may call the function exposed by the normal BSP no other ways of calling the function are supported	the framework-testing BSP shall expose the function the framework-testing application shall not expose the function the framework under test may call the function exposed by the framework-testing BSP no other ways of calling the function are supported	the BSP under test may expose the function the BSP-testing application is able to call the function exposed by the BSP under test no other ways of calling the function are supported

9.1.9 The BioAPI interface consists of the following standard BioAPI interface functions:

— `BioAPI_Init`;

— `BioAPI_Terminate`;

— `BioAPI_GetFrameworkInfo`;

— `BioAPI_EnumBSPs`;

— `BioAPI_BSPLoad`;

— `BioAPI_BSPUnload`;

— `BioAPI_BSPAttach`;

— `BioAPI_BSPDetach`;

— `BioAPI_QueryUnits`;

— `BioAPI_EnumBFPs`;

— `BioAPI_QueryBFPs`;

— `BioAPI_ControlUnit`;

— `BioAPI_LinkToEndpoint`;

— `BioAPI_UnlinkFromEndpoint`;

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

— BioAPI_FreeBIRHandle;

— BioAPI_GetBIRFromHandle;

— BioAPI_GetHeaderFromHandle;

— BioAPI_EnableEvent;

— BioAPI_SetGUICallbacks;

— BioAPI_NotifyGUIProgressEvent;

— BioAPI_NotifyGUISelectEvent;

— BioAPI_NotifyGUIStateEvent;

— BioAPI_QueryGUIEventSubscriptions;

— BioAPI_RedirectGUIEvents;

— BioAPI_SubscribeToGUIEvents;

— BioAPI_UnsubscribeFromGUIEvents;

— BioAPI_Capture;

— BioAPI_CreateTemplate;

— BioAPI_Process;

— BioAPI_ProcessUsingAuxBIRs;

— BioAPI_VerifyMatch;

— BioAPI_VerifyMatchUsingAuxBIRs;

— BioAPI_IdentifyMatch;

— BioAPI_Decide;

— BioAPI_Fuse;

— BioAPI_Enroll;

— BioAPI_Verify;

— BioAPI_Identify;

— BioAPI_Import;

— BioAPI_Export;

— BioAPI_PresetIdentifyPopulation;

— BioAPI_Transform;

— BioAPI_DbOpen;

— BioAPI_DbClose;

— BioAPI_DbCreate;

— BioAPI_DbDelete;

— BioAPI_DbSetMarker;

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

— BioAPI_DbFreeMarker;

— BioAPI_DbStoreBIR;

— BioAPI_DbGetBIR;

— BioAPI_DbGetNextBIR;

— BioAPI_DbDeleteBIR;

— BioAPI_SetPowerMode;

— BioAPI_SetIndicatorStatus;

— BioAPI_GetIndicatorStatus;

— BioAPI_CalibrateSensor;

— BioAPI_Cancel;

— BioAPI_Free;

— BioAPI_Util_InstallBSP;

— BioAPI_Util_InstallBFP;

— BioAPI_GUI_STATE_EVENT_HANDLER.

9.1.10 The BioSPI interface consists of the following standard BioAPI interface functions:

— BioSPI_BSPLoad;

— BioSPI_BSPUnload;

— BioSPI_BSPAttach;

— BioSPI_BSPDetach;

— BioSPI_QueryUnits;

— BioSPI_QueryBFPs;

— BioSPI_ControlUnit;

— BioSPI_FreeBIRHandle;

— BioSPI_GetBIRFromHandle;

— BioSPI_GetHeaderFromHandle;

— BioSPI_SubscribeToGUIEvents;

— BioSPI_UnsubscribeFromGUIEvents;

— BioSPI_EnableEvents;

— BioSPI_SetGUICallbacks;

— BioSPI_Capture;

— BioSPI_CreateTemplate;

— BioSPI_Process;

— BioSPI_ProcessUsingAuxBIRs;

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

— BioSPI_VerifyMatch;

— BioSPI_VerifyMatchUsingAuxBIRs;

— BioSPI_IdentifyMatch;

— BioSPI_IdentifyMatchUsingAuxBIRs;

— BioSPI_Decide;

— BioSPI_Fuse;

— BioSPI_Enroll;

— BioSPI_Verify;

— BioSPI_Identify;

— BioSPI_Import;

— BioSPI_Export;

— BioSPI_PresetIdentifyPopulation;

— BioSPI_Transform;

— BioSPI_DbOpen;

— BioSPI_DbClose;

— BioSPI_DbCreate;

— BioSPI_DbDelete;

— BioSPI_DbSetMarker;

— BioSPI_DbFreeMarker;

— BioSPI_DbStoreBIR;

— BioSPI_DbGetBIR;

— BioSPI_DbGetNextBIR;

— BioSPI_DbDeleteBIR;

— BioSPI_SetPowerMode;

— BioSPI_SetIndicatorStatus;

— BioSPI_GetIndicatorStatus;

— BioSPI_CalibrateSensor;

— BioSPI_Cancel;

— BioSPI_Free;

— BioAPI_GUI_ENROLL_TYPE;

— BioAPI_KEY_INFO;

— BioAPI_SECURITY_OPTIONS_MASK.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.1.11 The application callback interface consists of the following standard BioAPI interface functions:

— `BioAPI_EventHandler`;

— `BioAPI_GUI_STATE_CALLBACK`;

— `BioAPI_GUI_STREAMING_CALLBACK`;

— `BioAPI_NotifyGUIProgressEvent`;

— `BioAPI_NotifyGUISelectEvent`;

— `BioAPI_NotifyGUIStateEvent`;

— `BioAPI_QueryGUIEventSubscriptions`;

— `BioAPI_RedirectGUIEvents`;

— `BioAPI_SubscribeToGUIEvents`;

— `BioAPI_UnredirectGUIEvents`;

— `BioAPI_UnsubscribeFromGUIEvents`.

9.1.12 The framework callback interface consists of the following standard BioAPI interface functions:

— `BioSPI_EventHandler`;

— `BioSPI_GUI_STATE_CALLBACK`;

— `BioSPI_GUI_STREAMING_CALLBACK`;

— `BioSPI_BFP_ENUMERATION_HANDLER`;

— `BioSPI_MEMORY_FREE_HANDLER`;

— `BioSPI_GUI_PROGRESS_EVENT_HANDLER`;

— `BioSPI_GUI_SELECT_EVENT_HANDLER`;

— `BioSPI_GUI_STATE_EVENT_HANDLER`.

NOTE In ISO/IEC 19784-1, the standard BioAPI interface functions of the framework callback interface do not have function names, but are specified as function pointer types (which have names). In this document, these standard BioAPI interface functions are given names, both for ease of reference in the clauses of this document and for use in the assertion language.

9.2 Parameter groups

9.2.1 General

The following subclauses specify groups of parameters (of functions or activities). Each group is referenced either by one or more subsequent groups or by one or more subclauses of Clause 9 relative to standard BioAPI interface functions.

9.2.2 Parameter group “Biometric type”

9.2.2.1 The parameter group “Biometric type” consists of the following parameters:

— `NoBiotypeAvailable`;

— `TypeMultipleBiometricType`;

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

 © ISO/IEC 2017 – All rights reserved

— TypeFace;

— TypeVoice;

— TypeFingerprint;

— TypeIris;

— TypeRetina;

— TypeHandGeometry;

— TypeSignature;

— TypeKeystroke;

— TypeLipMovement;

— TypePalmprint;

— TypeGait;

— TypeVein;

— TypeDna;

— TypeEar;

— TypeFoot;

— TypeScent;

— TypeOther;

— TypePassword.

9.2.2.2 This parameter group supports the representation of the values of the native type `BioAPI_BIR_BIOMETRIC_TYPE` (which is an integer type).

9.2.2.3 An outbound value of each of these parameters shall be either a valid representation of a Boolean (see 7.5) or an empty string. An inbound value shall be the canonical representation of a Boolean (see 7.5.2).

9.2.2.4 The value (i.e. *V*) of the native type `BioAPI_BIR_BIOMETRIC_TYPE` represented by an outbound value of this parameter group shall be determined as follows.

a) The value *V* shall be initially set to zero.

b) For each member of the parameter group whose outbound value is "`true`", an integer shall be added to *V* according to Table 2.

Table 2

NoBiotypeAvailable	0
TypeMultipleBiometricType	$1 = 2^0$
TypeFace	$2 = 2^1$
TypeVoice	$4 = 2^2$
TypeFingerprint	$8 = 2^3$
TypeIris	$16 = 2^4$
TypeRetina	$32 = 2^5$

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

Table 2 *(continued)*

TypeHandGeometry	$64 = 2^6$
TypeSignature	$128 = 2^7$
TypeKeystroke	$256 = 2^8$
TypeLipMovement	$512 = 2^9$
TypePalmprint	$1024 = 2^{10}$
TypeGait	$4096 = 2^{12}$
TypeVein	$8192 = 2^{13}$
TypeDna	$16384 = 2^{14}$
TypeEar	$32768 = 2^{15}$
TypeFoot	$65536 = 2^{16}$
TypeScent	$131072 = 2^{17}$
TypeOther	$1073741824 = 2^{30}$
TypePassword	$2147483648 = 2^{31}$

If TypeMultiple is set to false, only one of the other types may be set to true.

9.2.2.5 Given an integer (i.e. *V*) that is a value of the native type BioAPI_BIR_BIOMETRIC_TYPE, the inbound value of this parameter group that canonically represents *V* shall be determined as follows.

a) The integer *V* shall be decomposed into a sum of powers of two, each occurring at most once.

b) For each power of two listed in Table 2 that occurs in the decomposition of *V*, the inbound value of the parameter in the corresponding row of the table shall be "true".

c) The inbound value of all the remaining parameters (if any) shall be "false".

d) An even value of *V* not being a single power of two indicates an invalid value.

9.2.3 Parameter group "Operations"

9.2.3.1 The parameter group "Operations" consists of the following parameters:

— OperationEnableEvents;

— OperationSubScribetoGuiEvents;

— OperationSetGUICallbacks;

— OperationCapture;

— OperationCreateTemplate;

— OperationProcess;

— OperationProcessWithAuxBIR;

— OperationVerifyMatch;

— OperationIdentifyMatch;

— OperationEnroll;

— OperationVerify;

— OperationIdentify;

— OperationImport;

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

— `OperationPresetIdentifyPopulation`;

— `OperationDatabaseOperations`;

— `OperationSetPowerMode`;

— `OperationSetIndicatorStatus`;

— `OperationGetIndicatorStatus`;

— `OperationCalibrateSensor`;

— `OperationUtilities`;

— `OperationQueryUnits`;

— `OperationQueryBFPs`;

— `OperationTransform`;

— `OperationProcessUsingAuxBIRs`;

— `OperationVerifyMatchUsingAuxBIRs`;

— `OperationDecide`;

— `OperationFuse`;

— `OperationExport`.

9.2.3.2 This parameter group supports the representation of the values of the native type `BioAPI_OPERATIONS_MASK` (which is an integer type).

9.2.3.3 An outbound value of each of these parameters shall be either a valid representation of a Boolean (see 7.5) or an empty string. An inbound value shall be the canonical representation of a Boolean (see 7.5.2).

9.2.3.4 The value (i.e. *V*) of the native type `BioAPI_OPERATIONS_MASK` represented by an outbound value of this parameter group shall be determined as follows.

a) The value *V* shall be initially set to zero.

b) For each member of the parameter group whose outbound value is "`true`", an integer shall be added to *V* according to Table 3.

Table 3

`OperationEnableEvents`	$1 = 2^0$
`OperationSubScribetoGuiEvents`	$2 = 2^1$
`OperationCapture`	$4 = 2^2$
`OperationCreateTemplate`	$8 = 2^3$
`OperationProcess`	$16 = 2^4$
`OperationProcessWithAuxBIR`	$32 = 2^5$
`OperationVerifyMatch`	$64 = 2^6$
`OperationIdentifyMatch`	$128 = 2^7$
`OperationEnroll`	$256 = 2^8$
`OperationVerify`	$512 = 2^9$
`OperationIdentify`	$1024 = 2^{10}$

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

Table 3 *(continued)*

OperationImport	2048 = 2^{11}
OperationPresetIdentifyPopulation	4096 = 2^{12}
OperationDatabaseOperations	8192 = 2^{13}
OperationSetPowerMode	16384 = 2^{14}
OperationSetIndicatorStatus	32768 = 2^{15}
OperationGetIndicatorStatus	65536 = 2^{16}
OperationCalibrateSensor	131072 = 2^{17}
OperationUtilities	262144 = 2^{18}
OperationQueryUnits	1048576 = 2^{20}
OperationQueryBFPs	2097152 = 2^{21}
OperationControlUnit	4194304 = 2^{22}
OperationTransform	8388608 = 2^{23}
OperationProcessUsingAuxBIRs	16777216 = 2^{24}
OperationVerifyMatchUsingAuxBIRs	33554432 = 2^{25}
OperationDecide	67108864 = 2^{26}
OperationFuse	134217728 = 2^{27}
OperationExport	536870912 = 2^{29}

9.2.3.5 Given an integer (i.e. *V*) that is a value of the native type `BioAPI_OPERATIONS_MASK`, the inbound value of this parameter group that canonically represents *V* shall be determined as follows.

a) The integer *V* shall be decomposed into a sum of powers of two, each occurring at most once.

b) For each power of two listed in Table 3 that occurs in the decomposition of *V*, the inbound value of the parameter in the corresponding row of the table shall be "`true`".

c) The inbound value of all the remaining parameters (if any) shall be "`false`".

9.2.4 Parameter group "Options"

9.2.4.1 The parameter group "Options" consists of the following parameters:

— `OptionRaw`;

— `OptionQualityRaw`;

— `OptionQualityIntermediate`;

— `OptionQualityProcessed`;

— `OptionAppGUI`;

— `OptionSourcePresent`;

— `OptionPayload`;

— `OptionBIRSign`;

— `OptionBIREncrypt`;

— `OptionTemplateUpdate`;

— `OptionAdaptation`;

— `OptionBinning`;

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

 © ISO/IEC 2017 – All rights reserved

— OptionSelfContainedDevice;

— OptionMOC;

— OptionSubtypeToCapture;

— OptionSensorBFP;

— OptionArchiveBFP;

— OptionMatchingBFP;

— OptionProcessingBFP;

— OptionCoarseScores.

9.2.4.2 This parameter group supports the representation of the values of the native type BioAPI_OPTIONS_MASK (which is an integer type).

9.2.4.3 An outbound value of each of these parameters shall be either a valid representation of a Boolean (see 7.5) or an empty string. An inbound value shall be the canonical representation of a Boolean (see 7.5.2).

9.2.4.4 The value (i.e. *V*) of the native type BioAPI_OPTIONS_MASK represented by an outbound value of this parameter group shall be determined as follows.

a) The value *V* shall be initially set to zero.

b) For each member of the parameter group whose outbound value is "true", an integer shall be added to *V* according to Table 4.

Table 4

OptionRaw	$1 = 2^0$
OptionQualityRaw	$2 = 2^1$
OptionQualityIntermediate	$4 = 2^2$
OptionQualityProcessed	$8 = 2^3$
OptionAppGUI	$16 = 2^4$
OptionSourcePresent	$64 = 2^6$
OptionPayload	$128 = 2^7$
OptionBIRSign	$256 = 2^8$
OptionBIREncrypt	$512 = 2^9$
OptionTemplateUpdate	$1024 = 2^{10}$
OptionAdaptation	$2048 = 2^{11}$
OptionBinning	$4096 = 2^{12}$
OptionSelfContainedDevice	$8192 = 2^{13}$
OptionMOC	$16384 = 2^{14}$
OptionSubtypeToCapture	$32768 = 2^{15}$
OptionSensorBFP	$65536 = 2^{16}$
OptionArchiveBFP	$131072 = 2^{17}$
OptionMatchingBFP	$262144 = 2^{18}$
OptionProcessingBFP	$524288 = 2^{19}$
OptionCoarseScores	$1048576 = 2^{20}$

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.2.4.5 Given an integer (i.e. *V*) that is a value of the native `type BioAPI_OPTIONS_MASK`, the inbound value of this parameter group that canonically represents *V* shall be determined as follows.

a) The integer *V* shall be decomposed into a sum of powers of two, each occurring at most once;

b) For each power of two listed in Table 4 that occurs in the decomposition of *V*, the inbound value of the parameter in the corresponding row of the table shall be "`true`".

c) The inbound value of all the remaining parameters (if any) shall be "`false`".

9.2.5 Parameter group "Events"

9.2.5.1 The parameter group "Events" consists of the following parameters:

— `EventNotifyInsert`;

— `EventNotifyRemove`;

— `EventNotifyFault`;

— `EventNotifySourcePresent`;

— `EventNotifySourceRemoved`.

9.2.5.2 This parameter group supports the representation of the values of the native type `BioAPI_EVENT_MASK` (which is an integer type).

9.2.5.3 An outbound value of each of these parameters shall be either a valid representation of a Boolean (see 7.5) or an empty string. An inbound value shall be the canonical representation of a Boolean (see 7.5.2).

9.2.5.4 The value (i.e. *V*) of the native type `BioAPI_EVENT_MASK` represented by an outbound value of this parameter group shall be determined as follows.

a) The value *V* shall be initially set to zero.

b) For each member of the parameter group whose outbound value is "`true`", an integer shall be added to *V* according to Table 5.

Table 5

`EventNotifyInsert`	$1 = 2^0$
`EventNotifyRemove`	$2 = 2^1$
`EventNotifyFault`	$4 = 2^2$
`EventNotifySourcePresent`	$8 = 2^3$
`EventNotifySourceRemoved`	$16 = 2^4$

9.2.5.5 Given an integer (i.e. *V*) that is a value of the native type `BioAPI_EVENT_MASK`, the inbound value of this parameter group that canonically represents *V* shall be determined as follows.

a) The integer *V* shall be decomposed into a sum of powers of two, each occurring at most once.

b) For each power of two listed in Table 5 that occurs in the decomposition of *V*, the inbound value of the parameter in the corresponding row of the table shall be "`true`".

c) The inbound value of all the remaining parameters (if any) shall be "`false`".

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.2.6 Parameter group "Biometric data type"

9.2.6.1 The parameter group "Biometric data type" consists of the following parameters:

— `Raw`;

— `Intermediate`;

— `ProcessedLevel`;

— `Scored`;

— `Decision`;

— `Biographic`;

— `Encrypted`;

— `Signed`;

— `IndexPresent`.

9.2.6.2 This parameter group supports the representation of the values of the native type `BioAPI_BIR_DATA_TYPE` (which is an integer type).

9.2.6.3 The members of this parameter group shall have inbound and outbound values as specified in the two following subclauses.

9.2.6.3.1 An outbound value of `ProcessedLevel` shall be either a valid representation of an integer (see 7.4) in the range 0 to 15 or an empty string. An inbound value shall be the canonical representation of an integer (see 7.4.3) in the same range.

9.2.6.3.2 An outbound value of `Encrypted`, `Signed`, and `IndexPresent` shall be either a valid representation of a Boolean (see 7.5) or an empty string. An inbound value shall be the canonical representation of a Boolean (see 7.5.2).

9.2.6.3.3 An outbound value of `Raw` and `Intermediate` shall be either a valid representation of an integer (see 7.4) in the range 0 to 15 or an empty string. An inbound value shall be the canonical representation of an integer (see 7.4.3) in the same range.

9.2.6.3.4 An outbound value of `Scored`, `Decision` and `Biographic` shall be either a valid representation of an integer (see 7.4) in the two bits or an empty string. An inbound value shall be the canonical representation of an integer (see 7.4.3) in the same range.

9.2.6.4 The value (i.e. *V*) of the native type `BioAPI_BIR_DATA_TYPE` represented by an outbound value of this parameter group shall be determined as follows.

a) The value *V* shall be initially set to the integer represented by the outbound value of `ProcessedLevel` (or zero, if the outbound value is an empty string).

b) For each member of the parameter group (apart from `ProcessedLevel`), whose outbound value is "`true`", an integer shall be added to *V* according to Table 6.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

Table 6

`Raw`	$1 = 2^0$
`Intermediate`	$2 = 2^1$
`Porcessed`	$4 = 2^2$
`Scored`	$8 = 2^3$
`Decision`	9(0x09)
`Biographic`	A(0x0A)
`Encrypted`	$16 = 2^4$
`Signed`	$32 = 2^5$
`IndexPresent`	$128 = 2^7$

9.2.6.5 Given an integer (i.e. *V*) that is a value of the native type `BioAPI_BIR_DATA_TYPE`, the inbound value of this parameter group that canonically represents *V* shall be determined as follows.

a) The integer *V* shall be decomposed into a sum of

   1) an integer less than 16,

   2) the value 16,

   3) the value 32, and

   4) the value 128 each occurring at most once.

b) For each power of two listed in Table 6 (16, 32, and 128) that occurs in the decomposition of *V*, the inbound value of the parameter in the corresponding row of the table shall be "`true`".

c) The inbound value of `ProcessedLevel` shall be the canonical representation of the integer in a) list item 1) (see 7.4.3).

d) The inbound value of all remaining parameters (if any) shall be "`false`".

9.2.7 Parameter group "Biometric subtype"

9.2.7.1 The parameter group "Biometric subtype" consists of the following parameters:

— `Available`;

— `LeftMask`;

— `RightMask`;

— `Thumb`;

— `PointerFinger`;

— `MiddleFinger`;

— `RingFinger`;

— `LittleFinger`;

— `Palm`;

— `Backofhand`;

— `Wrist`;

— `Multiple`;

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

 © ISO/IEC 2017 – All rights reserved

— ExtendedMask.

9.2.7.2 This parameter group supports the representation of the values of the native type BioAPI_BIR_SUBTYPE (which is an integer type).

9.2.7.3 An outbound value of each of these parameters shall be either a valid representation of a Boolean (see 7.5) or an empty string. An inbound value shall be the canonical representation of a Boolean (see 7.5.2).

9.2.7.4 The value (i.e. *V*) of the native type BioAPI_BIR_SUBTYPE represented by an outbound value of this parameter group shall be determined as follows:

a) The value *V* shall be initially set to zero.

b) For each member of the parameter group whose outbound value is "true", an integer shall be added to *V* according to Table 7.

Table 7

Available	0
Left	$1 = 2^0$
Right	$2 = 2^1$
Thumb	$4 = 2^2$
PointerFinger	$8 = 2^3$
MiddleFinger	$16 = 2^4$
RingFinger	$32 = 2^5$
LittleFinger	$64 = 2^6$
Palm	$4 = 2^2$
Backofhand	$8 = 2^3$
Wrist	$16 = 2^4$
Multiple	$64 = 2^6$
ExtendedMask	$128 = 2^7$

9.2.7.5 Given an integer (i.e. *V*) that is a value of the native type BioAPI_BIR_SUBTYPE, the inbound value of this parameter group that canonically represents *V* shall be determined as follows.

a) The integer *V* shall be decomposed into a sum of powers of two, each occurring at most once.

b) For each power of two listed in Table 7 that occurs in the decomposition of *V*, the inbound value of the parameter in the corresponding row of the table shall be "true".

c) The inbound value of all the remaining parameters (if any) shall be "false".

9.2.8 Parameter group "Date"

9.2.8.1 The parameter group "Date" consists of the following parameters:

— Year;

— Month;

— Day.

9.2.8.2 This parameter group supports the representation of the values of the native type BioAPI_DATE.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.2.8.3 The members of this parameter group shall have inbound and outbound values as specified in the two following subclauses.

9.2.8.3.1 An outbound value of `Year` shall be either a valid representation of an integer (see 7.4) in the range 0 to 65535 or an empty string. An inbound value shall be the canonical representation of an integer (see 7.4.3) in the same range.

9.2.8.3.2 An outbound value of `Month` and `Day` shall be either a valid representation of an integer (see 7.4) in the range 0 to 255 or an empty string. An inbound value shall be the canonical representation of an integer (see 7.4.3) in the same range.

9.2.8.4 The value (i.e. *V*) of the native type `BioAPI_DATE` represented by an outbound value of this parameter group shall be determined as follows. The integer represented by the outbound value of `Year`, `Month`, and `Day` (or zero if the outbound value is an empty string) shall be written to the fields `Year`, `Month`, and `Day` (respectively) of the field `Date` of *V*.

9.2.8.5 Given a value (i.e. *V*) of the native type `BioAPI_DATE`, the inbound value of this parameter group that canonically represents *V* shall be determined as follows. The inbound value of `Year`, `Month`, and `Day` shall be the canonical representation of the integer (see 7.4.3) in the fields `Year`, `Month`, and `Day` (respectively) of the field `Date` of *V*.

9.2.9 Parameter group "Date and time"

9.2.9.1 The parameter group "Date and time" consists of the following parameters:

— `Year`;

— `Month`;

— `Day`;

— `Hour`;

— `Minute`;

— `Second`.

9.2.9.2 This parameter group supports the representation of the values of the native type `BioAPI_DTG`.

9.2.9.3 The members of this parameter group shall have inbound and outbound values as specified in the two following subclauses.

9.2.9.3.1 An outbound value of `Year` shall be either a valid representation of an integer (see 7.4) in the range 0 to 65535 or an empty string. An inbound value shall be the canonical representation of an integer (see 7.4.3) in the same range.

9.2.9.3.2 An outbound value of `Month`, `Day`, `Hour`, `Minute`, and `Second` shall be either a valid representation of an integer (see 7.4) in the range 0 to 255 or an empty string. An inbound value shall be the canonical representation of an integer (see 7.4.3) in the same range.

9.2.9.4 The value (i.e. *V*) of the native type `BioAPI_DTG` represented by an outbound value of this parameter group shall be determined as specified in the two following subclauses.

9.2.9.4.1 The integer represented by the outbound value of `Year`, `Month`, and `Day` (or zero if the outbound value is an empty string) shall be written to the fields `Year`, `Month`, and `Day` (respectively) of the field `Date` of *V*.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

 © ISO/IEC 2017 – All rights reserved

9.2.9.4.2 The integer represented by the outbound value of `Hour`, `Minute`, and `Second` (or zero if the outbound value is an empty string) shall be written to the fields `Hour`, `Minute`, and `Second` (respectively) of the field `Time` of *V*.

9.2.9.5 Given a value (i.e. *V*) of the native type `BioAPI_DTG`, the inbound value of this parameter group that canonically represents *V* shall be determined as specified in the two following subclauses.

9.2.9.5.1 The inbound value of `Year`, `Month`, and `Day` shall be the canonical representation of the integer (see 7.4.3) in the fields `Year`, `Month`, and `Day` (respectively) of the field `Date` of *V*.

9.2.9.5.2 The inbound value of `Hour`, `Minute`, and `Second` shall be the canonical representation of the integer (see 7.4.3) in the fields `Hour`, `Minute`, and `Second` (respectively) of the field `Time` of *V*.

9.2.10 Parameter group "Framework schema"

9.2.10.1 The parameter group "Framework schema" consists of the following parameters:

— `FrameworkUuid`;

— `Description`;

— `Path`;

— `SpecVersion`;

— `ProductVersion`;

— `Vendor`;

— `FwPropertyId`;

— `FwProperty`.

9.2.10.2 This parameter group supports the representation of the values of the native type `BioAPI_FRAMEWORK_SCHEMA`.

9.2.10.3 The members of this parameter group shall have inbound and outbound values as specified in the five following subclauses.

9.2.10.3.1 An outbound value of `FrameworkUuid` and `FwPropertyId` shall be either a valid representation of a UUID (see 7.6) or an empty string. An inbound value shall be the canonical representation of a UUID (see 7.6.3).

9.2.10.3.2 An outbound value of `SpecVersion` shall be either a valid representation of an integer in the range 0 to 255 or an empty string. An inbound value shall be the canonical representation of an integer in the same range.

9.2.10.3.3 An outbound or inbound value of `ProductVersion`, `Vendor`, and `Description` shall be a character string whose UTF-8 encoding is no longer than 268 octets and which does not contain any NULL (0) characters.

9.2.10.3.4 An outbound value of `FwProperty` shall be a valid representation of an octet string (see 7.7). An inbound value shall be the canonical representation of an octet string (see 7.7.2).

9.2.10.3.5 An outbound or inbound value of `Path` shall be a character string that does not contain any NULL (0) characters.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.2.10.4 The value (i.e. *V*) of the native type `BioAPI_FRAMEWORK_SCHEMA` represented by an outbound value of this parameter group shall be determined as specified in the five following subclauses.

9.2.10.4.1 The UUID represented by the outbound value of `FrameworkUuid` and `FwPropertyId` (or the UUID "`00000000-0000-0000-0000-000000000000`" if the outbound value is an empty string) shall be written to the field of *V* with the same name.

9.2.10.4.2 The integer represented by the outbound value of `SpecVersion` (or zero if the outbound value is an empty string) shall be written to the field `SpecVersion` of *V*.

9.2.10.4.3 The character string that is the outbound value of `Description`, `ProductVersion`, and `Vendor` shall be written to the field of *V* with the same name, terminated by a NULL (0) character.

9.2.10.4.4 The octet string represented by the outbound value of `FwProperty` shall be written to a memory block of sufficient size. The address and length of that memory block shall be written to the fields `Data` and `Length` (respectively) of a variable of type `BioAPI_DATA`, whose address shall be written to the field `FwProperty` of *V*.

9.2.10.4.5 The character string that is the outbound value of `Path` shall be written, with a NULL (0) character appended to it, to a memory block of sufficient size, whose address shall be written to the field `Path` of *V*.

9.2.10.5 Given a value (i.e. *V*) of the native type `BioAPI_FRAMEWORK_SCHEMA`, the inbound value of this parameter group that canonically represents *V* shall be determined as specified in 9.2.10.5.1 to 9.2.10.5.5.

9.2.10.5.1 The inbound value of `FrameworkUuid` and `FwPropertyId` shall be the canonical representation (see 7.6.3) of the UUID in the field of *V* with the same name.

9.2.10.5.2 The inbound value of `SpecVersion` shall be the canonical representation of the integer in the field of *V* with the same name.

9.2.10.5.3 The inbound value of `Description`, `ProductVersion`, and `Vendor` shall be the character string in the field of *V* with the same name, without the final NULL (0) character.

9.2.10.5.4 The inbound value of `FwProperty` shall be the canonical representation of the octet string in the memory block, whose address and length are in the fields `Data` and `Length` (respectively) of the variable of type `BioAPI_DATA` pointed to by the field `FwProperty` of *V*.

9.2.10.5.5 The inbound value of `Path` shall be the character string pointed to by the field of *V* with the same name, without the final NULL (0) character.

9.2.11 Parameter group "BSP schema"

9.2.11.1 The parameter group "BSP schema" consists of the following parameters:

— `BSPUuid`;

— `Description`;

— `Path`;

— `SpecVersion`;

— `ProductVersion`;

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

 © ISO/IEC 2017 – All rights reserved

— Vendor;

— Format_1_FormatOwner;

— Format_1_FormatType;

— Format_2_FormatOwner;

— Format_2_FormatType;

— Format_3_FormatOwner;

— Format_3_FormatType;

— Format_4_FormatOwner;

— Format_4_FormatType;

— NumSupportedFormats;

— the members of the parameter group “Biometric type” (see 9.2.2);

— the members of the parameter group “Operations” (see 9.2.3);

— the members of the parameter group “Options” (see 9.2.4);

— PayloadPolicy;

— MaxPayloadSize;

— DefaultVerifyTimeout;

— DefaultIdentifyTimeout;

— DefaultCaptureTimeout;

— DefaultEnrollTimeout;

— DefaultCalibrateTimeout;

— MaxBSPDbSize;

— MaxIdentify.

9.2.11.2 This parameter group supports the representation of the values of the native type BioAPI_BSP_SCHEMA.

9.2.11.3 The members of this parameter group shall have inbound and outbound values as specified in the ten following subclauses.

9.2.11.3.1 An outbound value of BSPUuid shall be either a valid representation of a UUID (see 7.6) or an empty string. An inbound value shall be the canonical representation of a UUID (see 7.6.3).

9.2.11.3.2 An outbound or inbound value of BSPDescription, ProductVersion, and Vendor-HostingEndpointIRI shall be a character string, whose UTF-8 encoding is no longer than 268 octets, and which does not contain any NULL (0) characters.

9.2.11.3.3 An outbound or inbound value of Path shall be a character string that does not contain any NULL (0) characters.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.2.11.3.4 An outbound value of `SpecVersion` shall be either a valid representation of an integer (see 7.4) in the range 0 to 255 or an empty string. An inbound value shall be the canonical representation of an integer (see 7.4.3) in the same range.

9.2.11.3.5 An outbound value of `Format_X_FormatOwner` and `Format_X_FormatType` (with *X* = 1, 2, 3, or 4), shall be either a valid representation of an integer (see 7.4) in the range 0 to 65535 or an empty string. An inbound value shall be either the canonical representation of an integer (see 7.4.3) in the same range or an empty string.

9.2.11.3.6 An outbound value of `NumSupportedFormats`, `MaxPayloadSize`, `MaxBSPDbSize`, and `MaxIdentify` shall be either a valid representation of an integer (see 7.4) in the range 0 to 4294967295 or an empty string. An inbound value shall be the canonical representation of an integer (see 7.4.3) in the same range.

9.2.11.3.7 An outbound value of the parameter group "Biometric type" shall be a valid representation of a value of the native type `BioAPI_BIR_DATA_TYPE` (see 9.2.6.4). An inbound value shall be the canonical representation of a value of that type (see 9.2.6.5).

9.2.11.3.8 An outbound value of the parameter group "Operations" shall be a valid representation of a value of the native type `BioAPI_OPERATIONS_MASK` (see 9.2.3.4). An inbound value shall be the canonical representation of a value of that type (see 9.2.3.5).

9.2.11.3.9 An outbound value of the parameter group "Options" shall be a valid representation of a value of the native type `BioAPI_OPTIONS_MASK` (see 9.2.4.4). An inbound value shall be the canonical representation of a value of that type (see 9.2.4.5).

9.2.11.3.10 An outbound value of `PayloadPolicy`, `DefaultVerifyTimeout`, `DefaultIdentifyTimeout`, `DefaultCaptureTimeout`, `DefaultEnrollTimeout`, and `DefaultCalibrateTimeout` shall be either a valid representation of an integer (see 7.4) in the range −2147483648 to 2147483647 or an empty string. An inbound value shall be the canonical representation of an integer (see 7.4.3) in the same range.

9.2.11.4 The value (i.e. *V*) of the native type `BioAPI_BSP_SCHEMA` represented by an outbound value of this parameter group shall be determined as specified in the eight following subclauses.

9.2.11.4.1 The UUID represented by the outbound value of `BSPUuid` (or the UUID "`00000000-0000-0000-0000-000000000000`" if the outbound value is an empty string) shall be written to the field of *V* with the same name.

9.2.11.4.2 The character string that is the outbound value of `Description`, `ProductVersion`, and `Vendor` shall be written to the field of *V* with the same name, terminated by a NULL (0) character.

9.2.11.4.3 The character string that is the outbound value of `Path` shall be written to a memory block of sufficient size, whose address shall be written to the field `Path` of *V*.

9.2.11.4.4 The integer represented by the outbound value of `SpecVersion`, `NumSupportedFormats`, `PayloadPolicy`, `MaxPayloadSize`, `DefaultVerifyTimeout`, `DefaultIdentifyTimeout`, `DefaultCaptureTimeout`, `DefaultEnrollTimeout`, `DefaultCalibrateTimeout`, `MaxBSPDbSize`, and (or zero if the outbound value is an empty string) shall be written to the field of *V* with the same name.

9.2.11.4.5 The integer represented by the outbound value of `Format_X_FormatOwner` and `Format_X_FormatType` (with *X* = 1, 2, 3, or 4), or zero if the outbound value is an empty string, shall be written to the fields `FormatOwner` and `FormatType` (respectively) of the element at position *X* of

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

an array of four elements of type BioAPI_BIR_BIOMETRIC_DATA_FORMAT. The address of that array shall be written to the field BSPSupportedFormats of *V*.

9.2.11.4.6 The value of type BioAPI_BIR_BIOMETRIC_TYPE represented (see 9.2.2.4) by the outbound value of the parameter group "Biometric type" shall be written to the field FactorsMask of *V*.

9.2.11.4.7 The value of type BioAPI_OPERATIONS represented (see 9.2.3.4) by the outbound value of the parameter group "Operations" shall be written to the field Operations of *V*.

9.2.11.4.8 The value of type BioAPI_OPTIONS represented (see 9.2.4.4) by the outbound value of the parameter group "Options" shall be written to the field Options of *V*.

9.2.11.5 Given a value (i.e. *V*) of the native type BioAPI_BSP_SCHEMA, the inbound value of this parameter group that canonically represents *V* shall be determined as specified in the eight following subclauses.

9.2.11.5.1 The inbound value of BSPUuid shall be the canonical representation (see 7.6.3) of the UUID in the field of *V* with the same name.

9.2.11.5.2 The inbound value of Description, ProductVersion, and Vendor shall be the character string in the field of *V* with the same name.

9.2.11.5.3 The inbound value of Path shall be the character string pointed to by the field of *V* with the same name.

9.2.11.5.4 The inbound value of SpecVersion, NumSupportedFormats, PayloadPolicy, MaxPayloadSize, DefaultVerifyTimeout, DefaultIdentifyTimeout, DefaultCaptureTimeout, DefaultEnrollTimeout, DefaultCalibrateTimeout, MaxBSPDbSize, and MaxIdentify shall be the canonical representation of the integer in the field of *V* with the same name.

9.2.11.5.5 The inbound value of Format_*X*_FormatOwner and Format_*X*_FormatType (with *X* = 1, 2, 3, or 4) shall be determined as follows. If the field BSPSupportedFormats of *V* is NULL or the field NumSupportedFormats of *V* is less than *X*, then the inbound value shall be an empty string. Otherwise, the inbound value shall be the canonical representation of the integer in the fields FormatOwner and FormatType (respectively) of the element at position *X* of the array of type BioAPI_BIR_BIOMETRIC_DATA_FORMAT pointed to by the field BSPSupportedFormats of *V*.

9.2.11.5.6 The inbound value of the parameter group "Biometric type" shall be the canonical representation (see 9.2.2.5) of the value of type BioAPI_BIR_BIOMETRIC_TYPE in the field FactorsMask of *V*.

9.2.11.5.7 The inbound value of the parameter group "Operations" shall be the canonical representation (see 9.2.3.5) of the value of type BioAPI_OPERATIONS in the field Operations of *V*.

9.2.11.5.8 The inbound value of the parameter group "Options" shall be the canonical representation (see 9.2.4.5) of the value of type BioAPI_OPTIONS in the field Options of *V*.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.2.12 Parameter group “BFP schema”

9.2.12.1 The parameter group “BFP schema” consists of the following parameters:

— `BFPUuid`;

— `BFPCategory`;

— `BFPDescription`;

— `Path`;

— `SpecVersion`;

— `ProductVersion`;

— `Vendor`;

— `Format_1_FormatOwner`;

— `Format_1_FormatType`;

— `Format_2_FormatOwner`;

— `Format_2_FormatType`;

— `Format_3_FormatOwner`;

— `Format_3_FormatType`;

— `Format_4_FormatOwner`;

— `Format_4_FormatType`;

— `NumSupportedFormats`;

— the members of the parameter group “Biometric type” (see 9.2.2);

— `BFPPropertyID`;

— `BFPProperty`.

9.2.12.2 This parameter group supports the representation of the values of the native type `BioAPI_BFP_SCHEMA`.

9.2.12.3 The members of this parameter group shall have inbound and outbound values as specified in the eight following subclauses.

9.2.12.3.1 An outbound value of `BFPUuid` and `BFPPropertyID` shall be either a valid representation of a UUID (see 7.6) or an empty string. An inbound value shall be the canonical representation of a UUID (see 7.6.3).

9.2.12.3.2 An outbound value of `BFPCategory` and `NumSupportedFormats` shall be either a valid representation of an integer in the range 0 to 4294967295 or an empty string. An inbound value shall be the canonical representation of an integer in the same range.

9.2.12.3.3 An outbound or inbound value of `BFPDescription`, `ProductVersion` and `Vendor` shall be a character string, whose UTF-8 encoding is no longer than 268 octets, and which does not contain any NULL (0) characters.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

 © ISO/IEC 2017 – All rights reserved

9.2.12.3.4 An outbound or inbound value of `Path` shall be a character string that does not contain any NULL (0) characters.

9.2.12.3.5 An outbound value of `SpecVersion` shall be either a valid representation of an integer in the range 0 to 255 or an empty string. An inbound value shall be the canonical representation of an integer in the same range.

9.2.12.3.6 An outbound value of `Format_X_FormatOwner` and `Format_X_FormatType` (with *X* = 1, 2, 3, or 4) shall be either a valid representation of an integer (see 7.4) in the range 0 to 65535 or an empty string. An inbound value shall be either the canonical representation of an integer (see 7.4.3) in the same range or an empty string.

9.2.12.3.7 An outbound value of the parameter group "Biometric type" shall be a valid representation of a value of the native type `BioAPI_BIR_DATA_TYPE` (see 9.2.6.4). An inbound value shall be the canonical representation of a value of that type (see 9.2.6.5).

9.2.12.3.8 An outbound value of `BFPProperty` shall be a valid representation of an octet string (see 7.7). An inbound value shall be the canonical representation of an octet string (see 7.7.2).

9.2.12.4 The value (i.e. *V*) of the native type `BioAPI_BFP_SCHEMA` represented by an outbound value of this parameter group shall be determined as specified in the eight following subclauses.

9.2.12.4.1 The UUID represented by the outbound value of `BFPUuid` and `BFPPropertyID` (or the UUID "`00000000-0000-0000-0000-000000000000`" if the outbound value is an empty string) shall be written to the field of *V* with the same name.

9.2.12.4.2 The integer represented by the outbound value of `BFPCategory` and `NumSupportedFormats` (or zero if the outbound value is an empty string) shall be written to the field of *V* with the same name.

9.2.12.4.3 The character string that is the outbound value of `BFPDescription`, `ProductVersion` and `Vendor` shall be written to the field of *V* with the same name, terminated by a NULL (0) character.

9.2.12.4.4 The character string that is the outbound value of `Path` shall be written, with a NULL (0) character appended to it, to a memory block of sufficient size, whose address shall be written to the field `Path` of *V*.

9.2.12.4.5 The integer represented by the outbound value of `SpecVersion` (or zero if the outbound value is an empty string) shall be written to the field of *V* with the same name.

9.2.12.4.6 The integer represented by the outbound value of `Format_X_FormatOwner` and `Format_X_FormatType` (with *X* = 1, 2, 3, or 4), or zero if the outbound value is an empty string, shall be written to the fields `FormatOwner` and `FormatType` (respectively) of the element at position *X* of an array of four elements of type `BioAPI_BIR_BIOMETRIC_DATA_FORMAT`. The address of that array shall be written to the field `BFPSupportedFormats` of *V*.

9.2.12.4.7 The value of type `BioAPI_BIR_BIOMETRIC_TYPE` represented (see 9.2.2.4) by the outbound value of the parameter group "Biometric type" shall be written to the field `FactorsMask` of *V*.

9.2.12.4.8 The octet string represented by the outbound value of `BFPProperty` shall be written to a memory block of sufficient size. The address and length of that memory block shall be written to the fields `Data` and `Length` (respectively) of a variable of type `BioAPI_DATA`, whose address shall be written to the field BFPProperty of *V*.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.2.12.5 Given a value (i.e. *V*) of the native type `BioAPI_BFP_SCHEMA`, the inbound value of this parameter group that canonically represents *V* shall be determined as specified in the eight following subclauses.

9.2.12.5.1 The inbound value of `BFPUuid` and `BFPPropertyID` shall be the canonical representation (see 7.6.3) of the UUID in the field of *V* with the same name.

9.2.12.5.2 The inbound value of `BFPCategory` and `NumSupportedFormats` shall be the canonical representation of the integer in the field of *V* with the same name.

9.2.12.5.3 The inbound value of `BFPDescription`, `ProductVersion`, and `Vendor` shall be the character string in the field of *V* with the same name, without the final NULL (0) character.

9.2.12.5.4 The inbound value of `Path` shall be the character string pointed to by the field of *V* with the same name, without the final NULL (0) character.

9.2.12.5.5 The inbound value of `SpecVersion` shall be the canonical representation of the integer in the field of *V* with the same name.

9.2.12.5.6 The inbound value of `Format_X_FormatOwner` and `Format_X_FormatType` (with *X* = 1, 2, 3, or 4) shall be determined as follows. If the field `BFPSupportedFormats` of *V* is NULL or the field `NumSupportedFormats` of *V* is less than *X*, then the inbound value shall be an empty string. Otherwise, the inbound value shall be the canonical representation of the integer in the fields `FormatOwner` and `FormatType` (respectively) of the element at position *X* of the array of type `BioAPI_BIR_BIOMETRIC_DATA_FORMAT` pointed to by the field `BFPSupportedFormats` of *V*.

9.2.12.5.7 The inbound value of the parameter group "Biometric type" shall be the canonical representation (see 9.2.2.5) of the value of type `BioAPI_BIR_BIOMETRIC_TYPE` in the field `FactorsMask` of *V*.

9.2.12.5.8 The inbound value of `BFPProperty` shall be the canonical representation of the octet string in the memory block, whose address and length are in the fields `Data` and `Length` (respectively) of the variable of type `BioAPI_DATA` pointed to by the field `BFPProperty` of *V*.

9.2.13 Parameter group "Unit schema"

9.2.13.1 The parameter group "Unit schema" consists of the following parameters:

— `BSPUuid`;

— `UnitManagerUuid`;

— `UnitID`;

— `UnitCategory`;

— `UnitProperties`;

— `Vendor`;

— `ProductName`;

— the members of the parameter group "Events" (see 9.2.5);

— `UnitPropertyID`;

— `UnitProperty`;

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

— HardwareVersion;

— FirmwareVersion;

— SoftwareVersion;

— HardwareSerialNumber;

— AuthenticatedHardware;

— MaxBSPDbSize;

— MaxIdentify;

— SecurityProfile.

9.2.13.2 This parameter group supports the representation of the values of the native type BioAPI_UNIT_SCHEMA.

9.2.13.3 The members of this parameter group shall have inbound and outbound values as specified in the six following subclauses.

9.2.13.3.1 An outbound value of BSPUuid, UnitManagerUuid, UnitProperties, and UnitPropertyID shall be either a valid representation of a UUID (see 7.6) or an empty string. An inbound value shall be the canonical representation of a UUID (see 7.6.3).

9.2.13.3.2 An outbound or inbound value of Vendor and ProductName shall be a character string, whose UTF-8 encoding is no longer than 268 octets, and which does not contain any NULL (0) characters.

9.2.13.3.3 An outbound value of UnitID, UnitCategory, MaxBSPDbSize, and MaxIdentify shall be either a valid representation of an integer in the range 0 to 4294967295 or an empty string. An inbound value shall be the canonical representation of an integer in the same range.

9.2.13.3.4 An outbound or inbound value of VendorInformation, HardwareVersion, FirmwareVersion, SoftwareVersion, and HardwareSerialNumber shall be a character string, whose UTF-8 encoding is no longer than 268 octets, and which does not contain any NULL (0) characters.

9.2.13.3.5 An outbound value of the parameter group "Events" shall be a valid representation of a value of the native type BioAPI_EVENT_MASK. An inbound value shall be the canonical representation of a value of that type.

9.2.13.3.6 An outbound value of UnitProperty shall be a valid representation of an octet string (see 7.7). An inbound value shall be the canonical representation of an octet string (see 7.7.2).

9.2.13.3.7 An outbound value of AuthenticatedHardware shall be either a valid representation of a Boolean (see 7.5) or an empty string. An inbound value shall be the canonical representation of a Boolean (see 7.5.2).

9.2.13.3.8 An outbound value of SecurityProfile shall be a valid representation of a value of the native type BioAPI_SECURITY_PROFILE. An inbound value shall be the canonical representation of a value of that type.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.2.13.4 The value (i.e. *V*) of the native type `BioAPI_UNIT` represented by an outbound value of this parameter group shall be determined as specified in the six following subclauses.

9.2.13.4.1 The UUID represented by the outbound value of `BSPUuid`, `UnitManagerUuid`, `UnitProperties`, and `UnitPropertyID` (or the UUID "`00000000-0000-0000-0000-000000000000`" if the outbound value is an empty string) shall be written to the field of *V* with the same name.

9.2.13.4.2 The integer represented by the outbound value of `UnitID`, `UnitCategory`, `MaxBSPDbSize`, and `MaxIdentify` (or zero if the outbound value is an empty string) shall be written to the field of *V* with the same name.

9.2.13.4.3 The character string that is the outbound value of `Vendor` and `ProductName` shall be written to the field of *V* with the same name, terminated by a NULL (0) character.

9.2.13.4.4 The value of type `BioAPI_EVENT_MASK` represented (see 9.2.5.4) by the outbound value of the parameter group "Events" shall be written to the field `SupportedEvents` of *V*.

9.2.13.4.5 The character string that is the outbound value of `VendorInformation`, `HardwareVersion`, `FirmwareVersion`, `SoftwareVersion`, and `HardwareSerialNumber` shall be written to the field of *V* with the same name, terminated by a NULL (0) character.

9.2.13.4.6 The octet string represented by the outbound value of `UnitProperty` shall be written to a memory block of sufficient size. The address and length of that memory block shall be written to the fields `Data` and `Length` (respectively) of a variable of type `BioAPI_DATA`, whose address shall be written to the field `UnitProperty` of *V*.

9.2.13.4.7 The Boolean represented by the outbound value of `AuthenticatedHardware` (or "`false`" if the outbound value is an empty string) shall be written to the field of *V* with the same name.

9.2.13.4.8 The value of type `BioAPI_SECURITY_PROFILE` represented by the outbound value of the parameter group "Security" shall be written to the field `SecurityProfile` of *V*.

9.2.13.5 Given a value (i.e. *V*) of the native type `BioAPI_UNIT_SCHEMA`, the inbound value of this parameter group that canonically represents *V* shall be determined as specified in the six following subclauses.

9.2.13.5.1 The inbound value of `BSPUuid`, `UnitManagerUuid`, `UnitProperties`, and `UnitPropertyID` shall be the canonical representation (see 7.6.3) of the UUID in the field of *V* with the same name.

9.2.13.5.2 The inbound value of `UnitID`, `UnitCategory`, `MaxBSPDbSize`, and `MaxIdentify` shall be the canonical representation of the integer in the field of *V* with the same name.

9.2.13.5.3 The inbound value of `Vendor` and `ProductName` shall be the character string in the field of *V* with the same name, without the final NULL (0) character.

9.2.13.5.4 The inbound value of the parameter group "Events" shall be the canonical representation (see 9.2.2.5) of the value of type `BioAPI_EVENT_MASK` in the field `SupportedEvents` of *V*.

9.2.13.5.5 The inbound value of `VendorInformation`, `HardwareVersion`, `FirmwareVersion`, `SoftwareVersion`, and `HardwareSerialNumber` shall be the character string in the field of *V* with the same name, without the final NULL (0) character.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.2.13.5.6 The inbound value of `UnitProperty` shall be the canonical representation of the octet string in the memory block, whose address and length are in the fields `Data` and `Length` (respectively) of the variable of type `BioAPI_DATA` pointed to by the field `UnitProperty` of *V*.

9.2.13.5.7 The inbound value of `AuthenticatedHardware` shall be the canonical representation (see 7.5.2) of the Boolean in the field of *V* with the same name.

9.2.13.5.8 The inbound value of the parameter group "Security Profile" shall be the canonical representation of the value of type `BioAPI_SECURITY_PROFILE` in the field `SecurityProfile` of *V*.

9.2.14 Parameter group "BIR header"

9.2.14.1 The parameter group "BIR header" consists of the following parameters:

— `HeaderVersion`;

— the members of the parameter group "Biometric data type" (see 9.2.6);

— `FormatOwner`;

— `FormatType`;

— `Quality`;

— `Purpose`;

— the members of the parameter group "Biometric type" (see 9.2.2);

— `ProductOwner`;

— `ProductType`;

— the members of the parameter group "Date and time" (see 9.2.9), with their names prefixed by "`Creation_`";

— the members of the parameter group "Biometric subtype" (see 9.2.7);

— the members of the parameter group "Date" (see 9.2.8), with their names prefixed by "`Expiration_`";

— `SBFormatOwner`;

— `SBFormatType`;

— `Index`.

9.2.14.2 This parameter group supports the representation of the values of the native type `BioAPI_BIR_HEADER`.

9.2.14.3 The members of this parameter group shall have inbound and outbound values as specified in the nine following subclauses.

9.2.14.3.1 An outbound value of `HeaderVersion` and `Purpose` shall be either a valid representation of an integer in the range 0 to 255 or an empty string. An inbound value shall be the canonical representation of an integer in the same range.

9.2.14.3.2 An outbound value of the parameter group "Biometric data type" shall be a valid representation of a value of the native type `BioAPI_BIR_DATA_TYPE`. An inbound value shall be the canonical representation of a value of that type.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.2.14.3.3 An outbound value of `FormatOwner`, `FormatType`, `ProductOwner`, `ProductType`, `SBFormatOwner`, and `SBFormatType` shall be either a valid representation of an integer in the range 0 to 65535 or an empty string. An inbound value shall be the canonical representation of an integer in the same range.

9.2.14.3.4 An outbound value of `Quality` shall be either a valid representation of an integer in the range −128 to 127 or an empty string. An inbound value shall be the canonical representation of an integer in the same range.

9.2.14.3.5 An outbound value of the parameter group "Biometric type" shall be a valid representation of a value of the native type `BioAPI_BIR_BIOMETRIC_TYPE`. An inbound value shall be the canonical representation of a value of that type.

9.2.14.3.6 An outbound value of the parameter group "Date and time" shall be a valid representation of a value of the native type `BioAPI_DTG`. An inbound value shall be the canonical representation of a value of that type.

9.2.14.3.7 An outbound value of the parameter group "Biometric subtype" shall be a valid representation of a value of the native type `BioAPI_BIR_SUBTYPE`. An inbound value shall be the canonical representation of a value of that type.

9.2.14.3.8 An outbound value of the parameter group "Date" shall be a valid representation of a value of the native type `BioAPI_DATE`. An inbound value shall be the canonical representation of a value of that type.

9.2.14.3.9 An outbound value of `Index` shall be either a valid representation of a UUID (see 7.6) or an empty string. An inbound value shall be the canonical representation of a UUID (see 7.6.3).

9.2.14.4 The value (i.e. *V*) of the native type `BioAPI_BIR_HEADER` represented by an outbound value of this parameter group shall be determined as specified in the ten following subclauses.

9.2.14.4.1 The integer represented by the outbound value of `HeaderVersion`, `Quality`, and `Purpose` (or zero if the outbound value is an empty string) shall be written to the field of *V* with the same name.

9.2.14.4.2 The value of type `BioAPI_BIR_DATA_TYPE` represented (see 9.2.6.4) by the outbound value of the parameter group "Biometric data type" shall be written to the field `Type` of *V*.

9.2.14.4.3 The integer represented by the outbound value of `FormatOwner` and `FormatType` (or zero if the outbound value is an empty string) shall be written to the fields `FormatOwner` and `FormatType` (respectively) of the field `Format` of *V*.

9.2.14.4.4 The value of type `BioAPI_BIR_BIOMETRIC_TYPE` represented (see 9.2.2.4) by the outbound value of the parameter group "Biometric type" shall be written to the field `FactorsMask` of *V*.

9.2.14.4.5 The integer represented by the outbound value of `ProductOwner` and `ProductType` (or zero if the outbound value is an empty string) shall be written to the fields `ProductOwner` and `ProductType` (respectively) of the field `ProductID` of *V*.

9.2.14.4.6 The value of type `BioAPI_DTG` represented (see 9.2.9.4) by the outbound value of the parameter group "Date and time" (with the prefix "`Creation_`") shall be written to the field `CreationDTG` of *V*.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.2.14.4.7 The value of type `BioAPI_BIR_SUBTYPE` represented (see 9.2.7.4) by the outbound value of the parameter group "Biometric subtype" shall be written to the field `Subtype` of *V*.

9.2.14.4.8 The value of type `BioAPI_DATE` represented (see 9.2.8.4) by the outbound value of the parameter group "Date" (with the prefix "`Expiration_`") shall be written to the field `ExpirationDate` of *V*.

9.2.14.4.9 The integer represented by the outbound value of `SBFormatOwner` and `SBFormatType` (or zero if the outbound value is an empty string) shall be written to the fields `SecurityFormatOwner` and `SecurityFormatType` (respectively) of the field `SBFormat` of *V*.

9.2.14.4.10 The UUID represented by the outbound value of `Index` (or the UUID "`00000000-0000-0000-0000-000000000000`" if the outbound value is an empty string) shall be written to the field of *V* with the same name.

9.2.14.5 Given a value (i.e. *V*) of the native type `BioAPI_BIR_HEADER`, the inbound value of this parameter group that canonically represents *V* shall be determined as specified in the ten following subclauses.

9.2.14.5.1 The inbound value of `HeaderVersion`, `Quality`, and `Purpose` shall be the canonical representation of the integer in the field of *V* with the same name.

9.2.14.5.2 The inbound value of the parameter group "Biometric data type" shall be the canonical representation (see 9.2.6.5) of the value of type `BioAPI_BIR_DATA_TYPE` in the field `Type` of *V*.

9.2.14.5.3 The inbound value of `FormatOwner` and `FormatType` shall be the canonical representation of the integer in the fields `FormatOwner` and `FormatType` (respectively) of the field `Format` of *V*.

9.2.14.5.4 The inbound value of the parameter group "Biometric type" shall be the canonical representation (see 9.2.2.5) of the value of type `BioAPI_BIR_BIOMETRIC_TYPE` in the field `FactorsMask` of *V*.

9.2.14.5.5 The inbound value of `ProductOwner` and `ProductType` shall be the canonical representation of the integer in the fields `ProductOwner` and `ProductType` (respectively) of the field `ProductID` of *V*.

9.2.14.5.6 The inbound value of the parameter group "Date and time" (with the prefix "`Creation_`") shall be the canonical representation (see 9.2.9.5) of the value of type `BioAPI_DTG` in the field `CreationDTG` of *V*.

9.2.14.5.7 The inbound value of the parameter group "Biometric subtype" shall be the canonical representation (see 9.2.7.5) of the value of type `BioAPI_BIR_SUBTYPE` in the field `Subtype` of *V*.

9.2.14.5.8 The inbound value of the parameter group "Date" (with the prefix "`Expiration_`") shall be the canonical representation (see 9.2.8.5) of the value of type `BioAPI_DATE` in the field `ExpirationDate` of *V*.

9.2.14.5.9 The inbound value of `SBFormatOwner` and `SBFormatType` shall be the canonical representation of the integer in the fields `SecurityFormatOwner` and `SecurityFormatType` (respectively) of the field `SBFormat` of *V*.

9.2.14.5.10 The inbound value of `Index` shall be the canonical representation (see 7.6.3) of the UUID in the field of *V* with the same name.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.2.15 Parameter group “BIR”

9.2.15.1 The parameter group “BIR” consists of the following parameters:

— the members of the parameter group “BIR header” (see 9.2.14);

— `BiometricData`;

— `SecurityBlock`.

9.2.15.2 This parameter group supports the representation of the values of the native type `BioAPI_BIR`.

9.2.15.3 The members of this parameter group shall have inbound and outbound values as specified in the two following subclauses.

9.2.15.3.1 An outbound value of the parameter group “BIR header” shall be a valid representation of a value of the native type `BioAPI_BIR_HEADER`. An inbound value shall be the canonical representation of a value of that type.

9.2.15.3.2 An outbound value of `BiometricData` and `SecurityBlock` shall be a valid representation of an octet string (see 7.7). An inbound value shall be the canonical representation of an octet string (see 7.7.2).

9.2.15.4 The value (i.e. *V*) of the native type `BioAPI_BIR` represented by an outbound value of this parameter group shall be determined as specified in the three following subclauses.

9.2.15.4.1 The value of type `BioAPI_BIR_HEADER` represented (see 9.2.14.4) by the outbound value of the parameter group “BIR header” shall be written to the field `Header` of *V*.

9.2.15.4.2 The octet string represented by the outbound value of `BiometricData` shall be written to a memory block of sufficient size. The address and length of that memory block shall be written to the fields `Data` and `Length` (respectively) of the field `BiometricData` of *V*.

9.2.15.4.3 The octet string represented by the outbound value of `SecurityBlock` shall be written to a memory block of sufficient size. The address and length of that memory block shall be written to the fields `Data` and `Length` (respectively) of the field `SecurityBlock` of *V*.

9.2.15.5 Given a value (i.e. *V*) of the native type `BioAPI_BIR`, the inbound value of this parameter group that canonically represents *V* shall be determined as specified in the three following subclauses.

9.2.15.5.1 The inbound value of the parameter group “BIR header” shall be the canonical representation (see 9.2.14.5) of the value of type `BioAPI_BIR_HEADER` in the field `Header` of *V*.

9.2.15.5.2 The inbound value of `BiometricData` shall be the canonical representation of the octet string in the memory block, whose address and length are in the fields `Data` and `Length` (respectively) of the field `BiometricData` of *V*.

9.2.15.5.3 The inbound value of `SecurityBlock` shall be the canonical representation of the octet string in the memory block, whose address and length are in the fields `Data` and `Length` (respectively) of the field `SecurityBlock` of *V*.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.2.16 Parameter group "Input BIR"

9.2.16.1 The parameter group "Input BIR" consists of the following parameters:

— `Form`;

— `DbHandle`;

— `KeyValue`;

— `BIRHandle`;

— the members of the parameter group "BIR" (see 9.2.15).

9.2.16.2 This parameter group supports the representation of the values of the native type `BioAPI_INPUT_BIR`.

9.2.16.3 The members of this parameter group shall have inbound and outbound values as specified in the four following subclauses.

9.2.16.3.1 An outbound value of `Form` shall be either a valid representation of an integer (see 7.4) in the range 0 to 255 or an empty string. An inbound value shall be the canonical representation of an integer (see 7.4.3) in the same range.

9.2.16.3.2 An outbound value of `DbHandle` and `BIRHandle` shall be either a valid representation of an integer in the range −2147483648 to 2147483647 or an empty string. An inbound value shall be the canonical representation of an integer in the same range.

9.2.16.3.3 An outbound value of `KeyValue` shall be either a valid representation of a UUID (see 7.6) or an empty string. An inbound value shall be the canonical representation of a UUID (see 7.6.3).

9.2.16.3.4 An outbound value of the parameter group "BIR" shall be a valid representation of a value of the native type `BioAPI_BIR`. An inbound value shall be the canonical representation of a value of that type.

9.2.16.4 The value (i.e. *V*) of the native type `BioAPI_INPUT_BIR` represented by an outbound value of this parameter group shall be determined as specified in the five following subclauses.

9.2.16.4.1 The integer (say, *F*) represented by the outbound value of `Form` (or zero if the outbound value is an empty string) shall be written to the field of *V* with the same name.

9.2.16.4.2 If *F* is 1, then

a) the integer represented by the outbound value of `DbHandle` (or zero if the outbound value is an empty string) shall be written to the field `DbHandle` of a variable of type `BioAPI_DBBIR_ID`,

b) the UUID represented by the outbound value of `KeyValue` (or the UUID "`00000000-0000-0000-0000-000000000000`" if the outbound value is an empty string) shall be written to the field `KeyValue` of that variable, and

c) the address of that variable shall be written to the field `BIRInDb` of the field `InputBIR` of *V*.

9.2.16.4.3 If *F* is 2, then

a) the integer represented by the outbound value of `BIRHandle` (or zero if the outbound value is an empty string) shall be written to a variable of type `BioAPI_BIR_HANDLE`, and

b) the address of that variable shall be written to the field `BIRInBSP` of the field `InputBIR` of *V*.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.2.16.4.4 If *F* is 3, then

a) the value of type `BioAPI_BIR` represented (see 9.2.15.4) by the outbound value of the parameter group "BIR" shall be written to a variable of type `BioAPI_BIR`, and

b) the address of that variable shall be written to the field `BIR` of the field `InputBIR` of *V*.

9.2.16.4.5 If *F* is less than 1 or greater than 3, then the field BIR of the field InputBIR of *V* shall be set to NULL.

9.2.16.5 Given a value (i.e. *V*) of the native type `BioAPI_INPUT_BIR`, the inbound value of this parameter group that canonically represents *V* shall be determined as specified in the five following subclauses.

9.2.16.5.1 The inbound value of `Form` shall be the canonical representation of the integer (say, *F*) in the field of *V* with the same name.

9.2.16.5.2 If *F* is 1, then

a) the inbound value of `DbHandle` shall be the canonical representation of the integer in the field `DbHandle` of the variable of type `BioAPI_DBBIR_ID` pointed to by the field `BIRInDb` of the field `InputBIR` of *V*,

b) the inbound value of `KeyValue` shall be the canonical representation (see 7.6.3) of the UUID in the field `KeyValue` of that variable, and

c) the inbound value of all other parameters shall be an empty string.

9.2.16.5.3 If *F* is 2, then

a) the inbound value of `BIRHandle` shall be the canonical representation of the integer in the variable of type `BioAPI_BIR_HANDLE` pointed to by the field `BIRInBSP` of the field `InputBIR` of *V*, and

b) the inbound value of all other parameters shall be an empty string.

9.2.16.5.4 If *F* is 3, then

a) the inbound value of the parameter group "BIR" shall be the canonical representation (see 9.2.15.5) of the value of type `BioAPI_BIR` in the field `BIR` of the field `InputBIR` of *V*, and

b) the inbound value of all other parameters shall be an empty string.

9.2.16.5.5 If *F* is less than 1 or greater than 3, then the inbound value of all parameters except `Form` shall be an empty string.

9.2.17 Parameter group "Identify population"

9.2.17.1 The parameter group "Identify population" consists of the following parameters:

— `Type`;

— `BIRDataBase`;

— `NumberOfMembers`;

— the members of the parameter group "BIR" (see 9.2.15) with their names prefixed by "`BIR_1_`";

— the members of the parameter group "BIR" with their names prefixed by "`BIR_2_`";

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

— the members of the parameter group “BIR” with their names prefixed by “BIR_3_”;

— the members of the parameter group “BIR” with their names prefixed by “BIR_4_”.

9.2.17.2 This parameter group supports the representation of the values of the native type BioAPI_IDENTIFY_POPULATION.

9.2.17.3 The members of this parameter group shall have inbound and outbound values as specified in the four following subclauses.

9.2.17.3.1 An outbound value of Type shall be either a valid representation of an integer (see 7.4) in the range 0 to 255 or an empty string. An inbound value shall be the canonical representation of an integer (see 7.4.3) in the same range.

9.2.17.3.2 An outbound value of BIRDataBase shall be either a valid representation of an integer in the range −2147483648 to 2147483647 or an empty string. An inbound value shall be the canonical representation of an integer in the same range.

9.2.17.3.3 An outbound value of NumberOfMembers shall be either a valid representation of an integer in the range 0 to 4 or an empty string. An inbound value of NumberOfMembers shall be the canonical representation of an integer in the range 0 to 4294967295.

9.2.17.3.4 An outbound value of each parameter group “BIR” shall be a valid representation of a value of the native type BioAPI_BIR. An inbound value shall be either the canonical representation of a value of that type or a set of empty strings.

9.2.17.4 The value (i.e. *V*) of the native type BioAPI_IDENTIFY_POPULATION represented by an outbound value of this parameter group shall be determined as specified in the four following subclauses.

9.2.17.4.1 The integer (say, *T*) represented by the outbound value of Type (or zero if the outbound value is an empty string) shall be written to the field of *V* with the same name.

9.2.17.4.2 If *T* is 1, then

a) the integer represented by the outbound value of BIRDataBase (or zero if the outbound value is an empty string) shall be written to a variable of type BioAPI_DB_HANDLE, and

b) the address of that variable shall be written to the field BIRDataBase of the field BIRs of *V*.

9.2.17.4.3 If *T* is 2, then

a) the integer represented by the outbound value of NumberOfMembers (or zero if the outbound value is an empty string) shall be written to the field NumberOfMembers of a variable of type BioAPI_BIR_ARRAY_POPULATION,

b) the value of type BioAPI_BIR represented by the outbound value of the parameter group “BIR” with the prefix “BIR_*X*_” (with *X* = 1, 2, 3 or 4) shall be written to a variable of type BioAPI_BIR,

c) the addresses of all the variables of type BioAPI_BIR assigned in b) shall be written, in order, to an array of pointers,

d) the address of that array of pointers shall be written to the field Members of the variable of type BioAPI_BIR_ARRAY_POPULATION referenced in a), and

e) the address of that variable shall be written to the field BIRArray of the field BIRs of *V*.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.2.17.4.4 If *T* is less than 1 or greater than 2, then the field `BIRArray` of the field `BIRs` of *V* shall be set to NULL.

9.2.17.5 Given a value (i.e. *V*) of the native type `BioAPI_IDENTIFY_POPULATION`, the inbound value of this parameter group that canonically represents *V* shall be determined as specified in 9.2.17.5.1 to 9.2.17.5.4.

9.2.17.5.1 The inbound value of `Type` shall be the canonical representation of the integer (say, *T*) in the field of *V* with the same name.

9.2.17.5.2 If *T* is 1, then

a) the inbound value of `BIRDataBase` shall be the canonical representation of the integer in the variable of type `BioAPI_DB_HANDLE` pointed to by the field `BIRDataBase` of the field `BIRs` of *V*, and

b) the inbound value of all other parameters shall be an empty string.

9.2.17.5.3 If *T* is 2, then

a) the inbound value of `NumberOfMembers` shall be the canonical representation of the integer in the field `NumberOfMembers` of the variable of type `BioAPI_BIR_ARRAY_POPULATION` pointed to by the field `BIRArray` of the field `BIRs` of *V*,

b) the inbound value of the parameter group "BIR" with the prefix "`BIR_X_`" (with *X* = 1, 2, 3, and 4) shall be determined as follows. If the field `Members` of the variable in a) is NULL or the field `NumberOfMembers` is less than *X*, then the inbound value shall be a set of empty strings. Otherwise, the inbound value shall be the canonical representation of the inbound value of type `BioAPI_BIR` pointed to by the element at position *X* of the array of pointers pointed to by the field `Members`, and

c) the inbound value of `BIRDataBase` shall be an empty string.

9.2.17.5.4 If *T* is less than 1 or greater than 2, then the inbound value of all parameters except `Type` shall be an empty string.

9.2.18 Parameter group "Candidate"

9.2.18.1 The parameter group "Candidate" consists of the following parameters:

— `Type`;

— `BIRInDataBase`;

— `BIRInArray`;

— `FMRAchieved`.

9.2.18.2 This parameter group supports the representation of the values of the native type `BioAPI_CANDIDATE`.

9.2.18.3 The members of this parameter group shall have inbound and outbound values as specified in the four following subclauses.

9.2.18.3.1 An outbound value of `Type` shall be either a valid representation of an integer (see 7.4) in the range 0 to 255 or an empty string. An inbound value shall be the canonical representation of an integer (see 7.4.3) in the same range.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.2.18.3.2 An outbound value of `BIRInDataBase` shall be either a valid representation of a UUID (see 7.6) or an empty string. An inbound value shall be the canonical representation of a UUID (see 7.6.3).

9.2.18.3.3 An outbound value of `BIRInArray` shall be either a valid representation of an integer in the range 0 to 4294967295 or an empty string. An inbound value shall be the canonical representation of an integer in the same range.

9.2.18.3.4 An outbound value of `FMRAchieved` shall be either a valid representation of an integer in the range −2147483648 to 2147483647 or an empty string. An inbound value shall be the canonical representation of an integer in the same range.

9.2.18.4 The value (i.e. *V*) of the native type `BioAPI_CANDIDATE` represented by an outbound value of this parameter group shall be determined as specified in the five following subclauses.

9.2.18.4.1 The integer (say, *T*) represented by the outbound value of `Type` (or zero if the outbound value is an empty string) shall be written to the field `Type` of *V*.

9.2.18.4.2 If *T* is 1, then

a) the UUID represented by the outbound value of `BIRInDataBase` (or the UUID "`00000000-0000-0000-0000-000000000000`" if the outbound value is an empty string) shall be written to a variable of type `BioAPI_UUID`, and

b) the address of that variable shall be written to the field `BIRInDataBase` of the field `BIR` of *V*.

9.2.18.4.3 If *T* is either 2 or 3, then

a) the integer represented by the outbound value of `BIRInArray` (or zero if the outbound value is an empty string) shall be written to a variable of type `uint32_t`, and

b) the address of that variable shall be written to the field `BIRInArray` of the field `BIR` of *V*.

9.2.18.4.4 If *T* is less than 1 or greater than 3, then the field `BIRInArray` of the field `BIR` of *V* shall be set to NULL.

9.2.18.4.5 The integer represented by the outbound value of `FMRAchieved` (or zero if the outbound value is an empty string) shall be written to the field of *V* with the same name.

9.2.18.5 Given a value (i.e. *V*) of the native type `BioAPI_CANDIDATE`, the inbound value of this parameter group that canonically represents *V* shall be determined as specified in the four following subclauses.

9.2.18.5.1 The inbound value of `Type` shall be the canonical representation of the integer (say, *T*) in the field of *V* with the same name.

9.2.18.5.2 If *T* is 1, then the inbound value of `BIRInDataBase` shall be the canonical representation of the UUID in the variable of type `BioAPI_UUID` pointed to by the field `BIRInDataBase` of *V*. Otherwise, the inbound value of `BIRInDataBase` shall be an empty string.

9.2.18.5.3 If *T* is either 2 or 3, then the inbound value of `BIRInArray` shall be the canonical representation of the integer in the variable of type `uint32_t` pointed to by the field `BIRInArray` of *V*. Otherwise, the inbound value of `BIRInArray` shall be an empty string.

9.2.18.5.4 The inbound value of `FMRAchieved` shall be the canonical representation of the integer (say, *T*) in the field of *V* with the same name.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.2.19 Parameter group "GUI state"

9.2.19.1 The parameter group "GUI state" consists of the following parameters:

— `SampleAvailable`;

— `MessageProvided`;

— `ProgressProvided`.

9.2.19.2 This parameter group supports the representation of the values of the native type `BioAPI_GUI_STATE` (which is an integer type).

9.2.19.3 An outbound value of these parameters shall be either a valid representation of a Boolean (see 7.5) or an empty string. An inbound value of these parameters shall be the canonical representation of a Boolean (see 7.5.2).

9.2.19.4 The value (i.e. *V*) of the native type `BioAPI_GUI_STATE` represented by an outbound value of this parameter group shall be determined as follows.

a) The value *V* shall be initially set to zero.

b) For each member of the parameter group whose outbound value is "`true`", an integer shall be added to *V* according to Table 8.

Table 8

`SampleAvailable`	$1 = 2^0$
`MessageProvided`	$2 = 2^1$
`ProgressProvided`	$4 = 2^2$

9.2.19.5 Given an integer (i.e. *V*) that is a value of the native type `BioAPI_GUI_STATE`, the inbound value of this parameter group that canonically represents *V* shall be determined as follows.

a) The integer *V* shall be decomposed into a sum of powers of two, each occurring at most once.

b) For each power of two that occurs in the decomposition of *V*, the inbound value of the corresponding parameter (according to Table 8) shall be "`true`".

c) The inbound value of all the remaining parameters (if any) shall be "`false`".

9.2.20 Parameter group "Access type"

9.2.20.1 The parameter group "Access type" consists of the following parameters:

— `ReadAccess`;

— `WriteAccess`.

9.2.20.2 This parameter group supports the representation of the values of the native type `BioAPI_DB_ACCESS_TYPE` (which is an integer type).

9.2.20.3 An outbound value of these parameters shall be either a valid representation of a Boolean (see 7.5) or an empty string. An inbound value of these parameters shall be the canonical representation of a Boolean (see 7.5.2).

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.2.20.4 The value (i.e. *V*) of the native type `BioAPI_DB_ACCESS_TYPE` represented by an outbound value of this parameter group shall be determined as follows.

a) The value *V* shall be initially set to zero.

b) For each member of the parameter group whose outbound value is "`true`", an integer shall be added to *V* according to Table 9.

Table 9

`ReadAccess`	$1 = 2^0$
`WriteAccess`	$2 = 2^1$

9.2.20.5 Given an integer (i.e. *V*) that is a value of the native type `BioAPI_DB_ACCESS_TYPE`, the inbound value of this parameter group that canonically represents *V* shall be determined as follows.

a) The integer *V* shall be decomposed into a sum of powers of two, each occurring at most once.

b) For each power of two that occurs in the decomposition of *V*, the inbound value of the corresponding parameter (according to Table 9) shall be "`true`".

c) The inbound value of all the remaining parameters (if any) shall be "`false`".

9.2.21 Parameter group "GUI Event Subscription"

9.2.21.1 The parameter group "GUI Event Subscrition" consists of the following parameters:

— `SubScriberEndpointIRI`;

— `GUIEventSubscriptionUuid`;

— `GUISelectEventSubscribed`;

— `GUIStateEventSubscribed`;

— `GUIProgressEventSubscribed`.

9.2.21.2 This parameter group supports the representation of the values of the native type `BioAPI_GUI_EVENT_SUBSCRIPTION`.

9.2.21.3 The members of this parameter group shall have inbound and outbound values as specified in the three following subclauses.

9.2.21.3.1 An outbound value of `GUIEventSubscribedUuid` shall be either a valid representation of a UUID (see 7.6) or an empty string. An inbound value shall be the canonical representation of a UUID (see 7.6.3).

9.2.21.3.2 An outbound or inbound value of `SubscriberEndpointIRI` shall be a character string that does not contain any NULL (0) characters.

9.2.21.3.3 An outbound value of `GUISelectEventSubscribed`, `GUIStateEventSubscribed` and `BioProgressEventSubscribed` shall be either a valid representation of a Boolean (see 7.5) or an empty string. An inbound value shall be the canonical representation of a Boolean (see 7.5.2).

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.2.21.4 The value (i.e. *V*) of the native type `BioAPI_GUI_EVENT_SUBSCRIPTION` represented by an outbound value of this parameter group shall be determined as specified in 9.2.21.4.1 to 9.2.21.4.3.

9.2.21.4.1 The UUID represented by the outbound value of `GUIEventSubscribedUuid` (or the UUID "`00000000-0000-0000-0000-000000000000`" if the outbound value is an empty string) shall be written to the field of *V* with the same name.

9.2.21.4.2 The integer represented by the outbound value of `SubscriberEndpointIRI` (or zero if the outbound value is an empty string) shall be written to the field of *V* with the same name.

9.2.21.4.3 The Boolean represented by the outbound value of `GUISelectEventSubscribed`, `GUIStateEventSubscribed` and `BioProgressEventSubscribed` (or "`false`" if the outbound value is an empty string) shall be written to the field of *V* with the same name.

9.2.21.5 Given a value (i.e. *V*) of the native type `BioAPI_GUI_EVENT_SUBSCRIPTION`, the inbound value of this parameter group that canonically represents *V* shall be determined as specified in 9.2.21.5.1 to 9.2.21.5.3.

9.2.21.5.1 The inbound value of `GUIEventSubscribedUuid` shall be the canonical representation (see 7.6.3) of the UUID in the field of *V* with the same name.

9.2.21.5.2 The inbound value of `SubscriberEndpointIRI` shall be the canonical representation of the integer in the field of *V* with the same name.

9.2.21.5.3 The inbound value of `GUISelectEventSubscribed`, `GUIStateEventSubscribed` and `BioProgressEventSubscribed` shall be the canonical representation (see 7.5.2) of the Boolean in the field of *V* with the same name.

9.2.22 Parameter group "Key Information"

9.2.22.1 The parameter group "Key Information" consists of the following parameters:

— `KTInfo`;

— `KEKInfo`.

9.2.22.2 This parameter group supports the representation of the values of the native type `BioAPI_KEY_INFO`.

9.2.22.3 The members of this parameter group shall have inbound and outbound values as specified in a) and b).

a) An outbound value of `KTInfo` shall be either a representation of an encoded data of ASN.1 or an empty string. An inbound value shall be the canonical representation of a value of that type.

b) An outbound value of `KEKInfo` shall be either a representation of an encoded data of ASN.1 DER or an empty string. An inbound value shall be the canonical representation of a value of that type.

9.2.22.4 The value (i.e. *V*) of the native type `BioAPI_KEY_INFO` represented by an outbound value of this parameter group shall be determined as specified in a) and b).

a) The value of type `BioAPI_KEY_TRANSPORT` presented by the outbound value of the `KTInfo` shall be written to the field of *V* with the same name.

b) The value of type `BioAPI_ASN1_ENCODED` presented by the outbound value of the `KEKInfo` shall be written to the field of *V* with the same name.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.2.22.5 Given a value (i.e. *V*) of the native type `BioAPI_KEY_INFO`, the inbound value of this parameter group that canonically represents *V* shall be determined as specified in a) and b).

a) The inbound value of `KTInfo` shall be the canonical representation of the key information when key management technique of key transport is used.

b) The inbound value of `KEKInfo` shall be the key management technique of symmetric key encription keys.

9.2.23 Parameter group "Key Transport"

9.2.23.1 The parameter group "Key Transport" consists of the following parameters:

— `IssuerAndSerialNumber`;

— `Certificate`.

9.2.23.2 This parameter group supports the representation of the values of the native type `BioAPI_KEY_TRANSPORT`.

9.2.23.3 The members of this parameter group shall have inbound and outbound values as specified in the five following subclauses.

a) An outbound value of `IssueAndSerialNumber` shall be either a representation of an encoded data of ASN.1 or an empty string. An inbound value shall be the canonical representation of a value of that type.

b) An outbound value of `Cerificate` shall be either a representation of an encoded data of ASN.1 or an empty string. An inbound value shall be the canonical representation of a value of that type.

9.2.23.4 The value (i.e. *V*) of the native type `BioAPI_KEY_TRANSPORT` represented by an outbound value of this parameter group shall be determined as specified in a) and b).

a) The `BioAPI_ASN1_ENCODED` represented by the outbound value of `IssueAndSerialNumber` shall be written to the ASN.1 encoded data of ASN.1 type `IssuerAndSerialNumber` which contains the information of issuer and serial number of the X.509 certificate for the public key.

b) The `BioAPI_ASN1_ENCODED` represented by the outbound value of `Cerificate` shall be written to the ASN.1 encoded data of ASN.1 type certificate which contains X.509 certificate of the public key.

9.2.23.5 Given a value (i.e. *V*) of the native type `BioAPI_KEY_TRANSPORT`, the inbound value of this parameter group that canonically represents *V* shall be determined as specified in a) and b).

a) The inbound value of `IssueAndSerialNumber` shall be the canonical representation of the encoded data of ASN.1.

b) The inbound value of `Certificate` shall be the canonical representation of the encoded data of ASN.1.

9.2.24 Parameter group "MAC Algorithm Information"

9.2.24.1 The parameter group "MAC Algorithm Information" consists of the following parameters:

— `MACAlg`;

— `MACKeyInfo`;

— `NumberOfElementsMackKeyInfo`.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.2.24.2 This parameter group supports the representation of the values of the native type `BioAPI_MAC_INFO`.

9.2.24.3 The members of this parameter group shall have inbound and outbound values as specified in the two following subclauses.

a) An outbound value of `MACAlg` shall be either a valid representation of a MAC algorithm or an empty string. An inbound value shall be the canonical representation of a MAC algorithm.

b) An outbound value of `MACKeyInfo` shall be either a valid representation of an array of key information for message authentication code or an empty string. An inbound value shall be the canonical representation of the key information.

c) An outbound value of `NumberOfElementsMackKeyInfo` shall be either a valid representation of the array of `MackKeyInfo` or an empty string. An inbound value shall be the canonical representation of the `MackKeyInfo` information.

9.2.24.4 The value (i.e. *V*) of the native type `BioAPI_MAC_INFO` represented by an outbound value of this parameter group shall be determined as specified in the two following subclauses.

a) The `BioAPI_MAC_ALG` represented by the outbound value of `MACAlg` shall be written to the field of *V* with same name.

b) The `BioAPI_KEY_INFO` represented by the outbound value of `MACKeyInfo` shall be written to the field of *V* with same name.

c) The integer represented by the outbound value of `NumberOfElementsMackKeyInfo` shall be written to the field of *V* with the same name.

9.2.24.5 The integer represented by the outbound value of `NumberOfElementsMackKeyInfo` shall be written to the field of *V* with the same name. Given a value (i.e. *V*) of the native type `BioAPI_MAC_INFO`, the inbound value of this parameter group that canonically represents *V* shall be determined as specified in the two following subclauses.

a) The inbound value of `MACAlg` shall be the canonical representation of a MAC algorithm in the field of *V* with the same name.

b) The inbound value of `MACKeyInfo` shall be the canonical representation of an array of the key information for message authentication code in the field of *V* with the same name.

c) The inbound value of `NumberOfElementsMackKeyInfo` shall be the canonical representation of the integer in the field of *V* with same name.

9.2.25 Parameter group "Security Options Mask"

9.2.25.1 The parameter group "Security Options Mask" consists of the following parameters:

— `BioAPI_ENCRYPTION`;

— `BioAPI_MAC`;

— `BioAPI_DIGITAL_SIGNATURE`;

— `BioAPI_ACBio_GENERATION_WITH_MAC`;

— `BioAPI_ACBio_GENERATION_WITH_DIGITAL_SIGNATURE`.

9.2.25.2 This parameter group supports the representation of the values of the native type `BioAPI_SECURITY_OPTIONS_MASK`.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

 © ISO/IEC 2017 – All rights reserved

9.2.25.3 An outbound value of `BioAPI_ENCRYPTION`, `BioAPI_MAC`, `BioAPI_DIGITAL_SIGNATURE`, `BioAPI_ACBio_GENERATION_WITH_MAC` and `BioAPI_ACBio_GENERATION_WITH_DIGITAL_SIGNATURE` shall be either a valid representation of an integer in the range 0 to 4294967295 or an empty string. An inbound value shall be the canonical representation of an integer in the same range.

9.2.25.4 The value (i.e. *V*) of the native type `BioAPI_SECURITY_OPTIONS_MASK` represented by an outbound value of this parameter group shall be determined as specified in a) and b).

a) the value *V* shall be initially set to zero;

b) for each member of the parameter group whose outbound value is "`true`", an integer shall be added to *V* according to Table 10.

Table 10

`BioAPI_ENCRYPTION`	$1 = 2^0$
`BioAPI_MAC`	$2 = 2^1$
`BioAPI_DIGITAL_SIGNATURE`	$4 = 2^2$
`BioAPI_ACBio_GENERATION_WITH_MAC`	$16 = 2^4$
`BioAPI_ACBio_GENERATION_WITH_DIGITAL_SIGNATURE`	$32 = 2^5$

9.2.25.5 Given a value (i.e. *V*) of the native type `BioAPI_SECURITY_OPTIONS_MASK`, the inbound value of this parameter group that canonically represents *V* shall be determined as specified in a) to c).

a) the integer *V* shall be decomposed into a sum of powers of two, each occurring at most once;

b) for each power of two that occurs in the decomposition of *V*, the inbound value of the corresponding parameter (according to Table 10) shall be "`true`";

c) the inbound value of all the remaining parameters (if any) shall be "`false`".

9.2.26 Parameter group "Security Profile"

9.2.26.1 The parameter group "Security Profile" consists of the following parameters:

— `SupportedSecOption`;

— `ENCInfo`;

— `NumberOfElementsEncInfo`;

— `MACInfo`;

— `NumberOfElementsMACInfo`;

— `SIGNAlg`;

— `NumberOfElementsSIGNAlg`;

— `ACBioOption`;

— `HASHAlgForACBio`;

— `NumberOfElementsHASHAlgForACBio`;

— `MACInfoForACBio`;

— `NumberOfElementsMACInfoForACBio`;

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

— SIGNAlgForACBio;

— NumberOfElementsSIGNAlgForACBio.

9.2.26.2 This parameter group supports the representation of the values of the native type BioAPI_SECURITY_PROFILE.

9.2.26.3 The members of this parameter group shall have inbound and outbound values as specified in a) to f).

a) An outbound value of SupportedSecOption, SIGAlg, ACBioOption and NumberOfElementsEncInfo, NumberOfElementsMACInfo, NumberOfElementsSIGNAlg, NumberOfElementsHASHAlgForACBio, NumberOfElementsMACInfoForACBio and NumberOfElementsSIGNAlgForACBio shall be either a valid representation of an integer in the range 0 to 4294967295 or an empty string. An inbound value shall be the canonical representation of same name.

b) An outbound value of ENCInfo shall be either a valid representation of an encryption information used in the encryption of the BDB or an empty string. An inbound value shall be the canonical representation of same name.

c) An outbound value of MACInfo shall be either a valid representation of a MAC information used to keep the integrity of the BIR or an empty string. An inbound value shall be the canonical representation of same name.

d) An outbound value of HASHAlgForACBio shall be either a valid representation of a hash algorithm or an empty string. An inbound value shall be the canonical representation of same name.

e) An outbound value of MACInfoForACBio shall be either a valid representation of a MAC information used to generate ACBio instances or an empty string. An inbound value shall be the canonical representation of same name.

f) An outbound value of SIGNAlgForACBio shall be either a valid representation of a digital signature algorithm or an empty string. An inbound value shall be the canonical representation of same name.

9.2.26.4 The value (i.e. *V*) of the native type BioAPI_SECURITY_PROFILE represented by an outbound value of this parameter group shall be determined as specified in the following seven list items.

a) The integer represented by the outbound value of SupportedSecOption, SIGAlg and ACBioOption shall be written to the field of *V* with the same name.

b) The value of type BioAPI_ENCRPTION_INFO represented by the outbound value of the encryption information shall be written to the field ENCInfo of *V* with the same name.

c) The value of type BioAPI_MAC_INFO represented by the outbound value of the MAC information shall be written to the field MACInfo of *V* with the same name.

d) The value of type BioAPI_HASH_ALG represented by the outbound value of a hash algorithm shall be written to the field HASHAlgForACBio of *V* with the same name.

e) The value of MAC information represented by the outbound value of a MAC algorithm shall be written to the field MACInfoForACBio of *V* with the same name.

f) The value of a digital signature algorithm represented by the outbound value of SIGNAlgForACBio shall be written to the field of *V* with the same name.

g) An outbound value of NumberOfElementsEncInfo, NumberOfElementsMACInfo, NumberOfElementsSIGNAlg, NumberOfElementsHASHAlgForACBio, NumberOfElementsMACInfoForACBio and NumberOfElementsSIGNAlgForACBio shall

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

 © ISO/IEC 2017 – All rights reserved

be either a valid representation of an integer in the range 0 to 4294967295 or an empty string. An inbound value shall be the canonical representation of an integer in the same range.

9.2.26.5 Given a value (i.e.*V*) of the native type `BioAPI_SECURITY_PROFILE`, the inbound value of this parameter group that canonically represents *V* shall be determined as specified in the following seven list items.

a) The inbound value of `SupportedSecOption`, `SIGAlg` and `ACBioOption` shall be the canonical representation of the integer in the field of *V* with same name.

b) The inbound value of the `ENCInfo` shall be the canonical representation of the value of type `BioAPI_ENCRPTION_INFO` in the field of *V* with the same name.

c) The inbound value of the `MACInfo` shall be the canonical representation of the value of type `BioAPI_MAC_INFO` in the field of *V* with the same name.

d) The inbound value of the `HASHAlgForACBio` shall be the canonical representation of the value of type `BioAPI_HASH_ALG` in the field of *V* with the same name.

e) The inbound value of the `MACInfoForACBio` shall be the canonical representation of the value of the MAC information in the field of *V* with the same name.

f) The inbound value of the `SIGNAlgForACBio` shall be the canonical representation of the value of type `BioAPI_DIGITAL_SIGNATURE_ALG` in the field of *V* with the same name.

g) An inbound value of `NumberOfElementsEncInfo`, `NumberOfElementsMACInfo`, `NumberOfElementsSIGNAlg`, `NumberOfElementsHASHAlgForACBio`, `NumberOfElementsMACInfoForACBio` and `NumberOfElementsSIGNAlgForACBio` shall be the canonical representation of the integer in the variable of type `uint32_t` pointed to by the field of *V* with the same name.

9.2.27 Parameter group "ACBio parameters"

9.2.27.1 The parameter group "ACBio parameters" consists of the following parameters:

— `Challenge`;

— `InitialBPUIOIndexOutput`;

— `SupremumBPUIOIndexOutput`.

9.2.27.2 This parameter group supports the representation of the values of the native type `BioAPI_ACBio_PARAMETERS`.

9.2.27.3 The members of this parameter group shall have inbound and outbound values as specified in the following paragraph.

An outbound value of `Challenge`, `InitialBPUIOIndexOutput` and `SupremumBPUIOIndexOutput` shall be either a valid representation of an integer in the range 0 to 4294967295 or an empty string. An inbound value shall be the canonical representation of same name.

9.2.27.4 The value (i.e. *V*) of the native type `BioAPI_ACBio_PARAMETERS` represented by an outbound value of this parameter group shall be determined as specified in the following paragraph.

The integer represented by the outbound value of `Challenge`, `InitialBPUIOIndexOutput` and `SupremumBPUIOIndexOutput` shall be written to the field of *V* with the same name.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.2.27.5 Given a value (i.e. *V*) of the native type `BioAPI_ACBio_PARAMETERS`, the inbound value of this parameter group that canonically represents *V* shall be determined as specified in the following paragraph.

The inbound value of `Challenge`, `InitialBPUIOIndexOutput` and `SupremumBPUIOIndexOutput` shall be the canonical representation of the integer in the field of *V* with same name.

9.2.28 Parameter group "BFP List Element parameters"

9.2.28.1 The parameter group "BFP List Element parameters" consists of the following parameters:

— `BFPCategory`;

— `BFPUuid`.

9.2.28.2 This parameter group supports the representation of the values of the native type `BioAPI_BFP_LIST_ELEMENT`.

9.2.28.3 The members of this parameter group shall have inbound and outbound values as specified in the following paragraph.

An outbound value of `Challenge`, `BFPCategory` and `BFPUuid` shall be either a valid representation of an integer in the range 0 to 4294967295 or an empty string. An inbound value shall be the canonical representation of same name.

9.2.28.4 The value (i.e. *V*) of the native type `BioAPI_BFP_LIST_ELEMENT` represented by an outbound value of this parameter group shall be determined as specified in the following paragraph.

The integer represented by the outbound value of `Challenge`, `BFPCategory` and `BFPUuid` shall be written to the field of *V* with the same name.

9.2.28.5 Given a value (i.e. *V*) of the native type `BioAPI_BFP_LIST_ELEMENT`, the inbound value of this parameter group that canonically represents *V* shall be determined as specified in the following paragraph.

The inbound value of `Challenge`, `BFPCategory` and `BFPUuid` shall be the canonical representation of the integer in the field of *V* with same name.

9.2.29 Parameter group "Biometric subtype mask"

9.2.29.1 The parameter group "Biometric subtype mask" consists of the following parameters:

— `LEFT_BIT`;

— `RIGHT_BIT`;

— `LEFT_THUMB_BIT`;

— `LEFT_POINTFINGER_BIT`;

— `LEFT_MIDDLEFINGER_BIT`;

— `LEFT_RINGFINGER_BIT`;

— `LEFT_LITTLEFINGER_BIT`;

— `RIGHT_THUMB_BIT`;

— `RIGHT_POINTERFINGER_BIT`;

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

— RIGHT_MIDDLEFINGER_BIT;

— RIGHT_RINGFINGER_BIT;

— RIGHT_LITTLEFINGER_BIT;

— LEFT_PALM_BIT;

— LEFT_BACKOFHAND_BIT;

— LEFT_WRIST_BIT;

— LEFT_MULTIPLE_BIT;

— RIGHT_PALM_BIT;

— RIGHT_BACKOFHAND_BIT;

— RIGHT_WRIST_BIT;

— RIGHT_MULTIPLE_BIT.

9.2.29.2 This parameter group supports the representation of the values of the native type `BioAPI_BIR_SUBTYPE_MASK` (which is an integer type).

9.2.29.3 An outbound value of each of these parameters shall be either a valid representation of a Boolean (see 7.5) or an empty string. An inbound value shall be the canonical representation of a Boolean (see 7.5.2).

9.2.29.4 The value (i.e. *V*) of the native type `BioAPI_BIR_SUBTYPE_MASK` represented by an outbound value of this parameter group shall be determined as follows.

a) The value *V* shall be initially set to zero.

b) For each member of the parameter group whose outbound value is "`true`", an integer shall be added to *V* according to Table 11.

Table 11

LEFT_BIT	$1 = 2^0$
RIGHT_BIT	$2 = 2^1$
LEFT_THUMB_BIT	$4 = 2^2$
LEFT_POINTFINGER_BIT	$8 = 2^3$
LEFT_MIDDLEFINGER_BIT	$16 = 2^4$
LEFT_RINGFINGER_BIT	$32 = 2^5$
LEFT_LITTLEFINGER_BIT	$64 = 2^6$
RIGHT_THUMB_BIT	$128 = 2^7$
RIGHT_POINTERFINGER_BIT	$256 = 2^8$
RIGHT_MIDDLEFINGER_BIT	$512 = 2^9$
RIGHT_RINGFINGER_BIT	$1024 = 2^{10}$
RIGHT_LITTLEFINGER_BIT	$2048 = 2^{11}$
LEFT_PALM_BIT	$4096 = 2^{12}$
LEFT_BACKOFHAND_BIT	$8192 = 2^{13}$
LEFT_WRIST_BIT	$16384 = 2^{14}$
LEFT_MULTIPLE_BIT	$32768 = 2^{15}$
RIGHT_PALM_BIT	$65536 = 2^{16}$

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

Table 11 *(continued)*

RIGHT_BACKOFHAND_BIT	131072 = 2^{17}
RIGHT_WRIST_BIT	262144 = 2^{18}
RIGHT_MULTIPLE_BIT	524288 = 2^{19}

9.2.29.5 Given an integer (i.e. *V*) that is a value of the native type BioAPI_BIR_SUBTYPE_MASK, the inbound value of this parameter group that canonically represents *V* shall be determined as follows.

a) The integer *V* shall be decomposed into a sum of powers of two, each occurring at most once.

b) For each power of two listed in Table 11 that occurs in the decomposition of *V*, the inbound value of the parameter in the corresponding row of the table shall be "true".

c) The inbound value of all the remaining parameters (if any) shall be "false".

9.2.30 Parameter group "ENCRYPTION INFO"

9.2.30.1 The parameter group "ENCRYPTION Information" consists of the following parameters:

— ENCAlg;

— ENCKeyInfo;

— NumberOfElementsEncKeyInfo.

9.2.30.2 This parameter group supports the representation of the values of the native type BioAPI_ENCRYPTION_INFO.

9.2.30.3 The members of this parameter group shall have inbound and outbound values as specified in the two following subclauses.

a) An outbound value of ENCAlg shall be either a valid representation of a cryptographic algorithm or an empty string. An inbound value shall be the canonical representation of a cryptographic algorithm.

b) An outbound value of ENCKeyInfo shall be either a valid representaitn of an array of key information for message authentication code or an empty string. An inbound value shall be the canonical representation of the key information.

c) An outbound value of NumberOfElementsEncKeyInfo shall be either a valid representation of the array of ENCKeyInfo or an empty string. An inbound value shall be the canonical representation of the ENCKeyInfo information.

9.2.30.4 The value (i.e. *V*) of the native type BioAPI_ENCRYPTION_INFO represented by an outbound value of this parameter group shall be determined as specified in a) and b).

a) The BioAPI_ENCRYPTION_ALG represented by the outbound value of ENCAlg shall be written to the field of *V* with same name.

b) The BioAPI_ENCRYPTION_INFO represented by the outbound value of MACKeyInfo shall be written to the field of *V* with same name.

9.2.30.5 The integer represented by the outbound value of NumberOfElementsEncKeyInfo shall be written to the field of *V* with the same name. Given a value (i.e *V*) of the native type

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

 © ISO/IEC 2017 – All rights reserved

BioAPI_ENCRYPTION_INFO, the inbound value of this parameter group that canonically represents *V* shall be determined as specified in the two following subclauses.

a) The inbound value of ENCAlg shall be the canonical representation of a cryptographic algorithm in the field of *V* with the same name.

b) The inbound value of ENCKeyInfo shall be the canonical representation of an array of the key information for message authentication code in the field of *V* with the same name.

c) The inbound value of NumberOfElementsEncKeyInfo shall be the canonical representation of the integer in the field of *V* with same name.

9.3 BioAPI_Init

9.3.1 Function invocation scheme

This function belongs to the BioAPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioAPI_Init(

BioAPI_VERSION Version);

and the following parameters (see Table 12).

Table 12

Parameter	Function invocation (conformance testing model for frameworks)	Bound activity invocation (conformance testing model for applications)
Version	input, outbound	input, inbound
return	return, inbound	input, inbound

9.3.2 Constraints on the parameters

9.3.2.1 An outbound value of Version shall be a valid representation of an integer (see 7.4) in the range 0 to 255. An inbound value shall be the canonical representation of an integer (see 7.4.3) in the same range.

9.3.2.2 An outbound value of return shall be a valid representation of an integer in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer in the same range.

9.3.3 Function invocation input

The integer represented by the outbound value of Version shall be assigned to the native parameter with the same name.

9.3.4 Function invocation output

There are no output parameters.

9.3.5 Bound activity invocation input

9.3.5.1 The inbound value of Version shall be the canonical representation of the integer in the native parameter with the same name.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.3.5.2 The inbound value of `return` shall be the canonical representation of the integer returned by the native function.

9.3.6 Bound activity invocation output

There are no output parameters.

9.4 BioAPI_Terminate

9.4.1 Function invocation scheme

This function belongs to the BioAPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioAPI_Terminate(void);

and the following parameters (see Table 13).

Table 13

Parameter	Function invocation (conformance testing model for frameworks)	Bound activity invocation (conformance testing model for applications)
`return`	return, inbound	input, inbound

9.4.2 Constraints on the parameters

An outbound value of `return` shall be a valid representation of an integer in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer in the same range.

9.4.3 Function invocation input

There are no input parameters.

9.4.4 Function invocation output

There are no output parameters.

9.4.5 Bound activity invocation input

The inbound value of `return` shall be the canonical representation of the integer returned by the native function.

9.4.6 Bound activity invocation output

There are no output parameters.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.5 BioAPI_GetFrameworkInfo

9.5.1 Function invocation scheme

This function belongs to the BioAPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioAPI_GetFrameworkInfo(

BioAPI_FRAMEWORK_SCHEMA *FrameworkSchema);

and the following parameters (see Table 14).

Table 14

Parameter	Function invocation (conformance testing model for frameworks)	Bound activity invocation (conformance testing model for applications)
`no_FrameworkSchema`	input, outbound	input, inbound
the members of the parameter group "Framework schema" (see 9.2.10)	output, inbound	input, inbound
`return`	return, inbound	input, inbound

9.5.2 Constraints on the parameters

9.5.2.1 An outbound value of `no_FrameworkSchema` shall be either a valid representation of a Boolean (see 7.5) or an empty string. An inbound value shall be the canonical representation of a Boolean (see 7.5.2).

9.5.2.2 An outbound value of the parameter group "Framework schema" shall be a valid representation of a value of the native type `BioAPI_FRAMEWORK_SCHEMA`. An inbound value shall be either the canonical representation of a value of that type or a set of empty strings.

9.5.2.3 An outbound value of `return` shall be a valid representation of an integer in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer in the same range.

9.5.3 Function invocation input

If the outbound value of `no_FrameworkSchema` is "`true`", then the native parameter `FrameworkSchema` shall be set to NULL. Otherwise, it shall be set to the address of a variable of type `BioAPI_FRAMEWORK_SCHEMA`.

9.5.4 Function invocation output

The inbound value of the parameter group "Framework schema" shall be determined as follows. If the native parameter `FrameworkSchema` is NULL, then the inbound value shall be a set of empty strings. Otherwise, the inbound value shall be the canonical representation (see 9.2.10.5) of the value of type `BioAPI_FRAMEWORK_SCHEMA` pointed to by the native parameter `FrameworkSchema`.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.5.5 Bound activity invocation input

The inbound value of `no_FrameworkSchema` shall be "`true`" if the native parameter `FrameworkSchema` is NULL; otherwise, it shall be "`false`".

9.5.6 Bound activity invocation output

There are no output parameters.

9.6 BioAPI_EnumBSPs

9.6.1 Function invocation scheme

This function belongs to the BioAPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioAPI_EnumBSPs(

BioAPI_BSP_SCHEMA **BSPSchemaArray,

uint32_t *NumberOfElements);

and the following parameters (see Table 15).

Table 15

Parameter	Function invocation (conformance testing model for frameworks)	Bound activity invocation (conformance testing model for applications)
`no_BSPSchemaArray`	input, outbound	input, inbound
the members of the parameter group "BSP schema" (see 9.2.11) with their names prefixed by "`BSPSchema_1_`"	output, inbound	input, inbound
the members of the parameter group "BSP schema" with their names prefixed by "`BSPSchema_2_`"	output, inbound	input, inbound
the members of the parameter group "BSP schema" with their names prefixed by "`BSPSchema_3_`"	output, inbound	input, inbound
the members of the parameter group "BSP schema" with their names prefixed by "`BSPSchema_4_`"	output, inbound	input, inbound
`no_NumberOfElements`	input, outbound	input, inbound
`NumberOfElements`	output, inbound	input, inbound
`Return`	return, inbound	input, inbound

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.6.2 Constraints on the parameters

9.6.2.1 An outbound value of `no_BSPSchemaArray` and `no_NumberOfElements` shall be either a valid representation of a Boolean (see 7.5) or an empty string. An inbound value shall be the canonical representation of a Boolean (see 7.5.2).

9.6.2.2 An outbound value of each parameter group "BSP schema" shall be a valid representation of a value of the native type `BioAPI_BSP_SCHEMA`. An inbound value shall be either the canonical representation of a value of that type or a set of empty strings.

9.6.2.3 An outbound value of `NumberOfElements` shall be either a valid representation of an integer in the range 0 to 4294967295 or an empty string. An inbound value shall be either the canonical representation of an integer in the same range or an empty string.

9.6.2.4 An outbound value of `return` shall be a valid representation of an integer in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer in the same range.

9.6.3 Function invocation input

9.6.3.1 If the outbound value of `no_BSPSchemaArray` is "`true`", then the native parameter `BSPSchemaArray` shall be set to NULL. Otherwise, it shall be set to the address of a variable of type `BioAPI_BSP_SCHEMA*` (a pointer).

9.6.3.2 If the outbound value of `no_NumberOfElements` is "`true`", then the native parameter `NumberOfElements` shall be set to NULL. Otherwise, it shall be set to the address of a variable of type `uint32_t`.

9.6.4 Function invocation output

9.6.4.1 The inbound value of the parameter group "BSP schema" with the prefix "`BSPSchema_X_`" (with *X* = 1, 2, 3, or 4) shall be determined as follows. If the native parameter `BSPSchemaArray` is NULL or the variable pointed to by that native parameter is NULL or the native parameter `NumberOfElements` is NULL or the value of the integer variable pointed to by that native parameter is less than *X*, then the inbound value shall be a set of empty strings. Otherwise, the inbound value shall be the canonical representation (see 9.2.11.5) of the value of type `BioAPI_BSP_SCHEMA` at position *X* in the array pointed to by the variable pointed to by the native parameter `BSPSchemaArray`.

9.6.4.2 The inbound value of `NumberOfElements` shall be determined as follows. If the native parameter with the same name is NULL, then the inbound value shall be an empty string. Otherwise, the inbound value shall be the canonical representation of the integer in the variable of type `uint32_t` pointed to by the native parameter `NumberOfElements`.

9.6.5 Bound activity invocation input

9.6.5.1 The inbound value of `no_BSPSchemaArray` shall be "`true`" if the native parameter `BSPSchemaArray` is NULL; otherwise, it shall be "`false`".

9.6.5.2 The inbound value of `no_NumberOfElements` shall be "`true`" if the native parameter `NumberOfElements` is NULL; otherwise, it shall be "`false`".

9.6.5.3 The inbound value of `return` shall be the canonical representation of the integer returned by the native function.

9.6.5.4 The inbound values of the other input parameters shall be determined as specified in 9.6.4.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.6.6 Bound activity invocation output

There are no output parameters.

9.7 BioAPI_BSPLoad

9.7.1 Function invocation scheme

This function belongs to the BioAPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioAPI_BSPLoad(

const BioAPI_UUID *BSPUuid,

BioAPI_-EventHandler AppNotifyCallback,

void* AppNotifyCallbackCtx);

and the following parameters (see Table 16).

Table 16

Parameter	Function invocation (conformance testing model for frameworks)	Bound activity invocation (conformance testing model for applications)
`BSPUuid`	input, outbound	input, inbound
`AppNotifyCallback`	input, outbound	input, inbound
`AppNotifyCallbackCtx`	input, outbound	input, inbound
`return`	return, inbound	input, inbound

9.7.2 Constraints on the parameters

9.7.2.1 An outbound value of `BSPUuid` shall be a valid representation of a UUID (see 7.6). An inbound value shall be the canonical representation of a UUID (see 7.6.3).

9.7.2.2 An outbound value of `AppNotifyCallback` and `AppNotifyCallbackCtx` shall be either "`0`" or "`*`". An inbound value shall be the canonical representation of an integer (see 7.4.3) in the range 0 to 4294967295.

9.7.2.3 An outbound value of `return` shall be a valid representation of an integer in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer in the same range.

9.7.3 Function invocation input

9.7.3.1 The UUID represented by the outbound value of `BSPUuid` shall be written to a variable of `type BioAPI_UUID`, whose address shall be assigned to the native parameter `BSPUuid`.

9.7.3.2 If the outbound value of `AppNotifyCallback` is "`0`", a NULL pointer value shall be assigned to the native parameter `AppNotifyCallback`. If it is "`*`", a non-NULL pointer value, which is the address of a native function (within the testing component) implementing the standard BioAPI interface function `BioAPI_Event_Handler`, shall be assigned to the native parameter `AppNotifyCallback`.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

 © ISO/IEC 2017 – All rights reserved

NOTE If the outbound value of `AppNotifyCallback` is not "`0`", any subsequent incoming calls to the standard BioAPI interface function `BioAPI_EventHandler` will result in an invocation of the activity bound to this function, if such a binding exists.

9.7.3.3 If the outbound value of `AppNotifyCallbackCtx` is "`0`", a NULL pointer value shall be assigned to the native parameter `AppNotifyCallbackCtx`. If it is "`*`", a non-NULL pointer value, which is the address of a variable of type `void*` set to NULL, shall be assigned to the native parameter `AppNotifyCallbackCtx`.

9.7.4 Function invocation output

There are no output parameters.

9.7.5 Bound activity invocation input

9.7.5.1 The inbound value of `BSPUuid` shall be the canonical representation of the UUID in the variable of type `BioAPI_UUID` pointed to by the native parameter `BSPUuid`.

9.7.5.2 The inbound value of `AppNotifyCallback` and `AppNotifyCallbackCtx` shall be the canonical representation of the integer in the native parameter with the same name.

9.7.5.3 The inbound value of `return` shall be the canonical representation of the integer returned by the native function.

9.7.6 Bound activity invocation output

There are no output parameters.

9.8 BioAPI_BSPUnload

9.8.1 Function invocation scheme

This function belongs to the BioAPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioAPI_BSPUnload(

const BioAPI_UUID *BSPUuid,

BioAPI_EventHandler AppNotifyCallback,

void* AppNotifyCallbackCtx);

and the following parameters (see Table 17).

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

Table 17

Parameter	Function invocation (conformance testing model for frameworks)	Bound activity invocation (conformance testing model for applications)
`BSPUuid`	input, outbound	input, inbound
`AppNotifyCallback`	input, outbound	input, inbound
`AppNotifyCallbackCtx`	input, outbound	input, inbound
`return`	return, inbound	input, inbound

9.8.2 Constraints on the parameters

9.8.2.1 An outbound value of `BSPUuid` shall be a valid representation of a UUID (see 7.6). An inbound value shall be the canonical representation of a UUID (see 7.6.3).

9.8.2.2 An outbound value of `AppNotifyCallback` and `AppNotifyCallbackCtx` shall be either "`0`" or "`*`". An inbound value shall be the canonical representation of an integer (see 7.4.3) in the range 0 to 4294967295.

9.8.2.3 An outbound value of `return` shall be a valid representation of an integer in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer in the same range.

9.8.3 Function invocation input

9.8.3.1 The UUID represented by the outbound value of `BSPUuid` shall be written to a variable of type `BioAPI_UUID`, whose address shall be assigned to the native parameter `BSPUuid`.

9.8.3.2 If the outbound value of `AppNotifyCallback` is "`0`", a NULL pointer value shall be assigned to the native parameter `AppNotifyCallback`. If it is "`*`", a non-NULL pointer value, which is the address of a native function (within the testing component) implementing the standard BioAPI interface function `BioAPI_EventHandler`, shall be assigned to the native parameter `AppNotifyCallback`.

9.8.3.3 If the outbound value of `AppNotifyCallbackCtx` is "`0`", a NULL pointer value shall be assigned to the native parameter `AppNotifyCallbackCtx`. If it is "`*`", a non-NULL pointer value, which is the address of a variable of type `void*` set to NULL, shall be assigned to the native parameter `AppNotifyCallbackCtx`.

9.8.4 Function invocation output

There are no output parameters.

9.8.5 Bound activity invocation input

9.8.5.1 The inbound value of `BSPUuid` shall be the canonical representation of the UUID in the variable of type `BioAPI_UUID` pointed to by the native parameter `BSPUuid`.

9.8.5.2 The inbound value of `AppNotifyCallback` and `AppNotifyCallbackCtx` shall be the canonical representation of the integer in the native parameter with the same name.

9.8.5.3 The inbound value of `return` shall be the canonical representation of the integer returned by the native function.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

 © ISO/IEC 2017 – All rights reserved

9.8.6 Bound activity invocation output

There are no output parameters.

9.9 BioAPI_BSPAttach

9.9.1 Function invocation scheme

This function belongs to the BioAPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioAPI_BSPAttach(

const BioAPI_UUID *BSPUuid,

BioAPI_VERSION Version,

const BioAPI_UNIT_LIST_ELEMENT *UnitList,

uint32_t NumUnits,

BioAPI_HANDLE *NewBSPHandle);

and the following parameters (see Table 18).

Table 18

Parameter	Function invocation (conformance testing model for frameworks)	Bound activity invocation (conformance testing model for applications)
BSPUuid	input, outbound	input, inbound
Version	input, outbound	input, inbound
Unit_1_UnitCategory	input, outbound	input, inbound
Unit_1_UnitID	input, outbound	input, inbound
Unit_2_UnitCategory	input, outbound	input, inbound
Unit_2_UnitID	input, outbound	input, inbound
Unit_3_UnitCategory	input, outbound	input, inbound
Unit_3_UnitID	input, outbound	input, inbound
Unit_4_UnitCategory	input, outbound	input, inbound
Unit_4_UnitID	input, outbound	input, inbound
NumUnits	input, outbound	input, inbound
no_NewBSPHandle	input, outbound	input, inbound
NewBSPHandle	output, inbound	input, inbound
return	return, inbound	input, inbound

9.9.2 Constraints on the parameters

9.9.2.1 An outbound value of BSPUuid shall be a valid representation of a UUID (see 7.6). An inbound value shall be the canonical representation of a UUID (see 7.6.3).

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.9.2.2 An outbound value of `Version` shall be a valid representation of an integer (see 7.4) in the range 0 to 255. An inbound value shall be the canonical representation of an integer (see 7.4.3) in the same range.

9.9.2.3 An outbound value of `Unit_X_UnitCategory` and `Unit_X_UnitID` (with *X* = 1, 2, 3, or 4) shall be either a valid representation of an integer in the range 0 to 4294967295 or an empty string. An inbound value shall be either the canonical representation of an integer in the same range or an empty string.

9.9.2.4 An outbound value of `NumUnits` shall be a valid representation of an integer in the range 0 to 4. An inbound value shall be the canonical representation of an integer in the range 0 to 4294967295.

9.9.2.5 An outbound value of `no_NewBSPHandle` shall be either a valid representation of a Boolean (see 7.5) or an empty string. An inbound value shall be the canonical representation of a Boolean (see 7.5.2).

9.9.2.6 An outbound value of `NewBSPHandle` shall be either a valid representation of an integer in the range 0 to 4294967295 or an empty string. An inbound value shall be either the canonical representation of an integer in the same range or an empty string.

9.9.2.7 An outbound value of `return` shall be a valid representation of an integer in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer in the same range.

9.9.3 Function invocation input

9.9.3.1 The UUID represented by the outbound value of `BSPUuid` shall be written to a variable of type `BioAPI_UUID`, whose address shall be assigned to the native parameter `BSPUuid`.

9.9.3.2 The integer represented by the outbound value of `Version` and `NumUnits` shall be assigned to the native parameter with the same name.

9.9.3.3 The integer represented by the outbound value of `Unit_X_UnitCategory` and `Unit_X_UnitID` (with *X* = 1, 2, 3, or 4), or zero if that value is an empty string, shall be written to the fields `UnitCategory` and `UnitID` (respectively) of the element at position *X* of an array of four elements of type `BioAPI_UNIT_LIST_ELEMENT`. The address of that array shall be assigned to the native parameter `UnitList`.

9.9.3.4 If the outbound value of `no_NewBSPHandle` is "`true`", then the native parameter `NewBSPHandle` shall be set to NULL; otherwise, it shall be set to the address of a variable of type `BioAPI_HANDLE`.

9.9.4 Function invocation output

The inbound value of `NewBSPHandle` shall be determined as follows. If the native parameter with the same name is NULL, then the inbound value shall be an empty string. Otherwise, the inbound value shall be the canonical representation of the integer in the variable of type `BioAPI_HANDLE` pointed to by the native parameter `NewBSPHandle`.

9.9.5 Bound activity invocation input

9.9.5.1 The inbound value of `BSPUuid` shall be the canonical representation of the UUID in the variable of type `BioAPI_UUID` pointed to by the native parameter `BSPUuid`.

9.9.5.2 The inbound value of `Version` and `NumUnits` shall be the canonical representation of the integer in the native parameter with the same name.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

 © ISO/IEC 2017 – All rights reserved

9.9.5.3 The inbound value of `Unit_X_UnitCategory` and `Unit_X_UnitID` (with *X* = 1, 2, 3, or 4) shall be determined as follows. If the native parameter `NumUnits` is less than *X*, then the inbound value shall be an empty string. Otherwise, the inbound value shall be the canonical representation of the integer in the fields `UnitCategory` and `UnitID` (respectively) of the element at position *X* of the array of elements of type `BioAPI_UNIT_LIST_ELEMENT` pointed to by the native parameter `UnitList`.

9.9.5.4 The inbound value of `no_NewBSPHandle` shall be "`true`" if the native parameter `NewBSPHandle` is NULL; otherwise, it shall be "`false`".

9.9.5.5 The inbound value of `return` shall be the canonical representation of the integer returned by the native function.

9.9.5.6 The inbound values of the other input parameters shall be determined as specified in 9.9.4.

9.9.6 Bound activity invocation output

There are no output parameters.

9.10 BioAPI_BSPDetach

9.10.1 Function invocation scheme

This function belongs to the BioAPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioAPI_BSPDetach(

BioAPI_HANDLE BSPHandle);

and the following parameters (see Table 19).

Table 19

Parameter	Function invocation (conformance testing model for frameworks)	Bound activity invocation (conformance testing model for applications)
`BSPHandle`	input, outbound	input, inbound
`return`	return, inbound	input, inbound

9.10.2 Constraints on the parameters

9.10.2.1 An outbound value of `BSPHandle` shall be a valid representation of an integer (see 7.4) in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer (see 7.4.3) in the same range.

9.10.2.2 An outbound value of `return` shall be a valid representation of an integer in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer in the same range.

9.10.3 Function invocation input

The integer represented by the outbound value of `BSPHandle` shall be assigned to the native parameter with the same name.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.10.4 Function invocation output

There are no output parameters.

9.10.5 Bound activity invocation input

9.10.5.1 The inbound value of `BSPHandle` shall be the canonical representation of the integer in the native parameter with the same name.

9.10.5.2 The inbound value of `return` shall be the canonical representation of the integer returned by the native function.

9.10.6 Bound activity invocation output

There are no output parameters.

9.11 BioAPI_QueryUnits

9.11.1 Function invocation scheme

This function belongs to the BioAPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioAPI_QueryUnits(

const BioAPI_UUID *BSPUuid,

BioAPI_UNIT_SCHEMA **UnitSchemaArray,

uint32_t *NumberOfElements);

and the following parameters (see Table 20):

Table 20

Parameter	Function invocation (conformance testing model for frameworks)	Bound activity invocation (conformance testing model for applications)
`BSPUuid`	input, outbound	input, inbound
`no_UnitSchemaArray`	input, outbound	input, inbound
the members of the parameter group "Unit schema" (see 9.2.13) with their names prefixed by "`UnitSchema_1_`"	output, inbound	input, inbound
the members of the parameter group "Unit schema" with their names prefixed by "`UnitSchema_2_`"	output, inbound	input, inbound

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

Table 20 *(continued)*

Parameter	Function invocation (conformance testing model for frameworks)	Bound activity invocation (conformance testing model for applications)
the members of the parameter group "Unit schema" with their names prefixed by "`UnitSchema_3_`"	output, inbound	input, inbound
the members of the parameter group "Unit schema" with their names prefixed by "`UnitSchema_4_`"	output, inbound	input, inbound
`no_NumberOfElements`	input, outbound	input, inbound
`NumberOfElements`	output, inbound	input, inbound
`return`	return, inbound	input, inbound

9.11.2 Constraints on the parameters

9.11.2.1 An outbound value of `BSPUuid` shall be a valid representation of a UUID (see 7.6). An inbound value shall be the canonical representation of a UUID (see 7.6.3).

9.11.2.2 An outbound value of `no_UnitSchemaArray` and `no_NumberOfElements` shall be either a valid representation of a Boolean (see 7.5) or an empty string. An inbound value shall be the canonical representation of a Boolean (see 7.5.2).

9.11.2.3 An outbound value of each parameter group "Unit schema" shall be a valid representation of a value of the native type `BioAPI_UNIT_SCHEMA`. An inbound value shall be either the canonical representation of a value of that type, or a set of empty strings.

9.11.2.4 An outbound value of `NumberOfElements` shall be either a valid representation of an integer in the range 0 to 4294967295 or an empty string. An inbound value shall be either the canonical representation of an integer in the same range or an empty string.

9.11.2.5 An outbound value of `return` shall be a valid representation of an integer in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer in the same range.

9.11.3 Function invocation input

9.11.3.1 The UUID represented by the outbound value of `BSPUuid` shall be written to a variable of type `BioAPI_UUID`, whose address shall be assigned to the native parameter `BSPUuid`.

9.11.3.2 If the outbound value of `no_UnitSchemaArray` is "`true`", then the native parameter `UnitSchemaArray` shall be set to NULL; otherwise, it shall be set to the address of a variable of type `BioAPI_UNIT_SCHEMA*` (a pointer).

9.11.3.3 If the outbound value of `no_NumberOfElements` is "`true`", then the native parameter `NumberOfElements` shall be set to NULL; otherwise, it shall be set to the address of a variable of type `uint32_t`.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.11.4 Function invocation output

9.11.4.1 The inbound value of the parameter group "Unit schema" with the prefix "`UnitSchema_X_`" (with *X* = 1, 2, 3, or 4) shall be determined as follows. If the native parameter `UnitSchemaArray` is NULL or the variable pointed to by that native parameter is NULL or the native parameter `NumberOfElements` is NULL or the value of the integer variable pointed to by that native parameter is less than *X*, then the inbound value shall be a set of empty strings. Otherwise, the inbound value be shall the canonical representation (see 9.2.15.5) of the value of type `BioAPI_UNIT_SCHEMA` at position *X* in the array pointed to by the variable pointed to by the native parameter `UnitSchemaArray`.

9.11.4.2 The inbound value of `NumberOfElements` shall be determined as follows. If the native parameter with the same name is NULL, then the inbound value shall be an empty string. Otherwise, the inbound value shall be the canonical representation of the integer in the variable of type `uint32_t` pointed to by the native parameter `NumberOfElements`.

9.11.5 Bound activity invocation input

9.11.5.1 The inbound value of `BSPUuid` shall be the canonical representation of the UUID in the variable of type `BioAPI_UUID` pointed to by the native parameter `BSPUuid`.

9.11.5.2 The inbound value of `no_UnitSchemaArray` shall be "`true`" if the native parameter `UnitSchemaArray` is NULL; otherwise, it shall be "`false`".

9.11.5.3 The inbound value of `no_NumberOfElements` shall be "`true`" if the native parameter `NumberOfElements` is NULL; otherwise, it shall be "`false`".

9.11.5.4 The inbound value of `return` shall be the canonical representation of the integer returned by the native function.

9.11.5.5 The inbound values of the other input parameters shall be determined as specified in 9.11.4.

9.11.6 Bound activity invocation output

There are no output parameters.

9.12 BioAPI_EnumBFPs

9.12.1 Function invocation scheme

This function belongs to the BioAPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioAPI_EnumBFPs(

BioAPI_BFP_SCHEMA **BFPSchemaArray,

uint32_t *NumberOfElements);

and the following parameters (see Table 21).

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

 © ISO/IEC 2017 – All rights reserved

Table 21

Parameter	Function invocation (conformance testing model for frameworks)	Bound activity invocation (conformance testing model for applications)
`no_BFPSchemaArray`	input, outbound	input, inbound
the members of the parameter group "BFP schema" (see 9.2.12) with their names prefixed by "`BFPSchema_1_`"	output, inbound	input, inbound
the members of the parameter group "BFP schema" with their names prefixed by "`BFPSchema_2_`"	output, inbound	input, inbound
the members of the parameter group "BFP schema" with their names prefixed by "`BFPSchema_3_`"	output, inbound	input, inbound
the members of the parameter group "BFP schema" with their names prefixed by "`BFPSchema_4_`"	output, inbound	input, inbound
`no_NumberOfElements`	input, outbound	input, inbound
`NumberOfElements`	output, inbound	input, inbound
`return`	return, inbound	input, inbound

9.12.2 Constraints on the parameters

9.12.2.1 An outbound value of `no_BFPSchemaArray` and `no_NumberOfElements` shall be either a valid representation of a Boolean (see 7.5) or an empty string. An inbound value shall be the canonical representation of a Boolean (see 7.5.2).

9.12.2.2 An outbound value of each parameter group "BFP schema" shall be a valid representation of a value of the native type `BioAPI_BFP_SCHEMA`. An inbound value shall be either the canonical representation of a value of that type or a set of empty strings.

9.12.2.3 An outbound value of `NumberOfElements` shall be either a valid representation of an integer in the range 0 to 4294967295 or an empty string. An inbound value shall be either the canonical representation of an integer in the same range or an empty string.

9.12.2.4 An outbound value of `return` shall be a valid representation of an integer in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer in the same range.

9.12.3 Function invocation input

9.12.3.1 If the outbound value of `no_BFPSchemaArray` is "`true`", then the native parameter `BFPSchemaArray` shall be set to NULL; otherwise, it shall be set to the address of a variable of type `BioAPI_BFP_SCHEMA*` (a pointer).

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.12.3.2 If the outbound value of `no_NumberOfElements` is "`true`", then the native parameter `NumberOfElements` shall be set to NULL; otherwise, it shall be set to the address of a variable of type `uint32_t`.

9.12.4 Function invocation output

9.12.4.1 The inbound value of the parameter group "BFP schema" with the prefix "`BFPSchema_X_`" (with *X* = 1, 2, 3, or 4) shall be determined as follows. If the native parameter `BFPSchemaArray` is NULL or the variable pointed to by that native parameter is NULL or the native parameter `NumberOfElements` is NULL or the value of the integer variable pointed to that native parameter is less than *X*, then the inbound value shall be a set of empty strings. Otherwise, the inbound value shall be the canonical representation (see 9.2.12.5) of the value of type `BioAPI_BFP_SCHEMA` at position *X* in the array pointed to by the variable pointed to by the native parameter `BFPSchemaArray`.

9.12.4.2 The inbound value of `NumberOfElements` shall be determined as follows. If the native parameter with the same name is NULL, then the inbound value shall be an empty string. Otherwise, the inbound value shall be the canonical representation of the integer in the variable of type `uint32_t` pointed to by the native parameter `NumberOfElements`.

9.12.5 Bound activity invocation input

9.12.5.1 The inbound value of `no_BFPSchemaArray` shall be "`true`" if the native parameter `BFPSchemaArray` is NULL; otherwise, it shall be "`false`".

9.12.5.2 The inbound value of `no_NumberOfElements` shall be "`true`" if the native parameter `NumberOfElements` is NULL; otherwise, it shall be "`false`".

9.12.5.3 The inbound value of `return` shall be the canonical representation of the integer returned by the native function.

9.12.5.4 The inbound values of the other input parameters shall be determined as specified in 9.12.4.

9.12.6 Bound activity invocation output

There are no output parameters.

9.13 BioAPI_QueryBFPs

9.13.1 Function invocation scheme

This function belongs to the BioAPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioAPI_QueryBFPs(

const BioAPI_UUID *BSPUuid,

BioAPI_BFP_LIST_ELEMENT **BFPList,

uint32_t *NumberOfElements);

and the following parameters (see Table 22).

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

 © ISO/IEC 2017 – All rights reserved

Table 22

Parameter	Function invocation (conformance testing model for frameworks)	Bound activity invocation (conformance testing model for applications)
BSPHandle	input, outbound	input, inbound
no_BFPList	input, outbound	input, inbound
BFP_1_BFPCategory	output, inbound	input, inbound
BFP_1_BFPUuid	output, inbound	input, inbound
BFP_2_BFPCategory	output, inbound	input, inbound
BFP_2_BFPUuid	output, inbound	input, inbound
BFP_3_BFPCategory	output, inbound	input, inbound
BFP_3_BFPUuid	output, inbound	input, inbound
BFP_4_BFPCategory	output, inbound	input, inbound
BFP_4_BFPUuid	output, inbound	input, inbound
no_NumberOfElements	input, outbound	input, inbound
NumberOfElements	output, inbound	input, inbound
return	return, inbound	input, inbound

9.13.2 Constraints on the parameters

9.13.2.1 An outbound value of BSPHandle shall be a valid representation of an integer (see 7.4) in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer (see 7.4.3) in the same range.

9.13.2.2 An outbound value of no_BFPList and no_NumberOfElements shall be either a valid representation of a Boolean (see 7.5) or an empty string. An inbound value shall be the canonical representation of a Boolean (see 7.5.2).

9.13.2.3 An outbound value of NumberOfElements shall be either a valid representation of an integer in the range 0 to 4294967295 or an empty string. An inbound value shall be either the canonical representation of an integer in the same range or an empty string.

9.13.2.4 An outbound value of return shall be a valid representation of an integer in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer in the same range.

9.13.3 Function invocation input

9.13.3.1 The integer represented by the outbound value of BSPHandle shall be assigned to the native parameter with the same name.

9.13.3.2 If the outbound value of no_BFPList is "true", then the native parameter BFPList shall be set to NULL; otherwise, it shall be set to the address of a variable of type BioAPI_BFP_LIST_ELEMENT* (a pointer).

9.13.3.3 If the outbound value of no_NumberOfElements is "true", then the native parameter NumberOfElements shall be set to NULL; otherwise, it shall be set to the address of a variable of type uint32_t.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.13.4 Function invocation output

9.13.4.1 The inbound value of `BFP_X_BFPCategory` and `BFP_X_BFPUuid` (with *X* = 1, 2, 3, or 4) shall be determined as follows. If the native parameter `BFPList` is NULL or the variable pointed to by that native parameter is NULL or the native parameter `NumberOfElements` is NULL or the value of the integer variable pointed to by that native parameter is less than *X*, then the inbound value shall be an empty string. Otherwise, the inbound value shall be the canonical representation of the integer in the fields `BFPCategory` and `BFPUuid` (respectively) of the element at position *X* of the array of elements of type `BioAPI_BFP_LIST_ELEMENT` pointed to by the variable pointed to by the native parameter `BFPList`.

9.13.4.2 The inbound value of `NumberOfElements` shall be determined as follows. If the native parameter with the same name is NULL, then the inbound value shall be an empty string. Otherwise, the inbound value shall be the canonical representation of the integer in the variable of type `uint32_t` pointed to by the native parameter `NumberOfElements`.

9.13.5 Bound activity invocation input

9.13.4.1 The inbound value of `BSPHandle` shall be the canonical representation of the integer in the native parameter with the same name.

9.13.4.2 The inbound value of `no_BFPList` shall be "`true`" if the native parameter `BFPList` is NULL; otherwise, it shall be "`false`".

9.13.4.3 The inbound value of `no_NumberOfElements` shall be "`true`" if the native parameter `NumberOfElements` is NULL; otherwise, it shall be "`false`".

9.13.4.4 The inbound value of `return` shall be the canonical representation of the integer returned by the native function.

9.13.4.5 The inbound values of the other input parameters shall be determined as specified in 9.13.4.

9.13.6 Bound activity invocation output

There are no output parameters.

9.14 BioAPI_ControlUnit

9.14.1 Function invocation scheme

This function belongs to the BioAPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioAPI_ControlUnit(

BioAPI_HANDLE BSPHandle,

BioAPI_UNIT_ID UnitID,

uint32_t *ControlCode,

const BioAPI_DATA *InputData,

BioAPI_DATA *OutputData);

and the following parameters (see Table 23).

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

 © ISO/IEC 2017 – All rights reserved

Table 23

Parameter	Function invocation (conformance testing model for frameworks)	Bound activity invocation (conformance testing model for applications)
`BSPHandle`	input, outbound	input, inbound
`UnitID`	input, outbound	input, inbound
`ControlCode`	input, outbound	input, inbound
`InputData`	input, outbound	input, inbound
`no_OutputData`	input, outbound	input, inbound
`OutputData`	output, inbound	input, inbound
`return`	return, inbound	input, inbound

9.14.2 Constraints on the parameters

9.14.2.1 An outbound value of `BSPHandle`, `UnitID` and `ControlCode` shall be a valid representation of an integer (see 7.4) in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer (see 7.4.3) in the same range.

9.14.2.2 An outbound value of `InputData` and `OutputData` shall be a valid representation of an octet string (see 7.7). An inbound value shall be the canonical representation of an octet string (see 7.7.2).

9.14.2.3 An outbound value of `no_OutputData` shall be either a valid representation of a Boolean (see 7.5) or an empty string. An inbound value shall be the canonical representation of a Boolean (see 7.5.2).

9.14.2.4 An outbound value of `return` shall be a valid representation of an integer in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer in the same range.

9.14.3 Function invocation input

9.14.3.1 The integer represented by the outbound value of `BSPHandle`, `UnitID`, and `ControlCode` shall be assigned to the native parameter with the same name.

9.14.3.2 If the outbound value of `InputData` is an empty string, then the native parameter with the same name shall be set to NULL. Otherwise, the octet string represented by the outbound value shall be written to a memory block of sufficient size. The address and length of that memory block shall be written to the fields `Data` and `Length` (respectively) of a variable of type `BioAPI_DATA`, whose address shall be assigned to the native parameter `InputData`.

9.14.3.3 If the outbound value of `no_OutputData` is "`true`", then the native parameter `OutputData` shall be set to NULL; otherwise, it shall be set to the address of a variable of type `BioAPI_DATA`.

9.14.4 Function invocation output

The inbound value of `OutputData` shall be determined as follows. If the native parameter with the same name is NULL, then the inbound value shall be an empty string. Otherwise, the inbound value shall be the canonical representation of the octet string in the memory block, whose address and length are in the fields `Data` and `Length` (respectively) of the variable of type `BioAPI_DATA` pointed to by the native parameter `OutputData`.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.14.5 Bound activity invocation input

9.14.5.1 The inbound value of `BSPHandle`, `UnitID` and `ControlCode` shall be the canonical representation of the integer in the native parameter with the same name.

9.14.5.2 The inbound value of `InputData` shall be determined as follows. If the native parameter with the same name is NULL, then the inbound value shall be an empty string. Otherwise, the inbound value shall be the canonical representation (see 7.7.2) of the octet string in the memory block, whose address and length are in the fields `Data` and `Length` (respectively) of the variable of type `BioAPI_DATA` pointed to by the native parameter `InputData`

9.14.5.3 The inbound value of `no_OutputData` shall be "`true`" if the native parameter `OutputData` is NULL; otherwise it shall be "`false`".

9.14.5.4 The inbound value of `return` shall be the canonical representation of the integer returned by the native function.

9.14.5.5 The inbound values of the other input parameters shall be determined as specified in 9.14.4.

9.14.6 Bound activity invocation output

There are no output parameters.

9.15 BioAPI_LinkToEndpoint

9.15.1 Function invocation scheme

This function belongs to the BioAPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioAPI_LinkToEndpoint(

const unit8_t *SlaveEndpointIRI);

and the following parameter (see Table 24).

Table 24

Parameter	Function invocation (conformance testing model for frameworks)	Bound activity invocation (conformance testing model for applications)
`SlaveEndpointIRI`	input, outbound	input, inbound
`return`	return, inbound	input, inbound

9.15.2 Constraints on the parameter

9.15.2.1 An outbound value of `SlaveEndpointIRI` shall be a valid representation of an integer (see 7.4) in the range 0 to 255. An inbound value shall be the canonical representation of an integer (see 7.4.3) in the same range.

9.15.2.2 An outbound value of `return` shall be a valid representation of an integer in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer in the same range.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

 © ISO/IEC 2017 – All rights reserved

9.15.3 Function invocation input

The integer represented by the outbound value of `SlaveEndpointIRI` shall be assigned to the native parameter with the same name.

9.15.4 Function invocation output

There are no output parameters.

9.15.5 Bound activity invocation input

9.15.5.1 The inbound value of `SlaveEndpointIRI` shall be the canonical representation of the integer in the native parameter with the same name.

9.15.5.2 The inbound value of `return` shall be the canonical representation of the integer returned by the native function.

9.15.6 Bound activity invocation output

There are no output parameters.

9.16 BioAPI_UnlinkFromEndpoint

9.16.1 Function invocation scheme

This function belongs to the BioAPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioAPI_UnlinkFromEndpoint(

const unit8_t *SlaveEndpointIRI);

and the following parameter (see Table 25).

Table 25

Parameter	Function invocation (conformance testing model for frameworks)	Bound activity invocation (conformance testing model for applications)
`SlaveEndpointIRI`	input, outbound	input, inbound
`return`	return, inbound	input, inbound

9.16.2 Constraints on the parameter

9.16.2.1 An outbound value of `SlaveEndpointIRI` shall be a valid representation of an integer (see 7.4) in the range 0 to 255. An inbound value shall be the canonical representation of an integer (see 7.4.3) in the same range.

9.16.2.2 An outbound value of `return` shall be a valid representation of an integer in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer in the same range.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.16.3 Function invocation input

The integer represented by the outbound value of `SlaveEndpointIRI` shall be assigned to the native parameter with the same name.

9.16.4 Function invocation output

There are no output parameters.

9.16.5 Bound activity invocation input

9.16.5.1 The inbound value of `SlaveEndpointIRI` shall be the canonical representation of the integer in the native parameter with the same name.

9.16.5.2 The inbound value of `return` shall be the canonical representation of the integer returned by the native function.

9.16.6 Bound activity invocation output

There are no output parameters.

9.17 BioAPI_EnumFrameworks

9.17.1 Function invocation scheme

This function belongs to the BioAPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioAPI_EnumFrameworks(

BioAPI_FRAMEWORK_SCHEMA **FwSchemaArray,

uint32_t * NumberOfElements);

and the following parameters (see Table 26).

Table 26

Parameter	Function invocation (conformance testing model for frameworks)	Bound activity invocation (conformance testing model for applications)
`no_FwSchemaArray`	input, outbound	input, inbound
the members of the parameter group "Framework schema" (see 9.2.10)	output, inbound	input, inbound
`no_NumberOfElements`	input, outbound	input, inbound
`NumberOfElements`	output, outbound	input, inbound
`return`	return, inbound	input, inbound

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.17.2 Constraints on the parameters

9.17.2.1 An outbound value of `no_FrameworkSchema` and `no_NumberOfElements` shall be either a valid representation of a Boolean (see 7.5) or an empty string. An inbound value shall be the canonical representation of a Boolean (see 7.5.2).

9.17.2.2 An outbound value of the parameter group "Framework schema" shall be a valid representation of a value of the native type `BioAPI_FRAMEWORK_SCHEMA`. An inbound value shall be either the canonical representation of a value of that type or a set of empty strings.

9.17.2.3 An outbound value of `NumberOfElements` shall be a valid representation of an integer in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer in the same range.

9.17.3 Function invocation input

9.17.3.1 If the outbound value of `no_FrameworkSchema` is "`true`", then the native parameter `FrameworkSchema` shall be set to NULL; otherwise, it shall be set to the address of a variable of type `BioAPI_FRAMEWORK_SCHEMA`.

9.17.3.2 If the outbound value of `no_NumberOfElements` is "`true`", then the native parameter `NumberOfElements` shall be set to NULL; otherwise, it shall be set to the address of a variable of type `unit32_t`.

9.17.4 Function invocation output

9.17.4.1 The inbound value of the parameter group "Framework schema" shall be determined as follows. If the native parameter `FrameworkSchema` is NULL, then the inbound value shall be a set of empty strings. Otherwise, the inbound value shall be the canonical representation (see 9.2.10.5) of the value of type `BioAPI_FRAMEWORK_SCHEMA` pointed to by the native parameter `FrameworkSchema`.

9.17.4.2 The inbound value of `NumberOfElements` shall be determined as follows. If the native parameter with the same name is NULL, then the inbound value shall be an empty string. Otherwise, the inbound value shall be the canonical representation of the integer in the variable of type `uint32_t` pointed to by the native parameter `NumberOfElements`.

9.17.5 Bound activity invocation input

9.17.5.1 The inbound value of `no_FrameworkSchema` shall be "`true`" if the native parameter `FrameworkSchema` is NULL; otherwise, it shall be "`false`".

9.17.5.2 The inbound value of `no_NumberOfElements` shall be "`true`" if the native parameter `NumberOfElements` is NULL; otherwise, it shall be "`false`".

9.17.5.3 The inbound value of `return` shall be the canonical representation of the integer returned by the native function.

9.17.6 Bound activity invocation output

There are no output parameters.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.18 BioAPI_FreeBIRHandle

9.18.1 Function invocation scheme

This function belongs to the BioAPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioAPI_FreeBIRHandle(

BioAPI_HANDLE BSPHandle,

BioAPI_BIR_HANDLE Handle);

and the following parameters (see Table 27).

Table 27

Parameter	Function invocation (conformance testing model for frameworks)	Bound activity invocation (conformance testing model for applications)
`BSPHandle`	input, outbound	input, inbound
`Handle`	input, outbound	input, inbound
`return`	return, inbound	input, inbound

9.18.2 Constraints on the parameters

9.18.2.1 An outbound value of `BSPHandle` shall be a valid representation of an integer (see 7.4) in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer (see 7.4.3) in the same range.

9.18.2.2 An outbound value of `Handle` shall be a valid representation of an integer in the range −2147483648 to 2147483647. An inbound value shall be the canonical representation of an integer in the same range.

9.18.2.3 An outbound value of `return` shall be a valid representation of an integer in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer in the same range.

9.18.3 Function invocation input

The integer represented by the outbound value of `BSPHandle` and `Handle` shall be assigned to the native parameter with the same name.

9.18.4 Function invocation output

There are no output parameters.

9.18.5 Bound activity invocation input

9.18.5.1 The inbound value of `BSPHandle` and `Handle` shall be the canonical representation of the integer in the native parameter with the same name.

9.18.5.2 The inbound value of `return` shall be the canonical representation of the integer returned by the native function.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

 © ISO/IEC 2017 – All rights reserved

9.18.6 Bound activity invocation output

There are no output parameters.

9.19 BioAPI_GetBIRFromHandle

9.19.1 Function invocation scheme

This function belongs to the BioAPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioAPI_GetBIRFromHandle(

BioAPI_HANDLE BSPHandle,

BioAPI_BIR_HANDLE Handle,

BioAPI_BIR *BIR);

and the following parameters (see Table 28).

Table 28

Parameter	Function invocation (conformance testing model for frameworks)	Bound activity invocation (conformance testing model for applications)
`BSPHandle`	input, outbound	input, inbound
`Handle`	input, outbound	input, inbound
`no_BIR`	input, outbound	input, inbound
the members of the parameter group "BIR" (see 9.2.15)	output, inbound	input, inbound
`return`	return, inbound	input, inbound

9.19.2 Constraints on the parameters

9.19.2.1 An outbound value of `BSPHandle` shall be a valid representation of an integer (see 7.4) in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer (see 7.4.3) in the same range.

9.19.2.2 An outbound value of `Handle` shall be a valid representation of an integer in the range –2147483648 to 2147483647. An inbound value shall be the canonical representation of an integer in the same range.

9.19.2.3 An outbound value of `no_BIR` shall be either a valid representation of a Boolean (see 7.5) or an empty string. An inbound value shall be the canonical representation of a Boolean (see 7.5.2).

9.19.2.4 An outbound value of the parameter group "BIR" shall be a valid representation of a value of the native type `BioAPI_BIR`. An inbound value shall be either the canonical representation of a value of that type or a set of empty strings.

9.19.2.5 An outbound value of `return` shall be a valid representation of an integer in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer in the same range.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.19.3 Function invocation input

9.19.3.1 The integer represented by the outbound value of `BSPHandle` and `Handle` shall be assigned to the native parameter with the same name.

9.19.3.2 If the outbound value of `no_BIR` is "`true`", then the native parameter `BIR` shall be set to NULL; otherwise, it shall be set to the address of a variable of type `BioAPI_BIR`.

9.19.4 Function invocation output

The inbound value of the parameter group "BIR" shall be determined as follows. If the native parameter `BIR` is NULL, then the inbound value shall be a set of empty strings. Otherwise, the inbound value shall be the canonical representation (see 9.2.15.5) of the value of type `BioAPI_BIR` pointed to by the native parameter `BIR`.

9.19.5 Bound activity invocation input

9.19.5.1 The inbound value of `BSPHandle` and `Handle` shall be the canonical representation of the integer in the native parameter with the same name.

9.19.5.2 The inbound value of `no_BIR` shall be "`true`" if the native parameter `BIR` is NULL; otherwise, it shall be "`false`".

9.19.5.3 The inbound value of `return` shall be the canonical representation of the integer returned by the native function.

9.19.5.4 The inbound values of the other input parameters shall be determined as specified in 9.16.5.

9.19.6 Bound activity invocation output

There are no output parameters.

9.20 BioAPI_GetHeaderFromHandle

9.20.1 Function invocation scheme

This function belongs to the BioAPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioAPI_GetHeaderFromHandle(

BioAPI_HANDLE BSPHandle,

BioAPI_BIR_HANDLE Handle,

BioAPI_BIR_HEADER *Header);

and the following parameters (see Table 29).

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

Table 29

Parameter	Function invocation (conformance testing model for frameworks)	Bound activity invocation (conformance testing model for applications)
`BSPHandle`	input, outbound	input, inbound
`Handle`	input, outbound	input, inbound
`no_Header`	input, outbound	input, inbound
the members of the parameter group "BIR header" (see 9.2.14)	output, inbound	input, inbound
`return`	return, inbound	input, inbound

9.20.2 Constraints on the parameters

9.20.2.1 An outbound value of `BSPHandle` shall be a valid representation of an integer (see 7.4) in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer (see 7.4.3) in the same range.

9.20.2.2 An outbound value of `Handle` shall be a valid representation of an integer in the range −2147483648 to 2147483647. An inbound value shall be the canonical representation of an integer in the same range.

9.20.2.3 An outbound value of `no_Header` shall be either a valid representation of a Boolean (see 7.5) or an empty string. An inbound value shall be the canonical representation of a Boolean (see 7.5.2).

9.20.2.4 An outbound value of the parameter group "BIR header" shall be a valid representation of a value of the native type `BioAPI_BIR_HEADER`. An inbound value shall be either the canonical representation of a value of that type or a set of empty strings.

9.20.2.5 An outbound value of `return` shall be a valid representation of an integer in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer in the same range.

9.20.3 Function invocation input

9.20.3.1 The integer represented by the outbound value of `BSPHandle` and `Handle` shall be assigned to the native parameter with the same name.

9.20.3.2 If the outbound value of `no_Header` is "`true`", then the native parameter `Header` shall be set to NULL; otherwise, it shall be set to the address of a variable of type `BioAPI_BIR_HEADER`.

9.20.4 Function invocation output

The inbound value of the parameter group "BIR header" shall be determined as follows. If the native parameter `Header` is NULL, then the inbound value shall be a set of empty strings. Otherwise, the inbound value shall be the canonical representation (see 9.2.14.5) of the value of type `BioAPI_BIR_HEADER` pointed to by the native parameter `Header`.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.20.5 Bound activity invocation input

9.20.5.1 The inbound value of `BSPHandle` and `Handle` shall be the canonical representation of the integer in the native parameter with the same name.

9.20.5.2 The inbound value of `no_Header` shall be "`true`" if the native parameter `Header` is NULL; otherwise, it shall be "`false`".

9.20.5.3 The inbound value of `return` shall be the canonical representation of the integer returned by the native function.

9.20.5.4 The inbound values of the other input parameters shall be determined as specified in 9.17.5.

9.20.6 Bound activity invocation output

There are no output parameters.

9.21 BioAPI_EnableEvents

9.21.1 Function invocation scheme

This function belongs to the BioAPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioAPI_EnableEvents(

BioAPI_HANDLE BSPHandle,

BioAPI_EVENT_MASK Events);

and the following parameters (see Table 30).

Table 30

Parameter	Function invocation (conformance testing model for frameworks)	Bound activity invocation (conformance testing model for applications)
`BSPHandle`	input, outbound	input, inbound
the members of the parameter group "Events" (see 9.2.5)	input, outbound	input, inbound
`return`	return, inbound	input, inbound

9.21.2 Constraints on the parameters

9.21.2.1 An outbound value of `BSPHandle` shall be a valid representation of an integer (see 7.4) in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer (see 7.4.3) in the same range.

9.21.2.2 An outbound value of the parameter group "Events" shall be a valid representation of a value of the native type `BioAPI_EVENT_MASK`. An inbound value shall be the canonical representation of a value of that type.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.21.2.3 An outbound value of `return` shall be a valid representation of an integer in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer in the same range.

9.21.3 Function invocation input

9.21.3.1 The integer represented by the outbound value of `BSPHandle` shall be assigned to the native parameter with the same name.

9.21.3.2 The value of type `BioAPI_EVENT_MASK` represented (see 9.2.5.4) by the outbound value of the parameter group "Events" shall be assigned to the native parameter `Events`.

9.21.4 Function invocation output

There are no output parameters.

9.21.5 Bound activity invocation input

9.21.5.1 The inbound value of `BSPHandle` shall be the canonical representation of the integer in the nateive parameter with the same name.

9.21.5.2 The inbound value of the parameter group "Events" shall be the canonical representation (see 9.2.5.5) of the value of type `BioAPI_EVENT_MASK` in the native parameter `Events`.

9.21.5.3 The inbound value of `return` shall be the canonical representation of the integer returned by the native function.

9.21.6 Bound activity invocation output

There are no output parameters.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.22 BioAPI_NotifyGUIProgressEvent

9.22.1 Function invocation scheme

This function belongs to the BioAPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioAPI_NotifyGUIProgressEvent(

const uint8_t *SubscriberEndpointIRI,

const BioAPI_UUID *GUIEventSubscriptionUuid,

const BioAPI_UUID *BSPUuid,

BioAPI_UNIT_ID UnitID,

BioAPI_GUI_OPERATION Operation,

BioAPI_GUI_SUBOPERATION Suboperation,

BioAPI_BIR_PURPOSE Purpose,

BioAPI_GUI_MOMENT Moment,

uint8_t SuboperationProgress,

const BioAPI_GUI_IMAGE_DATA_ARRAY *Images,

const uint8_t *Text,

BioAPI_GUI_RESPONSE *Response

);

and the following parameters (see Table 31).

Table 31

Parameter	Function invocation (conformance testing model for frameworks)	Bound activity invocation (conformance testing model for applications)
SubscriberEndpointIRI	input, outbound	input, inbound
GUIEventSubscriptionUuid	input, outbound	input, inbound
BSPUuid	input, outbound	input, inbound
UnitID	input, outbound	input, inbound
Operation	input, outbound	input, inbound
Suboperation	input, outbound	input, inbound
Purpose	input, outbound	input, inbound
Moment	input, outbound	input, inbound
SuboperationProgress	input, outbound	input, inbound
Images	input, outbound	input, inbound

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

Table 31 *(continued)*

Parameter	Function invocation (conformance testing model for frameworks)	Bound activity invocation (conformance testing model for applications)
`Text`	input, outbound	input, inbound
`Response`	input, outbound	input, inbound
`return`	return, inbound	input, inbound

9.22.2 Constraints on the parameters

9.22.2.1 An outbound value of `SubcribeEndpointIRI`, `SuboperationProgress` and `Text` shall be a valid representation of an integer (see 7.4) in the range 0 to 255. An inbound value shall be the canonical representation of an integer (see 7.4.3) in the same range

9.22.2.2 An outbound value of `GUIEventSubscriptionUuid` and `BSPUuid` shall be a valid representation of a UUID (see 7.6). An inbound value shall be the canonical representation of a UUID (see 7.6.3)

9.22.2.3 An outbound value of `Operation`, `Suboperation`, `Purpose`, `Moment` and `Response` shall be a valid representation of an integer in the range 0 to 255. An inbound value shall be the canonical representation of an integer in the same range.

9.22.2.4 An outbound value of `UnitID` shall be a valid representation of an interger (see 7.4) in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer (see 7.4.3) in the same range.

9.22.2.5 An outbound value of `Images` shall be a valid representation of an octet string (see 7.7). An inbound value shall be the canonical representation of an octet string (see 7.7.2).

9.22.2.6 An outbound value of `return` shall be a valid representation of an integer in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer in the same range.

9.22.3 Function invocation input

9.22.3.1 The integer represented by the outbound value of `SubcribeEndpointIRI`, `SuboperationProgress` and `Text` shall be assigned to the native parameter with the same name

9.22.3.2 The UUID represented by the outbound value of `GUIEventSubscriptionUuid` and `BSPUuid` shall be written to a variable of type `BioAPI_UUID`, whose address shall be assigned to the native parameter `GUIEventSubscriptionUuid` and `BSPUuid`.

9.22.3.3 The integer represented by the outbound value of `Operation`, `Suboperation`, `Purpose`, `Moment` and `Response` shall be assigned to the native parameter with the same name.

9.22.3.4 The integer represented by the outbound value of `UnitID` shall be assigned to the native parameter with the same name.

9.22.4 Function invocation output

There are no output parameters.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.22.5 Bound activity invocation input

9.22.5.1 The inbound value of `SubcribeEndpointIRI`, `SuboperationProgress` and `Text` shall be the canonical representation of the integer in the native parameter with the same name.

9.22.5.2 The inbound value of `GUIEventSubscriptionUuid` and `BSPUuid` shall be the canonical representation of the UUID in the variable of type `BioAPI_UUID` pointed to by the native parameter of `GUIEventSubscriptionUuid` and `BSPUuid`.

9.22.5.3 The inbound value of `Operation`, `Suboperation`, `Purpose`, `Moment` and `Response` shall be the canonical representation of the integer in the native parameter with the same name.

9.22.5.4 The inbound value of `UnitID` shall be the canonical representation of the integer in the native parameter with the same name.

9.22.5.5 The inbound value of `ImageData` shall be determined as follows. If the native parameter `ImageData` is NULL, then the inbound value shall be an empty string. Otherwise, the inbound value shall be the canonical representation (see 7.7.2) of the octet string in the memory block, whose address and length are in the fields `Data` and `Length` (respectively) of the variable of type `BioAPI_DATA` pointed to by the field `ImageData` of the variable of type `BioAPI_GUI_IMAGE_DATA_ARRAY` pointed to by the native parameter `Images`.

9.22.5.6 The inbound value of `return` shall be the canonical representation of the integer returned by the native function.

9.22.6 Bound activity invocation output

There are no output parameters

9.23 BioAPI_NotifyGUISelectEvent

9.23.1 Function invocation scheme

This function belongs to the BioAPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioAPI_NotifyGUIEvent(

const uint8_t *SubscriberEndpointIRI,

const BioAPI_UUID *GUIEventSubscriptionUuid,

const BioAPI_UUID *BSPUuid,

BioAPI_UNIT_ID UnitID,

BioAPI_GUI_OPERATION Operation,

BioAPI_GUI_MOMENT Moment,

BioAPI_RETRURN ResultCode,

Int32_t MaxNumEnrollSamples,

BioAPI_BIR_SUBTYPE_MASK SelectableInstances,

BioAPI_BIR_SUBTYPE_MASK *SelectedInstances,

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

BioAPI_BIR_SUBTYPE_MASK CapturedInstances,

const uint8_t *Text,

BioAPI_GUI_RESPONSE *Response

);

and the following parameters (see Table 32).

Table 32

Parameter	Function invocation (conformance testing model for frameworks)	Bound activity invocation (conformance testing model for applications)
SubscriberEndpointIRI	input, outbound	input, inbound
GUIEventSubscriptionUuid	input, outbound	input, inbound
BSPUuid	input, outbound	input, inbound
UnitID	input, outbound	input, inbound
Operation	input, outbound	input, inbound
Moment	input, outbound	input, inbound
ResultCode	input, outbound	input, inbound
MaxNumEnrollSamples	input, outbound	input, inbound
SelectableInstances	input, outbound	input, inbound
SelectedInstances	input, outbound	input, inbound
CapturedInstances	input, outbound	input, inbound
Text	input, outbound	input, inbound
Response	input, outbound	input, inbound
return	return, inbound	input, inbound

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

9.23.2 Constraints on the parameters

9.23.2.1 An outbound value of SubcribeEndpointIRI and Text shall be a valid representation of an integer (see 7.4) in the range 0 to 255. An inbound value shall be the canonical representation of an integer (see 7.4.3) in the same range.

9.23.2.2 An outbound value of GUIEventSubscriptionUuid and BSPUuid shall be a valid representation of a UUID (see 7.6). An inbound value shall be the canonical representation of a UUID (see 7.6.3).

9.23.2.3 An outbound value of Operation, Moment, SelectableInstances, SelectedInstances, CapturedInstances and Response shall be a valid representation of an integer in the range 0 to 255. An inbound value shall be the canonical representation of an integer in the same range.

9.23.2.4 The outbound value of ResultCode shall be either a valid representation of a Boolean or an empty string. An inbound value shall be the canonical representation of a Boolean or an empty string.

9.23.2.5 An outbound value of MaxNumEnrollSamples shall be a valid representation of an integer in the range 2147483648 to 2147483647. An inbound value shall be the canonical representation of an integer in the same range.

© ISO/IEC 2017 – All rights reserved

9.23.2.6 An outbound value of `UnitID` shall be a valid representation of an interger (see 7.4) in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer (see 7.4.3) in the same range.

9.23.2.7 An outbound value of `return` shall be a valid representation of an integer in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer in the same range.

9.23.3 Function invocation input

9.23.3.1 The integer represented by the outbound value of `SubcribeEndpointIRI` and `Text` shall be assigned to the native parameter with the same name.

9.23.3.2 The UUID represented by the outbound value `GUIEventSubscriptionUuid` and `BSPUuid` shall be written to a variable of type `BioAPI_UUID`, whose address shall be assigned to the native parameter `GUIEventSubscriptionUuid` and `BSPUuid`.

9.23.3.3 The integer represented by the outbound value `Operation`, `Moment`, `SelectableInstances`, `SelectedInstances`, `CapturedInstances` and `Response` shall be assigned to the native parameter with the same name.

9.23.3.4 The outbound value of `ResultCode` is "`true`", then the native parameter `ResultCode` shall be set to NULL; otherwise, it shall be set to the address of a variable of type `BioAPI_RETURN`.

9.23.3.5 The integer represented by the outbound value of `UnitID` shall be assigned to the native parameter with the same name.

9.23.2.6 The integer represented by the outbound value of `MaxNumEnrollSamples` shall be assigned to the native parameter with the same name.

9.23.4 Function invocation output

There are no output parameters.

9.23.5 Bound activity invocation input

9.23.5.1 The inbound value of `SubcribeEndpointIRI` and `Text` shall be the canonical representation of the integer in the native parameter with the same name.

9.23.5.2 The inbound value of `GUIEventSubscriptionUuid` and `BSPUuid` shall be the canonical representation of the UUID in the variable of type `BioAPI_UUID` pointed to by the native parameter of `GUIEventSubscriptionUuid` and `BSPUuid`.

9.23.5.3 The inbound value of `Operation`, `Moment`, `SelectableInstances`, `SelectedInstances`, `CapturedInstances` and `Response` shall be the canonical representation of the integer in the native parameter with the same name.

9.23.5.4 The inbound value of `ResultCode` shall be "`true`" if the native parameter `ResultCode` is NULL; otherwise, it shall be "`false`".

9.23.5.5 The inbound value of `MaxNumEnrollSamples` shall be the canonical representation of the integer in the native parameter with the same name.

9.23.5.6 The inbound value of `UnitID` shall be the canonical representation of the integer in the native parameter with the same name.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

 © ISO/IEC 2017 – All rights reserved

9.23.5.7 The inbound value of `return` shall be the canonical representation of the integer returned by the native function.

9.23.6 Bound activity invocation output

There are no output parameters.

9.24 BioAPI_NotifyGUIStateEvent

9.24.1 Function invocation scheme

This function belongs to the BioAPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioAPI_NotifyGUIStateEvent(

const uint8_t *SubscriberEndpointIRI,

const BioAPI_UUID *GUIEventSubscriptionUuid,

const BioAPI_UUID *BSPUuid,

BioAPI_UNIT_ID UnitID,

BioAPI_GUI_OPERATION Operation,

BioAPI_GUI_SUBOPERATION Suboperation,

BioAPI_BIR_PURPOSE Purpose,

BioAPI_GUI_MOMENT Moment,

BioAPI_RETURN ResultCode,

int32_t EnrollSampleIndex,

const BioAPI_GUI_ IMAGE_DATA_ARRAY *Images,

const uint8_t *Text,

BioAPI_GUI_RESPONSE *Response,

int32_t *EnrollSampleIndexToRecapture);

and the following parameters (see Table 33).

Table 33

Parameter	Function invocation (conformance testing model for frameworks)	Bound activity invocation (conformance testing model for applications)
`SubscriberEndpointIRI`	input, outbound	input, inbound
`GUIEventSubscriptionUuid`	input, outbound	input, inbound
`BSPUuid`	input, outbound	input, inbound
`UnitID`	input, outbound	input, inbound
`Operation`	input, outbound	input, inbound

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

Table 33 *(continued)*

Parameter	Function invocation (conformance testing model for frameworks)	Bound activity invocation (conformance testing model for applications)
`Suboperation`	input, outbound	input, inbound
`Purpose`	input, outbound	input, inbound
`Moment`	input, outbound	input, inbound
`ResultCode`	input, outbound	input, inbound
`EnrollSampleIndex`	input, outbound	input, inbound
`Images`	input, outbound	input, inbound
`Text`	input, outbound	input, inbound
`Response`	input, outbound	input, inbound
`EnrollSampleIndexToRecapture`	input, outbound	input, inbound
`return`	return, inbound	input, inbound

9.24.2 Constraints on the parameters

9.24.2.1 An outbound value of `SubcribeEndpointIRI` and `Text` shall be a valid representation of an integer (see 7.4) in the range 0 to 255. An inbound value shall be the canonical representation of an integer (see 7.4.3) in the same range.

9.24.2.2 An outbound value of `GUIEventSubscriptionUuid` and `BSPUuid` shall be a valid representation of a UUID (see 7.6). An inbound value shall be the canonical representation of a UUID (see 7.6.3).

9.24.2.3 An outbound value of `UnitID` shall be a valid representation of an interger (see 7.4) in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer (see 7.4.3) in the same range.

9.24.2.4 An outbound value of `Operation`, `Suboperation`, `Purpose`, `Moment` and `Response` shall be a valid representation of an integer in the range 0 to 255. An inbound value shall be the canonical representation of an integer in the same range.

9.24.2.5 The outbound value of `ResultCode` shall be either a valid representation of a Boolean or an empty string. An inbound value shall be the canonical representation of a Boolean or an empty string.

9.24.2.6 An outbound value of `EnrollSampleIndex` and `EnrollSampleIndexToRecapture` shall be a valid representation of an integer in the range 2147483648 to 2147483647. An inbound value shall be the canonical representation of an integer in the same range.

9.24.2.7 An outbound value of `Images` shall be a valid representation of an octet string (see 7.7). An inbound value shall be the canonical representation of an octet string (see 7.7.2).

9.24.2.8 An outbound value of `return` shall be a valid representation of an integer in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer in the same range.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.24.3 Function invocation input

9.24.3.1 The integer represented by the outbound value of `SubcribeEndpointIRI` and `Text` shall be assigned to the native parameter with the same name.

9.24.3.2 The UUID represented by the outbound value `GUIEventSubscriptionUuid` and `BSPUuid` shall be written to a variable of type `BioAPI_UUID`, whose address shall be assigned to the native parameter `GUIEventSubscriptionUuid` and `BSPUuid`.

9.24.3.3 The integer represented by the outbound value `Operation`, `Suboperation`, `Purpose`, `Moment` and `Response` shall be assigned to the native parameter with the same name.

9.24.3.4 The outbound value of `ResultCode` is "`true`", then the native parameter `ResultCode` shall be set to NULL; otherwise, it shall be set to the address of a variable of type `BioAPI_RETURN`.

9.24.3.5 The integer represented by the outbound value of `UnitID` shall be assigned to the native parameter with the same name.

9.24.3.6 The integer represented by the outbound value of `EnrollSampleIndex` and `EnrollSampleIndexToRecapture` shall be assigned to the native parameter with the same name.

9.24.3.7 If the value of Images is an empty string, then the native parameter `Images` shall be set to NULL. Otherwise,

a) the integer represented by the outbound value of `Width` and `Height` (or zero if the outbound value is an empty string) shall be written to the fields `Width` and `Height` (respectively) of a variable of type `BioAPI_GUI_IMAGE_DATA_ARRAY`, whose address shall be assigned to the native parameter `Bitmaps`,

b) the octet string represented by the outbound value of `Images` shall be written to a memory block of sufficient size,

c) the address and length of that memory block shall be written to the fields `Data` and `Length` (respectively) of a variable of type `BioAPI_DATA`, and

d) the address of that variable shall be written to the field `ImageData` of the variable of type `BioAPI_GUI_IMAGE_DATA_ARRAY` specified in a).

9.24.4 Function invocation output

There are no output parameters.

9.24.5 Bound activity invocation input

9.24.5.1 The inbound value of `SubcribeEndpointIRI` and `Text` shall be the canonical representation of the integer in the native parameter with the same name.

9.24.5.2 The inbound value of `GUIEventSubscriptionUuid` and `BSPUuid` shall be the canonical representation of the UUID in the variable of type `BioAPI_UUID` pointed to by the native parameter of `GUIEventSubscriptionUuid` and `BSPUuid`.

9.24.5.3 The inbound value of `UnitID` shall be the canonical representation of the integer in the native parameter with the same name.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.24.5.4 The inbound value of `Operation`, `Suboperation`, `Purpose`, `Moment` and `Response` shall be the canonical representation of the integer in the native parameter with the same name.

9.24.5.5 The inbound value of `ResultCode` shall be "`true`" if the native parameter `ResultCode` is NULL; otherwise, it shall be "`false`".

9.24.5.6 The inbound value of `EnrollSampleIndex` and `EnrollSampleIndexToRecapture` shall be the canonical representation of the integer in the native parameter with the same name.

9.24.5.7 The inbound value of `Images` shall be determined as follows. If the native parameter with the same name is NULL, then the inbound value shall be an empty string. Otherwise, the inbound value shall be the canonical representation (see 7.7.2) of the octet string in the memory block, whose address and length are in the fields `Data` and `Length` (respectively) of the variable of type `BioAPI_DATA` pointed to by the field `Images` of the variable of type `BioAPI_GUI_IMAGE_DATA_ARRAY` pointed to by the native parameter `Images`.

9.24.5.8 The inbound value of `return` shall be the canonical representation of the integer returned by the native function.

9.24.6 Bound activity invocation output

The integer represented by the outbound value of `return` shall be returned by the native function.

9.25 BioAPI_QueryGUIEventSubscriptions

9.25.1 Function invocation scheme

This function belongs to the BioAPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioAPI_QueryGUIEventSubscriptions(

const BioAPI_UUID *BSPUuid,

BioAPI_GUI_EVENT_SUBSCRIPTION **GUIEventSubscriptionList,

uint32_t *NumberOfElements);

and the following parameters (see Table 34).

Table 34

Parameter	Function invocation (conformance testing model for frameworks)	Bound activity invocation (conformance testing model for applications)
`BSPUuid`	input, outbound	input, inbound
`GUIEventSubscriptionList`	output, outbound	input, inbound
`NumberOfElements`	output, outbound	input, inbound
`return`	return, inbound	output, outbound

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.25.2 Constraints on the parameters

9.25.2.1 An outbound value of `BSPUuid` shall be a valid representation of a UUID (see 7.6). An inbound value shall be the canonical representation of a UUID (see 7.6.3).

9.25.2.2 An outbound of each paramger group "`GUIEventSubscription`" shall be a valid representation value of the native type `BioAPI_GUI_EVENT_SUBSCRIPTION`. An inbound value shall be either the canonical representation a value of that type or a set of empty strings.

9.25.2.3 An outbound value `NumberOfElements` shall be a valid representation of an integer in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer in the same range.

9.25.3 Function invocation input

The UUID represented by the outbound value of `BSPUuid` shall be written to a variable of type `BioAPI_UUID`, whose address shall be assigned to the native parameter `BSPUuid`.

9.25.4 Function invocation output

9.25.4.1 The inbound value of the parameter group "`GUIEventSubscription`" shall be determined as follows. If the native parameter with the same name is NULL, then the inbound value shall be an empty string. Otherwise, the inbound value shall be the canonical representation of the value of type `BioAPI_GUI_EVENT_SUBSCRIPTION`.

9.25.4.2 The inbound value of `NumberOfElements` shall be determined as follows. If the native parameter with the same name is NULL, then the inbound value shall be an empty string. Otherwise, the inbound value shall be the canonical representation of the integer in the variable of type `uint32_t` pointed to by the native parameter `NumberOfElements`.

9.25.5 Bound activity invocation input

The inbound value of `BSPUuid` shall be the canonical representation of the UUID in the variable of type `BioAPI_UUID` pointed to by the native parameter `BSPUuid`.

9.25.6 Bound activity invocation output

9.25.6.1 The outbound value of the parameter group "`GUIEventSubscription`" shall be determined as follows. If the native parameter `GUIEventSubscriptionList` is NULL, then the outbound value shall be ignored. Otherwise, the value of type `BioAPI_GUI_EVENT_SUBSCRIPTION` represented by the outbound value of the parameter group shall be written to the array of elements of type `BioAPI_GUI_EVENT_SUBSCRIPTION` pointed to by the native parameter `GUIEventSubscriptionList`.

9.25.6.2 The outbound value of `NumberOfElements` shall be processed as follows. If the native parameter with the same name is NULL, then the outbound value shall be ignored. Otherwise, the integer represented by the outbound value shall be written to the variable of type `uint32_t` pointed to by the native parameter `NumberOfElements`.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.26 BioAPI_RedirectGUIEvents

9.26.1 Function invocation scheme

This function belongs to the BioAPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioAPI_RedirectGUIEvents(

const unit8_t *SubscriberEndpointIRI,

const BioAPI_UUID *GUIEventSubscriptionUuid,

BioAPI_HANDLE BSPHandle,

BioAPI_BOOL GUISelectEventRedirected,

BioAPI_BOOL GUIStateEventRedircted,

BioAPI_BOOL GUIProgressEventRedirected

);

and the following parameters (see Table 35).

Table 35

Parameter	Function invocation (conformance testing model for frameworks)	Bound activity invocation (conformance testing model for applications)
`SubscriberEndpointIRI`	input, outbound	input, inbound
`GUIEventSubscriptionUuid`	input, outbound	input, inbound
`BSPHandle`	input, outbound	input, inbound
`GUISelectEventRedirected`	input, outbound	input, inbound
`GUIStateEventRedircted`	input, outbound	input, inbound
`GUIProgressEventRedirected`	input, outbound	input, inbound
`return`	return, inbound	output, outbound

9.26.2 Constraints on the parameters

9.26.2.1 An outbound value of `SubcriberEndpointIRI` shall be a valid representation of an integer (see 7.4) in the range 0 to 255. An inbound value shall be the canonical representation of an integer (see 7.4.3) in the same range.

9.26.2.2 An outbound value of `GUIEventSubscriptionUuid` shall be a valid representation of a UUID (see 7.6). An inbound value shall be the canonical representation of a UUID (see 7.6.3).

9.26.2.3 An outbound value of `BSPHandle` shall be either a valid representation of an integer in the range 0 to 4294967295 or an empty string. An inbound value shall be either the canonical representation of an integer in the same range or an empty string.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.26.2.4 An outbound value of `GUISelectEventRedirected`, `GUIStateEventRedircted` and `GUIProgressEventRedirected` shall be a valid representation of a Boolean. An inbound value shall be the canonical representation of a Boolean.

9.26.3 Function invocation input

9.26.3.1 The integer represented by the outbound value of `SubcriberEndpointIRI` shall be assigned to the native parameter with the same name.

9.26.3.2 The UUID represented by the outbound value of `GUIEventSubscriptionUuid` shall be written to a variable of type `BioAPI_UUID`, whose address shall be assigned to the native parameter `GUIEventSubscriptionUuid`.

9.26.3.3 The integer represented by the outbound value of `BSPHandle` shall be assigned to the native parameter with the same name.

9.26.3.4 The Boolean represented by the outbound value of `GUISelectEventRedirected`, `GUIStateEventRedircted` and `GUIProgressEventRedirected` shall be assigned to the native parameter with the same name.

9.26.4 Function invocation output

There are no output parameters.

9.26.5 Bound activity invocation input

9.26.5.1 The inbound value of `SubcriberEndpointIRI` shall be the canonical representation of the integer in the native parameter with the same name.

9.26.5.2 The inbound value of `GUIEventSubscriptionUuid` shall be the canonical representation of the UUID in the variable of type `BioAPI_UUID` pointed to by the native parameter `GUIEventSubscriptionUuid`.

9.26.5.3 The inbound value of `BSPHandle` shall be the canonical representation of the integer in the native parameter with the same name.

9.26.5.4 The inbound value of `GUISelectEventRedirected`, `GUIStateEventRedircted` and `GUIProgressEventRedirected` shall be the canonical representation of the Boolean in the native parameter with the same name.

9.26.6 Bound activity invocation output

There are no output parameters.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.27 BioAPI_SubscribeToGUIEvents

9.27.1 Function invocation scheme

This function belongs to the BioAPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioAPI_SubscribeToGUIEvents (

const BioAPI_UUID *GUIEventSubscriptionUuid,

const BioAPI_UUID *BSPUuid,

const BioAPI_HANDLE *BSPHandle,

BioAPI_GUI_SELECT_EVENT_HANDLER GUISelectEventHandler,

const void *GUISelectEventHandlerCtx,

BioAPI_GUI_STATE_EVENT_HANDLER GUIStateEventHandler,

const void *GUIStateEventHandlerCtx,

BioAPI_GUI_PROGRESS_EVENT_HANDLER GUISelectEventHandler,

const void *GUIProgressEventHandlerCtx

);

and the following parameters (see Table 36).

Table 36

Parameter	Function invocation (conformance testing model for frameworks)	Bound activity invocation (conformance testing model for applications)
`GUIEventSubscriptionUuid`	input, outbound	input, inbound
`BSPUuid`	input, outbound	input, inbound
`BSPHandle`	input, outbound	input, inbound
`GUISelectEventHandler`	input, outbound	input, inbound
`GUISelectEventHandlerCtx`	input, outbound	input, inbound
`GUIStateEventHandler`	input, outbound	input, inbound
`GUIStateEventHandlerCtx`	input, outbound	input, inbound
`GUIProgressEventHandle`	input, outbound	input, inbound
`GUIProgressEventHandlerCtx`	input, outbound	input, inbound
`return`	return, inbound	output, outbound

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

9.27.2 Constraints on the parameters

9.27.2.1 An outbound value of `GUIEventSubscriptionUuid` and `BSPUuid` shall be a valid representation of a UUID (see 7.6). An inbound value shall be the canonical representation of a UUID (see 7.6.3).

© ISO/IEC 2017 – All rights reserved

9.27.2.2 An outbound value of `BSPHandle` shall be a valid representation of an integer (see 7.4) in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer (see 7.4.3) in the same range.

9.27.2.3 An outbound value of `GUISelectEventHandler`, `GUIStateEventHandler` and `GUIProgressEventHandler` shall be a valid representation of an integer in the range 0 to 255. An inbound value shall be the canonical representation of an integer in the same range.

9.27.2.4 An outbound value of `GUISelectEventHandlerCtx`, `GUIStateEventHandlerCtx` and `GUIProgressEventHandlerCtx` shall be either "`0`" or "`*`". An inbound value shall be the canonical representation of an integer (see 7.4.3) in the range 0 to 4294967295.

9.27.2.5 An outbound value of `return` shall be a valid representation of an integer in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer in the same range.

9.27.3 Function invocation input

9.27.3.1 An outbound value of `GUIEventSubscriptionUuid` and `BSPUuid` shall be a valid representation of a UUID (see 7.6). An inbound value shall be the canonical representation of a UUID (see 7.6.3).

9.27.3.2 The integer represented by the outbound value `BSPHandle` shall be assigned to the native parameter with the same name.

9.27.3.3 The integer represented by the outbound value of shall `GUISelectEventHandler` and `GUIProgressEventHandle` be assigned to the native parameter with the same name.

9.27.3.4 If the outbound values of `GUISelectEventHandlerCtx`, `GUIStateEventHandlerCtx` and `GUIProgressEventHandlerCtx` are "`0`", a NULL pointer value shall be assigned to the native parameter `GUISelectEventHandlerCtx`, `GUIStateEventHandlerCtx` and `GUIProgressEventHandlerCtx`. If it is "`*`", a non-NULL pointer value, which is the address of a variable of type `void*` set to NULL, shall be assigned to the native parameter `GUISelectEventHandlerCtx`, `GUIStateEventHandlerCtx` and `GUIProgressEventHandlerCtx`.

9.27.4 Function invocation output

There are no output parameters.

9.27.5 Bound activity invocation input

9.27.5.1 The inbound value of `GUIEventSubscriptionUuid` and `BSPUuid` shall be the canonical representation of the UUID in the variable of type `BioAPI_UUID` pointed to by the native parameter `GUIEventSubscriptionUuid` and `BSPUuid`.

9.27.5.2 The inbound value of `BSPHandle` shall be the canonical representation of the integer in the native parameter with the same name.

9.27.5.3 The inbound value of `GUISelectEventHandler` and `GUIProgressEventHandle` shall be the canonical representation of the integer in the native parameter with the same name.

9.27.5.4 The inbound value of `GUISelectEventHandlerCtx`, `GUIStateEventHandlerCtx` and `GUIProgressEventHandlerCtx` shall be the canonical representation of the integer in the native parameter with the same name.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.27.5.5 The inbound value of `return` shall be the canonical representation of the integer returned by the native function.

9.27.6 Bound activity invocation output

There are no output parameters.

9.28 BioAPI_UnredirctGUIEvents

9.28.1 Function invocation scheme

This function belongs to the BioAPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioAPI_UnredirectGUIEvents (

const uint8_t *SubscriberEndpointIRI

const BioAPI_UUID *GUIEventSubscriptionUuid,

BioAPI_HANDLE BSPHandle,

BioAPI_BOOL GUISelectEventRedirected,

BioAPI_BOOL GUIStateEventRedircted,

BioAPI_BOOL GUIProgressEventRedirected

);

and the following parameters (see Table 37).

Table 37

Parameter	Function invocation (conformance testing model for frameworks)	Bound activity invocation (conformance testing model for applications)
`SubscriberEndpointIRI`	input, outbound	input, inbound
`GUIEventSubscriptionUuid`	input, outbound	input, inbound
`BSPHandle`	input, outbound	input, inbound
`GUISelectEventRedirected`	input, outbound	input, inbound
`GUIStateEventRedirected`	input, outbound	input, inbound
`GUIProgressEventRedirected`	input, outbound	input, inbound
`return`	return, inbound	output, outbound

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

9.28.2 Constraints on the parameters

9.28.2.1 An outbound value of `SubcriberEndpointIRI` shall be a valid representation of an integer (see 7.4) in the range 0 to 255. An inbound value shall be the canonical representation of an integer (see 7.4.3) in the same range.

9.28.2.2 An outbound value of `GUIEventSubscriptionUuid` shall be a valid representation of a UUID (see 7.6). An inbound value shall be the canonical representation of a UUID (see 7.6.3).

© ISO/IEC 2017 – All rights reserved

9.28.2.3 An outbound value of `BSPHandle` shall be either a valid representation of an integer in the range 0 to 4294967295 or an empty string. An inbound value shall be either the canonical representation of an integer in the same range or an empty string.

9.28.2.4 An outbound value of `GUISelectEventRedirected`, `GUIStateEventRedirected` and `GUIProgressEventRedirected` shall be a valid representation of a Boolean. An inbound value shall be the canonical representation of a Boolean.

9.28.3 Function invocation input

9.28.3.1 The integer represented by the outbound value of `SubcriberEndpointIRI` shall be assigned to the native parameter with the same name.

9.28.3.2 The UUID represented by the outbound value of `GUIEventSubscriptionUuid` shall be written to a variable of type `BioAPI_UUID`, whose address shall be assigned to the native parameter `GUIEventSubscriptionUuid`.

9.28.3.3 The integer represented by the outbound value of `BSPHandle` shall be assigned to the native parameter with the same name.

9.28.3.4 The Boolean represented by the outbound value of `GUISelectEventRedirected`, `GUIStateEventRedirected` and `GUIProgressEventRedirected` shall be assigned to the native parameter with the same name.

9.28.4 Function invocation output

There are no output parameters.

9.28.5 Bound activity invocation input

9.28.5.1 The inbound value of `SubcriberEndpointIRI` shall be the canonical representation of the integer in the native parameter with the same name.

9.28.5.2 The inbound value of `GUIEventSubscriptionUuid` shall be the canonical representation of the UUID in the variable of type `BioAPI_UUID` pointed to by the native parameter `GUIEventSubscriptionUuid`.

9.28.5.3 The inbound value of `BSPHandle` shall be the canonical representation of the integer in the native parameter with the same name.

9.28.5.4 The inbound value of `GUISelectEventRedirected`, `GUIStateEventRedirected` and `GUIProgressEventRedirected` shall be the canonical representation of the Boolean in the native parameter with the same name.

9.28.6 Bound activity invocation output

There are no output parameters.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.29 BioAPI_UnsubscribeFromGUIEvents

9.29.1 Function invocation scheme

This function belongs to the BioAPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioAPI_UnsubscribeFromGUIEvents (

const BioAPI_UUID *GUIEventSubscriptionUUID,

const BioAPI_UUID *BSPUuid,

const BioAPI_HANDLE *BSPHandle,

BioAPI_GUI_SELECT_EVENT_HANDLER GUISelectEventHandler,

const void *GUISelectEventHandlerCtx,

BioAPI_GUI_STATE_EVENT_HANDLER GUIStateEventHandler,

const void *GUIStateEventHandlerCtx,

BioAPI_GUI_PROGRESS_EVENT_HANDLER GUIProgressEventHandler,

const void *GUIProgressEventHandlerCtx

);

and the following parameters (see Table 38).

Table 38

Parameter	Function invocation (conformance testing model for frameworks)	Bound activity invocation (conformance testing model for applications)
`GUIEventSubscriptionUUID`	input, outbound	input, inbound
`BSPUuid`	input, outbound	input, inbound
`BSPHandle`	input, outbound	input, inbound
`GUISelectEventHandler`	input, outbound	input, inbound
`GUISelectEventHandlerCtx`	input, outbound	input, inbound
`GUIStateEventHandler`	input, outbound	input, inbound
`GUIStateEventHandlerCtx`	input, outbound	input, inbound
`GUIProgressEventHandler`	input, outbound	input, inbound
`GUIProgressEventHandlerCtx`	input, outbound	input, inbound
`return`	return, inbound	output, outbound

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

9.29.2 Constraints on the parameters

9.29.2.1 An outbound value of `GUIEventSubscriptionUUID` and `BSPUuid` shall be a valid representation of a UUID (see 7.6). An inbound value shall be the canonical representation of a UUID (see 7.6.3).

© ISO/IEC 2017 – All rights reserved

9.29.2.2 An outbound value of `BSPHandle` shall be either a valid representation of an integer in the range 0 to 4294967295 or an empty string. An inbound value shall be either the canonical representation of an integer in the same range or an empty string.

9.29.2.3 An outbound value of `GUISelectEventHandler`, `GUIStateEventHandler` and `GUIProgressEventHandler` shall be a valid representation of an integer in the range 0 to 255. An inbound value shall be the canonical representation of an integer in the same range.

9.29.2.4 An outbound value of `GUISelectEventHandlerCtx`, `GUIStateEventHandlerCtx` and `GUIProgressEventHandlerCtx` shall be either "`0`" or "`*`". An inbound value shall be the canonical representation of an integer (see 7.4.3) in the range 0 to 4294967295.

9.29.3 Function invocation input

9.29.3.1 The UUID represented by the outbound value of `GUIEventSubscriptionUUID` and `BSPUuid` shall be written to a variable of type `BioAPI_UUID`, whose address shall be assigned to the native parameter `GUIEventSubscriptionUUID` and `BSPUuid`.

9.29.3.2 The integer represented by the outbound value of `BSPHandle` shall be assigned to the native parameter with the same name.

9.29.3.3 The Boolean represented by the outbound value of `GUISelectEventHandler`, `GUIStateEventHandler` and `GUIProgressEventHandler` shall be assigned to the native parameter with the same name.

9.29.3.4 An outbound value of `GUISelectEventHandlerCtx`, `GUIStateEventHandlerCtx` and `GUIProgressEventHandlerCtx` shall be either "`0`" or "`*`". An inbound value shall be the canonical representation of an integer (see 7.4.3) in the range 0 to 4294967295.

9.29.4 Function invocation output

There are no output parameters.

9.29.5 Bound activity invocation input

9.29.5.1 The inbound value of `GUIEventSubscriptionUUID` and `BSPUuid` shall be the canonical representation of the UUID in the variable of type `BioAPI_UUID` pointed to by the native parameter `GUIEventSubscriptionUuid` and `BSPUuid`.

9.29.5.2 The inbound value of `BSPHandle` shall be the canonical representation of the integer in the native parameter with the same name.

9.29.5.3 The inbound value of `GUISelectEventHandler`, `GUIStateEventHandler` and `GUIProgressEventHandler` shall be the canonical representation of the Boolean in the native parameter with the same name.

9.29.5.4 The inbound value of `GUISelectEventHandlerCtx`, `GUIStateEventHandlerCtx` and `GUIProgressEventHandlerCtx` shall be the canonical representation of the integer in the native parameter with the same name.

9.29.6 Bound activity invocation output

There are no output parameters.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.30 BioAPI_SetGUICallbacks

9.30.1 Function invocation scheme

This function belongs to the BioAPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioAPI_SetGUICallbacks(

BioAPI_HANDLE BSPHandle,

BioAPI_GUI_STREAMING_CALLBACK GuiStreamingCallback,

void *GuiStreamingCallbackCtx,

BioAPI_GUI_STATE_CALLBACK GuiStateCallback,

void *GuiStateCallbackCtx);

and the following parameters (see Table 39).

Table 39

Parameter	Function invocation (conformance testing model for frameworks)	Bound activity invocation (conformance testing model for applications)
`BSPHandle`	input, outbound	input, inbound
`GuiStreamingCallback`	input, outbound	input, inbound
`GuiStreamingCallbackCtx`	input, outbound	input, inbound
`GuiStateCallback`	input, outbound	input, inbound
`GuiStateCallbackCtx`	input, outbound	input, inbound
`return`	return, inbound	input, inbound

9.30.2 Constraints on the parameters

9.30.2.1 An outbound value of `BSPHandle` shall be a valid representation of an integer (see 7.4) in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer (see 7.4.3) in the same range.

9.30.2.2 An outbound value of `GuiStreamingCallback`, `GuiStreamingCallbackCtx`, `GuiStateCallback`, and `GuiStateCallbackCtx` shall be either "`0`" or "`*`". An inbound value shall be the canonical representation of an integer in the range 0 to 4294967295.

9.30.2.3 An outbound value of `return` shall be a valid representation of an integer in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer in the same range.

9.30.3 Function invocation input

9.30.3.1 The integer represented by the outbound value of `BSPHandle` shall be assigned to the native parameter with the same name.

9.30.3.2 If the outbound value of `GuiStreamingCallback` is "`0`", a NULL pointer value shall be assigned to the native parameter `GuiStreamingCallback`. If it is "`*`", a non-NULL pointer value, which

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

 © ISO/IEC 2017 – All rights reserved

is the address of a native function (within the testing component) implementing the standard BioAPI interface function `BioSPI_GUI_STREAMING_CALLBACK`, shall be assigned to the native parameter `GuiStreamingCallback`.

NOTE If the outbound value of `GuiStreamingCallback` is not "`0`", any subsequent incoming calls to the standard BioAPI interface function `BioSPI_GUI_STREAMING_CALLBACK` will result in an invocation of the activity bound to this function, if such a binding exists.

9.30.3.3 If the outbound value of `GuiStreamingCallbackCtx` is "`0`", a NULL pointer value shall be assigned to the native parameter `GuiStreamingCallbackCtx`. If it is "`*`", a non-NULL pointer value, which is the address of a variable of type `void*` set to NULL, shall be assigned to the native parameter `GuiStreamingCallbackCtx`.

9.30.3.4 If the outbound value of `GuiStateCallback` is "`0`", a NULL pointer value shall be assigned to the native parameter `GuiStateCallback`. If it is "`*`", a non-NULL pointer value, which is the address of a native function (within the testing component) implementing the standard BioAPI interface function `BioSPI_GUI_STATE_CALLBACK`, shall be assigned to the native parameter `GuiStateCallback`.

NOTE If the outbound value of `GuiStateCallback` is not "`0`", any subsequent incoming calls to the standard BioAPI interface function `BioSPI_GUI_STATE_CALLBACK` will result in an invocation of the activity bound to this function, if such a binding exists.

9.30.3.5 If the outbound value of `GuiStateCallbackCtx` is "`0`", a NULL pointer value shall be assigned to the native parameter `GuiStateCallbackCtx`. If it is "`*`", a non-NULL pointer value, which is the address of a variable of type `void*` set to NULL, shall be assigned to the native parameter `GuiStateCallbackCtx`.

9.30.4 Function invocation output

There are no output parameters.

9.30.5 Bound activity invocation input

9.30.5.1 The inbound value of `BSPHandle` shall be the canonical representation of the integer in the native parameter with the same name.

9.30.5.2 The inbound value of `GuiStreamingCallback`, `GuiStreamingCallbackCtx`, `GuiStateCallback`, and `GuiStateCallbackCtx` shall be the canonical representation of the integer in the native parameter with the same name.

9.30.5.3 The inbound value of `return` shall be the canonical representation of the integer returned by the native function.

9.30.6 Bound activity invocation output

There are no output parameters.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.31 BioAPI_Capture

9.31.1 Function invocation scheme

This function belongs to the BioAPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioAPI_Capture(

BioAPI_HANDLE BSPHandle,

BioAPI_BIR_PURPOSE Purpose,

BioAPI_BIR_SUBTYPE Subtype,

const BioAPI_BIR_BIOMETRIC_DATA_FORMAT *OutputFormat,

BioAPI_BIR_HANDLE *CapturedBIR,

int32_t Timeout,

BioAPI_BIR_HANDLE *AuditData);

and the following parameters (see Table 40).

Table 40

Parameter	Function invocation (conformance testing model for frameworks)	Bound activity invocation (conformance testing model for applications)
`BSPHandle`	input, outbound	input, inbound
`Purpose`	input, outbound	input, inbound
`Subtype`	input, outbound	input, inbound
`OutputFormatOwner`	input, outbound	input, inbound
`OutputFormatType`	input, outbound	input, inbound
`no_CapturedBIR`	input,outbound	input, inbound
`Timeout`	input, outbound	input, inbound
`no_AuditData`	input, outbound	input, inbound
`CapturedBIR`	output,inbound	input,inbound
`AuditData`	output, inbound	input, inbound
`return`	return, inbound	input, inbound

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

9.31.2 Constraints on the parameters

9.31.2.1 An outbound value of `BSPHandle` shall be a valid representation of an integer (see 7.4) in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer (see 7.4.3) in the same range.

9.31.2.2 An outbound value of `Purpose` and `Subtype` shall be a valid representation of an integer in the range 0 to 255. An inbound value shall be the canonical representation of an integer in the same range.

© ISO/IEC 2017 – All rights reserved

9.31.2.3 An outbound value of `OutputFormatOwner` and `OutputFormatType` shall be a valid representation of an integer in the range 0 to 65535. An inbound value shall be the canonical representation of an integer in the same range.

9.31.2.4 An outbound value of `no_CapturedBIR` and `no_AuditData` shall be either a valid representation of a Boolean (see 7.5) or an empty string. An inbound value shall be the canonical representation of a Boolean (see 7.5.2).

9.31.2.5 An outbound value of `Timeout` shall be a valid representation of an integer in the range −2147483648 to 2147483647. An inbound value shall be the canonical representation of an integer in the same range.

9.31.2.6 An outbound value of `CapturedBIR` and `AuditData` shall be a valid representation of an integer in the range −2147483648 to 2147483647 or an empty string. An inbound value shall be the canonical representation of an integer in the same range or an empty string.

9.31.2.7 An outbound value of `return` shall be a valid representation of an integer in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer in the same range.

9.31.3 Function invocation input

9.31.3.1 The integer represented by the outbound value of `BSPHandle`, `Purpose`, `Subtype`, and `Timeout` shall be assigned to the native parameter with the same name.

9.31.3.2 The integer represented by the outbound value of `OutputFormatOwner` and `OutputFormatType` shall be written to the fields `FormatOwner` and `FormatType` (respectively) of a variable of type `BioAPI_BIR_BIOMETRIC_DATA_FORMAT`, whose address shall be assigned to the native parameter `OutputFormat`.

9.31.3.3 If the outbound value of `no_CapturedBIR` is "`true`", then the native parameter `CapturedBIR` shall be set to NULL; otherwise, it shall be set to the address of a variable of type `BioAPI_BIR_HANDLE`.

9.31.3.4 If the outbound value of `no_AuditData` is "`true`", then the native parameter `AuditData` shall be set to NULL; otherwise, it shall be set to the address of a variable of type `BioAPI_BIR_HANDLE`.

9.31.4 Function invocation output

9.31.4.1 The inbound value of `CapturedBIR` shall be determined as follows. If the native parameter with the same name is NULL, then the inbound value shall be an empty string. Otherwise, the inbound value shall be the canonical representation of the integer in the variable of type `BioAPI_BIR_HANDLE` pointed to by the native parameter `CapturedBIR`.

9.31.4.2 The inbound value of `AuditData` shall be determined as follows. If the native parameter with the same name is NULL, then the inbound value shall be an empty string. Otherwise, the inbound value shall be the canonical representation of the integer in the variable of type `BioAPI_BIR_HANDLE` pointed to by the native parameter `AuditData`.

9.31.5 Bound activity invocation input

9.31.5.1 The inbound value of `BSPHandle`, `Purpose`, `Subtype`, and `Timeout` shall be the canonical representation of the integer in the native parameter with the same name.

9.31.5.2 The inbound value of `OutputFormatOwner` and `OutputFormatType` shall be the canonical representation of the integer in the fields `FormatOwner` and `FormatType` (respectively)

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

of the variable of type `BioAPI_BIR_BIOMETRIC_DATA_FORMAT` pointed to by the native parameter `OutputFormat`.

9.31.5.3 The inbound value of `no_CapturedBIR` shall be "`true`" if the native parameter `CapturedBIR` is NULL; otherwise, it shall be "`false`".

9.31.5.4 The inbound value of `no_AuditData` shall be "`true`" if the native parameter `AuditData` is NULL; otherwise, it shall be "`false`".

9.31.5.5 The inbound value of `return` shall be the canonical representation of the integer returned by the native function.

9.31.5.6 The inbound values of the other input parameters shall be determined as specified in 9.20.4.

9.31.6 Bound activity invocation output

There are no output parameters.

9.32 BioAPI_CreateTemplate

9.32.1 Function invocation scheme

This function belongs to the BioAPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioAPI_CreateTemplate(

BioAPI_HANDLE BSPHandle,

const BioAPI_INPUT_BIR *CapturedBIR,

const BioAPI_INPUT_BIR *ReferenceTemplate,

const BioAPI_BIR_BIOMETRIC_DATA_FORMAT *OutputFormat,

BioAPI_BIR_HANDLE *NewTemplate,

Const BioAPI_DATA *Payload,

BioAPI_UUID *TemplateUUID);

and the following parameters (see Table 41).

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

Table 41

Parameter	Function invocation (conformance testing model for frameworks)	Bound activity invocation (conformance testing model for applications)
`BSPHandle`	input, outbound	input, inbound
the members of the parameter group "Input BIR" (see 9.2.16) with their names prefixed by "`CapturedBIR_`"	input, outbound	input, inbound
the members of the parameter group "Input BIR" with their names prefixed by "`ReferenceTemplate_`"	input, outbound	input, inbound
`OutputFormatOwner`	input, outbound	input, inbound
`OutputFormatType`	input, outbound	input, inbound
`no_NewTemplate`	input, outbound	input, inbound
`Payload`	input, outbound	input, inbound
`no_TemplateUUID`	input, outbound	input, inbound
`NewTemplate`	output, inbound	input, inbound
`TemplateUUID`	output, inbound	input, inbound
`Return`	return, inbound	input, inbound

9.32.2 Constraints on the parameters

9.32.2.1 An outbound value of `BSPHandle` shall be a valid representation of an integer (see 7.4) in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer (see 7.4.3) in the same range.

9.32.2.2 An outbound value of each parameter group "Input BIR" shall be a valid representation of a value of the native type `BioAPI_INPUT_BIR`. An inbound value shall be the canonical representation of a value of that type.

9.32.2.3 An outbound value of `OutputFormatOwner` and `OutputFormatType` shall be a valid representation of an integer in the range 0 to 65535. An inbound value shall be the canonical representation of an integer in the same range.

9.32.2.4 An outbound value of `no_NewTemplate` and `no_TemplateUUID` shall be either a valid representation of a Boolean (see 7.5) or an empty string. An inbound value shall be the canonical representation of a Boolean (see 7.5.2).

9.32.2.5 An outbound value of `Payload` shall be a valid representation of an octet string (see 7.7). An inbound value shall be the canonical representation of an octet string (see 7.7.2).

9.32.2.6 An outbound value of `NewTemplate` shall be either a valid representation of an integer in the range −2147483648 to 2147483647 or an empty string. An inbound value shall be either the canonical representation of an integer in the same range or an empty string.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.32.2.7 An outbound value of `TemplateUUID` shall be either a valid representation of a UUID (see 7.6) or an empty string. An inbound value shall be either the canonical representation of a UUID (see 7.6.3) or an empty string.

9.32.2.8 An outbound value of `return` shall be a valid representation of an integer in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer in the same range.

9.32.3 Function invocation input

9.32.3.1 The integer represented by the outbound value of `BSPHandle` shall be assigned to the native parameter with the same name.

9.32.3.2 The value of type `BioAPI_INPUT_BIR` represented (see 9.2.16.4) by the outbound value of the parameter group "Input BIR" with the prefix "`CapturedBIR_`" shall be written to a variable of type `BioAPI_INPUT_BIR`, whose address shall be assigned to the native parameter `CapturedBIR`.

9.32.3.3 The value of type `BioAPI_INPUT_BIR` represented (see 9.2.16.4) by the outbound value of the parameter group "Input BIR" with the prefix "`ReferenceTemplate_`" shall be written to a variable of type `BioAPI_INPUT_BIR`, whose address shall be assigned to the native parameter `ReferenceTemplate`.

9.32.3.4 The integer represented by the outbound value of `OutputFormatOwner` and `OutputFormatType` shall be written to the fields `FormatOwner` and `FormatType` (respectively) of a variable of type `BioAPI_BIR_BIOMETRIC_DATA_FORMAT`, whose address shall be assigned to the native parameter `OutputFormat`.

9.32.3.5 If the outbound value of `no_NewTemplate` is "`true`", then the native parameter `NewTemplate` shall be set to NULL. Otherwise, it shall be set to the address of a variable of type `BioAPI_BIR_HANDLE`.

9.32.3.6 If the outbound value of `Payload` is an empty string, then the native parameter `Payload` shall be set to NULL. Otherwise, the octet string represented by the outbound value shall be written to a memory block of sufficient size. The address and length of that memory block shall be written to the fields `Data` and `Length` (respectively) of a variable of type `BioAPI_DATA`, whose address shall be assigned to the native parameter `Payload`.

9.32.3.7 If the outbound value of `no_TemplateUUID` is "`true`", then the native parameter `TemplateUUID` shall be set to NULL; otherwise, it shall be set to the address of a variable of type `BioAPI_UUID`.

9.32.4 Function invocation output

9.32.4.1 The inbound value of `NewTemplate` shall be determined as follows. If the native parameter with the same name is NULL, then the inbound value shall be an empty string. Otherwise, the inbound value shall be the canonical representation of the integer in the variable of type `BioAPI_BIR_HANDLE` pointed to by the native parameter `NewTemplate`.

9.32.4.2 The inbound value of `TemplateUUID` shall be determined as follows. If the native parameter with the same name is NULL, then the inbound value shall be an empty string. Otherwise, the inbound value shall be the canonical representation of the UUID in the variable of type `BioAPI_UUID` pointed to by the native parameter `TemplateUUID`.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.32.5 Bound activity invocation input

9.32.5.1 The inbound value of `BSPHandle` shall be the canonical representation of the integer in the native parameter with the same name.

9.32.5.2 The inbound value of the parameter group "Input BIR" with the prefix "`CapturedBIR_`" shall be the canonical representation (see 9.2.16.5) of the value of type `BioAPI_INPUT_BIR` in the variable pointed to by the native parameter `CapturedBIR`.

9.32.5.3 The inbound value of the parameter group "Input BIR" with the prefix "`ReferenceTemplate_`" shall be the canonical representation (see 9.2.16.5) of the value of type `BioAPI_INPUT_BIR` in the variable pointed to by the native parameter `ReferenceTemplate`.

9.32.5.4 The inbound value of `OutputFormatOwner` and `OutputFormatType` shall be the canonical representation of the integer in the fields `FormatOwner` and `FormatType` (respectively) of the variable of type `BioAPI_BIR_BIOMETRIC_DATA_FORMAT` pointed to by the native parameter `OutputFormat`.

9.32.5.5 The inbound value of `no_NewTemplate` shall be "`true`" if the native parameter `NewTemplate` is NULL; otherwise, it shall be "`false`".

9.32.5.6 The inbound value of `Payload` shall be determined as follows. If the native parameter with the same name is NULL, then the inbound value shall be an empty string. Otherwise, the inbound value shall be the canonical representation (see 7.7.2) of the octet string in the memory block, whose address and length are in the fields `Data` and `Length` (respectively) of the variable of type `BioAPI_DATA` pointed to by the native parameter `Payload`.

9.32.5.7 The inbound value of `no_TemplateUUID` shall be "`true`" if the native parameter `TemplateUUID` is NULL; otherwise, it shall be "`false`".

9.32.5.8 The inbound value of `return` shall be the canonical representation of the integer returned by the native function.

9.32.5.9 The inbound values of the other input parameters shall be determined as specified in 9.21.5.

9.32.6 Bound activity invocation output

There are no output parameters.

9.33 BioAPI_Process

9.33.1 Function invocation scheme

This function belongs to the BioAPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioAPI_Process(

BioAPI_HANDLE BSPHandle,

const BioAPI_INPUT_BIR *CapturedBIR,

const BioAPI_BIR_BIOMETRIC_DATA_FORMAT *OutputFormat,

BioAPI_BIR_HANDLE *ProcessedBIR);

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

and the following parameters (see Table 42).

Table 42

Parameter	Function invocation (conformance testing model for frameworks)	Bound activity invocation (conformance testing model for applications)
`BSPHandle`	input, outbound	input, inbound
the members of the parameter group "Input BIR" (see 9.2.16) with their names prefixed by "`CapturedBIR_`"	input, outbound	input, inbound
`OutputFormatOwner`	input, outbound	input, inbound
`OutputFormatType`	input, outbound	input, inbound
`no_ProcessedBIR`	input, outbound	input, inbound
`ProcessedBIR`	output, inbound	input, inbound
`return`	return, inbound	input, inbound

9.33.2 Constraints on the parameters

9.33.2.1 An outbound value of `BSPHandle` shall be a valid representation of an integer (see 7.4) in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer (see 7.4.3) in the same range.

9.33.2.2 An outbound value of the parameter group "Input BIR" shall be a valid representation of a value of the native type `BioAPI_INPUT_BIR`. An inbound value shall be the canonical representation of a value of that type.

9.33.2.3 An outbound value of `OutputFormatOwner` and `OutputFormatType` shall be a valid representation of an integer in the range 0 to 65535. An inbound value shall be the canonical representation of an integer in the same range.

9.33.2.4 An outbound value of `no_ProcessedBIR` shall be either a valid representation of a Boolean (see 7.5) or an empty string. An inbound value shall be the canonical representation of a Boolean (see 7.5.2).

9.33.2.5 An outbound value of `ProcessedBIR` shall be either a valid representation of an integer in the range −2147483648 to 2147483647 or an empty string. An inbound value shall be either the canonical representation of an integer in the same range or an empty string.

9.33.2.6 An outbound value of `return` shall be a valid representation of an integer in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer in the same range.

9.33.3 Function invocation input

9.33.3.1 The integer represented by the outbound value of `BSPHandle` shall be assigned to the native parameter with the same name.

9.33.3.2 The value of type `BioAPI_INPUT_BIR` represented (see 9.2.16.4) by the outbound value of the parameter group "Input BIR" shall be written to a variable of type `BioAPI_INPUT_BIR`, whose address shall be assigned to the native parameter `CapturedBIR`.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

 © ISO/IEC 2017 – All rights reserved

9.33.3.3 The integer represented by the outbound value of `OutputFormatOwner` and `OutputFormatType` shall be written to the fields `FormatOwner` and `FormatType` (respectively) of a variable of type `BioAPI_BIR_BIOMETRIC_DATA_FORMAT`, whose address shall be assigned to the native parameter `OutputFormat`.

9.33.3.4 If the outbound value of `no_ProcessedBIR` is "`true`", then the native parameter `ProcessedBIR` shall be set to NULL; otherwise, it shall be set to the address of a variable of type `BioAPI_BIR_HANDLE`.

9.33.4 Function invocation output

The inbound value of `ProcessedBIR` shall be determined as follows. If the native parameter with the same name is NULL, then the inbound value shall be an empty string. Otherwise, the inbound value shall be the canonical representation of the integer in the variable of type `BioAPI_BIR_HANDLE` pointed to by the native parameter `ProcessedBIR`.

9.33.5 Bound activity invocation input

9.33.5.1 The inbound value of `BSPHandle` shall be the canonical representation of the integer in the native parameter with the same name.

9.33.5.2 The inbound value of the parameter group "Input BIR" shall be the canonical representation (see 9.2.16.5) of the value of type `BioAPI_INPUT_BIR` in the variable pointed to by the native parameter `CapturedBIR`.

9.33.5.3 The inbound value of `OutputFormatOwner` and `OutputFormatType` shall be the canonical representation of the integer in the fields `FormatOwner` and `FormatType` (respectively) of the variable of type `BioAPI_BIR_BIOMETRIC_DATA_FORMAT` pointed to by the native parameter `OutputFormat`.

9.33.5.4 The inbound value of `no_ProcessedBIR` shall be "`true`" if the native parameter `ProcessedBIR` is NULL; otherwise, it shall be "`false`".

9.33.5.5 The inbound value of `return` shall be the canonical representation of the integer returned by the native function.

9.33.5.6 The inbound values of the other input parameters shall be determined as specified in 9.22.5.

9.33.6 Bound activity invocation output

There are no output parameters.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.34 BioAPI_ProcessUsingAuxBIRs

9.34.1 Function invocation scheme

This function belongs to the BioAPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioAPI_ProcessUsingAuxBIRs (

BioAPI_HANDLE BSPHandle,

uint32_t NumBIRs,

const BioAPI_INPUT_BIR *CapturedBIRList,

uint32_t NumberOfAuxBIRs,

const BioAPI_INPUT_BIR *AuxBIR,

const BioAPI_BIR_BIOMETRIC_DATA_FORMAT *OutputFormat,

BioAPI_HANDLE *ProcessedBIR);

and the following parameters (see Table 43).

Table 43

Parameter	Function invocation (conformance testing model for frameworks)	Bound activity invocation (conformance testing model for applications)
`BSPHandle`	input, outbound	input, inbound
`NumBIRs`	input, outbound	input, inbound
the members of the parameter group "Input BIR" (see 9.2.16) with their names prefixed by "`CapturedBIRList_`"	input, outbound	input, inbound
the members of the parameter group "Input BIR" with their names prefixed by "`AuxBIRs_`"	input, outbound	input, inbound
`OutputFormatOwner`	input, outbound	input, inbound
`OutputFormatType`	input, outbound	input, inbound
`no_ProcessedBIR`	input, outbound	input, inbound
`ProcessedBIR`	output, inbound	input, inbound
`return`	return, inbound	input, inbound

9.34.2 Constraints on the parameters

9.34.4.1 An outbound value of `BSPHandle`, `NumBIRs`, and `NumberOfAuxBIRs` shall be a valid representation of an integer (see 7.4) in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer (see 7.4.3) in the same range.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.34.4.2 An outbound value of each parameter group "Input BIR" shall be a valid representation of a value of the native type `BioAPI_INPUT_BIR`. An inbound value shall be the canonical representation of a value of that type.

9.34.4.3 An outbound value of `OutputFormatOwner` and `OutputFormatType` shall be a valid representation of an integer in the range 0 to 65535. An inbound value shall be the canonical representation of an integer in the same range.

9.34.4.4 An outbound value of `no_ProcessedBIR` shall be either a valid representation of a Boolean (see 7.5) or an empty string. An inbound value shall be the canonical representation of a Boolean (see 7.5.2).

9.34.4.5 An outbound value of `ProcessedBIR` shall be either a valid representation of an integer in the range −2147483648 to 2147483647 or an empty string. An inbound value shall be either the canonical representation of an integer in the same range or an empty string.

9.34.4.6 An outbound value of `return` shall be a valid representation of an integer in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer in the same range.

9.34.3 Function invocation input

9.34.3.1 The integer represented by the outbound value of `BSPHandle`, `NumBIRs`, and `NumberOfAuxBIRs` shall be assigned to the native parameter with the same name.

9.34.3.2 The value of type `BioAPI_INPUT_BIR` represented (see 9.2.16.4) by the outbound value of the parameter group "Input BIR" with the prefix "`CaptureBIRList_`" shall be written to a variable of type `BioAPI_INPUT_BIR`, whose address shall be assigned to the native parameter `CapturedBIRList`.

9.34.3.3 The value of type `BioAPI_INPUT_BIR` represented (see 9.2.16.4) by the outbound value of the parameter group "Input BIR" with the prefix "`AuxBIRs`" shall be written to a variable of type `BioAPI_INPUT_BIR`, whose address shall be assigned to the native parameter `AuxBIRs`.

9.34.3.4 The integer represented by the outbound value of `OutputFormatOwner` and `OutputFormatType` shall be written to the fields `FormatOwner` and `FormatType` (respectively) of a variable of type `BioAPI_BIR_BIOMETRIC_DATA_FORMAT`, whose address shall be assigned to the native parameter `OutputFormat`.

9.34.3.5 If the outbound value of `no_ProcessedBIR` is "`true`", then the native parameter `ProcessedBIR` shall be set to NULL; otherwise, it shall be set to the address of a variable of type `BioAPI_BIR_HANDLE`.

9.34.4 Function invocation output

The inbound value of `ProcessedBIR` shall be determined as follows. If the native parameter with the same name is NULL, then the inbound value shall be an empty string. Otherwise, the inbound value shall be the canonical representation of the integer in the variable of type `BioAPI_BIR_HANDLE` pointed to by the native parameter `ProcessedBIR`.

9.34.5 Bound activity invocation input

9.34.5.1 The inbound value of `BSPHandle`, `NumBIRs`, and `NumberOfAuxBIRs` shall be the canonical representation of the integer in the native parameter with the same name.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.34.5.2 The inbound value of the parameter group "Input BIR" with the prefix "`CapturedBIRList_`" shall be the canonical representation (see 9.2.16.5) of the value of type `BioAPI_INPUT_BIR` in the variable pointed to by the native parameter `CapturedBIRList`.

9.34.5.3 The inbound value of the parameter group "Input BIR" with the prefix "`AuxBIRs_`" shall be the canonical representation (see 9.2.16.5) of the value of type `BioAPI_INPUT_BIR` in the variable pointed to by the native parameter `AuxBIRs`.

9.34.5.4 The inbound value of `OutputFormatOwner` and `OutputFormatType` shall be the canonical representation of the integer in the fields `FormatOwner` and `FormatType` (respectively) of the variable of type `BioAPI_BIR_BIOMETRIC_DATA_FORMAT` pointed to by the native parameter `OutputFormat`.

9.34.5.5 The inbound value of `no_ProcessedBIR` shall be "`true`" if the native parameter `ProcessedBIR` is NULL; otherwise, it shall be "`false`".

9.34.5.6 The inbound value of `return` shall be the canonical representation of the integer returned by the native function.

9.34.5.7 The inbound values of the other input parameters shall be determined as specified in 9.23.5.

9.34.6 Bound activity invocation output

There are no output parameters.

9.35 BioAPI_VerifyMatch

9.35.1 Function invocation scheme

This function belongs to the BioAPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioAPI_VerifyMatch(

BioAPI_HANDLE BSPHandle,

BioAPI_FMR MaxFMRRequested,

const BioAPI_INPUT_BIR *ProcessedBIR,

const BioAPI_INPUT_BIR *ReferenceTemplate,

BioAPI_BIR_HANDLE *AdaptedBIR,

BioAPI_BOOL *Result,

BioAPI_FMR *FMRAchieved,

BioAPI_DATA *Payload);

and the following parameters (see Table 44).

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

 © ISO/IEC 2017 – All rights reserved

Table 44

Parameter	Function invocation (conformance testing model for frameworks)	Bound activity invocation (conformance testing model for applications)
`BSPHandle`	input, outbound	input, inbound
`MaxFMRRequested`	input, outbound	input, inbound
the members of the parameter group "Input BIR" (see 9.2.16) with their names prefixed by "`ProcessedBIR_`"	input, outbound	input, inbound
the members of the parameter group "Input BIR" with their names prefixed by "`ReferenceTemplate_`"	input, outbound	input, inbound
`no_AdaptedBIR`	input, outbound	input, inbound
`no_Result`	input, outbound	input, inbound
`no_FMRAchieved`	input, outbound	input, inbound
`no_Payload`	input, outbound	input, inbound
`AdaptedBIR`	output, inbound	input, inbound
`Result`	output, inbound	input, inbound
`FMRAchieved`	output, inbound	input, inbound
`Payload`	output, inbound	input, inbound
`return`	return, inbound	input, inbound

9.35.2 Constraints on the parameters

9.35.2.1 An outbound value of `BSPHandle` shall be a valid representation of an integer (see 7.4) in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer (see 7.4.3) in the same range.

9.35.2.2 An outbound value of `MaxFMRRequested` shall be a valid representation of an integer in the range −2147483648 to 2147483647. An inbound value shall be the canonical representation of an integer in the same range.

9.35.2.3 An outbound value of each parameter group "Input BIR" shall be a valid representation of a value of the native type `BioAPI_INPUT_BIR`. An inbound value shall be the canonical representation of a value of that type.

9.35.2.4 An outbound value of `no_ProcessedBIR` shall be either a valid representation of a Boolean (see 7.5) or an empty string. An inbound value shall be the canonical representation of a Boolean (see 7.5.2).

9.35.2.5 An outbound value of `AdaptedBIR` and `FMRAchieved` shall be either a valid representation of an integer in the range −2147483648 to 2147483647 or an empty string. An inbound value shall be the canonical representation of an integer in the same range or an empty string.

9.35.2.6 An outbound value of `Result` shall be either a valid representation of a Boolean or an empty string. An inbound value shall be the canonical representation of a Boolean or an empty string.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.35.2.7 An outbound value of `Payload` shall be a valid representation of an octet string. An inbound value shall be the canonical representation of an octet string.

9.35.2.8 An outbound value of `return` shall be a valid representation of an integer in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer in the same range.

9.35.3 Function invocation input

9.35.3.1 The integer represented by the outbound value of `BSPHandle` and `MaxFMRRequested` shall be assigned to the native parameter with the same name.

9.35.3.2 The value of type `BioAPI_INPUT_BIR` represented (see 9.2.16.4) by the outbound value of the parameter group "Input BIR" with the prefix "`ProcessedBIR_`" shall be written to a variable of type `BioAPI_INPUT_BIR`, whose address shall be assigned to the native parameter `ProcessedBIR`.

9.35.3.3 The value of type `BioAPI_INPUT_BIR` represented (see 9.2.16.4) by the outbound value of the parameter group "Input BIR" with the prefix "`ReferenceTemplate_`" shall be written to a variable of type `BioAPI_INPUT_BIR`, whose address shall be assigned to the native parameter `ReferenceTemplate`.

9.35.3.4 If the outbound value of `no_AdaptedBIR` is "`true`", then the native parameter `AdaptedBIR` shall be set to NULL; otherwise, it shall be set to the address of a variable of type `BioAPI_BIR_HANDLE`.

9.35.3.5 If the outbound value of `no_Result` is "`true`", then the native parameter `Result` shall be set to NULL; otherwise, it shall be set to the address of a variable of type `BioAPI_BOOL`.

9.35.3.6 If the outbound value of `no_FMRAchieved` is "`true`", then the native parameter `FMRAchieved` shall be set to NULL; otherwise, it shall be set to the address of a variable of type `BioAPI_FMR`.

9.35.3.7 If the outbound value of `no_Payload` is "`true`", then the native parameter `Payload` shall be set to NULL; otherwise, it shall be set to the address of a variable of type `BioAPI_DATA`.

9.35.4 Function invocation output

9.35.4.1 The inbound value of `AdaptedBIR` shall be determined as follows. If the native parameter with the same name is NULL, then the inbound value shall be an empty string. Otherwise, the inbound value shall be the canonical representation of the integer in the variable of type `BioAPI_BIR_HANDLE` pointed to by the native parameter `AdaptedBIR`.

9.35.4.2 The inbound value of `FMRAchieved` shall be determined as follows. If the native parameter with the same name is NULL, then the inbound value shall be an empty string. Otherwise, the inbound value shall be the canonical representation of the integer in variable of type `BioAPI_FMR` pointed to by the native parameter `FMRAchieved`.

9.35.4.3 The inbound value of `Result` shall be determined as follows. If the native parameter with the same name is NULL, then the inbound value shall be an empty string. Otherwise, the inbound value shall be the canonical representation of the Boolean in the variable of type `BioAPI_BOOL` pointed to by the native parameter `Result`.

9.35.4.4 The inbound value of `Payload` shall be determined as follows. If the native parameter with the same name is NULL, then the inbound value shall be an empty string. Otherwise, the inbound value shall be the canonical representation of the octet string in the memory block, whose address and length are in the fields `Data` and `Length` (respectively) of the variable of type `BioAPI_DATA` pointed to by the native parameter `Payload`.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

 © ISO/IEC 2017 – All rights reserved

9.35.5 Bound activity invocation input

9.35.5.1 The inbound value of `BSPHandle` and `MaxFMRRequested` shall be the canonical representation of the integer in the native parameter with the same name.

9.35.5.2 The inbound value of the parameter group "Input BIR" with the prefix "`ProcessedBIR_`" shall be the canonical representation (see 9.2.16.5) of the value of type `BioAPI_INPUT_BIR` in the variable pointed to by the native parameter `ProcessedBIR`.

9.35.5.3 The inbound value of the parameter group "Input BIR" with the prefix "`ReferenceTemplate_`" shall be the canonical representation (see 9.2.16.5) of the value of type `BioAPI_INPUT_BIR` in the variable pointed to by the native parameter `ReferenceTemplate`.

9.35.5.4 The inbound value of `no_AdaptedBIR` shall be "`true`" if the native parameter `AdaptedBIR` is NULL; otherwise, it shall be "`false`".

9.35.5.5 The inbound value of `no_Result` shall be "`true`" if the native parameter `Result` is NULL; otherwise, it shall be "`false`".

9.35.5.6 The inbound value of `no_FMRAchieved` shall be "`true`" if the native parameter `FMRAchieved` is NULL; otherwise, it shall be "`false`".

9.35.5.7 The inbound value of `no_Payload` shall be "`true`" if the native parameter `Payload` is NULL; otherwise, it shall be "`false`".

9.35.5.8 The inbound value of `return` shall be the canonical representation of the integer returned by the native function.

9.35.5.9 The inbound values of the other input parameters shall be determined as specified in 9.24.5.

9.35.6 Bound activity invocation output

There are no output parameters.

9.36 BioAPI_VerifyMatchUsingAuxBIRs

9.36.1 Function invocation scheme

This function belongs to the BioAPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioAPI_VerifyMatchUsingAuxBIRs(

BioAPI_HANDLE BSPHandle,

BioAPI_FMR MaxFMRRequested,

const BioAPI_INPUT_BIR *ProcessedBIR,

const BioAPI_INPUT_BIR *ReferenceTemplate,

uint32_t NumberOfAuxBIRs,

const BioAPI_INPUT_BIR *AuxBIRs,

BioAPI_BIR_HANDLE *AdaptedBIR,

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

BioAPI_BOOL *Result,

BioAPI_FMR *FMRAchieved,

BioAPI_BIR_HANDLE *ResultBIR,

BioAPI_AUXILIARY_SCALE_RESULT *AuxResult,

BioAPI_DATA *Payload

);

and the following parameters (see Table 45).

Table 45

Parameter	Function invocation (conformance testing model for frameworks)	Bound activity invocation (conformance testing model for applications)
`BSPHandle`	input, outbound	input, inbound
`MaxFMRRequested`	input, outbound	input, inbound
the members of the parameter group "Input BIR" (see 9.2.16) with their names prefixed by "`ProcessedBIR_`"	input, outbound	input, inbound
the members of the parameter group "Input BIR" with their names prefixed by "`ReferenceTemplate_`"	input, outbound	input, inbound
`NumberOfAuxBIRs`	input, outbound	input, inbound
the members of the parameter group "Input BIR" (see 9.2.16) with their names prefixed by "`AuxBIRs_`"	input, outbound	input, inbound
`AdaptedBIR`	output, outbound	input, inbound
`Result`	output, outbound	input, inbound
`FMRAchieved`	output, outbound	input, inbound
`ResultBIR`	output, outbound	input, inbound
`AuxResult`	output, outbound	input, inbound
`Payload`	output, outbound	input, inbound
`return`	return, inbound	input, inbound

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

9.36.2 Constraints on the parameters

9.36.2.1 An outbound value of `BSPHandle` and `NumberOfAuxBIRs` shall be a valid representation of an integer (see 7.4) in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer (see 7.4.3) in the same range.

9.36.2.2 An outbound value of `MaxFMRRequested` and `FMRAchieved` shall be a valid representation of an integer in the range 2147483648 to 2147483647. An inbound value shall be the canonical representation of an integer in the same range.

© ISO/IEC 2017 – All rights reserved

9.36.2.3 An outbound value of each parameter group "Input BIR" shall be a valid representation of a value of the native type `BioAPI_INPUT_BIR`. An inbound value shall be the canonical representation of a value of that type.

9.36.2.4 An outbound value of `Result` shall be either a valid representation of a Boolean or an empty string. An inbound value shall be the canonical representation of a Boolean or an empty string.

9.36.2.5 An outbound value of `Payload` shall be a valid representation of an octet string (see 7.7). An inbound value shall be the canonical representation of an octet string (see 7.7.2).

9.36.2.6 An outbound value of `AdaptedBIR`, `ResultBIR` and `AuxResult` shall be a valid representation of an integer in the range −2147483648 to 2147483647. An inbound value shall be the canonical representation of an integer in the same range.

9.36.2.7 An outbound value of `return` shall be a valid representation of an integer in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer in the same range.

9.36.3 Function invocation input

9.36.3.1 The integer represented by the outbound value of `BSPHandle`, `MaxFMRRequested` and `NumberOfAuxBIRs` shall be assigned to the native parameter with the same name.

9.36.3.2 The value of type `BioAPI_INPUT_BIR` represented (see 9.2.16.4) by the outbound value of the parameter group "Input BIR" with the prefix "`ProcessedBIR_`" shall be written to a variable of type `BioAPI_INPUT_BIR`, whose address shall be assigned to the native parameter `ProcessedBIR`.

9.36.3.3 The value of type `BioAPI_INPUT_BIR` represented (see 9.2.16.4) by the outbound value of the parameter group "Input BIR" with the prefix "`ReferenceTemplate_`" shall be written to a variable of type `BioAPI_INPUT_BIR`, whose address shall be assigned to the native parameter `ReferenceTemplate`.

9.36.3.4 The value of type `BioAPI_INPUT_BIR` represented (see 9.2.16.4) by the outbound value of the parameter group "Input BIR" with the prefix "`AuxBIRs_`" shall be written to a variable of type `BioAPI_INPUT_BIR`, whose address shall be assigned to the native parameter `AuxBIRs`.

9.36.3.5 If the outbound value of `no_FMRAchieved` is "`true`", then the native parameter `FMRAchieved` shall be set to NULL, otherwise, it shall be set to the address of a variable of type `BioAPI_FMR`.

9.36.4 Function invocation output

9.36.4.1 The inbound value of `AdaptedBIR` and `ResultBIR` shall be determined as follows. If the native parameter with the same name is NULL, then the inbound value shall be an empty string. Otherwise, the inbound value shall be the canonical representation of the integer in the variable of type `BioAPI_BIR_HANDLE` pointed to by the native parameter `AdaptedBIR` and `ResultBIR`.

9.36.4.2 The inbound value of `Result` shall be determined as follows. If the native parameter with the same name is NULL, then the inbound value shall be an empty string. Otherwise, the inbound value shall be the canonical representation of the Boolean in the variable of type `BioAPI_BOOL` pointed to by the native parameter `Result`.

9.36.4.3 The inbound value of `FMRAchieved` shall be determined as follows. If the native parameter with the same name is NULL, then the inbound value shall be an empty string. Otherwise, the inbound value shall be the canonical representation of the integer in variable of type `BioAPI_FMR` pointed to by the native parameter `FMRAchieved`.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.36.4.4 The inbound value of `AuxResult` shall be determined as follows. If the native parameter with the same name is NULL, then the inbound value shall be an empty string. Otherwise, the inbound value shall be the canonical representation of the integer in variable of type `BioAPI_AUXILIARYRESULTS` in the `BioAPI_OPTIONS_MASK` of the component registry indicates.

9.36.4.5 The inbound value of `Payload` shall be determined as follows. If the native parameter with the same name is NULL, then the inbound value shall be an empty string. Otherwise, the inbound value shall be the canonical representation of the octet string in the memory block, whose address and length are in the fields `Data` and `Length` (respectively) of the variable of type `BioAPI_DATA` pointed to by the native parameter `Payload`.

9.36.5 Bound activity invocation input

9.36.5.1 The inbound value of `BSPHandle`, `MaxFMRRequested` and `NumberOfAuxBIRs` shall be the canonical representation of the integer in the native parameter with the same name.

9.36.5.2 The inbound value of the parameter group "Input BIR" with the prefix "`ProcessedBIR_`" shall be the canonical representation (see 9.2.16.5) of the value of type `BioAPI_INPUT_BIR` in the variable pointed to by the native parameter `ProcessedBIR`.

9.36.5.3 The inbound value of the parameter group "Input BIR" with the prefix "`ReferenceTemplate_`" shall be the canonical representation (see 9.2.16.5) of the value of type `BioAPI_INPUT_BIR` in the variable pointed to by the native parameter `ReferenceTemplate`.

9.36.5.4 The inbound value of the parameter group "Input BIR" with the prefix "`AuxBIRs_`" shall be the canonical representation (see 9.2.16.5) of the value of type `BioAPI_INPUT_BIR` in the variable pointed to by the native parameter `AUXBIRs`.

9.36.5.5 The inbound value of `no_FMRAchieved` shall be "`true`" if the native parameter `FMRAchieved` is NULL; otherwise, it shall be "`false`".

9.36.6 Bound activity invocation output

There are no output parameters.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.37 BioAPI_IdentifyMatch

9.37.1 Function invocation scheme

This function belongs to the BioAPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioAPI_IdentifyMatch(

BioAPI_HANDLE BSPHandle,

BioAPI_FMR MaxFMRRequested,

const BioAPI_INPUT_BIR *ProcessedBIR,

const BioAPI_IDENTIFY_POPULATION *Population,

uint32_t TotalNumberOfTemplates,

BioAPI_BOOL Binning,

uint32_t MaxNumberOfResults,

uint32_t *NumberOfResults,

BioAPI_CANDIDATE **Candidates,

int32_t Timeout);

and the following parameters (see Table 46).

Table 46

Parameter	Function invocation (conformance testing model for frameworks)	Bound activity invocation (conformance testing model for applications)
`BSPHandle`	input, outbound	input, inbound
`MaxFMRRequested`	input, outbound	input, inbound
the members of the parameter group “Input BIR” (see 9.2.16) with their names prefixed by “`ProcessedBIR_`”	input, outbound	input, inbound
the members of the parameter group “Identify population” (see 9.2.17)	input, outbound	input, inbound
`TotalNumberOfTemplates`	input, outbound	input, inbound
`Binning`	input, outbound	input, inbound
`MaxNumberOfResults`	input, outbound	input, inbound
`no_NumberOfResults`	input, outbound	input, inbound
`no_Candidates`	input, outbound	input, inbound
`Timeout`	input, outbound	input, inbound
`NumberOfResults`	output, inbound	input, inbound

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

Table 46 *(continued)*

Parameter	Function invocation (conformance testing model for frameworks)	Bound activity invocation (conformance testing model for applications)
the members of the parameter group "Candidate" (see 9.2.18) with their names prefixed by "Candidate_1_"	output, inbound	input, inbound
the members of the parameter group "Candidate" with their names prefixed by "Candidate_2_"	output, inbound	input, inbound
the members of the parameter group "Candidate" with their names prefixed by "Candidate_3_"	output, inbound	input, inbound
the members of the parameter group "Candidate" with their names prefixed by "Candidate_4_"	output, inbound	input, inbound
return	return, inbound	input, inbound

9.37.2 Constraints on the parameters

9.37.2.1 An outbound value of BSPHandle, TotalNumberOfTemplates and MaxNumberOfResults shall be a valid representation of an integer (see 7.4) in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer (see 7.4.3) in the same range.

9.37.2.2 An outbound value of MaxFMRRequested shall be a valid representation of an integer in the range −2147483648 to 2147483647. An inbound value shall be the canonical representation of an integer in the same range.

9.37.2.3 An outbound value of the parameter group "Input BIR" shall be a valid representation of a value of the native type BioAPI_INPUT_BIR. An inbound value shall be the canonical representation of a value of that type.

9.37.2.4 An outbound value of the parameter group "Identify population" shall be a valid representation of a value of the native type BioAPI_IDENTIFY_POPULATION. An inbound value shall be the canonical representation of a value of that type.

9.37.2.5 An outbound value of Binning shall be a valid representation of a Boolean. An inbound value shall be the canonical representation of a Boolean.

9.37.2.6 An outbound value of no_NumberOfResults and no_Candidates shall be either a valid representation of a Boolean or an empty string. An inbound value shall be the canonical representation of a Boolean.

9.37.2.7 An outbound value of Timeout shall be a valid representation of an integer in the range −2147483648 to 2147483647. An inbound value shall be the canonical representation of an integer in the same range.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.37.2.8 An outbound value of `NumberOfResults` shall be either a valid representation of an integer in the range 0 to 4294967295 or an empty string. An inbound value shall be either the canonical representation of an integer in the same range or an empty string.

9.37.2.9 An outbound value of each parameter group "Candidate" shall be a valid representation of a value of the native type `BioAPI_CANDIDATE`. An inbound value shall be either the canonical representation of a value of that type or a set of empty strings.

9.37.2.10 An outbound value of `return` shall be a valid representation of an integer in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer in the same range.

9.37.3 Function invocation input

9.37.3.1 The integer represented by the outbound value of `BSPHandle`, `MaxFMRRequested`, `TotalNumberOfTemplates`, `MaxNumberOfResults`, and `Timeout` shall be assigned to the native parameter with the same name.

9.37.3.2 The Boolean represented by the outbound value of `Binning` shall be assigned to the native parameter with the same name.

9.37.3.3 The value of type `BioAPI_INPUT_BIR` represented (see 9.2.16.4) by the outbound value of the parameter group "Input BIR" shall be written to a variable of type `BioAPI_INPUT_BIR`, whose address shall be assigned to the native parameter `ProcessedBIR`.

9.37.3.4 The value of type `BioAPI_IDENTIFY_POPULATION` represented (see 9.2.17.4) by the outbound value of the parameter group "Identify population" shall be written to a variable of type `BioAPI_IDENTIFY_POPULATION`, whose address shall be assigned to the native parameter `Population`.

9.37.3.5 If the outbound value of `no_NumberOfResults` is "`true`", then the native parameter `NumberOfResults` shall be set to NULL; otherwise, it shall be set to the address of a variable of type `uint32_t`.

9.37.3.6 If the outbound value of `no_Candidates` is "`true`", then the native parameter `Candidates` shall be set to NULL; otherwise, it shall be set to the address of a variable of type `BioAPI_CANDIDATE*` (a pointer).

9.37.4 Function invocation output

9.37.4.1 The inbound value of `NumberOfResults` shall be determined as follows. If the native parameter with the same name is NULL, then the inbound value shall be an empty string. Otherwise, the inbound value shall be the canonical representation of the integer in the variable of type `uint32_t` pointed to by the native parameter `NumberOfResults`.

9.37.4.2 The inbound value of the parameter group "Candidate" with the prefix "`Candidate_X_`" (with *X* = 1, 2, 3, or 4) shall be determined as follows. If the native parameter `Candidates` is NULL or the variable pointed to by that native parameter is NULL or the native parameter `NumberOfResults` is NULL or the value of the integer variable pointed to that native parameter is less than *X*, then the inbound value shall be a set of empty strings. Otherwise, the inbound value shall be the canonical representation (see 9.2.15.5) of the value of type `BioAPI_CANDIDATE` at position *X* in the array pointed to by the variable pointed to by the native parameter `Candidates`.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.37.5 Bound activity invocation input

9.37.5.1 The inbound value of `BSPHandle`, `MaxFMRRequested`, `TotalNumberOfTemplates`, `MaxNumberOfResults`, and `Timeout` shall be the canonical representation of the integer in the native parameter with the same name.

9.37.5.2 The inbound value of `Binning` shall be the canonical representation of the Boolean in the native parameter with the same name.

9.37.5.3 The inbound value of the parameter group "Input BIR" shall be the canonical representation (see 9.2.16.5) of the value of type `BioAPI_INPUT_BIR` in the variable pointed to by the native parameter `ProcessedBIR`.

9.37.5.4 The inbound value of the parameter group "Identify population" shall be the canonical representation (see 9.2.17.5) of the value of type `BioAPI_IDENTIFY_POPULATION` in the variable pointed to by the native parameter `Population`.

9.37.5.5 The inbound value of `no_NumberOfResults` shall be "`true`" if the native parameter `NumberOfResults` is NULL; otherwise, it shall be "`false`".

9.37.5.6 The inbound value of `no_Candidates` shall be "`true`" if the native parameter `Candidates` is NULL; otherwise, it shall be "`false`".

9.37.5.7 The inbound value of `return` shall be the canonical representation of the integer returned by the native function.

9.37.5.8 The inbound values of the other input parameters shall be determined as specified in 9.25.5.

9.37.6 Bound activity invocation output

There are no output parameters.

9.38 BioAPI_Decide

9.38.1 Function invocation scheme

This function belongs to the BioAPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioAPI_Decide(

BioAPI_HANDLE BSPHandle,

const BioAPI_INPUT_BIR *ScoreBIR,

uint32_t NumberOfAuxBIRs,

const BioAPI_INPUT_BIR *AuxBIRs,

BioAPI_BIR_HANDLE *DecisionBIR);

and the following parameters (see Table 47).

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

 © ISO/IEC 2017 – All rights reserved

Table 47

Parameter	Function invocation (conformance testing model for frameworks)	Bound activity invocation (conformance testing model for applications)
BSPHandle	input, outbound	input, inbound
the members of the parameter group "Input BIR" (see 9.2.16) with their names prefixed by "ScoreBIR_"	input, outbound	input, inbound
NumberOfAuxBIRs	input, outbound	input, inbound
the members of the parameter group "Input BIR" (see 9.2.16) with their names prefixed by "AuxBIRs_"	input, inbound	input, inbound
DecisionBIR	output, inbound	input, inbound
return	return, inbound	input, inbound

9.38.2 Constraints on the parameters

9.38.2.1 An outbound value of BSPHandle and NumberOfAuxBIRs and DecisionBIR shall be a valid representation of an integer (see 7.4) in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer (see 7.4.3) in the same range.

9.38.2.2 An outbound value of the parameter group "Input BIR" shall be a valid representation of a value of the native type BioAPI_INPUT_BIR. An inbound value shall be the canonical representation of a value of that type.

9.38.2.3 An outbound value of DecisionBIR shall be either a valid representation of an integer in the range -2147483648 to 2147483647 or an empty string. An inbound value shall be the canonical representation of an integer in the same range or an empty string.

9.38.3 Function invocation input

9.38.3.1 The integer represented by the outbound value of BSPHandle and NumberOfAuxBIRs shall be assigned to the native parameter with the same name.

9.38.3.2 The value of type BioAPI_INPUT_BIR represented (see 9.2.16.4) by the outbound value of the parameter group "Input BIR" with the prefix "ScoreBIR_" shall be written to a variable of type BioAPI_INPUT_BIR, whose address shall be assigned to the native parameter ScoreBIR.

9.38.3.3 The value of type BioAPI_INPUT_BIR represented (see 9.2.16.4) by the outbound value of the parameter group "Input BIR" with the prefix "AuxBIRs_" shall be written to a variable of type BioAPI_INPUT_BIR, whose address shall be assigned to the native parameter AuxBIRs.

9.38.4 Function invocation output

The inbound value of DecisionBIR shall be determined as follows. If the native parameter with the same name is NULL, then the inbound value shall be an empty string. Otherwise, the inbound value shall be the canonical representation of the integer in the variable of type BioAPI_BIR_HANDLE pointed to by the native parameter DecisionBIR.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.38.5 Bound activity invocation input

9.38.5.1 The inbound value of `BSPHandle` and `NumberOfAuxBIRs` shall be the canonical representation of the integer in the native parameter with the same name.

9.38.5.2 The inbound value of the parameter group "Input BIR" with the prefix "`ScoreBIR_`" shall be the canonical representation (see 9.2.16.5) of the value of type `BioAPI_INPUT_BIR` in the variable pointed to by the native parameter `ScoreBIR`.

9.38.5.3 The inbound value of the parameter group "Input BIR" with the prefix "`AuxBIRs_`" shall be the canonical representation (see 9.2.16.5) of the value of type `BioAPI_INPUT_BIR` in the variable pointed to by the native parameter `AuxBIRs`.

9.38.6 Bound activity invocation output

There are no output parameters.

9.39 BioAPI_Fuse

9.39.1 Function invocation scheme

This function belongs to the BioAPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioAPI_Fuse(

BioAPI_HHANDLE BSPHandle,

uint32_t NumberOfSourceBIRs,

const BioAPI_INPUT_BIR *SourceBIRs,

uint32_t NumberOfAuxBIRs,

const BioAPI_INPUT_BIR *AuxBIRs,

BioAPI_BIR_HANDLE *FusionBIR

);

and the following parameters (see Table 48).

Table 48

Parameter	Function invocation (conformance testing model for frameworks)	Bound activity invocation (conformance testing model for applications)
`BSPHandle`	input, outbound	input, inbound
`NumberOfSourceBIRs`	input, outbound	input, inbound
the members of the parameter group "Input BIR" (see 9.2.16) with their names prefixed by "`SourceBIRs_`"	input, outbound	input, inbound
`NumberOfAuxBIRs`	input, outbound	input, inbound

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

Table 48 *(continued)*

Parameter	Function invocation (conformance testing model for frameworks)	Bound activity invocation (conformance testing model for applications)
the members of the parameter group "Input BIR" (see 9.2.16) with their names prefixed by "AuxBIRs_"	input, outbound	input, inbound
FusionBIR	output, inbound	input, inbound
return	return, inbound	input, inbound

9.39.2 Constraints on the parameters

9.39.2.1 An outbound value of BSPHandle, NumberOfAuxBIRs, NumberOfSourceBIRs and DecisionBIR shall be a valid representation of an integer (see 7.4) in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer (see 7.4.3) in the same range.

9.39.2.2 An outbound value of the parameter group "Input BIR" shall be a valid representation of a value of the native type BioAPI_INPUT_BIR. An inbound value shall be the canonical representation of a value of that type.

9.39.2.3 An outbound value of FusionBIR shall be either a valid representation of an integer in the range –2147483648 to 2147483647 or an empty string. An inbound value shall be the canonical representation of an integer in the same range or an empty string.

9.39.3 Function invocation input

9.39.3.1 The integer represented by the outbound value of BSPHandle, NumberOfAuxBIRs and NumberOfSourceBIRs shall be assigned to the native parameter with the same name.

9.39.3.2 The value of type BioAPI_INPUT_BIR represented (see 9.2.16.4) by the outbound value of the parameter group "Input BIR" with the prefix "SourceBIRs_" shall be written to a variable of type BioAPI_INPUT_BIR, whose address shall be assigned to the native parameter SourceBIRs.

9.39.3.3 The value of type BioAPI_INPUT_BIR represented (see 9.2.16.4) by the outbound value of the parameter group "Input BIR" with the prefix "AuxBIRs_" shall be written to a variable of type BioAPI_INPUT_BIR, whose address shall be assigned to the native parameter AuxBIRs.

9.39.4 Function invocation output

The inbound value of FusionBIR shall be determined as follows. If the native parameter with the same name is NULL, then the inbound value shall be an empty string. Otherwise, the inbound value shall be the canonical representation of the integer in the variable of type BioAPI_BIR_HANDLE pointed to by the native parameter FusionBIR.

9.39.5 Bound activity invocation input

9.39.5.1 The inbound value of BSPHandle, NumberOfAuxBIRs and NumberOfSourceBIRs shall be the canonical representation of the integer in the native parameter with the same name.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.39.5.2 The inbound value of the parameter group "Input BIR" with the prefix "`SourceBIRs_`" shall be the canonical representation (see 9.2.16.5) of the value of type `BioAPI_INPUT_BIR` in the variable pointed to by the native parameter `SourceBIRs`.

9.39.5.3 The inbound value of the parameter group "Input BIR" with the prefix "`AuxBIRs_`" shall be the canonical representation (see 9.2.16.5) of the value of type `BioAPI_INPUT_BIR` in the variable pointed to by the native parameter `AuxBIRs`.

9.39.6 Bound activity invocation output

There are no output parameters.

9.40 BioAPI_Enroll

9.40.1 Function invocation scheme

This function belongs to the BioAPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioAPI_Enroll(

BioAPI_HANDLE BSPHandle,

BioAPI_BIR_PURPOSE Purpose,

BioAPI_BIR_SUBTYPE Subtype,

const BioAPI_BIR_BIOMETRIC_DATA_FORMAT *OutputFormat,

const BioAPI_INPUT_BIR *ReferenceTemplate,

BioAPI_BIR_HANDLE *NewTemplate,

const BioAPI_DATA *Payload,

int32_t Timeout,

BioAPI_BIR_HANDLE *AuditData,

BioAPI_UUID *TemplateUUID);

and the following parameters (see Table 49).

Table 49

Parameter	Function invocation (conformance testing model for frameworks)	Bound activity invocation (conformance testing model for applications)
`BSPHandle`	input, outbound	input, inbound
`Purpose`	input, outbound	input, inbound
`Subtype`	input, outbound	input, inbound
`OutputFormatOwner`	input, outbound	input, inbound
`OutputFormatType`	input, outbound	input, inbound

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

Table 49 *(continued)*

Parameter	Function invocation (conformance testing model for frameworks)	Bound activity invocation (conformance testing model for applications)
the members of the parameter group "Input BIR" (see 9.2.16) with their names prefixed by "ReferenceTemplate_"	input, outbound	input, inbound
No_NewTemplate	input, outbound	input, inbound
Payload	input, outbound	input, inbound
Timeout	input, outbound	input, inbound
no_AuditData	input, outbound	input, inbound
no_TemplateUUID	input, outbound	input, inbound
NewTemplate	output, inbound	input, inbound
AuditData	output, inbound	input, inbound
TemplateUUID	output, inbound	input, inbound
Return	return, inbound	input, inbound

9.40.2 Constraints on the parameters

9.40.2.1 An outbound value of BSPHandle shall be a valid representation of an integer (see 7.4) in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer (see 7.4.3) in the same range.

9.40.2.2 An outbound value of Purpose and Subtype shall be a valid representation of an integer in the range 0 to 255. An inbound value shall be the canonical representation of an integer in the same range.

9.40.2.3 An outbound value of OutputFormatOwner and OutputFormatType shall be a valid representation of an integer in the range 0 to 65535. An inbound value shall be the canonical representation of an integer in the same range.

9.40.2.4 An outbound value of the parameter group "Input BIR" shall be a valid representation of a value of the native type BioAPI_INPUT_BIR. An inbound value shall be the canonical representation of a value of that type.

9.40.2.5 An outbound value of no_NewTemplate, no_AuditData and no_TemplateUUID shall be either a valid representation of a Boolean (see 7.5) or an empty string. An inbound value shall be the canonical representation of a Boolean (see 7.5.2).

9.40.2.6 An outbound value of Payload shall be a valid representation of an octet string (see 7.7). An inbound value shall be the canonical representation of an octet string (see 7.7.2).

9.40.2.7 An outbound value of Timeout shall be a valid representation of an integer in the range −2147483648 to 2147483647. An inbound value shall be the canonical representation of an integer in the same range.

9.40.2.8 An outbound value of NewTemplates and AuditData shall be either a valid representation of an integer in the range −2147483648 to 2147483647 or an empty string. An inbound value shall be either the canonical representation of an integer in the same range or an empty string.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.40.2.9 An outbound value of `TemplateUUID` shall be either a valid representation of a UUID (see 7.6) or an empty string. An inbound value shall be either the canonical representation of a UUID (see 7.6.3) or an empty string.

9.40.2.10 An outbound value of `return` shall be a valid representation of an integer in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer in the same range.

9.40.3 Function invocation input

9.40.3.1 The integer represented by the outbound value of `BSPHandle`, `Purpose`, `Subtype`, and `Timeout` shall be assigned to the native parameter with the same name.

9.40.3.2 The integer represented by the outbound value of `OutputFormatOwner` and `OutputFormatType` shall be written to the fields `FormatOwner` and `FormatType` (respectively) of a variable of type `BioAPI_BIR_BIOMETRIC_DATA_FORMAT`, whose address shall be assigned to the native parameter `OutputFormat`.

9.40.3.3 The value of type `BioAPI_INPUT_BIR` represented (see 9.2.16.4) by the outbound value of the parameter group "Input BIR" shall be written to a variable of type `BioAPI_INPUT_BIR`, whose address shall be assigned to the native parameter `ReferenceTemplate`.

9.40.3.4 The integer represented by the outbound value of `no_NewTemplates` is "`true`", then the native parameter `NewTemplate` shall be set to NULL; otherwise, it shall be set to the address of a variable of type `BioAPI_BIR_HANDLE`.

9.40.3.5 If the outbound value of `Payload` is an empty string, then the native parameter with the same name shall be set to NULL. Otherwise, the octet string represented by the outbound value shall be written to a memory block of sufficient size. The address and length of that memory block shall be written to the fields `Data` and `Length` (respectively) of a variable of type `BioAPI_DATA`, whose address shall be assigned to the native parameter `Payload`.

9.40.3.6 If the outbound value of `no_AuditData` is "`true`", then the native parameter `AuditData` shall be set to NULL; otherwise, it shall be set to the address of a variable of type `BioAPI_BIR_HANDLE`.

9.40.3.7 If the outbound value of `no_TemplateUUID` is "`true`", then the native parameter `TemplateUUID` shall be set to NULL; otherwise, it shall be set to the address of a variable of type `BioAPI_UUID`.

9.40.4 Function invocation output

9.40.4.1 The inbound value of `NewTemplate` shall be determined as follows. If the native parameter with the same name is NULL, then the inbound value shall be an empty string. Otherwise, the inbound value shall be the canonical representation of the integer in the variable of type `BioAPI_BIR_HANDLE` pointed to by the native parameter `NewTemplate`.

9.40.4.2 The inbound value of `AuditData` shall be determined as follows. If the native parameter with the same name is NULL, then the inbound value shall be an empty string. Otherwise, the inbound value shall be the canonical representation of the integer in the variable of type `BioAPI_BIR_HANDLE` pointed to by the native parameter `AuditData`.

9.40.4.3 The inbound value of `TemplateUUID` shall be determined as follows. If the native parameter with the same name is NULL, then the inbound value shall be an empty string. Otherwise, the inbound value value shall be the canonical representation of the UUID in the variable of type `BioAPI_UUID` pointed to by the native parameter `TemplateUUID`.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

 © ISO/IEC 2017 – All rights reserved

9.40.5 Bound activity invocation input

9.40.5.1 The inbound value of `BSPHandle`, `Purpose`, `Subtype`, and `Timeout` shall be the canonical representation of the integer in the native parameter with the same name.

9.40.5.2 The inbound value of `OutputFormatOwner` and `OutputFormatType` shall be the canonical representation of the integer in the fields `FormatOwner` and `FormatType` (respectively) of the variable of type `BioAPI_BIR_BIOMETRIC_DATA_FORMAT` pointed to by the native parameter `OutputFormat`.

9.40.5.3 The inbound value of the parameter group "Input BIR" with the prefix "`ReferenceTemplate_`" shall be the canonical representation (see 9.2.16.5) of the value of type `BioAPI_INPUT_BIR` in the variable pointed to by the native parameter `ReferenceTemplate`.

9.40.5.4 The inbound value of `no_NewTemplate` shall be "`true`" if the native parameter `NewTemplate` is NULL; otherwise, it shall be "`false`".

9.40.5.5 The inbound value of `Payload` shall be determined as follows. If the native parameter with the same name is NULL, then the inbound value shall be an empty string. Otherwise, the inbound value shall be the canonical representation (see 7.7.2) of the octet string in the memory block, whose address and length are in the fields `Data` and `Length` (respectively) of the variable of type `BioAPI_DATA` pointed to by the native parameter `Payload`.

9.40.5.6 The inbound value of `no_AuditData` shall be "`true`" if the native parameter `AuditData` is NULL; otherwise, it shall be "`false`".

9.40.5.7 The inbound value of `no_TemplateUUID` shall be "`true`" if the native parameter `TemplateUUID` is NULL; otherwise, it shall be "`false`".

9.40.5.8 The inbound value of `return` shall be the canonical representation of the integer returned by the native function.

9.40.5.9 The inbound values of the other input parameters shall be determined as specified in 9.26.5.

9.40.6 Bound activity invocation output

There are no output parameters.

9.41 BioAPI_Verify

9.41.1 Function invocation scheme

This function belongs to the BioAPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioAPI_Verify(

BioAPI_HANDLE BSPHandle,

BioAPI_FMR MaxFMRRequested,

const BioAPI_INPUT_BIR *ReferenceTemplate,

BioAPI_BIR_SUBTYPE Subtype,

BioAPI_BIR_HANDLE *AdaptedBIR,

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

BioAPI_BOOL *Result,

BioAPI_FMR *FMRAchieved,

BioAPI_DATA *Payload,

int32_t Timeout,

BioAPI_BIR_HANDLE *AuditData);

and the following parameters (see Table 50).

Table 50

Parameter	Function invocation (conformance testing model for frameworks)	Bound activity invocation (conformance testing model for applications)
`BSPHandle`	input, outbound	input, inbound
`MaxFMRRequested`	input, outbound	input, inbound
the members of the parameter group "Input BIR" (see 9.2.16) with their names prefixed by "`ReferenceTemplate_`"	input, outbound	input, inbound
`Subtype`	input, outbound	input, inbound
`no_AdaptedBIR`	input, outbound	input, inbound
`no_Result`	input, outbound	input, inbound
`no_FMRAchieved`	input, outbound	input, inbound
`no_Payload`	input, outbound	input, inbound
`Timeout`	input, outbound	input, inbound
`no_AuditData`	input, outbound	input, inbound
`AdaptedBIR`	output, inbound	input, inbound
`Result`	output, inbound	input, inbound
`FMRAchieved`	output, inbound	input, inbound
`Payload`	output, inbound	input, inbound
`AuditData`	output, inbound	input, inbound
`Return`	return, inbound	input, inbound

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

9.41.2 Constraints on the parameters

9.41.2.1 An outbound value of `BSPHandle` shall be a valid representation of an integer (see 7.4) in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer (see 7.4.3) in the same range.

9.41.2.2 An outbound value of `MaxFMRRequested` shall be a valid representation of an integer in the range −2147483648 to 2147483647. An inbound value shall be the canonical representation of an integer in the same range.

9.41.2.3 An outbound value of the parameter group "Input BIR" shall be a valid representation of a value of the native type `BioAPI_INPUT_BIR`. An inbound value shall be the canonical representation of a value of that type.

© ISO/IEC 2017 – All rights reserved

9.41.2.4 An outbound value of `no_AdaptedBIR`, `no_Result`, `no_FMRAchieved`, `no_Payload`, and `no_AuditData` shall be either a valid representation of a Boolean (see 7.5) or an empty string. An inbound value shall be the canonical representation of a Boolean (see 7.5.2).

9.41.2.5 An outbound value of `Subtype` shall be a valid representation of an integer in the range 0 to 255. An inbound value shall be the canonical representation of an integer in the same range.

9.41.2.6 An outbound value of `Timeout` shall be a valid representation of an integer in the range −2147483648 to 2147483647. An inbound value shall be the canonical representation of an integer in the same range.

9.41.2.7 An outbound value of `AdaptedBIR`, `FMRAchieved`, and `AuditData` shall be either a valid representation of an integer in the range −2147483648 to 2147483647 or an empty string. An inbound value shall be the canonical representation of an integer in the same range or an empty string.

9.41.2.8 An outbound value of `Result` shall be either a valid representation of a Boolean or an empty string. An inbound value shall be the canonical representation of a Boolean or an empty string.

9.41.2.9 An outbound value of `Payload` shall be a valid representation of an octet string. An inbound value shall be the canonical representation of an octet string.

9.41.2.10 An outbound value of `return` shall be a valid representation of an integer in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer in the same range.

9.41.3 Function invocation input

9.41.3.1 The integer represented by the outbound value of `BSPHandle`, `MaxFMRRequested`, `Subtype` and `Timeout` shall be assigned to the native parameter with the same name.

9.41.3.2 The value of type `BioAPI_INPUT_BIR` represented (see 9.2.16.4) by the outbound value of the parameter group "Input BIR" shall be written to a variable of type `BioAPI_INPUT_BIR`, whose address shall be assigned to the native parameter `ReferenceTemplate`.

9.41.3.3 If the outbound value of `no_AdaptedBIR` is "`true`", then the native parameter `AdaptedBIR` shall be set to NULL; otherwise, it shall be set to the address of a variable of type `BioAPI_BIR_HANDLE`.

9.41.3.4 If the outbound value of `no_Result` is "`true`", then the native parameter `Result` shall be set to NULL; otherwise, it shall be set to the address of a variable of type `BioAPI_BOOL`.

9.41.3.5 If the outbound value of `no_FMRAchieved` is "`true`", then the native parameter `FMRAchieved` shall be set to NULL; otherwise, it shall be set to the address of a variable of type `BioAPI_FMR`.

9.41.3.6 If the outbound value of `no_Payload` is "`true`", then the native parameter `Payload` shall be set to NULL; otherwise, it shall be set to the address of a variable of type `BioAPI_DATA`.

9.41.3.7 If the outbound value of `no_AuditData` is "`true`", then the native parameter `AuditData` shall be set to NULL; otherwise, it shall be set to the address of a variable of type `BioAPI_BIR_HANDLE`.

9.41.4 Function invocation output

9.41.4.1 The inbound value of `AdaptedBIR` shall be determined as follows. If the native parameter with the same name is NULL, then the inbound value shall be an empty string. Otherwise, the inbound

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

value shall be the canonical representation of the integer in the variable of type `BioAPI_BIR_HANDLE` pointed to by the native parameter `AdaptedBIR`.

9.41.4.2 The inbound value of `FMRAchieved` shall be determined as follows. If the native parameter with the same name is NULL, then the inbound value shall be an empty string. Otherwise, the inbound value shall be the canonical representation of the integer in the variable of type `BioAPI_FMR` pointed to by the native parameter `FMRAchieved`.

9.41.4.3 The inbound value of `Result` shall be determined as follows. If the native parameter with the same name is NULL, then the inbound value shall be an empty string. Otherwise, the inbound value shall be the canonical representation of the Boolean in the variable of type `BioAPI_BOOL` pointed to by the native parameter `Result`.

9.41.4.4 The inbound value of `Payload` shall be determined as follows. If the native parameter with the same name is NULL, then the inbound value shall be an empty string. Otherwise, the inbound value shall be the canonical representation of the octet string in the memory block, whose address and length are in the fields `Data` and `Length` (respectively) of the variable of type `BioAPI_DATA` pointed to by the native parameter `Payload`.

9.41.4.5 The inbound value of `AuditData` shall be determined as follows. If the native parameter with the same name is NULL, then the inbound value shall be an empty string. Otherwise, the inbound value shall be the canonical representation of the integer in the variable of type `BioAPI_BIR_HANDLE` pointed to by the native parameter `AuditData`.

9.41.5 Bound activity invocation input

9.41.5.1 The inbound value of `BSPHandle`, `MaxFMRRequested`, `Subtype` and `Timeout` shall be the canonical representation of the integer in the native parameter with the same name.

9.41.5.2 The inbound value of the parameter group "Input BIR" with the prefix "`ReferenceTemplate_`" shall be the canonical representation (see 9.2.16.5) of the value of type `BioAPI_INPUT_BIR` in the variable pointed to by the native parameter `ReferenceTemplate`.

9.41.5.3 The inbound value of `no_AdaptedBIR` shall be "`true`" if the native parameter `AdaptedBIR` is NULL; otherwise, it shall be "`false`".

9.41.5.4 The inbound value of `no_Result` shall be "`true`" if the native parameter `Result` is NULL; otherwise, it shall be "`false`".

9.41.5.5 The inbound value of `no_FMRAchieved` shall be "`true`" if the native parameter `FMRAchieved` is NULL; otherwise, it shall be "`false`".

9.41.5.6 The inbound value of `no_Payload` shall be "`true`" if the native parameter `Payload` is NULL; otherwise, it shall be "`false`".

9.41.5.7 The inbound value of `no_AuditData` shall be "`true`" if the native parameter `AuditData` is NULL; otherwise, it shall be "`false`".

9.41.5.8 The inbound value of `return` shall be the canonical representation of the integer returned by the native function.

9.41.5.9 The inbound values of the other input parameters shall be determined as specified in 9.27.5.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.41.6 Bound activity invocation output

There are no output parameters.

9.42 BioAPI_Identify

9.42.1 Function invocation scheme

This function belongs to the BioAPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioAPI_Identify(

BioAPI_HANDLE BSPHandle,

BioAPI_FMR MaxFMRRequested,

BioAPI_BIR_SUBTYPE Subtype,

const BioAPI_IDENTIFY_POPULATION *Population,

uint32_t TotalNumberOfTemplates,

BioAPI_BOOL Binning,

uint32_t MaxNumberOfResults,

uint32_t *NumberOfResults,

BioAPI_CANDIDATE **Candidates,

int32_t Timeout,

BioAPI_BIR_HANDLE *AuditData);

and the following parameters (see Table 51).

Table 51

Parameter	Function invocation (conformance testing model for frameworks)	Bound activity invocation (conformance testing model for applications)
`BSPHandle`	input, outbound	input, inbound
`MaxFMRRequested`	input, outbound	input, inbound
`Subtype`	input, outbound	input, inbound
the members of the parameter group “Identify population” (see 9.2.17)	input, outbound	input, inbound
`TotalNumberOfTemplates`	input, outbound	input, inbound
`Binning`	input, outbound	input, inbound
`MaxNumberOfResults`	input, outbound	input, inbound
`no_NumberOfResults`	input, outbound	input, inbound
`no_Candidates`	input, outbound	input, inbound
`Timeout`	input, outbound	input, inbound
`no_AuditData`	input, outbound	input, inbound

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

Table 51 *(continued)*

Parameter	Function invocation (conformance testing model for frameworks)	Bound activity invocation (conformance testing model for applications)
NumberOfResults	output, inbound	input, inbound
the members of the parameter group "Candidate" (see 9.2.18) with their names prefixed by "Candidate_1_"	output, inbound	input, inbound
the members of the parameter group "Candidate" with their names prefixed by "Candidate_2_"	output, inbound	input, inbound
the members of the parameter group "Candidate" with their names prefixed by "Candidate_3_"	output, inbound	input, inbound
the members of the parameter group "Candidate" with their names prefixed by "Candidate_4_"	output, inbound	input, inbound
AuditData	output, inbound	input, inbound
Return	return, inbound	input, inbound

9.42.2 Constraints on the parameters

9.42.2.1 An outbound value of BSPHandle, TotalNumberOfTemplates and MaxNumberOfResults shall be a valid representation of an integer (see 7.4) in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer (see 7.4.3) in the same range.

9.42.2.2 An outbound value of MaxFMRRequested shall be a valid representation of an integer in the range −2147483648 to 2147483647. An inbound value shall be the canonical representation of an integer in the same range.

9.42.2.3 An outbound value of Subtype shall be a valid representation of an integer in the range 0 to 255. An inbound value shall be the canonical representation of an integer in the same range.

9.42.2.4 An outbound value of the parameter group "Identify population" shall be a valid representation of a value of the native type BioAPI_IDENTIFY_POPULATION. An inbound value shall be the canonical representation of a value of that type.

9.42.2.5 An outbound value of Binning shall be a valid representation of a Boolean. An inbound value shall be the canonical representation of a Boolean.

9.42.2.6 An outbound value of no_NumberOfResults, no_Candidates, and no_AuditData shall be either a valid representation of a Boolean (see 7.5) or an empty string. An inbound value shall be the canonical representation of a Boolean (see 7.5.2).

9.42.2.7 An outbound value of Timeout shall be a valid representation of an integer in the range −2147483648 to 2147483647. An inbound value shall be the canonical representation of an integer in the same range.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.42.2.8 An outbound value of `NumberOfResults` shall be either a valid representation of an integer in the range 0 to 4294967295 or an empty string. An inbound value shall be either the canonical representation of an integer in the same range or an empty string.

9.42.2.9 An outbound value of `AuditData` shall be either a valid representation of an integer in the range −2147483648 to 2147483647 or an empty string. An inbound value shall be either the canonical representation of an integer in the same range or an empty string.

9.42.2.10 An outbound value of each parameter group "Candidate" shall be a valid representation of a value of the native type `BioAPI_CANDIDATE`. An inbound value shall be either the canonical representation of a value of that type or a set of empty strings.

9.42.2.11 An outbound value of `return` shall be a valid representation of an integer in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer in the same range.

9.42.3 Function invocation input

9.42.3.1 The integer represented by the outbound value of `BSPHandle`, `MaxFMRRequested`, `Subtype`, `TotalNumberOfTemplates`, `MaxNumberOfResults` and `Timeout` shall be assigned to the native parameter with the same name.

9.42.3.2 The value of type `BioAPI_IDENTIFY_POPULATION` represented (see 9.2.17.4) by the outbound value of the parameter group "Identify population" shall be written to a variable of type `BioAPI_IDENTIFY_POPULATION`, whose address shall be assigned to the native parameter `Population`.

9.42.3.3 The Boolean represented by the outbound value of `Binning` shall be assigned to the native parameter with the same name.

9.42.3.4 If the outbound value of `no_NumberOfResults` is "`true`", then the native parameter `NumberOfResults` shall be set to NULL; otherwise, it shall be set to the address of a variable of type `uint32_t`.

9.42.3.5 If the outbound value of `no_Candidates` is "`true`", then the native parameter `Candidates` shall be set to NULL; otherwise, it shall be set to the address of a variable of type `BioAPI_CANDIDATE*` (a pointer).

9.42.3.6 If the outbound value of `no_AuditData` is "`true`", then the native parameter `AuditData` shall be set to NULL; otherwise, it shall be set to the address of a variable of type `BioAPI_BIR_HANDLE`.

9.42.4 Function invocation output

9.42.4.1 The inbound value of `NumberOfResults` shall be determined as follows. If the native parameter with the same name is NULL, then the inbound value shall be an empty string. Otherwise, the inbound value shall be the canonical representation of the integer in the variable of type `uint32_t` pointed to by the native parameter `NumberOfResults`.

9.42.4.2 The inbound value of the parameter group "Candidate" with the prefix "`Candidate_X_`" (with *X* = 1, 2, 3, or 4) shall be determined as follows. If the native parameter `Candidates` is NULL or the variable pointed to by that native parameter is NULL or the native parameter `NumberOfResults` is NULL or the value of the integer variable pointed to by that native parameter is less than *X*, then the inbound value shall be a set of empty strings. Otherwise, the inbound value shall be the canonical representation (see 9.2.15.5) of the value of type `BioAPI_CANDIDATE` at position *X* in the array pointed to by the variable pointed to by the native parameter `Candidates`.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.42.4.3 The inbound value of `AuditData` shall be determined as follows. If the native parameter with the same name is NULL, then the inbound value shall be an empty string. Otherwise, the inbound value shall be the canonical representation of the integer in the variable of type `BioAPI_BIR_HANDLE` pointed to by the native parameter `AuditData`.

9.42.5 Bound activity invocation input

9.42.5.1 The inbound value of `BSPHandle`, `MaxFMRRequested`, `Subtype`, `TotalNumberOfTemplates`, `MaxNumberOfResults` and `Timeout` shall be the canonical representation of the integer in the native parameter with the same name.

9.42.5.2 The inbound value of the parameter group "Identify population" shall be the canonical representation (see 9.2.17.5) of the value of type `BioAPI_IDENTIFY_POPULATION` in the variable pointed to by the native parameter `Population`.

9.42.5.3 The inbound value of `Binning` shall be the canonical representation of the Boolean in the native parameter with the same name.

9.42.5.4 The inbound value of `no_NumberOfResults` shall be "`true`" if the native parameter `NumberOfResults` is NULL; otherwise, it shall be "`false`".

9.42.5.5 The inbound value of `no_Candidates` shall be "`true`" if the native parameter `Candidates` is NULL; otherwise, it shall be "`false`".

9.42.5.6 The inbound value of `no_AuditData` shall be "`true`" if the native parameter `AuditData` is NULL; otherwise, it shall be "`false`".

9.42.5.7 The inbound value of `return` shall be the canonical representation of the integer returned by the native function.

9.42.5.8 The inbound values of the other input parameters shall be determined as specified in 9.28.5.

9.42.6 Bound activity invocation output

There are no output parameters.

9.43 BioAPI_Import

9.43.1 Function invocation scheme

This function belongs to the BioAPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioAPI_Import(

BioAPI_HANDLE BSPHandle,

const BioAPI_DATA *InputData,

const BioAPI_BIR_BIOMETRIC_DATA_FORMAT *InputFormat,

const BioAPI_BIR_BIOMETRIC_DATA_FORMAT *OutputFormat,

BioAPI_BIR_PURPOSE Purpose,

BioAPI_BIR_HANDLE *ConstructedBIR);

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

 © ISO/IEC 2017 – All rights reserved

and the following parameters (see Table 52).

Table 52

Parameter	Function invocation (conformance testing model for frameworks)	Bound activity invocation (conformance testing model for applications)
`BSPHandle`	input, outbound	input, inbound
`InputData`	input, outbound	input, inbound
`InputFormatOwner`	input, outbound	input, inbound
`InputFormatType`	input, outbound	input, inbound
`OutputFormatOwner`	input, outbound	input, inbound
`OutputFormatType`	input, outbound	input, inbound
`Purpose`	input, outbound	input, inbound
`no_ConstructedBIR`	input, outbound	input, inbound
`ConstructedBIR`	output, inbound	input, inbound
`return`	return, inbound	input, inbound

9.43.2 Constraints on the parameters

9.43.2.1 An outbound value of `BSPHandle` shall be a valid representation of an integer (see 7.4) in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer (see 7.4.3) in the same range.

9.43.2.2 An outbound value of `InputData` shall be a valid representation of an octet string (see 7.7). An inbound value shall be the canonical representation of an octet string (see 7.7.2).

9.43.2.3 An outbound value of `InputFormatOwner`, `InputFormatType`, `OutputFormatOwner`, and `OutputFormatType` shall be a valid representation of an integer in the range 0 to 65535. An inbound value shall be the canonical representation of an integer in the same range.

9.43.2.4 An outbound value of `Purpose` shall be a valid representation of an integer in the range 0 to 255. An inbound value shall be the canonical representation of an integer in the same range.

9.43.2.5 An outbound value of `no_ConstructedBIR` shall be either a valid representation of a Boolean (see 7.5) or an empty string. An inbound value shall be the canonical representation of a Boolean (see 7.5.2).

9.43.2.6 An outbound value of `ConstructedBIR` shall be either a valid representation of an integer in the range −2147483648 to 2147483647 or an empty string. An inbound value shall be either the canonical representation of an integer in the same range or an empty string.

9.43.2.7 An outbound value of `return` shall be a valid representation of an integer in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer in the same range.

9.43.3 Function invocation input

9.43.3.1 The integer represented by the outbound value of `BSPHandle` and `Purpose` shall be assigned to the native parameter with the same name.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.43.3.2 If the outbound value of `InputData` is an empty string, then the native parameter with the same name shall be set to NULL. Otherwise, the octet string represented by the outbound value shall be written to a memory block of sufficient size. The address and length of that memory block shall be written to the fields `Data` and `Length` (respectively) of a variable of type `BioAPI_DATA`, whose address shall be assigned to the native parameter `InputData`.

9.43.3.3 The integer represented by the outbound value of `InputFormatOwner` and `InputFormatType` shall be written to the fields `FormatOwner` and `FormatType` (respectively) of a variable of type `BioAPI_BIR_BIOMETRIC_DATA_FORMAT`, whose address shall be assigned to the native parameter `InputFormat`.

9.43.3.4 The integer represented by the outbound value of `OutputFormatOwner` and `OutputFormatType` shall be written to the fields `FormatOwner` and `FormatType` (respectively) of a variable of type `BioAPI_BIR_BIOMETRIC_DATA_FORMAT`, whose address shall be assigned to the native parameter `OutputFormat`.

9.43.3.5 If the outbound value of `no_ConstructedBIR` is "`true`", then the native parameter `ConstructedBIR` shall be set to NULL; otherwise, it shall be set to the address of a variable of type `BioAPI_BIR_HANDLE`.

9.43.4 Function invocation output

The inbound value of `ConstructedBIR` shall be determined as follows. If the native parameter with the same name is NULL, then the inbound value shall be an empty string. Otherwise, the inbound value shall be the canonical representation of an integer in the range –2147483648 to 2147483647 (see 7.4.3). The integer shall be read from the variable of type `BioAPI_BIR_HANDLE` pointed to by the native parameter `ConstructedBIR`.

9.43.5 Bound activity invocation input

9.43.5.1 The inbound value of `BSPHandle` and `Purpose` shall be the canonical representation of the integer in the native parameter with the same name.

9.43.5.2 The inbound value of `InputData` shall be determined as follows. If the native parameter with the same name is NULL, then the inbound value shall be an empty string. Otherwise, the inbound value shall be the canonical representation (see 7.7.2) of the octet string in the memory block, whose address and length are in the fields `Data` and `Length` (respectively) of the variable of type `BioAPI_DATA` pointed to by the native parameter `InputData`.

9.43.5.3 The inbound value of `InputFormatOwner` and `InputFormatType` shall be the canonical representation of the integer in the fields `FormatOwner` and `FormatType` (respectively) of the variable of type `BioAPI_BIR_BIOMETRIC_DATA_FORMAT` pointed to by the native parameter `InputFormat`.

9.43.5.4 The inbound value of `OutputFormatOwner` and `OutputFormatType` shall be the canonical representation of the integer in the fields `FormatOwner` and `FormatType` (respectively) of the variable of type `BioAPI_BIR_BIOMETRIC_DATA_FORMAT` pointed to by the native parameter `OutputFormat`.

9.43.5.5 The inbound value of `no_ConstructedBIR` shall be "`true`" if the native parameter `ConstructedBIR` is NULL; otherwise, it shall be "`false`".

9.43.5.6 The inbound value of `return` shall be the canonical representation of the integer returned by the native function.

9.43.5.7 The inbound values of the other input parameters shall be determined as specified in 9.29.5.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

 © ISO/IEC 2017 – All rights reserved

9.43.6 Bound activity invocation output

There are no output parameters.

9.44 BioAPI_Export

9.44.1 Function invocation scheme

This function belongs to the BioAPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioAPI_Export(

BioAPI_HANDLE BSPHandle,

BioAPI_BIR_HANDLE Handle,

const BioAPI_BIR_BIOMETRIC_DATA_FORMAT *OutputBDBFormat,

const BioAPI_BIR_SECURITY_BLOCK_FORMAT *OutputSBFormat,

BioAPI_BIR *BIR);

and the following parameters (see Table 52).

Table 52

Parameter	Function invocation (conformance testing model for frameworks)	Bound activity invocation (conformance testing model for applications)
`BSPHandle`	input, outbound	input, inbound
`Handle`	input, outbound	input, inbound
`OutputBDBFormat`	input, outbound	input, inbound
`OutputSBFormat`	input, outbound	input, inbound
`no_BIR`	input, outbound	input, inbound
the members of the parameter group "BIR" (see 9.2.15)	output, inbound	input, inbound
`return`	return, inbound	input, inbound

9.44.2 Constraints on the parameters

9.44.2.1 An outbound value of `BSPHandle` shall be a valid representation of an integer (see 7.4) in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer (see 7.4.3) in the same range.

9.44.2.2 An outbound value of `Handle` shall be either a valid representation of an integer in the range −2147483648 to 2147483647 or an empty string. An inbound value shall be the canonical representation of an integer in the same range or an empty string.

9.44.2.3 An outbound value of `OutputBDBFormat` and `OutputSBFormat` shall be a valid representation of an integer in the range 0 to 65535. An inbound value shall be the canonical representation of an integer in the same range.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.44.2.4 An outbound value of the parameter group "BIR" shall be a valid representation of a value of the native type `BioAPI_BIR`. An inbound value shall be either the canonical representation of a value of that type or a set of empty strings.

9.44.2.5 An outbound value of `return` shall be a valid representation of an integer in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer in the same range.

9.44.3 Function invocation input

9.44.3.1 The integer represented by the outbound value of `BSPHandle` shall be assigned to the native parameter with the same name.

9.44.3.2 If the outbound value of `no_BIR` is "`true`", then the native parameter BIR shall be set to NULL; otherwise, it shall be set to the address of a variable of type `BioAPI_BIR`.

9.44.3.3 The inbound value of `Handle` shall be determined as follows. If the native parameter with the same name is NULL, then the inbound value shall be an empty string. Otherwise, the inbound value shall be the canonical representation of the integer in the variable of type `BioAPI_BIR_HANDLE` pointed to by the native parameter `Handle`.

9.44.3.4 The integer represented by the outbound value of `OutputBDBFormat` shall be written to the fields `FormatOwner` and `FormatType` (respectively) of a variable of type `BioAPI_BIR_BIOMETRIC_DATA_FORMAT`, whose address shall be assigned to the native parameter `OutputBDBFormat`.

9.44.3.5 The integer represented by the outbound value of `OutputSBFormat` shall be written to the fields of a variable of type `BioAPI_BIR_SECURITU_BLOCK_FORMAT`, whose address shall be assigned to the native parameter `OutputSBFormat`.

9.44.4 Function invocation output

The inbound value of the parameter group "BIR" shall be determined as follows. If the native parameter `BIR` is NULL, then the inbound value shall be a set of empty strings. Otherwise, the inbound value shall be the canonical representation (see 9.2.15.5) of the value of type `BioAPI_BIR` pointed to by the native parameter `BIR`.

9.44.5 Bound activity invocation input

9.44.5.1 The inbound value of `BSPHandle` shall be the canonical representation of the integer in the native parameter with the same name.

9.44.5.2 The inbound value of `no_Handle` shall be "`true`" if the native parameter `Handle` is NULL; otherwise, it shall be "`false`".

9.44.5.3 The inbound value of `OutputBDBFormat` shall be the canonical representation of the integer in the fields of the variable of type `BioAPI_BIR_BIOMETRIC_DATA_FORMAT` pointed to by the native parameter `OutputBDBFormat`.

9.44.5.4 The inbound value of `OutputSBFormat` shall be the canonical representation of the integer in the fields of the variable of type `BioAPI_BIR_SECURITY_BLOCK_FORMAT` pointed to by the native parameter `OutputSBFormat`.

9.44.5.5 The inbound value of `no_BIR` shall be "`true`" if the native parameter BIR is NULL; otherwise, it shall be "`false`".

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

 © ISO/IEC 2017 – All rights reserved

9.44.5.6 The inbound value of `return` shall be the canonical representation of the integer returned by the native function.

9.44.6 Bound activity invocation output

There are no output parameters.

9.45 BioAPI_PresetIdentifyPopulation

9.45.1 Function invocation scheme

This function belongs to the BioAPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioAPI_PresetIdentifyPopulation(

BioAPI_HANDLE BSPHandle,

const BioAPI_IDENTIFY_POPULATION *Population);

and the following parameters (see Table 53).

Table 53

Parameter	Function invocation (conformance testing model for frameworks)	Bound activity invocation (conformance testing model for applications)
`BSPHandle`	input, outbound	input, inbound
members of the parameter group "Identify population" (see 9.2.17)	input, outbound	input, inbound
`return`	return, inbound	input, inbound

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

9.45.2 Constraints on the parameters

9.45.2.1 An outbound value of `BSPHandle` shall be a valid representation of an integer (see 7.4) in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer (see 7.4.3) in the same range.

9.45.2.2 An outbound value of the parameter group "Identify population" shall be a valid representation of a value of the native type `BioAPI_IDENTIFY_POPULATION`. An inbound value shall be the canonical representation of a value of that type.

9.45.2.3 An outbound value of `return` shall be a valid representation of an integer in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer in the same range.

9.45.3 Function invocation input

9.45.3.1 The integer represented by the outbound value of `BSPHandle` shall be assigned to the native parameter with the same name.

© ISO/IEC 2017 – All rights reserved

9.45.3.2 The value of type `BioAPI_IDENTIFY_POPULATION` represented (see 9.2.17.4) by the outbound value of the parameter group "Identify population" shall be written to a variable of type `BioAPI_IDENTIFY_POPULATION`, whose address shall be assigned to the native parameter `Population`.

9.45.4 Function invocation output

There are no output parameters.

9.45.5 Bound activity invocation input

9.45.5.1 The inbound value of `BSPHandle` shall be the canonical representation of the integer in the native parameter with the same name.

9.45.5.2 The inbound value of the parameter group "Identify population" shall be the canonical representation (see 9.2.17.5) of the value of type `BioAPI_IDENTIFY_POPULATION` in the variable pointed to by the native parameter `Population`.

9.45.5.3 The inbound value of `return` shall be the canonical representation of the integer returned by the native function.

9.45.6 Bound activity invocation output

There are no output parameters.

9.46 BioAPI_Transform

9.46.1 Function invocation scheme

This function belongs to the BioAPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioAPI_Transform(

BioAPI_HANDLE BSPHandle,

const BioAPI_UUID *OperationUUID,

const BioAPI_INPUT_BIR *InputBIRs,

uint32_t NumberOfInputBIRs,

BioAPI_BIR_HANDLE **OutputBIR,

uint32_t *NumberOfOutputBIRs);

and the following parameters (see Table 54).

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

Table 54

Parameter	Function invocation (conformance testing model for frameworks)	Bound activity invocation (conformance testing model for applications)
`BSPHandle`	input, outbound	input, inbound
`OperationUUID`	input, outbound	input, inbound
the members of the parameter group "Input BIR" (see 9.2.16) with their names prefixed by "`InputBIRs_`"	input, outbound	input, inbound
`NumberOfInputBIRs`	input, outbound	input, inbound
`no_ OutputBIR`	input, outbound	input, inbound
`OutputBIR`	output, inbound	input, inbound
`NumberOfOutputBIRs`	output, inbound	input, inbound
`return`	return, inbound	input, inbound

9.46.2 Constraints on the parameters

9.46.2.1 An outbound value of `BSPHandle`, `NumberOfInputBIRs` and `NumberOfOutputBIRs` shall be a valid representation of an integer (see 7.4) in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer (see 7.4.3) in the same range.

9.46.2.2 An outbound value of `OperationUUID` shall be a valid representation of a UUID (see 7.6). An inbound value shall be the canonical representation of a UUID (see 7.6.3).

9.46.2.3 An outbound value of the parameter group "Input BIR" shall be a valid representation of a value of the native type `BioAPI_INPUT_BIR`. An inbound value shall be the canonical representation of a value of that type.

9.46.2.4 An outbound value of each parameter group "OutputBIR" shall be a valid representation of a value of the native type `BioAPI_BIR_HANDLE`. An inbound value shall be either the canonical representation of a value of that type, or a set of empty strings.

9.46.2.5 An outbound value of `return` shall be a valid representation of an integer in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer in the same range.

9.46.3 Function invocation input

9.46.3.1 The integer represented by the outbound value of `BSPHandle` and `NumberOfInputBIRs` shall be assigned to the native parameter with the same name.

9.46.3.2 The UUID represented by the outbound value of `OperationUUID` shall be written to a variable of type `BioAPI_UUID`, whose address shall be assigned to the native parameter `OperationUUID`.

9.46.3.3 The value of type `BioAPI_INPUT_BIR` represented (see 9.2.16.4) by the outbound value of the parameter group "Input BIR" with the prefix "`InputBIRs_`" shall be written to a variable of type `BioAPI_INPUT_BIR`, whose address shall be assigned to the native parameter `InputBIRs`.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.46.3.4 If the outbound value of `no_OutputBIR` is "`true`", then the native parameter `OutputBIR` shall be set to NULL; otherwise, it shall be set to the address of a variable of type `BioAPI_BIR_HANDLE*` (a pointer).

9.46.4 Function invocation output

The inbound value of `NumberOfOutputBIRs` shall be determined as follows. If the native parameter with the same name is NULL, then the inbound value shall be an empty string. Otherwise, the inbound value shall be the canonical representation of the integer in the variable of type `uint32_t` pointed to by the native parameter `NumberOfOutputBIRs`.

9.46.5 Bound activity invocation input

9.46.5.1 The inbound value of `BSPHandle` and `NumberOfInputBIRs` shall be the canonical representation of the integer in the native parameter with the same name.

9.46.5.2 The inbound value of `OperationUUID` shall be the canonical representation of the UUID in the variable of type `BioAPI_UUID` pointed to by the native parameter `OperationUUID`.

9.46.5.3 The inbound value of the parameter group "Input BIR" with the prefix "`InputBIRs_`" shall be the canonical representation (see 9.2.16.5) of the value of type `BioAPI_INPUT_BIR` in the variable pointed to by the native parameter `InputBIRs`.

9.46.5.4 The inbound value of `no_OutputBIR` shall be "`true`" if the native parameter `OutputBIR` is NULL; otherwise, it shall be "`false`".

9.46.5.5 The inbound value of `return` shall be the canonical representation of the integer returned by the native function.

9.46.6 Bound activity invocation output

There are no output parameters.

9.47 BioAPI_DbOpen

9.47.1 Function invocation scheme

This function belongs to the BioAPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioAPI_DbOpen(

BioAPI_HANDLE BSPHandle,

const BioAPI_UUID *DbUuid,

BioAPI_DB_ACCESS_TYPE AccessRequest,

BioAPI_DB_HANDLE *DbHandle,

BioAPI_DB_MARKER_HANDLE *MarkerHandle);

and the following parameters (see Table 55).

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

Table 55

Parameter	Function invocation (conformance testing model for frameworks)	Bound activity invocation (conformance testing model for applications)
`BSPHandle`	input, outbound	input, inbound
`DbUuid`	input, outbound	input, inbound
the members of the parameter group "Access type" (see 9.2.20)	input, outbound	input, inbound
`no_DbHandle`	input, outbound	input, inbound
`no_MarkerHandle`	input, outbound	input, inbound
`DbHandle`	output, inbound	input, inbound
`MarkerHandle`	output, inbound	input, inbound
`return`	return, inbound	input, inbound

9.47.2 Constraints on the parameters

9.47.2.1 An outbound value of `BSPHandle` shall be a valid representation of an integer (see 7.4) in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer (see 7.4.3) in the same range.

9.47.2.2 An outbound value of `DbUuid` shall be a valid representation of a UUID (see 7.6). An inbound value shall be the canonical representation of a UUID (see 7.6.3).

9.47.2.3 An outbound value of the parameter group "Access type" shall be a valid representation of a value of the native type `BioAPI_DB_ACCESS_TYPE`. An inbound value shall be the canonical representation of a value of that type.

9.47.2.4 An outbound value of `no_DbHandle` and `no_MarkerHandle` shall be either a valid representation of a Boolean (see 7.5) or an empty string. An inbound value shall be the canonical representation of a Boolean (see 7.5.2).

9.47.2.5 An outbound value of `DbHandle` shall be either a valid representation of an integer in the range −2147483648 to 2147483647 or an empty string. An inbound value shall be either the canonical representation of an integer in the same range or an empty string.

9.47.2.6 An outbound value of `MarkerHandle` shall be either a valid representation of an integer in the range 0 to 4294967295 or an empty string. An inbound value shall be either the canonical representation of an integer in the same range or an empty string.

9.47.2.7 An outbound value of `return` shall be a valid representation of an integer in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer in the same range.

9.47.3 Function invocation input

9.47.3.1 The integer represented by the outbound value of `BSPHandle` shall be assigned to the native parameter with the same name.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.47.3.2 The UUID represented by the outbound value of `DbUuid` shall be written to a variable of type `BioAPI_UUID`, whose address shall be assigned to the native parameter `DbUuid`.

9.47.3.3 The value of type `BioAPI_DB_ACCESS_TYPE` represented (see 9.2.20.4) by the outbound value of the parameter group "Access type" shall be assigned to the native parameter `AccessRequest`.

9.47.3.4 If the outbound value of `no_DbHandle` is "`true`", then the native parameter `DbHandle` shall be set to NULL; otherwise, it shall be set to the address of a variable of type `BioAPI_DB_HANDLE`.

9.47.3.5 If the outbound value of `no_MarkerHandle` is "`true`", then the native parameter `MarkerHandle` shall be set to NULL; otherwise, it shall be set to the address of a variable of type `BioAPI_DB_MARKER_HANDLE`.

9.47.4 Function invocation output

9.47.4.1 The inbound value of `DbHandle` shall be determined as follows. If the native parameter with the same name is NULL, then the inbound value shall be an empty string. Otherwise, the inbound value shall be the canonical representation of the integer in the variable of type `BioAPI_DB_HANDLE` pointed to by the native parameter `DbHandle`.

9.47.4.2 The inbound value of `MarkerHandle` shall be determined as follows. If the native parameter with the same name is NULL, then the inbound value shall be an empty string. Otherwise, the inbound value shall be the canonical representation of the integer in the variable of type `BioAPI_DB_MARKER_HANDLE` pointed to by the native parameter `MarkerHandle`.

9.47.5 Bound activity invocation input

9.47.5.1 The inbound value of `BSPHandle` shall be the canonical representation of the integer in the native parameter with the same name.

9.47.5.2 The inbound value of `DbUuid` shall be the canonical representation of the UUID in the variable of type `BioAPI_UUID` pointed to by the native parameter `DbUuid`.

9.47.5.3 The inbound value of the parameter group "Access type" shall be the canonical representation (see 9.2.20.5) of the value of type `BioAPI_DB_ACCESS_TYPE` in the native parameter `AccessRequest`.

9.47.5.4 The inbound value of `no_DbHandle` shall be "`true`" if the native parameter `DbHandle` is NULL; otherwise, it shall be "`false`".

9.47.5.5 The inbound value of `no_MarkerHandle` shall be "`true`" if the native parameter `MarkerHandle` is NULL; otherwise, it shall be "`false`".

9.47.5.6 The inbound value of `return` shall be the canonical representation of the integer returned by the native function.

9.47.5.7 The inbound values of the other input parameters shall be determined as specified in 9.31.4.

9.47.6 Bound activity invocation output

There are no output parameters.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.48 BioAPI_DbClose

9.48.1 Function invocation scheme

This function belongs to the BioAPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioAPI_DbClose(

BioAPI_HANDLE BSPHandle,

BioAPI_DB_HANDLE DbHandle);

and the following parameters (see Table 56).

Table 56

Parameter	Function invocation (conformance testing model for frameworks)	Bound activity invocation (conformance testing model for applications)
`BSPHandle`	input, outbound	input, inbound
`DbHandle`	input, outbound	input, inbound
`return`	return, inbound	input, inbound

9.48.2 Constraints on the parameters

9.48.2.1 An outbound value of `BSPHandle` shall be a valid representation of an integer (see 7.4) in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer (see 7.4.3) in the same range.

9.48.2.2 An outbound value of `DbHandle` shall be a valid representation of an integer in the range -2147483648 to 2147483647. An inbound value shall be the canonical representation of an integer in the same range.

9.48.2.3 An outbound value of `return` shall be a valid representation of an integer in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer in the same range.

9.48.3 Function invocation input

The integer represented by the outbound value of `BSPHandle` and `DbHandle` shall be assigned to the native parameter with the same name.

9.48.4 Function invocation output

There are no output parameters.

9.48.5 Bound activity invocation input

9.48.5.1 The inbound value of `BSPHandle` and `DbHandle` shall be the canonical representation of the integer in the native parameter with the same name.

9.48.5.2 The inbound value of `return` shall be the canonical representation of the integer returned by the native function.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.48.6 Bound activity invocation output

There are no output parameters.

9.49 BioAPI_DbCreate

9.49.1 Function invocation scheme

This function belongs to the BioAPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioAPI_DbCreate(

BioAPI_HANDLE BSPHandle,

const BioAPI_UUID *DbUuid,

uint32_t NumberOfRecords,

BioAPI_DB_ACCESS_TYPE AccessRequest,

BioAPI_DB_HANDLE *DbHandle);

and the following parameters (see Table 57).

Table 57

Parameter	Function invocation (conformance testing model for frameworks)	Bound activity invocation (conformance testing model for applications)
`BSPHandle`	input, outbound	input, inbound
`DbUuid`	input, outbound	input, inbound
`NumberOfRecords`	input, outbound	input, inbound
the members of the parameter group "Access type" (see 9.2.20)	input, outbound	input, inbound
`no_DbHandle`	input, outbound	input, inbound
`DbHandle`	output, inbound	input, inbound
`Return`	return, inbound	input, inbound

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

9.49.2 Constraints on the parameters

9.49.2.1 An outbound value of `BSPHandle` and `NumberOfRecords` shall be a valid representation of an integer (see 7.4) in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer (see 7.4.3) in the same range.

9.49.2.2 An outbound value of `DbUuid` shall be a valid representation of a UUID (see 7.6). An inbound value shall be the canonical representation of a UUID (see 7.6.3).

9.49.2.3 An outbound value of the parameter group "Access type" shall be a valid representation of a value of the native type `BioAPI_DB_ACCESS_TYPE`. An inbound value shall be the canonical representation of a value of that type.

© ISO/IEC 2017 – All rights reserved

9.49.2.4 An outbound value of `no_DbHandle` shall be either a valid representation of a Boolean (see 7.5) or an empty string. An inbound value shall be the canonical representation of a Boolean (see 7.5.2).

9.49.2.5 An outbound value of `DbHandle` shall be either a valid representation of an integer in the range −2147483648 to 2147483647 or an empty string. An inbound value shall be either the canonical representation of an integer in the same range, or an empty string.

9.49.2.6 An outbound value of `return` shall be a valid representation of an integer in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer in the same range.

9.49.3 Function invocation input

9.49.3.1 The integer represented by the outbound value of `BSPHandle` and `NumberOfRecords` shall be assigned to the native parameter with the same name.

9.49.3.2 The UUID represented by the outbound value of `DbUuid` shall be written to a variable of type `BioAPI_UUID`, whose address shall be assigned to the native parameter `DbUuid`.

9.49.3.3 The value of type `BioAPI_DB_ACCESS_TYPE` represented (see 9.2.20.4) by the outbound value of the parameter group "Access type" shall be assigned to the native parameter `AccessRequest`.

9.49.3.4 If the outbound value of `no_DbHandle` is "`true`", then the native parameter `DbHandle` shall be set to NULL; otherwise, it shall be set to the address of a variable of type `BioAPI_DB_HANDLE`.

9.49.4 Function invocation output

The inbound value of `DbHandle` shall be determined as follows. If the native parameter with the same name is NULL, then the inbound value shall be an empty string. Otherwise, the inbound value shall be the canonical representation of the integer in the variable of type `BioAPI_DB_HANDLE` pointed to by the native parameter `DbHandle`.

9.49.5 Bound activity invocation input

9.49.5.1 The inbound value of `BSPHandle` and `NumberOfRecords` shall be the canonical representation of the integer in the native parameter with the same name.

9.49.5.2 The inbound value of `DbUuid` shall be the canonical representation of the UUID in the variable of type `BioAPI_UUID` pointed to by the native parameter `DbUuid`.

9.49.5.3 The inbound value of the parameter group "Access type" shall be the canonical representation (see 9.2.20.5) of the value of type `BioAPI_DB_ACCESS_TYPE` in the native parameter `AccessRequest`.

9.49.5.4 The inbound value of `no_DbHandle` shall be "`true`" if the native parameter `DbHandle` is NULL; otherwise, it shall be "`false`".

9.49.5.5 The inbound value of `return` shall be the canonical representation of the integer returned by the native function.

9.49.5.6 The inbound values of the other input parameters shall be determined as specified in 9.33.4.

9.49.6 Bound activity invocation output

There are no output parameters.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.50 BioAPI_DbDelete

9.50.1 Function invocation scheme

This function belongs to the BioAPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioAPI_DbDelete(

BioAPI_HANDLE BSPHandle,

const BioAPI_UUID *DbUuid);

and the following parameters (see Table 58).

Table 58

Parameter	Function invocation (conformance testing model for frameworks)	Bound activity invocation (conformance testing model for applications)
`BSPHandle`	input, outbound	input, inbound
`DbUuid`	input, outbound	input, inbound
`return`	return, inbound	input, inbound

9.50.2 Constraints on the parameters

9.50.2.1 An outbound value of `BSPHandle` shall be a valid representation of an integer (see 7.4) in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer (see 7.4.3) in the same range.

9.50.2.2 An outbound value of `DbUuid` shall be a valid representation of a UUID (see 7.6). An inbound value shall be the canonical representation of a UUID (see 7.6.3).

9.50.2.3 An outbound value of `return` shall be a valid representation of an integer in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer in the same range.

9.50.3 Function invocation input

9.50.3.1 The integer represented by the outbound value of `BSPHandle` shall be assigned to the native parameter with the same name.

9.50.3.2 The UUID represented by the outbound value of `DbUuid` shall be written to a variable of type `BioAPI_UUID`, whose address shall be assigned to the native parameter `DbUuid`.

9.50.4 Function invocation output

There are no output parameters.

9.50.5 Bound activity invocation input

9.50.5.1 The inbound value of `BSPHandle` shall be the canonical representation of the integer in the native parameter with the same name.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

 © ISO/IEC 2017 – All rights reserved

9.50.5.2 The inbound value of `DbUuid` shall be the canonical representation of the UUID in the variable of type `BioAPI_UUID` pointed to by the native parameter `DbUuid`.

9.50.5.3 The inbound value of `return` shall be the canonical representation of the integer returned by the native function.

9.50.6 Bound activity invocation output

There are no output parameters.

9.51 BioAPI_DbSetMarker

9.51.1 Function invocation scheme

This function belongs to the BioAPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioAPI_DbSetMarker(

BioAPI_HANDLE BSPHandle,

BioAPI_DB_HANDLE DbHandle,

const BioAPI_UUID *KeyValue,

BioAPI_DB_MARKER_HANDLE MarkerHandle);

and the following parameters (see Table 59).

Table 59

Parameter	Function invocation (conformance testing model for frameworks)	Bound activity invocation (conformance testing model for applications)
`BSPHandle`	input, outbound	input, inbound
`DbHandle`	input, outbound	input, inbound
`KeyValue`	input, outbound	input, inbound
`MarkerHandle`	input, outbound	input, inbound
`return`	return, inbound	input, inbound

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

9.51.2 Constraints on the parameters

9.51.2.1 An outbound value of `BSPHandle` and `MarkerHandle` shall be a valid representation of an integer (see 7.4) in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer (see 7.4.3) in the same range.

9.51.2.2 An outbound value of `DbHandle` shall be a valid representation of an integer in the range −2147483648 to 2147483647. An inbound value shall be the canonical representation of an integer in the same range.

9.51.2.3 An outbound value of `KeyValue` shall be a valid representation of a UUID (see 7.6). An inbound value shall be the canonical representation of a UUID (see 7.6.3).

© ISO/IEC 2017 – All rights reserved

9.51.2.4 An outbound value of `return` shall be a valid representation of an integer in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer in the same range.

9.51.3 Function invocation input

9.51.3.1 The integer represented by the outbound value of `BSPHandle`, `DbHandle`, and `MarkerHandle` shall be assigned to the native parameter with the same name.

9.51.3.2 The UUID represented by the outbound value of `KeyValue` shall be written to a variable of type `BioAPI_UUID`, whose address shall be assigned to the native parameter `KeyValue`.

9.51.4 Function invocation output

There are no output parameters.

9.51.5 Bound activity invocation input

9.51.5.1 The inbound value of `BSPHandle`, `DbHandle`, and `MarkerHandle` shall be the canonical representation of the integer in the native parameter with the same name.

9.51.5.2 The inbound value of `KeyValue` shall be the canonical representation of the UUID in the variable of type `BioAPI_UUID` pointed to by the native parameter `KeyValue`.

9.51.5.3 The inbound value of `return` shall be the canonical representation of the integer returned by the native function.

9.51.5.4 The inbound values of the other input parameters shall be determined as specified in 9.35.4.

9.51.6 Bound activity invocation output

There are no output parameters.

9.52 BioAPI_DbFreeMarker

9.52.1 Function invocation scheme

This function belongs to the BioAPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioAPI_DbFreeMarker(

BioAPI_HANDLE BSPHandle,

BioAPI_DB_MARKER_HANDLE MarkerHandle);

and the following parameters (see Table 60).

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

Table 60

Parameter	Function invocation (conformance testing model for frameworks)	Bound activity invocation (conformance testing model for applications)
`BSPHandle`	input, outbound	input, inbound
`MarkerHandle`	input, outbound	input, inbound
`return`	return, inbound	input, inbound

9.52.2 Constraints on the parameters

9.52.2.1 An outbound value of `BSPHandle` and `MarkerHandle` shall be a valid representation of an integer (see 7.4) in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer (see 7.4.3) in the same range.

9.52.2.2 An outbound value of `return` shall be a valid representation of an integer in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer in the same range.

9.52.3 Function invocation input

The integer represented by the outbound value of `BSPHandle` and `MarkerHandle` shall be assigned to the native parameter with the same name.

9.52.4 Function invocation output

There are no output parameters.

9.52.5 Bound activity invocation input

9.52.5.1 The inbound value of `BSPHandle` and `MarkerHandle` shall be the canonical representation of the integer in the native parameter with the same name.

9.52.5.2 The inbound value of `return` shall be the canonical representation of the integer returned by the native function.

9.52.6 Bound activity invocation output

There are no output parameters.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.53 BioAPI_DbStoreBIR

9.53.1 Function invocation scheme

This function belongs to the BioAPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioAPI_DbStoreBIR(

BioAPI_HANDLE BSPHandle,

const BioAPI_INPUT_BIR *BIRToStore,

BioAPI_DB_HANDLE DbHandle,

BioAPI_UUID *BirUuid);

and the following parameters (see Table 61).

Table 61

Parameter	Function invocation (conformance testing model for frameworks)	Bound activity invocation (conformance testing model for applications)
`BSPHandle`	input, outbound	input, inbound
the members of the parameter group "Input BIR" (see 9.2.16) with their names prefixed by "`BIRToStore_`"	input, outbound	input, inbound
`DBHandle`	input, outbound	input, inbound
`no_BirUuid`	input, outbound	input, inbound
`BirUuid`	output, inbound	input, inbound
`return`	return, inbound	input, inbound

9.53.2 Constraints on the parameters

9.53.2.1 An outbound value of `BSPHandle` shall be a valid representation of an integer (see 7.4) in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer (see 7.4.3) in the same range.

9.53.2.2 An outbound value of the parameter group "Input BIR" shall be a valid representation of a value of the native type `BioAPI_INPUT_BIR`. An inbound value shall be the canonical representation of a value of that type.

9.53.2.3 An outbound value of `DbHandle` shall be a valid representation of an integer in the range −2147483648 to 2147483647. An inbound value shall be the canonical representation of an integer in the same range.

9.53.2.4 An outbound value of `no_BirUuid` shall be either a valid representation of a Boolean (see 7.5) or an empty string. An inbound value shall be the canonical representation of a Boolean (see 7.5.2).

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.53.2.5 An outbound value of `BirUuid` shall be either a valid representation of a UUID (see 7.6) or an empty string. An inbound value shall be either the canonical representation of a UUID (see 7.6.3) or an empty string.

9.53.2.6 An outbound value of `return` shall be a valid representation of an integer in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer in the same range.

9.53.3 Function invocation input

9.53.3.1 The integer represented by the outbound value of `BSPHandle` and `DbHandle` shall be assigned to the native parameter with the same name.

9.53.3.2 The value of type `BioAPI_INPUT_BIR` represented (see 9.2.16.4) by the outbound value of the parameter group "Input BIR" shall be written to a variable of type `BioAPI_INPUT_BIR`, whose address shall be assigned to the native parameter `BIRToStore`.

9.53.3.3 If the outbound value of `no_BirUuid` is "`true`", then the native parameter `BirUuid` shall be set to NULL; otherwise, it shall be set to the address of a variable of type `BioAPI_UUID`.

9.53.4 Function invocation output

The inbound value of `BirUuid` shall be determined as follows. If the native parameter with the same name is NULL, then the inbound value shall be an empty string. Otherwise, the inbound value shall be the canonical representation of the UUID in the variable of type `BioAPI_UUID` pointed to by the native parameter `BirUuid`.

9.53.5 Bound activity invocation input

9.53.5.1 The inbound value of `BSPHandle` and `DbHandle` shall be the canonical representation of the integer in the native parameter with the same name.

9.53.5.2 The inbound value of the parameter group "Input BIR" shall be the canonical representation (see 9.2.16.5) of the value of type `BioAPI_INPUT_BIR` in the variable pointed to by the native parameter `BIRToStore`.

9.53.5.3 The inbound value of `no_BirUuid` shall be "`true`" if the native parameter `BirUuid` is NULL; otherwise, it shall be "`false`".

9.53.5.4 The inbound value of `return` shall be the canonical representation of the integer returned by the native function.

9.53.5.5 The inbound values of the other input parameters shall be determined as specified in 9.37.4.

9.53.6 Bound activity invocation output

There are no output parameters.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.54 BioAPI_DbGetBIR

9.54.1 Function invocation scheme

This function belongs to the BioAPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioAPI_DbGetBIR(

BioAPI_HANDLE BSPHandle,

BioAPI_DB_HANDLE DbHandle,

const BioAPI_UUID *KeyValue,

BioAPI_BIR_HANDLE *RetrievedBIR,

BioAPI_DB_MARKER_HANDLE *MarkerHandle);

and the following parameters (see Table 62).

Table 62

Parameter	Function invocation (conformance testing model for frameworks)	Bound activity invocation (conformance testing model for applications)
`BSPHandle`	input, outbound	input, inbound
`DbHandle`	input, outbound	input, inbound
`KeyValue`	input, outbound	input, inbound
`no_RetrievedBIR`	input, outbound	input, inbound
`no_MarkerHandle`	input, outbound	input, inbound
`RetrievedBIR`	output, inbound	input, inbound
`MarkerHandle`	output, inbound	input, inbound
`return`	return, inbound	input, inbound

9.54.2 Constraints on the parameters

9.54.2.1 An outbound value of `BSPHandle` shall be a valid representation of an integer (see 7.4) in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer (see 7.4.3) in the same range.

9.54.2.2 An outbound value of `DbHandle` shall be a valid representation of an integer in the range −2147483648 to 2147483647. An inbound value shall be the canonical representation of an integer in the same range.

9.54.2.3 An outbound value of `KeyValue` shall be a valid representation of a UUID (see 7.6). An inbound value shall be the canonical representation of a UUID (see 7.6.3).

9.54.2.4 An outbound value of `no_RetrievedBIR` and `no_MarkerHandle` shall be either a valid representation of a Boolean (see 7.5) or an empty string. An inbound value shall be the canonical representation of a Boolean (see 7.5.2).

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.54.2.5 An outbound value of `RetrievedBIR` shall be either a valid representation of an integer in the range −2147483648 to 2147483647 or an empty string. An inbound value shall be the canonical representation of an integer in the same range or an empty string.

9.54.2.6 An outbound value of `MarkerHandle` shall be either a valid representation of an integer in the range 0 to 4294967295 or an empty string. An inbound value shall be the canonical representation of an integer in the same range or an empty string.

9.54.2.7 An outbound value of `return` shall be a valid representation of an integer in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer in the same range.

9.54.3 Function invocation input

9.54.3.1 The integer represented by the outbound value of `BSPHandle` and `DbHandle` shall be assigned to the native parameter with the same name.

9.54.3.2 The UUID represented by the outbound value of `KeyValue` shall be written to a variable of type `BioAPI_UUID`, whose address shall be assigned to the native parameter `KeyValue`.

9.54.3.3 If the outbound value of `no_RetrievedBIR` is "`true`", then the native parameter `RetrievedBIR` shall be set to NULL; otherwise, it shall be set to the address of a variable of type `BioAPI_BIR_HANDLE`.

9.54.3.4 If the outbound value of `no_MarkerHandle` is "`true`", then the native parameter `MarkerHandle` shall be set to NULL; otherwise, it shall be set to the address of a variable of type `BioAPI_DB_MARKER_HANDLE`.

9.54.4 Function invocation output

9.54.4.1 The inbound value of `RetrievedBIR` shall be determined as follows. If the native parameter with the same name is NULL, then the inbound value shall be an empty string. Otherwise, the inbound value shall be the canonical representation of the integer in the variable of type `BioAPI_BIR_HANDLE` pointed to by the native parameter `RetrievedBIR`.

9.54.4.2 The inbound value of `MarkerHandle` shall be determined as follows. If the native parameter with the same name is NULL, then the inbound value shall be an empty string. Otherwise, the inbound value shall be the canonical representation of the integer in the variable of type `BioAPI_DB_MARKER_HANDLE` pointed to by the native parameter `MarkerHandle`.

9.54.5 Bound activity invocation input

9.54.5.1 The inbound value of `BSPHandle` and `DbHandle` shall be the canonical representation of the integer in the native parameter with the same name.

9.54.5.2 The inbound value of `KeyValue` shall be the canonical representation of the UUID in the variable of type `BioAPI_UUID` pointed to by the native parameter `KeyValue`.

9.54.5.3 The inbound value of `no_RetrievedBIR` shall be "`true`" if the native parameter `RetrievedBIR` is NULL; otherwise, it shall be "`false`".

9.54.5.4 The inbound value of `no_MarkerHandle` shall be "`true`" if the native parameter `MarkerHandle` is NULL; otherwise, it shall be "`false`".

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.54.5.5 The inbound value of `return` shall be the canonical representation of the integer returned by the native function.

9.54.5.6 The inbound values of the other input parameters shall be determined as specified in 9.38.4.

9.54.6 Bound activity invocation output

There are no output parameters.

9.55 BioAPI_DbGetNextBIR

9.55.1 Function invocation scheme

This function belongs to the BioAPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioAPI_DbGetNextBIR(

BioAPI_HANDLE BSPHandle,

BioAPI_DB_HANDLE DbHandle,

BioAPI_DB_MARKER_HANDLE MarkerHandle,

BioAPI_BIR_HANDLE *RetrievedBIR,

BioAPI_UUID *BirUuid);

and the following parameters (see Table 63).

Table 63

Parameter	Function invocation (conformance testing model for frameworks)	Bound activity invocation (conformance testing model for applications)
`BSPHandle`	input, outbound	input, inbound
`DbHandle`	input, outbound	input, inbound
`MarkerHandle`	input, outbound	input, inbound
`no_RetrievedBIR`	input, outbound	input, inbound
`no_BirUuid`	input, outbound	input, inbound
`RetrievedBIR`	output, inbound	input, inbound
`BirUuid`	output, inbound	input, inbound
`return`	return, inbound	input, inbound

9.55.2 Constraints on the parameters

9.55.2.1 An outbound value of `BSPHandle` and `MarkerHandle` shall be a valid representation of an integer (see 7.4) in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer (see 7.4.3) in the same range.

9.55.2.2 An outbound value of `DbHandle` shall be a valid representation of an integer in the range −2147483648 to 2147483647. An inbound value shall be the canonical representation of an integer in the same range.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

 © ISO/IEC 2017 – All rights reserved

9.55.2.3 An outbound value of `no_RetrievedBIR` and `no_BirUuid` shall be either a valid representation of a Boolean (see 7.5) or an empty string. An inbound value shall be the canonical representation of a Boolean (see 7.5.2).

9.55.2.4 An outbound value of `RetrievedBIR` shall be either a valid representation of an integer in the range –2147483648 to 2147483647 or an empty string. An inbound value shall be the canonical representation of an integer in the same range or an empty string.

9.55.2.5 An outbound value of `BirUuid` shall be either a valid representation of a UUID (see 7.6) or an empty string. An inbound value shall be either the canonical representation of a UUID (see 7.6.3) or an empty string.

9.55.2.6 An outbound value of `return` shall be a valid representation of an integer in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer in the same range.

9.55.3 Function invocation input

9.55.3.1 The integer represented by the outbound value of `BSPHandle`, `DbHandle`, and `MarkerHandle` shall be assigned to the native parameter with the same name.

9.55.3.2 If the outbound value of `no_RetrievedBIR` is "`true`", then the native parameter `RetrievedBIR` shall be set to NULL; otherwise, it shall be set to the address of a variable of type `BioAPI_BIR_HANDLE`.

9.55.3.3 If the outbound value of `no_BirUuid` is "`true`", then the native parameter `BirUuid` shall be set to NULL; otherwise, it shall be set to the address of a variable of type `BioAPI_UUID`.

9.55.4 Function invocation output

9.55.4.1 The inbound value of `RetrievedBIR` shall be determined as follows. If the native parameter with the same name is NULL, then the inbound value shall be an empty string. Otherwise, the inbound value shall be the canonical representation of the integer in the variable of type `BioAPI_BIR_HANDLE` pointed to by the native parameter `RetrievedBIR`.

9.55.4.2 The inbound value of `BirUuid` shall be determined as follows. If the native parameter with the same name is NULL, then the inbound value shall be an empty string. Otherwise, the inbound value shall be the canonical representation of the UUID in the variable of type `BioAPI_UUID` pointed to by the native parameter `BirUuid`.

9.55.5 Bound activity invocation input

9.55.5.1 The inbound value of `BSPHandle`, `DbHandle`, and `MarkerHandle` shall be the canonical representation of the integer in the native parameter with the same name.

9.55.5.2 The inbound value of `no_RetrievedBIR` shall be "`true`" if the native parameter `RetrievedBIR` is NULL; otherwise, it shall be "`false`".

9.55.5.3 The inbound value of `no_BirUuid` shall be "`true`" if the native parameter `BirUuid` is NULL; otherwise, it shall be "`false`".

9.55.5.4 The inbound value of `return` shall be the canonical representation of the integer returned by the native function.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.55.5.5 The inbound values of the other input parameters shall be determined as specified in 9.39.4.

9.55.6 Bound activity invocation output

There are no output parameters.

9.56 BioAPI_DbDeleteBIR

9.56.1 Function invocation scheme

This function belongs to the BioAPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioAPI_DbDeleteBIR(

BioAPI_HANDLE BSPHandle,

BioAPI_DB_HANDLE DbHandle,

const BioAPI_UUID *KeyValue);

and the following parameters (see Table 64).

Table 64

Parameter	Function invocation (conformance testing model for frameworks)	Bound activity invocation (conformance testing model for applications)
`BSPHandle`	input, outbound	input, inbound
`DbHandle`	input, outbound	input, inbound
`KeyValue`	input, outbound	input, inbound
`return`	return, inbound	input, inbound

9.56.2 Constraints on the parameters

9.56.2.1 An outbound value of `BSPHandle` shall be a valid representation of an integer (see 7.4) in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer (see 7.4.3) in the same range.

9.56.2.2 An outbound value of `DbHandle` shall be a valid representation of an integer in the range -2147483648 to 2147483647. An inbound value shall be the canonical representation of an integer in the same range.

9.56.2.3 An outbound value of `KeyValue` shall be a valid representation of a UUID (see 7.6). An inbound value shall be the canonical representation of a UUID (see 7.6.3).

9.56.2.4 An outbound value of `return` shall be a valid representation of an integer in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer in the same range.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.56.3 Function invocation input

9.56.3.1 The integer represented by the outbound value of `BSPHandle` and `DbHandle` shall be assigned to the native parameter with the same name.

9.56.3.2 The UUID represented by the outbound value of `KeyValue` shall be written to a variable of type `BioAPI_UUID`, whose address shall be assigned to the native parameter `KeyValue`.

9.56.4 Function invocation output

There are no output parameters.

9.56.5 Bound activity invocation input

9.56.5.1 The inbound value of `BSPHandle` and `DbHandle` shall be the canonical representation of the integer in the native parameter with the same name.

9.56.5.2 The inbound value of `KeyValue` shall be the canonical representation of the UUID in the variable of type `BioAPI_UUID` pointed to by the native parameter `KeyValue`.

9.56.5.3 The inbound value of `return` shall be the canonical representation of the integer returned by the native function.

9.56.6 Bound activity invocation output

There are no output parameters.

9.57 BioAPI_SetPowerMode

9.57.1 Function invocation scheme

This function belongs to the BioAPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioAPI_SetPowerMode(

BioAPI_HANDLE BSPHandle,

BioAPI_UNIT_ID UnitID,

BioAPI_POWER_MODE PowerMode);

and the following parameters (see Table 65).

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

Table 65

Parameter	Function invocation (conformance testing model for frameworks)	Bound activity invocation (conformance testing model for applications)
`BSPHandle`	input, outbound	input, inbound
`UnitID`	input, outbound	input, inbound
`PowerMode`	input, outbound	input, inbound
`return`	return, inbound	input, inbound

9.57.2 Constraints on the parameters

9.57.2.1 An outbound value of `BSPHandle`, `UnitID`, and `PowerMode` shall be a valid representation of an integer (see 7.4) in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer (see 7.4.3) in the same range.

9.57.2.2 An outbound value of `return` shall be a valid representation of an integer in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer in the same range.

9.57.3 Function invocation input

The integer represented by the outbound value of `BSPHandle_UnitID` and `PowerMode` shall be assigned to the native parameter with the same name. The available power mode values are indicated in `BioAPI_VALUE_POWER_MODE_MASK` in the `BSPSchema`. If a power mode value not supported by the BSP is specified by the application, this function returns `BioAPIERR_INVALID_PARAMETER`.

9.57.4 Function invocation output

There are no output parameters.

9.57.5 Bound activity invocation input

9.57.5.1 The inbound value of `BSPHandle_UnitID` and `PowerMode` shall be the canonical representation of the integer in the native parameter with the same name.

9.57.5.2 The inbound value of `return` shall be the canonical representation of the integer returned by the native function.

9.57.6 Bound activity invocation output

There are no output parameters.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.58 BioAPI_SetIndicatorStatus

9.58.1 Function invocation scheme

This function belongs to the BioAPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioAPI_SetIndicatorStatus(

BioAPI_HANDLE BSPHandle,

BioAPI_UNIT_ID UnitID,

BioAPI_INDICATOR_STATUS IndicatorStatus);

and the following parameters (see Table 66).

Table 66

Parameter	Function invocation (conformance testing model for frameworks)	Bound activity invocation (conformance testing model for applications)
`BSPHandle`	input, outbound	input, inbound
`UnitID`	input, outbound	input, inbound
`IndicatorStatus`	input, outbound	input, inbound
`return`	return, inbound	input, inbound

9.58.2 Constraints on the parameters

9.58.2.1 An outbound value of `BSPHandle` and `UnitID` shall be a valid representation of an integer (see 7.4) in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer (see 7.4.3) in the same range.

9.58.2.2 An outbound value of `IndicatorStatus` shall be a valid representation of an integer in the range 0 to 255. An inbound value shall be the canonical representation of an integer in the same range.

9.58.2.3 An outbound value of return shall be a valid representation of an integer in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer in the same range.

9.58.3 Function invocation input

The integer represented by the outbound value of `BSPHandle`, `UnitID`, and `IndicatorStatus` shall be assigned to the native parameter with the same name.

9.58.4 Function invocation output

There are no output parameters.

9.58.5 Bound activity invocation input

9.58.5.1 The inbound value of `BSPHandle`, `UnitID` and `IndicatorStatus` shall be the canonical representation of the integer in the native parameter with the same name.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.58.5.2 The inbound value of `return` shall be the canonical representation of the integer returned by the native function.

9.58.6 Bound activity invocation output

There are no output parameters.

9.59 BioAPI_GetIndicatorStatus

9.59.1 Function invocation scheme

This function belongs to the BioAPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioAPI_GetIndicatorStatus(

BioAPI_HANDLE BSPHandle,

BioAPI_UNIT_ID UnitID,

BioAPI_INDICATOR_STATUS *IndicatorStatus);

and the following parameters (see Table 67).

Table 67

Parameter	Function invocation (conformance testing model for frameworks)	Bound activity invocation (conformance testing model for applications)
`BSPHandle`	input, outbound	input, inbound
`UnitID`	input, outbound	input, inbound
`no_IndicatorStatus`	input, outbound	input, inbound
`IndicatorStatus`	output, inbound	input, inbound
`return`	return, inbound	input, inbound

9.59.2 Constraints on the parameters

9.59.1.1 An outbound value of `BSPHandle` and `UnitID` shall be a valid representation of an integer (see 7.4) in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer (see 7.4.3) in the same range.

9.59.1.2 An outbound value of `no_IndicatorStatus` shall be either a valid representation of a Boolean (see 7.5) or an empty string. An inbound value shall be the canonical representation of a Boolean (see 7.5.2).

9.59.1.3 An outbound value of `IndicatorStatus` shall be either a valid representation of an integer in the range 0 to 255 or an empty string. An inbound value shall be either the canonical representation of an integer in the same range or an empty string.

9.59.1.4 An outbound value of `return` shall be a valid representation of an integer in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer in the same range.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

 © ISO/IEC 2017 – All rights reserved

9.59.3 Function invocation input

9.59.3.1 The integer represented by the outbound value of `BSPHandle` and `UnitID` shall be assigned to the native parameter with the same name.

9.59.3.2 If the outbound value of `no_IndicatorStatus` is "`true`", then the native parameter IndicatorStatus shall be set to NULL; otherwise, it shall be set to the address of a variable of type `BioAPI_INDICATOR_STATUS`.

9.59.4 Function invocation output

The inbound value of `IndicatorStatus` shall be determined as follows. If the native parameter with the same name is NULL, then the inbound value shall be an empty string. Otherwise, the inbound value shall be the canonical representation of the integer in the variable of type `BioAPI_INDICATOR_STATUS` pointed to by the native parameter `IndicatorStatus`.

9.59.5 Bound activity invocation input

9.59.5.1 The inbound value of `BSPHandle` and `UnitID` shall be the canonical representation of the integer in the native parameter with the same name.

9.59.5.2 The inbound value of `no_IndicatorStatus` shall be "`true`" if the native parameter IndicatorStatus is NULL; otherwise, it shall be "`false`".

9.59.5.3 The inbound value of `return` shall be the canonical representation of the integer returned by the native function.

9.59.5.4 The inbound values of the other input parameters shall be determined as specified in 9.43.4.

9.59.6 Bound activity invocation output

There are no output parameters.

9.60 BioAPI_CalibrateSensor

9.60.1 Function invocation scheme

This function belongs to the BioAPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioAPI_CalibrateSensor(

BioAPI_HANDLE BSPHandle,

int32_t Timeout);

and the following parameters (see Table 68).

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

Table 68

Parameter	Function invocation (conformance testing model for frameworks)	Bound activity invocation (conformance testing model for applications)
`BSPHandle`	input, outbound	input, inbound
`Timeout`	input, outbound	input, inbound
`return`	return, inbound	input, inbound

9.60.2 Constraints on the parameters

9.60.2.1 An outbound value of `BSPHandle` shall be a valid representation of an integer (see 7.4) in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer (see 7.4.3) in the same range.

9.60.2.2 An outbound value of `Timeout` shall be a valid representation of an integer (see 7.4) in the range −2147483648 to 2147483647. An inbound value shall be the canonical representation of an integer (see 7.4.3) in the same range.

9.60.2.3 An outbound value of `return` shall be a valid representation of an integer in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer in the same range.

9.60.3 Function invocation input

The integer represented by the outbound value of `BSPHandle` and `Timeout` shall be assigned to the native parameter with the same name.

9.60.4 Function invocation output

There are no output parameters.

9.60.5 Bound activity invocation input

9.60.5.1 The inbound value of `BSPHandle` and `Timeout` shall be the canonical representation of the integer in the native parameter with the same name.

9.60.5.2 The inbound value of `return` shall be the canonical representation of the integer returned by the native function.

9.60.6 Bound activity invocation output

There are no output parameters.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.61 BioAPI_Cancel

9.61.1 Function invocation scheme

This function belongs to the BioAPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioAPI_Cancel(

BioAPI_HANDLE BSPHandle);

and the following parameters (see Table 69).

Table 69

Parameter	Function invocation (conformance testing model for frameworks)	Bound activity invocation (conformance testing model for applications)
`BSPHandle`	input, outbound	input, inbound
`return`	return, inbound	input, inbound

9.61.2 Constraints on the parameters

9.61.2.1 An outbound value of `BSPHandle` shall be a valid representation of an integer (see 7.4) in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer (see 7.4.3) in the same range.

9.61.2.2 An outbound value of `return` shall be a valid representation of an integer in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer in the same range.

9.61.3 Function invocation input

The integer represented by the outbound value of `BSPHandle` shall be assigned to the native parameter with the same name.

9.61.4 Function invocation output

There are no output parameters.

9.61.5 Bound activity invocation input

9.61.5.1 The inbound value of `BSPHandle` shall be the canonical representation of the integer in the native parameter with the same name.

9.61.5.2 The inbound value of `return` shall be the canonical representation of the integer returned by the native function.

9.61.6 Bound activity invocation output

There are no output parameters.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.62 BioAPI_Free

9.62.1 Function invocation scheme

This function belongs to the BioAPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioAPI_Free(

void* Ptr);

and the following parameters (see Table 70).

Table 70

Parameter	Function invocation (conformance testing model for frameworks)	Bound activity invocation (conformance testing model for applications)
`Ptr`	input, outbound	input, inbound
`return`	return, inbound	input, inbound

9.62.2 Constraints on the parameters

9.62.2.1 An outbound value of `Ptr` shall be a valid representation of an integer (see 7.4) in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer (see 7.4.3) in the same range.

9.62.2.2 An outbound value of `return` shall be a valid representation of an integer in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer in the same range.

9.62.3 Function invocation input

The integer represented by the outbound value of `Ptr` shall be assigned to the native parameter with the same name.

9.62.4 Function invocation output

There are no output parameters.

9.62.5 Bound activity invocation input

9.62.5.1 The inbound value of `Ptr` shall be the canonical representation of the pointer (interpreted as an integer) in the native parameter with the same name.

9.62.5.2 The inbound value of `return` shall be the canonical representation of the integer returned by the native function.

9.62.6 Bound activity invocation output

There are no output parameters.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

 © ISO/IEC 2017 – All rights reserved

9.63 BioAPI_Util_InstallBSP

9.63.1 Function invocation scheme

This function belongs to the BioAPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioAPI_Util_InstallBSP (

BioAPI_INSTALL_ACTION Action,

BioAPI_INSTALL_ERROR *Error,

const BioAPI_BSP_SCHEMA *BSPSchema);

and the following parameters (see Table 71).

Table 71

Parameter	Function invocation (conformance testing model for frameworks)	Bound activity invocation (conformance testing model for applications)
`Action`	input, outbound	input, inbound
`no_Error`	input, outbound	input, inbound
the members of the parameter group "BSP schema" (see 9.2.11)	input, outbound	input, inbound
`ErrorCode`	output, inbound	input, inbound
`ErrorString`	output, inbound	input, inbound
`return`	return, inbound	input, inbound

9.63.2 Constraints on the parameters

9.63.2.1 An outbound value of `Action` shall be a valid representation of an integer (see 7.4) in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer (see 7.4.3) in the same range.

9.63.2.2 An outbound value of `no_Error` shall be either a valid representation of a Boolean (see 7.5) or an empty string. An inbound value shall be the canonical representation of a Boolean (see 7.5.2).

9.63.2.3 An outbound value of the parameter group "BSP schema" shall be a valid representation of a value of the native type `BioAPI_BSP_SCHEMA`. An inbound value shall be either the canonical representation of a value of that type or a set of empty strings.

9.63.2.4 An outbound value of `Update` shall be a valid representation of a Boolean. An inbound value shall be the canonical representation of a Boolean.

9.63.2.5 An outbound value of `HostingEndpointIRI` shall be a valid representation of an integer (see 7.4) in the range 0 to 255. An inbound value shall be the canonical representation of an integer (see 7.4.3) in the same range.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.63.2.6 An outbound value of `ErrorCode` shall be either a valid representation of an integer in the range 0 to 4294967295 or an empty string. An inbound value shall be either the canonical representation of an integer in the same range or an empty string.

9.63.2.7 An outbound or inbound value of `ErrorString` shall be a valid representation of a character string, whose UTF-8 encoding is no longer than 268 octets and which does not contain any NULL (0) characters.

9.63.2.8 An outbound value of `return` shall be a valid representation of an integer in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer in the same range.

9.63.3 Function invocation input

9.63.3.1 The integer represented by the outbound value of `Action` shall be assigned to the native parameter with the same name.

9.63.3.2 If the outbound value of `no_Error` is "`true`", then the native parameter `Error` shall be set to NULL; otherwise, it shall be set to the address of a variable of type `BioAPI_INSTALL_ERROR`.

9.63.3.3 The value of type `BioAPI_BSP_SCHEMA` represented (see 9.2.11.4) by the outbound value of the parameter group "BSP schema" shall be written to a variable of type `BioAPI_BSP_SCHEMA`, whose address shall be assigned to the native parameter `BSPSchema`.

9.63.4 Function invocation output

The inbound value of `ErrorCode` and `ErrorString` shall be determined as follows. If the native parameter `Error` is NULL, then the inbound value shall be an empty string. Otherwise, the inbound value of `ErrorCode` shall be the canonical representation of the integer in the field `ErrorCode` of the variable of type `BioAPI_INSTALL_ERROR` pointed to by the native parameter `Error` and the inbound value of `ErrorString` shall be the character string in the field `ErrorString` of that variable.

9.63.5 Bound activity invocation input

9.63.5.1 The inbound value of `Action` shall be the canonical representation of the integer in the native parameter with the same name.

9.63.5.2 The inbound value of `no_Error` shall be "`true`" if the native parameter `Error` is NULL; otherwise, it shall be "`false`".

9.63.5.3 The inbound value of the parameter group "BSP schema" shall be the canonical representation (see 9.2.11.5) of the value of type `BioAPI_BSP_SCHEMA` in the variable pointed to by the native parameter `BSPSchema`.

9.63.5.4 The inbound value of `return` shall be the canonical representation of the integer returned by the native function.

9.63.5.5 The inbound values of the other input parameters shall be determined as specified in 9.47.4.

9.63.6 Bound activity invocation output

There are no output parameters.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.64 BioAPI_Util_InstallBFP

9.64.1 Function invocation scheme

This function belongs to the BioAPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioAPI_Util_InstallBFP (

BioAPI_INSTALL_ACTION Action,

BioAPI_INSTALL_ERROR *Error,

const BioAPI_BFP_SCHEMA *BFPSchema);

and the following parameters (see Table 72).

Table 72

Parameter	Function invocation (conformance testing model for frameworks)	Bound activity invocation (conformance testing model for applications)
`no_Error`	input, outbound	input, inbound
the members of the parameter group "BFP schema" (see 9.2.12)	input, outbound	input, inbound
`ErrorCode`	output, inbound	input, inbound
`ErrorString`	output, inbound	input, inbound
`return`	return, inbound	input, inbound

9.64.2 Constraints on the parameters

9.64.2.1 An outbound value of `Action` shall be a valid representation of an integer (see 7.4) in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer (see 7.4.3) in the same range.

9.64.2.2 An outbound value of `no_Error` shall be either a valid representation of a Boolean (see 7.5) or an empty string. An inbound value shall be the canonical representation of a Boolean (see 7.5.2).

9.64.2.3 An outbound value of the parameter group "BFP schema" shall be a valid representation of a value of the native type `BioAPI_BFP_SCHEMA`. An inbound value shall be either the canonical representation of a value of that type or a set of empty strings.

9.64.2.4 An outbound value of `ErrorCode` shall be either a valid representation of an integer in the range 0 to 4294967295 or an empty string. An inbound value shall be either the canonical representation of an integer in the same range or an empty string.

9.64.2.5 An outbound or inbound value of `ErrorString` shall be a valid representation of a character string, whose UTF-8 encoding is no longer than 268 octets and which does not contain any NULL (0) characters.

9.64.2.6 An outbound value of `return` shall be a valid representation of an integer in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer in the same range.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.64.3 Function invocation input

9.64.3.1 The integer represented by the outbound value of `Action` shall be assigned to the native parameter with the same name.

9.64.3.2 If the outbound value of `no_Error` is "`true`", then the native parameter `Error` shall be set to NULL; otherwise, it shall be set to the address of a variable of type `BioAPI_INSTALL_ERROR`.

9.64.3.3 The value of type `BioAPI_BFP_SCHEMA` represented (see 9.2.11.4) by the outbound value of the parameter group "BFP schema" shall be written to a variable of type `BioAPI_BFP_SCHEMA`, whose address shall be assigned to the native parameter `BFPSchema`.

9.64.4 Function invocation output

The inbound value of `ErrorCode` and `ErrorString` shall be determined as follows. If the native parameter `Error` is NULL, then the inbound value shall be an empty string. Otherwise, the inbound value of `ErrorCode` shall be the canonical representation of the integer in the field `ErrorCode` of the variable of type `BioAPI_INSTALL_ERROR` pointed to by the native parameter `Error` and the inbound value of `ErrorString` shall be the character string in the field `ErrorString` of that variable.

9.64.5 Bound activity invocation input

9.64.5.1 The inbound value of `Action` shall be the canonical representation of the integer in the native parameter with the same name.

9.64.5.2 The inbound value of `no_Error` shall be "`true`" if the native parameter `Error` is NULL; otherwise, it shall be "`false`".

9.64.5.3 The inbound value of the parameter group "BFP schema" shall be the canonical representation (see 9.2.11.5) of the value of type `BioAPI_BFP_SCHEMA` in the variable pointed to by the native parameter `BFPSchema`.

9.64.5.4 The inbound value of `return` shall be the canonical representation of the integer returned by the native function.

9.64.5.5 The inbound values of the other input parameters shall be determined as specified in 9.48.4.

9.64.6 Bound activity invocation output

There are no output parameters.

9.65 BioSPI_BSPLoad

9.65.1 Function invocation scheme

This function belongs to the BioSPI interface and has the following native prototype:

BioAPI_RETURN BioAPI BioSPI_BSPLoad(

const BioAPI_UUID *BSPUuid,

BioSPI_EventHandler BioAPINotifyCallback,

BioSPI_BFP_ENUMERATION_HANDLER BFPEnumerationHandler,

BioSPI_MEMORY_FREE_HANDLER MemoryFreeHandler);

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

 © ISO/IEC 2017 – All rights reserved

and the following parameters (see Table 73).

Table 73

Parameter	Function invocation (conformance testing model for BSPs)	Bound activity invocation (conformance testing model for frameworks)
`BSPUuid`	input, outbound	input, inbound
`BioAPINotifyCallback`	input, outbound	input, inbound
`BFPEnumerationHandler`	input, outbound	input, inbound
`MemoryFreeHandler`	input, outbound	input, inbound
`return`	return, inbound	output, outbound

9.65.2 Constraints on the parameters

9.65.2.1 An outbound value of `BSPUuid` shall be a valid representation of a UUID (see 7.6). An inbound value shall be the canonical representation of a UUID (see 7.6.3).

9.65.2.2 An outbound value of `BioAPINotifyCallback`, `BFPEnumerationHandler`, and `MemoryFreeHandler` shall be either "`0`" or "`*`". An inbound value shall be the canonical representation of an integer (see 7.4.3) in the range 0 to 4294967295.

9.65.2.3 An outbound value of `return` shall be a valid representation of an integer in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer in the same range.

9.65.3 Function invocation input

9.65.3.1 The UUID represented by the outbound value of `BSPUuid` shall be written to a variable of type `BioAPI_UUID`, whose address shall be assigned to the native parameter BSPUuid.

9.65.3.2 If the outbound value of `BioAPINotifyCallback` is "`0`", a NULL pointer value shall be assigned to the native parameter `BioAPINotifyCallback`. If it is "`*`", a non-NULL pointer value, which is the address of a native function (within the testing component) implementing the standard BioAPI interface function `BioSPI_EventHandler`, shall be assigned to the native parameter `BioAPINotifyCallback`.

NOTE If the outbound value of `BioAPINotifyCallback` is not "`0`", any subsequent incoming calls to the standard BioAPI interface function `BioSPI_EventHandler` will result in an invocation of the activity bound to this function, if such a binding exists.

9.65.3.3 If the outbound value of `BFPEnumerationHandler` is "`0`", a NULL pointer value shall be assigned to the native parameter `BFPEnumerationHandler`. If it is "`*`", a non-NULL pointer value, which is the address of a native function (within the testing component) implementing the standard BioAPI interface function `BioSPI_BFP_ENUMERATION_HANDLER`, shall be assigned to the native parameter `BFPEnumerationHandler`.

NOTE If the outbound value of `BFPEnumerationHandler` is not "`0`", any subsequent incoming calls to the standard BioAPI interface function `BioSPI_BFP_ENUMERATION_HANDLER` will result in an invocation of the activity bound to this function, if such a binding exists.

9.65.3.4 If the outbound value of `MemoryFreeHandler` is "`0`", a NULL pointer value shall be assigned to the native parameter `MemoryFreeHandler`. If it is "`*`", a non-NULL pointer value, which is the address

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

of a native function (within the testing component) implementing the standard BioAPI interface function `BioSPI_MEMORY_FREE_HANDLER`, shall be assigned to the native parameter `MemoryFreeHandler`.

NOTE If the outbound value of `MemoryFreeHandler` is not "`0`", any subsequent incoming calls to the standard BioAPI interface function `BioSPI_MEMORY_FREE_HANDLER` will result in an invocation of the activity bound to this function, if such a binding exists.

9.65.4 Function invocation output

There are no output parameters.

9.65.5 Bound activity invocation input

9.65.5.1 The inbound value of `BSPUuid` shall be the canonical representation of the UUID in the variable of type `BioAPI_UUID` pointed to by the native parameter `BSPUuid`.

9.65.5.2 The inbound value of `BioAPINotifyCallback`, `BFPEnumerationHandler`, and `MemoryFreeHandler` shall be the canonical representation of the integer in the native parameter with the same name.

9.65.6 Bound activity invocation output

The integer represented by the outbound value of `return` shall be returned by the native function.

9.65.7 Default output

If there is no activity bound to this standard BioAPI interface function, the native function shall return zero.

9.66 BioSPI_BSPUnload

9.66.1 Function invocation scheme

This function belongs to the BioSPI interface and has the following native prototype:

BioAPI_RETURN BioAPI BioSPI_BSPUnload(

const BioAPI_UUID *BSPUuid);

and the following parameters (see Table 74).

Table 74

Parameter	Function invocation (conformance testing model for BSPs)	Bound activity invocation (conformance testing model for frameworks)
`BSPUuid`	input, outbound	input, inbound
`return`	return, inbound	output, outbound

9.66.2 Constraints on the parameters

9.66.2.1 An outbound value of `BSPUuid` shall be a valid representation of a UUID (see 7.6). An inbound value shall be the canonical representation of a UUID (see 7.6.3).

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.66.2.2 An outbound value of `return` shall be a valid representation of an integer in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer in the same range.

9.66.3 Function invocation input

The UUID represented by the outbound value of `BSPUuid` shall be written to a variable of type `BioAPI_UUID`, whose address shall be assigned to the native parameter `BSPUuid`.

9.66.4 Function invocation output

There are no output parameters.

9.66.5 Bound activity invocation input

The inbound value of `BSPUuid` shall be the canonical representation of the UUID in the variable of type `BioAPI_UUID` pointed to by the native parameter `BSPUuid`.

9.66.6 Bound activity invocation output

The integer represented by the outbound value of `return` shall be returned by the native function.

9.66.7 Default output

If there is no activity bound to this standard BioAPI interface function, the native function shall return zero.

9.67 BioSPI_BSPAttach

9.67.1 Function invocation scheme

This function belongs to the BioSPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioSPI_BSPAttach(

const BioAPI_UUID *BSPUuid,

BioAPI_VERSION Version,

const BioAPI_UNIT_LIST_ELEMENT *UnitList,

uint32_t NumUnits,

BioAPI_HANDLE BSPHandle);

and the following parameters (see Table 75).

Table 75

Parameter	Function invocation (conformance testing model for BSPs)	Bound activity invocation (conformance testing model for frameworks)
`BSPUuid`	input, outbound	input, inbound
`Version`	input, outbound	input, inbound
`Unit_1_UnitCategory`	input, outbound	input, inbound

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

Table 75 *(continued)*

Parameter	Function invocation (conformance testing model for BSPs)	Bound activity invocation (conformance testing model for frameworks)
`Unit_1_UnitID`	input, outbound	input, inbound
`Unit_2_UnitCategory`	input, outbound	input, inbound
`Unit_2_UnitID`	input, outbound	input, inbound
`Unit_3_UnitCategory`	input, outbound	input, inbound
`Unit_3_UnitID`	input, outbound	input, inbound
`Unit_4_UnitCategory`	input, outbound	input, inbound
`Unit_4_UnitID`	input, outbound	input, inbound
`SecurityProfileList`	input, outbound	input, inbound
`NumUnits`	input, outbound	input, inbound
`BSPHandle`	input, outbound	input, inbound
`return`	return, inbound	output, outbound

9.67.2 Constraints on the parameters

9.67.2.1 An outbound value of `BSPUuid` shall be a valid representation of a UUID (see 7.6). An inbound value shall be the canonical representation of a UUID (see 7.6.3).

9.67.2.2 An outbound value of `Version` shall be a valid representation of an integer (see 7.4) in the range 0 to 255. An inbound value shall be the canonical representation of an integer (see 7.4.3) in the same range.

9.67.2.3 An outbound value of `Unit_`*X*`_UnitCategory` and `Unit_`*X*`_UnitID` (with *X* = 1, 2, 3, or 4) shall be either a valid representation of an integer in the range 0 to 4294967295 or an empty string. An inbound value shall be either the canonical representation of an integer (see 7.4.3) in the same range or an empty string.

9.67.2.4 An outbound value of `NumUnits` shall be a valid representation of an integer in the range 0 to 4. An inbound value shall be the canonical representation of an integer in the range 0 to 4294967295.

9.67.2.5 An outbound value of `BSPHandle` shall be a valid representation of an integer (see 7.4) in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer (see 7.4.3) in the same range.

9.67.2.6 An outbound value of `return` shall be a valid representation of an integer in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer in the same range.

9.67.3 Function invocation input

9.67.3.1 The UUID represented by the outbound value of `BSPUuid` shall be written to a variable of type `BioAPI_UUID`, whose address shall be assigned to the native parameter `BSPUuid`.

9.67.3.2 The integer represented by the outbound value of `Version`, `NumUnits`, and `BSPHandle` shall be assigned to the native parameter with the same name.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.67.3.3 The integer represented by the outbound value of `Unit_X_UnitCategory` and `Unit_X_UnitID` (with *X* = 1, 2, 3, or 4), or zero if that value is an empty string, shall be written to the fields `UnitCategory` and `UnitID` (respectively) of the element at position *X* of an array of four elements of type `BioAPI_UNIT_LIST_ELEMENT`. The address of that array shall be assigned to the native parameter `UnitList`.

9.67.4 Function invocation output

There are no output parameters.

9.67.5 Bound activity invocation input

9.67.5.1 The inbound value of `BSPUuid` shall be the canonical representation of the UUID in the variable of type `BioAPI_UUID` pointed to by the native parameter `BSPUuid`.

9.67.5.2 The inbound value of `Version`, `NumUnits`, and `BSPHandle` shall be the canonical representation of the integer in the native parameter with the same name.

9.67.5.3 The inbound value of `Unit_X_UnitCategory` and `Unit_X_UnitID` (with *X* = 1, 2, 3 or 4) shall be determined as follows. If the native parameter `NumUnits` is less than *X*, then the inbound value shall be an empty string. Otherwise, the inbound value shall be the canonical representation of the integer in the fields `UnitCategory` and `UnitID` (respectively) of the element at position *X* of the array of elements of type `BioAPI_UNIT_LIST_ELEMENT` pointed to by the native parameter `UnitList`.

9.67.6 Bound activity invocation output

The integer represented by the outbound value of `return` shall be returned by the native function.

9.67.7 Default output

If there is no activity bound to this standard BioAPI interface function, the native function shall return zero.

9.68 BioSPI_BSPDetach

9.68.1 Function invocation scheme

This function belongs to the BioSPI interface and has the following native prototype:

BioAPI_RETURN BioAPI BioSPI_BSPDetach(

BioAPI_HANDLE BSPHandle);

and the following parameters (see Table 76).

Table 76

Parameter	Function invocation (conformance testing model for BSPs)	Bound activity invocation (conformance testing model for frameworks)
`BSPHandle`	input, outbound	input, inbound
`return`	return, inbound	output, outbound

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.68.2 Constraints on the parameters

9.68.2.1 An outbound value of `BSPHandle` shall be a valid representation of an integer (see 7.4) in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer (see 7.4.3) in the same range.

9.68.2.2 An outbound value of `return` shall be a valid representation of an integer in the range 0 to 4294967295. An inbound value shall be the canonical representation of an integer in the same range.

9.68.3 Function invocation input

The integer represented by the outbound value of `BSPHandle` shall be assigned to the native parameter with the same name.

9.68.4 Function invocation output

There are no output parameters.

9.68.5 Bound activity invocation input

The inbound value of `BSPHandle` shall be the canonical representation of the integer in the native parameter with the same name.

9.68.6 Bound activity invocation output

The integer represented by the outbound value of `return` shall be returned by the native function.

9.68.7 Default output

If there is no activity bound to this standard BioAPI interface function, the native function shall return zero.

9.69 BioSPI_QueryUnits

9.69.1 Function invocation scheme

This function belongs to the BioSPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioSPI_QueryUnits(

const BioAPI_UUID *BSPUuid,

BioAPI_UNIT_SCHEMA **UnitSchemaArray,

uint32_t *NumberOfElements);

and the following parameters (see Table 77).

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

Table 77

Parameter	Function invocation (conformance testing model for BSPs)	Bound activity invocation (conformance testing model for frameworks)
`BSPUuid`	input, outbound	input, inbound
`no_UnitSchemaArray`	input, outbound	input, inbound
the members of the parameter group "Unit schema" (see 9.2.13) with their names prefixed by "`UnitSchema_1_`"	output, inbound	output, outbound
the members of the parameter group "Unit schema" with their names prefixed by "`UnitSchema_2_`"	output, inbound	output, outbound
the members of the parameter group "Unit schema" with their names prefixed by "`UnitSchema_3_`"	output, inbound	output, outbound
the members of the parameter group "Unit schema" with their names prefixed by "`UnitSchema_4_`"	output, inbound	output, outbound
`no_NumberOfElements`	input, outbound	input, inbound
`NumberOfElements`	output, inbound	output, outbound
`return`	return, inbound	output, outbound

The specification of the constraints on the parameters, function invocation input, function invocation output, and bound activity invocation input of the function `BioAPI_QueryUnits` also applies to this standard BioAPI interface function.

9.69.2 Bound activity invocation output

9.69.2.1 If the native parameter `UnitSchemaArray` is not NULL and the integer (say, *N*) represented by the outbound value of `NumberOfElements` is greater than 0, then a memory block of sufficient size to contain an array of *N* elements of type `BioAPI_UNIT_SCHEMA` shall be allocated and its address shall be written to the variable pointed to by the native parameter `UnitSchemaArray`.

9.69.2.2 The outbound value of the parameter group "Unit schema" with the prefix `UnitSchema_X_` (with *X* = 1, 2, 3 or 4) shall be processed as follows. If the native parameter `UnitSchemaArray` is NULL or the integer represented by the outbound value of `NumberOfElements` is less than *X*, then the outbound value of the parameter group shall be ignored. Otherwise, the value of type `BioAPI_UNIT_SCHEMA` represented by the outbound value of the parameter group shall be written to the element at position *X* of the array of elements of type `BioAPI_UNIT_SCHEMA` pointed to by the variable pointed to by the native parameter `UnitSchemaArray`.

9.69.2.3 The outbound value of `NumberOfElements` shall be processed as follows. If the native parameter with the same name is NULL, then the outbound value shall be ignored. Otherwise, the integer represented by the outbound value shall be written to the variable of type `uint32_t` pointed to by the native parameter `NumberOfElements`.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.69.2.4 The integer represented by the outbound value of `return` shall be returned by the native function.

9.69.3 Default output

If there is no activity bound to this standard BioAPI interface function, then

a) the variable pointed to by the native parameter `NumberOfElements` shall be set to zero,

b) the variable pointed to by the native parameter `UnitSchemaArray` shall be set to NULL, and

c) the native function shall return zero.

9.70 BioSPI_QueryBFPs

9.70.1 Function invocation scheme

This function belongs to the BioSPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioSPI_QueryBFPs(

const BioAPI_UUID *BSPUuid,

BioAPI_BFP_LIST_ELEMENT **BFPList,

uint32_t *NumberOfElements);

and the following parameters (see Table 78).

Table 78

Parameter	Function invocation (conformance testing model for BSPs)	Bound activity invocation (conformance testing model for frameworks)
`BSPHandle`	input, outbound	input, inbound
`no_BFPList`	input, outbound	input, inbound
`BFP_1_BFPCategory`	output, inbound	output, outbound
`BFP_1_BFPUuid`	output, inbound	output, outbound
`BFP_2_BFPCategory`	output, inbound	output, outbound
`BFP_2_BFPUuid`	output, inbound	output, outbound
`BFP_3_BFPCategory`	output, inbound	output, outbound
`BFP_3_BFPUuid`	output, inbound	output, outbound
`BFP_4_BFPCategory`	output, inbound	output, outbound
`BFP_4_BFPUuid`	output, inbound	output, outbound
`no_NumberOfElements`	input, outbound	input, inbound
`NumberOfElements`	output, inbound	output, outbound
`return`	return, inbound	output, outbound

The specification of the constraints on the parameters, function invocation input, function invocation output, and bound activity invocation input of the function `BioAPI_QueryBFPs` also applies to this standard BioAPI interface function.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.70.2 Bound activity invocation output

9.70.2.1 If the native parameter `BFPList` is not NULL and the integer (say, *N*) represented by the outbound value of `NumberOfElements` is greater than 0, then a memory block of sufficient size to contain an array of *N* elements of type `BioAPI_BFP_LIST_ELEMENT` shall be allocated and its address shall be written to the variable pointed to by the native parameter `BFPList`.

9.70.2.2 The outbound value of `BFP_X_BFPCategory` and `BFP_X_BFPUuid` (with *X*=1, 2, 3, or 4) shall be processed as follows. If the native parameter `BFPList` is NULL or the integer represented by the outbound value of `NumberOfElements` is less than *X*, then the outbound value of `BFP_X_BFPCategory` and `BFP_X_BFPUuid` shall be ignored. Otherwise, the integer represented by the outbound value of `BFP_X_BFPCategory` and the UUID represented by the outbound value of `BFP_X_BFPUuid` shall be written to the fields `BFPCategory` and `BFPUuid` (respectively) of the element at position *X* of the array of elements of type `BioAPI_BFP_LIST_ELEMENT` pointed to by the variable pointed to by the native parameter `BFPList`.

9.70.2.3 The outbound value of `NumberOfElements` shall be processed as follows. If the native parameter with the same name is NULL, then the outbound value shall be ignored. Otherwise, the integer represented by the outbound value shall be written to the variable of type `uint32_t` pointed to by the native parameter `NumberOfElements`.

9.70.2.4 The integer represented by the outbound value of `return` shall be returned by the native function.

9.70.3 Default output

If there is no activity bound to this standard BioAPI interface function, then

a) the variable pointed to by the native parameter `NumberOfElements` shall be set to zero,

b) the variable pointed to by the native parameter `BFPList` shall be set to NULL, and

c) the native function shall return zero.

9.71 BioSPI_ControlUnit

9.71.1 Function invocation scheme

This function belongs to the BioSPI interface and has the following native prototype:

```
BioAPI_RETURN BioAPI
BioSPI_ControlUnit(
    BioAPI_HANDLE BSPHandle,
    BioAPI_UNIT_ID UnitID,
    uint32_t ControlCode,
    const BioAPI_DATA *InputData,
    BioAPI_DATA *OutputData
);
```

and the following parameters (see Table 79).

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

Table 79

Parameter	Function invocation (conformance testing model for BSPs)	Bound activity invocation (conformance testing model for frameworks)
`BSPHandle`	input, outbound	input, inbound
`UnitID`	input, outbound	input, inbound
`ControlCode`	input, outbound	input, inbound
`InputData`	input, outbound	input, inbound
`no_OutputData`	input, outbound	input, inbound
`OutputData`	output, inbound	output, outbound
`return`	return, inbound	output, outbound

The specification of the constraints on the parameters, function invocation input, function invocation output, and bound activity invocation input of the function `BioAPI_ControlUnit` also applies to this standard BioAPI interface function.

9.71.2 Bound activity invocation output

9.71.2.1 The outbound value of `OutputData` shall be processed as follows. If the native parameter with the same name is NULL, then the outbound value shall be ignored. Otherwise, the octet string represented by the outbound value shall be written to a memory block, whose address and size shall be written to the fields `Data` and `Length` (respectively) of the variable of type `BioAPI_DATA` pointed to by the native parameter `OutputData`.

9.71.2.1 The integer represented by the outbound value of `return` shall be returned by the native function.

9.71.3 Default output

If there is no activity bound to this standard BioAPI interface function, then

a) the fields `Data` and `Length` of the variable pointed to by the native parameter `OutputData` shall be both set to zero, and

b) the native function shall return zero.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.72 BioSPI_SetConfiguration

9.72.1 Function invocation scheme

This function belongs to the application callback interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioSPI_SetConfiguration (

BioAPI_HANDLE BSPHandle,

BioAPI_UNIT_ID UnitID,

const BioAPI_UUID *Parameter,

BioAPI_CONFIGURATION_TYPE ConfigurationType,

const BioAPI_DATA *Value);

and the following parameters (see Table 80).

Table 80

Parameter	Function invocation (conformance testing model for BSPs)	Bound activity invocation (conformance testing model for frameworks)
`BSPHandle`	input, outbound	input, inbound
`UnitID`	input, outbound	input, inbound
`Parameter`	input, outbound	input, inbound
`ConfigurationType`	input, outbound	input, inbound
`Value`	input, outbound	input, inbound
`return`	return, inbound	output, outbound

The specification of the constraints on the parameters, function invocation input, function invocation output, and bound activity invocation input of the function `BioAPI_SetConfiguration` also applies to this standard BioAPI interface function.

9.72.2 Bound activity invocation output

The integer represented by the outbound value of `return` shall be returned by the native function.

9.72.3 Default output

If there is no activity bound to this standard BioAPI interface function, then the native function shall return zero.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.73 BioSPI_FreeBIRHandle

9.73.1 Function invocation scheme

This function belongs to the BioSPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioSPI_FreeBIRHandle(

BioAPI_HANDLE BSPHandle,

BioAPI_BIR_HANDLE Handle);

and the following parameters (see Table 81).

Table 81

Parameter	Function invocation (conformance testing model for BSPs)	Bound activity invocation (conformance testing model for frameworks)
`BSPHandle`	input, outbound	input, inbound
`Handle`	input, outbound	input, inbound
`return`	return, inbound	output, outbound

The specification of the constraints on the parameters, function invocation input, function invocation output, and bound activity invocation input of the function `BioAPI_FreeBIRHandle` also applies to this standard BioAPI interface function.

9.73.2 Bound activity invocation output

The integer represented by the outbound value of `return` shall be returned by the native function.

9.73.3 Default output

If there is no activity bound to this standard BioAPI interface function, the native function shall return zero.

9.74 BioSPI_GetBIRFromHandle

9.74.1 Function invocation scheme

This function belongs to the BioSPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioSPI_GetBIRFromHandle(

BioAPI_HANDLE BSPHandle,

BioAPI_BIR_HANDLE Handle,

BioAPI_BIR *BIR);

and the following parameters (see Table 82).

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

Table 82

Parameter	Function invocation (conformance testing model for BSPs)	Bound activity invocation (conformance testing model for frameworks)
`BSPHandle`	input, outbound	input, inbound
`Handle`	input, outbound	input, inbound
`no_BIR`	input, outbound	input, inbound
the members of the parameter group "BIR" (see 9.2.15)	output, inbound	output, outbound
`return`	return, inbound	output, outbound

The specification of the constraints on the parameters, function invocation input, function invocation output, and bound activity invocation input of the function `BioAPI_GetBIRFromHandle` also applies to this standard BioAPI interface function.

9.74.2 Bound activity invocation output

9.74.2.1 The outbound value of the parameter group "BIR" shall be processed as follows. If the native parameter `BIR` is NULL, then the outbound value shall be ignored. Otherwise, the value of type `BioAPI_BIR` represented by the outbound value shall be written to the variable pointed to by the native parameter `BIR`.

9.74.2.2 The integer represented by the outbound value of `return` shall be returned by the native function.

9.74.3 Default output

If there is no activity bound to this standard BioAPI interface function, then

a) the variable pointed to by the native parameter `BIR` shall have all its fields set to zero, and

b) the native function shall return zero.

9.75 BioSPI_GetHeaderFromHandle

9.75.1 Function invocation scheme

This function belongs to the BioSPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioSPI_GetHeaderFromHandle(

BioAPI_HANDLE BSPHandle,

BioAPI_BIR_HANDLE Handle,

BioAPI_BIR_HEADER *Header);

and the following parameters (see Table 83).

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

Table 83

Parameter	Function invocation (conformance testing model for BSPs)	Bound activity invocation (conformance testing model for frameworks)
`BSPHandle`	input, outbound	input, inbound
`Handle`	input, outbound	input, inbound
`no_Header`	input, outbound	input, inbound
the members of the parameter group "BIR header" (see 9.2.14)	output, inbound	output, outbound
`return`	return, inbound	output, outbound

The specification of the constraints on the parameters, function invocation input, function invocation output, and bound activity invocation input of the function `BioAPI_GetHeaderFromHandle` also applies to this standard BioAPI interface function.

9.75.2 Bound activity invocation output

9.75.2.1 The outbound value of the parameter group "BIR header" shall be processed as follows. If the native parameter `Header` is NULL, then the outbound value shall be ignored. Otherwise, the value of type `BioAPI_BIR_HEADER` represented by the outbound value shall be written to the variable pointed to by the native parameter `Header`.

9.75.2.3 The integer represented by the outbound value of `return` shall be returned by the native function.

9.75.3 Default output

If there is no activity bound to this standard BioAPI interface function, then

a) the variable pointed to by the native parameter `Header` shall have all its fields set to zero, and

b) the native function shall return zero.

9.76 BioSPI_SubscribeToGUIEvents

9.76.1 Function invocation scheme

This function belongs to the BioSPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioSPI_SubscribeToGUIEvents (

const BioAPI_UUID *BSPUuid,

BioSPI_GUI_SELECT_EVENT_HANDLER FwGUISelectEventHandler,

BioSPI_GUI_STATE_EVENT_HANDLER FwGUIStateEventHandler,

BioSPI_GUI_PROGRESS_EVENT_HANDLER FwGUIProgressEventHandler);

and the following parameters (see Table 84).

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

 © ISO/IEC 2017 – All rights reserved

Table 84

Parameter	Function invocation (conformance testing model for frameworks)	Bound activity invocation (conformance testing model for applications)
BSPUuid	input, outbound	input, inbound
FwGUISelectEventHandler	input, outbound	input, inbound
FwGUIStateEventHandler	input, outbound	input, inbound
FwGUIProgressEventHandler	input, outbound	input, inbound
return	return, inbound	output, outbound

The specification of the constraints on the parameters, function invocation input, function invocation output, and bound activity invocation input of the function BioAPI_SubscribeToGUIEvents also applies to this standard BioAPI interface function.

9.76.2 Bound activity invocation output

The integer represented by the outbound value of return shall be returned by the native function.

9.76.3 Default output

If there is no activity bound to this standard BioAPI interface function, the native function shall return zero.

9.77 BioSPI_UnsubscribeFromGUIEvents

9.77.1 Function invocation scheme

This function belongs to the BioSPI interface and has the following native prototype:

BioAPI_RETURN BioAPI BioSPI_UnsubscribeFromGUIEvents (

const BioAPI_UUID *BSPUuid);

and the following parameters (see Table 85).

Table 85

Parameter	Function invocation (conformance testing model for frameworks)	Bound activity invocation (conformance testing model for applications)
BSPUuid	input, outbound	input, inbound
return	return, inbound	output, outbound

The specification of the constraints on the parameters, function invocation input, function invocation output, and bound activity invocation input of the function BioAPI_UnsubscribeFromGUIEvents also applies to this standard BioAPI interface function.

9.77.2 Bound activity invocation output

The integer represented by the outbound value of return shall be returned by the native function.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.77.3 Default output

If there is no activity bound to this standard BioAPI interface function, the native function shall return zero.

9.78 BioSPI_EnableEvents

9.78.1 Function invocation scheme

This function belongs to the BioSPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioSPI_EnableEvents(

BioAPI_HANDLE BSPHandle,

BioAPI_EVENT_MASK Events);

and the following parameters (see Table 86).

Table 86

Parameter	Function invocation (conformance testing model for BSPs)	Bound activity invocation (conformance testing model for frameworks)
`BSPHandle`	input, outbound	input, inbound
the members of the parameter group "Events" (see 9.2.5)	input, outbound	input, inbound
`return`	return, inbound	output, outbound

The specification of the constraints on the parameters, function invocation input, function invocation output, and bound activity invocation input of the function `BioAPI_EnableEvents` also applies to this standard BioAPI interface function.

9.78.2 Bound activity invocation output

The integer represented by the outbound value of `return` shall be returned by the native function.

9.78.3 Default output

If there is no activity bound to this standard BioAPI interface function, the native function shall return zero.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.79 BioSPI_SetGUICallbacks

9.79.1 Function invocation scheme

This function belongs to the BioSPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioSPI_SetGUICallbacks(

BioAPI_HANDLE BSPHandle,

BioAPI_GUI_STREAMING_CALLBACK GuiStreamingCallback,

void *GuiStreamingCallbackCtx,

BioAPI_GUI_STATE_CALLBACK GuiStateCallback,

void *GuiStateCallbackCtx);

and the following parameters (see Table 87).

Table 87

Parameter	Function invocation (conformance testing model for BSPs)	Bound activity invocation (conformance testing model for frameworks)
`BSPHandle`	input, outbound	input, inbound
`GuiStreamingCallback`	input, outbound	input, inbound
`GuiStreamingCallbackCtx`	input, outbound	input, inbound
`GuiStateCallback`	input, outbound	input, inbound
`GuiStateCallbackCtx`	input, outbound	input, inbound
`return`	return, inbound	output, outbound

The specification of the constraints on the parameters, function invocation input, function invocation output, and bound activity invocation input of the function `BioAPI_SetGUICallbacks` also applies to this standard BioAPI interface function.

9.79.2 Bound activity invocation output

The integer represented by the outbound value of `return` shall be returned by the native function.

9.79.3 Default output

If there is no activity bound to this standard BioAPI interface function, the native function shall return zero.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.80 BioSPI_Capture

9.80.1 Function invocation scheme

This function belongs to the BioSPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioSPI_Capture(

BioAPI_HANDLE BSPHandle,

BioAPI_BIR_PURPOSE Purpose,

BioAPI_BIR_SUBTYPE Subtype,

const BioAPI_BIR_BIOMETRIC_DATA_FORMAT *OutputFormat,

BioAPI_BIR_HANDLE *CapturedBIR,

int32_t Timeout,

BioAPI_BIR_HANDLE *AuditData);

and the following parameters (see Table 88).

Table 88

Parameter	Function invocation (conformance testing model for BSPs)	Bound activity invocation (conformance testing model for frameworks)
BSPHandle	input, outbound	input, inbound
Purpose	input, outbound	input, inbound
Subtype	input, outbound	input, inbound
OutputFormatOwner	input, outbound	input, inbound
OutputFormatType	input, outbound	input, inbound
no_CapturedBIR	input, outbound	input, inbound
Timeout	input, outbound	input, inbound
no_AuditData	input, outbound	input, inbound
CapturedBIR	output, inbound	output, outbound
AuditData	output, inbound	output, outbound
return	return, inbound	output, outbound

The specification of the constraints on the parameters, function invocation input, function invocation output, and bound activity invocation input of the function BioAPI_Capture also applies to this standard BioAPI interface function.

9.80.2 Bound activity invocation output

9.80.2.1 The outbound value of CapturedBIR shall be processed as follows. If the native parameter with the same name is NULL, then the outbound value shall be ignored. Otherwise, the integer represented by the outbound value shall be written to the variable of type BioAPI_BIR_HANDLE pointed to by the native parameter CapturedBIR.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.80.2.2 The outbound value of `AuditData` shall be processed as follows. If the native parameter with the same name is NULL, then the outbound value shall be ignored. Otherwise, the integer represented by the outbound value shall be written to the variable of type `BioAPI_BIR_HANDLE` pointed to by the native parameter `AuditData`.

9.80.2.3 The integer represented by the outbound value of `return` shall be returned by the native function.

9.80.3 Default output

If there is no activity bound to this standard BioAPI interface function, then

a) the variable pointed to by the native parameter `CapturedBIR` shall be set to zero,

b) the variable pointed to by the native parameter `AuditData` shall be set to zero, and

c) the native function shall return zero.

9.81 BioSPI_CreateTemplate

9.81.1 Function invocation scheme

This function belongs to the BioSPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioSPI_CreateTemplate(

BioAPI_HANDLE BSPHandle,

const BioAPI_INPUT_BIR *CapturedBIR,

const BioAPI_INPUT_BIR *ReferenceTemplate,

const BioAPI_BIR_BIOMETRIC_DATA_FORMAT *OutputFormat,

BioAPI_BIR_HANDLE *NewTemplate,

const BioAPI_DATA *Payload,

BioAPI_UUID *TemplateUUID);

and the following parameters (see Table 89).

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

Table 89

Parameter	Function invocation (conformance testing model for BSPs)	Bound activity invocation (conformance testing model for frameworks)
`BSPHandle`	input, outbound	input, inbound
the members of the parameter group "Input BIR" (see 9.2.15) with their names prefixed by "`CapturedBIR_`"	input, outbound	input, inbound
the members of the parameter group "Input BIR" with their names prefixed by "`ReferenceTemplate_`"	input, outbound	input, inbound
`OutputFormatOwner`	input, outbound	input, inbound
`OutputFormatType`	input, outbound	input, inbound
`no_NewTemplate`	input, outbound	input, inbound
`Payload`	input, outbound	input, inbound
`no_TemplateUUID`	input, outbound	input, inbound
`NewTemplate`	output, inbound	output, outbound
`TemplateUUID`	output, inbound	output, outbound
`return`	return, inbound	output, outbound

The specification of the constraints on the parameters, function invocation input, function invocation output, and bound activity invocation input of the function `BioAPI_CreateTemplate` also applies to this standard BioAPI interface function.

9.81.2 Bound activity invocation output

9.81.2.1 The outbound value of `NewTemplate` shall be processed as follows. If the native parameter with the same name is NULL, then the outbound value shall be ignored. Otherwise, the integer represented by the outbound value shall be written to the variable of type `BioAPI_BIR_HANDLE` pointed to by the native parameter `NewTemplate`.

9.81.2.2 The outbound value of `TemplateUUID` shall be processed as follows. If the native parameter with the same name is NULL, then the outbound value shall be ignored. Otherwise, the UUID represented by the outbound value shall be written to the variable of type `BioAPI_UUID` pointed to by the native parameter `TemplateUUID`.

9.81.2.3 The integer represented by the outbound value of `return` shall be returned by the native function.

9.81.3 Default output

If there is no activity bound to this standard BioAPI interface function, then

a) the variable pointed to by the native parameter `NewTemplate` shall be set to zero,

b) the variable pointed to by the native parameter `TemplateUUID` shall be set to the UUID "`00000000-0000-0000-0000-000000000000`", and

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

c) the native function shall return zero.

9.82 BioSPI_Process

9.82.1 Function invocation scheme

This function belongs to the BioSPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioSPI_Process(

BioAPI_HANDLE BSPHandle,

const BioAPI_INPUT_BIR *CapturedBIR,

const BioAPI_BIR_BIOMETRIC_DATA_FORMAT *OutputFormat,

BioAPI_BIR_HANDLE *ProcessedBIR);

and the following parameters (see Table 90).

Table 90

Parameter	Function invocation (conformance testing model for BSPs)	Bound activity invocation (conformance testing model for frameworks)
`BSPHandle`	input, outbound	input, inbound
the members of the parameter group "Input BIR" (see 9.2.16) with their names prefixed by "`CapturedBIR_`"	input, outbound	input, inbound
`OutputFormatOwner`	input, outbound	input, inbound
`OutputFormatType`	input, outbound	input, inbound
`no_ProcessedBIR`	input, outbound	input, inbound
`ProcessedBIR`	output, inbound	output, outbound
`return`	return, inbound	output, outbound

The specification of the constraints on the parameters, function invocation input, function invocation output, and bound activity invocation input of the function `BioAPI_Process` also applies to this standard BioAPI interface function.

9.82.2 Bound activity invocation output

9.82.2.1 The outbound value of `ProcessedBIR` shall be processed as follows. If the native parameter with the same name is NULL, then the outbound value shall be ignored. Otherwise, the integer represented by the outbound value shall be written to the variable of type `BioAPI_BIR_HANDLE` pointed to by the native parameter `ProcessedBIR`.

9.82.2.2 The integer represented by the outbound value of `return` shall be returned by the native function.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.82.3 Default output

If there is no activity bound to this standard BioAPI interface function, then

a) the variable pointed to by the native parameter `ProcessedBIR` shall be set to zero, and

b) the native function shall return zero.

9.83 BioSPI_ProcessUsingAuxBIRs

9.83.1 Function invocation scheme

This function belongs to the BioSPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioSPI_ProcessUsingAuxBIRs (

BioAPI_HANDLE BSPHandle,

Uint32_t NumBIRs,

const BioAPI_INPUT_BIR *CapturedBIRList,

uint32_t NumberOfAuxBIRs,

const BioAPI_INPUT_BIR *AuxBIRs,

const BioAPI_BIR_BIOMETRIC_DATA_FORMAT *OutputFormat,

BioAPI_BIR_HANDLE *ProcessedBIR

);

and the following parameters (see Table 91).

Table 91

Parameter	Function invocation (conformance testing model for BSPs)	Bound activity invocation (conformance testing model for frameworks)
`BSPHandle`	input, outbound	input, inbound
`NumBIRs`	input, outbound	input, inbound
the members of the parameter group “Input BIR” (see 9.2.16) with their names prefixed by “`CapturedBIRList_`”	input, outbound	input, inbound
`NumberOfAuxBIRs`	input, outbound	input, inbound
the members of the parameter group “Input BIR” with their names prefixed by “`AuxBIRs_`”	input, outbound	input, inbound
`OutputFormatOwner`	input, outbound	input, inbound
`OutputFormatType`	input, outbound	input, inbound

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

Table 91 *(continued)*

Parameter	Function invocation (conformance testing model for BSPs)	Bound activity invocation (conformance testing model for frameworks)
`no_ProcessedBIR`	input, outbound	input, inbound
`ProcessedBIR`	output, inbound	output, outbound
`return`	return, inbound	output, outbound

The specification of the constraints on the parameters, function invocation input, function invocation output, and bound activity invocation input of the function `BioAPI_ProcessUsingAuxBIRs` also applies to this standard BioAPI interface function.

9.83.2 Bound activity invocation output

9.83.2.1 The outbound value of `ProcessedBIR` shall be processed as follows. If the native parameter with the same name is NULL, then the outbound value shall be ignored. Otherwise, the integer represented by the outbound value shall be written to the variable of type `BioAPI_BIR_HANDLE` pointed to by the native parameter `ProcessedBIR`.

9.83.2.2 The integer represented by the outbound value of return shall be `returned` by the native function.

9.83.3 Default output

If there is no activity bound to this standard BioAPI interface function, then

a) the variable pointed to by the native parameter `ProcessedBIR` shall be set to zero, and

b) the native function shall return zero.

9.84 BioSPI_VerifyMatch

9.84.1 Function invocation scheme

This function belongs to the BioSPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioSPI_VerifyMatch(

BioAPI_HANDLE BSPHandle,

BioAPI_FMR MaxFMRRequested,

const BioAPI_INPUT_BIR *ProcessedBIR,

const BioAPI_INPUT_BIR *ReferenceTemplate,

BioAPI_BIR_HANDLE *AdaptedBIR,

BioAPI_BOOL *Result,

BioAPI_FMR *FMRAchieved,

BioAPI_DATA *Payload);

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

and the following parameters (see Table 92).

Table 92

Parameter	Function invocation (conformance testing model for BSPs)	Bound activity invocation (conformance testing model for frameworks)
`BSPHandle`	input, outbound	input, inbound
`MaxFMRRequested`	input, outbound	input, inbound
the members of the parameter group "Input BIR" (see 9.2.16) with their names prefixed by "`ProcessedBIR_`"	input, outbound	input, inbound
the members of the parameter group "Input BIR" with their names prefixed by "`ReferenceTemplate_`"	input, outbound	input, inbound
`no_AdaptedBIR`	input, outbound	input, inbound
`no_Result`	input, outbound	input, inbound
`no_FMRAchieved`	input, outbound	input, inbound
`no_Payload`	input, outbound	input, inbound
`AdaptedBIR`	output, inbound	output, outbound
`Result`	output, inbound	output, outbound
`FMRAchieved`	output, inbound	output, outbound
`Payload`	output, inbound	output, outbound
`Return`	return, inbound	output, outbound

The specification of the constraints on the parameters, function invocation input, function invocation output, and bound activity invocation input of the function `BioAPI_VerifyMatch` also applies to this standard BioAPI interface function.

9.84.2 Bound activity invocation output

9.84.2.1 The outbound value of `AdaptedBIR` shall be processed as follows. If the native parameter with the same name is NULL, then the outbound value shall be ignored. Otherwise, the integer represented by the outbound value shall be written to the variable of type `BioAPI_BIR_HANDLE` pointed to by the native parameter `AdaptedBIR`.

9.84.2.2 The outbound value of `Result` shall be processed as follows. If the native parameter with the same name is NULL, then the outbound value shall be ignored. Otherwise, the Boolean represented by the outbound value shall be written to the variable of type `BioAPI_BOOL` pointed to by the native parameter `Result`.

9.84.2.3 The outbound value of `FMRAchieved` shall be processed as follows. If the native parameter with the same name is NULL, then the outbound value shall be ignored. Otherwise, the integer represented by the outbound value shall be written to the variable of type `BioAPI_FMR` pointed to by the native parameter `FMRAchieved`.

9.84.2.4 The outbound value of `Payload` shall be processed as follows. If the native parameter with the same name is NULL, then the outbound value shall be ignored. Otherwise, the octet string represented

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

 © ISO/IEC 2017 – All rights reserved

by the outbound value shall be written to a memory block, whose address and size shall be written to the fields `Data` and `Length` (respectively) of the variable of type `BioAPI_DATA` pointed to by the native parameter `Payload`.

9.84.2.5 The integer represented by the outbound value of `return` shall be returned by the native function.

9.84.3 Default output

If there is no activity bound to this standard BioAPI interface function, then

a) the variable pointed to by the native parameter `AdaptedBIR` shall be set to zero,

b) the variable pointed to by the native parameter `Result` shall be set to zero,

c) the variable pointed to by the native parameter `FMRAchieved` shall be set to zero,

d) the fields `Data` and `Length` of the variable pointed to by the native parameter `Payload` shall be both set to zero, and

e) the native function shall return zero.

9.85 BioSPI_VerifyMatchUsingAuxBIRs

9.85.1 Function invocation scheme

This function belongs to the BioSPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioSPI_VerifyMatchUsingAuxBIRs(

BioAPI_HANDLE BSPHandle,

BioAPI_FMR MaxFMRRequested,

const BioAPI_INPUT_BIR *ProcessedBIR,

const BioAPI_INPUT_BIR *ReferenceTemplate,

uint32_t NumberOfAuxBIRs,

const BioAPI_INPUT_BIR *AuxBIRs,

BioAPI_BIR_HANDLE *AdaptedBIR,

BioAPI_BOOL *Result,

BioAPI_FMR *FMRAchieved,

BioAPI_BIR_HANDLE *ResultBIR,

BioAPI_AUXILIARY_SCALE_RESULT *AuxResult,

BioAPI_DATA *Payload);

and the following parameters (see Table 93).

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

Table 93

Parameter	Function invocation (conformance testing model for BSPs)	Bound activity invocation (conformance testing model for frameworks)
BSPHandle	input, outbound	input, inbound
MaxFMRRequested	input, outbound	input, inbound
the members of the parameter group "Input BIR" (see 9.2.16) with their names prefixed by "ProcessedBIR_"	input, outbound	input, inbound
the members of the parameter group "Input BIR" with their names prefixed by "ReferenceTemplate_"	input, outbound	input, inbound
NumberOfAuxBIRs	input, outbound	input, inbound
AuxBIRs	input, outbound	input, inbound
no_AdaptedBIR	input, outbound	input, inbound
no_Result	input, outbound	input, inbound
no_FMRAchieved	input, outbound	input, inbound
no_Payload	input, outbound	input, inbound
AdaptedBIR	output, inbound	output, outbound
Result	output, inbound	output, outbound
FMRAchieved	output, inbound	output, outbound
ResultBIR	input, outbound	input, inbound
AuxResult	output, inbound	output, outbound
Payload	output, inbound	output, outbound
Return	return, inbound	output, outbound

The specification of the constraints on the parameters, function invocation input, function invocation output, and bound activity invocation input of the function BioAPI_VerifyMatchUsingAuxBIRs also applies to this standard BioAPI interface function.

9.85.2 Bound activity invocation output

9.85.2.1 The outbound value of AdaptedBIR shall be processed as follows. If the native parameter with the same name is NULL, then the outbound value shall be ignored. Otherwise, the integer represented by the outbound value shall be written to the variable of type BioAPI_BIR_HANDLE pointed to by the native parameter AdaptedBIR.

9.85.2.2 The outbound value of Result shall be processed as follows. If the native parameter with the same name is NULL, then the outbound value shall be ignored. Otherwise, the Boolean represented by the outbound value shall be written to the variable of type BioAPI_BOOL pointed to by the native parameter Result.

9.85.2.3 The outbound value of FMRAchieved shall be processed as follows. If the native parameter with the same name is NULL, then the outbound value shall be ignored. Otherwise, the integer represented by the outbound value shall be written to the variable of type BioAPI_FMR pointed to by the native parameter FMRAchieved.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

 © ISO/IEC 2017 – All rights reserved

9.85.2.4 The outbound value of `AuxResult` shall be processed as follows. If the native parameter with the same name is NULL, then the outbound value shall be ignored. Otherwise, the integer represented by the outbound value shall be written to the variable of type `BioAPI_AUXILIARY_SCALE_RESULT` pointed to by the native parameter `AuxResult`.

9.85.2.5 The outbound value of `Payload` shall be processed as follows. If the native parameter with the same name is NULL, then the outbound value shall be ignored. Otherwise, the octet string represented by the outbound value shall be written to a memory block, whose address and size shall be written to the fields `Data` and `Length` (respectively) of the variable of type `BioAPI_DATA` pointed to by the native parameter `Payload`.

9.85.2.6 The integer represented by the outbound value of `return` shall be returned by the native function.

9.85.3 Default output

If there is no activity bound to this standard BioAPI interface function, then

a) the variable pointed to by the native parameter `AdaptedBIR` shall be set to zero,

b) the variable pointed to by the native parameter `Result` shall be set to zero,

c) the variable pointed to by the native parameter `FMRAchieved` shall be set to zero,

d) the fields `Data` and `Length` of the variable pointed to by the native parameter `Payload` shall be both set to zero,

e) the variable pointed to by the native parameter `AuxResult` shall be set to zero, and

f) the native function shall return zero.

9.86 BioSPI_IdentifyMatch

9.86.1 Function invocation scheme

This function belongs to the BioSPI interface and has the following native prototype:

```
BioAPI_RETURN BioAPI
BioSPI_IdentifyMatch(
    BioAPI_HANDLE BSPHandle,
    BioAPI_FMR MaxFMRRequested,
    const BioAPI_INPUT_BIR *ProcessedBIR,
    const BioAPI_IDENTIFY_POPULATION *Population,
    uint32_t TotalNumberOfTemplates,
    BioAPI_BOOL Binning,
    uint32_t MaxNumberOfResults,
    uint32_t *NumberOfResults,
    BioAPI_CANDIDATE_ARRAY **Candidates,
    int32_t Timeout);
```

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

and the following parameters (see Table 94).

Table 94

Parameter	Function invocation (conformance testing model for BSPs)	Bound activity invocation (conformance testing model for frameworks)
`BSPHandle`	input, outbound	input, inbound
`MaxFMRRequested`	input, outbound	input, inbound
the members of the parameter group "Input BIR" (see 9.2.16) with their names prefixed by "`ProcessedBIR_`"	input, outbound	input, inbound
the members of the parameter group "Identify population" (see 9.2.17)	input, outbound	input, inbound
`TotalNumberOfTemplates`	input, outbound	input, inbound
`Binning`	input, outbound	input, inbound
`MaxNumberOfResults`	input, outbound	input, inbound
`no_NumberOfResults`	input, outbound	input, inbound
`no_Candidates`	input, outbound	input, inbound
`Timeout`	input, outbound	input, inbound
`NumberOfResults`	output, inbound	output, outbound
the members of the parameter group "Candidate" (see 9.2.18) with their names prefixed by "`Candidate_1_`"	output, inbound	output, outbound
the members of the parameter group "Candidate" with their names prefixed by "`Candidate_2_`"	output, inbound	output, outbound
the members of the parameter group "Candidate" with their names prefixed by "`Candidate_3_`"	output, inbound	output, outbound
the members of the parameter group "Candidate" with their names prefixed by "`Candidate_4_`"	output, inbound	output, outbound
`return`	return, inbound	output, outbound

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

The specification of the constraints on the parameters, function invocation input, function invocation output, and bound activity invocation input of the function `BioAPI_IdentifyMatch` also applies to this standard BioAPI interface function.

9.86.2 Bound activity invocation output

9.86.2.1 If the native parameter `Candidates` is not NULL and the integer (say, *N*) represented by the outbound value of `NumberOfResults` is greater than 0, then a memory block of sufficient size to contain an array of *N* elements of type `BioAPI_CANDIDATE` shall be allocated and its address shall be written to the variable pointed to by the native parameter `Candidates`.

© ISO/IEC 2017 – All rights reserved

9.86.2.2 The outbound value of `NumberOfResults` shall be processed as follows. If the native parameter with the same name is NULL, then the outbound value shall be ignored. Otherwise, the integer represented by the outbound value shall be written to the variable of type `uint32_t` pointed to by the native parameter `NumberOfResults`.

9.86.2.3 The outbound value of the parameter group "Candidate" with the prefix `Candidate_X_` (with *X* = 1, 2, 3 or 4) shall be processed as follows. If the native parameter `Candidates` is NULL or the integer represented by the outbound value of `NumberOfResults` is less than *X*, then the outbound value of the parameter group shall be ignored. Otherwise, the value of type `BioAPI_CANDIDATE` represented by the outbound value of the parameter group shall be written to the element at position *X* of the array of elements of type `BioAPI_CANDIDATE` pointed to by the variable pointed to by the native parameter `Candidates`.

9.86.2.4 The integer represented by the outbound value of `return` shall be returned by the native function.

9.86.3 Default output

If there is no activity bound to this standard BioAPI interface function, then

a) the variable pointed to by the native parameter `NumberOfResults` shall be set to zero,

b) the variable pointed to by the native parameter `Candidates` shall be set to NULL, and

c) the native function shall return zero.

9.87 BioSPI_Decide

9.87.1 Function invocation scheme

This function belongs to the BioSPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioSPI_Decide(

BioAPI_HANDLE BSPHandle,

const BioAPI_INPUT_BIR *ScoreBIR,

uint32_t NumberOfAuxBIRs,

const BioAPI_INPUT_BIR *AuxBIRs,

BioAPI_BIR_HANDLE *DecisionBIR);

and the following parameters (see Table 95).

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

Table 95

Parameter	Function invocation (conformance testing model for BSPs)	Bound activity invocation (conformance testing model for frameworks)
`BSPHandle`	input, outbound	input, inbound
the members of the parameter group "Input BIR" (see 9.2.16) with their names prefixed by "`ScoreBIR_`"	input, outbound	input, inbound
`NumberOfAuxBIRs`	input, outbound	input, inbound
the members of the parameter group "Input BIR" (see 9.2.16) with their names prefixed by "`AuxBIRs_`"	input, inbound	input, inbound
`DecisionBIR`	output, inbound	input, inbound
`Return`	return, inbound	output, outbound

The specification of the constraints on the parameters, function invocation input, function invocation output, and bound activity invocation input of the function `BioAPI_Decide` also applies to this standard BioAPI interface function.

9.87.2 Bound activity invocation output

9.87.2.1 The inbound value of BSPHandle and NumberOfAuxBIRs shall be the canonical representation of the integer in the native parameter with the same name.

9.87.2.2 The inbound value of the parameter group "Input BIR" with the prefix "ScoreBIR_" shall be the canonical representation (see 9.2.16.5) of the value of type BioAPI_INPUT_BIR in the variable pointed to by the native parameter ScoreBIR.

9.87.2.3 The inbound value of the parameter group "Input BIR" with the prefix "AuxBIRs_" shall be the canonical representation (see 9.2.16.5) of the value of type BioAPI_INPUT_BIR in the variable pointed to by the native parameter AuxBIRs.

9.87.2.4 The integer represented by the outbound value of return shall be returned by the native function.

9.87.3 Default output

If there is no activity bound to this standard BioAPI interface function, then

a) the variable pointed to by the native parameter `DedisionBIR` shall be set to zero, and

b) the native function shall return zero.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.88 BioSPI_Fuse

9.88.1 Function invocation scheme

This function belongs to the BioSPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioSPI_Fuse(

BioAPI_HHANDLE BSPHandle,

uint32_t NumberOfSourceBIRs,

const BioAPI_INPUT_BIR *SourceBIRs,

uint32_t NumberOfAuxBIRs,

const BioAPI_INPUT_BIR *AuxBIRs,

BioAPI_BIR_HANDLE *FusionBIR

);

and the following parameters (see Table 96).

Table 96

Parameter	Function invocation (conformance testing model for BSPs)	Bound activity invocation (conformance testing model for frameworks)
`BSPHandle`	input, outbound	input, inbound
`NumberOfSourceBIRs`	input, outbound	input, inbound
the members of the parameter group "Input BIR" (see 9.2.16) with their names prefixed by "`SourceBIRs_`"	input, outbound	input, inbound
`NumberOfAuxBIRs`	input, outbound	input, inbound
the members of the parameter group "Input BIR" (see 9.2.16) with their names prefixed by "`AuxBIRs_`"	input, outbound	input, inbound
`FusionBIR`	output, inbound	input, inbound
`Return`	return, inbound	output, outbound

The specification of the constraints on the parameters, function invocation input, function invocation output, and bound activity invocation input of the function `BioAPI_Fuse` also applies to this standard BioAPI interface function.

9.88.2 Bound activity invocation output

9.88.2.1 The inbound value of `BSPHandle`, `NumberOfAuxBIRs` and `NumberOfSourceBIRs` shall be the canonical representation of the integer in the native parameter with the same name.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.88.2.2 The inbound value of the parameter group "Input BIR" with the prefix "`SourceBIRs_`" shall be the canonical representation (see 9.2.16.5) of the value of type `BioAPI_INPUT_BIR` in the variable pointed to by the native parameter `SourceBIRs`.

9.88.2.3 The inbound value of the parameter group "Input BIR" with the prefix "`AuxBIRs_`" shall be the canonical representation (see 9.2.16.5) of the value of type `BioAPI_INPUT_BIR` in the variable pointed to by the native parameter `AuxBIRs`.

9.88.2.4 The integer represented by the outbound value of `return` shall be returned by the native function.

9.88.3 Default output

If there is no activity bound to this standard BioAPI interface function, then

a) the variable pointed to by the native parameter `FusionBIR` shall be set to zero, and

b) the native function shall return zero.

9.89 BioSPI_Enroll

9.89.1 Function invocation scheme

This function belongs to the BioSPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioSPI_Enroll(

BioAPI_HANDLE BSPHandle,

BioAPI_BIR_PURPOSE Purpose,

BioAPI_BIR_SUBTYPE Subtype,

const BioAPI_BIR_BIOMETRIC_DATA_FORMAT *OutputFormat,

const BioAPI_INPUT_BIR *ReferenceTemplate,

BioAPI_BIR_HANDLE NewTemplate,

const BioAPI_DATA *Payload,

int32_t Timeout,

BioAPI_BIR_HANDLE *AuditData,

BioAPI_UUID *TemplateUUID);

and the following parameters (see Table 97).

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

 © ISO/IEC 2017 – All rights reserved

Table 97

Parameter	Function invocation (conformance testing model for BSPs)	Bound activity invocation (conformance testing model for frameworks)
BSPHandle	input, outbound	input, inbound
Purpose	input, outbound	input, inbound
Subtype	input, outbound	input, inbound
OutputFormatOwner	input, outbound	input, inbound
OutputFormatType	input, outbound	input, inbound
the members of the parameter group "Input BIR" (see 9.2.16) with their names prefixed by "ReferenceTemplate_"	input, outbound	input, inbound
Payload	input, outbound	input, inbound
Timeout	input, outbound	input, inbound
no_AuditData	input, outbound	input, inbound
no_TemplateUUID	input, outbound	input, inbound
NewTemplate	output, inbound	output, outbound
AuditData	output, inbound	output, outbound
TemplateUUID	output, inbound	output, outbound
Return	return, inbound	output, outbound

The specification of the constraints on the parameters, function invocation input, function invocation output, and bound activity invocation input of the function BioAPI_Enroll also applies to this standard BioAPI interface function.

9.89.2 Bound activity invocation output

9.89.2.1 The outbound value of NewTemplate shall be processed as follows. If the native parameter with the same name is NULL, then the outbound value shall be ignored. Otherwise, the integer represented by the outbound value shall be written to the variable of type BioAPI_BIR_HANDLE pointed to by the native parameter NewTemplate.

9.89.2.2 The outbound value of AuditData shall be processed as follows. If the native parameter with the same name is NULL, then the outbound value shall be ignored. Otherwise, the integer represented by the outbound value shall be written to the variable of type BioAPI_BIR_HANDLE pointed to by the native parameter AuditData.

9.89.2.3 The outbound value of TemplateUUID shall be processed as follows. If the native parameter with the same name is NULL, then the outbound value shall be ignored. Otherwise, the UUID represented by the outbound value shall be written to the variable of type BioAPI_UUID pointed to by the native parameter TemplateUUID.

9.89.2.4 The integer represented by the outbound value of return shall be returned by the native function.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.89.3 Default output

If there is no activity bound to this standard BioAPI interface function, then

a) the variable pointed to by the native parameter `NewTemplate` shall be set to zero,

b) the variable pointed to by the native parameter `AuditData` shall be set to zero,

c) the variable pointed to by the native parameter `TemplateUUID` shall be set to the UUID "`00000000-0000-0000-0000-000000000000`", and

d) the native function shall return zero.

9.90 BioSPI_Verify

9.90.1 Function invocation scheme

This function belongs to the BioSPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioSPI_Verify(

BioAPI_HANDLE BSPHandle,

BioAPI_FMR MaxFMRRequested,

const BioAPI_INPUT_BIR *ReferenceTemplate,

BioAPI_BIR_SUBTYPE Subtype,

BioAPI_BIR_HANDLE *AdaptedBIR,

BioAPI_BOOL *Result,

BioAPI_FMR *FMRAchieved,

BioAPI_DATA *Payload,

int32_t Timeout,

BioAPI_BIR_HANDLE *AuditData

and the following parameters (see Table 98).

Table 98

Parameter	Function invocation (conformance testing model for BSPs)	Bound activity invocation (conformance testing model for frameworks)
`BSPHandle`	input, outbound	input, inbound
`MaxFMRRequested`	input, outbound	input, inbound
the members of the parameter group "Input BIR" (see 9.2.16) with their names prefixed by "`ReferenceTemplate_`"	input, outbound	input, inbound
`Subtype`	input, outbound	input, inbound

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

Table 98 *(continued)*

Parameter	Function invocation (conformance testing model for BSPs)	Bound activity invocation (conformance testing model for frameworks)
no_AdaptedBIR	input, outbound	input, inbound
no_Result	input, outbound	input, inbound
no_FMRAchieved	input, outbound	input, inbound
no_Payload	input, outbound	input, inbound
Timeout	input, outbound	input, inbound
no_AuditData	input, outbound	input, inbound
AdaptedBIR	output, inbound	output, outbound
Result	output, inbound	output, outbound
FMRAchieved	output, inbound	output, outbound
Payload	output, inbound	output, outbound
AuditData	output, inbound	output, outbound
Return	return, inbound	output, outbound

The specification of the constraints on the parameters, function invocation input, function invocation output, and bound activity invocation input of the function `BioAPI_Verify` also applies to this standard BioAPI interface function.

9.90.2 Bound activity invocation output

9.90.2.1 The outbound value of `AdaptedBIR` shall be processed as follows. If the native parameter with the same name is NULL, then the outbound value shall be ignored. Otherwise, the integer represented by the outbound value shall be written to the variable of type `BioAPI_BIR_HANDLE` pointed to by the native parameter `AdaptedBIR`.

9.90.2.2 The outbound value of `Result` shall be processed as follows. If the native parameter with the same name is NULL, then the outbound value shall be ignored. Otherwise, the Boolean represented by the outbound value shall be written to the variable of type `BioAPI_BOOL` pointed to by the native parameter `Result`.

9.90.2.3 The outbound value of `FMRAchieved` shall be processed as follows. If the native parameter with the same name is NULL, then the outbound value shall be ignored. Otherwise, the integer represented by the outbound value shall be written to the variable of type `BioAPI_FMR` pointed to by the native parameter `FMRAchieved`.

9.90.2.4 The outbound value of `Payload` shall be processed as follows. If the native parameter with the same name is NULL, then the outbound value shall be ignored. Otherwise, the octet string represented by the outbound value shall be written to a memory block, whose address and size shall be written to the fields `Data` and `Length` (respectively) of the variable of type `BioAPI_DATA` pointed to by the native parameter `Payload`.

9.90.2.5 The outbound value of `AuditData` shall be processed as follows. If the native parameter with the same name is NULL, then the outbound value shall be ignored. Otherwise, the integer represented by the outbound value shall be written to the variable of type `BioAPI_BIR_HANDLE` pointed to by the native parameter `AuditData`.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.90.2.6 The integer represented by the outbound value of `return` shall be returned by the native function.

9.90.3 Default output

If there is no activity bound to this standard BioAPI interface function, then

a) the variable pointed to by the native parameter `AdaptedBIR` shall be set to zero,

b) the variable pointed to by the native parameter `Result` shall be set to zero,

c) the variable pointed to by the native parameter `FMRAchieved` shall be set to zero,

d) the fields `Data` and `Length` of the variable pointed to by the native parameter `Payload` shall be both set to zero,

e) the variable pointed to by the native parameter `AuditData` shall be set to zero, and

f) the native function shall return zero.

9.91 BioSPI_Identify

9.91.1 Function invocation scheme

This function belongs to the BioSPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioSPI_Identify(

BioAPI_HANDLE BSPHandle,

BioAPI_FMR MaxFMRRequested,

BioAPI_BIR_SUBTYPE Subtype,

const BioAPI_IDENTIFY_POPULATION *Population,

uint32_t TotalNumberOfTemplates,

BioAPI_BOOL Binning,

uint32_t MaxNumberOfResults,

uint32_t *NumberOfResults,

BioAPI_CANDIDATE **Candidates,

int32_t Timeout,

BioAPI_BIR_HANDLE *AuditData);

and the following parameters (see Table 99).

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

 © ISO/IEC 2017 – All rights reserved

Table 99

Parameter	Function invocation (conformance testing model for BSPs)	Bound activity invocation (conformance testing model for frameworks)
`BSPHandle`	input, outbound	input, inbound
`MaxFMRRequested`	input, outbound	input, inbound
`Subtype`	input, outbound	input, inbound
the members of the parameter group "Identify population" (see 9.2.17)	input, outbound	input, inbound
`TotalNumberOfTemplates`	input, outbound	input, inbound
`Binning`	input, outbound	input, inbound
`MaxNumberOfResults`	input, outbound	input, inbound
`no_NumberOfResults`	input, outbound	input, inbound
`no_Candidates`	input, outbound	input, inbound
`Timeout`	input, outbound	input, inbound
`no_AuditData`	input, outbound	input, inbound
`NumberOfResults`	output, inbound	output, outbound
the members of the parameter group "Candidate" (see 9.2.18) with their names prefixed by "`Candidate_1_`"	output, inbound	output, outbound
the members of the parameter group "Candidate" with their names prefixed by "`Candidate_2_`"	output, inbound	output, outbound
the members of the parameter group "Candidate" with their names prefixed by "`Candidate_3_`"	output, inbound	output, outbound
the members of the parameter group "Candidate" with their names prefixed by "`Candidate_4_`"	output, inbound	output, outbound
`AuditData`	output, inbound	output, outbound
`Return`	return, inbound	output, outbound

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

The specification of the constraints on the parameters, function invocation input, function invocation output, and bound activity invocation input of the function `BioAPI_Identify` also applies to this standard BioAPI interface function.

9.91.2 Bound activity invocation output

9.91.2.1 If the native parameter `Candidates` is not NULL and the integer (say, *N*) represented by the outbound value of `NumberOfResults` is greater than 0, then a memory block of sufficient size to contain an array of *N* elements of type `BioAPI_CANDIDATE` shall be allocated and its address shall be written to the variable pointed to by the native parameter `Candidates`.

9.91.2.2 The outbound value of `NumberOfResults` shall be processed as follows. If the native parameter with the same name is NULL, then the outbound value shall be ignored. Otherwise, the integer

© ISO/IEC 2017 – All rights reserved

represented by the outbound value shall be written to the variable of type `uint32_t` pointed to by the native parameter `NumberOfResults`.

9.91.2.3 The outbound value of the parameter group "Candidate" with the prefix `Candidate_X_` (with *X* = 1, 2, 3, or 4) shall be processed as follows. If the native parameter `Candidates` is NULL or the integer represented by the outbound value of `NumberOfResults` is less than *X*, then the outbound value of the parameter group shall be ignored. Otherwise, the value of type `BioAPI_CANDIDATE` represented by the outbound value of the parameter group shall be written to the element at position *X* of the array of elements of type `BioAPI_CANDIDATE` pointed to by the variable pointed to by the native parameter `Candidates`.

9.91.2.4 The outbound value of `AuditData` shall be processed as follows. If the native parameter with the same name is NULL, then the outbound value shall be ignored. Otherwise, the integer represented by the outbound value shall be written to the variable of type `BioAPI_BIR_HANDLE` pointed to by the native parameter `AuditData`.

9.91.2.5 The integer represented by the outbound value of `return` shall be returned by the native function.

9.91.3 Default output

If there is no activity bound to this standard BioAPI interface function, then

a) the variable pointed to by the native parameter `NumberOfResults` shall be set to zero,

b) the variable pointed to by the native parameter `Candidates` shall be set to NULL,

c) the variable pointed to by the native parameter `AuditData` shall be set to zero, and

d) the native function shall return zero.

9.92 BioSPI_Import

9.92.1 Function invocation scheme

This function belongs to the BioSPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioSPI_Import(

BioAPI_HANDLE BSPHandle,

const BioAPI_DATA *InputData,

const BioAPI_BIR_BIOMETRIC_DATA_FORMAT *InputFormat,

const BioAPI_BIR_BIOMETRIC_DATA_FORMAT *OutputFormat,

BioAPI_BIR_PURPOSE Purpose,

BioAPI_BIR_HANDLE *ConstructedBIR);

and the following parameters (see Table 100).

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

Table 100

Parameter	Function invocation (conformance testing model for BSPs)	Bound activity invocation (conformance testing model for frameworks)
BSPHandle	input, outbound	input, inbound
InputData	input, outbound	input, inbound
InputFormatOwner	input, outbound	input, inbound
InputFormatType	input, outbound	input, inbound
OutputFormatOwner	input, outbound	input, inbound
OutputFormatType	input, outbound	input, inbound
Purpose	input, outbound	input, inbound
no_ConstructedBIR	input, outbound	input, inbound
ConstructedBIR	output, inbound	output, outbound
return	return, inbound	output, outbound

The specification of the constraints on the parameters, function invocation input, function invocation output, and bound activity invocation input of the function BioAPI_Import also applies to this standard BioAPI interface function.

9.92.2 Bound activity invocation output

9.92.2.1 The outbound value of ConstructedBIR shall be processed as follows. If the native parameter with the same name is NULL, then the outbound value shall be ignored. Otherwise, the integer represented by the outbound value shall be written to the variable of type BioAPI_BIR_HANDLE pointed to by the native parameter ConstructedBIR.

9.92.2.2 The integer represented by the outbound value of return shall be returned by the native function.

9.92.3 Default output

If there is no activity bound to this standard BioAPI interface function, then

a) the variable pointed to by the native parameter ConstructedBIR shall be set to zero, and

b) the native function shall return zero.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.93 BioSPI_Export

9.93.1 Function invocation scheme

This function belongs to the BioSPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioSPI_Export(

BioAPI_HANDLE BSPHandle,

BioAPI_BIR_HANDLE Handle,

const BioAPI_BIR_BIOMETRIC_DATA_FORMAT *OutputBDBFormat,

const BioAPI_BIR_SECURITY_BLOCK_FORMAT *OutputSBFormat,

BioAPI_BIR *BIR);

and the following parameters (see Table 101).

Table 101

Parameter	Function invocation (conformance testing model for BSPs)	Bound activity invocation (conformance testing model for frameworks)
`BSPHandle`	input, outbound	input, inbound
`Handle`	input, outbound	input, inbound
`OutputBDBFormat`	input, outbound	input, inbound
`OutputSBFormat`	input, outbound	input, inbound
`no_BIR`	input, outbound	input, inbound
the members of the parameter group "BIR" (see 9.2.15)	output, inbound	input, inbound
`return`	return, inbound	input, inbound

The specification of the constraints on the parameters, function invocation input, function invocation output, and bound activity invocation input of the function `BioAPI_Export` also applies to this standard BioAPI interface function.

9.93.2 Bound activity invocation output

9.93.2.1 The inbound value of `BSPHandle` shall be the canonical representation of the integer in the native parameter with the same name.

9.93.2.2 The inbound value of `no_Handle` shall be "`true`" if the native parameter Handle is NULL; otherwise, it shall be "`false`".

9.93.2.3 The inbound value of `OutputBDBFormat` shall be the canonical representation of the integer in the fields of the variable of type `BioAPI_BIR_BIOMETRIC_DATA_FORMAT` pointed to by the native parameter `OutputBDBFormat`.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

 © ISO/IEC 2017 – All rights reserved

9.93.2.4 The inbound value of `OutputSBFormat` shall be the canonical representation of the integer in the fields of the variable of type `BioAPI_BIR_SECURITY_BLOCK_FORMAT` pointed to by the native parameter `OutputSBFormat`.

9.93.2.5 The inbound value of `no_BIR` shall be "`true`" if the native parameter `BIR` is NULL; otherwise, it shall be "`false`".

9.93.2.6 The integer represented by the outbound value of `return` shall be returned by the native function.

9.93.3 Default output

If there is no activity bound to this standard BioAPI interface function, then

a) the variable pointed to by the native parameter `BIR` shall be set to NULL and

b) the native function shall return zero.

9.94 BioSPI_PresetIdentifyPopulation

9.94.1 Function invocation scheme

This function belongs to the BioSPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioSPI_PresetIdentifyPopulation(

BioAPI_HANDLE BSPHandle,

const BioAPI_IDENTIFY_POPULATION *Population);

and the following parameters (see Table 102).

Table 102

Parameter	Function invocation (conformance testing model for BSPs)	Bound activity invocation (conformance testing model for frameworks)
`BSPHandle`	input, outbound	input, inbound
members of the parameter group "Identify population" (see 9.2.17)	input, outbound	input, inbound
`return`	return, inbound	output, outbound

The specification of the constraints on the parameters, function invocation input, function invocation output, and bound activity invocation input of the function `BioAPI_PresetIdentifyPopulation` also applies to this standard BioAPI interface function.

9.94.2 Bound activity invocation output

The integer represented by the outbound value of `return` shall be returned by the native function.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.94.3 Default output

If there is no activity bound to this standard BioAPI interface function, the native function shall return zero.

9.95 BioSPI_Transform

9.95.1 Function invocation scheme

This function belongs to the BioSPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioSPI_Transform(

BioAPI_HANDLE BSPHandle,

const BioAPI_UUID *OperationUUID,

const BioAPI_INPUT_BIR *InputBIRs,

uint32_t NumberOfInputBIRs,

BioAPI_BIR_HANDLE **OutputBIR,

uint32_t *NumberOfOutputBIRs);

and the following parameters (see Table 103).

Table 103

Parameter	Function invocation (conformance testing model for BSPs)	Bound activity invocation (conformance testing model for frameworks)
`BSPHandle`	input, outbound	input, inbound
`OperationUUID`	input, outbound	input, inbound
the members of the parameter group “Input BIR” (see 9.2.16) with their names prefixed by “`InputBIRs_`”	input, outbound	input, inbound
`NumberOfInputBIRs`	input, outbound	input, inbound
`no_OutputBIR`	input, outbound	input, inbound
`OutputBIR`	output, inbound	input, inbound
`NumberOfOutputBIRs`	output, inbound	input, inbound
`return`	return, inbound	output, outbound

The specification of the constraints on the parameters, function invocation input, function invocation output, and bound activity invocation input of the function `BioAPI_Transform` also applies to this standard BioAPI interface function.

9.95.2 Bound activity invocation output

9.95.2.1 The inbound value of `BSPHandle` and `NumberOfInputBIRs` shall be the canonical representation of the integer in the native parameter with the same name.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.95.2.2 The inbound value of `OperationUUID` shall be the canonical representation of the UUID in the variable of type `BioAPI_UUID` pointed to by the native parameter `OperationUUID`.

9.95.2.3 The inbound value of the parameter group "Input BIR" with the prefix "`InputBIRs_`" shall be the canonical representation (see 9.2.16.5) of the value of type `BioAPI_INPUT_BIR` in the variable pointed to by the native parameter `InputBIRs`.

9.95.2.4 The inbound value of `no_OutputBIR` shall be "`true`" if the native parameter `OutputBIR` is NULL; otherwise, it shall be "`false`".

9.95.2.5 The integer represented by the outbound value of `return` shall be returned by the native function.

9.95.3 Default output

If there is no activity bound to this standard BioAPI interface function, then

a) the variable pointed to by the native parameter `OutputBIR` shall be set to zero,

b) the variable pointed to by the native parameter `NumberOfOutputBIRs` shall be set to zero, and

c) the native function shall return zero.

9.96 BioSPI_DbOpen

9.96.1 Function invocation scheme

This function belongs to the BioSPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioSPI_DbOpen(

BioAPI_HANDLE BSPHandle,

const BioAPI_UUID *DbUuid,

BioAPI_DB_ACCESS_TYPE AccessRequest,

BioAPI_DB_HANDLE *DbHandle,

BioAPI_DB_MARKER_HANDLE *MarkerHandle);

and the following parameters (see Table 104).

Table 104

Parameter	Function invocation (conformance testing model for BSPs)	Bound activity invocation (conformance testing model for frameworks)
`BSPHandle`	input, outbound	input, inbound
`DbUuid`	input, outbound	input, inbound
the members of the parameter group "Access type" (see 9.2.20)	input, outbound	input, inbound

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

Table 104 *(continued)*

Parameter	Function invocation (conformance testing model for BSPs)	Bound activity invocation (conformance testing model for frameworks)
`no_DbHandle`	input, outbound	input, inbound
`no_MarkerHandle`	input, outbound	input, inbound
`DbHandle`	output, inbound	output, outbound
`MarkerHandle`	output, inbound	output, outbound
`return`	return, inbound	output, outbound

The specification of the constraints on the parameters, function invocation input, function invocation output, and bound activity invocation input of the function `BioAPI_DbOpen` also applies to this standard BioAPI interface function.

9.96.2 Bound activity invocation output

9.96.2.1 The outbound value of `DbHandle` shall be processed as follows. If the native parameter with the same name is NULL, then the outbound value shall be ignored. Otherwise, the integer represented by the outbound value shall be written to the variable of type `BioAPI_DB_HANDLE` pointed to by the native parameter `DbHandle`.

9.96.2.2 The outbound value of `MarkerHandle` shall be processed as follows. If the native parameter with the same name is NULL, then the outbound value shall be ignored. Otherwise, the integer represented by the outbound value shall be written to the variable of type `BioAPI_DB_MARKER_HANDLE` pointed to by the native parameter `MarkerHandle`.

9.96.2.3 The integer represented by the outbound value of `return` shall be returned by the native function.

9.96.3 Default output

If there is no activity bound to this standard BioAPI interface function, then

a) the variable pointed to by the native parameter `DbHandle` shall be set to zero,

b) the variable pointed to by the native parameter `MarkerHandle` shall be set to zero, and

c) the native function shall return zero.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.97 BioSPI_DbClose

9.97.1 Function invocation scheme

This function belongs to the BioSPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioSPI_DbClose(

BioAPI_HANDLE BSPHandle,

BioAPI_DB_HANDLE DbHandle);

and the following parameters (see Table 105).

Table 105

Parameter	Function invocation (conformance testing model for BSPs)	Bound activity invocation (conformance testing model for frameworks)
`BSPHandle`	input, outbound	input, inbound
`DbHandle`	input, outbound	input, inbound
`return`	return, inbound	output, outbound

The specification of the constraints on the parameters, function invocation input, function invocation output, and bound activity invocation input of the function `BioAPI_DbClose` also applies to this standard BioAPI interface function.

9.97.2 Bound activity invocation output

The integer represented by the outbound value of `return` shall be returned by the native function.

9.97.3 Default output

If there is no activity bound to this standard BioAPI interface function, the native function shall return zero.

9.98 BioSPI_DbCreate

9.98.1 Function invocation scheme

This function belongs to the BioSPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioSPI_DbCreate(

BioAPI_HANDLE BSPHandle,

const BioAPI_UUID *DbUuid,

uint32_t NumberOfRecords,

BioAPI_DB_ACCESS_TYPE AccessRequest,

BioAPI_DB_HANDLE *DbHandle);

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

and the following parameters (see Table 106).

Table 106

Parameter	Function invocation (conformance testing model for BSPs)	Bound activity invocation (conformance testing model for frameworks)
`BSPHandle`	input, outbound	input, inbound
`DbUuid`	input, outbound	input, inbound
`NumberOfRecords`	input, outbound	input, inbound
the members of the parameter group "Access type" (see 9.2.20)	input, outbound	input, inbound
`no_DbHandle`	input, outbound	input, inbound
`DbHandle`	output, inbound	output, outbound
`Return`	return, inbound	output, outbound

The specification of the constraints on the parameters, function invocation input, function invocation output, and bound activity invocation input of the function `BioAPI_DbCreate` also applies to this standard BioAPI interface function.

9.98.2 Bound activity invocation output

9.98.2.1 The outbound value of `DbHandle` shall be processed as follows. If the native parameter with the same name is NULL, then the outbound value shall be ignored. Otherwise, the integer represented by the outbound value shall be written to the variable of type `BioAPI_DB_HANDLE` pointed to by the native parameter `DbHandle`.

9.98.2.2 The integer represented by the outbound value of `return` shall be returned by the native function.

9.98.3 Default output

If there is no activity bound to this standard BioAPI interface function, then

a) the variable pointed to by the native parameter `DbHandle` shall be set to zero, and

b) the native function shall return zero.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.99 BioSPI_DbDelete

9.99.1 Function invocation scheme

This function belongs to the BioSPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioSPI_DbDelete(

BioAPI_HANDLE BSPHandle,

const BioAPI_UUID *DbUuid);

and the following parameters (see Table 107).

Table 107

Parameter	Function invocation (conformance testing model for BSPs)	Bound activity invocation (conformance testing model for frameworks)
`BSPHandle`	input, outbound	input, inbound
`DbUuid`	input, outbound	input, inbound
`return`	return, inbound	output, outbound

The specification of the constraints on the parameters, function invocation input, function invocation output, and bound activity invocation input of the function `BioAPI_DbDelete` also applies to this standard BioAPI interface function.

9.99.2 Bound activity invocation output

The integer represented by the outbound value of `return` shall be returned by the native function.

9.99.3 Default output

If there is no activity bound to this standard BioAPI interface function, the native function shall return zero.

9.100 BioSPI_DbSetMarker

9.100.1 Function invocation scheme

This function belongs to the BioSPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioSPI_DbSetMarker(

BioAPI_HANDLE BSPHandle,

BioAPI_DB_HANDLE DbHandle,

const BioAPI_UUID *KeyValue,

BioAPI_DB_MARKER_HANDLE MarkerHandle);

and the following parameters (see Table 108).

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

Table 108

Parameter	Function invocation (conformance testing model for BSPs)	Bound activity invocation (conformance testing model for frameworks)
`BSPHandle`	input, outbound	input, inbound
`DbHandle`	input, outbound	input, inbound
`KeyValue`	input, outbound	input, inbound
`MarkerHandle`	input, outbound	input, inbound
`return`	return, inbound	output, outbound

The specification of the constraints on the parameters, function invocation input, function invocation output, and bound activity invocation input of the function `BioAPI_DbSetMarker` also applies to this standard BioAPI interface function.

9.100.2 Bound activity invocation output

The integer represented by the outbound value of `return` shall be returned by the native function.

9.100.3 Default output

If there is no activity bound to this standard BioAPI interface function, then the native function shall return zero.

9.101 BioSPI_DbFreeMarker

9.101.1 Function invocation scheme

This function belongs to the BioSPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioSPI_DbFreeMarker(

BioAPI_HANDLE BSPHandle,

BioAPI_DB_MARKER_HANDLE MarkerHandle);

and the following parameters (see Table 109).

Table 109

Parameter	Function invocation (conformance testing model for BSPs)	Bound activity invocation (conformance testing model for frameworks)
`BSPHandle`	input, outbound	input, inbound
`MarkerHandle`	input, outbound	input, inbound
`return`	return, inbound	output, outbound

The specification of the constraints on the parameters, function invocation input, function invocation output, and bound activity invocation input of the function `BioAPI_DbFreeMarker` also applies to this standard BioAPI interface function.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.101.2 Bound activity invocation output

The integer represented by the outbound value of `return` shall be returned by the native function.

9.101.3 Default output

If there is no activity bound to this standard BioAPI interface function, the native function shall return zero.

9.102 BioSPI_DbStoreBIR

9.102.1 Function invocation scheme

This function belongs to the BioSPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioSPI_DbStoreBIR(

BioAPI_HANDLE BSPHandle,

const BioAPI_INPUT_BIR *BIRToStore,

BioAPI_DB_HANDLE DbHandle,

BioAPI_UUID *BirUuid);

and the following parameters (see Table 110).

Table 110

Parameter	Function invocation (conformance testing model for BSPs)	Bound activity invocation (conformance testing model for frameworks)
`BSPHandle`	input, outbound	input, inbound
the members of the parameter group "Input BIR" (see 9.2.16) with their names prefixed by "`BIRToStore_`"	input, outbound	input, inbound
`DBHandle`	input, outbound	input, inbound
`no_BirUuid`	input, outbound	input, inbound
`BirUuid`	output, inbound	output, outbound
`return`	return, inbound	output, outbound

The specification of the constraints on the parameters, function invocation input, function invocation output, and bound activity invocation input of the function `BioAPI_DbStoreBIR` also applies to this standard BioAPI interface function.

9.102.2 Bound activity invocation output

9.102.2.1 The outbound value of `BirUuid` shall be processed as follows. If the native parameter with the same name is NULL, then the outbound value shall be ignored. Otherwise, the UUID represented

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

by the outbound value shall be written to the variable of type `BioAPI_UUID` pointed to by the native parameter `BirUuid`.

9.102.2.2 The integer represented by the outbound value of `return` shall be returned by the native function.

9.102.3 Default output

If there is no activity bound to this standard BioAPI interface function, then

a) the variable pointed to by the native parameter `BirUuid` shall be set to the UUID "`00000000-0000-0000-0000-000000000000`", and

b) the native function shall return zero.

9.103 BioSPI_DbGetBIR

9.103.1 Function invocation scheme

This function belongs to the BioSPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioSPI_DbGetBIR(

BioAPI_HANDLE BSPHandle,

BioAPI_DB_HANDLE DbHandle,

const BioAPI_UUID *KeyValue,

BioAPI_BIR_HANDLE *RetrievedBIR,

BioAPI_DB_MARKER_HANDLE *MarkerHandle);

and the following parameters (see Table 111).

Table 111

Parameter	Function invocation (conformance testing model for BSPs)	Bound activity invocation (conformance testing model for frameworks)
`BSPHandle`	input, outbound	input, inbound
`DbHandle`	input, outbound	input, inbound
`KeyValue`	input, outbound	input, inbound
`no_RetrievedBIR`	input, outbound	input, inbound
`no_MarkerHandle`	input, outbound	input, inbound
`RetrievedBIR`	output, inbound	output, outbound
`MarkerHandle`	output, inbound	output, outbound
`return`	return, inbound	output, outbound

The specification of the constraints on the parameters, function invocation input, function invocation output, and bound activity invocation input of the function `BioAPI_DbGetBIR` also applies to this standard BioAPI interface function.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.103.2 Bound activity invocation output

9.103.2.1 The outbound value of `RetrievedBIR` shall be processed as follows. If the native parameter with the same name is NULL, then the outbound value shall be ignored. Otherwise, the integer represented by the outbound value shall be written to the variable of type `BioAPI_BIR_HANDLE` pointed to by the native parameter `RetrievedBIR`.

9.103.2.2 The outbound value of `MarkerHandle` shall be processed as follows. If the native parameter with the same name is NULL, then the outbound value shall be ignored. Otherwise, the integer represented by the outbound value shall be written to the variable of type `BioAPI_DB_MARKER_HANDLE` pointed to by the native parameter `MarkerHandle`.

9.103.2.3 The integer represented by the outbound value of `return` shall be returned by the native function.

9.103.3 Default output

If there is no activity bound to this standard BioAPI interface function, then

a) the variable pointed to by the native parameter `RetrievedBIR` shall be set to zero,

b) the variable pointed to by the native parameter `MarkerHandle` shall be set to zero, and

c) the native function shall return zero.

9.104 BioSPI_DbGetNextBIR

9.104.1 Function invocation scheme

This function belongs to the BioSPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioSPI_DbGetNextBIR(

BioAPI_HANDLE BSPHandle,

BioAPI_DB_HANDLE DbHandle,

BioAPI_DB_MARKER_HANDLE MarkerHandle,

BioAPI_BIR_HANDLE *RetrievedBIR,

BioAPI_UUID *BirUuid);

and the following parameters (see Table 112).

Table 112

Parameter	Function invocation (conformance testing model for BSPs)	Bound activity invocation (conformance testing model for frameworks)
`BSPHandle`	input, outbound	input, inbound
`DbHandle`	input, outbound	input, inbound
`MarkerHandle`	input, outbound	input, inbound

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

Table 112 *(continued)*

Parameter	Function invocation (conformance testing model for BSPs)	Bound activity invocation (conformance testing model for frameworks)
no_RetrievedBIR	input, outbound	input, inbound
no_BirUuid	input, outbound	input, inbound
RetrievedBIR	output, inbound	output, outbound
BirUuid	output, inbound	output, outbound
return	return, inbound	output, outbound

The specification of the constraints on the parameters, function invocation input, function invocation output, and bound activity invocation input of the function BioAPI_DbGetNextBIR also applies to this standard BioAPI interface function.

9.104.2 Bound activity invocation output

9.104.2.1 The outbound value of RetrievedBIR shall be processed as follows. If the native parameter with the same name is NULL, then the outbound value shall be ignored. Otherwise, the integer represented by the outbound value shall be written to the variable of type BioAPI_BIR_HANDLE pointed to by the native parameter RetrievedBIR.

9.104.2.2 The outbound value of BirUuid shall be processed as follows. If the native parameter with the same name is NULL, then the outbound value shall be ignored. Otherwise, the UUID represented by the outbound value shall be written to the variable of type BioAPI_UUID pointed to by the native parameter BirUuid.

9.104.2.3 The integer represented by the outbound value of return shall be returned by the native function.

9.104.3 Default output

If there is no activity bound to this standard BioAPI interface function, then

a) the variable pointed to by the native parameter RetrievedBIR shall be set to zero,

b) the variable pointed to by the native parameter BirUuid shall be set to the UUID "00000000-0000-0000-0000-000000000000", and

c) the native function shall return zero.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.105 BioSPI_DbDeleteBIR

9.105.1 Function invocation scheme

This function belongs to the BioSPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioSPI_DbDeleteBIR(

BioAPI_HANDLE BSPHandle,

BioAPI_DB_HANDLE DbHandle,

const BioAPI_UUID *KeyValue);

and the following parameters (see Table 113).

Table 113

Parameter	Function invocation (conformance testing model for BSPs)	Bound activity invocation (conformance testing model for frameworks)
`BSPHandle`	input, outbound	input, inbound
`DbHandle`	input, outbound	input, inbound
`KeyValue`	input, outbound	input, inbound
`return`	return, inbound	output, outbound

The specification of the constraints on the parameters, function invocation input, function invocation output, and bound activity invocation input of the function `BioAPI_DbDeleteBIR` also applies to this standard BioAPI interface function.

9.105.2 Bound activity invocation output

The integer represented by the outbound value of `return` shall be returned by the native function.

9.105.3 Default output

If there is no activity bound to this standard BioAPI interface function, the native function shall return zero.

9.106 BioSPI_SetPowerMode

9.106.1 Function invocation scheme

This function belongs to the BioSPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioSPI_SetPowerMode(

BioAPI_HANDLE BSPHandle,

BioAPI_UNIT_ID UnitID,

BioAPI_POWER_MODE PowerMode);

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

and the following parameters (see Table 114).

Table 114

Parameter	Function invocation (conformance testing model for BSPs)	Bound activity invocation (conformance testing model for frameworks)
`BSPHandle`	input, outbound	input, inbound
`UnitID`	input, outbound	input, inbound
`PowerMode`	input, outbound	input, inbound
`return`	return, inbound	output, outbound

The specification of the constraints on the parameters, function invocation input, function invocation output, and bound activity invocation input of the function `BioAPI_SetPowerMode` also applies to this standard BioAPI interface function.

9.106.2 Bound activity invocation output

The integer represented by the outbound value of `return` shall be returned by the native function.

9.106.3 Default output

If there is no activity bound to this standard BioAPI interface function, the native function shall return zero.

9.107 BioSPI_SetIndicatorStatus

9.107.1 Function invocation scheme

This function belongs to the BioSPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioSPI_SetIndicatorStatus(

BioAPI_HANDLE BSPHandle,

BioAPI_UNIT_ID UnitID,

BioAPI_INDICATOR_STATUS IndicatorStatus);

and the following parameters (see Table 115).

Table 115

Parameter	Function invocation (conformance testing model for BSPs)	Bound activity invocation (conformance testing model for frameworks)
`BSPHandle`	input, outbound	input, inbound
`UnitID`	input, outbound	input, inbound
`IndicatorStatus`	input, outbound	input, inbound
`return`	return, inbound	output, outbound

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

The specification of the constraints on the parameters, function invocation input, function invocation output, and bound activity invocation input of the function `BioAPI_SetIndicatorStatus` also applies to this standard BioAPI interface function.

9.107.2 Bound activity invocation output

The integer represented by the outbound value of `return` shall be returned by the native function.

9.107.3 Default output

If there is no activity bound to this standard BioAPI interface function, the native function shall return zero.

9.108 BioSPI_GetIndicatorStatus

9.108.1 Function invocation scheme

This function belongs to the BioSPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioSPI_GetIndicatorStatus(

BioAPI_HANDLE BSPHandle,

BioAPI_UNIT_ID UnitID,

BioAPI_INDICATOR_STATUS *IndicatorStatus);

and the following parameters (see Table 116).

Table 116

Parameter	Function invocation (conformance testing model for BSPs)	Bound activity invocation (conformance testing model for frameworks)
`BSPHandle`	input, outbound	input, inbound
`UnitID`	input, outbound	input, inbound
`no_IndicatorStatus`	input, outbound	input, inbound
`IndicatorStatus`	output, inbound	output, outbound
`return`	return, inbound	output, outbound

The specification of the constraints on the parameters, function invocation input, function invocation output, and bound activity invocation input of the function `BioAPI_GetIndicatorStatus` also applies to this standard BioAPI interface function.

9.108.2 Bound activity invocation output

9.108.2.1 The outbound value of `IndicatorStatus` shall be processed as follows. If the native parameter with the same name is NULL, then the outbound value shall be ignored. Otherwise, the integer represented by the outbound value shall be written to the variable of type `BioAPI_INDICATOR_STATUS` pointed to by the native parameter `IndicatorStatus`.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

9.108.2.2 The integer represented by the outbound value of `return` shall be returned by the native function.

9.108.3 Default output

If there is no activity bound to this standard BioAPI interface function, then

a) the variable pointed to by the native parameter `IndicatorStatus` shall be set to zero, and

b) the native function shall return zero.

9.109 BioSPI_CalibrateSensor

9.109.1 Function invocation scheme

This function belongs to the BioSPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioSPI_CalibrateSensor(

BioAPI_HANDLE BSPHandle,

int32_t Timeout);

and the following parameters (see Table 117).

Table 117

Parameter	Function invocation (conformance testing model for BSPs)	Bound activity invocation (conformance testing model for frameworks)
`BSPHandle`	input, outbound	input, inbound
`Timeout`	input, outbound	input, inbound
`return`	return, inbound	output, outbound

The specification of the constraints on the parameters, function invocation input, function invocation output, and bound activity invocation input of the function `BioAPI_CalibrateSensor` also applies to this standard BioAPI interface function.

9.109.2 Bound activity invocation output

The integer represented by the outbound value of `return` shall be returned by the native function.

9.109.3 Default output

If there is no activity bound to this standard BioAPI interface function, the native function shall return zero.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

 © ISO/IEC 2017 – All rights reserved

9.110 BioSPI_Cancel

9.110.1 Function invocation scheme

This function belongs to the BioSPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioSPI_Cancel(

BioAPI_HANDLE BSPHandle);

and the following parameters (see Table 118).

Table 118

Parameter	Function invocation (conformance testing model for BSPs)	Bound activity invocation (conformance testing model for frameworks)
`BSPHandle`	input, outbound	input, inbound
`return`	return, inbound	output, outbound

The specification of the constraints on the parameters, function invocation input, function invocation output, and bound activity invocation input of the function `BioAPI_Cancel` also applies to this standard BioAPI interface function.

9.110.2 Bound activity invocation output

The integer represented by the outbound value of `return` shall be returned by the native function.

9.110.3 Default output

If there is no activity bound to this standard BioAPI interface function, the native function shall return zero.

9.111 BioSPI_Free

9.111.1 Function invocation scheme

This function belongs to the BioSPI interface and has the following native prototype:

BioAPI_RETURN BioAPI

BioSPI_Free(

void* Ptr);

and the following parameters (see Table 119).

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

Table 119

Parameter	Function invocation (conformance testing model for BSPs)	Bound activity invocation (conformance testing model for frameworks)
`Ptr`	input, outbound	input, inbound
`return`	return, inbound	output, outbound

The specification of the constraints on the parameters, function invocation input, function invocation output, and bound activity invocation input of the function `BioAPI_Free` also applies to this standard BioAPI interface function.

9.111.2 Bound activity invocation output

The integer represented by the outbound value of `return` shall be returned by the native function.

9.111.3 Default output

If there is no activity bound to this standard BioAPI interface function, the native function shall return zero.

9.112 BioAPI_GUI_STATE_EVENT_HANDLER

9.112.1 Function invocation scheme

This function belongs to the application callback interface and has the following native prototype:

typedef BioAPI_RETURN (BioAPI *BioAPI_GUI_STATE_EVENT_HANDLER)(

const BioAPI_UUID *BSPUuid,

BioAPI_UNIT_ID UnitID,

const BioAPI_HANDLE *BSPHandle,

const void *GUIStateEventHandlerCtx,

BioAPI_GUI_OPERATION Operation,

BioAPI_GUI_SUBOPERATION Suboperation,

BioAPI_BIR_PURPOSE Purpose,

BioAPI_GUI_MOMENT Moment,

BioAPI_RETURN ResultCode,

int32_t EnrollSampleIndex,

const BioAPI_GUI_ IMAGE_DATA_ARRAY *Images,

const uint8_t *Text,

BioAPI_GUI_RESPONSE *Response,

int32_t *EnrollSampleIndexToRecapture);

and the following parameters (see Table 120).

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved

Table 120

Parameter	Bound activity invocation (conformance testing model for applications)	Bound activity invocation (conformance testing model for frameworks)
BSPUuid	input, inbound	input, inbound
UnitID	input, inbound	input, inbound
BSPHandle	input, inbound	input, inbound
GUIStateEventHandlerCtx	input, inbound	input, inbound
Operation	input, inbound	input, inbound
Suboperation	input, inbound	input, inbound
Purpose	input, inbound	input, inbound
Moment	input, inbound	input, inbound
ResultCode	input, inbound	input, inbound
EnrollSampleIndex	input, inbound	input, inbound
Images	input, inbound	input, inbound
Text	input, inbound	input, inbound
Response	output, inbound	input, inbound
EnrollSampleIndexToRecapture	output, inbound	input, inbound
return	input, inbound	input, inbound

9.112.2 Bound activity invocation output

9.112.2.1 The inbound value of BSPUuid shall be the canonical representation of the UUID in the variable of type BioAPI_UUID pointed to by the native parameter BSPUuid.

9.112.2.2 An outbound value of UnitID and GUIStateEventHandlerCtx shall be either a valid representation of an integer (see 7.4) in the range 0 to 4294967295 or an empty string. An inbound value shall be the canonical representation of an integer (see 7.4.3) in the same range.

9.112.2.3 The inbound value of BSPHandle shall be the canonical representation of the integer in the native parameter with the same name.

9.112.2.4 An outbound value of the parameter group "Operation" shall be a valid representation of a value of the native type BioAPI_GUI_OPERATION. An inbound value shall be the canonical representation of a value of that type.

9.112.2.5 An outbound value of the parameter group "Suboperation" shall be a valid representation of a value of the native type BioAPI_GUI_SUBOPERATION. An inbound value shall be the canonical representation of a value of that type.

9.112.2.6 An outbound value of the parameter group "Purpose" shall be a valid representation of a value of the native type BioAPI_BIR_PURPOSE. An inbound value shall be the canonical representation of a value of that type.

9.112.2.7 An outbound value of the parameter group "Moment" shall be a valid representation of a value of the native type BioAPI_GUI_MOMENT. An inbound value shall be the canonical representation of a value of that type.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 24709-1:2017

© ISO/IEC 2017 – All rights reserved