
**Information technology — Document
description and processing languages —
Office Open XML File Formats —**

**Part 1:
Fundamentals and Markup Language
Reference**

AMENDMENT 1

*Technologies de l'information — Description des documents et
langages de traitement — Formats de fichier "Office Open XML" —*

Partie 1: Principes essentiels et référence de langage de balisage

AMENDEMENT 1

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2010

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Foreword	xviii
Notational conventions	xix
1. §2.6.1, “Base Application Description”, p. 5	1
2. §2.6.2, “Full Application Description, p. 5	1
3. §11.2, “Package Structure”, p. 30	1
4. §11.3.1, “Alternative Format Import Part”, p. 32	1
5. §11.3.2, “Comments Part”, p. 34	1
6. §11.3.3, “Document Settings Part”, p. 36	2
7. §11.3.4, “Endnotes Part”, p. 37	2
8. §11.3.5, “Font Table Part”, p. 40	2
9. §11.3.6, “Footer Part”, p. 41	2
10. §11.3.7, “Footnotes Part”, p. 43	2
11. §11.3.8, “Glossary Document Part”, p. 46	2
12. §11.3.9, “Header Part”, p. 48	3
13. §11.3.10, “Main Document Part”, p. 51	3
14. §11.3.11, “Numbering Definitions Part”, p. 52	3
15. §11.3.12, “Style Definitions Part”, p. 55	3
16. §11.3.13, “Web Settings Part”, p. 57	3
17. §11.4, “Document Template”, p. 58	3
18. §11.5, “Framesets”, p. 58	3
19. §11.6, “Master Documents and Subdocuments”, p. 59	4
20. §11.7, “Mail Merge Data Source”, p. 61	4
21. §11.8, “Mail Merge Header Data Source”, p. 61	4
22. §11.9, “XSL Transformation”, p. 62	4
23. §12.2, “Package Structure”, pp. 65–66	4
24. §12.3, “Part Summary”, pp. 67–68	4
25. §12.3.1, “Calculation Chain Part”, p. 68	5
26. §12.3.2, “Chartsheet Part”, p. 69	5
27. §12.3.3, “Comments Part”, p. 70	5
28. §12.3.4, “Connections Part”, p. 71	5
29. §12.3.5, “Custom Property Part”, p. 73	5

30.	§12.3.6, “Custom XML Mappings Part”, p. 74.....	6
31.	§12.3.6, “Custom XML Mappings Part”, p. 74.....	6
32.	§12.3.7, “Dialogsheet Part”, p. 75	6
33.	§12.3.8, “Drawings Part”, p. 77	6
34.	§12.3.9, “External Workbook References Part”, p. 78	6
35.	§12.3.10, “Metadata part”, pp. 80–81.....	6
36.	§12.3.11, “Pivot Table Part”, p. 83	6
37.	§12.3.12, “Pivot Table Cache Definition Part”, p. 84.....	7
38.	§12.3.13, “Pivot Table Cache Records Part”, p. 86.....	7
39.	§12.3.14, “Query Table Part”, p. 87	7
40.	§12.3.15, “Shared Strings Table Part”, p. 88.....	7
41.	§12.3.16, “Shared Workbook Revision Headers Part”, p. 89.....	7
42.	§12.3.17, “Shared Workbook Revision Log Part”, p. 90	7
43.	§12.3.18, “Shared Workbook User Data Part”, pp. 91–92	8
44.	§12.3.19, “Single Cell Table Definition Part”, p. 92–93	8
45.	§12.3.20, “Styles Part”, p. 94.....	8
46.	§12.3.21, “Table Definition Part”, p. 95.....	8
47.	§12.3.22, “Volatile Dependencies Part”, p. 96.....	8
48.	§12.3.23, “Workbook Part”, p. 97	9
49.	§12.3.24, “Worksheet Part”, p. 99.....	9
50.	§12.4, “External Workbooks”, p. 101	9
51.	§13.2, “Package Structure”, p. 104.....	9
52.	§13.3.1, “Comment Authors Part”, p. 107	9
53.	§13.3.2, “Comments Part”, p. 108	9
54.	§13.3.3, “Handout Master Part”, p. 109	10
55.	§13.3.4, “Notes Master Part”, p. 111.....	10
56.	§13.3.5, “Notes Slide Part”, p. 112	10
57.	§13.3.6, “Presentation Part”, pp. 113–114	10
58.	§13.3.7, “Presentation Properties Part”, p. 115	10
59.	§13.3.8, “Slide Part”, p. 116	10
60.	§13.3.9, “Slide Layout Part”, p. 118.....	11
61.	§13.3.10, “Slide Master Part”, p. 120	11

62.	§13.3.11, “Slide Synchronization Data Part”, p. 121	11
63.	§13.3.12, “User Defined Tags Part”, p. 122.....	11
64.	§13.3.31, “View Properties Part”, p. 123	11
65.	§13.4, “HTML Publish Location”, p. 124	11
66.	§13.5, “Slide Synchronization Server Location”, p. 125	11
67.	§14.2.1, “Chart Part”, p. 128	12
68.	§14.2.2, “Chart Drawing Part”, p. 130	12
69.	§14.2.3, “Diagram Colors Part”, p. 131	12
70.	§14.2.4, “Diagram Data Part”, p. 132	12
71.	§14.2.5, “Diagram Layout Definition Part”, pp. 133–134	12
72.	§14.2.6, “Diagram Style Part”, p. 135	12
73.	§14.2.7, “Theme Part”, p. 136	13
74.	§14.2.8, “Theme Override Part”, p. 138	13
75.	§14.2.9, “Table Styles Part”, p. 139	13
76.	§15.2.2, “Audio Part”, p. 144.....	13
77.	§15.2.3, “Bibliography Part”, pp. 144–145	13
78.	§15.2.4, “Content Part”, p. 146	13
79.	§15.2.5, “Custom XML Data Storage Part”, p. 147	13
80.	§15.2.6, “Custom XML Data Storage Properties Part”, p. 147.....	14
81.	§15.2.9, “Embedded Control Persistence Part”, p. 150.....	14
82.	§15.2.9, “Embedded Control Persistence Part”, p. 151.....	14
83.	§15.2.10, “Embedded Object Part”, p. 152	14
84.	§15.2.11, “Embedded Package Part”, p. 154	14
85.	§15.2.12.2, “Custom File Properties Part”, p. 156.....	14
86.	§15.2.12.3, “Extended File Properties Part”, p. 158.....	14
87.	§15.2.13, “Font Part”, p. 160	15
88.	§15.2.14, “Image Part”, p. 160	15
89.	§15.2.15, “Printer Settings Part”, p. 161.....	15
90.	§15.2.16, “Thumbnail Part”, p. 163	15
91.	§15.2.17, “Video Part”, p. 164.....	15
92.	§15.3, “Hyperlinks Part”, p. 164	15
93.	§16.2, “SpreadsheetML Summary”, p. 167.....	15

94. §17.3.2.43, “w (Expanded/Compressed Text)”, pp. 342–343.....	16
95. §17.3.3.2, “contentPart (ContentPart)”, p. 346	16
96. §17.3.3.2, “contentPart (ContentPart)”, p. 348	16
97. §17.3.3.2, “contentPart (ContentPart)”, p. 348, attribute id.....	17
98. §17.3.3.3, “control (Embedded Control)”, p. 349, attribute id.....	17
99. §17.3.3.17, “movie (Embedded Video)”, p. 361.....	18
100. §17.3.3.17, “movie (Embedded Video)”, p. 362, attribute id.....	18
101. §17.3.3.20, “objectEmbed (Embedded Object Properties)”, p. 366, attribute id	19
102. §17.3.3.21, “objectLink (Linked Object Properties)”, p. 368, attribute id.....	19
103. §17.4.88, “Table Measurement (CT_TblWidth)”, p. 527, attribute w.....	19
104. §17.6.2, “bottom (Bottom Border)”, pp. 612–614, attribute various.....	20
105. §17.6.7, “left (LeftBorder)”, p. 630, attribute id	21
106. §17.6.14, “printerSettings (Reference to Printer Settings Data)”, p. 650, attribute id	21
107. §17.6.15, “right (Right Border)”, p. 653, attribute id	22
108. §17.6.21, “top (Top Border)”, pp. 670–676, attribute various	22
109. §17.8.3.3, “embedBold (Bold Style Font Style Embedding)”, p. 754, attribute id.....	23
110. §17.8.3.4, “embedBoldItalic (Bold Italic Font Style Embedding)”, p. 756, attribute id	24
111. §17.8.3.5, “embedItalic (Italic Font Style Embedding)”, pp. 758–759, attribute id	25
112. §17.8.3.6, “embedRegular (Regular Font Style Embedding)”, pp. 760–761, attribute id.....	26
113. §17.10.2, “footerReference (Footer Reference)”, pp. 823–824.....	26
114. §17.10.2, “footerReference (Footer Reference)”, p. 825, attribute id.....	27
115. §17.10.5, “headerReference (Header Reference)”, pp. 832–834	27
116. §17.10.5, “headerReference (Header Reference)”, p. 834, attribute id	28
117. §17.14.9, “dataSource (Data Source File Path)”, pp. 1057–1058, attribute id.....	29
118. §17.14.9, “dataSource (Data Source File Path)”, p. 1058, attribute id	29
119. §17.14.16, “headerSource (Header Definition File Path)”, p. 1064	30
120. §17.14.16, “headerSource (Header Definition File Path)”, p. 1065, attribute id	30
121. §17.14.28, “recipientData (Reference to Inclusion/Exclusion Data for Data Source)”, pp. 1079–1080	30
122. §17.14.28, “recipientData (Reference to Inclusion/Exclusion Data for Data Source)”, p. 1080–1081, attribute id.....	31
123. §17.14.30, “src (ODSO Data Source File Path)”, p. 1083	32
124. §17.14.30, “src (ODSO Data Source File Path)”, p. 1083, attribute id.....	32
125. §17.14.35, “uniqueTag (Unique Value for Record)”, pp. 1088–1089.....	32

126. §17.15.1.6, “attachedTemplate (Attached Document Template)”, pp. 1097–1098, attribute id	33
127. §17.15.1.76, “saveThroughXslt (Custom XSL Transform To Use When Saving As XML File)”, p. 1193, attribute id	33
128. §17.15.2.23, longDesc (Frame Long Description)”, p. 1253.....	34
129. §17.15.2.23, “longDesc (Frame Long Description)”, p. 1253, attribute id	34
130. §17.15.2.39, “sourceFileName (Source File for Frame)”, p. 1276.....	34
131. §17.15.2.39, “sourceFileName (Source File for Frame)”, pp. 1277–1278, attribute id.....	35
132. §17.16.22, “hyperlink (Hyperlink)”, p. 1426, attribute id.....	35
133. §17.17.1.1, “subDoc (Anchor for Subdocument Location)”, pp. 1444–1445	35
134. §17.17.1.1, “subDoc (Anchor for Subdocument Location)”, p. 1446, attribute id	36
135. §17.17.2.1, “altChunk (Anchor for Imported External Content)”, pp. 1447–1448	37
136. §17.17.2.1, “altChunk (Anchor for Imported External Content)”, p. 1449, attribute id.....	37
137. §17.18, “Simple Types”, p. 1453.....	37
138. §17.18.95, “ST_TextScale (Text Expansion/Compression Percentage)”, p. 1668.....	37
139. §17.18.106, “ST_TextScalePercent (Text Expansion/Compression Percentage), new subclause	38
140. §17.18.107, “ST_MeasurementOrPercent (Measurement or Percentage Value)”, new subclause	39
141. §18.2.7, “ext (Extension)”, p. 1721.....	39
142. §18.2.8, “externalReference (External Reference)”, p. 1722, attribute id.....	40
143. §18.2.17, “pivotCache (PivotCache)”, p. 1731, attribute id.....	40
144. §18.2.19, “sheet (Sheet Information)”, p. 1732, attribute id	40
145. §18.2.27, “workbook (Workbook)”, p. 1739.....	41
146. §18.3.1.19, “control (Embedded Control)”, p. 1776, attribute id	41
147. §18.3.1.20, “controlPr (Embedded Control Properties)”, p. 1779, attribute id	41
148. §18.3.1.22, “customPr (Custom Property)”, p. 1782, attribute id	42
149. §18.3.1.30, “dataRef (Data Consolidation Reference)”, p. 1790, attribute id	42
150. §18.3.1.36, “drawing (Drawing)”, p. 1796, attribute id.....	42
151. §18.3.1.37, “drawingHF (Drawing Reference in Header Footer)”, pp. 1798–1799, attribute id.....	43
152. §18.3.1.47, “hyperlink (Hyperlink)”, p. 1812, attribute id.....	43
153. §18.3.1.56, “objectPr (Embedded Object Properties)”, p. 1821, attribute id	44
154. §18.3.1.59, “oleObject (Embedded Object)”, p. 1824, attribute id	44
155. §18.3.1.63, “pageSetup (Page Setup Settings)”, p. 1829, attribute id	44
156. §18.3.1.64, “pageSetup (Chart Sheet Page Setup)”, p. 1832, attribute id	45
157. §18.3.1.67, “picture (Background Image)”, p. 1837, attribute id	45

158. §18.3.1.69, “pivotSelection (PivotTable Selection)”, p. 1841, attribute id	45
159. §18.3.1.94, “tablePart (Table Part)”, p. 1882, attribute id	46
160. §18.4, “Shared String Table”, pp. 1896–1897	46
161. §18.4.1, “charset (Character Set)”, p. 1898	46
162. §18.5, “Tables”, p. 1907	47
163. §18.6, “Calculation Chain”, pp. 1925–1926	47
164. §18.8.18, “family (Font Family)”, p. 1952	47
165. §18.9, “Metadata”, p. 1994	48
166. §18.10.1.67, “pivotCacheDefinition (PivotCache Definition)”, p. 2095, attribute id	49
167. §18.10.1.79, “rangeSet (Range Set)”, p. 2154, attribute id	49
168. §18.10.1.95, “worksheetSource (Worksheet PivotCache Source)”, p. 2170, attribute id	49
169. §18.11.1.1, “header (Header)”, p. 2180, attribute id	50
170. §18.14.7, “externalBook (External Workbook)”, p. 2248, attribute id	50
171. §18.14.11, “oleLink (Generic Object Link Connection)”, p. 2251, attribute id	50
172. §18.17.2.3, “Cell References”, pp. 2282–2284	51
173. §18.17.5.2, “Precision”, p. 2296	51
174. §18.17.7.204, “MATCH”, p. 2510	51
175. §18.18, “Simple Types”, p. 2664	52
176. §18.18.94, “ST_FontFamily (Font Family)”, new subclause	52
177. §19.2.1.1, “bold (Bold Embedded Font)”, p. 2760, attribute id	53
178. §19.2.1.2, “bolditalic (Bold Italic Embedded Font)”, pp. 2760–2761, attribute id	53
179. §19.2.1.11, “ext (Extension)”, p. 2767	53
180. §19.2.1.13, “font (Embedded Font Name)”, pp. 2768–2770, attribute various	54
181. §19.2.1.14, “handoutMasterId (Handout Master ID)”, p. 2771, attribute id	55
182. §19.2.1.16, “italic (Italic Embedded Font)”, p. 2772, attribute id	55
183. §19.2.1.20, “notesMasterId (Notes Master ID)”, p. 2778, attribute id	55
184. §19.2.1.22, “notesSz (Notes Slide Size)”, p. 2779, attribute various	56
185. §19.2.1.29, “regular (Regular Embedded Font)”, p. 2787, attribute id	56
186. §19.2.1.31, “sld (Presentation Slide)”, p. 2789, attribute id	56
187. §19.2.1.33, “sldId (Slide ID)”, p. 2790, attribute id	57
188. §19.2.1.36, “sldMasterId (Slide Master ID)”, p. 2791, attribute id	57
189. §19.2.1.40, “SmartTags (SmartTags)”, p. 2795, attribute id	57

190. §19.2.2.3, “gridSpacing (Grid Spacing)”, p. 2797, attribute various	58
191. §19.2.2.9, “origin (View Origin)”, p. 2801, attribute various.....	58
192. §19.2.2.14, “sld (Presentation Slide)”, p. 2804, attribute id	59
193. §19.3.1.3, “bgRef (Background Style Reference)”, pp. 2809–2810, attribute idx	59
194. §19.3.1.4, “blipFill (Picture Fill)”, p. 2812, attribute various	59
195. §19.3.1.6, “clrMap (Color Scheme Map)”, p. 2814–2815, attribute various.....	60
196. §19.3.1.11, “cNvPicPr (Non-Visual Picture Drawing Properties)”, pp. 2817–2818, attribute preferRelativeResize	62
197. §19.3.1.12, “cNvPr (Non-Visual Drawing Properties)”, pp. 2819–2820, attribute various.....	62
198. §19.3.1.13, “cNvSpPr (Non-Visual Drawing Properties for a Shape)”, p. 2821, attribute txBBox.....	63
199. §19.3.1.14, “ContentPart (Content Part)”, pp. 2821–2824	63
200. §19.3.1.14, “ContentPart (Content Part)”, p. 2824, attribute id	64
201. §19.3.1.17, “custData (Customer Data)”, p. 2826, attribute id	64
202. §19.3.1.23, “grpSpPr (Group Shape Properties)”, p. 2831, attribute bwMode.....	64
203. §19.3.1.40, “sldLayoutId (Slide Layout ID)”, p. 2844, attribute id	65
204. §19.3.1.44, “spPr (Shape Properties)”, pp. 2847–2848, attribute bwMode	65
205. §19.3.1.47, “tags (Customer Data Tags)”, p. 2851, attribute id.....	65
206. §19.3.1.53, “xfrm (2D Transform for Graphic Frame)”, p. 2856, attribute various	66
207. §19.3.2.1, “control (Embedded Control)”, p. 2857, attribute id.....	66
208. §19.3.2.4, “oleObj (Global Element for Embedded objects and Controls)”, p. 2859, attribute id.....	67
209. §19.4.5, “pos (Comment Position)”, p. 2865, attribute various	67
210. §19.5.68, “snd (Sound)”, p. 2942, attribute various	68
211. §19.5.70, “sndTgt (Sound Target)”, p. 2943, attribute various.....	68
212. §19.7, “Simple Types”, p. 2974.....	69
213. §20.1.2.2.14, “ext (Extension)”, p. 3028	69
214. §20.1.2.2.23, “hlinkHover (Hyperlink for Hover)”, p. 3037, attribute id.....	69
215. §20.1.2.2.32, “snd (Hyperlink Sound)”, p. 3044, attribute embed	69
216. §20.1.3.2, “audioFile (Audio from File)”, pp. 3083–3084, attribute link.....	70
217. §20.1.3.4, “quickTimeFile (QuickTime from File)”, pp. 3085–3086, attribute link	70
218. §20.1.3.6, “videoFile (Video from File)”, p. 3088, attribute link.....	70
219. §20.1.3.7, “wavAudioFile (Audio from WAV File)”, p. 3089, attribute embed	71
220. §20.1.8.13, “blip (Blip)”, p. 3187, attribute embed.....	71
221. §20.1.10, “Simple Types”, p. 3262.....	71

222. §20.1.10.41, “ST_PercentageDecimal (Percentage as Decimal Number)”, p. 3298	72
223. §20.1.10.62, “ST_TextBulletSizePercent (Bullet Size Percentage)”, p. 3420	72
224. §20.1.10.87, “ST_TextBulletSize (Bullet Size Percentage)”, new subclause	72
225. §20.2.2.1, “blipFill (Picture Fill)”, pp. 3450–3451, attribute various	73
226. §20.2.2.2, “cNvPicPr (Non-Visual Picture Drawing Properties)”, p. 3452, attribute preferRelativeResize	73
227. §20.2.2.3, “cNvPr (Non-Visual Drawing Properties)”, pp. 3453–3454, attribute various	74
228. §20.2.2.6, “spPr (Shape Properties)”, p. 3457, attribute bwMode	75
229. §20.4.2.5, “docPr (Drawing Object Non-Visual Properties)”, pp. 3470–3472, attribute various	75
230. §20.4.2.7, “extent (Drawing Object Size)”, pp. 3476–3477, attribute various	76
231. §20.4.2.9, “lineTo (Wrapping Polygon Line End Position)”, p. 3481, attribute various	76
232. §20.4.2.13, “simplePos (Simple Positioning Coordinates)”, pp. 3485–3486, attribute various	77
233. §20.4.2.14, “start (Wrapping Polygon Start)”, pp. 3486–3487, attribute various	77
234. §20.4.3, “Simple Types”, p. 3500	78
235. §20.5, “DrawingML – SpreadsheetML Drawing”, pp. 3507–3508	78
236. §20.5.2.2, “blipFill (Picture Fill)”, p. 3512, attribute various	78
237. §20.5.2.7, “cNvPicPr (Non-Visual Picture Drawing Properties)”, p. 3515, attribute preferRelativeResize	79
238. §20.5.2.8, “cNvPr (Non-Visual Drawing Properties)”, pp. 3516–3517, attribute various	79
239. §20.5.2.9, “cNvSpPr (Connection Non-Visual Shape Properties)”, p. 3518, attribute txBBox	80
240. §20.5.2.12, “contentPart (Content Part)”, pp. 3519–3523	80
241. §20.5.2.12, “contentPart (Content Part)”, p. 3523, attribute id	81
242. §20.5.2.14, “ext (Shape Extent)”, pp. 3524–3525, attribute various	81
243. §20.5.2.18, “grpSpPr (Group Shape Properties)”, p. 3529, attribute bwMode	82
244. §20.5.2.26, “pos (Position)”, p. 3534, attribute various	82
245. §20.5.2.30, “spPr (Shape Properties)”, p. 3537, attribute bwMode	83
246. §20.5.2.36, “xfrm (2D Transform for Graphic Frames)”, pp. 3541–3542, attribute various	83
247. §20.5.3, “Simple Types”, p. 3542	83
248. §21.1.2.3.5, “hlinkClick (Click Hyperlink)”, p. 3610, attribute id	84
249. §21.1.2.3.6, “hlinkMouseOver (Mouse-Over Hyperlink)”, p. 3612, attribute id	84
250. §21.2.2.21, “bubbleScale (Bubble Scale)”, p. 3767	84
251. §21.2.2.26, “chart (Reference to Chart Part)”, p. 3770, attribute id	85
252. §21.2.2.30, “clrMapOvr (Color Map Override)”, pp. 3773–3775, attribute various	85
253. §21.2.2.41, “depthPercent (Depth Percent)”, p. 3780	87

254. §21.2.2.63, “externalData (External Data Relationship)”, p. 3790, attribute id	87
255. §21.2.2.74, “gapDepth (Gap Depth)”, p. 3795, attribute val.....	88
256. §21.2.2.75, “gapWidth (Gap Width)”, p. 3796, attribute val.....	88
257. §21.2.2.82, “holeSize (Hole Size)”, p. 3799, attribute val.....	88
258. §21.2.2.83, “hPercent (Height Percent)”, p. 3800.....	88
259. §21.2.2.91, “lblOffset (Label Offset)”, p. 3803, attribute val.....	88
260. §21.2.2.131, “overlap (Overlap)”, p. 3820, attribute val.....	89
261. §21.2.2.136, “perspective (Perspective)”, p. 3827, attribute val.....	89
262. §21.2.2.164, “secondPieSize (Second Pie Size)”, p. 3839, attribute val	89
263. §21.2.2.197, “spPr (Shape Properties)”, p. 3858, attribute bwMode	89
264. §21.2.2.206, “thickness (Thickness)”, pp. 3861–3862, attribute val.....	90
265. §21.2.2.221, “userShapes (Reference to Chart Drawing Part)”, p. 3868, attribute id	90
266. §21.2.3, “Simple Types”, p. 3875	90
267. §21.2.3.5, “ST_BubbleScale (Bubble Scale)”, pp. 3877–3878	90
268. §21.2.3.9, “ST_DepthPercent (Depth Percent)”, p. 3880	91
269. §21.2.3.16, “ST_GapAmount (Gap Amount)”, p. 3883.....	91
270. §21.2.3.18, “ST_HoleSize (Hole Size)”, p. 3884	91
271. §21.2.3.19, “ST_HPercent (Height Percent)”, p. 3885.....	92
272. §21.2.3.23, “ST_LblOffset (Label Offset)”, pp. 3886–3887	92
273. §21.2.3.31, “ST_Overlap (Overlap)”, p. 3891	92
274. §21.2.3.34, “ST_Perspective (Perspective)”, p. 3892	93
275. §21.2.3.41, “ST_SecondPieSize (Second Pie Size)”, p. 3896	93
276. §21.2.3.51, “ST_DepthPercentWithSymbol (Depth Percent with Symbol)”, new subclause	93
277. §21.2.3.52, “ST_HPercentWithSymbol (Height Percent with Symbol)”, new subclause	93
278. §21.2.3.53, “ST_GapAmountPercent (Gap Amount Percentage)”, new subclause.....	94
279. §21.2.3.54, “ST_PerspectivePercent (Perspective Percentage)”, new subclause	94
280. §21.2.3.55, “ST_SecondPieSizePercent (Second Pie Size Percentage)”, new subclause	94
281. §21.2.3.56, “ST_HoleSizePercent (Hole Size Percentage)”, new subclause	94
282. §21.2.3.57, “ST_LblOffsetPercent (Label Offset Percentage)”, new subclause.....	95
283. §21.2.3.58, “ST_OverlapPercent (Overlap Percentage)”, new subclause	95
284. §21.2.3.59, “ST_BubbleScalePercent (Bubble Scale Percentage)”, new subclause.....	95
285. §21.2.3.60, “ST_Thickness (Thickness Percentage)”, new subclause	95

286. §21.2.3.61, “ST_ThicknessPercent (Thickness Percentage)”, new subclause	96
287. §21.3.2.2, “blipFill (Picture Fill)”, pp. 3913–3914, attribute various.....	96
288. §21.3.2.6, “cNvPicPr (Non-Visual Picture Drawing Properties)”, p. 3916, attribute preferRelativeResize	96
289. §21.3.2.7, “cNvPr (Non-Visual Drawing Properties)”, pp. 3917–3918, attribute various.....	97
290. §21.3.2.8, “cNvSpPr (Non-Visual Shape Drawing Properties)”, p. 3919, attribute txBox.....	98
291. §21.3.2.10, “ext (Shape Extent)”, p. 3922, attribute various	98
292. §21.3.2.14, “grpSpPr (Group Shape Properties)”, p. 3926, attribute bwMode.....	98
293. §21.3.2.23, “spPr (Shape Properties)”, p. 3934, attribute bwMode.....	99
294. §21.3.2.28, “xfrm (Graphics Frame Transform)”, p. 3937, attribute various	99
295. §21.3.3, “Simple Types”, p. 3938.....	99
296. §21.4.2.14, “forEach (For Each)”, p. 3955	100
297. §21.4.2.19, “layoutNode (Layout Node)”, p. 3964.....	100
298. §21.4.2.22, “relIds (Explicit Relationships to Diagram Parts)”, p. 3968, attribute various.....	100
299. §21.4.2.27, “shape (Shape)”, p. 3973, attribute blip.....	101
300. §21.4.3.4, “prSet (Property Set)”, pp. 3983–3984 attributes various.....	102
301. §21.4.3.7, “spPr (Shape Properties)”, p. 3988, attribute bwMode.....	103
302. §21.4.4.3, “colorsDef (Color Transform Definitions)”, p. 3991.....	103
303. §21.4.5.6, “sp3d (3-D Shape Properties)”, pp. 4008–4009, attribute various.....	103
304. §21.4.5.7, “styleDef (Style Definition)”, p. 4010.....	104
305. §21.4.7, “Simple Types”, p. 4021.....	104
306. §21.4.7.66, “ST_PrSetCustVal (Property Set Customized Value)”, new subclause	104
307. §22.1.3, “Simple Types”, p. 4223.....	105
308. §22.2, “Extended Properties”, p. 4230	105
309. §22.3, “Custom Properties”, p. 4240	105
310. §22.4.3, “Simple Types”, p. 4256.....	105
311. §22.6.2.60, “sources (Sources)”, p. 4300	105
312. §22.6.3, “Simple Types”, p. 4310.....	106
313. §22.7.3, “Simple Types”, p. 4315.....	106
314. §22.8.2, “Simple Types”, p. 4316.....	106
315. §22.9.2, “Simple Types”, p. 4317	106
316. §A.1, “WordprocessingML”, p. 4345, lines 1–18.....	107
317. §A.1, “WordprocessingML”, p. 4347, lines 108–113	107

318. §A.1, “WordprocessingML”, p. 4385, lines 2143–2146	108
319. §A.1, “WordprocessingML”, p. 4392, lines 2500–2506	108
320. §A.2, “SpreadsheetML”, p. 4410, lines 1–13.....	109
321. §A.2, “SpreadsheetML”, pp. 4481–4482, lines 3792–3811	109
322. §A.2, “SpreadsheetML”, new type	109
323. §A.3, “PresentationML”, p. 4494, lines 1–13	110
324. §A.3, “PresentationML”, p. 4508, lines 768–773	110
325. §A.3, “PresentationML”, p. 4510, lines 849–857	111
326. §A.3, “PresentationML”, p. 4522, lines 1505–1508	111
327. §A.4.1, “DrawingML – Main”, p. 4525, lines 1–20	111
328. §A.4.1, “DrawingML – Main”, p. 4528, lines 184–189	112
329. §A.4.1, “DrawingML – Main”, p. 4529, lines 240–242.....	112
330. §A.4.1, “DrawingML – Main”, p. 4536, lines 597–602	112
331. §A.4.1, “DrawingML – Main”, p. 4541, lines 835–840	113
332. §A.4.1, “DrawingML – Main”, p. 4555, lines 1617–1619.....	113
333. §A.4.1, “DrawingML – Main”, p. 4577, lines 2742–2747.....	113
334. §A.4.1, “DrawingML – Main”, p. 4577, lines 2749–2751.....	113
335. §A.4.1, “DrawingML – Main”, p. 4577, lines 2752–2754.....	113
336. §A.4.1, “DrawingML – Main”, p. 4578, lines 2814–2819.....	114
337. §A.4.2, “DrawingML – Picture”, p. 4582, lines 1–6	114
338. §A.4.3, “DrawingML – Locked Canvas”, p. 4583, lines 1–10.....	114
339. §A.4.4, “DrawingML – WordprocessingML Drawing”, p. 4583, lines 1–10	115
340. §A.4.5, “DrawingML – SpreadsheetML Drawing”, p. 4587, lines 1–10	115
341. §A.5.1, “DrawingML – Charts”, p. 4590, lines 1–16	116
342. §A.5.1, “DrawingML – Charts”, p. 4594, lines 198–206	116
343. §A.5.1, “DrawingML – Charts”, p. 4594, lines 216–224	117
344. §A.5.1, “DrawingML – Charts”, p. 4594, lines 225–233	117
345. §A.5.1, “DrawingML – Charts”, p. 4595, lines 245–252	118
346. §A.5.1, “DrawingML – Charts”, p. 4595, lines 264–272	118
347. §A.5.1, “DrawingML – Charts”, p. 4595, lines 273–281	119
348. §A.5.1, “DrawingML – Charts”, p. 4595–4596, lines 282–290.....	119
349. §A.5.1, “DrawingML – Charts”, p. 4596, lines 309–317	120

350. §A.5.1, “DrawingML - Charts”, pp. 4596–4597, lines 336–344	120
351. §A.5.1, “DrawingML - Charts”, p. 4612, lines 1139–1147	120
352. §A.5.2, “DrawingML – Chart Drawings”, p. 4617, lines 1–7	121
353. §A.5.3, “DrawingML - Diagrams”, p. 4620, lines 1–13	121
354. §A.5.3, “DrawingML - Diagrams”, p. 4621, lines 64–90	122
355. §A.5.3, “DrawingML - Diagrams”, p. 4627, lines 369–400	122
356. §A.5.3, “DrawingML - Diagrams”, p. 4628, lines 427–430	123
357. §A.5.3, “DrawingML - Diagrams”, pp. 4628–4629, lines 455–463	123
358. §A.5.3, “DrawingML - Diagrams”, p. 4631, lines 578–605	124
359. §A.6.1, “Math”, p. 4641, lines 1–11	124
360. §A.6.2, “Extended Properties”, p. 4652, lines 1–7	125
361. §A.6.3, “Custom Properties”, p. 4653, lines 1–10	125
362. §A.6.4, “Variant Types”, p. 4654, lines 1–7	126
363. §A.6.5, “Custom XML Data Properties”, p. 4658, lines 1–7	126
364. §A.6.6, “Bibliography”, p. 4659, lines 1–7	126
365. §A.6.7, “Additional Characteristics”, p. 4661, lines 1–4	127
366. §A.6.8, “Office Document Relationships”, p. 4662, lines 1–5	127
367. §A.6.9, “Shared Simple Types”, p. 4662, lines 1–4	127
368. §A.6.9, “Shared Simple Types”, p. 4663, lines 41–43	127
369. §A.7, “Custom XML Schema References”, p. 4665, lines 1–4	128
370. §B.1, “WordprocessingML”, p. 4667, lines 1–15	128
371. §B.1, “WordprocessingML”, p. 4668, line 48	128
372. §B.1, “WordprocessingML”, p. 4692, lines 1338–1340	128
373. §B.1, “WordprocessingML”, p. 4696, lines 1538–1541	129
374. §B.2, “SpreadsheetML”, p. 4712, lines 1–12	129
375. §B.2, “SpreadsheetML”, p. 4788, lines 4031–4046	129
376. §B.2, “SpreadsheetML”, new type	129
377. §B.3, “PresentationML”, p. 4806, lines 1–10	130
378. §B.3, “PresentationML”, p. 4815, lines 470–472	130
379. §B.3, “PresentationML”, p. 4816, lines 522–527	130
380. §B.3, “PresentationML”, p. 4826, lines 1032–1034	130
381. §B.4.1, “DrawingML – Main”, p. 4831, lines 1–8	131

382. §B.4.1, "DrawingML - Main", p. 4833, lines 107–109.....	131
383. §B.4.1, "DrawingML – Main", p. 4834, line 134	131
384. §B.4.1, "DrawingML - Main", p. 4840, lines 446–448.....	131
385. §B.4.1, "DrawingML - Main", p. 4844, lines 673–675.....	131
386. §B.4.1, "DrawingML - Main", p. 4856, line 1307	131
387. §B.4.1, "DrawingML - Main", p. 4871, lines 2115–2116.....	131
388. §B.4.1, "DrawingML - Main", p. 4871, lines 2118–2119.....	132
389. §B.4.1, "DrawingML - Main", p. 4871, line 2120.....	132
390. §B.4.1, "DrawingML - Main", p. 4872, lines 2150–2158.....	132
391. §B.4.2, "DrawingML – Picture", p. 4875, lines 1–5.....	132
392. §B.4.3, "DrawingML – Locked Canvas", p. 4876, lines 1–8.....	132
393. §B.4.4, "DrawingML – WordprocessingML Drawing", p. 4876, lines 1–10	133
394. §B.4.5, "DrawingML – SpreadsheetML Drawing", p. 4878, lines 1–11	133
395. §B.5.1, "DrawingML – Charts", p. 4880, lines 1–12.....	134
396. §B.5.1, "DrawingML - Charts", p. 4882, lines 118–123.....	134
397. §B.5.1, "DrawingML - Charts", p. 4883, lines 130–135.....	134
398. §B.5.1, "DrawingML - Charts", p. 4883, lines 138–141.....	135
399. §B.5.1, "DrawingML - Charts", p. 4883, lines 150–154.....	135
400. §B.5.1, "DrawingML - Charts", p. 4884, lines 163–168.....	135
401. §B.5.1, "DrawingML - Charts", p. 4884, lines 169–174.....	136
402. §B.5.1, "DrawingML - Charts", p. 4884, lines 175–180.....	136
403. §B.5.1, "DrawingML - Charts", p. 4884, lines 192–197.....	136
404. §B.5.1, "DrawingML - Charts", pp. 4884, lines 209–214.....	136
405. §B.5.1, "DrawingML - Charts", p. 4894, lines 710–715.....	137
406. §B.5.2, "DrawingML – Chart Drawings", p. 4899, lines 1–5.....	137
407. §B.5.3, "DrawingML - Diagrams", p. 4900, lines 1–10.....	137
408. §B.5.3, "DrawingML - Diagrams", p. 4901, lines 44–58.....	138
409. §B.5.3, "DrawingML - Diagrams", p. 4906, lines 300–318	138
410. §B.5.3, "DrawingML - Diagrams", p. 4907, lines 373–374.....	138
411. §B.5.3, "DrawingML - Diagrams", p. 4908, lines 394–402	139
412. §B.5.3, "DrawingML - Diagrams", p. 4909, lines 475–490	139
413. §B.6.1, "Math", p. 4916, lines 1–8.....	139

414. §B.6.2, “Extended Properties”, p. 4921, lines 1–8	140
415. §B.6.3, “Custom Properties”, p. 4922, lines 1–10	140
416. §B.6.4, “Variant Types”, p. 4923, lines 1–8.....	140
417. §B.6.5, “Custom XML Data Properties”, p. 4927, lines 1–5	141
418. §B.6.6, “Bibliography”, p. 4927, lines 1–7.....	141
419. §B.6.7, “Additional Characteristics”, p. 4929, lines 1–5	141
420. §B.6.8, “Office Document Relationships”, p. 4930, lines 1–3.....	141
421. §B.6.9, “Shared Simple Types”, p. 4930, lines 1–3	142
422. §B.7, “Custom XML Schema References”, p. 4932, lines 1–3	142
423. §C, “Additional Syntax Constraints”, p. 4935.....	142
424. §D, “Namespace Prefix Mapping in Examples”, p. 4935–4936	142
425. §E.1, “Handling raw bitfields”, p. 4937	144
426. §E.2, “Handling hexadecimal-encoded bitfields”, p. 4938	144
427. §F, “WordprocessingML Custom XML Data Extraction”, p. 4940	144
428. §K.4.1, “Understanding the Type of a Document”, p. 5038	144
429. §K.4.2, “Understanding the Function of a Document”, p. 5039–5040.....	145
430. §K.4.3, “Understanding the Length of a Document”, pp. 5040–5041.....	145
431. §K.5.7, “Creating Image Map-Like Functionality”, p. 5061.....	146
432. §M.1.6.1, “Smart Tags”, p. 5088.....	147
433. §M.1.8.1, “Styles Part”, p. 5096	147
434. §M.1.9.4, “Font Table”, p. 5112	148
435. §M.1.10.1, “Numbering Part”, pp. 5113–5114	148
436. §M.1.11.1, “Header Part”, p. 5127	148
437. §M.1.11.2, “Footer Part”, p. 5127	148
438. §M.1.12.1, “Footnote Part”, p. 5133	148
439. §M.1.12.2, “Endnote Part”, p. 5133	149
440. §M.2.13.5, “Supporting Workbook Cache (Cell C2)”, p. 5280	149
441. §M.2.15.4.3, “The Table XML”, p. 5292	149
442. §M.2.15.4.4, “Single Cell XML”, p. 5292	149
443. §M.6.2.3, “Extended Properties”, p. 5531	149
444. §M.6.2.4, “Custom Properties”, p. 5531.....	150
445. §M.6.3, “Custom XML Data”, p. 5532.....	150

446. §M.7.2.1, “Embedded Packages”, p. 5539 150

447. §M.7.2.2, “Embedded Objects”, p. 5540 150

448. §M.7.2.5, “Embeddings in a PresentationML Document”, p. 5543 150

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 29500-1:2008/Amd 1:2010

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of the joint technical committee is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75% of the national bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

Amendment 1 to ISO/IEC 29500-1:2008 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 34, *Document description and processing languages*.

Notational conventions

The title of each change is the complete reference to the clause or subclause being modified. In all cases, the title begins with the clause or subclause number, the clause or subclause name, and the page number. In those cases containing changes to a particular row of a table, the value in that row's first column is appended to the title. As the lines in each XML schema subclause are numbered starting at 1 and going to the end of a schema, modifications to schemas also contain the numbers of the lines being modified.

A change can contain any one or more of the following kinds of edits:

1. Addition of text: New text is displayed in blue and is underlined, as demonstrated here.
2. Deletion of text: ~~Deleted text is displayed in red and is struck through, as demonstrated here.~~
3. Change of format of text: Text whose format (but not its content) has changed is displayed in green and is double-underlined, as demonstrated here.

Many changes involve edits to large paragraphs, tables, and/or XML fragments. In such cases, the changes contain only as much unchanged content as is necessary to establish the correct context of each change. Unchanged content that is not necessary to establish the correct context of a change is represented by an ellipsis (...).

Within a change, intent that cannot be represented visually as an edit is written as an instruction in italic and delimited by curly brackets; for example: *{In paragraph 2, item 4, and in paragraph 4, make the numbers in the text "17–23" hyperlinked forward references to Clauses 17 and 23.}*

Two documents modify the base standard ISO/IEC 29500-1:2008. They are ISO/IEC 29500-1:2008/Cor.1:2010 and this amendment, ISO/IEC 29500-1:2008/Amd.1:2010, which were published in that order. Both of these documents show changes relative to the base standard. Specifically, the amendment does not reflect changes made by the corrigendum.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 29500-1:2008/Amd 1:2010

Information technology — Document description and processing languages — Office Open XML File Formats —

Part 1: Fundamentals and Markup Language Reference

AMENDMENT 1

1. §2.6.1, “Base Application Description”, p. 5

Description URI: <http://descriptions.openxmlformats.org/description/base>
<http://purl.oclc.org/ooxml/descriptions/base>

2. §2.6.2, “Full Application Description”, p. 5

Description URI: <http://descriptions.openxmlformats.org/description/full>
<http://purl.oclc.org/ooxml/descriptions/full>

3. §11.2, “Package Structure”, p. 30

```
<Relationships xmlns="...">
  <Relationship Id="rId1"
    Type="http://schemas.openxmlformats.org/officeDocument/2006/
relationships/officeDocument"
http://purl.oclc.org/ooxml/officeDocument/relationships/officeDocument
    Target="document.xml"/>
</Relationships>
```

4. §11.3.1, “Alternative Format Import Part”, p. 32

Source Relationship:	http://schemas.openxmlformats.org/officeDocument/2006/relationships/aFChunk http://purl.oclc.org/ooxml/officeDocument/relationships/aFChunk
----------------------	--

5. §11.3.2, “Comments Part”, p. 34

Root Namespace:	http://schemas.openxmlformats.org/wordprocessingml/2006/main http://purl.oclc.org/ooxml/wordprocessingml/main
Source Relationship:	http://schemas.openxmlformats.org/officeDocument/2006/relationships/comments http://purl.oclc.org/ooxml/officeDocument/relationships/comments

6. §11.3.3, “Document Settings Part”, p. 36

Root Namespace:	http://schemas.openxmlformats.org/wordprocessingml/2006/main http://purl.oclc.org/ooxml/wordprocessingml/main
Source Relationship:	http://schemas.openxmlformats.org/officeDocument/2006/relationships/settings http://purl.oclc.org/ooxml/officeDocument/relationships/settings

7. §11.3.4, “Endnotes Part”, p. 37

Root Namespace:	http://schemas.openxmlformats.org/wordprocessingml/2006/main http://purl.oclc.org/ooxml/wordprocessingml/main
Source Relationship:	http://schemas.openxmlformats.org/officeDocument/2006/relationships/endnotes http://purl.oclc.org/ooxml/officeDocument/relationships/endnotes

8. §11.3.5, “Font Table Part”, p. 40

Root Namespace:	http://schemas.openxmlformats.org/wordprocessingml/2006/main http://purl.oclc.org/ooxml/wordprocessingml/main
Source Relationship:	http://schemas.openxmlformats.org/officeDocument/2006/relationships/fontTable http://purl.oclc.org/ooxml/officeDocument/relationships/fontTable

9. §11.3.6, “Footer Part”, p. 41

Root Namespace:	http://schemas.openxmlformats.org/wordprocessingml/2006/main http://purl.oclc.org/ooxml/wordprocessingml/main
Source Relationship:	http://schemas.openxmlformats.org/officeDocument/2006/relationships/footer http://purl.oclc.org/ooxml/officeDocument/relationships/footer

10. §11.3.7, “Footnotes Part”, p. 43

Root Namespace:	http://schemas.openxmlformats.org/wordprocessingml/2006/main http://purl.oclc.org/ooxml/wordprocessingml/main
Source Relationship:	http://schemas.openxmlformats.org/officeDocument/2006/relationships/footnotes http://purl.oclc.org/ooxml/officeDocument/relationships/footnotes

11. §11.3.8, “Glossary Document Part”, p. 46

Root Namespace:	http://schemas.openxmlformats.org/wordprocessingml/2006/main http://purl.oclc.org/ooxml/wordprocessingml/main
Source Relationship:	http://schemas.openxmlformats.org/officeDocument/2006/relationships/glossaryDocument http://purl.oclc.org/ooxml/officeDocument/relationships/glossaryDocument

12. §11.3.9, “Header Part”, p. 48

Root Namespace:	http://schemas.openxmlformats.org/wordprocessingml/2006/main http://purl.oclc.org/ooxml/wordprocessingml/main
Source Relationship:	http://schemas.openxmlformats.org/officeDocument/2006/relationships/header http://purl.oclc.org/ooxml/officeDocument/relationships/header

13. §11.3.10, “Main Document Part”, p. 51

Root Namespace:	http://schemas.openxmlformats.org/wordprocessingml/2006/main http://purl.oclc.org/ooxml/wordprocessingml/main
Source Relationship:	http://schemas.openxmlformats.org/officeDocument/2006/relationships/officeDocument http://purl.oclc.org/ooxml/officeDocument/relationships/officeDocument

14. §11.3.11, “Numbering Definitions Part”, p. 52

Root Namespace:	http://schemas.openxmlformats.org/wordprocessingml/2006/main http://purl.oclc.org/ooxml/wordprocessingml/main
Source Relationship:	http://schemas.openxmlformats.org/officeDocument/2006/relationships/numbering http://purl.oclc.org/ooxml/officeDocument/relationships/numbering

15. §11.3.12, “Style Definitions Part”, p. 55

Root Namespace:	http://schemas.openxmlformats.org/wordprocessingml/2006/main http://purl.oclc.org/ooxml/wordprocessingml/main
Source Relationship:	http://schemas.openxmlformats.org/officeDocument/2006/relationships/styles http://purl.oclc.org/ooxml/officeDocument/relationships/styles

16. §11.3.13, “Web Settings Part”, p. 57

Root Namespace:	http://schemas.openxmlformats.org/wordprocessingml/2006/main http://purl.oclc.org/ooxml/wordprocessingml/main
Source Relationship:	http://schemas.openxmlformats.org/officeDocument/2006/relationships/webSettings http://purl.oclc.org/ooxml/officeDocument/relationships/webSettings

17. §11.4, “Document Template”, p. 58

Source Relationship:	http://schemas.openxmlformats.org/officeDocument/2006/relationships/attachedTemplate http://purl.oclc.org/ooxml/officeDocument/relationships/attachedTemplate
----------------------	--

18. §11.5, “Framesets”, p. 58

Source Relationship:	http://schemas.openxmlformats.org/officeDocument/2006/relationships/frame http://purl.oclc.org/ooxml/officeDocument/relationships/frame
----------------------	--

19. §11.6, “Master Documents and Subdocuments”, p. 59

Source	http://schemas.openxmlformats.org/officeDocument/2006/relationships/subDocument
Relationship:	http://purl.oclc.org/ooxml/officeDocument/relationships/subDocument

20. §11.7, “Mail Merge Data Source”, p. 61

Source	http://schemas.openxmlformats.org/officeDocument/2006/relationships/mailMergeSource
Relationship:	http://purl.oclc.org/ooxml/officeDocument/relationships/mailMergeSource

21. §11.8, “Mail Merge Header Data Source”, p. 61

Source	http://schemas.openxmlformats.org/officeDocument/2006/relationships/mailMergeHeaderSource
Relationship:	http://purl.oclc.org/ooxml/officeDocument/relationships/mailMergeHeaderSource

22. §11.9, “XSL Transformation”, p. 62

Source	http://schemas.openxmlformats.org/officeDocument/2006/relationships/transform
Relationship:	http://purl.oclc.org/ooxml/officeDocument/relationships/transform

23. §12.2, “Package Structure”, pp. 65–66

```

<Relationships xmlns="...">
  <Relationship Id="rId1"
    Type="http://schemas.openxmlformats.org/officeDocument/2006/
—relationships/officeDocument
http://purl.oclc.org/ooxml/officeDocument/relationships/officeDocument"
    Target="workbook.xml" />
</Relationships>

<Relationships xmlns="...">
  <Relationship Id="rId1"
    Type="http://schemas.openxmlformats.org/officeDocument/2006/
—relationships/worksheet
http://purl.oclc.org/ooxml/officeDocument/relationships/worksheet"
    Target="sheet1.xml" />
</Relationships>

```

24. §12.3, “Part Summary”, pp. 67–68

Part	Relationship Target of	Root Element	Ref.
Custom XML Mappings	Workbook	~~mapInfo~~ MapInfo	§12.3.6
Dialogsheet	Workbook	~~dialogSheet~~ dialogsheetsheet	§12.3.7

Part	Relationship Target of	Root Element	Ref.
External Workbook References	Workbook	~~externalReference~~ externalLink	§12.3.9
Single Cell Table Definitions	Dialogsheet, Worksheet	~~singleCells~~ singleXmlCells	§12.3.19

25. §12.3.1, “Calculation Chain Part”, p. 68

Root Namespace:	~~http://schemas.openxmlformats.org/spreadsheetml/2006/main~~ http://purl.oclc.org/ooxml/spreadsheetml/main
Source Relationship:	~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/calcChain~~ http://purl.oclc.org/ooxml/officeDocument/relationships/calcChain

26. §12.3.2, “Chartsheet Part”, p. 69

Root Namespace:	~~http://schemas.openxmlformats.org/spreadsheetml/2006/main~~ http://purl.oclc.org/ooxml/spreadsheetml/main
Source Relationship:	~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/chartsheet~~ http://purl.oclc.org/ooxml/officeDocument/relationships/chartsheet

27. §12.3.3, “Comments Part”, p. 70

Root Namespace:	~~http://schemas.openxmlformats.org/spreadsheetml/2006/main~~ http://purl.oclc.org/ooxml/spreadsheetml/main
Source Relationship:	~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/comments~~ http://purl.oclc.org/ooxml/officeDocument/relationships/comments

28. §12.3.4, “Connections Part”, p. 71

Root Namespace:	~~http://schemas.openxmlformats.org/spreadsheetml/2006/main~~ http://purl.oclc.org/ooxml/spreadsheetml/main
Source Relationship:	~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/connections~~ http://purl.oclc.org/ooxml/officeDocument/relationships/connections

29. §12.3.5, “Custom Property Part”, p. 73

Root Namespace:	Not applicable
Source Relationship:	~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/customProperty~~ http://purl.oclc.org/ooxml/officeDocument/relationships/customProperty

30. §12.3.6, “Custom XML Mappings Part”, p. 74

Root Namespace:	http://schemas.openxmlformats.org/spreadsheetml/2006/main http://purl.oclc.org/ooxml/spreadsheetml/main
Source Relationship:	http://schemas.openxmlformats.org/officeDocument/2006/relationships/xmlMaps http://purl.oclc.org/ooxml/officeDocument/relationships/xmlMaps

31. §12.3.6, “Custom XML Mappings Part”, p. 74

The root element for a part of this content type shall be [mapInfo](#) [MapInfo](#).

32. §12.3.7, “Dialogsheet Part”, p. 75

Root Namespace:	http://schemas.openxmlformats.org/spreadsheetml/2006/main http://purl.oclc.org/ooxml/spreadsheetml/main
Source Relationship:	http://schemas.openxmlformats.org/officeDocument/2006/relationships/dialogsheet http://purl.oclc.org/ooxml/officeDocument/relationships/dialogsheet

33. §12.3.8, “Drawings Part”, p. 77

Root Namespace:	http://schemas.openxmlformats.org/drawingml/2006/spreadsheetDrawing http://purl.oclc.org/ooxml/drawingml/spreadsheetDrawing
Source Relationship:	http://schemas.openxmlformats.org/officeDocument/2006/relationships/drawing http://purl.oclc.org/ooxml/officeDocument/relationships/drawing

34. §12.3.9, “External Workbook References Part”, p. 78

Root Namespace:	http://schemas.openxmlformats.org/spreadsheetml/2006/main http://purl.oclc.org/ooxml/spreadsheetml/main
Source Relationship:	http://schemas.openxmlformats.org/officeDocument/2006/relationships/externalLink http://purl.oclc.org/ooxml/officeDocument/relationships/externalLink

35. §12.3.10, “Metadata part”, pp. 80–81

Root Namespace:	http://schemas.openxmlformats.org/spreadsheetml/2006/main http://purl.oclc.org/ooxml/spreadsheetml/main
Source Relationship:	http://schemas.openxmlformats.org/officeDocument/2006/relationships/sheetMetadata http://purl.oclc.org/ooxml/officeDocument/relationships/sheetMetadata

36. §12.3.11, “Pivot Table Part”, p. 83

Root Namespace:	http://schemas.openxmlformats.org/spreadsheetml/2006/main http://purl.oclc.org/ooxml/spreadsheetml/main
-----------------	--

Source Relationship:	http://schemas.openxmlformats.org/officeDocument/2006/relationships/pivotTable http://purl.oclc.org/ooxml/officeDocument/relationships/pivotTable
----------------------	--

37. §12.3.12, “Pivot Table Cache Definition Part”, p. 84

Root Namespace:	http://schemas.openxmlformats.org/spreadsheetml/2006/main http://purl.oclc.org/ooxml/spreadsheetml/main
Source Relationship:	http://schemas.openxmlformats.org/officeDocument/2006/relationships/pivotCacheDefinition http://purl.oclc.org/ooxml/officeDocument/relationships/pivotCacheDefinition

38. §12.3.13, “Pivot Table Cache Records Part”, p. 86

Root Namespace:	http://schemas.openxmlformats.org/spreadsheetml/2006/main http://purl.oclc.org/ooxml/spreadsheetml/main
Source Relationship:	http://schemas.openxmlformats.org/officeDocument/2006/relationships/pivotCacheRecords http://purl.oclc.org/ooxml/officeDocument/relationships/pivotCacheRecords

39. §12.3.14, “Query Table Part”, p. 87

Root Namespace:	http://schemas.openxmlformats.org/spreadsheetml/2006/main http://purl.oclc.org/ooxml/spreadsheetml/main
Source Relationship:	http://schemas.openxmlformats.org/officeDocument/2006/relationships/queryTable http://purl.oclc.org/ooxml/officeDocument/relationships/queryTable

40. §12.3.15, “Shared Strings Table Part”, p. 88

Root Namespace:	http://schemas.openxmlformats.org/spreadsheetml/2006/main http://purl.oclc.org/ooxml/spreadsheetml/main
Source Relationship:	http://schemas.openxmlformats.org/officeDocument/2006/relationships/sharedStrings http://purl.oclc.org/ooxml/officeDocument/relationships/sharedStrings

41. §12.3.16, “Shared Workbook Revision Headers Part”, p. 89

Root Namespace:	http://schemas.openxmlformats.org/spreadsheetml/2006/main http://purl.oclc.org/ooxml/spreadsheetml/main
Source Relationship:	http://schemas.openxmlformats.org/officeDocument/2006/relationships/revisionHeaders http://purl.oclc.org/ooxml/officeDocument/relationships/revisionHeaders

42. §12.3.17, “Shared Workbook Revision Log Part”, p. 90

Root Namespace:	http://schemas.openxmlformats.org/spreadsheetml/2006/main http://purl.oclc.org/ooxml/spreadsheetml/main
Source Relationship:	http://schemas.openxmlformats.org/officeDocument/2006/relationships/revisionLog http://purl.oclc.org/ooxml/officeDocument/relationships/revisionLog

43. §12.3.18, “Shared Workbook User Data Part”, pp. 91–92

Root Namespace:	http://schemas.openxmlformats.org/spreadsheetml/2006/main http://purl.oclc.org/ooxml/spreadsheetml/main
Source Relationship:	http://schemas.openxmlformats.org/officeDocument/2006/relationships/usernames http://purl.oclc.org/ooxml/officeDocument/relationships/usernames

44. §12.3.19, “Single Cell Table Definition Part”, p. 92–93

Root Namespace:	http://schemas.openxmlformats.org/spreadsheetml/2006/main http://purl.oclc.org/ooxml/spreadsheetml/main
Source Relationship:	http://schemas.openxmlformats.org/officeDocument/2006/relationships/tableSingleCells http://purl.oclc.org/ooxml/officeDocument/relationships/tableSingleCells

The root element for a part of this content type shall be [singleCells](#)[singleXmlCells](#).

<[singleCells](#)[singleXmlCells](#) ...>

...

</[singleCells](#)[singleXmlCells](#)>

45. §12.3.20, “Styles Part”, p. 94

Root Namespace:	http://schemas.openxmlformats.org/spreadsheetml/2006/main http://purl.oclc.org/ooxml/spreadsheetml/main
Source Relationship:	http://schemas.openxmlformats.org/officeDocument/2006/relationships/styles http://purl.oclc.org/ooxml/officeDocument/relationships/styles

46. §12.3.21, “Table Definition Part”, p. 95

Root Namespace:	http://schemas.openxmlformats.org/spreadsheetml/2006/main http://purl.oclc.org/ooxml/spreadsheetml/main
Source Relationship:	http://schemas.openxmlformats.org/officeDocument/2006/relationships/table http://purl.oclc.org/ooxml/officeDocument/relationships/table

47. §12.3.22, “Volatile Dependencies Part”, p. 96

Root Namespace:	http://schemas.openxmlformats.org/spreadsheetml/2006/main http://purl.oclc.org/ooxml/spreadsheetml/main
Source Relationship:	http://schemas.openxmlformats.org/officeDocument/2006/relationships/volatileDependencies http://purl.oclc.org/ooxml/officeDocument/relationships/volatileDependencies

48. §12.3.23, “Workbook Part”, p. 97

Root Namespace:	http://schemas.openxmlformats.org/spreadsheetml/2006/main http://purl.oclc.org/ooxml/spreadsheetml/main
Source Relationship:	http://schemas.openxmlformats.org/officeDocument/2006/relationships/officeDocument http://purl.oclc.org/ooxml/officeDocument/relationships/officeDocument

49. §12.3.24, “Worksheet Part”, p. 99

Root Namespace:	http://schemas.openxmlformats.org/spreadsheetml/2006/main http://purl.oclc.org/ooxml/spreadsheetml/main
Source Relationship:	http://schemas.openxmlformats.org/officeDocument/2006/relationships/worksheet http://purl.oclc.org/ooxml/officeDocument/relationships/worksheet

50. §12.4, “External Workbooks”, p. 101

Source Relationship:	http://schemas.openxmlformats.org/officeDocument/2006/relationships/externalLinkPath http://purl.oclc.org/ooxml/officeDocument/relationships/externalLinkPath
----------------------	--

51. §13.2, “Package Structure”, p. 104

```

<Relationships xmlns="...">
  <Relationship Id="rId1"
    Type="http://schemas.openxmlformats.org/officeDocument/2006/
relationships/officeDocument"
    Target="presentation.xml"/>
</Relationships>

```

52. §13.3.1, “Comment Authors Part”, p. 107

Root Namespace:	http://schemas.openxmlformats.org/presentationml/2006/main http://purl.oclc.org/ooxml/presentationml/main
Source Relationship:	http://schemas.openxmlformats.org/officeDocument/2006/relationships/commentAuthors http://purl.oclc.org/ooxml/officeDocument/relationships/commentAuthors

53. §13.3.2, “Comments Part”, p. 108

Root Namespace:	http://schemas.openxmlformats.org/presentationml/2006/main http://purl.oclc.org/ooxml/presentationml/main
Source Relationship:	http://schemas.openxmlformats.org/officeDocument/2006/relationships/comments http://purl.oclc.org/ooxml/officeDocument/relationships/comments

54. §13.3.3, “Handout Master Part”, p. 109

Root Namespace:	http://schemas.openxmlformats.org/presentationml/2006/main http://purl.oclc.org/ooxml/presentationml/main
Source Relationship:	http://schemas.openxmlformats.org/officeDocument/2006/relationships/handoutMaster http://purl.oclc.org/ooxml/officeDocument/relationships/handoutMaster

55. §13.3.4, “Notes Master Part”, p. 111

Root Namespace:	http://schemas.openxmlformats.org/presentationml/2006/main http://purl.oclc.org/ooxml/presentationml/main
Source Relationship:	http://schemas.openxmlformats.org/officeDocument/2006/relationships/notesMaster http://purl.oclc.org/ooxml/officeDocument/relationships/notesMaster

56. §13.3.5, “Notes Slide Part”, p. 112

Root Namespace:	http://schemas.openxmlformats.org/presentationml/2006/main http://purl.oclc.org/ooxml/presentationml/main
Source Relationship:	http://schemas.openxmlformats.org/officeDocument/2006/relationships/notesSlide http://purl.oclc.org/ooxml/officeDocument/relationships/notesSlide

57. §13.3.6, “Presentation Part”, pp. 113–114

Root Namespace:	http://schemas.openxmlformats.org/presentationml/2006/main http://purl.oclc.org/ooxml/presentationml/main
Source Relationship:	http://schemas.openxmlformats.org/officeDocument/2006/relationships/officeDocument http://purl.oclc.org/ooxml/officeDocument/relationships/officeDocument

58. §13.3.7, “Presentation Properties Part”, p. 115

Root Namespace:	http://schemas.openxmlformats.org/presentationml/2006/main http://purl.oclc.org/ooxml/presentationml/main
Source Relationship:	http://schemas.openxmlformats.org/officeDocument/2006/relationships/presProps http://purl.oclc.org/ooxml/officeDocument/relationships/presProps

59. §13.3.8, “Slide Part”, p. 116

Root Namespace:	http://schemas.openxmlformats.org/presentationml/2006/main http://purl.oclc.org/ooxml/presentationml/main
Source Relationship:	http://schemas.openxmlformats.org/officeDocument/2006/relationships/slide http://purl.oclc.org/ooxml/officeDocument/relationships/slide

60. §13.3.9, “Slide Layout Part”, p. 118

Root Namespace:	http://schemas.openxmlformats.org/presentationml/2006/main http://purl.oclc.org/ooxml/presentationml/main
Source Relationship:	http://schemas.openxmlformats.org/officeDocument/2006/relationships/slideLayout http://purl.oclc.org/ooxml/officeDocument/relationships/slideLayout

61. §13.3.10, “Slide Master Part”, p. 120

Root Namespace:	http://schemas.openxmlformats.org/presentationml/2006/main http://purl.oclc.org/ooxml/presentationml/main
Source Relationship:	http://schemas.openxmlformats.org/officeDocument/2006/relationships/slideMaster http://purl.oclc.org/ooxml/officeDocument/relationships/slideMaster

62. §13.3.11, “Slide Synchronization Data Part”, p. 121

Root Namespace:	http://schemas.openxmlformats.org/presentationml/2006/main http://purl.oclc.org/ooxml/presentationml/main
Source Relationship:	http://schemas.openxmlformats.org/officeDocument/2006/relationships/slideUpdateInfo http://purl.oclc.org/ooxml/officeDocument/relationships/slideUpdateInfo

63. §13.3.12, “User Defined Tags Part”, p. 122

Root Namespace:	http://schemas.openxmlformats.org/presentationml/2006/main http://purl.oclc.org/ooxml/presentationml/main
Source Relationship:	http://schemas.openxmlformats.org/officeDocument/2006/relationships/tags http://purl.oclc.org/ooxml/officeDocument/relationships/tags

64. §13.3.31, “View Properties Part”, p. 123

Root Namespace:	http://schemas.openxmlformats.org/presentationml/2006/main http://purl.oclc.org/ooxml/presentationml/main
Source Relationship:	http://schemas.openxmlformats.org/officeDocument/2006/relationships/viewProps http://purl.oclc.org/ooxml/officeDocument/relationships/viewProps

65. §13.4, “HTML Publish Location”, p. 124

Source Relationship:	http://schemas.openxmlformats.org/officeDocument/2006/relationships/htmlPubSaveAs http://purl.oclc.org/ooxml/officeDocument/relationships/htmlPubSaveAs
----------------------	--

66. §13.5, “Slide Synchronization Server Location”, p. 125

Source Relationship:	http://schemas.openxmlformats.org/officeDocument/2006/relationships/slideUpdateUrl http://purl.oclc.org/ooxml/officeDocument/relationships/slideUpdateUrl
----------------------	--

67. §14.2.1, “Chart Part”, p. 128

Root Namespace:	http://schemas.openxmlformats.org/drawingml/2006/chart http://purl.oclc.org/ooxml/drawingml/chart
Source Relationship:	http://schemas.openxmlformats.org/officeDocument/2006/relationships/chart http://purl.oclc.org/ooxml/officeDocument/relationships/chart

68. §14.2.2, “Chart Drawing Part”, p. 130

Root Namespace:	http://schemas.openxmlformats.org/drawingml/2006/chart http://purl.oclc.org/ooxml/drawingml/chart
Source Relationship:	http://schemas.openxmlformats.org/officeDocument/2006/relationships/chartUserShapes http://purl.oclc.org/ooxml/officeDocument/relationships/chartUserShapes

69. §14.2.3, “Diagram Colors Part”, p. 131

Root Namespace:	http://schemas.openxmlformats.org/drawingml/2006/diagram http://purl.oclc.org/ooxml/drawingml/diagram
Source Relationship:	http://schemas.openxmlformats.org/officeDocument/2006/relationships/diagramColors http://purl.oclc.org/ooxml/officeDocument/relationships/diagramColors

70. §14.2.4, “Diagram Data Part”, p. 132

Root Namespace:	http://schemas.openxmlformats.org/drawingml/2006/diagram http://purl.oclc.org/ooxml/drawingml/diagram
Source Relationship:	http://schemas.openxmlformats.org/officeDocument/2006/relationships/diagramData http://purl.oclc.org/ooxml/officeDocument/relationships/diagramData

71. §14.2.5, “Diagram Layout Definition Part”, pp. 133–134

Root Namespace:	http://schemas.openxmlformats.org/drawingml/2006/diagram http://purl.oclc.org/ooxml/drawingml/diagram
Source Relationship:	http://schemas.openxmlformats.org/officeDocument/2006/relationships/diagramLayout http://purl.oclc.org/ooxml/officeDocument/relationships/diagramLayout

72. §14.2.6, “Diagram Style Part”, p. 135

Root Namespace:	http://schemas.openxmlformats.org/drawingml/2006/diagram http://purl.oclc.org/ooxml/drawingml/diagram
Source Relationship:	http://schemas.openxmlformats.org/officeDocument/2006/relationships/diagramQuickStyle http://purl.oclc.org/ooxml/officeDocument/relationships/diagramQuickStyle

73. §14.2.7, “Theme Part”, p. 136

Root Namespace:	http://schemas.openxmlformats.org/drawingml/2006/main http://purl.oclc.org/ooxml/drawingml/main
Source Relationship:	http://schemas.openxmlformats.org/officeDocument/2006/relationships/theme http://purl.oclc.org/ooxml/officeDocument/relationships/theme

74. §14.2.8, “Theme Override Part”, p. 138

Root Namespace:	http://schemas.openxmlformats.org/drawingml/2006/main http://purl.oclc.org/ooxml/drawingml/main
Source Relationship:	http://schemas.openxmlformats.org/officeDocument/2006/relationships/themeOverride http://purl.oclc.org/ooxml/officeDocument/relationships/themeOverride

75. §14.2.9, “Table Styles Part”, p. 139

Root Namespace:	http://schemas.openxmlformats.org/drawingml/2006/main http://purl.oclc.org/ooxml/drawingml/main
Source Relationship:	http://schemas.openxmlformats.org/officeDocument/2006/relationships/tableStyles http://purl.oclc.org/ooxml/officeDocument/relationships/tableStyles

76. §15.2.2, “Audio Part”, p. 144

Source Relationship:	http://schemas.openxmlformats.org/officeDocument/2006/relationships/audio http://purl.oclc.org/ooxml/officeDocument/relationships/audio
----------------------	--

77. §15.2.3, “Bibliography Part”, pp. 144–145

Root Namespace:	http://schemas.openxmlformats.org/officeDocument/2006/bibliography http://purl.oclc.org/ooxml/officeDocument/bibliography
Source Relationship:	http://schemas.openxmlformats.org/officeDocument/2006/relationships/customXml http://purl.oclc.org/ooxml/officeDocument/relationships/customXml

78. §15.2.4, “Content Part”, p. 146

Source Relationship:	http://schemas.openxmlformats.org/officeDocument/2006/relationships/customXml http://purl.oclc.org/ooxml/officeDocument/relationships/customXml
----------------------	--

79. §15.2.5, “Custom XML Data Storage Part”, p. 147

Source Relationship:	http://schemas.openxmlformats.org/officeDocument/2006/relationships/customXml http://purl.oclc.org/ooxml/officeDocument/relationships/customXml
----------------------	--

80. §15.2.6, “Custom XML Data Storage Properties Part”, p. 147

Root Namespace:	http://schemas.openxmlformats.org/officeDocument/2006/customXmlDataProps http://purl.oclc.org/ooxml/officeDocument/customXmlDataProps
Source Relationship:	http://schemas.openxmlformats.org/officeDocument/2006/relationships/customXmlProps http://purl.oclc.org/ooxml/officeDocument/relationships/customXmlProps

81. §15.2.9, “Embedded Control Persistence Part”, p. 150

Source Relationship:	http://schemas.openxmlformats.org/officeDocument/2006/relationships/control http://purl.oclc.org/ooxml/officeDocument/relationships/control
----------------------	--

82. §15.2.9, “Embedded Control Persistence Part”, p. 151

The relationship type for rId5 is: <http://schemas.openxmlformats.org/officeDocument/2006/relationships/control>
<http://purl.oclc.org/ooxml/officeDocument/relationships/control>

...

The relationship type for rId5 is: <http://schemas.openxmlformats.org/officeDocument/2006/relationships/control>
<http://purl.oclc.org/ooxml/officeDocument/relationships/control>

83. §15.2.10, “Embedded Object Part”, p. 152

Source Relationship:	http://schemas.openxmlformats.org/officeDocument/2006/relationships/oleObject http://purl.oclc.org/ooxml/officeDocument/relationships/oleObject
----------------------	--

84. §15.2.11, “Embedded Package Part”, p. 154

Source Relationship:	http://schemas.openxmlformats.org/officeDocument/2006/relationships/package http://purl.oclc.org/ooxml/officeDocument/relationships/package
----------------------	--

85. §15.2.12.2, “Custom File Properties Part”, p. 156

Root Namespace:	http://schemas.openxmlformats.org/officeDocument/2006/custom-properties http://purl.oclc.org/ooxml/officeDocument/customProperties
Source Relationship:	http://schemas.openxmlformats.org/officeDocument/2006/relationships/custom-properties http://purl.oclc.org/ooxml/officeDocument/relationships/customProperties

86. §15.2.12.3, “Extended File Properties Part”, p. 158

Root Namespace:	http://schemas.openxmlformats.org/officeDocument/2006/extended-properties http://purl.oclc.org/ooxml/officeDocument/extendedProperties
-----------------	--

Source Relationship:	http://schemas.openxmlformats.org/officeDocument/2006/relationships/extended-properties http://purl.oclc.org/ooxml/officeDocument/relationships/extendedProperties
----------------------	--

87. §15.2.13, “Font Part”, p. 160

Source Relationship:	http://schemas.openxmlformats.org/officeDocument/2006/relationships/font http://purl.oclc.org/ooxml/officeDocument/relationships/font
----------------------	--

88. §15.2.14, “Image Part”, p. 160

Source Relationship:	http://schemas.openxmlformats.org/officeDocument/2006/relationships/image http://purl.oclc.org/ooxml/officeDocument/relationships/image
----------------------	--

89. §15.2.15, “Printer Settings Part”, p. 161

Source Relationship:	http://schemas.openxmlformats.org/officeDocument/2006/relationships/printerSettings http://purl.oclc.org/ooxml/officeDocument/relationships/printerSettings
----------------------	--

90. §15.2.16, “Thumbnail Part”, p. 163

Source Relationship:	http://schemas.openxmlformats.org/package/2006/relationships/metadata/thumbnail http://purl.oclc.org/ooxml/officeDocument/relationships/metadata/thumbnail
----------------------	--

91. §15.2.17, “Video Part”, p. 164

Source Relationship:	http://schemas.openxmlformats.org/officeDocument/2006/relationships/video http://purl.oclc.org/ooxml/officeDocument/relationships/video
----------------------	--

92. §15.3, “Hyperlinks Part”, p. 164

Source Relationship:	http://schemas.openxmlformats.org/officeDocument/2006/relationships/hyperlink http://purl.oclc.org/ooxml/officeDocument/relationships/hyperlink
----------------------	--

93. §16.2, “SpreadsheetML Summary”, p. 167

Part	Root Element	Ref.
Custom XML Mappings	~~mapInfo~~ MapInfo	§18.16.3
Dialogsheet	~~dialogSheet~~ dialogsheetsheet	§18.3.1.34
Single Cell Table Definitions	~~singleCells~~ singleXmlCells	§18.5.2.2

94. §17.3.2.43, “w (Expanded/Compressed Text)”, pp. 342–343

[Example: ...

```
<w:rPr>
  <w:w w:val="200%" />
</w:rPr>
```

This run explicitly declares that the w value is 200%, so the contents of this run appear at 200% of their normal character width by stretching the width of each character. *end example]*

...

Attributes	Description
val (Text Expansion/Compression Value)	... [Example: ... <w:rPr> <w:w w:val="50%" /> </w:rPr> This run explicitly declares that the w value is 50%, so the contents of this run appear at 50% of their normal character width by compressing the width of each character. <i>end example]</i> ...

95. §17.3.3.2, “contentPart (ContentPart)”, p. 346

The relationship type of the explicit relationship specified by this element shall be <http://schemas.openxmlformats.org/officeDocument/2006/customXml> <http://purl.oclc.org/ooxml/officeDocument/relationships/customXml> and have a TargetMode attribute value of Internal. If an application cannot process content of the content type specified by the targeted part, then it should continue to process the file. If possible, it should also provide some indication that unknown content was not imported.

96. §17.3.3.2, “contentPart (ContentPart)”, p. 348

```
<Relationships ... >
...
  <Relationship Id="rId8" TargetMode="Internal"
Type="http://schemas.openxmlformats.org/officeDocument/2006/relationships/customXml"
http://purl.oclc.org/ooxml/officeDocument/relationships/customXml"
Target="math1.xml" />
...
</Relationships>
```

97. §17.3.3.2, “contentPart (ContentPart)”, p. 348, attribute id

Attributes	Description
id (Relationship to Part) Namespace: ~~...~~ /officeDocument/2006/relationships ~~ps~~ http://purl.oclc.org/ooxml/officeDocument/relationships	Specifies the relationship ID to a specified part. The specified relationship shall match the relationship type required by the parent element: ~~http://schemas.openxmlformats.org/officeDocument/2006/customXml~~http://purl.oclc.org/ooxml/officeDocument/customXml for the contentPart element ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/footer~~ http://purl.oclc.org/ooxml/officeDocument/relationships/footer for the footerReference element ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/header~~ http://purl.oclc.org/ooxml/officeDocument/relationships/header for the headerReference element ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/font~~ http://purl.oclc.org/ooxml/officeDocument/relationships/font for the embedBold, embedBoldItalic, embedItalic, or embedRegular elements ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/printerSettings~~ http://purl.oclc.org/ooxml/officeDocument/relationships/printerSettings for the printerSettings element ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/hyperlink~~ http://purl.oclc.org/ooxml/officeDocument/relationships/hyperlink for the longDesc or hyperlink element ...

98. §17.3.3.3, “control (Embedded Control)”, p. 349, attribute id

Attributes	Description
id (Embedded Control Properties Relationship Reference) Namespace: ~~...~~ /officeDocument/2006/relationships ~~ps~~ http://purl.oclc.org/ooxml/officeDocument/relationships	... The relationship explicitly targeted by this attribute shall be of type http://schemas.openxmlformats.org/officeDocument/2006/relationships/control http://purl.oclc.org/ooxml/officeDocument/relationships/control or the document shall be considered non-conformant. ...

99. §17.3.3.17, “movie (Embedded Video)”, p. 361

If the relationship type of the relationship specified by this element is not <http://schemas.openxmlformats.org/officeDocument/2006/movie> <http://purl.oclc.org/ooxml/officeDocument/movie>, or is not present, then the document shall be considered non-conformant. If an application cannot process external content of the content type specified by the targeted part, then it can be ignored.

...

```
<Relationships ... >
...
<Relationship Id="rIdMovie" TargetMode="Internal"
Type="http://schemas.openxmlformats.org/officeDocument/2006/relationships/movie
http://purl.oclc.org/ooxml/officeDocument/movie" Target="movie.mov" />
...
</Relationships>
```

100. §17.3.3.17, “movie (Embedded Video)”, p. 362, attribute id

Attributes	Description
id (Relationship to Part)	Specifies the relationship ID to a specified part.
Namespace: .../officeDocument/2006/relationships	The specified relationship shall match the relationship type required by the parent element:
http://purl.oclc.org/ooxml/officeDocument/relationships	• http://schemas.openxmlformats.org/officeDocument/2006/customXml http://purl.oclc.org/ooxml/officeDocument/customXml for the contentPart element • http://schemas.openxmlformats.org/officeDocument/2006/relationships/footer http://purl.oclc.org/ooxml/officeDocument/relationships/footer for the footerReference element • http://schemas.openxmlformats.org/officeDocument/2006/relationships/header http://purl.oclc.org/ooxml/officeDocument/relationships/header for the headerReference element • http://schemas.openxmlformats.org/officeDocument/2006/relationships/font http://purl.oclc.org/ooxml/officeDocument/relationships/font for the embedBold, embedBoldItalic, embedItalic, or embedRegular elements • http://schemas.openxmlformats.org/officeDocument/2006/relationships/printerSettings http://purl.oclc.org/ooxml/officeDocument/relationships/printerSettings for the printerSettings element • http://schemas.openxmlformats.org/officeDocument/2006/relationships/hyperlink http://purl.oclc.org/ooxml/officeDocument/relationships/hyperlink for the longDesc or hyperlink element
	...

101. §17.3.3.20, “objectEmbed (Embedded Object Properties)”, p. 366, attribute id

Attributes	Description
id (Relationship to Embedded Object Data)	...
Namespace: ~~.../officeDocument/2006/relationships~~ ps http://purl.oclc.org/ooxml/officeDocument/relationships	The specified relationship shall be of type ~~http://schemas.openxmlformats.org/officeDocument/2006/oleObject~~ http://purl.oclc.org/ooxml/officeDocument/oleObject or the document shall be considered non-conformant. ...

102. §17.3.3.21, “objectLink (Linked Object Properties)”, p. 368, attribute id

Attributes	Description
id (Relationship to Embedded Object Data)	...
Namespace: ~~.../officeDocument/2006/relationships~~ ps http://purl.oclc.org/ooxml/officeDocument/relationships	The specified relationship shall be of type ~~http://schemas.openxmlformats.org/officeDocument/2006/oleObject~~ http://purl.oclc.org/ooxml/officeDocument/oleObject or the document shall be considered non-conformant. ...

103. §17.4.88, “Table Measurement (CT_TblWidth)”, p. 527, attribute w

Attributes	Description
w (Table Width Value)	... The possible values for this attribute are defined by the ~~ST_DecimalNumberOrPercent~~ ST_MeasurementOrPercent simple type (§17.18.44107).

104. §17.6.2, “bottom (Bottom Border)”, pp. 612–614, attribute various

Attributes	Description
bottomLeft (Custom Defined Bottom Left Border Relationship Reference) Namespace: ~~.../officeDocument~~ ~~/2006/relationships~~ ~~ps~~ http://purl.oclc.org/ooxml/officeDocument/relationships/ps	... The relationship explicitly targeted by this attribute shall be of type http://schemas.openxmlformats.org/officeDocument/2006/relationships/image http://purl.oclc.org/ooxml/officeDocument/relationships/image or the document shall be considered non-conformant. ...
bottomRight (Custom Defined Bottom Right Border Relationship Reference) Namespace: ~~.../officeDocument~~ ~~/2006/relationships~~ ~~ps~~ http://purl.oclc.org/ooxml/officeDocument/relationships/ps	... The relationship explicitly targeted by this attribute shall be of type http://schemas.openxmlformats.org/officeDocument/2006/relationships/image http://purl.oclc.org/ooxml/officeDocument/relationships/image or the document shall be considered non-conformant. ...
id (Custom Defined Border Relationship Reference) Namespace: ~~.../officeDocument~~ ~~/2006/relationships~~ ~~ps~~ http://purl.oclc.org/ooxml/officeDocument/relationships/ps	... The relationship explicitly targeted by this attribute shall be of type http://schemas.openxmlformats.org/officeDocument/2006/relationships/image http://purl.oclc.org/ooxml/officeDocument/relationships/image or the document shall be considered non-conformant. ...

105. §17.6.7, “left (LeftBorder)”, p. 630, attribute id

Attributes	Description
id (Custom Defined Border Relationship Reference)	...
Namespace: ~~.../officeDocument/2006/relationships~~ ~~ps~~ http://purl.oclc.org/ooxml/officeDocument/relationships	The relationship explicitly targeted by this attribute shall be of type http://schemas.openxmlformats.org/officeDocument/2006/relationships/image http://purl.oclc.org/ooxml/officeDocument/relationships/image or the document shall be considered non-conformant. ...

106. §17.6.14, “printerSettings (Reference to Printer Settings Data)”, p. 650, attribute id

Attributes	Description
id (Relationship to Part)	Specifies the relationship ID to a specified part.
Namespace: ~~.../officeDocument/2006/relationships~~ ~~ps~~ http://purl.oclc.org/ooxml/officeDocument/relationships	The specified relationship shall match the relationship type required by the parent element: • ~~http://schemas.openxmlformats.org/officeDocument/2006/customXml~~ http://purl.oclc.org/ooxml/officeDocument/customXml for the contentPart element • ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/footer~~ http://purl.oclc.org/ooxml/officeDocument/relationships/footer for the footerReference element • ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/header~~ http://purl.oclc.org/ooxml/officeDocument/relationships/header for the headerReference element • ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/font~~ http://purl.oclc.org/ooxml/officeDocument/relationships/font for the embedBold, embedBoldItalic, embedItalic, or embedRegular elements • ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/printerSettings~~ http://purl.oclc.org/ooxml/officeDocument/relationships/printerSettings for the printerSettings element • ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/hyperlink~~ http://purl.oclc.org/ooxml/officeDocument/relationships/hyperlink for the longDesc or hyperlink element
	...

107. §17.6.15, “right (Right Border)”, p. 653, attribute id

Attributes	Description
id (Custom Defined Border Relationship Reference)	...
Namespace: .../officeDocument/2006/relationships	The relationship explicitly targeted by this attribute shall be of type http://schemas.openxmlformats.org/officeDocument/2006/relationships/image or the document shall be considered non-conformant.
ps http://purl.oclc.org/ooxml/officeDocument/relationships	...

108. §17.6.21, “top (Top Border)”, pp. 670–676, attribute various

Attributes	Description
id (Custom Defined Border Relationship Reference)	...
Namespace: .../officeDocument/2006/relationships	The relationship explicitly targeted by this attribute shall be of type http://schemas.openxmlformats.org/officeDocument/2006/relationships/image or the document shall be considered non-conformant.
ps http://purl.oclc.org/ooxml/officeDocument/relationships	...
topLeft (Custom Defined Top Left Border Relationship Reference)	...
Namespace: .../officeDocument/2006/relationships	The relationship explicitly targeted by this attribute shall be of type http://schemas.openxmlformats.org/officeDocument/2006/relationships/image or the document shall be considered non-conformant.
ps http://purl.oclc.org/ooxml/officeDocument/relationships	...

Attributes	Description
topRight (Custom Defined Top Right Border Relationship Reference)	...
Namespace: ~~.../officeDocument/2006/relationships~~ ~~ps~~ http://purl.oclc.org/ooxml/officeDocument/relationships	The relationship explicitly targeted by this attribute shall be of type http://schemas.openxmlformats.org/officeDocument/2006/relationships/image http://purl.oclc.org/ooxml/officeDocument/relationships/image or the document shall be considered non-conformant. ...

109. §17.8.3.3, “embedBold (Bold Style Font Style Embedding)”, p. 754, attribute id

Attributes	Description
id (Relationship to Part)	Specifies the relationship ID to a specified part.
Namespace: ~~.../officeDocument/2006/relationships~~ ~~ps~~ http://purl.oclc.org/ooxml/officeDocument/relationships	The specified relationship shall match the relationship type required by the parent element: • ~~http://schemas.openxmlformats.org/officeDocument/2006/customXml~~ http://purl.oclc.org/ooxml/officeDocument/customXml for the contentPart element • ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/footer~~ http://purl.oclc.org/ooxml/officeDocument/relationships/footer for the footerReference element • ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/header~~ http://purl.oclc.org/ooxml/officeDocument/relationships/header for the headerReference element • ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/font~~ http://purl.oclc.org/ooxml/officeDocument/relationships/font for the embedBold, embedBoldItalic, embedItalic, or embedRegular elements • ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/printerSettings~~ http://purl.oclc.org/ooxml/officeDocument/relationships/printerSettings for the printerSettings element • ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/hyperlink~~ http://purl.oclc.org/ooxml/officeDocument/relationships/hyperlink for the longDesc or hyperlink element
	...

110. §17.8.3.4, “embedBoldItalic (Bold Italic Font Style Embedding)”, p. 756, attribute id

Attributes	Description
id (Relationship to Part) Namespace: ~~.../officeDocument/2006/relationships~~ http://purl.oclc.org/ooxml/officeDocument/relationships	Specifies the relationship ID to a specified part. The specified relationship shall match the relationship type required by the parent element: ~~http://schemas.openxmlformats.org/officeDocument/2006/customXml~~http://purl.oclc.org/ooxml/officeDocument/customXml for the contentPart element ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/footer~~ http://purl.oclc.org/ooxml/officeDocument/relationships/footer for the footerReference element ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/header~~ http://purl.oclc.org/ooxml/officeDocument/relationships/header for the headerReference element ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/font~~ http://purl.oclc.org/ooxml/officeDocument/relationships/font for the embedBold, embedBoldItalic, embedItalic, or embedRegular elements ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/printerSettings~~ http://purl.oclc.org/ooxml/officeDocument/relationships/printerSettings for the printerSettings element ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/hyperlink~~ http://purl.oclc.org/ooxml/officeDocument/relationships/hyperlink for the longDesc or hyperlink element ...

111. §17.8.3.5, “embedItalic (Italic Font Style Embedding)”, pp. 758–759, attribute id

Attributes	Description
id (Relationship to Part) Namespace: http://purl.oclc.org/officeDocument/relationships	Specifies the relationship ID to a specified part. The specified relationship shall match the relationship type required by the parent element: • http://schemas.openxmlformats.org/officeDocument/2006/customXml for the contentPart element • http://schemas.openxmlformats.org/officeDocument/2006/relationships/footer for the footerReference element • http://schemas.openxmlformats.org/officeDocument/2006/relationships/header for the headerReference element • http://schemas.openxmlformats.org/officeDocument/2006/relationships/font for the embedBold, embedBoldItalic, embedItalic, or embedRegular elements • http://schemas.openxmlformats.org/officeDocument/2006/relationships/printerSettings for the printerSettings element • http://schemas.openxmlformats.org/officeDocument/2006/relationships/hyperlink for the longDesc or hyperlink element ...

112. §17.8.3.6, “embedRegular (Regular Font Style Embedding)”, pp. 760–761, attribute id

Attributes	Description
id (Relationship to Part)	Specifies the relationship ID to a specified part.
Namespace: ~~.../officeDocument/2006/relationships~~ http://purl.oclc.org/ooxml/officeDocument/relationships	The specified relationship shall match the relationship type required by the parent element: ~~http://schemas.openxmlformats.org/officeDocument/2006/customXml~~http://purl.oclc.org/ooxml/officeDocument/customXml for the contentPart element ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/footer~~http://purl.oclc.org/ooxml/officeDocument/relationships/footer for the footerReference element ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/header~~http://purl.oclc.org/ooxml/officeDocument/relationships/header for the headerReference element ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/font~~http://purl.oclc.org/ooxml/officeDocument/relationships/font for the embedBold, embedBoldItalic, embedItalic, or embedRegular elements ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/printerSettings~~http://purl.oclc.org/ooxml/officeDocument/relationships/printerSettings for the printerSettings element ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/hyperlink~~http://purl.oclc.org/ooxml/officeDocument/relationships/hyperlink for the longDesc or hyperlink element ...

113. §17.10.2, “footerReference (Footer Reference)”, pp. 823–824

If the relationship type of the relationship specified by this element is not

~~http://schemas.openxmlformats.org/officeDocument/2006/footer~~<http://purl.oclc.org/ooxml/officeDocument/relationships/footer>, is not present, or does not have a TargetMode attribute value of Internal, then the document shall be considered non-conformant.

...

```
<Relationships
```

```
xmlns="http://schemas.openxmlformats.org/package/2006/relationships">
```

```
...
```

```
<Relationship Id="rId6"
```

```
Type="http://schemas.openxmlformats.org/officeDocument/2006/relationships/footer  
http://purl.oclc.org/ooxml/officeDocument/relationships/footer" Target="footer1.xml" />
```

```

<Relationship Id="rId7"
Type="http://schemas.openxmlformats.org/officeDocument/2006/relationships/footer
http://purl.oclc.org/ooxml/officeDocument/relationships/footer" Target="footer2.xml" />
<Relationship Id="rId10"
Type="http://schemas.openxmlformats.org/officeDocument/2006/relationships/footer
http://purl.oclc.org/ooxml/officeDocument/relationships/footer" Target="footer3.xml" />
...
</Relationships>

```

114. §17.10.2, “footerReference (Footer Reference)”, p. 825, attribute id

Attributes	Description
id (Relationship to Part) Namespace: ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships~~ http://purl.oclc.org/ooxml/officeDocument/relationships	Specifies the relationship ID to a specified part. The specified relationship shall match the relationship type required by the parent element: • ~~http://schemas.openxmlformats.org/officeDocument/2006/customXml~~http://purl.oclc.org/ooxml/officeDocument/customXml for the contentPart element • ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/footer~~ http://purl.oclc.org/ooxml/officeDocument/relationships/footer for the footerReference element • ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/header~~ http://purl.oclc.org/ooxml/officeDocument/relationships/header for the headerReference element • ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/font~~ http://purl.oclc.org/ooxml/officeDocument/relationships/font for the embedBold, embedBoldItalic, embedItalic, or embedRegular elements • ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/printerSettings~~ http://purl.oclc.org/ooxml/officeDocument/relationships/printerSettings for the printerSettings element • ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/hyperlink~~ http://purl.oclc.org/ooxml/officeDocument/relationships/hyperlink for the longDesc or hyperlink element ...

115. §17.10.5, “headerReference (Header Reference)”, pp. 832–834

If the relationship type of the relationship specified by this element is not ~~http://schemas.openxmlformats.org/officeDocument/2006/header~~ <http://purl.oclc.org/ooxml/officeDocument/relationships/header>, is not present, or does not have a TargetMode attribute value of Internal, then the document shall be considered non-conformant.

...

```

<Relationships
xmlns="http://schemas.openxmlformats.org/package/2006/relationships">
...
  <Relationship Id="rId2"
Type="http://schemas.openxmlformats.org/officeDocument/2006/relationships/header
http://purl.oclc.org/ooxml/officeDocument/relationships/header"
Target="header1.xml" />
  <Relationship Id="rId3"
Type="http://schemas.openxmlformats.org/officeDocument/2006/relationships/header
http://purl.oclc.org/ooxml/officeDocument/relationships/header"
Target="header2.xml" />
  <Relationship Id="rId5"
Type="http://schemas.openxmlformats.org/officeDocument/2006/relationships/header
http://purl.oclc.org/ooxml/officeDocument/relationships/header"
Target="header3.xml" />
...
</Relationships>

```

116. §17.10.5, “headerReference (Header Reference)”, p. 834, attribute id

Attributes	Description
id (Relationship to Part) Namespace: ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships~~ http://purl.oclc.org/ooxml/officeDocument/relationships	Specifies the relationship ID to a specified part. The specified relationship shall match the relationship type required by the parent element: • ~~http://schemas.openxmlformats.org/officeDocument/2006/customXml~~http://purl.oclc.org/ooxml/officeDocument/customXml for the contentPart element • ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/footer~~http://purl.oclc.org/ooxml/officeDocument/relationships/footer for the footerReference element • ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/header~~http://purl.oclc.org/ooxml/officeDocument/relationships/header for the headerReference element • ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/font~~http://purl.oclc.org/ooxml/officeDocument/relationships/font for the embedBold, embedBoldItalic, embedItalic, or embedRegular elements • ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/printerSettings~~http://purl.oclc.org/ooxml/officeDocument/relationships/printerSettings for the printerSettings element • ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/hyperlink~~http://purl.oclc.org/ooxml/officeDocument/relationships/hyperlink for the longDesc or hyperlink element ...

117. §17.14.9, “dataSource (Data Source File Path)”, pp. 1057–1058, attribute id

If this element is omitted, then no file location is specified for the data source for the current mail merge. If no relationship exists with the given relationship ID, or this relationship is not of type

<http://schemas.openxmlformats.org/officeDocument/2006/relationships/mailMergeSource> <http://purl.oclc.org/ooxml/officeDocument/relationships/mailMergeSource> then this document shall be considered non-conformant.

...

```
<Relationships>
  <Relationship Id="rId1"
    Type="http://schemas.openxmlformats.org/officeDocument/2006/relationships/mailMergeSource"
    Target="file:///c:/example_file.mdb" TargetMode="External" />
</Relationships>
```

118. §17.14.9, “dataSource (Data Source File Path)”, p. 1058, attribute id

Attributes	Description
id (Relationship to Part) Namespace: ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships~~ http://purl.oclc.org/ooxml/officeDocument/relationships	Specifies the relationship ID to a specified part. The specified relationship shall match the relationship type required by the parent element: • ~~http://schemas.openxmlformats.org/officeDocument/2006/customXml~~ http://purl.oclc.org/ooxml/officeDocument/customXml for the contentPart element • ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/footer~~ http://purl.oclc.org/ooxml/officeDocument/relationships/footer for the footerReference element • ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/header~~ http://purl.oclc.org/ooxml/officeDocument/relationships/header for the headerReference element • ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/font~~ http://purl.oclc.org/ooxml/officeDocument/relationships/font for the embedBold, embedBoldItalic, embedItalic, or embedRegular elements • ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/printerSettings~~ http://purl.oclc.org/ooxml/officeDocument/relationships/printerSettings for the printerSettings element • ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/hyperlink~~ http://purl.oclc.org/ooxml/officeDocument/relationships/hyperlink for the longDesc or hyperlink element ...

119. §17.14.16, “headerSource (Header Definition File Path)”, p. 1064

```
<Relationships>
  <Relationship Id="rId2"
Type="http://schemas.openxmlformats.org/officeDocument/2006/relationships/mailMergeSourcehttp://purl.oclc.org/ooxml/officeDocument/relationships/mailMergeSource
" Target="file:///c:/headerData.txt" TargetMode="External" />
</Relationships>
```

120. §17.14.16, “headerSource (Header Definition File Path)”, p. 1065, attribute id

Attributes	Description
id (Relationship to Part)	Specifies the relationship ID to a specified part.
Namespace: http://schemas.openxmlformats.org/officeDocument/2006/relationships	The specified relationship shall match the relationship type required by the parent element: • http://schemas.openxmlformats.org/officeDocument/2006/customXml for the contentPart element • http://schemas.openxmlformats.org/officeDocument/2006/relationships/footer for the footerReference element • http://schemas.openxmlformats.org/officeDocument/2006/relationships/header for the headerReference element • http://schemas.openxmlformats.org/officeDocument/2006/relationships/font for the embedBold, embedBoldItalic, embedItalic, or embedRegular elements • http://schemas.openxmlformats.org/officeDocument/2006/relationships/printerSettings for the printerSettings element • http://schemas.openxmlformats.org/officeDocument/2006/relationships/hyperlink for the longDesc or hyperlink element
...	...

121. §17.14.28, “recipientData (Reference to Inclusion/Exclusion Data for Data Source)”, pp. 1079–1080

If the relationship type of the relationship specified by this element is not <http://schemas.openxmlformats.org/officeDocument/2006/mailMergeRecipientData> <http://purl.oclc.org/ooxml/officeDocument/relationships/mailMergeRecipientData>, is not present, or does not have a TargetMode attribute value of Internal, then the document shall be considered non-conformant. If an application cannot process external content of the content type specified by the targeted part, then it can be ignored.

...

<Relationships ... >

...

<Relationship Id="recipient1" TargetMode="Internal"
 Type="~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/mailMergeRecipientData~~<http://purl.oclc.org/ooxml/officeDocument/relationships/mailMergeRecipientData>" Target="recipientData.xml" />

...

</Relationships>

122. §17.14.28, “recipientData (Reference to Inclusion/Exclusion Data for Data Source)”, p. 1080–1081, attribute id

Attributes	Description
id (Relationship to Part) Namespace: ~~.../officeDocument/2006/relationships~~ http://purl.oclc.org/ooxml/officeDocument/relationships	Specifies the relationship ID to a specified part. The specified relationship shall match the relationship type required by the parent element: • ~~http://schemas.openxmlformats.org/officeDocument/2006/customXml~~http://purl.oclc.org/ooxml/officeDocument/customXml for the contentPart element • ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/footer~~http://purl.oclc.org/ooxml/officeDocument/relationships/footer for the footerReference element • ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/header~~http://purl.oclc.org/ooxml/officeDocument/relationships/header for the headerReference element • ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/font~~http://purl.oclc.org/ooxml/officeDocument/relationships/font for the embedBold, embedBoldItalic, embedItalic, or embedRegular elements • ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/printerSettings~~http://purl.oclc.org/ooxml/officeDocument/relationships/printerSettings for the printerSettings element • ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/hyperlink~~http://purl.oclc.org/ooxml/officeDocument/relationships/hyperlink for the longDesc or hyperlink element ...

123. §17.14.30, “src (ODSO Data Source File Path)”, p. 1083

```
<Relationships>
  <Relationship Id="rId1"
Type="http://schemas.openxmlformats.org/officeDocument/2006/relationships/mailMergeSource"
  Target="file:///c:/example_file.mdb" TargetMode="External" />
</Relationships>
```

124. §17.14.30, “src (ODSO Data Source File Path)”, p. 1083, attribute id

Attributes	Description
id (Relationship to Part)	Specifies the relationship ID to a specified part.
Namespace: ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships~~ http://purl.oclc.org/ooxml/officeDocument/relationships	The specified relationship shall match the relationship type required by the parent element: ~~http://schemas.openxmlformats.org/officeDocument/2006/customXml~~http://purl.oclc.org/ooxml/officeDocument/customXml for the contentPart element ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/footer~~http://purl.oclc.org/ooxml/officeDocument/relationships/footer for the footerReference element ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/header~~http://purl.oclc.org/ooxml/officeDocument/relationships/header for the headerReference element ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/font~~http://purl.oclc.org/ooxml/officeDocument/relationships/font for the embedBold, embedBoldItalic, embedItalic, or embedRegular elements ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/printerSettings~~http://purl.oclc.org/ooxml/officeDocument/relationships/printerSettings for the printerSettings element ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/hyperlink~~http://purl.oclc.org/ooxml/officeDocument/relationships/hyperlink for the longDesc or hyperlink element
...	...

125. §17.14.35, “uniqueTag (Unique Value for Record)”, pp. 1088–1089

The possible values for this element are defined by the [CT_Base64Binary](#) ~~W3C XML Schema base64Binary~~ datatype.

126. §17.15.1.6, “attachedTemplate (Attached Document Template)”, pp. 1097–1098, attribute id

Attributes	Description
id (Relationship to Part) Namespace: ~~...~~ /officeDocument/2006/relationships http://purl.oclc.org/ooxml/officeDocument/relationships	Specifies the relationship ID to a specified part. The specified relationship shall match the relationship type required by the parent element: ~~http://schemas.openxmlformats.org/officeDocument/2006/customXml~~http://purl.oclc.org/ooxml/officeDocument/customXml for the contentPart element ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/footer~~http://purl.oclc.org/ooxml/officeDocument/relationships/footer for the footerReference element ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/header~~http://purl.oclc.org/ooxml/officeDocument/relationships/header for the headerReference element ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/font~~http://purl.oclc.org/ooxml/officeDocument/relationships/font for the embedBold, embedBoldItalic, embedItalic, or embedRegular elements ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/printerSettings~~http://purl.oclc.org/ooxml/officeDocument/relationships/printerSettings for the printerSettings element ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/hyperlink~~http://purl.oclc.org/ooxml/officeDocument/relationships/hyperlink for the longDesc or hyperlink element ...

127. §17.15.1.76, “saveThroughXslt (Custom XSL Transform To Use When Saving As XML File)”, p. 1193, attribute id

Attributes	Description
id (XSL Transformation Location) Namespace: ~~...~~ /officeDocument/2006/relationships http://purl.oclc.org/ooxml/officeDocument/relationships	Specifies an explicit relationship to the location of the XSL Transformation which shall be applied. The relationship targeted by this element shall be of type http://schemas.openxmlformats.org/officeDocument/2006/relationships/transform http://purl.oclc.org/ooxml/officeDocument/relationships/transform , or this document shall be declared non-conformant. ...

128. §17.15.2.23, longDesc (Frame Long Description), p. 1253

```
<Relationships ... >
...
<Relationship Id="rIdMenuBar" TargetMode="External"
Type="http://schemas.openxmlformats.org/officeDocument/2006/relationships/hyperlinkhttp://purl.oclc.org/ooxml/officeDocument/relationships/hyperlink"
Target="myexample-desc.html#menubar" />
...
</Relationships>
```

129. §17.15.2.23, “longDesc (Frame Long Description)”, p. 1253, attribute id

Attributes	Description
id (Relationship to Part)	Specifies the relationship ID to a specified part.
Namespace: ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships~~ http://purl.oclc.org/ooxml/officeDocument/relationships	The specified relationship shall match the relationship type required by the parent element: ~~http://schemas.openxmlformats.org/officeDocument/2006/customXml~~http://purl.oclc.org/ooxml/officeDocument/customXml for the contentPart element ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/footer~~http://purl.oclc.org/ooxml/officeDocument/relationships/footer for the footerReference element ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/header~~http://purl.oclc.org/ooxml/officeDocument/relationships/header for the headerReference element ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/font~~http://purl.oclc.org/ooxml/officeDocument/relationships/font for the embedBold, embedBoldItalic, embedItalic, or embedRegular elements ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/printerSettings~~http://purl.oclc.org/ooxml/officeDocument/relationships/printerSettings for the printerSettings element ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/hyperlink~~http://purl.oclc.org/ooxml/officeDocument/relationships/hyperlink for the longDesc or hyperlink element
	...

130. §17.15.2.39, “sourceFileName (Source File for Frame)”, p. 1276

The relationship referenced by this element's id attribute shall exist in the relationship part item for the Web Settings part, or this document shall be considered non-conformant. Also, the type of the relationship referenced by this element's id attribute shall be ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/frame~~<http://purl.oclc.org/ooxml/officeDocument/relationships/frame>, or this document shall be considered non-conformant.

131. §17.15.2.39, “sourceFileName (Source File for Frame)”, pp. 1277–1278, attribute id

Attributes	Description
id (Relationship to Part) Namespace: ~~.../officeDocument/2006/relationships~~ http://purl.oclc.org/ooxml/officeDocument/relationships	Specifies the relationship ID to a specified part. The specified relationship shall match the relationship type required by the parent element: ~~http://schemas.openxmlformats.org/officeDocument/2006/customXml~~http://purl.oclc.org/ooxml/officeDocument/customXml for the contentPart element ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/footer~~http://purl.oclc.org/ooxml/officeDocument/relationships/footer for the footerReference element ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/header~~http://purl.oclc.org/ooxml/officeDocument/relationships/header for the headerReference element ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/font~~http://purl.oclc.org/ooxml/officeDocument/relationships/font for the embedBold, embedBoldItalic, embedItalic, or embedRegular elements ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/printerSettings~~http://purl.oclc.org/ooxml/officeDocument/relationships/printerSettings for the printerSettings element ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/hyperlink~~http://purl.oclc.org/ooxml/officeDocument/relationships/hyperlink for the longDesc or hyperlink element ...

132. §17.16.22, “hyperlink (Hyperlink)”, p. 1426, attribute id

Attributes	Description
id (Hyperlink Target) Namespace: http://purl.oclc.org/ooxml/officeDocument/relationships ~~.../officeDocument/2006/relationships~~	...

133. §17.17.1.1, “subDoc (Anchor for Subdocument Location)”, pp. 1444–1445

If the relationship type of the relationship specified by this element is not

~~http://schemas.openxmlformats.org/officeDocument/2006/subDocument~~<http://purl.oclc.org/ooxml/office>

[Document/relationships/subDocument](#), is not present, or does not have a TargetMode attribute value of External, then the document shall be considered non-conformant.

...

```
<Relationships ... >
  ...
  <Relationship Id="subDocRel1" TargetMode="External"
Type="http://schemas.openxmlformats.org/officeDocument/2006/relationships/subDoc
umenthttp://purl.oclc.org/ooxml/officeDocument/relationships/subDocument"
Target="Chapter1.docx" />
  <Relationship Id="subDocRel2" TargetMode="External"
Type="http://schemas.openxmlformats.org/officeDocument/2006/relationships/subDoc
umenthttp://purl.oclc.org/ooxml/officeDocument/relationships/subDocument"
Target="Chapter2.docx" />
  ...
</Relationships>
```

134. §17.17.1.1, “subDoc (Anchor for Subdocument Location)”, p. 1446, attribute id

Attributes	Description
id (Relationship to Part) Namespace: ~~.../officeDocument/2006/relationships~~ http://purl.oclc.org/ooxml/officeDocument/relationships	Specifies the relationship ID to a specified part. The specified relationship shall match the relationship type required by the parent element: • ~~http://schemas.openxmlformats.org/officeDocument/2006/customXml~~http://purl.oclc.org/ooxml/officeDocument/customXml for the contentPart element • ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/footer~~http://purl.oclc.org/ooxml/officeDocument/relationships/footer for the footerReference element • ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/header~~http://purl.oclc.org/ooxml/officeDocument/relationships/header for the headerReference element • ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/font~~http://purl.oclc.org/ooxml/officeDocument/relationships/font for the embedBold, embedBoldItalic, embedItalic, or embedRegular elements • ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/printerSettings~~http://purl.oclc.org/ooxml/officeDocument/relationships/printerSettings for the printerSettings element • ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/hyperlink~~http://purl.oclc.org/ooxml/officeDocument/relationships/hyperlink for the longDesc or hyperlink element ...

135. §17.17.2.1, “altChunk (Anchor for Imported External Content)”, pp. 1447–1448

If the relationship type of the relationship specified by this element is not

<http://schemas.openxmlformats.org/officeDocument/2006/afChunk><http://purl.oclc.org/ooxml/officeDocument/relationships/afChunk>, is not present, or does not have a TargetMode attribute value of Internal, then the document shall be considered non-conformant. If an application cannot process external content of the content type specified by the targeted part, then it should ignore the specified alternate content but continue to process the file. If possible, it should also provide some indication that unknown content was not imported.

...

```
<Relationships ... >
```

...

```
<Relationship Id="altChunk1" TargetMode="Internal"
Type="http://schemas.openxmlformats.org/officeDocument/2006/relationships/afChunk
http://purl.oclc.org/ooxml/officeDocument/relationships/afChunk" Target="import.htm" />
```

...

```
</Relationships>
```

136. §17.17.2.1, “altChunk (Anchor for Imported External Content)”, p. 1449, attribute id

Attributes	Description
id (Relationship to Part)	...
Namespace: http://schemas.openxmlformats.org/officeDocument/2006/relationships	

137. §17.18, “Simple Types”, p. 1453

This is the complete list of simple types [dedicated to WordprocessingML](http://schemas.openxmlformats.org/wordprocessingml/2006/main-namespaces) in the <http://schemas.openxmlformats.org/wordprocessingml/2006/main-namespaces>.

138. §17.18.95, “ST_TextScale (Text Expansion/Compression Percentage)”, p. 1668

[Example: ...

Consider a run of text which must be compressed ~~to 200%~~by half when displaying each character within the contents of the run. This constraint is specified using the following WordprocessingML:

```
<w:rPr>
  <w:w w:val="50%" />
</w:rPr>
```

This run explicitly declares that the w value is 50%, so the contents of this run appear at 50% of their normal character width by compressing the width of each character. *end example*]

This simple type's ~~contents are a restriction of the W3C XML Schema integer datatype.~~ is a union of the following types:

- The ST_TextScalePercent simple type (§A.1).

~~This simple type also specifies the following restrictions:~~

- ~~• This simple type has a minimum value of greater than or equal to 0.~~
- ~~• This simple type has a maximum value of less than or equal to 600.~~

139. §17.18.106, “ST_TextScalePercent (Text Expansion/Compression Percentage), new subclause

This simple type specifies that the percentage by which the contents of a run shall be expanded or compressed with respect to its normal (100%) character width, with a minimum width of 1% and maximum width of 600%.

[Example: Consider a run of text that must be compressed by half when displaying each character within the contents of the run. This constraint is specified using the following WordprocessingML:

```
<w:rPr>
  <w:w w:val="50%" />
</w:rPr>
```

This run explicitly declares that the w value is 50%, so the contents of this run appear at 50% of their normal character width by compressing the width of each character. *end example*]

This simple type also specifies the following restrictions:

- This simple type's contents shall match the following regular expression pattern: 0*(600|([0-5]?[0-9]?[0-9]))%.

Referenced By
ST_TextScale (§17.18.95)

[*Note:* The W3C XML Schema definition of this simple type's content model (ST_TextScalePercent) is located in §A.1. *end note*]

140. §17.18.107, “ST_MeasurementOrPercent (Measurement or Percentage Value)”, new subclause

This simple type specifies the possible values for a table measurement, which can be percentage-based or absolute. See the union's member types for details.

This simple type is a union of the following types:

[The ST_DecimalNumberOrPercent simple type \(§17.18.11\).](#)

[The ST_UniversalMeasure simple type \(§22.9.2.15\).](#)

Referenced By
CT_TblWidth (§17.4.88)

[*Note:* The W3C XML Schema definition of this simple type's content model (ST_MeasurementOrPercent) is located in §A.1. *end note*]

141. §18.2.7, “ext (Extension)”, p. 1721

[*Example:* ...

```
<extLst>
  <ext
    uri='http://schemas.openxmlformats.org/spreadsheetml/versionTwoExtensionhttp://p
    url.oclc.org/ooxml/spreadsheetml/versionTwoExtension'>
    <v2:newContent
      xmlns:v2='http://schemas.openxmlformats.org/spreadsheetml/versionTwoExtensionhttp
      ://purl.oclc.org/ooxml/spreadsheetml/versionTwoExtension'>
      ...
    </v2:newContent>
  </ext>
  ...
</extLst>
```

end example]

142. §18.2.8, “externalReference (External Reference)”, p. 1722, attribute id

Attributes	Description
id (Relationship Id) Namespace: ~~.../officeDocument~~ ~~/2006/relationships~~ ~~ps~~ http://purl.oclc.org/ooxml/officeDocument/relationships	...

143. §18.2.17, “pivotCache (PivotCache)”, p. 1731, attribute id

Attributes	Description
id (Relationship Id) Namespace: ~~.../officeDocument~~ ~~/2006/relationships~~ ~~ps~~ http://purl.oclc.org/ooxml/officeDocument/relationships	...

144. §18.2.19, “sheet (Sheet Information)”, p. 1732, attribute id

Attributes	Description
id (Relationship Id) Namespace: ~~.../officeDocument~~ ~~/2006/relationships~~ ~~ps~~ http://purl.oclc.org/ooxml/officeDocument/relationships	...

145. §18.2.27, “workbook (Workbook)”, p. 1739

[Example:

```
<?xml version="1.0" encoding="UTF-8" standalone="yes"?>
<workbook
xmlns="http://schemas.openxmlformats.org/spreadsheetml/2006/5/main"
xmlns:r="http://schemas.openxmlformats.org/officeDocument/2006/relationships"
  <fileVersion lastEdited="4" lowestEdited="4" rupBuild="4017"/>
  ...
</workbook>
```

end example]

146. §18.3.1.19, “control (Embedded Control)”, p. 1776, attribute id

Attributes	Description
id (Relationship Id) Namespace: ~~.../officeDocument/2006/relationships~~ http://purl.oclc.org/ooxml/officeDocument/relationships	...

147. §18.3.1.20, “controlPr (Embedded Control Properties)”, p. 1779, attribute id

Attributes	Description
id (Relationship ID for Embedded Control Properties) Namespace: ~~.../officeDocument/2006/relationships~~ http://purl.oclc.org/ooxml/officeDocument/relationships	... The relationship explicitly targeted by this attribute shall be of relationship type http://schemas.openxmlformats.org/officeDocument/2006/relationships/control http://purl.oclc.org/ooxml/officeDocument/relationships/control or the document shall be considered non-conformant. ...

148. §18.3.1.22, “customPr (Custom Property)”, p. 1782, attribute id

Attributes	Description
id (Relationship Id) Namespace: ~~.../officeDocument~~ ~~/2006/relationships~~ ~~ps~~ http://purl.oclc.org/ooxml/officeDocument/relationships	...

149. §18.3.1.30, “dataRef (Data Consolidation Reference)”, p. 1790, attribute id

Attributes	Description
id (relationship Id) Namespace: ~~.../officeDocument~~ ~~/2006/relationships~~ ~~ps~~ http://purl.oclc.org/ooxml/officeDocument/relationships	...

150. §18.3.1.36, “drawing (Drawing)”, p. 1796, attribute id

Attributes	Description
id (Relationship id) Namespace: ~~.../officeDocument~~ ~~/2006/relationships~~ ~~ps~~ http://purl.oclc.org/ooxml/officeDocument/relationships	...

**151. §18.3.1.37, “drawingHF (Drawing Reference in Header Footer)”,
pp. 1798–1799, attribute id**

Attributes	Description
id (Relationship ID for Embedded Control Properties) Namespace: ~~.../officeDocument~~ ~~/2006/relationships~~ ~~ps~~ http://purl.oclc.org/ooxml/officeDocument/relationships	...

152. §18.3.1.47, “hyperlink (Hyperlink)”, p. 1812, attribute id

Attributes	Description
id (Relationship Id) Namespace: ~~.../officeDocument~~ ~~/2006/relationships~~ ~~ps~~ http://purl.oclc.org/ooxml/officeDocument/relationships	...

153. §18.3.1.56, “objectPr (Embedded Object Properties)”, p. 1821, attribute id

Attributes	Description
id (Relationship ID to Embedded Object Data)	...
Namespace: ~~.../officeDocument/2006/relationships~~ ps http://purl.oclc.org/ooxml/officeDocument/relationships	The specified relationship shall be of type http://schemas.openxmlformats.org/officeDocument/2006/oleObject or the document shall be considered non-conformant. ...

154. §18.3.1.59, “oleObject (Embedded Object)”, p. 1824, attribute id

Attributes	Description
id (Relationship Id)	...
Namespace: ~~.../officeDocument/2006/relationships~~ ps http://purl.oclc.org/ooxml/officeDocument/relationships	

155. §18.3.1.63, “pageSetup (Page Setup Settings)”, p. 1829, attribute id

Attributes	Description
id (Id)	...
Namespace: ~~.../officeDocument/2006/relationships~~ ps http://purl.oclc.org/ooxml/officeDocument/relationships	

156. §18.3.1.64, “pageSetup (Chart Sheet Page Setup)”, p. 1832, attribute id

Attributes	Description
id (Id) Namespace: ~~...~~ /officeDocument ~~/2006/relationships~~ ~~ps~~ http://purl.oclc.org/ooxml/officeDocument/relationships	...

157. §18.3.1.67, “picture (Background Image)”, p. 1837, attribute id

Attributes	Description
id (Relationship Id) Namespace: ~~...~~ /officeDocument ~~/2006/relationships~~ ~~ps~~ http://purl.oclc.org/ooxml/officeDocument/relationships	...

158. §18.3.1.69, “pivotSelection (PivotTable Selection)”, p. 1841, attribute id

Attributes	Description
id (Relationship Id) Namespace: ~~...~~ /officeDocument ~~/2006/relationships~~ ~~ps~~ http://purl.oclc.org/ooxml/officeDocument/relationships	...

159. §18.3.1.94, “tablePart (Table Part)”, p. 1882, attribute id

Attributes	Description
id (Relationship Id) Namespace: ~~.../officeDocument~~ ~~/2006/relationships~~ ~~ps~~ http://purl.oclc.org/ooxml/officeDocument/relationships ps	...

160. §18.4, “Shared String Table”, pp. 1896–1897

[Example:

```
<sst
xmlns=http://schemas.openxmlformats.org/spreadsheetml/2006/5/mainhttp://purl.oclc.org/ooxml/spreadsheetml/main
count="8" uniqueCount="4">
...
</sst>
```

...

[Example:

```
<sst xmlns=
http://schemas.openxmlformats.org/spreadsheetml/2006/5/mainhttp://purl.oclc.org/ooxml/spreadsheetml/main
count="8" uniqueCount="4">
...
</sst>
```

161. §18.4.1, “charset (Character Set)”, p. 1898

INT Value	Character Set
...	...
~~129~~	~~HANGEUL_CHARSET~~
129	HANGUL_CHARSET
...	...

162. §18.5, “Tables”, p. 1907

[Example:

```
<table xmlns=
http://schemas.openxmlformats.org/spreadsheetml/2006/5/mainhttp://purl.oclc.org/ooxml/spreadsheetml/main
  id="1" name="MarginTable" displayName="MarginTable" ref="D3:G6"
  totalsRowShown="0">
  ...
</table>
```

163. §18.6, “Calculation Chain”, pp. 1925–1926

[Example:

```
<calcChain xmlns=
http://schemas.openxmlformats.org/spreadsheetml/2006/5/mainhttp://purl.oclc.org/ooxml/spreadsheetml/main ">
  <c r="E5" i="1"/>
  ...
</calcChain>
```

...

```
<calcChain xmlns=
http://schemas.openxmlformats.org/spreadsheetml/2006/5/mainhttp://purl.oclc.org/ooxml/spreadsheetml/main ">
  <c r="B1" i="1"/>
  ...
</calcChain>
```

end example]

164. §18.8.18, “family (Font Family)”, p. 1952

The font family this font belongs to. ~~A font family is a set of fonts having common stroke width and serif characteristics. This is system level font information.~~ The font name overrides when there are conflicting values.

Value	Font Family
0	Not applicable.
1	Roman

Value	Font Family
2	Swiss
3	Modern
4	Script
5	Decorative

Attributes	Description
val (Value)	The font family this font belongs to ~~value of an integer, where each value corresponds to a different character set. This attribute is restricted to values ranging from 0 to 255.~~ The possible values for this attribute are defined by the ST_FonFamily simple type (§18.18.94) W3C XML Schema int datatype.

[Note: The W3C XML Schema definition of this element's content model ([CT_IntPropertyCT_FonFamily](#)) is located in §A.2. end note]

165. §18.9, "Metadata", p. 1994

[Example: The CUBEMEMBER() function ...]

```
<metadata xmlns="
http://schemas.openxmlformats.org/spreadsheetml/2006/5/mainhttp://purl.oclc.org/ooxml/spreadsheetml/main ">
...
</metadata>
```

166. §18.10.1.67, “pivotCacheDefinition (PivotCache Definition)”, p. 2095, attribute id

Attributes	Description
id (Relationship Identifier) Namespace: ~~.../officeDocument~~ ~~/2006/relationships~~ ~~ps~~ http://purl.oclc.org/ooxml/officeDocument/relationships	...

167. §18.10.1.79, “rangeSet (Range Set)”, p. 2154, attribute id

Attributes	Description
id (Relationship Id) Namespace: ~~.../officeDocument~~ ~~/2006/relationships~~ ~~ps~~ http://purl.oclc.org/ooxml/officeDocument/relationships	...

168. §18.10.1.95, “worksheetSource (Worksheet PivotCache Source)”, p. 2170, attribute id

Attributes	Description
id (Relationship Id) Namespace: ~~.../officeDocument~~ ~~/2006/relationships~~ ~~ps~~ http://purl.oclc.org/ooxml/officeDocument/relationships	...

169. §18.11.1.1, “header (Header)”, p. 2180, attribute id

Attributes	Description
id (Relationship ID) Namespace: ~~.../officeDocument~~ ~~/2006/relationships~~ ~~ps~~ http://purl.oclc.org/ooxml/officeDocument/relationships	...

170. §18.14.7, “externalBook (External Workbook)”, p. 2248, attribute id

Attributes	Description
id (Relationship to supporting book file path) Namespace: ~~.../officeDocument~~ ~~/2006/relationships~~ ~~ps~~ http://purl.oclc.org/ooxml/officeDocument/relationships	...

171. §18.14.11, “oleLink (Generic Object Link Connection)”, p. 2251, attribute id

Attributes	Description
id (Object Link Relationship) Namespace: ~~.../officeDocument~~ ~~/2006/relationships~~ ~~ps~~ http://purl.oclc.org/ooxml/officeDocument/relationships	...

172. §18.17.2.3, “Cell References”, pp. 2282–2284

- Type shall be set to <http://schemas.openxmlformats.org/officeDocument/2006/relationships/externalLinkPath> <http://purl.oclc.org/ooxml/officeDocument/relationships/externalLinkPath>
- Target shall specify the full file path and file name, and
- TargetMode shall be set to External.

...

[Example:

Consider the formula =SUM('C:\[Source.xlsx]Sheet1'!\$A\$1:\$A\$3) ...

```
<Relationship Id="rId4" Type=
"http://schemas.openxmlformats.org/officeDocument/2006/relationships/externalLink"
Target="externalLinks/externalLink1.xml"/>
```

...

```
<externalBook
xmlns:r="http://schemas.openxmlformats.org/officeDocument/2006/relationships"
r:id="rId1">
```

...

```
<Relationship Id="rId1" Type=
"http://schemas.openxmlformats.org/officeDocument/2006/relationships/externalLinkPath"
Target="file:///C:/Source.xlsx" TargetMode="External"/>
```

... end example]

173. §18.17.5.2, “Precision”, p. 2296

The *value space* consists of the values $(-1)^s \times m \times 2^n$, where s is 0 or 1, where m is an integer greater than or equal to 0 and whose absolute value is less than 2^{53} , and n is an integer between -107⁴⁵ and 97¹⁰, inclusive.

174. §18.17.7.204, “MATCH”, p. 2510

However, if

- No match is found, ~~#N/A~~^{#NUM!} is returned.

175. §18.18, “Simple Types”, p. 2664

This is the complete list of simple types [dedicated to SpreadsheetML](http://schemas.openxmlformats.org/spreadsheetml/2006/main-namespace) in the <http://schemas.openxmlformats.org/spreadsheetml/2006/main-namespace>.

176. §18.18.94, “ST_FontFamily (Font Family)”, new subclause

This simple type specifies a font family. A font family is a set of fonts having common stroke width and serif characteristics. This is system level font information.

This simple type's contents are a restriction of the W3C XML Schema unsignedInt datatype.

This simple type is restricted to the values listed in the following table:

<u>Value</u>	<u>Font Family</u>
<u>0</u>	<u>Not applicable.</u>
<u>1</u>	<u>Roman</u>
<u>2</u>	<u>Swiss</u>
<u>3</u>	<u>Modern</u>
<u>4</u>	<u>Script</u>
<u>5</u>	<u>Decorative</u>
<u>6</u>	<u>Reserved for future use</u>
<u>7</u>	<u>Reserved for future use</u>
<u>8</u>	<u>Reserved for future use</u>
<u>9</u>	<u>Reserved for future use</u>
<u>10</u>	<u>Reserved for future use</u>
<u>11</u>	<u>Reserved for future use</u>
<u>12</u>	<u>Reserved for future use</u>
<u>13</u>	<u>Reserved for future use</u>
<u>14</u>	<u>Reserved for future use</u>

Referenced By
fontFamily@val (§18.8.18)

[Note: The W3C XML Schema definition of this simple type's content model (ST FontFamily) is located in §A.2.
end note]

177. §19.2.1.1, “bold (Bold Embedded Font)”, p. 2760, attribute id

Attributes	Description
id (Relationship Identifier) Namespace: ~~...~~ /officeDocument ~~/2006/relationships~~ ~~ps~~ http://purl.oclc.org/ooxml/officeDocument/relationships	...

178. §19.2.1.2, “boldItalic (Bold Italic Embedded Font)”, pp. 2760–2761, attribute id

Attributes	Description
id (Relationship Identifier) Namespace: ~~...~~ /officeDocument ~~/2006/relationships~~ ~~ps~~ http://purl.oclc.org/ooxml/officeDocument/relationships	...

179. §19.2.1.11, “ext (Extension)”, p. 2767

Child Elements	Subclause
Zero or more ~~Any~~ elements in any namespace	n/a

180. §19.2.1.13, “font (Embedded Font Name)”, pp. 2768–2770, attribute various

Attributes	Description
charset (Similar Character Set) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...
panose (Panose Setting) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...
pitchFamily (Similar Font Family) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...
typeface (Text Typeface) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...

181. §19.2.1.14, “handoutMasterId (Handout Master ID)”, p. 2771, attribute id

Attributes	Description
id (Relationship Identifier) Namespace: ~~.../officeDocument~~ ~~/2006/relationships~~ ~~ps~~ http://purl.oclc.org/ooxml/officeDocument/relationships	...

182. §19.2.1.16, “italic (Italic Embedded Font)”, p. 2772, attribute id

Attributes	Description
id (Relationship Identifier) Namespace: ~~.../officeDocument~~ ~~/2006/relationships~~ ~~ps~~ http://purl.oclc.org/ooxml/officeDocument/relationships	...

183. §19.2.1.20, “notesMasterId (Notes Master ID)”, p. 2778, attribute id

Attributes	Description
id (Relationship Identifier) Namespace: ~~.../officeDocument~~ ~~/2006/relationships~~ ~~ps~~ http://purl.oclc.org/ooxml/officeDocument/relationships	...

184. §19.2.1.22, “notesSz (Notes Slide Size)”, p. 2779, attribute various

Attributes	Description
cx (Extent Length) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...
cy (Extent Width) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...

185. §19.2.1.29, “regular (Regular Embedded Font)”, p. 2787, attribute id

Attributes	Description
id (Relationship Identifier) Namespace: ~~.../officeDocument/2006/relationships~~ http://purl.oclc.org/ooxml/officeDocument/relationships	...

186. §19.2.1.31, “slid (Presentation Slide)”, p. 2789, attribute id

Attributes	Description
id (Relationship ID) Namespace: ~~.../officeDocument/2006/relationships~~ http://purl.oclc.org/ooxml/officeDocument/relationships	...

187. §19.2.1.33, “sldId (Slide ID)”, p. 2790, attribute id

Attributes	Description
id (Relationship Identifier) Namespace: ~~...~~ /officeDocument ~~/2006/relationships~~ ~~ps~~ http://purl.oclc.org/ooxml/officeDocument/relationships	...

188. §19.2.1.36, “sldMasterId (Slide Master ID)”, p. 2791, attribute id

Attributes	Description
id (Relationship Identifier) Namespace: ~~...~~ /officeDocument ~~/2006/relationships~~ ~~ps~~ http://purl.oclc.org/ooxml/officeDocument/relationships	...

189. §19.2.1.40, “SmartTags (SmartTags)”, p. 2795, attribute id

Attributes	Description
id (Relationship Identifier) Namespace: ~~...~~ /officeDocument ~~/2006/relationships~~ ~~ps~~ http://purl.oclc.org/ooxml/officeDocument/relationships	...

190. §19.2.2.3, “gridSpacing (Grid Spacing)”, p. 2797, attribute various

Attributes	Description
cx (Extent Length) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...
cy (Extent Width) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...

191. §19.2.2.9, “origin (View Origin)”, p. 2801, attribute various

Attributes	Description
x (X-Axis Coordinate) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...
y (Y-Axis Coordinate) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...

192. §19.2.2.14, “sld (Presentation Slide)”, p. 2804, attribute id

Attributes	Description
id (Relationship Identifier) Namespace: ~~...~~ /officeDocument/2006/relationshipshttp://purl.oclc.org/ooxml/officeDocument/relationships	...

193. §19.3.1.3, “bgRef (Background Style Reference)”, pp. 2809–2810, attribute idx

Attributes	Description
idx (Style Matrix Index) Namespace: ~~...~~ /drawingml/2006/mainhttp://purl.oclc.org/ooxml/drawingml/main	...

194. §19.3.1.4, “blipFill (Picture Fill)”, p. 2812, attribute various

Attributes	Description
dpi (DPI Setting) Namespace: ~~...~~ /drawingml/2006/mainhttp://purl.oclc.org/ooxml/drawingml/main	...
rotWithShape (Rotate With Shape) Namespace: ~~...~~ /drawingml/2006/mainhttp://purl.oclc.org/ooxml/drawingml/main	...

195. §19.3.1.6, “clrMap (Color Scheme Map)”, p. 2814–2815, attribute various

Attributes	Description
accent1 (Accent 1) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...
accent2 (Accent 2) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...
accent3 (Accent 3) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...
accent4 (Accent 4) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...
accent5 (Accent 5) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...
accent6 (Accent 6) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...

Attributes	Description
bg1 (Background 1) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...
bg2 (Background 2) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...
folHlink (Followed Hyperlink) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...
hlink (Hyperlink) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...
tx1 (Text 1) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...
tx2 (Text 2) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...

196. §19.3.1.11, “cNvPicPr (Non-Visual Picture Drawing Properties)”, pp. 2817–2818, attribute preferRelativeResize

Attributes	Description
preferRelativeResize (Relative Resize Preferred) Namespace: .../drawingml/2006/mainhttp://purl.oclc.org/ooxml/drawingml/main	...

197. §19.3.1.12, “cNvPr (Non-Visual Drawing Properties)”, pp. 2819–2820, attribute various

Attributes	Description
descr (Alternative Text for Object) Namespace: .../drawingml/2006/mainhttp://purl.oclc.org/ooxml/drawingml/main	...
hidden (Hidden) Namespace: .../drawingml/2006/mainhttp://purl.oclc.org/ooxml/drawingml/main	...
id (Unique Identifier) Namespace: .../drawingml/2006/mainhttp://purl.oclc.org/ooxml/drawingml/main	...

Attributes	Description
name (Name) Namespace: .../drawingml/2006/main http://purl.oclc.org/ooxml/drawingml/main	...
title (Title) Namespace: .../drawingml/2006/main http://purl.oclc.org/ooxml/drawingml/main	...

198. §19.3.1.13, “cNvSpPr (Non-Visual Drawing Properties for a Shape)”, p. 2821, attribute txBox

Attributes	Description
txBox (Text Box) Namespace: .../drawingml/2006/main http://purl.oclc.org/ooxml/drawingml/main	...

199. §19.3.1.14, “ContentPart (Content Part)”, pp. 2821–2824

The relationship type of the explicit relationship specified by this element shall be

<http://schemas.openxmlformats.org/officeDocument/2006/customXml> and have a TargetMode attribute value of Internal. If an application cannot process content of the content type specified by the targeted part, then it should continue to process the file. If possible, it should also provide some indication that unknown content was not imported.

...

```
<Relationships ... >
```

```
...
<Relationship Id="smil01" TargetMode="Internal"
```

```
Type="http://schemas.openxmlformats.org/officeDocument/2006/relationships/custom
Xmlhttp://purl.oclc.org/ooxml/officeDocument/relationships/customXml"
```

```
Target="smil1.xml" />
```

```
...
</Relationships>
```

200. §19.3.1.14, “ContentPart (Content Part)”, p. 2824, attribute id

Attributes	Description
id (Relationship to Part) Namespace: ~~...~~ /officeDocument ~~/2006/relationships~~ ~~ps~~ http://purl.oclc.org/ooxml/officeDocument/relationships	...

201. §19.3.1.17, “custData (Customer Data)”, p. 2826, attribute id

Attributes	Description
id (Relationship ID) Namespace: ~~...~~ /officeDocument ~~/2006/relationships~~ ~~ps~~ http://purl.oclc.org/ooxml/officeDocument/relationships	...

202. §19.3.1.23, “grpSpPr (Group Shape Properties)”, p. 2831, attribute bwMode

Attributes	Description
bwMode (Black and White Mode) Namespace: ~~...~~ /drawingml/2006/main ~~http://purl.oclc.org/ooxml/drawingml/main~~	...

203. §19.3.1.40, “sldLayoutId (Slide Layout ID)”, p. 2844, attribute id

Attributes	Description
id (ID Tag) Namespace: ~~...~~ /officeDocument ~~/2006/relationships~~ ~~ps~~ http://purl.oclc.org/ooxml/officeDocument/relationships	...

204. §19.3.1.44, “spPr (Shape Properties)”, pp. 2847–2848, attribute bwMode

Attributes	Description
bwMode (Black and White Mode) Namespace: ~~...~~ /drawingml/2006/main ~~http://purl.oclc.org/ooxml/drawingml/main~~	...

205. §19.3.1.47, “tags (Customer Data Tags)”, p. 2851, attribute id

Attributes	Description
id (Relationship ID) Namespace: ~~...~~ /officeDocument ~~/2006/relationships~~ ~~ps~~ http://purl.oclc.org/ooxml/officeDocument/relationships	...

206. §19.3.1.53, “xfrm (2D Transform for Graphic Frame)”, p. 2856, attribute various

Attributes	Description
flipH (Horizontal Flip) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...
flipV (Vertical Flip) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...
rot (Rotation) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...

207. §19.3.2.1, “control (Embedded Control)”, p. 2857, attribute id

Attributes	Description
id (Relationship ID) Namespace: ~~.../officeDocument/2006/relationships~~ http://purl.oclc.org/ooxml/officeDocument/relationships	...

208. §19.3.2.4, “oleObj (Global Element for Embedded objects and Controls)”, p. 2859, attribute id

Attributes	Description
id (Relationship ID) Namespace: ~~.../officeDocument~~ ~~/2006/relationships~~ ~~ps~~ http://purl.oclc.org/ooxml/officeDocument/relationships	...

209. §19.4.5, “pos (Comment Position)”, p. 2865, attribute various

Attributes	Description
x (X-Axis Coordinate) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...
y (Y-Axis Coordinate) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...

210. §19.5.68, “snd (Sound)”, p. 2942, attribute various

Attributes	Description
embed (Embedded Audio File Relationship ID) Namespace: ~~...~~ /officeDocument/2006/relationships http://purl.oclc.org/ooxml/officeDocument/relationships	...
name (Sound Name) Namespace: ~~...~~ /drawingml/2006/main http://purl.oclc.org/ooxml/drawingml/main	...

211. §19.5.70, “sndTgt (Sound Target)”, p. 2943, attribute various

Attributes	Description
embed (Embedded Audio File Relationship ID) Namespace: ~~...~~ /officeDocument/2006/relationships http://purl.oclc.org/ooxml/officeDocument/relationships	...
name (Sound Name) Namespace: ~~...~~ /drawingml/2006/main http://purl.oclc.org/ooxml/drawingml/main	...

212. §19.7, “Simple Types”, p. 2974

This is the complete list of simple types [dedicated to PresentationML](http://schemas.openxmlformats.org/presentationml/2006/main-namespace-) in the <http://schemas.openxmlformats.org/presentationml/2006/main-namespace->

213. §20.1.2.2.14, “ext (Extension)”, p. 3028

Child Elements	Subclause
Zero or more Any elements in any namespace	n/a

214. §20.1.2.2.23, “hlinkHover (Hyperlink for Hover)”, p. 3037, attribute id

Attributes	Description
id (Drawing Object Hyperlink Target) Namespace: ~~.../officeDocument~~ ~~/2006/relationships~~ ~~ps~~ http://purl.oclc.org/ooxml/officeDocument/relationships	...

215. §20.1.2.2.32, “snd (Hyperlink Sound)”, p. 3044, attribute embed

Attributes	Description
embed (Embedded Audio File Relationship ID) Namespace: ~~.../officeDocument~~ ~~/2006/relationships~~ ~~ps~~ http://purl.oclc.org/ooxml/officeDocument/relationships	...

216. §20.1.3.2, “audioFile (Audio from File)”, pp. 3083–3084, attribute link

Attributes	Description
link (Linked Relationship ID) Namespace: ~~.../officeDocument~~ ~~/2006/relationships~~ ~~ps~~ http://purl.oclc.org/ooxml/officeDocument/relationships	...

217. §20.1.3.4, “quickTimeFile (QuickTime from File)”, pp. 3085–3086, attribute link

Attributes	Description
link (Linked Relationship ID) Namespace: ~~.../officeDocument~~ ~~/2006/relationships~~ ~~ps~~ http://purl.oclc.org/ooxml/officeDocument/relationships	...

218. §20.1.3.6, “videoFile (Video from File)”, p. 3088, attribute link

Attributes	Description
link (Linked Relationship ID) Namespace: ~~.../officeDocument~~ ~~/2006/relationships~~ ~~ps~~ http://purl.oclc.org/ooxml/officeDocument/relationships	...

219. §20.1.3.7, “wavAudioFile (Audio from WAV File)”, p. 3089, attribute embed

Attributes	Description
embed (Embedded Audio File Relationship ID) Namespace: ~~...~~ ~~/officeDocument/2006/relationships~~ http://purl.oclc.org/ooxml/officeDocument/relationships	...

220. §20.1.8.13, “blip (Blip)”, p. 3187, attribute embed

Attributes	Description
embed (Embedded Picture Reference) Namespace: http://purl.oclc.org/ooxml/officeDocument/relationships ~~...~~ ~~/officeDocument/2006/relationships~~	...
link (Linked Picture Reference) Namespace: ~~...~~ ~~/officeDocument/2006/relationships~~ http://purl.oclc.org/ooxml/officeDocument/relationships	...

221. §20.1.10, “Simple Types”, p. 3262

This is the complete list of simple types [dedicated to DrawingML framework](http://schemas.openxmlformats.org/drawingml/2006/main). ~~in the~~
~~<http://schemas.openxmlformats.org/drawingml/2006/main>~~
~~namespace.~~

**222. §20.1.10.41, “ST_PercentageDecimal (Percentage as Decimal Number)”,
p. 3298**

~~20.1.10.41 — ST_PercentageDecimal (Percentage as Decimal Number)~~

~~This simple type represents a percentage in 1000ths of a percent, e.g., a value of 1 represents 0.001% == 0.00001; a value of 100000 is equal to 100%. Percentages have no intrinsic units, but are used to scale other values with units.~~

~~This simple type's contents are a restriction of the W3C XML Schema int datatype.~~

Referenced By
ST_Percentage (§xx); ST_TextBulletSizePercent (§224)

~~[Note: The W3C XML Schema definition of this simple type's content model (ST_PercentageDecimal) is located in §xx. end note]~~

**223. §20.1.10.62, “ST_TextBulletSizePercent (Bullet Size Percentage)”,
p. 3420**

This simple type specifies the range that the bullet percent can be. A bullet percent is the size of the bullet with respect to the text that should follow it. ~~25000 – 25 % 400000 – 400 %~~

~~This simple type's contents are a restriction of the ST_PercentageDecimal datatype (§0).~~

This simple type also specifies the following restrictions:

- ~~• This simple type has a minimum value of greater than or equal to 25000.~~
- ~~• This simple type has a maximum value of less than or equal to 400000.~~
- This simple type's contents shall match the following regular expression pattern:
0*(([25-9])|([3-9][0-9])|([1-3][0-9][0-9])|400)%.

Referenced By
buSzPet@val (§xx) ST_TextBulletSize (§20.1.10.86)

224. §20.1.10.87, “ST_TextBulletSize (Bullet Size Percentage)”, new subclause

This simple type specifies the range that the bullet percent can be. A bullet percent is the size of the bullet with respect to the text that should follow it, with a minimum size of 25% and maximum size of 400%.

This simple type is a union of the following types:

- The ST_TextBulletSizePercent simple type (§20.1.10.62)

Referenced By[buSzPct@val \(§21.1.2.4.9\)](#)

[Note: The W3C XML Schema definition of this simple type's content model (ST_TextBulletSize) is located in § A.4.1. end note]

225. §20.2.2.1, “blipFill (Picture Fill)”, pp. 3450–3451, attribute various

Attributes	Description
dpi (DPI Setting) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...
rotWithShape (Rotate With Shape) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...

226. §20.2.2.2, “cNvPicPr (Non-Visual Picture Drawing Properties)”, p. 3452, attribute preferRelativeResize

Attributes	Description
preferRelativeResize (Relative Resize Preferred) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...

227. §20.2.2.3, “cNvPr (Non-Visual Drawing Properties)”, pp. 3453–3454, attribute various

Attributes	Description
descr (Alternative Text for Object) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...
hidden (Hidden) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...
id (Unique Identifier) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...
name (Name) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...
title (Title) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...

228. §20.2.2.6, “spPr (Shape Properties)”, p. 3457, attribute bwMode

Attributes	Description
bwMode (Black and White Mode) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...

229. §20.4.2.5, “docPr (Drawing Object Non-Visual Properties)”, pp. 3470–3472, attribute various

Attributes	Description
descr (Alternative Text for Object) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	... The possible values for this attribute are defined by the W3C XML Schema string datatype.
hidden (Hidden) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...
id (Unique Identifier) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...
name (Name) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...

Attributes	Description
title (Title) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...

230. §20.4.2.7, “extent (Drawing Object Size)”, pp. 3476–3477, attribute various

Attributes	Description
cx (Extent Length) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...
cy (Extent Width) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...

231. §20.4.2.9, “lineTo (Wrapping Polygon Line End Position)”, p. 3481, attribute various

Attributes	Description
x (X-Axis Coordinate) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...

Attributes	Description
y (Y-Axis Coordinate) Namespace: .../drawingml/2006/main http://purl.oclc.org/ooxml/drawingml/main	...

232. §20.4.2.13, “simplePos (Simple Positioning Coordinates)”, pp. 3485–3486, attribute various

Attributes	Description
x (X-Axis Coordinate) Namespace: .../drawingml/2006/main http://purl.oclc.org/ooxml/drawingml/main	...
y (Y-Axis Coordinate) Namespace: .../drawingml/2006/main http://purl.oclc.org/ooxml/drawingml/main	...

233. §20.4.2.14, “start (Wrapping Polygon Start)”, pp. 3486–3487, attribute various

Attributes	Description
x (X-Axis Coordinate) Namespace: .../drawingml/2006/main http://purl.oclc.org/ooxml/drawingml/main	...

Attributes	Description
y (Y-Axis Coordinate) Namespace: .../drawingml/2006/main http://purl.oclc.org/ooxml/drawingml/main	...

234. §20.4.3, “Simple Types”, p. 3500

This is the complete list of simple types [dedicated to DrawingML – WordprocessingML Drawing](http://schemas.openxmlformats.org/drawingml/2006/wordprocessingDrawing) in the <http://schemas.openxmlformats.org/drawingml/2006/wordprocessingDrawing> namespace.

235. §20.5, “DrawingML – SpreadsheetML Drawing”, pp. 3507–3508

```

<xdr:twoCellAnchor>
...
<xdr:graphicFrame>
...
<a:graphic>
  <a:graphicData
    uri="http://schemas.openxmlformats.org/drawingml/2006/diagram
http://purl.oclc.org/ooxml/drawingml/diagram">
    <dgm:relIds xmlns:dgm="..." xmlns:r="..." r:dm="rId1" r:lo="rId2"
      r:qs="rId3" r:cs="rId4" />
  </a:graphicData>
</a:graphic>
</xdr:graphicFrame>
</xdr:twoCellAnchor>

```

236. §20.5.2.2, “blipFill (Picture Fill)”, p. 3512, attribute various

Attributes	Description
dpi (DPI Setting) Namespace: .../drawingml/2006/main http://purl.oclc.org/ooxml/drawingml/main	...

Attributes	Description
rotWithShape (Rotate With Shape) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...

237. §20.5.2.7, “cNvPicPr (Non-Visual Picture Drawing Properties)”, p. 3515, attribute preferRelativeResize

Attributes	Description
preferRelativeResize (Relative Resize Preferred) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...

238. §20.5.2.8, “cNvPr (Non-Visual Drawing Properties)”, pp. 3516–3517, attribute various

Attributes	Description
descr (Alternative Text for Object) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...
hidden (Hidden) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...

Attributes	Description
id (Unique Identifier) Namespace: .../drawingml/2006/main http://purl.oclc.org/ooxml/drawingml/main	...
name (Name) Namespace: .../drawingml/2006/main http://purl.oclc.org/ooxml/drawingml/main	...
title (Title) Namespace: .../drawingml/2006/main http://purl.oclc.org/ooxml/drawingml/main	...

239. §20.5.2.9, “cNvSpPr (Connection Non-Visual Shape Properties)”, p. 3518, attribute **txBox**

Attributes	Description
txBox (Text Box) Namespace: .../drawingml/2006/main http://purl.oclc.org/ooxml/drawingml/main	...

240. §20.5.2.12, “contentPart (Content Part)”, pp. 3519–3523

The relationship type of the explicit relationship specified by this element shall be <http://schemas.openxmlformats.org/officeDocument/2006/customXml> <http://purl.oclc.org/ooxml/officeDocument/relationships/customXml> and have a TargetMode attribute value of Internal. If an application cannot process content of the content type specified by the targeted part, then it should continue to process the file. If possible, it should also provide some indication that unknown content was not imported.

...

<Relationships ... >

...

<Relationship Id="svg1" TargetMode="Internal"

Type="[http://schemas.openxmlformats.org/officeDocument/2006/relationships/custom](http://schemas.openxmlformats.org/officeDocument/2006/relationships/customXml)
[Xml http://purl.oclc.org/ooxml/officeDocument/relationships/customXml](http://purl.oclc.org/ooxml/officeDocument/relationships/customXml)" Target="svg1.xml" />

...

</Relationships>

241. §20.5.2.12, “contentPart (Content Part)”, p. 3523, attribute id

Attributes	Description
id (Relationship to Part)	...
Namespace: .../officeDocument/2006/relationships	

242. §20.5.2.14, “ext (Shape Extent)”, pp. 3524–3525, attribute various

Attributes	Description
cx (Extent Length)	...
Namespace: .../drawingml/2006/main	
cy (Extent Width)	...
Namespace: .../drawingml/2006/main	

243. §20.5.2.18, “grpSpPr (Group Shape Properties)”, p. 3529, attribute **bwMode**

Attributes	Description
bwMode (Black and White Mode) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...

244. §20.5.2.26, “pos (Position)”, p. 3534, attribute various

Attributes	Description
x (X-Axis Coordinate) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...
y (Y-Axis Coordinate) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...

245. §20.5.2.30, “spPr (Shape Properties)”, p. 3537, attribute bwMode

Attributes	Description
bwMode (Black and White Mode) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...

246. §20.5.2.36, “xfrm (2D Transform for Graphic Frames)”, pp. 3541–3542, attribute various

Attributes	Description
flipH (Horizontal Flip) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...
flipV (Vertical Flip) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...
rot (Rotation) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...

247. §20.5.3, “Simple Types”, p. 3542

This is the complete list of simple types [dedicated to DrawingML – SpreadsheetML Drawing](http://schemas.openxmlformats.org/drawingml/2006/spreadsheetDrawing). ~~in the~~
~~<http://schemas.openxmlformats.org/drawingml/2006/spreadsheetDrawing> namespace.~~

248. §21.1.2.3.5, “hlinkClick (Click Hyperlink)”, p. 3610, attribute id

Attributes	Description
id (Drawing Object Hyperlink Target) Namespace: ~~...~~ /officeDocument ~~/2006/relationships~~ ~~ps~~ http://purl.oclc.org/ooxml/officeDocument/relationships	...

249. §21.1.2.3.6, “hlinkMouseOver (Mouse-Over Hyperlink)”, p. 3612, attribute id

Attributes	Description
id (Drawing Object Hyperlink Target) Namespace: ~~...~~ /officeDocument ~~/2006/relationships~~ ~~ps~~ http://purl.oclc.org/ooxml/officeDocument/relationships	...

250. §21.2.2.21, “bubbleScale (Bubble Scale)”, p. 3767

This element specifies the scale factor for the bubble chart. This element can be an ~~integer~~ [percentage](#) value from 0% to 300%, corresponding to a percentage of the default size.

251. §21.2.2.26, “chart (Reference to Chart Part)”, p. 3770, attribute id

Attributes	Description
id (Relationship Reference) Namespace: ~~.../officeDocument~~ ~~/2006/relationships~~ ~~ps~~ http://purl.oclc.org/ooxml/officeDocument/relationships	...

252. §21.2.2.30, “clrMapOvr (Color Map Override)”, pp. 3773–3775, attribute various

Attributes	Description
accent1 (Accent 1) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...
accent2 (Accent 2) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...
accent3 (Accent 3) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...
accent4 (Accent 4) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...

Attributes	Description
accent5 (Accent 5) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...
accent6 (Accent 6) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...
bg1 (Background 1) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...
bg2 (Background 2) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...
folHlink (Followed Hyperlink) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...
hlink (Hyperlink) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...

Attributes	Description
tx1 (Text 1) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...
tx2 (Text 2) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...

253. §21.2.2.41, “depthPercent (Depth Percent)”, p. 3780

Attributes	Description
val (Depth Percent Value)	Specifies ~~an integer~~ a percentage value for the property defined by the parent XML element. The possible values for this attribute are defined by the ST_DepthPercent simple type (§21.2.3.9).

254. §21.2.2.63, “externalData (External Data Relationship)”, p. 3790, attribute id

Attributes	Description
id (Relationship Reference) Namespace: ~~.../officeDocument/2006/relationships~~ ~~ps~~ http://purl.oclc.org/ooxml/officeDocument/relationships	Specifies the relationship ID for the relationship for this chart. The relationship explicitly targeted by this attribute shall be of type http://schemas.openxmlformats.org/officeDocument/2006/relationships/package http://purl.oclc.org/ooxml/officeDocument/relationships/package

255. §21.2.2.74, “gapDepth (Gap Depth)”, p. 3795, attribute val

Attributes	Description
val (Gap Size Value)	Specifies that the contents of this attribute contain a gap amount between 0% and 500%. The possible values for this attribute are defined by the ST_GapAmount simple type (§21.2.3.16).

256. §21.2.2.75, “gapWidth (Gap Width)”, p. 3796, attribute val

Attributes	Description
val (Gap Size Value)	Specifies that the contents of this attribute contain a gap amount between 0% and 500%. The possible values for this attribute are defined by the ST_GapAmount simple type (§21.2.3.16).

257. §21.2.2.82, “holeSize (Hole Size)”, p. 3799, attribute val

Attributes	Description
val (Hole Size Value)	Specifies that the contents of this attribute contain a hole size between 10% and 90% ~~that is measured as a percentage~~ of the size of the plot area. The possible values for this attribute are defined by the ST_HoleSize simple type (§21.2.3.18).

258. §21.2.2.83, “hPercent (Height Percent)”, p. 3800

Attributes	Description
val (Height Percent Value)	Specifies that the contents of this attribute contain a height percent between 5% and 500%. The possible values for this attribute are defined by the ST_HPercent simple type (§21.2.3.18).

259. §21.2.2.91, “lblOffset (Label Offset)”, p. 3803, attribute val

Attributes	Description
val (Label Offset Value)	Specifies the contents of this attribute contain an ~~percentage~~ integer between 0% and 1000%. The possible values for this attribute are defined by the ST_LblOffset simple type (§21.2.3.23).

260. §21.2.2.131, “overlap (Overlap)”, p. 3820, attribute val

Attributes	Description
val (Overlap Value)	Specifies the contents of this attribute contain an ~~integer~~ <u>percentage</u> between -100% and 100%. The possible values for this attribute are defined by the ST_Overlap simple type (§21.2.3.31).

261. §21.2.2.136, “perspective (Perspective)”, p. 3827, attribute val

Attributes	Description
val (Perspective Value)	Specifies the contents of this attribute contain an ~~integer~~ <u>a percentage</u> between 0% and ~~100~~ <u>240</u> %. The possible values for this attribute are defined by the ST_Perspective simple type (§21.2.3.34).

262. §21.2.2.164, “secondPieSize (Second Pie Size)”, p. 3839, attribute val

Attributes	Description
val (Second Pie Size Value)	Specifies the contents of this attribute contain an ~~integer~~ <u>a percentage</u> between 5% and 200%. The possible values for this attribute are defined by the ST_SecondPieSize simple type (§21.2.3.41).

263. §21.2.2.197, “spPr (Shape Properties)”, p. 3858, attribute bwMode

Attributes	Description
bwMode (Black and White Mode) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...

264. §21.2.2.206, “thickness (Thickness)”, pp. 3861–3862, attribute val

Attributes	Description
val (Integer Value)	Specifies that the contents of this attribute contain ~~an integer number~~ <u>a percentage</u>. The contents of this number are interpreted based on the context of the parent XML element. The possible values for this attribute are defined by the ~~W3C XML Schema unsignedInt datatype~~ <u>ST_Thickness simple type (§21.2.3.60)</u>.

[Note: The W3C XML Schema definition of this element’s content model (CT ~~UnsignedInt~~ Thickness) is located in §A.5.1. *end note*]

265. §21.2.2.221, “userShapes (Reference to Chart Drawing Part)”, p. 3868, attribute id

Attributes	Description
id (Relationship Reference) Namespace: ~~.../officeDocument~~ ~~/2006/relationships~~ ~~ps~~ http://purl.oclc.org/ooxml/officeDocument/relationships	...

266. §21.2.3, “Simple Types”, p. 3875

This is the complete list of simple types dedicated to DrawingML – Charts. ~~in the~~
~~http://schemas.openxmlformats.org/drawingml/2006/chart namespace.~~

267. §21.2.3.5, “ST_BubbleScale (Bubble Scale)”, pp. 3877–3878

This simple type specifies that its contents contain an ~~integer~~ percentage between 0% and 300%.

This simple type ~~’s contents are a restriction of the W3C XML Schema unsignedInt datatype.~~ is a union of the following types:

- ST_BubbleScalePercent simple type (§21.2.3.59).

~~This simple type also specifies the following restrictions:~~

- ~~This simple type has a minimum value of greater than or equal to 0.~~
- ~~This simple type has a maximum value of less than or equal to 300.~~

268. §21.2.3.9, “ST_DepthPercent (Depth Percent)”, p. 3880

This simple type specifies that its contents contain a ~~whole number~~[percentage](#) between 20% and 2000%, ~~whose contents are a percentage.~~

This simple type's ~~contents are a restriction of the W3C XML Schema unsignedShort datatype.~~ [is a union of the following types:](#)

- [ST_DepthPercentWithSymbol simple type \(§21.2.3.51\).](#)

~~This simple type also specifies the following restrictions:~~

- ~~This simple type has a minimum value of greater than or equal to 20.~~
- ~~This simple type has a maximum value of less than or equal to 2000.~~

269. §21.2.3.16, “ST_GapAmount (Gap Amount)”, p. 3883

This simple type specifies that its contents contain ~~an integer~~ [a percentage](#) between 0% and 500%, ~~whose contents are a percentage.~~

This simple type's ~~contents are a restriction of the W3C XML Schema unsignedShort datatype.~~ [is a union of the following types:](#)

- [ST_GapAmountPercent simple type \(§21.2.3.53\).](#)

~~This simple type also specifies the following restrictions:~~

- ~~This simple type has a minimum value of greater than or equal to 0.~~
- ~~This simple type has a maximum value of less than or equal to 500.~~

270. §21.2.3.18, “ST_HoleSize (Hole Size)”, p. 3884

This simple type specifies that its contents contain an [percentage](#) ~~integer~~ between 10% and 90%, ~~whose contents are a percentage.~~

This simple type's ~~contents are a restriction of the W3C XML Schema unsignedByte datatype.~~ [is a union of the following types:](#)

- [ST_HoleSizePercent simple type \(§21.2.3.56\).](#)

~~This simple type also specifies the following restrictions:~~

- ~~This simple type has a minimum value of greater than or equal to 10.~~
- ~~This simple type has a maximum value of less than or equal to 90.~~

271. §21.2.3.19, “ST_HPercent (Height Percent)”, p. 3885

This simple type specifies that its contents contain ~~an integer~~ a percentage between 5% and 500% ~~whose contents are a percentage~~.

This simple type ~~'s contents are a restriction of the W3C XML Schema unsignedShort datatype~~ is a union of the following types:

- ST_HPercentWithSymbol simple type (§21.2.3.52).

~~This simple type also specifies the following restrictions:~~

- ~~• This simple type has a minimum value of greater than or equal to 5.~~
- ~~• This simple type has a maximum value of less than or equal to 500.~~

272. §21.2.3.23, “ST_LblOffset (Label Offset)”, pp. 3886–3887

This simple type specifies that its contents contain ~~an integer~~ percentage between 0% and 1000% ~~whose contents are a percentage of the default value~~.

This simple type ~~'s contents are a restriction of the W3C XML Schema unsignedShort datatype~~ is a union of the following types:

- ST_LblOffsetPercent simple type (§21.2.3.57).

~~This simple type also specifies the following restrictions:~~

- ~~• This simple type has a minimum value of greater than or equal to 0.~~
- ~~• This simple type has a maximum value of less than or equal to 1000.~~

273. §21.2.3.31, “ST_Overlap (Overlap)”, p. 3891

This simple type specifies that its contents contain ~~an integer~~ percentage between -100% and 100% ~~whose contents are a percentage~~.

This simple type ~~'s contents are a restriction of the W3C XML Schema byte datatype~~ is a union of the following types:

- ST_OverlapPercent simple type (§21.2.3.58).

~~This simple type also specifies the following restrictions:~~

- ~~• This simple type has a minimum value of greater than or equal to -100.~~
- This simple type has a maximum value of less than or equal to 100.

274. §21.2.3.34, “ST_Perspective (Perspective)”, p. 3892

This simple type specifies that its contents contain ~~an integer~~ a percentage between 0% and ~~100~~240%, ~~whose contents are a percentage.~~

This simple type ~~'s contents are a restriction of the W3C XML Schema unsignedByte datatype.~~ is a union of the following types:

- ST_PerspectivePercent simple type (§21.2.3.54).

~~This simple type also specifies the following restrictions:~~

- ~~This simple type has a minimum value of greater than or equal to 0.~~
- ~~This simple type has a maximum value of less than or equal to 240.~~

275. §21.2.3.41, “ST_SecondPieSize (Second Pie Size)”, p. 3896

This simple type specifies that its contents contain ~~an integer~~ a percentage between 5% and 200%, ~~whose contents consist of a percentage.~~

This simple type ~~'s contents are a restriction of the W3C XML Schema unsignedShort datatype.~~ is a union of the following types:

- ST_SecondPieSizePercent simple type (§21.2.3.55).

~~This simple type also specifies the following restrictions:~~

- ~~This simple type has a maximum value of less than or equal to 200.~~
- ~~This simple type has a minimum value of greater than or equal to 5.~~

276. §21.2.3.51, “ST_DepthPercentWithSymbol (Depth Percent with Symbol)”, new subclause

This simple type specifies that its contents contain a percentage between 20% and 2000%.

The simple type's contents shall match the following regular expression pattern:

0*(([2-9][0-9])|(1[0-9][0-9])|(1[0-9][0-9][0-9])|2000)%.

Referenced By
<u>ST_DepthPercent (§21.2.3.9)</u>

277. §21.2.3.52, “ST_HPercentWithSymbol (Height Percent with Symbol)”, new subclause

This simple type specifies that its contents contain a percentage between 5% and 500%.

The simple type's contents shall match the following regular expression pattern:

[0*\(\[5-9\]\)|\(\[1-9\]\[0-9\]\)|\(\[1-4\]\[0-9\]\[0-9\]\)|500\)%.](#)

Referenced By
ST_HPercent (§21.2.3.19)

278. §21.2.3.53, “ST_GapAmountPercent (Gap Amount Percentage)”, new subclause

[This simple type specifies that its contents contain a percentage between 0% and 500%.](#)

[The simple type’s contents shall match the following regular expression pattern:](#)

[0*\(\[0-9\]\)|\(\[1-9\]\[0-9\]\)|\(\[1-4\]\[0-9\]\[0-9\]\)|500\)%.](#)

Referenced By
ST_GapAmount (§21.2.3.16)

279. §21.2.3.54, “ST_PerspectivePercent (Perspective Percentage)”, new subclause

[This simple type specifies that its contents contain a percentage between 0% and 240%.](#)

[The simple type’s contents shall match the following regular expression pattern:](#)

[0*\(\[0-9\]\)|\(\[1-9\]\[0-9\]\)|\(1\[0-9\]\[0-9\]\)|\(2\[0-3\]\[0-9\]\)|240\)%.](#)

Referenced By
ST_Perspective (§21.2.3.34)

280. §21.2.3.55, “ST_SecondPieSizePercent (Second Pie Size Percentage)”, new subclause

[This simple type specifies that its contents contain a percentage between 5% and 200%.](#)

[The simple type’s contents shall match the following regular expression pattern:](#)

[0*\(\[5-9\]\)|\(\[1-9\]\[0-9\]\)|\(1\[0-9\]\[0-9\]\)|200\)%.](#)

Referenced By
ST_SecondPieSize (§21.2.3.41)

281. §21.2.3.56, “ST_HoleSizePercent (Hole Size Percentage)”, new subclause

[This simple type specifies that its contents contain a percentage between 1% and 90%.](#)

[The simple type’s contents shall match the following regular expression pattern: 0*\(\[1-9\]\)|\(\[1-8\]\[0-9\]\)|90\)%.](#)

Referenced By
ST_HoleSize (§21.2.3.18)

282. §21.2.3.57, “ST_LblOffsetPercent (Label Offset Percentage)”, new subclause

[This simple type specifies that its contents contain a percentage between 0% and 1000%.](#)

[The simple type’s contents shall match the following regular expression pattern:](#)

[0*\(\[0-9\]\)|\(\[1-9\]\[0-9\]\)|\(\[1-9\]\[0-9\]\[0-9\]\)|1000\)%.](#)

Referenced By
ST_LblOffset (§21.2.3.23)

283. §21.2.3.58, “ST_OverlapPercent (Overlap Percentage)”, new subclause

[This simple type specifies that its contents contain a percentage between 0% and 100%.](#)

[The simple type’s contents shall match the following regular expression pattern:](#)

[\(-?0*\(\[0-9\]\)|\(\[1-9\]\[0-9\]\)|100\)%.](#)

Referenced By
ST_Overlap (§21.2.3.31)

284. §21.2.3.59, “ST_BubbleScalePercent (Bubble Scale Percentage)”, new subclause

[This simple type specifies that its contents contain a percentage between 0% and 300%.](#)

[The simple type’s contents shall match the following regular expression pattern:](#)

[0*\(\[0-9\]\)|\(\[1-9\]\[0-9\]\)|\(\[1-2\]\[0-9\]\[0-9\]\)|300\)%.](#)

Referenced By
ST_BubbleScale (§21.2.3.5)

285. §21.2.3.60, “ST_Thickness (Thickness Percentage)”, new subclause

[This simple type specifies that its contents contain a percentage.](#)

[This simple type is a union of the following types:](#)

- [ST_ThicknessPercent simple type \(§21.2.3.61\).](#)

286. §21.2.3.61, “ST_ThicknessPercent (Thickness Percentage)”, new subclause

[This simple type specifies that its contents contain a percentage.](#)

[The simple type’s contents shall match the following regular expression pattern: \(\[0-9\]+\)%.](#)

Referenced By
ST_Thickness (§21.2.3.60)

287. §21.3.2.2, “blipFill (Picture Fill)”, pp. 3913–3914, attribute various

Attributes	Description
dpi (DPI Setting) Namespace: .../drawingml/2006/main http://purl.oclc.org/ooxml/drawingml/main	...
rotWithShape (Rotate With Shape) Namespace: .../drawingml/2006/main http://purl.oclc.org/ooxml/drawingml/main	...

288. §21.3.2.6, “cNvPicPr (Non-Visual Picture Drawing Properties)”, p. 3916, attribute preferRelativeResize

Attributes	Description
preferRelativeResize (Relative Resize Preferred) Namespace: .../drawingml/2006/main http://purl.oclc.org/ooxml/drawingml/main	...

**289. §21.3.2.7, “cNvPr (Non-Visual Drawing Properties)”, pp. 3917–3918,
attribute various**

Attributes	Description
descr (Alternative Text for Object) Namespace: .../drawingml/2006/main http://purl.oclc.org/ooxml/drawingml/main	...
hidden (Hidden) Namespace: .../drawingml/2006/main http://purl.oclc.org/ooxml/drawingml/main	...
id (Unique Identifier) Namespace: .../drawingml/2006/main http://purl.oclc.org/ooxml/drawingml/main	...
name (Name) Namespace: .../drawingml/2006/main http://purl.oclc.org/ooxml/drawingml/main	...
title (Title) Namespace: .../drawingml/2006/main http://purl.oclc.org/ooxml/drawingml/main	...

290. §21.3.2.8, “cNvSpPr (Non-Visual Shape Drawing Properties)”, p. 3919, attribute txBox

Attributes	Description
txBox (Text Box) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...

291. §21.3.2.10, “ext (Shape Extent)”, p. 3922, attribute various

Attributes	Description
cx (Extent Length) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...
cy (Extent Width) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...

292. §21.3.2.14, “grpSpPr (Group Shape Properties)”, p. 3926, attribute bwMode

Attributes	Description
bwMode (Black and White Mode) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...

293. §21.3.2.23, “spPr (Shape Properties)”, p. 3934, attribute bwMode

Attributes	Description
bwMode (Black and White Mode) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...

294. §21.3.2.28, “xfrm (Graphics Frame Transform)”, p. 3937, attribute various

Attributes	Description
flipH (Horizontal Flip) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...
flipV (Vertical Flip) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...
rot (Rotation) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...

295. §21.3.3, “Simple Types”, p. 3938

This is the complete list of simple types [dedicated to DrawingML – Chart Drawings](http://schemas.openxmlformats.org/drawingml/2006/chartDrawing). ~~in the~~
<http://schemas.openxmlformats.org/drawingml/2006/chartDrawing> namespace.

296. §21.4.2.14, “forEach (For Each)”, p. 3955

```
<shape
xmlns:r="http://purl.oclc.org/ooxml/officeDocument/relationships" r:blip="">
```

297. §21.4.2.19, “layoutNode (Layout Node)”, p. 3964

```
<shape type="rect"
xmlns:r="http://purl.oclc.org/ooxml/officeDocument/relationships" r:blip="">
```

298. §21.4.2.22, “relIds (Explicit Relationships to Diagram Parts)”, p. 3968, attribute various

Attributes	Description
cs (Explicit Relationship to Diagram Colors Part) Namespace: ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships~~ http://purl.oclc.org/ooxml/officeDocument/relationships	... This relationship shall be of type ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/diagramColors~~ http://purl.oclc.org/ooxml/officeDocument/relationships/diagramColors or the document shall be considered non-conformant. ...
dm (Explicit Relationship to Diagram Data Part) Namespace: ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships~~ http://purl.oclc.org/ooxml/officeDocument/relationships	... This relationship shall be of type ~~http://schemas.openxmlformats.org/officeDocument/2006/relationships/diagramData~~ http://purl.oclc.org/ooxml/officeDocument/relationships/diagramData or the document shall be considered non-conformant. ...

Attributes	Description
lo (Explicit Relationship to Diagram Layout Definition Part) Namespace: .../officeDocument/2006/relationships http://purl.oclc.org/ooxml/officeDocument/relationships	... This relationship shall be of type http://schemas.openxmlformats.org/officeDocument/2006/relationships/diagramLayout http://purl.oclc.org/ooxml/officeDocument/relationships/diagramLayout or the document shall be considered non-conformant. ...
qs (Explicit Relationship to Style Definition Part) Namespace: .../officeDocument/2006/relationships http://purl.oclc.org/ooxml/officeDocument/relationships	... This relationship shall be of type http://schemas.openxmlformats.org/officeDocument/2006/relationships/diagramQuickStyle http://purl.oclc.org/ooxml/officeDocument/relationships/diagramQuickStyle or the document shall be considered non-conformant. ...

299. §21.4.2.27, “shape (Shape)”, p. 3973, attribute blip

Attributes	Description
blip (Relationship to Image Part) Namespace: .../officeDocument/2006/relationships http://purl.oclc.org/ooxml/officeDocument/relationships	... This relationship shall be of type http://schemas.openxmlformats.org/officeDocument/2006/relationships/image http://purl.oclc.org/ooxml/officeDocument/relationships/image or the document shall be considered non-conformant. ...

300. §21.4.3.4, “prSet (Property Set)”, pp. 3983–3984 attributes various

Attributes	Description
custLinFactNeighborX (Neighbor Offset Width)	Specifies the percentage of the neighbor's width used for offsetting shape. The possible values for this attribute are defined by the ~~W3C XML Schema int datatype~~ST_PrSetCustVal simple type (§21.4.7.66).
custLinFactNeighborY (Neighbor Offset Height)	Specifies the percentage of the neighbor's height used for offsetting shape. The possible values for this attribute are defined by the ~~W3C XML Schema int datatype~~ST_PrSetCustVal simple type (§21.4.7.66).
custLinFactX (Custom Factor Width)	Specifies the percentage of the current shape width used for offsetting the shape. The possible values for this attribute are defined by the ~~W3C XML Schema int datatype~~ST_PrSetCustVal simple type (§21.4.7.66).
custLinFactY (Custom Factor Height)	Specifies the percentage of the current shape height used for offsetting the shape. The possible values for this attribute are defined by the ~~W3C XML Schema int datatype~~ST_PrSetCustVal simple type (§21.4.7.66).
custRadScaleInc (Include Angle Scale)	Specifies the ~~amount~~percent that the include angle has been scaled by. The possible values for this attribute are defined by the ~~W3C XML Schema int datatype~~ST_PrSetCustVal simple type (§21.4.7.66).
custRadScaleRad (Radius Scale)	Specifies ~~the percent that~~how much the radius has been scaled by. The possible values for this attribute are defined by the ~~W3C XML Schema int datatype~~ST_PrSetCustVal simple type (§21.4.7.66).
custScaleX (Width Scale)	Specifies the ~~amount~~percent that the width has been scaled by. The possible values for this attribute are defined by the ~~W3C XML Schema int datatype~~ST_PrSetCustVal simple type (§21.4.7.66).
custScaleY (Height Scale)	Specifies the ~~amount~~percent that the height has been scaled by. The possible values for this attribute are defined by the ~~W3C XML Schema int datatype~~ST_PrSetCustVal simple type (§21.4.7.66).

301. §21.4.3.7, “spPr (Shape Properties)”, p. 3988, attribute bwMode

Attributes	Description
bwMode (Black and White Mode) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...

302. §21.4.4.3, “colorsDef (Color Transform Definitions)”, p. 3991

xmlns:dgm="http://schemas.openxmlformats.org/drawingml/2006/~~3~~diagram"
 xmlns:a="http://schemas.openxmlformats.org/drawingml/2006/~~3~~main"

303. §21.4.5.6, “sp3d (3-D Shape Properties)”, pp. 4008–4009, attribute various

Attributes	Description
contourW (Contour Width) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...
extrusionH (Extrusion Height) Namespace: ~~.../drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...

Attributes	Description
prstMaterial (Preset Material Type) Namespace: ~~...~~ ~~/drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...
z (Shape Depth) Namespace: ~~...~~ ~~/drawingml/2006/main~~ http://purl.oclc.org/ooxml/drawingml/main	...

304. §21.4.5.7, “styleDef (Style Definition)”, p. 4010

xmlns:dgm="http://schemas.openxmlformats.org/drawingml/2006/~~3/~~diagram"
xmlns:a="http://schemas.openxmlformats.org/drawingml/2006/~~3/~~main"

305. §21.4.7, “Simple Types”, p. 4021

This is the complete list of simple types [dedicated to DrawingML – Diagrams](http://schemas.openxmlformats.org/drawingml/2006/diagram-namespace). ~~in the~~
~~http://schemas.openxmlformats.org/drawingml/2006/diagram-namespace.~~

306. §21.4.7.66, “ST_PrSetCustVal (Property Set Customized Value)”, new subclause

[This simple type defines customization percentage values for certain elements in DrawingML.](#)

[This simple type is a union of the following types:](#)

- [The ST_Percentage simple type \(§22.9.2.9\).](#)

Referenced By
prSet@custScaleX (§21.4.3.4); prSet@custScaleY (§21.4.3.4); prSet@custLinFactX (§21.4.3.4); prSet@custLinFactY (§21.4.3.4); prSet@custLinFactNeighborX (§21.4.3.4); prSet@custLinFactNeighborY (§21.4.3.4); prSet@custRadScaleRad (§21.4.3.4); prSet@custRadScaleInc (§21.4.3.4);

[Note: The W3C XML Schema definition of this simple type's content model (ST_PrSetCustVal) is located in §A.5.3. *end note*]

307. §22.1.3, "Simple Types", p. 4223

This is the complete list of simple types [dedicated to Math](http://schemas.openxmlformats.org/officeDocument/2006/math-namespace). *in the*
<http://schemas.openxmlformats.org/officeDocument/2006/math-namespace>.

308. §22.2, "Extended Properties", p. 4230

Extended properties are stored within an Extended File Properties part with:

- Source Relationship:
<http://schemas.openxmlformats.org/officeDocument/2006/relationships/extended-properties>
<http://purl.oclc.org/ooxml/officeDocument/relationships/extendedProperties>
- Content Type: application/vnd.openxmlformats-officedocument.extended-properties+xml

309. §22.3, "Custom Properties", p. 4240

Custom properties are represented by property elements (§22.3.2.2) stored in the Custom File Properties part with:

- Source Relationship:
<http://schemas.openxmlformats.org/officeDocument/2006/relationships/custom-properties>
<http://purl.oclc.org/ooxml/officeDocument/relationships/customProperties>
- Content Type: application/vnd.openxmlformats-officedocument.custom-properties+xml

310. §22.4.3, "Simple Types", p. 4256

This is the complete list of simple types [dedicated to Variant Types](http://schemas.openxmlformats.org/officeDocument/2006/docPropsVTypes-namespace). *in the*
<http://schemas.openxmlformats.org/officeDocument/2006/docPropsVTypes-namespace>.

311. §22.6.2.60, "sources (Sources)", p. 4300

Attributes	Description
SelectedStyle (Selected Style)	... [Example: <pre><b:Sources SelectedStyle="\APA.XSL" StyleName="APA" URI="http://schemas.openxmlformats.org/bibliographicStyle/APAhttp://purl.oclc.org/ooxml/bibliographicStyle/APA"></pre> <i>end example</i>] ...

312. §22.6.3, “Simple Types”, p. 4310

This is the complete list of simple types [dedicated to Bibliography](http://schemas.openxmlformats.org/officeDocument/2006/bibliography-namespace). ~~in the~~
~~<http://schemas.openxmlformats.org/officeDocument/2006/bibliography-namespace>~~.

313. §22.7.3, “Simple Types”, p. 4315

This is the complete list of simple types [dedicated to Additional Characteristics](http://schemas.openxmlformats.org/officeDocument/2006/characteristics-namespace). ~~in the~~
~~<http://schemas.openxmlformats.org/officeDocument/2006/characteristics-namespace>~~.

314. §22.8.2, “Simple Types”, p. 4316

This is the complete list of simple types [dedicated to Office Document Relationships](http://schemas.openxmlformats.org/officeDocument/2006/relationships-namespace). ~~in the~~
~~<http://schemas.openxmlformats.org/officeDocument/2006/relationships-namespace>~~.

315. §22.9.2, “Simple Types”, p. 4317

This is the complete list of simple types [dedicated to Shared Simple Types](http://schemas.openxmlformats.org/officeDocument/2006/sharedTypes-namespace). ~~in the~~
~~<http://schemas.openxmlformats.org/officeDocument/2006/sharedTypes-namespace>~~.

316. §A.1, "WordprocessingML", p. 4345, lines 1–18

```

<xsd:schema xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:m="http://schemas.openxmlformats.org/officeDocument/2006/mathhttp://purl.oc
  lc.org/ooxml/officeDocument/math"
  xmlns:r="http://schemas.openxmlformats.org/officeDocument/2006/relationshipshttp://
  purl.oclc.org/ooxml/officeDocument/relationships"
  xmlns:sl="http://schemas.openxmlformats.org/schemaLibrary/2006/mainhttp://purl.oc
  lc.org/ooxml/schemaLibrary/main"
  xmlns:wp="http://schemas.openxmlformats.org/drawingml/2006/wordprocessingDrawingh
  ttp://purl.oclc.org/ooxml/drawingml/wordprocessingDrawing"
  xmlns="http://schemas.openxmlformats.org/wordprocessingml/2006/mainhttp://purl.oc
  lc.org/ooxml/wordprocessingml/main"
  xmlns:s="http://schemas.openxmlformats.org/officeDocument/2006/sharedTypeshttp://
  purl.oclc.org/ooxml/officeDocument/sharedTypes" elementFormDefault="qualified"
  attributeFormDefault="qualified" blockDefault="#all"
  targetNamespace="http://schemas.openxmlformats.org/wordprocessingml/2006/mainhttp
  ://purl.oclc.org/ooxml/wordprocessingml/main">
  <xsd:import
    namespace="http://schemas.openxmlformats.org/drawingml/2006/wordprocessingDraw
    inghttp://purl.oclc.org/ooxml/drawingml/wordprocessingDrawing"
    schemaLocation="dml-wordprocessingDrawing.xsd"/>
  <xsd:import
    namespace="http://schemas.openxmlformats.org/officeDocument/2006/mathhttp://pu
    rl.oclc.org/ooxml/officeDocument/math" schemaLocation="shared-math.xsd"/>
  <xsd:import
    namespace="http://schemas.openxmlformats.org/officeDocument/2006/relationships
    http://purl.oclc.org/ooxml/officeDocument/relationships"
    schemaLocation="shared-relationshipReference.xsd"/>
  <xsd:import
    namespace="http://schemas.openxmlformats.org/officeDocument/2006/sharedTypesht
    tp://purl.oclc.org/ooxml/officeDocument/sharedTypes" schemaLocation="shared-
    commonSimpleTypes.xsd"/>
  <xsd:import
    namespace="http://schemas.openxmlformats.org/schemaLibrary/2006/mainhttp://pur
    l.oclc.org/ooxml/schemaLibrary/main" schemaLocation="shared-
    customXmlSchemaProperties.xsd"/>

```

317. §A.1, "WordprocessingML", p. 4347, lines 108–113

```

<xsd:simpleType name="ST_TextScale">
  <xsd:union memberTypes="ST_TextScalePercent"/>
  <del><xsd:restriction base="xsd:integer">
  <xsd:minInclusive value="0"/>


```

```

<xsd:maxInclusive value="600"/>
</xsd:restriction>
</xsd:simpleType>
<xsd:simpleType name="ST_TextScalePercent">
  <xsd:restriction base="xsd:string">
    <xsd:pattern value="0*(600|([0-5]?[0-9]?[0-9]))%"/>
  </xsd:restriction>
</xsd:simpleType>

```

318. §A.1, "WordprocessingML", p. 4385, lines 2143–2146

```

<xsd:simpleType name="ST_MeasurementOrPercent">
  <xsd:union memberTypes="ST_DecimalNumberOrPercent s:ST_UniversalMeasure"/>
</xsd:simpleType>
<xsd:complexType name="CT_TblWidth">
  <xsd:attribute name="w" type="ST_DecimalNumberOrPercent ST_MeasurementOrPercent"/>
  <xsd:attribute name="type" type="ST_TblWidth"/>
</xsd:complexType>

```

319. §A.1, "WordprocessingML", p. 4392, lines 2500–2506

```

<xsd:complexType name="CT_RecipientData">
  <xsd:sequence>
    <xsd:element name="active" type="CT_OnOff" minOccurs="0"/>
    <xsd:element name="column" type="CT_DecimalNumber" minOccurs="1"/>
    <xsd:element name="uniqueTag" type="xsd:base64Binary CT_Base64Binary"
      minOccurs="1"/>
  </xsd:sequence>
</xsd:complexType>
<xsd:complexType name="CT_Base64Binary">
  <xsd:attribute name="val" type="xsd:base64Binary" use="required">
  </xsd:attribute>
</xsd:complexType>

```

320. §A.2, “SpreadsheetML”, p. 4410, lines 1–13

```

<xsd:schema xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns="http://schemas.openxmlformats.org/spreadsheetml/2006/main" http://purl.oclc.org/ooxml/spreadsheetml/main"
  xmlns:r="http://schemas.openxmlformats.org/officeDocument/2006/relationships" http://purl.oclc.org/ooxml/officeDocument/relationships"
  xmlns:xdr="http://schemas.openxmlformats.org/drawingml/2006/spreadsheetDrawing" http://purl.oclc.org/ooxml/drawingml/spreadsheetDrawing"
  xmlns:s="http://schemas.openxmlformats.org/officeDocument/2006/sharedTypes" http://purl.oclc.org/ooxml/officeDocument/sharedTypes"
  targetNamespace="http://schemas.openxmlformats.org/spreadsheetml/2006/main" http://purl.oclc.org/ooxml/spreadsheetml/main" elementFormDefault="qualified">
  <xsd:import
    namespace="http://schemas.openxmlformats.org/officeDocument/2006/relationships" http://purl.oclc.org/ooxml/officeDocument/relationships"
    schemaLocation="shared-relationshipReference.xsd"/>
  <xsd:import id="s"
    namespace="http://schemas.openxmlformats.org/officeDocument/2006/sharedTypes" http://purl.oclc.org/ooxml/officeDocument/sharedTypes" schemaLocation="shared-commonSimpleTypes.xsd"/>
  <xsd:import id="xdr"
    namespace="http://schemas.openxmlformats.org/drawingml/2006/spreadsheetDrawing" http://purl.oclc.org/ooxml/drawingml/spreadsheetDrawing" schemaLocation="dml-spreadsheetDrawing.xsd"/>

```

321. §A.2, “SpreadsheetML”, pp. 4481–4482, lines 3792–3811

```

<xsd:complexType name="CT_Font">
  <xsd:choice maxOccurs="unbounded">
    ...
    <xsd:element name="family" type="CT_IntPropertyCT_FontFamily" minOccurs="0" maxOccurs="1"/>
    ...
  </xsd:choice>
</xsd:complexType>

```

322. §A.2, “SpreadsheetML”, new type

```

<xsd:complexType name="CT_FontFamily">
  <xsd:attribute name="val" type="ST_FontFamily" use="required"/>
</xsd:complexType>

<xsd:simpleType name="ST_FontFamily">

```

```

<xsd:restriction base="xsd:integer">
  <xsd:minInclusive value="0"/>
  <xsd:maxInclusive value="14"/>
</xsd:restriction>
</xsd:simpleType>

```

323. §A.3, "PresentationML", p. 4494, lines 1–13

```

<xsd:schema xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns="http://schemas.openxmlformats.org/presentationml/2006/mainhttp://purl.oclc.org/ooxml/presentationml/main"
  xmlns:p="http://schemas.openxmlformats.org/presentationml/2006/mainhttp://purl.oclc.org/ooxml/presentationml/main"
  xmlns:a="http://schemas.openxmlformats.org/drawingml/2006/mainhttp://purl.oclc.org/ooxml/drawingml/main"
  xmlns:r="http://schemas.openxmlformats.org/officeDocument/2006/relationshipshttp://purl.oclc.org/ooxml/officeDocument/relationships"
  xmlns:s="http://schemas.openxmlformats.org/officeDocument/2006/sharedTypeshttp://purl.oclc.org/ooxml/officeDocument/sharedTypes" elementFormDefault="qualified"
  targetNamespace="http://schemas.openxmlformats.org/presentationml/2006/mainhttp://purl.oclc.org/ooxml/presentationml/main">
  <xsd:import
    namespace="http://schemas.openxmlformats.org/officeDocument/2006/relationshipshttp://purl.oclc.org/ooxml/officeDocument/relationships"
    schemaLocation="shared-relationshipReference.xsd"/>
  <xsd:import
    namespace="http://schemas.openxmlformats.org/drawingml/2006/mainhttp://purl.oclc.org/ooxml/drawingml/main" schemaLocation="dml-main.xsd"/>
  <xsd:import id="s"
    namespace="http://schemas.openxmlformats.org/officeDocument/2006/sharedTypeshttp://purl.oclc.org/ooxml/officeDocument/sharedTypes" schemaLocation="shared-commonSimpleTypes.xsd"/>

```

324. §A.3, "PresentationML", p. 4508, lines 768–773

```

<xsd:complexType name="CT_Extension">
  <xsd:sequence>
    <xsd:any processContents="lax" minOccurs="0" maxOccurs="unbounded"/>
  </xsd:sequence>
  <xsd:attribute name="uri" type="xsd:token" use="required"/>
</xsd:complexType>

```

325. §A.3, "PresentationML", p. 4510, lines 849–857

```

<xsd:complexType name="CT_OleObject">
  <xsd:sequence>
    <xsd:choice minOccurs="1" maxOccurs="1">
      <xsd:element name="embed" type="CT_OleObjectEmbed"/>
      <xsd:element name="link" type="CT_OleObjectLink"/>
      <xsd:element name="pic" type="CT_Picture"/>
    </xsd:choice>
    <xsd:element name="pic" type="CT Picture" minOccurs="1" maxOccurs="1"/>
  </xsd:sequence>
  <xsd:attributeGroup ref="AG_Ole"/>
  <xsd:attribute name="progId" type="xsd:string" use="optional"/>
</xsd:complexType>

```

326. §A.3, "PresentationML", p. 4522, lines 1505–1508

```

<xsd:complexType name="CT_StringTag">
  <xsd:attribute name="name" type="xsd:string" use="required"/>
  <xsd:attribute name="val" type="xsd:string" use="required"/>
</xsd:complexType>

```

327. §A.4.1, "DrawingML – Main", p. 4525, lines 1–20

```

<xsd:schema xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:r="http://schemas.openxmlformats.org/officeDocument/2006/relationshipshttp://purl.oclc.org/ooxml/officeDocument/relationships"
  xmlns:s="http://schemas.openxmlformats.org/officeDocument/2006/sharedTypeshttp://purl.oclc.org/ooxml/officeDocument/sharedTypes"
  xmlns="http://schemas.openxmlformats.org/drawingml/2006/main" http://purl.oclc.org/ooxml/drawingml/main"
  targetNamespace="http://schemas.openxmlformats.org/drawingml/2006/mainhttp://purl.oclc.org/ooxml/drawingml/main" elementFormDefault="qualified">
  <xsd:import
    namespace="http://schemas.openxmlformats.org/officeDocument/2006/relationshipshttp://purl.oclc.org/ooxml/officeDocument/relationships"
    schemaLocation="shared-relationshipReference.xsd"/>
  <xsd:import
    namespace="http://schemas.openxmlformats.org/officeDocument/2006/sharedTypeshttp://purl.oclc.org/ooxml/officeDocument/sharedTypes" schemaLocation="shared-commonSimpleTypes.xsd"/>
  <xsd:import
    namespace="http://schemas.openxmlformats.org/drawingml/2006/diagramhttp://purl.oclc.org/ooxml/drawingml/diagram" schemaLocation="dml-diagram.xsd"/>

```

```
<xsd:import
  namespace="http://schemas.openxmlformats.org/drawingml/2006/charthttp://purl.oclc.org/ooxml/drawingml/chart" schemaLocation="dml-chart.xsd"/>
<xsd:import
  namespace="http://schemas.openxmlformats.org/drawingml/2006/picturehttp://purl.oclc.org/ooxml/drawingml/picture" schemaLocation="dml-picture.xsd"/>
<xsd:import
  namespace="http://schemas.openxmlformats.org/drawingml/2006/compatibility"
  schemaLocation="dml-compatibility.xsd"/> [Deleted by ISO/IEC 29500-1:2008/Cor.1:2010]
<xsd:import
  namespace="http://schemas.openxmlformats.org/drawingml/2006/lockedCanvashttp://purl.oclc.org/ooxml/drawingml/lockedCanvas" schemaLocation="dml-lockedCanvas.xsd"/>
```

328. §A.4.1, "DrawingML - Main", p. 4528, lines 184–189

```
<xsd:complexType name="CT_OfficeArtExtension">
  <xsd:sequence>
    <xsd:any processContents="lax" minOccurs="0" maxOccurs="unbounded"/>
  </xsd:sequence>
  <xsd:attribute name="uri" type="xsd:token" use="required"/>
</xsd:complexType>
```

329. §A.4.1, "DrawingML - Main", p. 4529, lines 240–242

```
<xsd:simpleType name="ST_PercentageDecimal">
  <xsd:restriction base="xsd:int"/>
</xsd:simpleType>
```

330. §A.4.1, "DrawingML - Main", p. 4536, lines 597–602

```
<xsd:complexType name="CT_PresetColor">
  <xsd:sequence>
    <xsd:group ref="EG_ColorTransform" minOccurs="0" maxOccurs="unbounded"/>
  </xsd:sequence>
  <xsd:attribute name="val" type="ST_PresetColorVal" use="required"/>
</xsd:complexType>
```

331. §A.4.1, “DrawingML - Main”, p. 4541, lines 835–840

```

<xsd:complexType name="CT_GraphicalObjectData">
  <xsd:sequence>
    <xsd:any minOccurs="0" maxOccurs="unbounded" processContents="strict"/>
  </xsd:sequence>
  <xsd:attribute name="uri" type="xsd:token" use="required"/>
</xsd:complexType>

```

332. §A.4.1, “DrawingML - Main”, p. 4555, lines 1617–1619

```

<xsd:complexType name="CT_EffectReference">
  <xsd:attribute name="ref" type="xsd:token" use="required"/>
</xsd:complexType>

```

333. §A.4.1, “DrawingML - Main”, p. 4577, lines 2742–2747

```

<xsd:simpleType name="ST_TextBulletSize">
  <xsd:union memberTypes="ST_TextBulletSizePercent"/>
</xsd:simpleType>
<xsd:simpleType name="ST_TextBulletSizePercent">
  <xsd:restriction base="ST_PercentageDecimal">
  <xsd:minInclusive value="25000"/>
  <xsd:maxInclusive value="400000"/>
  </xsd:restriction>
  <xsd:restriction base="xsd:string">
    <xsd:pattern value="0*(([2-9]|([3-9][0-9])|([1-3][0-9][0-9])|400)%"/>
  </xsd:restriction>
</xsd:simpleType>

```

334. §A.4.1, “DrawingML - Main”, p. 4577, lines 2749–2751

```

<xsd:complexType name="CT_TextBulletSizePercent">
  <xsd:attribute name="val" type="ST_TextBulletSizePercent" use="required"/>
</xsd:complexType>

```

335. §A.4.1, “DrawingML - Main”, p. 4577, lines 2752–2754

```

<xsd:complexType name="CT_TextBulletSizePoint">
  <xsd:attribute name="val" type="ST_TextFontSize" use="required"/>
</xsd:complexType>

```

336. §A.4.1, “DrawingML - Main”, p. 4578, lines 2814–2819

```
<xsd:complexType name="CT_TextFont">
  <xsd:attribute name="typeface" type="ST_TextTypeface" use="required"/>
  ...
</xsd:complexType>
```

337. §A.4.2, “DrawingML - Picture”, p. 4582, lines 1–6

```
<xsd:schema xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns="http://schemas.openxmlformats.org/drawingml/2006/picturehttp://purl.oclc.org/ooxml/drawingml/picture"
  xmlns:a="http://schemas.openxmlformats.org/drawingml/2006/mainhttp://purl.oclc.org/ooxml/drawingml/main" elementFormDefault="qualified"
  targetNamespace="http://schemas.openxmlformats.org/drawingml/2006/picturehttp://purl.oclc.org/ooxml/drawingml/picture">
  <xsd:import
    namespace="http://schemas.openxmlformats.org/drawingml/2006/mainhttp://purl.oclc.org/ooxml/drawingml/main" schemaLocation="dml-main.xsd"/>
```

338. §A.4.3, “DrawingML - Locked Canvas”, p. 4583, lines 1–10

```
<xsd:schema xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns="http://schemas.openxmlformats.org/drawingml/2006/lockedCanvashttp://purl.oclc.org/ooxml/drawingml/lockedCanvas"
  xmlns:a="http://schemas.openxmlformats.org/drawingml/2006/mainhttp://purl.oclc.org/ooxml/drawingml/main"
  xmlns:r="http://schemas.openxmlformats.org/officeDocument/2006/relationshipshttp://purl.oclc.org/ooxml/officeDocument/relationships"
  elementFormDefault="qualified"
  targetNamespace="http://schemas.openxmlformats.org/drawingml/2006/lockedCanvashttp://purl.oclc.org/ooxml/drawingml/lockedCanvas">
  <xsd:import
    namespace="http://schemas.openxmlformats.org/drawingml/2006/mainhttp://purl.oclc.org/ooxml/drawingml/main" schemaLocation="dml-main.xsd"/>
  <xsd:element name="lockedCanvas" type="a:CT_GvmlGroupShape"/>
</xsd:schema>
```

339. §A.4.4, “DrawingML – WordprocessingML Drawing”, p. 4583, lines 1–10

```

<xsd:schema xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:a="http://schemas.openxmlformats.org/drawingml/2006/mainhttp://purl.oclc.org/ooxml/drawingml/main"
  xmlns:w="http://schemas.openxmlformats.org/wordprocessingml/2006/mainhttp://purl.oclc.org/ooxml/wordprocessingml/main"
  xmlns="http://schemas.openxmlformats.org/drawingml/2006/wordprocessingDrawinghttp://purl.oclc.org/ooxml/drawingml/wordprocessingDrawing"
  targetNamespace="http://schemas.openxmlformats.org/drawingml/2006/wordprocessingDrawinghttp://purl.oclc.org/ooxml/drawingml/wordprocessingDrawing"
  elementFormDefault="qualified">
  <xsd:import
    namespace="http://schemas.openxmlformats.org/drawingml/2006/mainhttp://purl.oclc.org/ooxml/drawingml/main" schemaLocation="dml-main.xsd"/>
  <xsd:import schemaLocation="wml.xsd"
    namespace="http://schemas.openxmlformats.org/wordprocessingml/2006/mainhttp://purl.oclc.org/ooxml/wordprocessingml/main"/>

```

340. §A.4.5, “DrawingML – SpreadsheetML Drawing”, p. 4587, lines 1–10

```

<xsd:schema xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:a="http://schemas.openxmlformats.org/drawingml/2006/mainhttp://purl.oclc.org/ooxml/drawingml/main"
  xmlns="http://schemas.openxmlformats.org/drawingml/2006/spreadsheetDrawinghttp://purl.oclc.org/ooxml/drawingml/spreadsheetDrawing"
  xmlns:r="http://schemas.openxmlformats.org/officeDocument/2006/relationshipshttp://purl.oclc.org/ooxml/officeDocument/relationships"
  targetNamespace="http://schemas.openxmlformats.org/drawingml/2006/spreadsheetDrawinghttp://purl.oclc.org/ooxml/drawingml/spreadsheetDrawing"
  elementFormDefault="qualified">
  <xsd:import
    namespace="http://schemas.openxmlformats.org/drawingml/2006/mainhttp://purl.oclc.org/ooxml/drawingml/main" schemaLocation="dml-main.xsd"/>
  <xsd:import schemaLocation="shared-relationshipReference.xsd"
    namespace="http://schemas.openxmlformats.org/officeDocument/2006/relationshipshttp://purl.oclc.org/ooxml/officeDocument/relationships"/>

```

341. §A.5.1, “DrawingML – Charts”, p. 4590, lines 1–16

```

<xsd:schema xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:a="http://schemas.openxmlformats.org/drawingml/2006/mainhttp://purl.oclc.org/ooxml/drawingml/main"
  xmlns:r="http://schemas.openxmlformats.org/officeDocument/2006/relationshipshttp://purl.oclc.org/ooxml/officeDocument/relationships"
  xmlns="http://schemas.openxmlformats.org/drawingml/2006/charthttp://purl.oclc.org/ooxml/drawingml/chart"
  xmlns:cdr="http://schemas.openxmlformats.org/drawingml/2006/chartDrawinghttp://purl.oclc.org/ooxml/drawingml/chartDrawing"
  xmlns:s="http://schemas.openxmlformats.org/officeDocument/2006/sharedTypeshttp://purl.oclc.org/ooxml/officeDocument/sharedTypes"
  targetNamespace="http://schemas.openxmlformats.org/drawingml/2006/charthttp://purl.oclc.org/ooxml/drawingml/chart" elementFormDefault="qualified"
  attributeFormDefault="unqualified" blockDefault="#all">
  <xsd:import
    namespace="http://schemas.openxmlformats.org/officeDocument/2006/relationshipshttp://purl.oclc.org/ooxml/officeDocument/relationships"
    schemaLocation="shared-relationshipReference.xsd"/>
  <xsd:import
    namespace="http://schemas.openxmlformats.org/drawingml/2006/mainhttp://purl.oclc.org/ooxml/drawingml/main" schemaLocation="dml-main.xsd"/>
  <xsd:import
    namespace="http://schemas.openxmlformats.org/drawingml/2006/chartDrawinghttp://purl.oclc.org/ooxml/drawingml/chartDrawing" schemaLocation="dml-chartDrawing.xsd"/>
  <xsd:import
    namespace="http://schemas.openxmlformats.org/officeDocument/2006/sharedTypeshttp://purl.oclc.org/ooxml/officeDocument/sharedTypes" schemaLocation="shared-commonSimpleTypes.xsd"/>

```

342. §A.5.1, “DrawingML - Charts”, p. 4594, lines 198–206

```

<xsd:simpleType name="ST_HPercent">
<xsd:restriction base="xsd:unsignedShort">
<xsd:minInclusive value="5"/>
<xsd:maxInclusive value="500"/>
</xsd:restriction>
  <xsd:union memberTypes="ST_HPercentWithSymbol"/>
</xsd:simpleType>

<xsd:simpleType name="ST_HPercentWithSymbol">
  <xsd:pattern value="0*([5-9]|([1-9][0-9])|([1-4][0-9][0-9])|500)%"/>

```

```
</xsd:simpleType>
```

```
<xsd:complexType name="CT_HPercent">
  <xsd:attribute name="val" type="ST_HPercent" default="100%"/>
</xsd:complexType>
```

343. §A.5.1, "DrawingML - Charts", p. 4594, lines 216–224

```
<xsd:simpleType name="ST_DepthPercent">
— <xsd:restriction base="xsd:unsignedShort">
— <xsd:minInclusive value="20"/>
— <xsd:maxInclusive value="2000"/>
— </xsd:restriction>
  <xsd:union memberTypes="ST_DepthPercentWithSymbol"/>
</xsd:simpleType>

<xsd:simpleType name="ST_DepthPercentWithSymbol">
  <xsd:restriction base="xsd:string">
    <xsd:pattern value="0*(([2-9][0-9])|([1-9][0-9][0-9])|(1[0-9][0-9][0-9])|2000)%"/>
  </xsd:restriction>
</xsd:simpleType>

<xsd:complexType name="CT_DepthPercent">
  <xsd:attribute name="val" type="ST_DepthPercent" default="100%"/>
</xsd:complexType>
```

344. §A.5.1, "DrawingML - Charts", p. 4594, lines 225–233

```
<xsd:simpleType name="ST_Perspective">
— <xsd:restriction base="xsd:unsignedByte">
— <xsd:minInclusive value="0"/>
— <xsd:maxInclusive value="240"/>
— </xsd:restriction>
  <xsd:union memberTypes="ST_PerspectivePercent"/>
</xsd:simpleType>

<xsd:simpleType name="ST_PerspectivePercent">
  <xsd:restriction base="xsd:string">
    <xsd:pattern value="0*(([0-9])|([1-9][0-9])|(1[0-9][0-9])|(2[0-3][0-9])|240)%"/>
  </xsd:restriction>
</xsd:simpleType>
```