

INTERNATIONAL STANDARD

ISO/IEC
8613-10

First edition
1991-06-01

AMENDMENT 2
1991-12-15

Information processing — Text and office systems — Office Document Architecture (ODA) and interchange format —

Part 10: Formal specifications

AMENDMENT 2: Formal specification of the Raster Graphics content architectures

*Traitement de l'information — Bureautique — Architecture des documents de
bureau (ODA) et format d'échange —*

Partie 10: Spécifications formelles

*AMENDEMENT 2: Spécification formelle de l'architecture des contenus des
caractères graphiques à raster*



Reference number
ISO/IEC 8613-10 : 1991/Amd.2 : 1991 (E)

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Amendment 2 to International Standard ISO/IEC 8613-10 : 1991 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*.

**Information processing — Text and office systems —
Office Document Architecture (ODA) and interchange
format —**

Part 10:
Formal specifications

**AMENDMENT 2: Formal specification of the Raster Graphics
content architectures**

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 8613-10:1991/Amd 2:1991

Annex D

(normative)

Formal specification of the raster graphics content architectures

D.1 Introduction

This annex gives a formal specification of the raster graphics content architectures as described in part 7 of ISO 8613. This annex is composed of 5 clauses:

Clause D.1 provides a general introduction, including a list of all definitions which are given in clauses D.2, D.3 and D.4

Clause D.2 provides the interface to the document profile and its formal specification.

Clauses D.3 and D.4 provide the interface to the document architecture by giving a formal specification of raster graphics presentation attributes and content portion attributes that apply to raster graphics content portions.

Clause D.5 is an index to the terms (definitions, operators, attribute names) used in clauses D.2, D.3 and D.4.

At any time a clause number is specified in the semi-formal descriptions this refers to a clause number in ISO 8613-7.

What follows is the outline of the formula which specifies the raster graphics content architecture. The dots indicate formal text fragments which have been left out for the sake of readability. The full formula can be obtained by replacing each line (apart from the *and*) with the definition which is referenced by the superscript of the predicate symbol or operator symbol, respectively. The variables used in the definition of the predicate have to be replaced by those appearing in the outline (if they are different).

NOTE — A definition is a formula, hence it may never yield an undefined result, whatever value has been inserted for the variable.

... IsDefaultableRasterGraphicsContentArchitectureAttribute^{7.1}(*att*) ...
and ... IsRasterGraphicsCodingSpecification^{7.2}(*v*) ...
and ... IsRasterGraphicsPresentationFeature^{7.3}(*v*) ...
and ... SatisfiesRasterGraphicsContentArchitectureConstraints^{7.4}(*prof*, *doby*) ...
and ... IsFormattedProcessableRasterGraphicsContent^{7.5}(*cont*) ...
and ... IsFormattedRasterGraphicsContent^{7.6}(*cont*) ...
and ... IsRasterGraphicsContentPortionDescription^{7.7}(*cont*) ...
and ... IsRasterGraphicsContentPresentationAttribute^{7.8}(*att*) ...
and ... IsRasterGraphicsContentCodingAttribute^{7.9}(*att*) ...
and ... IsRasterGraphicsContentPortionAttributeSet^{7.10}(*as*) ...
and ... IsClippingValue^{7.11}(*v*) ...
and ... IsRasterGraphicsLineProgressionValue^{7.12}(*v*) ...
and ... IsPelPathValue^{7.13}(*v*) ...
and ... IsRasterGraphicsInitialOffsetValue^{7.14}(*v*) ...
and ... IsPelTransmissionDensityValue^{7.15}(*v*) ...
and ... IsImageDimensionsValue^{7.16}(*v*) ...
and ... IsPelSpacingValue^{7.17}(*v*) ...
and ... IsSpacingRatioValue^{7.18}(*v*) ...
and ... IsRasterGraphicsContentArchitectureClassValue^{7.19}(*v*) ...
and ... IsRasterGraphicsContentTypeOfCodingValue^{7.20}(*v*) ...
and ... IsCompressionValue^{7.21}(*v*) ...
and ... IsNumberOfLinesValue^{7.22}(*v*) ...
and ... IsNumberOfPelsPerLineValue^{7.23}(*v*) ...
and ... IsNumberOfDiscardedPelsValue^{7.24}(*v*) ...
and ... IsRasterGraphicsContentInformationValue^{7.25}(*v*) ...

and ... IsNumberOfLinesPerTileValue^{7.26}(*v*) ...
and ... IsNumberOfPelsPerTileLineValue^{7.27}(*v*) ...
and ... IsTilingOffsetValue^{7.28}(*v*) ...
and ... IsTileTypesValue^{7.29}(*v*) ...
and ... IsTileEncodingValue^{7.30}(*v*) ...

NOTE — Other predicates or operators which are used here, but are defined in clause 6, are not listed here.

D.2 Interface to the Document Profile

Semiformal Description 7.1

Predicate "is a defaultable raster graphics content architecture attribute"

A defaultable raster graphics content architecture attribute is one of the attributes 'clipping', 'compression', 'image dimensions', 'initial offset', 'line progression', 'number of discarded pels', 'number of lines per tile', 'number of pels per line', 'number of pels per tile line', 'pel path', 'pel spacing', 'pel transmission density', 'spacing ratio', 'tile types', 'tiling offset' or 'type of coding' with an appropriate value.

NOTE — This predicate is used in annex B.

Definition 7.1

```

1   $\forall att$ 
2  (0IsDefaultableRasterGraphicsContentArchitectureAttribute(att) iff
3     $\exists n, c$ 
4    (1att = [n : c] and
5      n ∈ ['clipping'; 'compression';
6        'image dimensions'; 'initial offset';
7        'line progression'; 'number of discarded pels';
8        'number of lines per tile'; 'number of pels per line';
9        'number of pels per tile line'; 'pel path';
10       'pel spacing'; 'pel transmission density';
11       'spacing ratio'; 'tile types';
12       'tiling offset'; 'type of coding'] and
13      (2n = 'clipping' impl IsClippingValue7.11(c) 2) and
14      (3n = 'compression' impl IsCompressionValue7.21(c) 3) and
15      (4n = 'image dimensions' impl IsImageDimensionsValue7.16(c) 4) and
16      (5n = 'initial offset' impl IsRasterGraphicsInitialOffsetValue7.14(c) 5) and
17      (6n = 'line progression' impl IsRasterGraphicsLineProgressionValue7.12(c) 6) and
18      (7n = 'number of discarded pels' impl IsNumberOfDiscardedPelsValue7.24(c) 7) and
19      (8n = 'number of lines per tile' impl IsNumberOfLinesPerTileValue7.26(c) 8) and
20      (9n = 'number of pels per line' impl IsNumberOfPelsPerLineValue7.23(c) 9) and
21      (10n = 'number of pels per tile line' impl IsNumberOfPelsPerTileLineValue7.27(c) 10) and
22      (11n = 'pel path' impl IsPelPathValue7.13(c) 11) and
23      (12n = 'pel spacing' impl IsPelSpacingValue7.17(c) 12) and
24      (13n = 'pel transmission density' impl IsPelTransmissionDensityValue7.15(c) 13) and
25      (14n = 'spacing ratio' impl IsSpacingRatioValue7.18(c) 14) and
26      (15n = 'tile types' impl IsTileTypesValue7.29(c) 15) and
27      (16n = 'tiling offset' impl IsTilingOffsetValue7.28(c) 16) and
28      (17n = 'type of coding' impl IsRasterGraphicsContentTypeOfCodingValue7.20(c) 17) 0)

```

Semi-formal Description 7.2

Predicate "is a raster graphics coding specification"

A raster graphics coding specification is a nomination where each element is a raster graphics content coding attribute.

NOTE — This predicate is used in annex B.

Definition 7.2

- 1 $\forall v$
- 2 $(\text{IsRasterGraphicsCodingSpecification}(v) \text{ iff}$
- 3 $(\text{IsNom}(v) \text{ and}$
- 4 $\forall b \in \sim v. (\text{IsRasterGraphicsContentCodingAttribute}^{7.9}(C\ b)) \text{)})$

Semi-formal Description 7.3

Predicate "is a raster graphics presentation feature"

A raster graphics presentation feature is a nomination where each element is a raster graphics content presentation attribute.

NOTE — This predicate is used in annex B.

Definition 7.3

- 1 $\forall v$
- 2 $(\text{IsRasterGraphicsPresentationFeature}(v) \text{ iff}$
- 3 $(\text{IsNom}(v) \text{ and}$
- 4 $\forall b \in \sim v. (\text{IsRasterGraphicsContentPresentationAttribute}^{7.8}(C\ b)) \text{)})$

D.3 Interface to the Document Architecture

Semi-formal Description 7.4

Predicate "satisfies raster graphics content architecture constraints"

A document profile *prof* and a document body *doby* satisfy the constraints imposed by the raster graphics content architecture if the following holds:

For all constituents for which the attribute 'content architecture class' is specified and has the value '2 8 2 7 2' (4), the content portion is a formatted processable raster graphics content portion (5).

For all constituents for which the attribute 'content architecture class' is specified and has the value '2 8 2 7 0' (6), the content portion is a formatted raster graphics content portion (7).

The value '2 8 2 7 2' appears in the document profile attribute 'content architecture classes' if and only if there exists a content portion for which the attribute 'content architecture class' has also this value (8, 9).

The value '2 8 2 7 0' appears in the document profile attribute 'content architecture classes' if and only if there exists a content portion for which the attribute 'content architecture class' has also this value (10, 11).

NOTE — This predicate is used in clause 7 of this part of ISO 8613.

Definition 7.4

- 1 $\forall prof, doby$
- 2 $({}_0 \text{SatisfiesRasterGraphicsContentArchitectureConstraints}(prof, doby) \text{ iff}$
- 3 $\forall cont \in doby$
- 4 $({}_1 ({}_2 C \wedge cont \bullet 'content architecture class' = '2 8 2 7 2' \text{ impl}$
- 5 $\text{IsFormattedProcessableRasterGraphicsContent}^{7.5}(cont)_2) \text{ and}$
- 6 $({}_3 C \wedge cont \bullet 'content architecture class' = '2 8 2 7 0' \text{ impl}$
- 7 $\text{IsFormattedRasterGraphicsContent}^{7.6}(cont)_3)_1) \text{ and}$
- 8 $'2 8 2 7 2' \in C \wedge prof \bullet 'content architecture classes' \text{ iff}$
- 9 $\exists cont \in doby (C \wedge cont \bullet 'content architecture class' = '2 8 2 7 2') \text{ and}$
- 10 $'2 8 2 7 0' \in C \wedge prof \bullet 'content architecture classes' \text{ iff}$
- 11 $\exists cont \in doby (C \wedge cont \bullet 'content architecture class' = '2 8 2 7 0') {}_0)$

Semiformal Description 7.5

Predicate "is formatted processable raster graphics content"

A formatted processable raster graphics content portion is a raster graphics content portion description. The attribute 'number of pels per line' is explicitly specified and the attribute 'number of discarded pels' is not specified.

Definition 7.5

- 1 $\forall cont$
- 2 $({}_0 \text{IsFormattedProcessableRasterGraphicsContent}(cont) \text{ iff}$
- 3 $({}_1 \text{IsRasterGraphicsContentPortionDescription}^{7.7}(cont) \text{ and}$
- 4 $\text{not IsPlaceholder}^{1.19}(C \wedge cont \bullet 'number of pels per line') \text{ and}$
- 5 $\text{not 'number of discarded pels' } \in \text{NAMS}^{1.18}(cont)_1)_0)$

Semiformal Description 7.6

Predicate "is formatted raster graphics content"

A formatted raster graphics content portion is a raster graphics content portion description. The attributes 'number of lines', 'number of lines per tile', 'number of pels per tile line', 'tile types' and 'tiling offset' are not specified.

Definition 7.6

- 1 $\forall cont$
- 2 $({}_0 \text{IsFormattedRasterGraphicsContent}(cont) \text{ iff}$
- 3 $({}_1 \text{IsRasterGraphicsContentPortionDescription}^{7.7}(cont) \text{ and}$
- 4 $['number of lines'; 'number of lines per tile'; 'number of pels per tile line';$
- 5 $'tile types'; 'tiling offset'] \cap \text{NAMS}^{1.18}(cont) = [:]_1)_0)$

Semiformal Description 7.7

Predicate "is a raster graphics content portion description" (clause 7)

A raster graphics content portion description is a set of raster graphics content portion attributes, which are 'compression', 'content information', 'number of discarded pels', 'number of lines', 'number of lines per tile', 'number of pels per line', 'number of pels per tile line', 'tile types', 'tiling offset' and 'type of coding' (6–10). The attributes 'compression', 'content information', 'number of pels per line' and 'type of coding' must be present (4, 5). If the value of the attribute 'type of coding' is '2 8 3 7 5' (tiled encoding), the attributes 'number of lines per tile', 'number of pels per tile line', 'tile types' and 'tiling offset' must also be specified (11–13). If the attribute 'tiling offset' is specified, the first component of the value of this attribute must be less than the value of the attribute 'number of pels per tile line' and the last (second) component must be less than the value of the attribute 'number of lines per tile' (14–16).

NOTE — This predicate is used in clause 7 of this part of ISO 8613.

Definition 7.7

1 $\forall cont$
 2 $(\text{IsRasterGraphicsContentPortionDescription}(cont) \text{ iff}$
 3 $(\text{IsRasterGraphicsContentPortionAttributeSet}^{7,10}(cont) \text{ and}$
 4 $\text{NAMS}^{1,18}(cont) \supseteq [\text{'compression'}; \text{'content information'};$
 5 $\text{'number of pels per line'}; \text{'type of coding'}] \text{ and}$
 6 $\text{NAMS}^{1,18}(cont) \subseteq [\text{'compression'}; \text{'content information'};$
 7 $\text{'number of discarded pels'}; \text{'number of lines'};$
 8 $\text{'number of lines per tile'}; \text{'number of pels per line'};$
 9 $\text{'number of pels per tile line'}; \text{'tile types'};$
 10 $\text{'tiling offset'}; \text{'type of coding'}] \text{ and}$
 11 $(C \sim cont \cdot \text{'type of coding'} = \text{'2 8 3 7 5'} \text{ impl}$
 12 $\text{NAMS}^{1,18}(cont) \supseteq$
 13 $[\text{'number of lines per tile'}; \text{'number of pels per tile line'}; \text{'tile types'}; \text{'tiling offset'}]_2) \text{ and}$
 14 $(\text{'tiling offset'} \in \text{NAMS}^{1,18}(cont) \text{ impl}$
 15 $(\text{HEAD}^{1,13}(C \sim cont \cdot \text{'tiling offset'}) < C \sim cont \cdot \text{'number of pels per tile line'} \text{ and}$
 16 $\text{LASTC}^{1,14}(C \sim cont \cdot \text{'tiling offset'}) < C \sim cont \cdot \text{'number of lines per tile'}_4)_3)_1)_0)$

Semiformal Description 7.8

Predicate "is a raster graphics content presentation attribute" (clause 6)

A raster graphics content presentation attribute is one of the attributes 'clipping', 'image dimensions', 'initial offset', 'line progression', 'pel path', 'pel spacing', 'pel transmission density' or 'spacing ratio' with an appropriate value.

NOTE — This predicate is used in clause 7 of this part of ISO 8613.

Definition 7.8

1 $\forall att$
2 $(\text{IsRasterGraphicsContentPresentationAttribute}(att) \text{ iff}$
3 $\exists n, c$
4 $(\text{att} = [n : c] \text{ and}$
5 $n \in ['clipping'; \text{'image dimensions'};$
6 $\text{'initial offset'}; \text{'line progression'};$
7 $\text{'pel path'}; \text{'pel spacing'};$
8 $\text{'pel transmission density'}; \text{'spacing ratio'}] \text{ and}$
9 $(\text{ }_2 n = \text{'clipping'} \text{ impl}$
10 $(\text{ }_3 \text{IsPlaceholder}^{1.19}(c) \text{ or } \text{IsClippingValue}^{7.11}(c) \text{ }_3 \text{ }_2) \text{ and}$
11 $(\text{ }_4 n = \text{'image dimensions'} \text{ impl}$
12 $(\text{ }_5 \text{IsPlaceholder}^{1.19}(c) \text{ or } \text{IsImageDimensionsValue}^{7.16}(c) \text{ }_5 \text{ }_4) \text{ and}$
13 $(\text{ }_6 n = \text{'initial offset'} \text{ impl}$
14 $(\text{ }_7 \text{IsPlaceholder}^{1.19}(c) \text{ or } \text{IsRasterGraphicsInitialOffsetValue}^{7.14}(c) \text{ }_7 \text{ }_6) \text{ and}$
15 $(\text{ }_8 n = \text{'line progression'} \text{ impl}$
16 $(\text{ }_9 \text{IsPlaceholder}^{1.19}(c) \text{ or } \text{IsRasterGraphicsLineProgressionValue}^{7.12}(c) \text{ }_9 \text{ }_8) \text{ and}$
17 $(\text{ }_{10} n = \text{'pel path'} \text{ impl}$
18 $(\text{ }_{11} \text{IsPlaceholder}^{1.19}(c) \text{ or } \text{IsPelPathValue}^{7.13}(c) \text{ }_{11} \text{ }_{10}) \text{ and}$
19 $(\text{ }_{12} n = \text{'pel spacing'} \text{ impl}$
20 $(\text{ }_{13} \text{IsPlaceholder}^{1.19}(c) \text{ or } \text{IsPelSpacingValue}^{7.17}(c) \text{ }_{13} \text{ }_{12}) \text{ and}$
21 $(\text{ }_{14} n = \text{'pel transmission density'} \text{ impl}$
22 $(\text{ }_{15} \text{IsPlaceholder}^{1.19}(c) \text{ or } \text{IsPelTransmissionDensityValue}^{7.15}(c) \text{ }_{15} \text{ }_{14}) \text{ and}$
23 $(\text{ }_{16} n = \text{'spacing ratio'} \text{ impl}$
24 $(\text{ }_{17} \text{IsPlaceholder}^{1.19}(c) \text{ or } \text{IsSpacingRatioValue}^{7.18}(c) \text{ }_{17} \text{ }_{16}) \text{ }_{16} \text{ }_{10})$

Semiformal Description 7.9

Predicate "is a raster graphics content coding attribute" (clauses 7.1 and 7.2)

A raster graphics content coding attribute is one of the attributes 'compression', 'number of discarded pels', 'number of lines', 'number of lines per tile', 'number of pels per line', 'number of pels per tile line', 'tile types', 'tiling offset' and 'type of coding' with an appropriate value.

NOTE — This predicate is used in clause 7 of this part of ISO 8613.

Definition 7.9

1 $\forall att$
2 $(\text{IsRasterGraphicsContentCodingAttribute}(att) \text{ iff}$
3 $\exists n, c$
4 $(att = [n : c] \text{ and}$
5 $n \in \text{'compression'; 'number of discarded pels'; 'number of lines'; 'number of lines per tile';}$
6 $\text{'number of pels per line'; 'number of pels per tile line'; 'tile types'; 'tiling offset';}$
7 $\text{'type of coding'}) \text{ and}$
8 $(n = \text{'compression'} \text{ impl}$
9 $(\text{IsPlaceholder}^{1.19}(c) \text{ or IsCompressionValue}^{7.21}(c)) \text{ and}$
10 $(n = \text{'number of discarded pels'} \text{ impl}$
11 $(\text{IsPlaceholder}^{1.19}(c) \text{ or IsNumberOfDiscardedPelsValue}^{7.24}(c)) \text{ and}$
12 $(n = \text{'number of lines'} \text{ impl IsNumberOfLinesValue}^{7.22}(c)) \text{ and}$
13 $(n = \text{'number of lines per tile'} \text{ impl}$
14 $(\text{IsPlaceholder}^{1.19}(c) \text{ or IsNumberOfLinesPerTileValue}^{7.26}(c)) \text{ and}$
15 $(n = \text{'number of pels per line'} \text{ impl}$
16 $(\text{IsPlaceholder}^{1.19}(c) \text{ or IsNumberOfPelsPerLineValue}^{7.23}(c)) \text{ and}$
17 $(n = \text{'number of pels per tile line'} \text{ impl}$
18 $(\text{IsPlaceholder}^{1.19}(c) \text{ or IsNumberOfPelsPerTileLineValue}^{7.27}(c)) \text{ and}$
19 $(n = \text{'tile types'} \text{ impl}$
20 $(\text{IsPlaceholder}^{1.19}(c) \text{ or IsTileTypesValue}^{7.29}(c)) \text{ and}$
21 $(n = \text{'tiling offset'} \text{ impl}$
22 $(\text{IsPlaceholder}^{1.19}(c) \text{ or IsTilingOffsetValue}^{7.28}(c)) \text{ and}$
23 $(n = \text{'type of coding'} \text{ impl}$
24 $(\text{IsPlaceholder}^{1.19}(c) \text{ or IsRasterGraphicsContent.TypeOfCodingValue}^{7.20}(c)))$

D.4 Attributes of the Raster Graphics Content Architecture

Semiformal Description 7.10

Predicate "is a raster graphics content portion attribute set"

A raster graphics content portion attribute set contains one or more of the attributes 'compression', 'content information', 'number of discarded pels', 'number of lines', 'number of lines per tile', 'number of pels per line', 'number of pels per tile line', 'tile types', 'tiling offset' and 'type of coding' with an appropriate value.

Definition 7.10

1 $\forall as$
2 $({}_0 \text{IsRasterGraphicsContentPortionAttributeSet}(as) \text{ iff}$
3 $({}_1 \text{IsNeNom}^{1.2}(as) \text{ and}$
4 $\forall a \in \sim as.$
5 $({}_2 N a = \text{'compression'} \text{ impl}$
6 $({}_3 \text{IsPlaceholder}^{1.19}(C a) \text{ or } \text{IsCompressionValue}^{7.21}(C a) {}_4)_3) \text{ and}$
7 $({}_5 N a = \text{'content information'} \text{ impl}$
8 $({}_6 \text{IsPlaceholder}^{1.19}(C a) \text{ or } \text{IsRasterGraphicsContentInformationValue}^{7.25}(C a) {}_8)_5) \text{ and}$
9 $({}_7 N a = \text{'number of discarded pels'} \text{ impl}$
10 $({}_8 \text{IsPlaceholder}^{1.19}(C a) \text{ or } \text{IsNumberOfDiscardedPelsValue}^{7.24}(C a) {}_9)_7) \text{ and}$
11 $({}_9 N a = \text{'number of lines'} \text{ impl } \text{IsNumberOfLinesValue}^{7.22}(C a) {}_9) \text{ and}$
12 $({}_{10} N a = \text{'number of lines per tile'} \text{ impl}$
13 $({}_{11} \text{IsPlaceholder}^{1.19}(c) \text{ or } \text{IsNumberOfLinesPerTileValue}^{7.26}(c) {}_{11})_{10}) \text{ and}$
14 $({}_{12} N a = \text{'number of pels per line'} \text{ impl}$
15 $({}_{13} \text{IsPlaceholder}^{1.19}(C a) \text{ or } \text{IsNumberOfPelsPerLineValue}^{7.23}(C a) {}_{13})_{12}) \text{ and}$
16 $({}_{14} N a = \text{'number of pels per tile line'} \text{ impl}$
17 $({}_{15} \text{IsPlaceholder}^{1.19}(c) \text{ or } \text{IsNumberOfPelsPerTileLineValue}^{7.27}(c) {}_{15})_{14}) \text{ and}$
18 $({}_{16} N a = \text{'tile types'} \text{ impl}$
19 $({}_{17} \text{IsPlaceholder}^{1.19}(c) \text{ or } \text{IsTileTypesValue}^{7.29}(c) {}_{17})_{16}) \text{ and}$
20 $({}_{18} N a = \text{'tiling offset'} \text{ impl}$
21 $({}_{19} \text{IsPlaceholder}^{1.19}(c) \text{ or } \text{IsTilingOffsetValue}^{7.28}(c) {}_{19})_{18}) \text{ and}$
22 $({}_{20} N a = \text{'type of coding'} \text{ impl}$
23 $({}_{21} \text{IsPlaceholder}^{1.19}(C a) \text{ or } \text{IsRasterGraphicsContentTypeOfCodingValue}^{7.20}(C a) {}_{21})_{20})_{21})_0)$

Semiformal Description 7.11

Predicate "is a clipping value" (clause 6.1.1)

The value of the attribute 'clipping' is a catenation of two elements where each element is a pair of non-negative integers.

Definition 7.11

1 $\forall v$
2 $({}_0 \text{IsClippingValue}(v) \text{ iff}$
3 $\exists l, r$
4 $({}_1 v = [\rightarrow l \rightarrow r \rightarrow] \text{ and}$
5 $\text{IsPairOfNnInt}^{1.8}(l) \text{ and } \text{IsPairOfNnInt}^{1.8}(r) {}_1)_0)$

Semiinformal Description 7.12

Predicate "is a raster graphics line progression value" (clause 6.1.2)

The value of the attribute 'line progression' is either '90°' or '270°'.

NOTE — Since the attribute 'line progression' is also used within the character content architectures the qualifier "RasterGraphics" has been added to the predicate name.

Definition 7.12

- 1 $\forall v$
- 2 $(\text{IsRasterGraphicsLineProgressionValue}(v) \text{ iff}$
- 3 $v \in ['90^\circ'; '270^\circ']_o)$

Semiinformal Description 7.13

Predicate "is a pel path value" (clause 6.1.3)

The value of the attribute 'pel path' is one of '0°', '90°', '180°' or '270°'.

Definition 7.13

- 1 $\forall v$
- 2 $(\text{IsPelPathValue}(v) \text{ iff}$
- 3 $v \in ['0^\circ'; '90^\circ'; '180^\circ'; '270^\circ']_o)$

Semiinformal Description 7.14

Predicate "is a raster graphics initial offset value" (clause 6.2.1)

The value of the attribute 'initial offset' is a nomination with two elements. The names are 'horizontal coordinate' and 'vertical coordinate' and the corresponding components are integers.

NOTE — Since the attribute 'initial offset' is also used within the character content architectures the qualifier "RasterGraphics" has been added to the predicate name.

Definition 7.14

- 1 $\forall v$
- 2 $(\text{IsRasterGraphicsInitialOffsetValue}(v) \text{ iff}$
- 3 $(\text{IsNeNom}^{1.2}(v) \text{ and}$
- 4 $\text{NAMS}^{1.18}(v) = ['horizontal coordinate'; 'vertical coordinate'] \text{ and}$
- 5 $\forall b \in \sim v. (\text{IsInt}(C\ b))_o)$

Semiinformal Description 7.15

Predicate "is a pel transmission density value" (clause 6.2.2)

The value of the attribute pel transmission density is one of '1 BMU', '2 BMU', '3 BMU', '4 BMU', '5 BMU' or '6 BMU'.

Definition 7.15

- 1 $\forall v$
- 2 $(\text{IsPelTransmissionDensityValue}(v) \text{ iff}$
- 3 $v \in ['1 \text{ BMU}'; '2 \text{ BMU}'; '3 \text{ BMU}'; '4 \text{ BMU}'; '5 \text{ BMU}'; '6 \text{ BMU}']_o)$

Semiformal Description 7.16

Predicate "is an image dimensions value" (clause 6.3.1)

The value of the attribute 'image dimensions' is a nomination where the name is one of 'width controlled', 'height controlled', 'area controlled' or 'automatic'. For the name 'width controlled' the corresponding component is a non-empty nomination with the names 'minimum width' and 'preferred width' and the associated components are non-negative integers. For the name 'height controlled' the corresponding component is a non-empty nomination with the names 'minimum height' and 'preferred height' and the associated components are non-negative integers. For the name 'area controlled' the corresponding component is a non-empty nomination with the names 'minimum width', 'preferred width', 'minimum height', 'preferred height' (the components are non-negative integers) and 'aspect ratio flag' (the component is either 'fixed' or 'variable'). For the name 'automatic' the component is 'null'.

Definition 7.16

```

1   $\forall v$ 
2  ( $_0$  IsImageDimensionsValue( $v$ ) iff
3     $\exists n, a$ 
4    ( $_1 v = [n : a]$  and
5      ( $_2 n = \text{'width controlled'}$  impl
6        ( $_3$  IsNeNom1.2( $a$ ) and
7          NAMS1.18( $a$ ) = ['minimum width'; 'preferred width'] and
8             $\forall b \in \sim a \cdot (\text{IsNnInt}^{1.7}(C\ b))$   $_3$ )  $_2$ ) and
9      ( $_4 n = \text{'height controlled'}$  impl
10        ( $_5$  IsNeNom1.2( $a$ ) and
11          NAMS1.18( $a$ ) = ['minimum height'; 'preferred height'] and
12             $\forall b \in \sim a \cdot \text{IsNnInt}^{1.7}(C\ b)$   $_5$ )  $_4$ ) and
13        ( $_6 n = \text{'area controlled'}$  impl
14          ( $_7$  IsNeNom1.2( $a$ ) and
15            NAMS1.18( $a$ ) = ['minimum height'; 'preferred height';
16              'minimum width'; 'preferred width'; 'aspect ratio flag'] and
17               $\forall b \in \sim a \cdot$ 
18                ( $_8 N\ b \in [\text{'minimum width'; 'preferred width'; 'minimum height'; 'preferred height'}]$  impl
19                   $\text{IsNnInt}^{1.7}(C\ b)$   $_8$ ) and
20                ( $_9 N\ b = \text{'aspect ratio flag'}$  impl  $C\ b \in [\text{'fixed'; 'variable'}]$   $_9$ )  $_7$ ) and
21            ( $_11 n = \text{'automatic'}$  impl  $a = \text{'null'}$   $_11$ )  $_0$ )

```

Semiformal Description 7.17

Predicate "is a pel spacing value" (clause 6.3.2)

The value of the attribute 'pel spacing' is either 'null' or a nomination with two elements. The names are 'length' and 'pel spaces' and the corresponding components are positive integers.

Definition 7.17

```

1   $\forall v$ 
2  ( $_0$  IsPelSpacingValue( $v$ ) iff
3    ( $_1 (v = \text{'null'})$  or
4      ( $_2$  IsNeNom1.2( $v$ ) and
5        NAMS1.18( $v$ ) = ['length'; 'pel spaces'] and
6         $\forall b \in \sim v \cdot (\text{IsNat}(C\ b))$   $_2$ )  $_0$ )

```

Semiformal Description 7.18

Predicate "is a spacing ratio value" (clause 6.3.3)

The value of the attribute 'spacing ratio' a nomination with two elements. The names are 'line spacing value' and 'pel spacing value' and the corresponding components are positive integers.

Definition 7.18

- 1 $\forall v$
- 2 $(\text{IsSpacingRatioValue}(v) \text{ iff}$
- 3 $(\text{IsNeNom}^{1.2}(v) \text{ and}$
- 4 $\text{NAMS}^{1.18}(v) = [\text{'line spacing value'; 'pel spacing value'}] \text{ and}$
- 5 $\forall b \in \sim v. (\text{IsNat}(C\ b)) \text{ ,})$

Semiformal Description 7.19

Predicate "is a raster graphics content architecture class value" (clause 6.4.1)

The value of the attribute 'content architecture class' is an ASN.1 object identifier with either the value '2 8 2 7 0' or '2 8 2 7 2' for raster graphics content.

NOTE — This predicate is used in clause 7 of this part of ISO 8613.

Definition 7.19

- 1 $\forall v$
- 2 $(\text{IsRasterGraphicsContentArchitectureClassValue}(v) \text{ iff}$
- 3 $v \in [\text{'2 8 2 7 0'; '2 8 2 7 2'}]_0)$

Semiformal Description 7.20

Predicate "is a raster graphics content type of coding value" (clause 7.1.1)

For a raster graphics content portion the value of the attribute 'type of coding' is either 0 or an ASN.1 object identifier with either the value '2 8 3 7 0', '2 8 3 7 1', '2 8 3 7 2', '2 8 3 7 3' or '2 8 3 7 5'.

NOTE — This predicate is used in clause 7 of this part of ISO 8613.

Definition 7.20

- 1 $\forall v$
- 2 $(\text{IsRasterGraphicsContentTypeOfCodingValue}(v) \text{ iff}$
- 3 $(v = 0 \text{ or } v \in [\text{'2 8 3 7 0'; '2 8 3 7 1'; '2 8 3 7 2'; '2 8 3 7 3'; '2 8 3 7 5'}]_0)$

Semiformal Description 7.21

Predicate "is a compression value" (clause 7.2.1)

The value of the attribute 'compression' is either 'compressed' or 'uncompressed'.

Definition 7.21

- 1 $\forall v$
- 2 $(\text{IsCompressionValue}(v) \text{ iff}$
- 3 $v \in [\text{'compressed'; 'uncompressed'}]_0)$

Semiformal Description 7.22

Predicate “is a number of lines value” (clause 7.2.2)

The value of the attribute 'number of lines' is a positive integer.

Definition 7.22

- 1 $\forall v$
- 2 $(\text{IsNumberOfLinesValue}(v) \text{ iff}$
- 3 $\text{IsNat}(v)_o)$

Semiformal Description 7.23

Predicate “is a number of pels per line value” (clause 7.2.3)

The value of the attribute 'number of pels per line' is a non-negative integer.

Definition 7.23

- 1 $\forall v$
- 2 $(\text{IsNumberOfPelsPerLineValue}(v) \text{ iff}$
- 3 $\text{IsNnInt}^{1.7}(v)_o)$

Semiformal Description 7.24

Predicate “is a number of discarded pels value” (clause 7.2.4)

The value of the attribute 'number of discarded pels' is a non-negative integer.

Definition 7.24

- 1 $\forall v$
- 2 $(\text{IsNumberOfDiscardedPelsValue}(v) \text{ iff}$
- 3 $\text{IsNnInt}^{1.7}(v)_o)$

Semiformal Description 7.25

Predicate “is a raster graphics content information value” (clause 7.3.1)

For a raster graphics content portion the value of the attribute 'content information' is an octet string, representing the pel array.

NOTE — This predicate is used in clause 7 of this part of ISO 8613.

Definition 7.25

- 1 $\forall v$
- 2 $(\text{IsRasterGraphicsContentInformationValue}(v) \text{ iff}$
- 3 $\text{IsOctetString}^{1.10}(v)_o)$

Semiformal Description 7.26

Predicate "is a number of lines per tile value" (clause 7.2.5)

For a raster graphics content portion the value of the attribute 'number of lines per tile' is a positive integer.

Definition 7.26

- 1 $\forall v$
- 2 $(\text{IsNumberOfLinesPerTileValue}(v) \text{ iff}$
- 3 $\text{IsNat}(v)_0)$

Semiformal Description 7.27

Predicate "is a number of pels per tile line" (clause 7.2.6)

For a raster graphics content portion the value of the attribute 'number of pels per tile line' is a positive integer.

Definition 7.27

- 1 $\forall v$
- 2 $(\text{IsNumberOfPelsPerTileLineValue}(v) \text{ iff}$
- 3 $\text{IsNat}(v)_0)$

Semiformal Description 7.28

Predicate "is a tiling offset value" (clause 7.2.7)

For a raster graphics content portion the value of the attribute 'tiling offset' is a sequence of two non-negative integers.

Definition 7.28

- 1 $\forall v$
- 2 $(\text{IsTilingOffsetValue}(v) \text{ iff}$
- 3 $\exists a, b \text{ and}$
- 4 $(v = [\rightarrow a \rightarrow b \rightarrow] \text{ and } \text{IsNnInt}^{1.7}(a) \text{ and } \text{IsNnInt}^{1.7}(b)_0)$

Semiformal Description 7.29

Predicate "is a tile types value" (clause 7.2.8)

For a raster graphics content portion the value of the attribute 'tile types' is a non-empty catenation of tile encoding values.

Definition 7.29

- 1 $\forall v$
- 2 $(\text{IsTileTypesValue}(v) \text{ iff}$
- 3 $(\text{IsNeCat}^{1.3}(v) \text{ and}$
- 4 $\forall a \in v. \text{IsTileEncodingValue}^{7.30}(a)_0)$