

INTERNATIONAL STANDARD

ISO/IEC
9593-1

First edition
1990-06-01

AMENDMENT 1
1995-04-15

Information processing systems — Computer graphics — Programmer's Hierarchical Interactive Graphics System (PHIGS) language bindings —

Part 1:
FORTRAN

AMENDMENT 1

*Systèmes de traitement de l'information — Infographie — Interfaces langage
entre un programme d'application et son support graphique*

Partie 1: FORTRAN

AMENDEMENT 1



Reference number
ISO/IEC 9593-1:1990/Amd.1:1995(E)

Contents

1. Scope	1
2. Normative references	1
3. Principles	2
3.1. Specification	2
3.2. Mapping of PHIGS function names to FORTRAN subroutine names	2
3.3. Parameters	2
3.4. The FORTRAN subset	2
3.5. Error handling	3
4. Generating FORTRAN subroutine names	4
5. Data types	6
6. Enumeration types	10
7. List of the PHIGS function names	10
8. PHIGS errors specific to the FORTRAN binding	10
9. The PHIGS function interface	10
10. Utility functions not defined in PHIGS	10
11. PHIGS PLUS Enumeration types	11
12. List of the PHIGS PLUS function names	16
12.1. List of functions ordered alphabetically by bound name	16
12.2. List of functions ordered alphabetically by PHIGS PLUS function name	18
13. The PHIGS PLUS function interface	20
13.1. General principles	20
13.2. Output primitive functions	20
13.3. Attribute specification functions	33
13.3.1. Bundled attribute selection	33
13.3.2. Individual attribute selection	34
13.3.3. Aspect source flag setting	46
13.3.4. Workstation attribute table definition	47
13.4. Inquiry functions	55
13.4.1. Inquiry functions for workstation state list	55
13.4.2. Inquiry functions for workstation description table	63
14. Utility functions not defined in PHIGS and PHIGS PLUS	111
Annex A FORTRAN Examples(informative)	118
Annex B Function Lists(normative)	124
Annex C Memory Management(normative)	130

© ISO/IEC 1995

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

ISO/IEC Copyright Office • Case postale 56 • CH-1211 Genève 20 • Switzerland

Printed in Switzerland

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Amendment 1 to International Standard ISO/IEC 9593-1:1990 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 9593-1:1990/Amd.1:1995

Introduction

Replace the Introduction of ISO/IEC 9593-1 with the following text:

ISO/IEC 9592-1:1989, provides a set of functions for the display and modification of 2D or 3D graphical data. Part 1 is extended by Part 4 (PHIGS PLUS) to incorporate the effects of lighting, shading and other properties that are important for the display of surfaces and multidimensional data.

ISO/IEC 9592-1 and ISO/IEC 9592-4 are specified in a language independent manner and must be embedded in language dependent layers (language bindings) for use with particular programming languages.

The purpose of this part of ISO/IEC 9593 is to define the FORTRAN language binding for ISO/IEC 9592-1 and ISO/IEC 9592-4.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 9593-1:1990/Amd 1:1995

**Information processing systems — Computer graphics —
Programmer's Hierarchical Interactive Graphics System (PHIGS)
language bindings —**

**Part 1:
FORTRAN**

AMENDMENT 1

1 Scope

Replace clause 1:

The "Programmer's Hierarchical Interactive Graphics System" (PHIGS), ISO/IEC 9592-1:1989, and ISO/IEC 9592-4:1992, specify a language independent nucleus of a graphics system. For integration into a programming language, PHIGS PLUS is embedded in a language dependent layer obeying the particular conventions of that language. This part of ISO/IEC 9593 specifies the FORTRAN language dependent layer.

2 Normative references

Add the following reference to clause 2:

ISO/IEC 9592-4:1992, *Information processing systems - Computer graphics - Programmer's Hierarchical Interactive Graphics System (PHIGS) Part 4 - Plus Lumière Und Surfaces (PHIGS PLUS)*.

3 Principles

3.1 Specification

Replace subclause 3.1, Specification, of ISO/IEC 9593-1 with the following text:

This part of ISO/IEC 9593 defines the PHIGS and PHIGS PLUS language binding interface for FORTRAN 77, as described in ISO 1539: 1980. With some minor modifications, application programs can be transported between full FORTRAN77 and FORTRAN77 Subset PHIGS and PHIGS PLUS installations.

This binding incorporates the rules of conformance defined in the PHIGS (ISO/IEC 9592-1) and PHIGS PLUS (ISO/IEC 9592-4) Standard for PHIGS and PHIGS PLUS implementations, with those additional requirements specifically defined for FORTRAN language implementations defined in this part of ISO/IEC 9593. The following criteria are established for determining conformance of an implementation to this binding:

In order to conform, an implementation of the FORTRAN binding of PHIGS shall implement those functions specified in ISO/IEC 9592-1. The implementation shall make visible all of the declarations in the FORTRAN binding specified in clause 5 to 10 in this part of ISO/IEC 9593.

In order to conform, an implementation of the FORTRAN binding of PHIGS PLUS shall implement those functions specified in ISO/IEC 9592-1 and also those functions specified in ISO/IEC 9592-4. The implementation shall make visible all of the declarations in the FORTRAN binding specified in clause 11 to 14 and in clause 5 to 10, as modified by clause 11 to 14, in this part of ISO/IEC 9593.

Thus, for example, the syntax of the function names shall be precisely as specified in this part of ISO/IEC 9593 and the parameters shall be of the data types stated in this part of ISO/IEC 9593.

A PHIGS FORTRAN application should run without modification under a PHIGS PLUS FORTRAN binding implementation.

3.2 Mapping of PHIGS function names to FORTRAN subroutine names

Append the following paragraph to subclause 3.2,

However, two abbreviations are changed for PHIGS PLUS; MAPPING becomes M and WORKSTATION becomes W, due to the FORTRAN subroutine naming restrictions.

3.3 Parameters

No change to ISO/IEC 9593-1.

3.4 The FORTRAN subset

No change to ISO/IEC 9593-1.

3.5 Error handling

No change to ISO/IEC 9593-1.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 9593-1:1990/Amd 1:1995

4 Generating FORTRAN subroutine names

Add the following, alphabetically, to table 2 of clause 4:

Table 2 - Reduce compound terms for uniqueness

REPRESENTATION PLUS	-> P
---------------------	------

Add the following, alphabetically, to table 3 of clause 4:

Table 3 - Deletions

GEOMETRIC	NON-UNIFORM	WITH
-----------	-------------	------

Add the following, alphabetically, to table 4 to clause 4:

Table 4 - Abbreviations

PHIGS PLUS word abbreviation		remarks
APPROXIMATION	A	
B-SPLINE	BS	
BACK	B	
CHARACTERISTICS	C	
COORDINATE	CD	
CRITERIA	C	
CUE	C	
CULLING	C	
CURVE	C	
DATA	D	
DEPTH	D	SET DEPTH CUE INDEX:DP
DIRECT	D	
DISTINGUISHING	D	
DYNAMICS	DC	
FACET	F	
LIGHT	L	
MAPPING	M	
MESH	M	FOR PHIGS PLUS
METHOD	M	
PARAMETRIC	P	
PLACEMENT	P	
PLUS	P	
PROPERTIES	P	
QUADRILATERAL	Q	
REFLECTANCE	RF	
RENDERING	R	
SHADING	S	
SPLINE	S	
STRIP	ST	
SURFACE	S	
SOURCE	S	
TRIMMING	T	
TRIANGLE	T	
WORKSTATION	W	FOR PHIGS PLUS

5 Data types

Append the following data type definitions to clause 5:

COLRV colour value

INTEGER containing colour index when CTYPE is INDIRECT

INTEGER NCC when CTYPE is not INDIRECT

REAL₁, **REAL**₂, **REAL**₃, ..., **REAL**_n containing C₁, C₂, C₃, ..., C_n (n=NCC) when CTYPE is not INDIRECT

COLRVH homogeneous colour value

REAL₁, **REAL**₂, **REAL**₃, ..., **REAL**_n and **REAL** containing WC₁, WC₂, WC₃, ..., WC_n and W (n=NCC)

GCOLOR general colour

a compound data type containing colour type and colour value of **COLRV**

NORM normal vector

REAL, **REAL**, **REAL** containing X-, Y- and Z- values

P2H two-dimensional homogeneous point

REAL, **REAL**, **REAL** containing WX-, WY- and W- values (or WU-, WV- and W- of a trimming curve control point) W value is ignored in case of non-rational type

P3H three-dimensional homogeneous point

REAL, **REAL**, **REAL**, **REAL** containing WX-, WY-, WZ- and W- values
W value is ignored in case of non-rational type

A(P3) array of coordinates of points

REAL(*), **REAL**(*), **REAL**(*) containing X-, Y- and Z- values (* = number of columns by number of rows)

L(L(P3{COLRV})) list of vertex data lists

REAL PXA(*), PYA(*), PZA(*) *=last value of array of end indices for point lists(NP)

INTEGER VCOLI(*) *=NP, when CTYPE is INDIRECT

REAL VCOLR(*) *=number of components of colour value(NCC) × NP, when CTYPE is not INDIRECT

{COLRV}{,NORM}{,L(R)} facet data

INTEGER FCOLI when CTYPE is INDIRECT

REAL FCOLR(*) *=number of components of colour value(NCC), when CTYPE is not INDIRECT

REAL FNXA, FNZA, FNZA facet normal data

REAL FDLEN length of application-specific data

REAL FDATA(FDLEN) facet application-specific data

L(L(E)) list of edge flags lists

INTEGER EDATA(*) *=last value of array of end indices for point lists

L(L(P2{COLRV}{,NORM}{,L(R)}))

REAL PXA(*), PYA(*) *=last value of array of end indices for point lists(NP)

INTEGER VCOLI(*) *=NP, when CTYPE is INDIRECT

REAL VCOLR(*) *=number of components of colour value(NCC) × NP, when CTYPE

is not INDIRECT

REAL VNXA(*),VN YA(*) vertex normal data(*=NP)

INTEGER VDLEN length of application-specific data

REAL VDATA(*) vertex application-specific data(*=VDLEN × NP)

L(L(P3{,COLRV}{,NORM}{,L(R)}))

REAL PXA(*),PYA(*),PZA(*) *=last value of array of end indices for point lists(NP)

INTEGER VCOLI(*) *=NP, when CTYPE is INDIRECT

REAL VCOLR(*) *=number of components of colour value(NCC) × NP, when CTYPE is not INDIRECT

REAL VNXA(*),VN YA(*),VN ZA(*) vertex normal data(*=NP)

INTEGER VDLEN length of application-specific data

REAL VDATA(*) vertex application-specific data(*=VDLEN × NP)

L(L(L(I))) list of lists of vertex indices lists

REAL VIND(*) *=last value of array of end vertex indices for each fill area

L(L(L(E))) list of lists of edge flags lists

INTEGER EDATA(*) *=last value of array of end vertex indices for each fill area

L({COLRV}{,NORM}{,L(R)}) list of facet data

INTEGER FCOLI(*) *=number of fill area sets(N) in set of fill area sets 3 with data or set of fill area sets with data, number of triangles(N) at following 4 functions, triangle set 3 with data, triangle set with data, triangle strip 3 with data and triangle strip with data, when CTYPE is INDIRECT

REAL FCOLR(*) *=number of components of colour value(NCC) × NFS, when CTYPE is not INDIRECT

REAL FNXA(*),FN YA(*),FN ZA(*) facet normal data(*=N)

INTEGER FDLEN length of application-specific data

REAL FDATA(*) facet application-specific data(*=FDLEN × N)

L(P3{,COLRV}{,NORM}{,L(R)}) list of vertex data

REAL PXA(*),PYA(*),PZA(*) *=number of points(NP)

INTEGER VCOLI(*) *=NP, when CTYPE is INDIRECT

REAL VCOLR(*) *=number of components of colour value(NCC) × NP, when CTYPE is not INDIRECT

REAL VNXA(*),VN YA(*),VN ZA(*) vertex normal data(*=NP)

INTEGER VDLEN length of application-specific data

REAL VDATA(*) vertex application-specific data(*=VDLEN × NP)

L(P2{,COLRV}{,NORM}{,L(R)}) list of vertex data

REAL PXA(*),PYA(*) *=number of points(NP)

INTEGER VCOLI(*) *=NP, when CTYPE is INDIRECT

REAL VCOLR(*) *=number of components of colour value(NCC) × NP, when CTYPE is not INDIRECT

REAL VNXA(*),VN YA(*),VN ZA(*) vertex normal data(*=NP)

INTEGER VDLEN length of application-specific data

REAL VDATA(*) vertex application-specific data(*=VDLEN × NP)

A(COLRV) colour array

INTEGER COLIA(*) *=number of columns(DIMX) × number of rows(DIMY), when CTYPE is INDIRECT

REAL COLRA(*) *=number of components of colour value(NCC) × DIMX × DIMY, when CTYPE is not INDIRECT

A({COLRV},{,NORM},{,L(R)}) array of facet data

INTEGER FCOLI(*) *=number of columns minus 1(NC-1) × number of rows minus 1(NR-1),
when CTYPE is INDIRECT

REAL FCOLR(*) *=number of components of colour value(NCC) × NC-1 × NR-1,
when CTYPE is not INDIRECT

REAL FNXA(*),FNYA(*),FNZA(*) facet normal data(*= NC-1 × NR-1)

INTEGER FDLEN length of application-specific data

REAL FDATA(*) facet application-specific data(*=FDLEN × NC-1 × NR-1)

A(P3,{COLRV},{,NORM},{,L(R)}) array of vertex data

REAL PXA(*),PYA(*),PZA(*) *=number of columns(NC) × number of rows(NR)

INTEGER VCOLI(*) *=NC × NR, when CTYPE is INDIRECT

REAL VCOLR(*) *=number of components of colour value(NCC) × NC × NR,
when CTYPE is not INDIRECT

REAL VNXA(*),VNYA(*),VNZA(*) vertex normal data(*= NC × NR)

INTEGER VDLEN length of application-specific data

REAL VDATA(*) vertex application-specific data(*=VDLEN × NC × NR)

A(P2,{COLRV},{,NORM},{,L(R)}) array of vertex data

REAL PXA(*),PYA(*) *=number of columns(NC) × number of rows(NR)

INTEGER VCOLI(*) *=NC × NR, when CTYPE is INDIRECT

REAL VCOLR(*) *=number of components of colour value(NCC) × NC × NR,
when CTYPE is not INDIRECT

REAL VNXA(*),VNYA(*),VNZA(*) vertex normal data(*= NC × NR)

INTEGER VDLEN length of application-specific data

REAL VDATA(*) vertex application-specific data(*=VDLEN × NC × NR)

A(2×E) array of edge data

INTEGER EDATA(*) *=2 × number of columns(NC) × number of rows(NR)

L(P3H)|L(P3) list of curve control points

REAL PXA(*),PYA(*),PZA(*),PWA(*) *=number of control points, when CRYTYPE is PRAT

REAL PXA(*),PYA(*),PZA(*) *=number of control points, when CRYTYPE is PNRAT

L(COLRVH)|L(COLRV) list of colour spline control points

REAL CSCR(*) *={number of components of colour value(NCC)+1} ×
number of colour spline control points(NCSCP), when CRYTYPE is PRAT

REAL CSCR(*) *=number of components of colour value(NCC) ×
number of colour spline control points(NCSCP), when CRYTYPE is PNRAT

A(P3H)|A(P3) array of surface control points

REAL PXA(*),PYA(*),PZA(*),PWA(*) *=u number of control points dimension(UNCP) ×
v number of control points dimension(VNCP), when CRYTYPE is PRAT

REAL PXA(*),PYA(*),PZA(*) *=u number of control points dimension(UNCP) ×
v number of control points dimension(VNCP), when CRYTYPE is PNRAT

L(L(TRIMCURVE)) list of trimming loop definitions lists

INTEGER TACRI(*) *=number of components of list of trimming loop definitions lists(NCLTL)

INTEGER TCVF(*) trimming curve visibility flag(*=NCLTL)

INTEGER TSORD(*) trimming curve spline order(*=NCLTL)

INTEGER TNKA(*) number of spline knots(*=NCLTL)

REAL TKNOTS(*) *=last value of array of number of spline knots in array(TNKA)

REAL TPARL(2,*) trimming curve parameter range limits(*=NCLTL)

INTEGER TRTYPE(*) trimming curve spline rationality(*=NCLTL)

INTEGER NTCCP(*) number of trimming curve spline control points(*=NCLTL)
REAL TPWXA(*),TPWYA(*),TPWWA(*) *=last value of number of trimming curve spline control points, when CRTYPE is PRAT
REAL TPWXA(*),TPWYA(*) *=last value of number of trimming curve spline control points, when CRTYPE is PNRAT

L(P2H)|L(P2) list of trimming curve control points

REAL TPWUA(*),TPWVA(*),TPWWA(*) *=number of control points, when CRTYPE is PRAT
REAL TPWUA(*),TPWVA(*) *=number of control points, when CRTYPE is PNRAT

A(COLRVH)|A(COLRV) array of colour spline control points

REAL CSCP(*) *={number of components of colour value(NCC)+1} ×
 u number of colour spline control points dimension(NUCSCP) ×
 v number of colour spline control points dimension(NVCSCP), when CRTYPE is PRAT
REAL CSCP(*) *=number of components of colour value(NCC) ×
 u number of colour spline control points dimension(NUCSCP) ×
 v number of colour spline control points dimension(NVCSCP), when CRTYPE is PNRAT

L(DATASPLINE) list of data spline (for non-uniform B-spline surface with data)

INTEGER DUSORD(*) u data spline order(*=NDS)
INTEGER DVSORD(*) v data spline order(*=NDS)
INTEGER DNUKA(*) number of u spline knots(*=NDS)
INTEGER DNVKA(*) number of v spline knots(*=NDS)
REAL DUKNTS(*) *=last value of number of u spline knots(DNUKA) × NDS
REAL DVKNTS(*) *=last value of number of v spline knots(DNVKA) × NDS
INTEGER DRTYPE(*) data spline rationality(*=NDS)
INTEGER NUDSCP(*) u number of data spline control points dimension(*=NDS)
INTEGER NVDSCP(*) v number of data spline control points dimension(*=NDS)
INTEGER DDIMS(*) data dimension(*=NDS)
REAL DSCP(*) *=

$$\sum_{i=1}^{NDS} (NUDSCP(i) \times NVDSCP(i) \times DDIMS(i))$$

DDIMS(i) = n+1 (n = d₁,d₂,d₃,...,d_n,w) when DRTYPE(i) is PRAT.

DDIMS(i) = n (n = d₁,d₂,d₃,...,d_n) when DRTYPE(i) is PNRAT.

A(DATAH)|A(DATA) control points of data spline

REAL DSCP(*) *=

$$\sum_{i=1}^{NDS} (NUDSCP(i) \times NVDSCP(i) \times DDIMS(i))$$

DDIMS(i) = n+1 (n = d₁,d₂,d₃,...,d_n,w) when DRTYPE(i) is PRAT.

DDIMS(i) = n (n = d₁,d₂,d₃,...,d_n) when DRTYPE(i) is PNRAT.

NDS=number of data spline

NUDSCP=u number of data spline control points dimension

NVDSCP=v number of data spline control points dimension

DDIMS=data dimension for spline

6 Enumeration types

No change to ISO/IEC 9593-1.

7 List of the PHIGS function names

No change to ISO/IEC 9593-1.

8 PHIGS errors specific to the FORTRAN binding

No change to ISO/IEC 9593-1.

9. The PHIGS function interface

No change to ISO/IEC 9593-1.

10 Utility functions not defined in PHIGS

No change to ISO/IEC 9593-1.

Add the following new clauses 11, 12, 13 and 14:

11 PHIGS PLUS Enumeration types

All the enumeration types of PHIGS PLUS are mapped to FORTRAN INTEGERS. The correspondence between PHIGS PLUS scalars and FORTRAN INTEGERS is shown as follows in a list of symbolic FORTRAN constants that may be included in any application program. This clause contains a mapping of PHIGS PLUS enumeration types to FORTRAN variable names.

"Polyline shading method", "interior shading method", "data mapping method", "reflectance property type", "reflectance model", "curve placement", "light source type", "colour mapping method", "curve approximation type", "surface approximation type" and "parametric surface characteristic type" are defined as INTEGER rather than enumeration types in PHIGS PLUS. Constant definitions for the explicitly defined and required values of these conceptually unbounded ranges are provided as a convenience.

Also, a numbering of all PHIGS PLUS functions is given for use in the error handling procedures.

Mnemonic FORTRAN names and their values for PHIGS PLUS ENUMERATION type values:

aspect identifier

	<i>polyline colour</i>				
INTEGER	PPLCOL,	PPMCOL,	PTXCOL,	PINCOL,	PEDCOL,
1	PPSHMD,	PISHMD,	PDMPMD,	PREFPR,	PREFM,
2	PBINSY,	PBINSI,	PBICOL,	PBISHM,	PBDMPM,
3	PBREFP,	PBREFM,	PCAPCR,	PSAPCR,	PPASUC
PARAMETER(	PPLCOL=18,	PPMCOL=19,	PTXCOL=20,	PINCOL=21,	PEDCOL=22,
1	PPSHMD=23,	PISHMD=24,	PDMPMD=25,	PREFPR=26,	PREFM=27,
2	PBINSY=28,	PBINSI=29,	PBICOL=30,	PBISHM=31,	PBDMPM=32,
3	PBREFP=33,	PBREFM=34,	PCAPCR=35,	PSAPCR=36,	PPASUC=37)

colour mapping method

	<i>true</i>	<i>pseudo</i>	<i>pseudo-n</i>
INTEGER	PTRUE,	PSUD,	PSUDN
PARAMETER(	PTRUE=1,	PSUD=2,	PSUDN=3)

INTEGER rather than enumeration type. Explicitly defined and required portion of conceptually unbounded range defined here.

colour type

	<i>indirect</i>
INTEGER	PINDIR
PARAMETER(	PINDIR=0)

The following colour models are also colour types.
RGB,CIELUV,HSV,HLS

culling mode

	<i>none</i>	<i>backfacing</i>	<i>frontfacing</i>
INTEGER	PNOFC,	PBKFC,	PFTFC
PARAMETER(	PNOFC=0,	PBKFC=1,	PFTFC=2)

curve approximation criteria type

	<i>workstation dependent chordal deviation in WC relative DC</i>	<i>constant between knots chordal deviation in NPC</i>	<i>chordal size in WC chordal deviation in DC</i>	<i>chordal size in NPC relative WC</i>	<i>chordal size in DC relative NPC</i>
INTEGER	PWDCA,	PCBKCA,	PCSWCA,	PCSNCA,	PCSDCA,
1	PCDWCA,	PCDNCA,	PCDDCA,	PRWCA,	PRNCA,
2	PRDCA				
PARAMETER(	PWDCA=1,	PCBKCA=2,	PCSWCA=3,	PCSNCA=4,	PCSDCA=5,
1	PCDWCA=6,	PCDNCA=7,	PCDDCA=8,	PRWCA=9,	PRNCA=10,
2	PRDCA=11)				

INTEGER rather than enumeration type. Explicitly defined and required portion of conceptually unbounded range defined here.

curve placement (of ISOPARAMETRIC CURVE)

	<i>over surface</i>	<i>between knots</i>
INTEGER	PUOSCP,	PUBKCP
PARAMETER(	PUOSCP=0,	PUBKCP=1)

curve visibility flag

Uses the POFF/PON enumeration defined for edge flag and error handling mode.

data mapping method

	<i>colour</i>	<i>single uniform</i>	<i>single non-uniform</i>	<i>BI uniform</i>	<i>BI non-uniform</i>
INTEGER	PCDM,	PSUDM,	PSNUDM,	PBUDM,	PBNUDM
PARAMETER(	PCDM=1,	PSUDM=2,	PSNUDM=3,	PBUDM=4,	PBNUDM=5)

INTEGER rather than enumeration type. Explicitly defined and required portion of conceptually unbounded range defined here.

depth cue mode

	<i>suppressed</i>	<i>allowed</i>
INTEGER	PSUPPR	PALLOW
PARAMETER(	PSUPPR=0,	PALLOW=1)

distinguishing mode

Uses the POFF/PON enumeration defined for edge flag and error handling mode.

edge data flag

	<i>none</i>	<i>edge visibility flag</i>
INTEGER	PENO	PEVF
PARAMETER(	PENO=0,	PEVF=1)

Not defined in PHIGS PLUS but used to indicate presence of optional data for FORTRAN binding.

element type

polyline set 3 with data

INTEGER	PEPLS3,	PEFS3D,	PEFSD,	PECA3P,	PESFS3,
1	PESFSD,	PETS3D,	PETSD,	PETST3,	PETSTD,
2	PEQM3D,	PEQMD,	PEBC3,	PEBC3C,	PEBS3,
3	PEBS3D,	PEDMI,	PERFI,	PEBII,	PEBDMI,
4	PEBRFI,	PEPRSI,	PEPLC,	PEPLSM,	PEPMC,
5	PETXC,	PEFDM,	PEFCM,	PEIC,	PEISM,
6	PEDMM,	PERFP,	PERFM,	PEBIS,	PEBISI,
7	PEBIC,	PEBISM,	PEBDMM,	PEBRFP,	PEBRFM,
8	PELSS,	PEEDC,	PECAC,	PESAC,	PEPSC,
9	PERCM,	PEDPCI,	PECM1)		
PARAMETER(	PEPLS3=71,	PEFS3D=72,	PEFSD=73,	PECA3P=74,	PESFS3=75,
1	PESFSD=76,	PETS3D=77,	PETSD=78,	PETST3=79,	PETSTD=80,
2	PEQM3D=81,	PEQMD=82,	PEBC3=83,	PEBC3C=84,	PEBS3=85,
3	PEBS3D=86,	PEDMI=87,	PERFI=88,	PEBII=89,	PEBDMI=90,
4	PEBRFI=91,	PEPRSI=92,	PEPLC=93,	PEPLSM=94,	PEPMC=95,
5	PETXC=96,	PEFDM=97,	PEFCM=98,	PEIC=99,	PEISM=100,
6	PEDMM=101,	PERFP=102,	PERFM=103,	PEBIS=104,	PEBISI=105,
7	PEBIC=106,	PEBISM=107,	PEBDMM=108,	PEBRFP=109,	PEBRFM=110,
8	PELSS=111,	PEEDC=112,	PECAC=113,	PESAC=114,	PEPSC=115,
9	PERCM=116,	PEDPCI=117,	PECM1=118)		

facet data flag

	<i>no facet data</i>	<i>colour</i>	<i>normal</i>	<i>data</i>	<i>colour/normal</i>
INTEGER	PFNO,	PFC,	PFN	PFD,	PFCN,
1	PFCD,	PFND,	PFCND		
PARAMETER(	PFNO=0,	PFC=1,	PFN=2,	PFD=3,	PFCN=4,
1	PFCD=5,	PFND=6,	PFCND=7)		

Not defined in PHIGS PLUS but used to indicate presence of optional data for FORTRAN binding.

GDP attributes

	<i>reflectance</i>	<i>parametric surface</i>
INTEGER	PRFATT,	PPSATT
PARAMETER(	PRFATT=5,	PPSATT=6)

interior shading method

	<i>none</i>	<i>colour</i>	<i>data</i>	<i>data/dot</i>	<i>data/normal</i>
INTEGER	PNOIS,	PCIS,	PDIS,	PDDIS,	PDNIS
PARAMETER(	PNOIS=1,	PCIS=2,	PDIS=3,	PDDIS=4,	PDNIS=5)

INTEGER rather than enumeration type. Explicitly defined and required portion of conceptually unbounded range defined here.

light source type

	<i>ambient</i>	<i>directional</i>	<i>positional</i>	<i>spot</i>
INTEGER	PAMB,	PDIRE,	PPOSI,	PSPOT
PARAMETER(	PAMB=1,	PDIRE=2,	PPOSI=3,	PSPOT=4)

INTEGER rather than enumeration type. Explicitly defined and required portion of conceptually unbounded range defined here.

parametric surface characteristic type

	<i>none</i>	<i>workstation dependent</i>	<i>isoparametric curve</i>	<i>level curve in MC</i>	<i>level curve in WC</i>
INTEGER	PNOPC,	PWDPC,	PICPC,	PLCMPC,	PLCWPC
PARAMETER(	PNOPC=1,	PWDPC=2,	PICPC=3,	PLCMPC=4,	PLCWPC=5)

INTEGER rather than enumeration type. Explicitly defined and required portion of conceptually unbounded range defined here.

polyline shading method

	<i>none</i>	<i>colour</i>
INTEGER	PNOPS,	PCPS
PARAMETER(	PNOPS=1,	PCPS=2)

INTEGER rather than enumeration type. Explicitly defined and required portion of conceptually unbounded range defined here.

rationality

	<i>rational</i>	<i>non-rational</i>
INTEGER	PRAT,	PNRAT
PARAMETER(	PRAT=0,	PNRAT=1)

reflectance model

	<i>no reflectance</i>	<i>ambient</i>	<i>ambient/diffuse</i>	<i>ambient/diffuse/specular</i>
INTEGER	PNORM,	PARM,	PADRM,	PADSRM
PARAMETER(	PNORM=1,	PARM=2,	PADRM=3,	PADSRM=4)

INTEGER rather than enumeration type. Explicitly defined and required portion of conceptually unbounded range defined here.

reflectance property type

	<i>simple reflectance</i>
INTEGER	PSRPT
PARAMETER(	PSRPT=1)

INTEGER rather than enumeration type. Explicitly defined and required portion of conceptually unbounded range defined here.

surface approximation criteria

	<i>workstation dependent planar deviation in WC relative in DC</i>	<i>constant between knots planar deviation in NPC</i>	<i>chordal size in WC planar deviation in DC</i>	<i>chordal size in NPC relative in WC</i>	<i>chordal size in DC relative in NPC</i>
INTEGER	PWDSA,	PCBKSA,	PCSWSA,	PCNSA,	PCSDSA,
1	PPDWSA,	PPDNSA,	PPDDSA,	PRWSA,	PRNSA,
2	PRDSA				
PARAMETER(	PWDSA=1,	PCBKSA=2,	PCSWSA=3,	PCNSA=4,	PCSDSA=5,
1	PPDWSA=6,	PPDNSA=7,	PPDDSA=8,	PRWSA=9,	PRNSA=10,
2	PRDSA=11)				

INTEGER rather than enumeration type. Explicitly defined and required portion of conceptually unbounded range defined here.

source selector

	<i>colour aspect</i>	<i>vertex colour</i>	<i>vertex data</i>	<i>facet colour</i>	<i>facet data</i>
INTEGER	PSCASF,	PSVC,	PSVD,	PSFC,	PSFD
PARAMETER(	PSCASF=0,	PSVC=1,	PSVD=2,	PSFC=3,	PSFD=4)

trimming curve visibility flag

Uses the POFF/PON enumeration defined for edge flag and error handling mode.

vertex data flag

	<i>coordinate only colour/data</i>	<i>colour normal/data</i>	<i>normal colour/normal/data</i>	<i>data</i>	<i>colour/normal</i>
INTEGER	PCD,	PCDC,	PCDN,	PCDD,	PCDCN,
1	PCDCD,	PCDND,	PCDCND		
PARAMETER(	PCD=0,	PCDC=1,	PCDN=2,	PCDD=3,	PCDCN=4,
1	PCDCD=5,	PCDND=6,	PCDCND=7)		

Not defined in PHIGS PLUS but used to indicate presence of optional data for FORTRAN binding.

PHIGS PLUS functions. These names are used for error handling. The names are the same as the PHIGS PLUS function names except that the sentinel character 'P' is replaced by 'E'. The same function identification used for full FORTRAN 77.

INTEGER	EPLS3C,	EFAS3D,	EFASD,	ECA3P,	ESFAS3
PARAMETER(	EPLS3C=183,	EFAS3D=184,	EFASD=185,	ECA3P=186,	ESFAS3=187)
INTEGER	ESFASD,	ETS3D,	ETSD,	ETST3D,	ETSTD
PARAMETER(	ESFASD=188,	ETS3D=189,	ETSD=190,	ETST3D=191,	ETSTD=192)
INTEGER	EQM3D,	EQMD,	EBSC3,	EBSC3C,	EBSS3
PARAMETER(	EQM3D=193,	EQMD=194,	EBSC3=195,	EBSC3C=196,	EBSS3=197)
INTEGER	EBSS3D,	ESDMI,	ESRFI,	ESBII,	ESBDMI
PARAMETER(	EBSS3D=198,	ESDMI=199,	ESRFI=200,	ESBII=201,	ESBDMI=202)
INTEGER	ESBRFI,	ESPSI,	ESPLC,	ESPLSM,	ESPMC
PARAMETER(	ESBRFI=203,	ESPSI=204,	ESPLC=205,	ESPLSM=206,	ESPMC=207)
INTEGER	ESTXC,	ESFDM,	ESFCM,	ESIC,	ESISM
PARAMETER(	ESTXC=208,	ESFDM=209,	ESFCM=210,	ESIC=211,	ESISM=212)
INTEGER	ESDMM,	ESRFP,	ESRFM,	ESBIS,	ESBISI
PARAMETER(	ESDMM=213,	ESRFP=214,	ESRFM=215,	ESBIS=216,	ESBISI=217)
INTEGER	ESBIC,	ESBISM,	ESBDMM,	ESBRFP,	ESBRFM
PARAMETER(	ESBIC=218,	ESBISM=219,	ESBDMM=220,	ESBRFP=221,	ESBRFM=222)
INTEGER	ESLSS,	ESEDC,	ESCAC,	ESSAC,	ESPSC
PARAMETER(	ESLSS=223,	ESEDC=224,	ESCAC=225,	ESSAC=226,	ESPSC=227)
INTEGER	ESRCM,	ESDPCI,	ESDMI,	ESPLP,	ESPMP
PARAMETER(	ESRCM=228,	ESDPCI=229,	ESDMI=230,	ESPLP=231,	ESPMP=232)
INTEGER	ESTXRP,	ESIP,	ESEDP,	ESDMR,	ESRFR
PARAMETER(	ESTXRP=233,	ESIP=234,	ESEDP=235,	ESDMR=236,	ESRFR=237)
INTEGER	ESPSR,	ESPAP,	ESLSR,	ESDCR,	ESCMR
PARAMETER(	ESPSR=238,	ESPAP=239,	ESLSR=240,	ESDCR=241,	ESCMR=242)

12. List of the PHIGS PLUS function names

The complete list of PHIGS PLUS function names follows.

12.1. List of functions ordered alphabetically by bound name

PBSC3	BS-C-3	NON-UNIFORM B-SPLINE CURVE 3
PBSC3C	BS-C-3-C	NON-UNIFORM B-SPLINE CURVE 3 WITH COLOUR
PBS3	BS-S-3	NON-UNIFORM B-SPLINE SURFACE 3
PBS33D	BS-S-3-D	NON-UNIFORM B-SPLINE SURFACE 3 WITH DATA
PCA3P	C-A-3-P	CELL ARRAY 3 PLUS
PFAS3D	F-A-S-3-D	FILL AREA SET 3 WITH DATA
PFASD	F-A-S-D	FILL AREA SET WITH DATA
PPCSC	P-C-S-C	PACK COLOUR SPLINE CURVE
PPCSS	P-C-S-S	PACK COLOUR SPLINE SURFACE
PPDSS	P-D-S-S	PACK DATA SPLINE SURFACE
PPLS3C	PL-S-3-C	POLYLINE SET 3 WITH COLOUR
PPTC	P-T-C	PACK TRIMMING CURVE
PQBSSF	Q-BS-S-F	INQUIRE B-SPLINE SURFACE FACILITIES
PQCMF	Q-C-M-F	INQUIRE COLOUR MAPPING FACILITIES
PQCMMF	Q-C-M-M-F	INQUIRE COLOUR MAPPING METHOD FACILITIES
PQCMR	Q-C-M-R	INQUIRE COLOUR MAPPING REPRESENTATION
PQCMS	Q-C-M-S	INQUIRE COLOUR MAPPING STATE
PQCVF	Q-CV-F	INQUIRE CURVE FACILITIES
PQDCF	Q-D-C-F	INQUIRE DEPTH CUE FACILITIES
PQDCMF	Q-D-C-M-F	INQUIRE DIRECT COLOUR MODEL FACILITIES
PQDCR	Q-D-C-R	INQUIRE DEPTH CUE REPRESENTATION
PQDCWP	Q-DC-W-P	INQUIRE DYNAMICS OF WORKSTATION PLUS
PQDMF	Q-D-M-F	INQUIRE DATA MAPPING FACILITIES
PQDMR	Q-D-M-R	INQUIRE DATA MAPPING REPRESENTATION
PQECMI	Q-E-C-M-I	INQUIRE LIST element OF COLOUR MAPPING INDICES
PQEDCI	Q-E-D-C-I	INQUIRE LIST element OF DEPTH CUE INDICES
PQEDMI	Q-E-D-M-I	INQUIRE LIST element OF DATA MAPPING INDICES
PQEDP	Q-ED-P	INQUIRE EDGE REPRESENTATION PLUS
PQELSI	Q-E-L-S-I	INQUIRE LIST element OF LIGHT SOURCE INDICES
PQEFSI	Q-E-P-S-I	INQUIRE LIST element OF PARAMETRIC SURFACE INDICES
PQERFI	Q-E-R-I	INQUIRE LIST element OF REFLECTANCE INDICES
PQIFP	Q-I-F-P	INQUIRE INTERIOR FACILITIES PLUS
PQIP	Q-I-P	INQUIRE INTERIOR REPRESENTATION PLUS
PQLSF	Q-L-S-F	INQUIRE LIGHT SOURCE FACILITIES
PQLSR	Q-L-S-R	INQUIRE LIGHT SOURCE REPRESENTATION
PQM3D	Q-M-3-D	QUADRILATERAL MESH 3 WITH DATA
PQMD	Q-M-D	QUADRILATERAL MESH WITH DATA
PQPAP	Q-PA-P	INQUIRE PATTERN REPRESENTATION PLUS
PQPCMR	Q-P-C-M-R	INQUIRE PREDEFINED COLOUR MAPPING REPRESENTATION
PQPCR	Q-P-D-C-R	INQUIRE PREDEFINED DEPTH CUE REPRESENTATION
PQPDMR	Q-P-D-M-R	INQUIRE PREDEFINED DATA MAPPING REPRESENTATION
PQPEDP	Q-P-ED-P	INQUIRE PREDEFINED EDGE REPRESENTATION PLUS
PQPPI	Q-P-I-P	INQUIRE PREDEFINED INTERIOR REPRESENTATION PLUS
PQPLFP	Q-PL-F-P	INQUIRE POLYLINE FACILITIES PLUS
PQPLP	Q-PL-P	INQUIRE POLYLINE REPRESENTATION PLUS
PQPLSR	Q-P-L-S-R	INQUIRE PREDEFINED LIGHT SOURCE REPRESENTATION
PQPMF	Q-PM-P	INQUIRE POLYMARKER REPRESENTATION PLUS
PQPPAP	Q-P-PA-P	INQUIRE PREDEFINED PATTERN REPRESENTATION PLUS
PQPPLP	Q-P-PL-P	INQUIRE PREDEFINED POLYLINE REPRESENTATION PLUS
PQPPMP	Q-P-PM-P	INQUIRE PREDEFINED POLYMARKER REPRESENTATION PLUS
PQPFSR	Q-P-P-S-R	INQUIRE PREDEFINED PARAMETRIC SURFACE REPRESENTATION
PQPRFR	Q-P-RF-R	INQUIRE PREDEFINED REFLECTANCE REPRESENTATION
PQPSF	Q-P-S-F	INQUIRE PARAMETRIC SURFACE FACILITIES
PQPSR	Q-P-S-R	INQUIRE PARAMETRIC SURFACE REPRESENTATION
PQPTXP	Q-P-TX-P	INQUIRE PREDEFINED TEXT REPRESENTATION PLUS
PQRCMF	Q-R-C-M-F	INQUIRE RENDERING COLOUR MODEL FACILITIES
PQRFF	Q-RF-F	INQUIRE REFLECTANCE FACILITIES
PQRFR	Q-RF-R	INQUIRE REFLECTANCE REPRESENTATION

PQTCF	Q-T-C-F	INQUIRE TRIMMING CURVE FACILITIES
PQTXP	Q-TX-P	INQUIRE TEXT REPRESENTATION PLUS
PQWSLP	Q-W-S-L-P	INQUIRE WORKSTATION STATE TABLE LENGTHS PLUS
PSBDMI	S-B-D-M-I	SET BACK DATA MAPPING INDEX
PSBDMM	S-B-D-M-M	SET BACK DATA MAPPING METHOD
PSBIC	S-B-I-C	SET BACK INTERIOR COLOUR
PSBII	S-B-I-I	SET BACK INTERIOR INDEX
PSBIS	S-B-I-S	SET BACK INTERIOR STYLE
PSBISI	S-B-I-S-I	SET BACK INTERIOR STYLE INDEX
PSBISM	S-B-I-S-M	SET BACK INTERIOR SHADING METHOD
PSBRFI	S-B-RF-I	SET BACK REFLECTANCE INDEX
PSBRFM	S-B-RF-M	SET BACK REFLECTANCE MODEL
PSBRFP	S-B-RF-P	SET BACK REFLECTANCE PROPERTIES
PSCAC	S-C-A-C	SET CURVE APPROXIMATION CRITERIA
PSCMI	S-C-M-I	SET COLOUR MAPPING INDEX
PSCMR	S-C-M-R	SET COLOUR MAPPING REPRESENTATION
PSDCI	S-D-C-I	SET DEPTH CUE INDEX
PSDCR	S-D-C-R	SET DEPTH CUE REPRESENTATION
PSDMI	S-D-M-I	SET DATA MAPPING INDEX
PSDMM	S-D-M-M	SET DATA MAPPING METHOD
PSDMR	S-D-M-R	SET DATA MAPPING REPRESENTATION
PSEDC	S-ED-C	SET EDGE COLOUR
PSEDP	S-ED-P	SET EDGE REPRESENTATION PLUS
PSFAS3	S-F-A-S-3	SET OF FILL AREA SETS 3 WITH DATA
PSFASD	S-F-A-S-D	SET OF FILL AREA SETS WITH DATA
PSFCM	S-F-C-M	SET FACET CULLING MODE
PSFDM	S-F-D-M	SET FACET DISTINGUISHING MODE
PSIC	S-I-C	SET INTERIOR COLOUR
PSIP	S-I-P	SET INTERIOR REPRESENTATION PLUS
PSISM	S-I-S-M	SET INTERIOR SHADING METHOD
PSLSR	S-L-S-R	SET LIGHT SOURCE REPRESENTATION
PSLSS	S-L-S-S	SET LIGHT SOURCE STATE
PSPAP	S-PA-P	SET PATTERN REPRESENTATION PLUS
PSPLC	S-PL-C	SET POLYLINE COLOUR
PSPLP	S-PL-P	SET POLYLINE REPRESENTATION PLUS
PSPLSM	S-PL-S-M	SET POLYLINE SHADING METHOD
PSPMC	S-PM-C	SET POLYMARKER COLOUR
PSPMP	S-PM-P	SET POLYMARKER REPRESENTATION PLUS
PSPSC	S-P-S-C	SET PARAMETRIC SURFACE CHARACTERISTICS
PSPSI	S-P-S-I	SET PARAMETRIC SURFACE INDEX
PSPSR	S-P-S-R	SET PARAMETRIC SURFACE REPRESENTATION
PSRCM	S-R-C-M	SET RENDERING COLOUR MODEL
PSRFI	S-RF-I	SET REFLECTANCE INDEX
PSRFM	S-RF-M	SET REFLECTANCE MODEL
PSRFP	S-RF-P	SET REFLECTANCE PROPERTIES
PSRFR	S-RF-R	SET REFLECTANCE REPRESENTATION
PSSAC	S-S-A-C	SET SURFACE APPROXIMATION CRITERIA
PSTXC	S-TX-C	SET TEXT COLOUR
PSTXRP	S-TX-R-P	SET TEXT REPRESENTATION PLUS
PTS3D	T-S-3-D	TRIANGLE SET 3 WITH DATA
PTSD	T-S-D	TRIANGLE SET WITH DATA
PTST3D	T-ST-3-D	TRIANGLE STRIP 3 WITH DATA
PTSTD	T-ST-D	TRIANGLE STRIP WITH DATA
PUCSC	U-C-S-C	UNPACK COLOUR SPLINE CURVE
PUCSS	U-C-S-S	UNPACK COLOUR SPLINE SURFACE
PUDSS	U-D-S-S	UNPACK DATA SPLINE SURFACE
PUTC	U-T-C	UNPACK TRIMMING CURVE

12.2 List of functions ordered alphabetically by PHIGS PLUS function name

PCA3P	C-A-3-P	CELL ARRAY 3 PLUS
PFAS3D	F-A-S-3-D	FILL AREA SET 3 WITH DATA
PFASD	F-A-S-D	FILL AREA SET WITH DATA
PQBSSF	Q-BS-S-F	INQUIRE B-SPLINE SURFACE FACILITIES
PQCMF	Q-C-M-F	INQUIRE COLOUR MAPPING FACILITIES
PQCMMF	Q-C-M-M-F	INQUIRE COLOUR MAPPING METHOD FACILITIES
PQCMR	Q-C-M-R	INQUIRE COLOUR MAPPING REPRESENTATION
PQCMS	Q-C-M-S	INQUIRE COLOUR MAPPING STATE
PQCVF	Q-CV-F	INQUIRE CURVE FACILITIES
PQDMF	Q-D-M-F	INQUIRE DATA MAPPING FACILITIES
PQDMR	Q-D-M-R	INQUIRE DATA MAPPING REPRESENTATION
PQDCF	Q-D-C-F	INQUIRE DEPTH CUE FACILITIES
PQDCR	Q-D-C-R	INQUIRE DEPTH CUE REPRESENTATION
PQDCMF	Q-D-C-M-F	INQUIRE DIRECT COLOUR MODEL FACILITIES
PQDCWP	Q-DC-W-P	INQUIRE DYNAMICS OF WORKSTATION PLUS
PQEDP	Q-ED-P	INQUIRE EDGE REPRESENTATION PLUS
PQIFP	Q-I-F-P	INQUIRE INTERIOR FACILITIES PLUS
PQIP	Q-I-P	INQUIRE INTERIOR REPRESENTATION PLUS
PQLSF	Q-L-S-F	INQUIRE LIGHT SOURCE FACILITIES
PQLSR	Q-L-S-R	INQUIRE LIGHT SOURCE REPRESENTATION
PQECMI	Q-E-C-M-I	INQUIRE LIST element OF COLOUR MAPPING INDICES
PQEDMI	Q-E-D-M-I	INQUIRE LIST element OF DATA MAPPING INDICES
PQEDCI	Q-E-D-C-I	INQUIRE LIST element OF DEPTH CUE INDICES
PQELSI	Q-E-L-S-I	INQUIRE LIST element OF LIGHT SOURCE INDICES
PQEPSI	Q-E-P-S-I	INQUIRE LIST element OF PARAMETRIC SURFACE INDICES
PQERFI	Q-E-R-I	INQUIRE LIST element OF REFLECTANCE INDICES
PQPSF	Q-P-S-F	INQUIRE PARAMETRIC SURFACE FACILITIES
PQPSR	Q-P-S-R	INQUIRE PARAMETRIC SURFACE REPRESENTATION
PQPAP	Q-PA-P	INQUIRE PATTERN REPRESENTATION PLUS
PQPLFP	Q-PL-F-P	INQUIRE POLYLINE FACILITIES PLUS
PQPLP	Q-PL-P	INQUIRE POLYLINE REPRESENTATION PLUS
PQPMF	Q-PM-P	INQUIRE POLYMARKER REPRESENTATION PLUS
PQPCMR	Q-P-C-M-R	INQUIRE PREDEFINED COLOUR MAPPING REPRESENTATION
PQPDMR	Q-P-D-M-R	INQUIRE PREDEFINED DATA MAPPING REPRESENTATION
PQPDCR	Q-P-D-C-R	INQUIRE PREDEFINED DEPTH CUE REPRESENTATION
PQPEDP	Q-P-ED-P	INQUIRE PREDEFINED EDGE REPRESENTATION PLUS
PQPIR	Q-P-I-P	INQUIRE PREDEFINED INTERIOR REPRESENTATION PLUS
PQPLSR	Q-P-L-S-R	INQUIRE PREDEFINED LIGHT SOURCE REPRESENTATION
PQPPSR	Q-P-P-S-R	INQUIRE PREDEFINED PARAMETRIC SURFACE REPRESENTATION
PQPPAP	Q-P-PA-P	INQUIRE PREDEFINED PATTERN REPRESENTATION PLUS
PQPPLP	Q-P-PL-P	INQUIRE PREDEFINED POLYLINE REPRESENTATION PLUS
PQPPMP	Q-P-PM-P	INQUIRE PREDEFINED POLYMARKER REPRESENTATION PLUS
PQPRFR	Q-P-RF-R	INQUIRE PREDEFINED REFLECTANCE REPRESENTATION
PQPTXP	Q-P-TX-P	INQUIRE PREDEFINED TEXT REPRESENTATION PLUS
PQRFF	Q-RF-F	INQUIRE REFLECTANCE FACILITIES
PQRFR	Q-RF-R	INQUIRE REFLECTANCE REPRESENTATION
PQRCMF	Q-R-C-M-F	INQUIRE RENDERING COLOUR MODEL FACILITIES
PQTXP	Q-TX-P	INQUIRE TEXT REPRESENTATION PLUS
PQTCF	Q-T-C-F	INQUIRE TRIMMING CURVE FACILITIES
PQWSLP	Q-W-S-L-P	INQUIRE WORKSTATION STATE TABLE LENGTHS PLUS
PBSC3	BS-C-3	NON-UNIFORM B-SPLINE CURVE 3
PBSCC3	BS-C-3-C	NON-UNIFORM B-SPLINE CURVE 3 WITH COLOUR
PBSS3	BS-S-3	NON-UNIFORM B-SPLINE SURFACE 3
PBSSD3	BS-S-3-D	NON-UNIFORM B-SPLINE SURFACE 3 WITH DATA
PPCSC	P-C-S-C	PACK COLOUR SPLINE CURVE
PPCSS	P-C-S-S	PACK COLOUR SPLINE SURFACE
PPDSS	P-D-S-S	PACK DATA SPLINE SURFACE
PPTC	P-T-C	PACK TRIMMING CURVE
PPLS3C	PL-S-3-C	POLYLINE SET 3 WITH COLOUR
PQM3D	Q-M-3-D	QUADRILATERAL MESH 3 WITH DATA
PQMD	Q-M-D	QUADRILATERAL MESH WITH DATA
PSBDMI	S-B-D-M-I	SET BACK DATA MAPPING INDEX

PSBDDMM	S-B-D-M-M	SET BACK DATA MAPPING METHOD
PSBIC	S-B-I-C	SET BACK INTERIOR COLOUR
PSBII	S-B-I-I	SET BACK INTERIOR INDEX
PSBISM	S-B-I-S-M	SET BACK INTERIOR SHADING METHOD
PSBIS	S-B-I-S	SET BACK INTERIOR STYLE
PSBISI	S-B-I-S-I	SET BACK INTERIOR STYLE INDEX
PSBRFI	S-B-RF-I	SET BACK REFLECTANCE INDEX
PSBRFM	S-B-RF-M	SET BACK REFLECTANCE MODEL
PSBRFP	S-B-RF-P	SET BACK REFLECTANCE PROPERTIES
PSCMI	S-C-M-I	SET COLOUR MAPPING INDEX
PSCMR	S-C-M-R	SET COLOUR MAPPING REPRESENTATION
PSCAC	S-C-A-C	SET CURVE APPROXIMATION CRITERIA
PSDMI	S-D-M-I	SET DATA MAPPING INDEX
PSDMM	S-D-M-M	SET DATA MAPPING METHOD
PSDMR	S-D-M-R	SET DATA MAPPING REPRESENTATION
PSDCI	S-D-C-I	SET DEPTH CUE INDEX
PSDCR	S-D-C-R	SET DEPTH CUE REPRESENTATION
PSEDC	S-ED-C	SET EDGE COLOUR
PSEDP	S-ED-P	SET EDGE REPRESENTATION PLUS
PSFCM	S-F-C-M	SET FACET CULLING MODE
PSFDM	S-F-D-M	SET FACET DISTINGUISHING MODE
PSIC	S-I-C	SET INTERIOR COLOUR
PSIP	S-I-P	SET INTERIOR REPRESENTATION PLUS
PSISM	S-I-S-M	SET INTERIOR SHADING METHOD
PSLSR	S-L-S-R	SET LIGHT SOURCE REPRESENTATION
PSLSS	S-L-S-S	SET LIGHT SOURCE STATE
PSFAS3	S-F-A-S-3	SET OF FILL AREA SETS 3 WITH DATA
PSFASD	S-F-A-S-D	SET OF FILL AREA SETS WITH DATA
PSPSC	S-P-S-C	SET PARAMETRIC SURFACE CHARACTERISTICS
PSPSI	S-P-S-I	SET PARAMETRIC SURFACE INDEX
PSPSR	S-P-S-R	SET PARAMETRIC SURFACE REPRESENTATION
PSPAP	S-PA-P	SET PATTERN REPRESENTATION PLUS
PSPLC	S-PL-C	SET POLYLINE COLOUR
PSPLP	S-PL-P	SET POLYLINE REPRESENTATION PLUS
PSPLSM	S-PL-S-M	SET POLYLINE SHADING METHOD
PSPMC	S-PM-C	SET POLYMARKER COLOUR
PSPMP	S-PM-P	SET POLYMARKER REPRESENTATION PLUS
PSRFI	S-RF-I	SET REFLECTANCE INDEX
PSRFM	S-RF-M	SET REFLECTANCE MODEL
PSRFP	S-RF-P	SET REFLECTANCE PROPERTIES
PSRFR	S-RF-R	SET REFLECTANCE REPRESENTATION
PSRCM	S-R-C-M	SET RENDERING COLOUR MODEL
PSSAC	S-S-A-C	SET SURFACE APPROXIMATION CRITERIA
PSTXC	S-TX-C	SET TEXT COLOUR
PSTXRP	S-TX-R-P	SET TEXT REPRESENTATION PLUS
PTS3D	T-S-3-D	TRIANGLE SET 3 WITH DATA
PTSD	T-S-D	TRIANGLE SET WITH DATA
PTST3D	T-ST-3-D	TRIANGLE STRIP 3 WITH DATA
PTSTD	T-ST-D	TRIANGLE STRIP WITH DATA
PUCSC	U-C-S-C	UNPACK COLOUR SPLINE CURVE
PUCSS	U-C-S-S	UNPACK COLOUR SPLINE SURFACE
PUDSS	U-D-S-S	UNPACK DATA SPLINE SURFACE
PUTC	U-T-C	UNPACK TRIMMING CURVE

13 The PHIGS PLUS function interface

13.1 General principles

For each PHIGS PLUS function the corresponding FORTRAN SUBROUTINE declaration is given. The name of the PHIGS PLUS function is listed, followed by its FORTRAN name and the corresponding parameters. After that, the list of parameters is described by type and a brief identifying phrase.

For the mapping of ENUMERATION types see clause 6 and clause 11.

13.2 Output primitive functions

POLYLINE SET 3 WITH COLOUR

SUBROUTINE PPLS3C(VFLAG,CTYPE,NCC,NPL,IXA,PXA,PYA,PZA,VCOLI,VCOLR)

Input Parameters:

INTEGER VFLAG	data per vertex data flag (PCD,PCDC)
INTEGER CTYPE	colour type
INTEGER NCC	number of components of colour value
INTEGER NPL	number of point lists
INTEGER IXA(NPL)	array of end indices for point lists
REAL PXA(IXA(NPL)),PYA(IXA(NPL)),PZA(IXA(NPL))	coordinates of points(MC)
INTEGER VCOLI(IXA(NPL))	vertex colour indices
REAL VCOLR(NCC*IXA(NPL))	vertex colour values

FILL AREA SET 3 WITH DATA

```

SUBROUTINE PFAS3D(FFLAG,EFLAG,VFLAG,CTYPE,NCC,FCOLI,FCOLR,FXA,
*FNXA,FNZA,FDLEN,FDATA,NPL,IXA,EDATA,PXA,PYA,PZA,VCOLI,VCOLR,
*VNXA,VNZA,VDLEN,VDATA)

```

Input Parameters:

INTEGER FFLAG	data per facet data flag (PFNO,PFC,PFN,PFDP,PCFN,PFCD,PFND,PCFND)
INTEGER EFLAG	data per edge data flag (PEN,PEVF)
INTEGER VFLAG	data per vertex data flag(PCD,PCDC,PCDN,PCDD,PCDCN,PCDCD,PCDND,PCDCND)
INTEGER CTYPE	colour type
INTEGER NCC	number of components of colour value
INTEGER FCOLI	facet colour index
REAL FCOLR(NCC)	facet colour values
REAL FXA,FNZA,FNZA	facet normal data(MC)
INTEGER FDLEN	length of application-specific data list per facet
REAL FDATA(FDLEN)	facet application-specific data
INTEGER NPL	number of point lists
INTEGER IXA(NPL)	array of end indices for point lists
INTEGER EDATA(IXA(NPL))	edge data(POFF,PON)
REAL PXA(IXA(NPL)),PYA(IXA(NPL)),PZA(IXA(NPL))	coordinates of points(MC)
INTEGER VCOLI(IXA(NPL))	vertex colour indices
REAL VCOLR(NCC*IXA(NPL))	vertex colour values
REAL VNXA(IXA(NPL)),VNZA(IXA(NPL)),VNZA(IXA(NPL))	vertex normal data(MC)
INTEGER VDLEN	length of application-specific data list per vertex
REAL VDATA(VDLEN*IXA(NPL))	vertex application-specific data

FILL AREA SET WITH DATA

```
SUBROUTINE PFASD(FFLAG,EFLAG,VFLAG,CTYPE,NCC,FCOLI,FCOLR,FXA,
*FNXA,FNZA,FDLEN,FDATA,NPL,IXA,EDATA,PXA,PYA,VCOLI,VCOLR,VNXA,
*VNXA,VNZA,VDLEN,VDATA)
```

Input Parameters:

INTEGER FFLAG	data per facet data flag (PFNO,PFC,PFN,PFD,PFCN,PFCN,PFCN,PFCN,PFCN,PFCN)
INTEGER EFLAG	data per edge data flag (PEN,PEN,PEN,PEN,PEN,PEN,PEN,PEN,PEN,PEN)
INTEGER VFLAG	data per vertex data flag(PCD,PCDC,PCDN,PCDD,PCDCN,PCDCD,PCDND,PCDCND)
INTEGER CTYPE	colour type
INTEGER NCC	number of components of colour value
INTEGER FCOLI	facet colour index
REAL FCOLR(NCC)	facet colour values
REAL FNXA,FNZA,FDLEN	facet normal data(MC)
INTEGER FDLEN	length of application-specific data list per facet
REAL FDATA(FDLEN)	facet application-specific data
INTEGER NPL	number of points lists
INTEGER IXA(NPL)	array of end indices for point lists
INTEGER EDATA(IXA(NPL))	edge data(POFF,PON)
REAL PXA(IXA(NPL)),PYA(IXA(NPL))	coordinates of points(MC)
INTEGER VCOLI(IXA(NPL))	vertex colour indices
REAL VCOLR(NCC*IXA(NPL))	vertex colour values
REAL VNXA(IXA(NPL)),VNZA(IXA(NPL)),VNZA(IXA(NPL))	vertex normal data(MC)
INTEGER VDLEN	length of application-specific data list per vertex
REAL VDATA(VDLEN*IXA(NPL))	vertex application-specific data

CELL ARRAY 3 PLUS

```
SUBROUTINE PCA3P(CPXA,CPYA,CPZA,DIMX,DIMY,ISC,ISR,DX,DY,CTYPE,
*NCC,COLIA,COLRA)
```

Input Parameters:

REAL CPXA(3),CPYA(3),CPZA(3)	cell parallelogram(P,Q,R)(MC)
INTEGER DIMX,DIMY	the number of columns and number of rows in COLIA or COLRA
INTEGER ISC,ISR	indices of start column, start row
INTEGER DX,DY	number of columns,number of rows
INTEGER CTYPE	colour type
INTEGER NCC	number of components of colour value
INTEGER COLIA(DIMX,DIMY)	colour index array
REAL COLRA(NCC*DIMX*DIMY)	colour value array

SET OF FILL AREA SETS 3 WITH DATA

```

SUBROUTINE PSFAS3(FFLAG,EFLAG,VFLAG,CTYPE,NCC,NFS,FCOLI,FCOLR,
*FNXA,FNYA,FNZA,FDLEN,FDATA,NF,NP,IXA,EDATA,PXA,PYA,PZA,VCOLI,
*VCOLR,VNXA,VNYA,VNZA,VDLEN,VDATA,VIND)

```

Input Parameters:

INTEGER FFLAG	data per facet data flag (PFNO, PFC, PFN, PFD, PFCN, PFCN, PFCN, PFCN, PFCN, PFCN)
INTEGER EFLAG	data per edge data flag (PENNO, PEV)
INTEGER VFLAG	data per vertex data flag (PCD, PCDC, PCDN, PCDD, PCDCN, PCDCD, PCDCN, PCDCN)
INTEGER CTYPE	colour type
INTEGER NCC	number of components of colour value
INTEGER NFS	number of fill area sets
INTEGER FCOLI(NFS)	facet colour indices
REAL FCOLR(NCC*NFS)	facet colour values
REAL FNXA(NFS), FNYA(NFS), FNZA(NFS)	facet normal data (MC)
INTEGER FDLEN	length of application-specific data list per facet
REAL FDATA(FDLEN*NFS)	facet application-specific data
INTEGER NF(NFS)	array of end vertex indices in IXA for each fill area set
INTEGER NP	number of points
INTEGER IXA(NF(NFS))	array of end vertex indices in VIND for each fill area
INTEGER EDATA(IXA(NF(NFS)))	edge data (POFF, PON)
REAL PXA(NP), PYA(NP), PZA(NP)	coordinates of points (MC)
INTEGER VCOLI(NP)	vertex colour indices
REAL VCOLR(NCC*NP)	vertex colour values
REAL VNXA(NP), VNYA(NP), VNZA(NP)	vertex normal data (MC)
INTEGER VDLEN	length of application-specific data list per vertex
REAL VDATA(VDLEN*NP)	vertex application-specific data
INTEGER VIND(IXA(NF(NFS)))	vertex indices for each fill area

SET OF FILL AREA SETS WITH DATA

SUBROUTINE PSFASD(FFLAG,EFLAG,VFLAG,CTYPE,NCC,NFS,FCOLI,FCOLR,
 *FNXA,FNYA,FNZA,FDLEN,FDATA,NF,NP,IXA,EDATA,PXA,PYA,VCOLI,VCOLR,
 *VNXA,VNYA,VNZA,VDLEN,VDATA,VIND)

Input Parameters:

INTEGER FFLAG	data per facet data flag (PFNO,PFC,PFN,PFD,PFCN,PFCD,PFND,PFCND)
INTEGER EFLAG	data per edge data flag (PENO,PEVF)
INTEGER VFLAG	data per vertex data flag(PCD,PCDC,PCDN, PCDD,PCDCN,PCDCD,PCDND,PCDCND)
INTEGER CTYPE	colour type
INTEGER NCC	number of components of colour value
INTEGER NFS	number of fill area sets
INTEGER FCOLI(NFS)	facet colour indices
REAL FCOLR(NCC*NFS)	facet colour values
REAL FNXA(NFS),FNYA(NFS),FNZA(NFS)	facet normal data(MC)
INTEGER FDLEN	length of application-specific data list per facet
REAL FDATA(FDLEN*NFS)	facet application-specific data
INTEGER NF(NFS)	array of end indices in IXA for each fill area set
INTEGER NP	number of points
INTEGER IXA(NF(NFS))	array of end vertex indices in VIND for each fill area
INTEGER EDATA(IXA(NF(NFS)))	edge data(POFF,PON)
REAL PXA(NP),PYA(NP)	coordinates of points(MC)
INTEGER VCOLI(NP)	vertex colour indices
REAL VCOLR(NCC*NP)	vertex colour values
REAL VNXA(NP),VNYA(NP),VNZA(NP)	vertex normal data(MC)
INTEGER VDLEN	length of application-specific data list per vertex
REAL VDATA(VDLEN*NP)	vertex application-specific data
INTEGER VIND(IXA(NF(NFS)))	vertex indices for each fill area

TRIANGLE SET 3 WITH DATA

```

SUBROUTINE PTS3D(FFLAG,EFLAG,VFLAG,CTYPE,NCC,NTRI,FCOLI,FCOLR,
*FNXA,FNYA,FNZA,FDLEN,FDATA,NP,EDATA,PXA,PYA,PZA,VCOLI,VCOLR,
*VNXA,VNYA,VNZA,VDLEN,VDATA,VIND)

```

Input Parameters:

INTEGER FFLAG	data per facet data flag (PFNO,PFC,PFN,PFD,PFCN,PFCD,PFND,PFCND)
INTEGER EFLAG	data per edge data flag (PEN0,PEVF)
INTEGER VFLAG	data per vertex data flag(PCD,PCDC,PCDN,PCDD,PCDCN,PCDCD,PCDND,PCDCND)
INTEGER CTYPE	colour type
INTEGER NCC	number of components of colour value
INTEGER NTRI	number of triangles
INTEGER FCOLI(NTRI)	facet colour indices
REAL FCOLR(NCC*NTRI)	facet colour values
REAL FNXA(NTRI),FNYA(NTRI),FNZA(NTRI)	facet normal data(MC)
INTEGER FDLEN	length of application-specific data list per facet
REAL FDATA(FDLEN*NTRI)	facet application-specific data
INTEGER NP	number of points
INTEGER EDATA(3*NTRI)	edge data(POFF,PON)
REAL PXA(NP),PYA(NP),PZA(NP)	coordinates of points(MC)
INTEGER VCOLI(NP)	vertex colour indices
REAL VCOLR(NCC*NP)	vertex colour values
REAL VNXA(NP),VNYA(NP),VNZA(NP)	vertex normal data(MC)
INTEGER VDLEN	length of application-specific data list per vertex
REAL VDATA(VDLEN*NP)	vertex application-specific data
INTEGER VIND(NTRI*3)	vertex indices

TRIANGLE SET WITH DATA

```

SUBROUTINE PTSD(FFLAG,EFLAG,VFLAG,CTYPE,NCC,NTRI,FCOLI,FCOLR,
*FNXA,FNYA,FNZA,FDLEN,FDATA,NP,EDATA,PXA,PYA,VCOLI,VCOLR,VNXA,
*VNZA,VNZA,VDLEN,VDATA,VIND)

```

Input Parameters:

INTEGER FFLAG	data per facet data flag (PFNO,PFC,PFN,PFID,PFCN,PFCD,PFND,PFCND)
INTEGER EFLAG	data per edge data flag (PEN0,PEVF)
INTEGER VFLAG	data per vertex data flag(PCD,PCDC,PCDN, PCDD,PCDCN,PCDCD,PCDND,PCDCND)
INTEGER CTYPE	colour type
INTEGER NCC	number of components of colour value
INTEGER NTRI	number of triangles
INTEGER FCOLI(NTRI)	facet colour indices
REAL FCOLR(NCC*NTRI)	facet colour values
REAL FNXA(NTRI),FNYA(NTRI),FNZA(NTRI)	facet normal data(MC)
INTEGER FDLEN	length of application-specific data list per facet
REAL FDATA(FDLEN*NTRI)	facet application-specific data
INTEGER NP	number of points
INTEGER EDATA(3*NTRI)	edge data(POFF,PON)
REAL PXA(NP),PYA(NP)	coordinates of points(MC)
INTEGER VCOLI(NP)	vertex colour indices
REAL VCOLR(NCC*NP)	vertex colour values
REAL VNXA(NP),VNZA(NP),VNZA(NP)	vertex normal data(MC)
INTEGER VDLEN	length of application-specific data list per vertex
REAL VDATA(VDLEN*NP)	vertex application-specific data
INTEGER VIND(NTRI*3)	vertex indices

TRIANGLE STRIP 3 WITH DATA

```

SUBROUTINE PTST3D(FFLAG,EFLAG,VFLAG,CTYPE,NCC,NP,FCOLI,FCOLR,
*FNXA,FNYA,FNZA,FDLEN,FDATA,EDATA,PXA,PYA,PZA,VCOLI,VCOLR,VNXA,
*VNYA,VNZA,VDLEN,VDATA)

```

Input Parameters:

INTEGER FFLAG	data per facet data flag (PFNO,PFC,PFN,PFD,PFCN,PFCN,PFCN,PFCN)
INTEGER EFLAG	data per edge data flag (PENNO,PEVF)
INTEGER VFLAG	data per vertex data flag(PCD,PCDC,PCDN, PCDD,PCDCN,PCDCD,PCDND,PCDCND)
INTEGER CTYPE	colour type
INTEGER NCC	number of components of colour value
INTEGER NP	number of points
INTEGER FCOLI(NP-2)	facet colour indices
REAL FCOLR(NCC*(NP-2))	facet colour values
REAL FNXA(NP-2),FNYA(NP-2),FNZA(NP-2)	facet normal data(MC)
INTEGER FDLEN	length of application-specific data list per facet
REAL FDATA(FDLEN*(NP-2))	facet application-specific data
INTEGER EDATA(2*NP-3)	edge data(POFF,PON)
REAL PXA(NP),PYA(NP),PZA(NP)	coordinates of points(MC)
INTEGER VCOLI(NP)	vertex colour indices
REAL VCOLR(NCC*NP)	vertex colour values
REAL VNXA(NP),VNYA(NP),VNZA(NP)	vertex normal data(MC)
INTEGER VDLEN	length of application-specific data list per vertex
REAL VDATA(VDLEN*NP)	vertex application-specific data

TRIANGLE STRIP WITH DATA

```

SUBROUTINE PTSTD(FFLAG,EFLAG,VFLAG,CTYPE,NCC,NP,FCOLI,FCOLR,
*FNXA,FNYA,FNZA,FDLEN,FDATA,EDATA,PXA,PYA,VCOLI,VCOLR,VNXA,VNYA,
*VNZA,VDLEN,VDATA)

```

Input Parameters:

INTEGER FFLAG	data per facet data flag (PFNO,PFC,PFN,PFD,PFCN,PFCD,PFND,PFCND)
INTEGER EFLAG	data per edge data flag (PEN,PEVF)
INTEGER VFLAG	data per vertex data flag(PCD,PCDC,PCDN,PCDD,PCDCN,PCDCD,PCDND,PCDCND)
INTEGER CTYPE	colour type
INTEGER NCC	number of components of colour value
INTEGER NP	number of points
INTEGER FCOLI(NP-2)	facet colour indices
REAL FCOLR(NCC*(NP-2))	facet colour values
REAL FNXA(NP-2),FNYA(NP-2),FNZA(NP-2)	facet normal data(MC)
INTEGER FDLEN	length of application-specific data list per facet
REAL FDATA(FDLEN*(NP-2))	facet application-specific data
INTEGER EDATA(2*NP-3)	edge data(POFF,PON)
REAL PXA(NP),PYA(NP)	coordinates of points(MC)
INTEGER VCOLI(NP)	vertex colour indices
REAL VCOLR(NCC*NP)	vertex colour values
REAL VNXA(NP),VNYA(NP),VNZA(NP)	vertex normal data(MC)
INTEGER VDLEN	length of application-specific data list per vertex
REAL VDATA(VDLEN*NP)	vertex application-specific data

QUADRILATERAL MESH 3 WITH DATA

```

SUBROUTINE PQM3D(FFLAG,EFLAG,VFLAG,CTYPE,NCC,NC,NR,FCOLI,FCOLR,
*FNXA,FNYA,FNZA,FDLEN,FDATA,EDATA,PXA,PYA,PZA,VCOLI,VCOLR,VNXA,
*VNYA,VNZA,VDLEN,VDATA)

```

Input Parameters:

INTEGER FFLAG	data per facet data flag (PFNO,PFC,PFN,PFDP,PCFN,PCFD,PFND,PCFND)
INTEGER EFLAG	data per edge data flag (PEN,PEVF)
INTEGER VFLAG	data per vertex data flag(PCD,PCDC,PCDN,PCDD,PCDCN,PCDCD,PCDND,PCDCND)
INTEGER CTYPE	colour type
INTEGER NCC	number of components of colour value
INTEGER NC,NR	number of columns,number of rows
INTEGER FCOLI((NC-1)*(NR-1))	facet colour indices
REAL FCOLR(NCC*(NC-1)*(NR-1))	facet colour values
REAL FNXA((NC-1)*(NR-1)),FNYA((NC-1)*(NR-1)),FNZA((NC-1)*(NR-1))	facet normal data(MC)
INTEGER FDLEN	length of application-specific data list per facet
REAL FDATA(FDLEN*(NC-1)*(NR-1))	facet application-specific data
INTEGER EDATA(2*NC*NR)	edge data(POFF,PON)
REAL PXA(NC*NR),PYA(NC*NR),PZA(NC*NR)	coordinates of points(MC)
INTEGER VCOLI(NC*NR)	vertex colour indices
REAL VCOLR(NCC*NC*NR)	vertex colour values
REAL VNXA(NC*NR),VNYA(NC*NR),VNZA(NC*NR)	vertex normal data(MC)
INTEGER VDLEN	length of application-specific data list per vertex
REAL VDATA(VDLEN*NC*NR)	vertex application-specific data

QUADRILATERAL MESH WITH DATA

```

SUBROUTINE PQMD(FFLAG,EFLAG,VFLAG,CTYPE,NCC,NC,NR,FCOLI,FCOLR,
*FNXA,FNYA,FNZA,FDLEN,FDATA,EDATA,PXA,PYA,VCOLI,VCOLR,VNXA,
*VNYA,VNZA,VDLEN,VDATA)

```

Input Parameters:

INTEGER FFLAG	data per facet data flag (PFNO,PFC,PFN,PFD,PFCN,PFCD,PFND,PFCND)
INTEGER EFLAG	data per edge data flag (PEN0,PEVF)
INTEGER VFLAG	data per vertex data flag(PCD,PCDC,PCDN,PCDD,PCDCN,PCDCD,PCDND,PCDCND)
INTEGER CTYPE	colour type
INTEGER NCC	number of components of colour value
INTEGER NC,NR	number of columns,number of rows
INTEGER FCOLI((NC-1)*(NR-1))	facet colour indices
REAL FCOLR(NCC*(NC-1)*(NR-1))	facet colour values
REAL FNXA((NC-1)*(NR-1)),FNYA((NC-1)*(NR-1)),FNZA((NC-1)*(NR-1))	facet normal data(MC)
INTEGER FDLEN	length of application-specific data list per facet
REAL FDATA(FDLEN*(NC-1)*(NR-1))	facet application-specific data
INTEGER EDATA(2*NC*NR)	edge data(POFF,PON)
REAL PXA(NC*NR),PYA(NC*NR)	coordinates of points(MC)
INTEGER VCOLI(NC*NR)	vertex colour indices
REAL VCOLR(NCC*NC*NR)	vertex colour values
REAL VNXA(NC*NR),VNZA(NC*NR),VNZA(NC*NR)	vertex normal data(MC)
INTEGER VDLEN	length of application-specific data list per vertex
REAL VDATA(VDLEN*NC*NR)	vertex application-specific data

NON-UNIFORM B-SPLINE CURVE 3

SUBROUTINE PBSC3(SORD,NKA,KNOTS,PARL,RTYPE,NCP,PXA,PYA,PZA,PWA)

Input Parameters:

INTEGER SORD	spline order
INTEGER NKA	number of knots
REAL KNOTS(NKA)	knots
REAL PARL(2)	parameter range limits
INTEGER RTYPE	rationality (PRAT,PNRAT)
INTEGER NCP	number of control points
REAL PXA(NCP),PYA(NCP),PZA(NCP),PWA(NCP)	control points(MC)

NON-UNIFORM B-SPLINE CURVE 3 WITH COLOUR

SUBROUTINE PBSC3C(SORD,NKA,KNOTS,PARL,RTYPE,NCP,PXA,PYA,PZA,PWA
*CSCLDR,CSCREC)

Input Parameters:

INTEGER SORD	spline order
INTEGER NKA	number of knots
REAL KNOTS(NKA)	knots
REAL PARL(2)	parameter range limits
INTEGER RTYPE	rationality (PRAT,PNRAT)
INTEGER NCP	number of control points
REAL PXA(NCP),PYA(NCP),PZA(NCP),PWA(NCP)	control points(MC)
INTEGER CSCLDR	number of array elements used in CSCREC
CHARACTER*80 CSCREC(CSCLDR)	colour spline curve data record ¹

NON-UNIFORM B-SPLINE SURFACE 3

SUBROUTINE PBSS3(USORD,VSORD,UNKA,VNKA,UKNOTS,VKNOTS,RTYPE,
*UNCP,VNCP,PXA,PYA,PZA,PWA,TCLDR,TCREC)

Input Parameters:

INTEGER USORD	u spline order
INTEGER VSORD	v spline order
INTEGER UNKA	number of knots for u
INTEGER VNKA	number of knots for v
REAL UKNOTS(UNKA)	u knots
REAL VKNOTS(VNKA)	v knots
INTEGER RTYPE	rationality (PRAT,PNRAT)
INTEGER UNCP	u number of control points dimension
INTEGER VNCP	v number of control points dimension
REAL PXA(UNCP*VNCP),PYA(UNCP*VNCP),PZA(UNCP*VNCP),PWA(UNCP*VNCP)	control points(MC)
INTEGER TCLDR	number of array elements used in TCREC

¹See PACK COLOUR SPLINE CURVE and UNPACK COLOUR SPLINE CURVE for a description of the colour spline curve data record.

CHARACTER*80 TCREC(TCLDR) trimming curve data record²

NON-UNIFORM B-SPLINE SURFACE 3 WITH DATA

SUBROUTINE PBSS3D(USORD,VSORD,UNKA,VNKA,UKNOTS,VKNOTS,RTYPE,
*UNCP,VNCP,PXA,PYA,PZA,PWA,TCLDR,TCREC,CSSLDR,CSSREC,DSSLDR,
*DSSREC)

Input Parameters:

INTEGER USORD	u spline order
INTEGER VSORD	v spline order
INTEGER UNKA	number of knots for u
INTEGER VNKA	number of knots for v
REAL UKNOTS(UNKA)	u knots
REAL VKNOTS(VNKA)	v knots
INTEGER RTYPE	rationality (PRAT,PNRAT)
INTEGER UNCP	u number of control points dimension
INTEGER VNCP	v number of control points dimension
REAL PXA(UNCP*VNCP),PYA(UNCP*VNCP),PZA(UNCP*VNCP),PWA(UNCP*VNCP)	control points(MC)
INTEGER TCLDR	number of array elements used in TCREC
CHARACTER*80 TCREC(TCLDR)	trimming curve data record ³
INTEGER CSSLDR	number of array elements used in CSSREC
CHARACTER*80 CSSREC(CSSLDR)	
	colour spline surface data record ⁴
INTEGER DSSLDR	number of array elements used in DSSREC
CHARACTER*80 DSSREC(DSSLDR)	data spline surface data record ⁵

²See PACK TRIMMING CURVE and UNPACK TRIMMING CURVE for a description of the trimming curve data record.

³See PACK TRIMMING CURVE and UNPACK TRIMMING CURVE for a description of the trimming curve data record.

⁴See PACK COLOUR SPLINE SURFACE and UNPACK COLOUR SPLINE SURFACE for a description of the colour spline surface data record.

⁵See PACK DATA SPLINE SURFACE and UNPACK DATA SPLINE SURFACE for a description of the data spline surface data record.

13.3 Attribute specification functions

13.3.1. Bundled attribute selection

SET DATA MAPPING INDEX

SUBROUTINE PSDMI(DMI)

Input Parameters:

INTEGER DMI

data mapping index

SET REFLECTANCE INDEX

SUBROUTINE PSRFI(RFI)

Input Parameters:

INTEGER RFI

reflectance index

SET BACK INTERIOR INDEX

SUBROUTINE PSBII(BII)

Input Parameters:

INTEGER BII

back interior index

SET BACK DATA MAPPING INDEX

SUBROUTINE PSBDMI(BDMI)

Input Parameters:

INTEGER BDMI

back data mapping index

SET BACK REFLECTANCE INDEX

SUBROUTINE PSBRFI(BRFI)

Input Parameters:

INTEGER BRFI

back reflectance index

SET PARAMETRIC SURFACE INDEX

SUBROUTINE PPSI(PSI)

Input Parameters:

INTEGER PSI

parametric surface index

13.3.2 Individual attribute selection**SET POLYLINE COLOUR**

SUBROUTINE PSPLC(CTYPE,COLI,NCC,COLR)

Input Parameters:

INTEGER CTYPE	polyline colour type
INTEGER COLI	colour index
INTEGER NCC	number of components of colour value
REAL COLR(NCC)	colour values

SET POLYLINE SHADING METHOD

SUBROUTINE PSPLSM(PLSM)

Input Parameters:

INTEGER PLSM	polyline shading method
--------------	-------------------------

SET POLYMARKER COLOUR

SUBROUTINE PSPMC(CTYPE,COLI,NCC,COLR)

Input Parameters:

INTEGER CTYPE	polymarker colour type
INTEGER COLI	colour index
INTEGER NCC	number of components of colour value
REAL COLR(NCC)	colour values

SET TEXT COLOUR

SUBROUTINE PSTXC(CTYPE,COLI,NCC,COLR)

Input Parameters:

INTEGER CTYPE	text colour type
INTEGER COLI	colour index
INTEGER NCC	number of components of colour value
REAL COLR(NCC)	colour values

SET FACET DISTINGUISHING MODE

SUBROUTINE PSFDM(DMODE)

Input Parameters:

INTEGER DMODE	distinguishing mode (POFF,PON)
---------------	--------------------------------

SET FACET CULLING MODE

SUBROUTINE PSFCM(CMODE)

Input Parameters:

INTEGER CMODE	culling mode (PNOFC,PBKFC,PFTFC)
---------------	----------------------------------

SET INTERIOR COLOUR

SUBROUTINE PSIC(CTYPE,COLI,NCC,COLR)

Input Parameters:

INTEGER CTYPE	interior colour type
INTEGER COLI	colour index
INTEGER NCC	number of components of colour value
REAL COLR(NCC)	colour values

SET INTERIOR SHADING METHOD

SUBROUTINE PSISM(ISM)

Input Parameters:

INTEGER ISM	interior shading method
-------------	-------------------------

SET DATA MAPPING METHOD

SUBROUTINE PSDMM(DMM,LDR,DATREC)

Input Parameters:

INTEGER DMM	data mapping method
INTEGER LDR	length of data record array
CHARACTER*80 DATREC(LDR)	data record

DATREC parameters to build DATA MAPPING METHOD DATA RECORD for

DMM = PCDDM:

The IA array contains:

- The number of source selectors
- The actual list of source selectors

The other arrays are empty.

Common element:

IL= 1+*

IA(1)= number of source selectors = NSS

IA= element 2 through NSS+1 contain source selectors

RL= 0

RA= ()

SL= 0

LSTR= ()

STR= ()

DATREC parameters to build DATA MAPPING METHOD DATA RECORD for

DMM = PSUDM:

The IA array contains:

- The number source selectors
- The actual list of source selectors
- The index of the data value
- The colour type(CT)
- The number of colour values(NCV)
- The list of colour indices. There are NCV colour indices, if CT is indirect.
- The number of components of colour value(NCC), if CT is not indirect.

The RA array contains:

- The lower range limit
- The upper range limit
- The list of colour values. There are NCV colour values, each having as many components as required by CT.

Common element:

IL= 5+*

IA(1)= number of source selectors = NSS

IA= element 2 through NSS+1 contain source selectors

IA(NSS+2)= data value index

IA(NSS+3)= colour type = CT

IA(NSS+4)= number of specified colour = NCV

RL= 2+*

RA(1)= lower range limit

RA(2)= upper range limit

SL= 0

LSTR= ()

STR= ()

Individual element:

CASE colour type=PINDDIR:

IA=element NSS+5 through NSS+4+NCV contain the colour indices

CASE colour type=PRGB or PCIE or PHSV or PHLS:

IA(NSS+5)= number of components of colour value = NCC

RA=element 3 through NCC*NCV+2 contain the colour values

example r1,g1,b1,r2,g2,b2,...

DATREC parameters to build DATA MAPPING METHOD DATA RECORD for

DMM = PSNUDM:

The IA array contains:

- The number of source selectors
- The actual list of source selectors
- The index of the data value
- The colour type(CT)
- The number of range boundaries(NRB)
- The list of colour indices. There are NRB+1 colour indices, if CT is indirect.
- The number of components of colour value(NCC), if CT is not indirect.

The RA array contains:

- The actual data of range boundaries
- The list of colour values. There are NRB+1 colour values, each having as many components as required by CT

Common element:

IL= 5+NSS+*

IA(1)= number of source selectors = NSS

IA= element 2 through NSS+1 contain source selectors

IA(NSS+2)= data value index

IA(NSS+3)= colour type = CT

IA(NSS+4)= number of range boundaries = number of specified colour -1 = NRB

RL= NRB+*

RA=element 1 through NRB contain the range boundary

SL= 0

LSTR= ()

STR= ()

Individual element:

CASE colour type=PINDIR:

IA=element NSS+5 through NSS+4+NRB+1 contain the colour indices

CASE colour type=PRGB or PCIE or PHSV or PHLS:

IA(NSS+5)= number of components of colour value = NCC

RA=element NRB+1 through NCC*(NRB+1)+NRB contain the colour values

example r1,g1,b1,r2,g2,b2,...

DATREC parameters to build DATA MAPPING METHOD DATA RECORD for
DMM = PBUDM:

The IA array contains:

- The number of source selectors
- The actual list of source selectors
- The two indices of the data value
- The colour type(CT)
- The number of colour lists(NCL)
- The array of end indices of colour lists
- The list of colour indices. There are a lot of colour indices, if CT is indirect.
- The number of components of colour value(NCC), if CT is not indirect.

The RA array contains:

- The actual data of lower and upper limit of Ra range boundary
- The actual data of lower and upper limit of Rb range boundary
- The list of colour values. There are a lot of colour values, each having as many components as required by CT.

Common element:

IL= 6+NSS+NCL

IA(1)= number of source selectors = NSS

IA= element 2 through NSS+1 contain source selectors

IA(NSS+2)= data value index 1

IA(NSS+3)= data value index 2

IA(NSS+4)= colour type = CT

IA(NSS+5)= number of colour lists = NCL

IA= element NSS+6 through NSS+5+NCL contain array of end indices of colour lists

RL= 4+*

RA(1)= lower limit of Ra range

RA(2)= upper limit of Ra range

RA(3)= lower limit of Rb range

RA(4)= upper limit of Rb range

SL= 0

LSTR= ()

STR= ()

Individual element:

CASE colour type=PINDIR:

IA=element NSS+5+NCL+1 through NSS+5+NCL+IA(NSS+5+NCL) contain
the colour indices

CASE colour type=PRGB or PCIE or PHSV or PHLS:

IA(NSS+5+NCL+1)= number of components of colour value = NCC

RA=element 5 through NCC*IA(NSS+5+NCL)+4 contain the colour values

example r1,g1,b1,r2,g2,b2,...

DATREC parameters to build DATA MAPPING METHOD DATA RECORD for
DMM = PBNUDM:

The IA array contains:

- The number of source selectors
- The actual list of source selectors

- The two indices of the data value
- The colour type(CT)
- The number of Ra range boundaries(NRAB)
- The array of end indices of Rb range boundaries data
- The list of colour indices. There is a lot of colour indices (number of Rb range boundaries data + number of Ra range boundaries), if CT is indirect.
- The number of components of colour value(NCC), if CT is not indirect.

The RA array contains:

- The actual data of Ra range boundaries
- The actual data of Rb range boundaries
- The list of colour values. There is a lot of colour values (number of Rb range boundaries data + number of Ra range boundaries), each having as many components as required by CT.

Common element:

IL= 6+*

IA(1)= number of source selectors = NSS

IA= element 2 through NSS+1 contain source selectors

IA(NSS+2)= data value index 1

IA(NSS+3)= data value index 2

IA(NSS+4)= colour type = CT

IA(NSS+5)= number of Ra range boundaries = NRAB

IA=element NSS+6 through NSS+5+NRAB array of end indices of Rb range boundaries

RL= NRAB+IA(NSS+5+NRAB)+*

RA=element 1 through NRAB contain Ra range boundary

RA=element NRAB+1 through NRAB+IA(NSS+5+NRAB) contain Rb range boundary

SL= 0

LSTR= ()

STR= ()

Individual element:

CASE colour type=PINDIR:

IA=element NSS+5+NRAB+1 through NSS+4+NRAB+1+IA(NSS+5+NRAB) contain colour indices

CASE colour type=PRGB or PCIE or PHSV or PHLS:

IA(NSS+5+NRAB+1)= number of components of colour value = NCC

RA=element NRAB+IA(NSS+5+NRAB)+1 through

NRAB+IA(NSS+5+NRAB)+NCC*(IA(NSS+5+NRAB))

contain the colour values

example r1,g1,b1,r2,g2,b2,...

SET REFLECTANCE PROPERTIES

SUBROUTINE PSRFP(RPTYPE,LDR,DATREC)

Input Parameters:

INTEGER RPTYPE reflectance properties type

INTEGER LDR length of data record array

CHARACTER*80 DATREC(LDR) data record

DATREC parameters to build REFLECTANCE PROPERTIES DATA RECORD for RPTYPE = PSRPT:

The IA array contains:

- The colour type(CT)
- The number of components of colour value(NCC)

- The colour index of the specular colour if CT is indirect.

The RA array contains:

- The actual data of ambient reflection coefficient
- The actual data of diffuse reflection coefficient
- The actual data of specular reflection coefficient
- The actual data of specular exponent
- The actual data of colour values as required by CT.

Common element:

IL= 2+*

IA(1)= colour type = CT

IA(2)= number of components of colour value = NCC

RL= 4+*

RA(1)= ambient reflection coefficient

RA(2)= diffuse reflection coefficient

RA(3)= specular reflection coefficient

RA(4)= specular exponent

SL= 0

LSTR= ()

STR= ()

Individual element:

CASE colour type=PINDIR:

IA(3)= specular colour index

CASE colour type=PRGB or PCIE or PHSV or PHLS:

RA=element 5 through 4+NCC contain the colour values

SET REFLECTANCE MODEL

SUBROUTINE PSRFM(RFM)

Input Parameters:

INTEGER RFM

reflectance model

SET BACK INTERIOR STYLE

SUBROUTINE PSBIS(INTS)

Input Parameters:

INTEGER INTS

interior style

(PHOLLO,PSOLID,PPATTR,PPATCH,PISEMP)

SET BACK INTERIOR STYLE INDEX

SUBROUTINE PSBISI(ISTYLI)

Input Parameters:

INTEGER ISTYLI

interior style index

SET BACK INTERIOR COLOUR

SUBROUTINE PSBIC(CTYPE,COLI,NCC,COLR)

Input Parameters:

INTEGER CTYPE	back interior colour type
INTEGER COLI	colour index
INTEGER NCC	number of components of colour value
REAL COLR(NCC)	colour values

SET BACK INTERIOR SHADING METHOD

SUBROUTINE PSBISM(ISM)

Input Parameters:

INTEGER ISM	interior shading method
-------------	-------------------------

SET BACK DATA MAPPING METHOD

SUBROUTINE PSBDMM(DMM,LDR,DATREC)

Input Parameters:

INTEGER DMM	data mapping method
INTEGER LDR	length of data record array
CHARACTER*80 DATREC(LDR)	data record ⁶

SET BACK REFLECTANCE PROPERTIES

SUBROUTINE PSBRFP(RPTYPE,LDR,DATREC)

Input Parameters:

INTEGER RPTYPE	reflectance properties type
INTEGER LDR	length of data record array
CHARACTER*80 DATREC(LDR)	data record ⁷

SET BACK REFLECTANCE MODEL

SUBROUTINE PSBRFM(RFM)

Input Parameters:

INTEGER RFM	reflectance model
-------------	-------------------

⁶See SET DATA MAPPING METHOD for a description of the data mapping method data records.

⁷See SET REFLECTANCE PROPERTIES for a description of the reflectance properties data records.

SET LIGHT SOURCE STATE

SUBROUTINE PSLSS(NACTI,ACTLST,NDEAI,DEALST)

Input Parameters:

INTEGER NACTI	number of activation indices
INTEGER ACTLST(NACTI)	activation list
INTEGER NDEAI	number of deactivation indices
INTEGER DEALST(NDEAI)	deactivation list

SET EDGE COLOUR

SUBROUTINE PSEDC(CTYPE,COLI,NCC,COLR)

Input Parameters:

INTEGER CTYPE	edge colour type
INTEGER COLI	colour index
INTEGER NCC	number of components of colour value
REAL COLR(NCC)	colour values

SET CURVE APPROXIMATION CRITERIA

SUBROUTINE PSCAC(ACRI,LDR,DATREC)

Input Parameters:

INTEGER ACRI	curve approximation criteria type
INTEGER LDR	length of data record array
CHARACTER*80 DATREC(LDR)	data record

DATREC parameters to build CURVE APPROXIMATION CRITERIA DATA RECORD
for ACRI=PWDCA: No data record

DATREC parameters to build CURVE APPROXIMATION CRITERIA DATA RECORD
for ACRI=PCBKCA:

The IA array contains:

- The actual data of count
- The other arrays are empty.

IL= 1
IA(1)= count
RL= 0
RA= ()
SL= 0
LSTR= ()
STR= ()

DATREC parameters to build CURVE APPROXIMATION CRITERIA DATA RECORD
for ACRI=PCSWCA or PCSNCA or PCSDCA or PCDWCA or PCDNCA or
PCDDCA or PRWCA or PRNCA or PRDCA:

The RA array contains:

- The actual data of approximation value
- The other arrays are empty.

IL= 0

IA= ()

RL= 1

RA(1)= approximation value

SL= 0

LSTR= ()

STR= ()

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 9593-1:1990/Amd 1:1995

SET SURFACE APPROXIMATION CRITERIA

SUBROUTINE PSSAC(ACRI,LDR,DATREC)

Input Parameters:

INTEGER ACRI	surface approximation criteria type
INTEGER LDR	length of data record array
CHARACTER*80 DATREC(LDR)	data record

DATREC parameters to build SURFACE APPROXIMATION CRITERIA DATA RECORD for
ACRI=PWDCA: No data record

DATREC parameters to build SURFACE APPROXIMATION CRITERIA DATA RECORD for
ACRI=PCBKSA:

The IA array contains:

- The actual data of u count
- The actual data of v count

The other arrays are empty.

IL= 2

IA(1)= u count

IA(2)= v count

RL= 0

RA= ()

SL= 0

LSTR= ()

STR= ()

DATREC parameters to build SURFACE APPROXIMATION CRITERIA DATA RECORD for
ACRI = PCSWSA or PCSNSA or PCSDSA:

The RA array contains:

- The actual data of u approximation value
- The actual data of v approximation value

The other arrays are empty.

IL= 0

IA= ()

RL= 2

RA(1)= u approximation value

RA(2)= v approximation value

SL= 0

LSTR= ()

STR= ()

DATREC parameters to build SURFACE APPROXIMATION CRITERIA DATA RECORD for
ACRI = PPDWSA or PPDNSA or PPDDSA or PRWSA or PRNSA or PRDSA:

The RA array contains:

- The actual data of approximation value

The other arrays are empty.

IL= 0

IA= ()

RL= 1

RA(1)= approximation value

SL= 0

LSTR= ()

STR= ()

SET PARAMETRIC SURFACE CHARACTERISTICS

SUBROUTINE PSPSC(PSTY,LDR,DATREC)

Input Parameters:

INTEGER PSTY	parametric surface characteristics type
INTEGER LDR	length of data record array
CHARACTER*80 DATREC(LDR)	data record

DATREC parameters to build PARAMETRIC SURFACE CHARACTERISTICS DATA
RECORD for PSTY = PNOPC or PWDPC: No data record

DATREC parameters to build PARAMETRIC SURFACE CHARACTERISTICS DATA
RECORD for PSTY = PICPC:

The IA array contains:

- The actual data of curve placement
- The actual data of curve count in u direction
- The actual data of curve count in v direction

The other arrays are empty.

IL= 3

IA(1)= curve placement(PUOSCP,PUBKCP)

IA(2)= curve count in u direction

IA(3)= curve count in v direction

RL= 0

RA= ()

SL= 0

LSTR= ()

STR= ()

DATREC parameters to build PARAMETRIC SURFACE CHARACTERISTICS DATA
RECORD for PSTY = PLCMPC:

The IA array contains:

- The number of parameters(NP)

The RA array contains:

- The actual data of origin point
- The actual data of direction vector
- The actual data of parameters. There are NP parameters.

IL= 1

IA(1)= number of parameters = NP

RL= 6+NP

RA(1)= x-coordinate of origin point(MC)

RA(2)= y-coordinate of origin point(MC)

RA(3)= z-coordinate of origin point(MC)

RA(4)= x-value of direction vector(MC)

RA(5)= y-value of direction vector(MC)

RA(6)= z-value of direction vector(MC)

RA= element 7 through NP+6 contain parameters

SL= 0

LSTR= ()

STR= ()

DATREC parameters to build PARAMETRIC SURFACE CHARACTERISTICS DATA

RECORD for PSCTY = PLCWPC:

The IA array contains:

- The number of parameters(NP)

The RA array contains:

- The actual data of origin point
- The actual data of direction vector
- The actual data of parameters. There are NP parameters.

IL= 1

IA(1)= number of parameters = NP

RL= 6+NP

RA(1)= x-coordinate of origin point(WC)

RA(2)= y-coordinate of origin point(WC)

RA(3)= z-coordinate of origin point(WC)

RA(4)= x-value of direction vector(WC)

RA(5)= y-value of direction vector(WC)

RA(6)= z-value of direction vector(WC)

RA= element 7 through NP+6 contain parameters

SL= 0

LSTR= ()

STR= ()

SET RENDERING COLOUR MODEL

SUBROUTINE PSRCM(RCOLM)

Input Parameters:

INTEGER RCOLM

rendering colour model

SET DEPTH CUE INDEX

SUBROUTINE PSDCI(DCI)

Input Parameters:

INTEGER DCI

depth cue index

SET COLOUR MAPPING INDEX

SUBROUTINE PSCMI(CMI)

Input Parameters:

INTEGER CMI

colour mapping index

13.3.3 Aspect source flag setting

SET INDIVIDUAL ASF

SUBROUTINE PSIASF(ASPCID,ASFVAL)

Input Parameters:

INTEGER ASPCID

aspect identifier

(PLN,PLWSC,PPLCI,PMK,PMKSC,PPMCI,PTXFN,
PTXPR,PCHXP,PCHSP,PTXCI,PIS,PISI,PICI,
PEDFG,PEDTY,PEWSC,PEDCI,⁸

PPLCOL,PPMCOL,PTXCOL,PINCOL,PEDCOL,
PPSHMD,PISHMD,PDMPMD,PREFPR,PREFM,
PBINSY,PBINSI,PBICOL,PBISHM,PBDMPM,
PBREFP,PBREFM,PCAPCR,PSAPCR,PPASUC)

INTEGER ASFVAL

aspect source flag value

(PBUNDL,PINDIV)

This function is defined in PHIGS part 1. Additional aspect identifiers are defined in PHIGS part 4. This binding shows those additional aspect identifiers.

⁸already defined in PHIGS

13.3.4 Workstation attribute table definition

SET POLYLINE REPRESENTATION PLUS

SUBROUTINE PSPLP(WKID,PLI,LTYPE,LWIDTH,CTYPE,COLI,NCC,COLR,PLSM,
*ACRI,LDR,DATREC)

Input Parameters:

INTEGER WKID	workstation identifier
INTEGER PLI	polyline index
INTEGER LTYPE	linetype
REAL LWIDTH	linewidth scale factor
INTEGER CTYPE	polyline colour type
INTEGER COLI	colour index
INTEGER NCC	number of components of colour value
REAL COLR(NCC)	colour values
INTEGER PLSM	polyline shading method
INTEGER ACRI	curve approximation criteria type
INTEGER LDR	length of data record array
CHARACTER*80 DATREC(LDR)	curve approximation criteria data record ⁹

SET POLYMARKER REPRESENTATION PLUS

SUBROUTINE PSPMP(WKID,PMI,MTYPE,MSZSF,CTYPE,COLI,NCC,COLR)

Input Parameters:

INTEGER WKID	workstation identifier
INTEGER PMI	polymarker index
INTEGER MTYPE	marker type
REAL MSZSF	marker size scale factor
INTEGER CTYPE	polymarker colour type
INTEGER COLI	colour index
INTEGER NCC	number of components of colour value
REAL COLR(NCC)	colour values

⁹See SET CURVE APPROXIMATION CRITERIA for a description of the curve approximation criteria data records.

SET TEXT REPRESENTATION PLUS

SUBROUTINE PSTXRP(WKID, TXI, FONT, PREC, CHXP, CHSP, CTYPE, COLI, NCC,
*COLR)

Input Parameters:

INTEGER WKID	workstation identifier
INTEGER TXI	text index
INTEGER FONT	text font
INTEGER PREC	text precision (PSTRP, PCHARP, PSTRKP)
REAL CHXP	character expansion factor
REAL CHSP	character spacing
INTEGER CTYPE	text colour type
INTEGER COLI	colour index
INTEGER NCC	number of components of colour value
REAL COLR(NCC)	colour values

SET INTERIOR REPRESENTATION PLUS

SUBROUTINE PSIP(WKID, II, INTS, STYLI, CTYPE, COLI, NCC, COLR, ISM)

Input Parameters:

INTEGER WKID	workstation identifier
INTEGER II	interior index
INTEGER INTS	interior style (PHOLI, PSOLID, PPATTR, PPATCH, PISEMP)
INTEGER STYLI	interior style index
INTEGER CTYPE	interior colour type
INTEGER COLI	colour index
INTEGER NCC	number of components of colour value
REAL COLR(NCC)	colour values
INTEGER ISM	interior shading method

SET EDGE REPRESENTATION PLUS

SUBROUTINE PSED(PWKID, EDI, EDFLAG, EDTYPE, EWIDTH, CTYPE, COLI, NCC,
*COLR)

Input Parameters:

INTEGER WKID	workstation identifier
INTEGER EDI	edge index
INTEGER EDFLAG	edge flag (POFF, PON)
INTEGER EDTYPE	edge type
REAL EWIDTH	edgewidth scale factor
INTEGER CTYPE	edge colour type
INTEGER COLI	colour index
INTEGER NCC	number of components of colour value
REAL COLR(NCC)	colour values

SET DATA MAPPING REPRESENTATION

SUBROUTINE PSDMR(WKID,DMI,DMM,LDR,DATREC)

Input Parameters:

INTEGER WKID	workstation identifier
INTEGER DMI	data mapping index
INTEGER DMM	data mapping method
INTEGER LDR	length of data record array
CHARACTER*80 DATREC(LDR)	data record ¹⁰

SET REFLECTANCE REPRESENTATION

SUBROUTINE PSRFR(WKID,RFI,RFM,RPTYPE,LDR,DATREC)

Input Parameters:

INTEGER WKID	workstation identifier
INTEGER RFI	reflectance index
INTEGER RFM	reflectance model
INTEGER RPTYPE	reflectance properties type
INTEGER LDR	length of data record array
CHARACTER*80 DATREC(LDR)	data record ¹¹

SET PARAMETRIC SURFACE REPRESENTATION

SUBROUTINE PSPSR(WKID,PSI,ACRI,LDRAC,DARECA,PSCTY,LDRPS,DARECP)

Input Parameters:

INTEGER WKID	workstation identifier
INTEGER PSI	parametric surface index
INTEGER ACRI	surface approximation criteria type
INTEGER LDRAC	length of surface approximation criteria data record array
CHARACTER*80 DARECA(LDRAC)	surface approximation criteria data record ¹²
INTEGER PSCTY	parametric surface characteristics type
INTEGER LDRPS	length of parametric surface characteristics data record array
CHARACTER*80 DARECP(LDRPS)	parametric surface characteristics data record ¹³

¹⁰See SET DATA MAPPING METHOD for a description of the data mapping method data records.

¹¹See SET REFLECTANCE PROPERTIES for a description of the reflectance properties data records.

¹²See SET SURFACE APPROXIMATION CRITERIA for a description of the surface approximation criteria data records.

¹³See SET PARAMETRIC SURFACE CHARACTERISTICS for a description of the parametric surface characteristics data records.

SET PATTERN REPRESENTATION PLUS

SUBROUTINE PSPAP(WKID,PAI,DIMX,DIMY,ISC,ISR,DX,DY,CTYPE,COLIA,
*NCC,COLRA)

Input Parameters:

INTEGER WKID	workstation identifier
INTEGER PAI	pattern index
INTEGER DIMX,DIMY	number of rows, number of columns in COLIA or COLRA
INTEGER ISC,ISR	indices of start column, start row for pattern
INTEGER DX,DY	number of columns, number of rows in pattern
INTEGER CTYPE	interior colour type
INTEGER COLIA(DIMX,DIMY)	colour index array
INTEGER NCC	number of components of colour value
REAL COLRA(NCC*DIMX*DIMY)	colour value array

SET LIGHT SOURCE REPRESENTATION

SUBROUTINE PLSR(WKID,LSI,LSTYP,LDR,DATREC)

Input Parameters:

INTEGER WKID	workstation identifier
INTEGER LSI	light source index
INTEGER LSTYP	light source type
INTEGER LDR	length of data record array
CHARACTER*80 DATREC(LDR)	data record

DATREC parameters to build LIGHT SOURCE DATA RECORD for LSTYP = PAMB:

The IA array contains:

- The colour type(CT)
- The actual data of colour index, if CT is indirect
- The number of components of colour value(NCC)

The RA array contains:

- The actual data of colour values as required by CT

Common element:

IL= 2

IA(1)= colour type = CT

RL= *

RA= ()

SL= 0

LSTR= ()

STR= ()

Individual element:

CASE colour type=PINDIR:

IA(2)= colour index

CASE colour type=PRGB or PCIE or PHSV or PHLS:

IA(2)= number of components of colour value = NCC

RA= element 1 through NCC contain the colour values

DATREC parameters to build LIGHT SOURCE DATA RECORD for LSTYP = PDIRE:

The IA array contains:

- The colour type(CT)
- The actual data of colour index, if CT is indirect.

- The number of components of colour value(NCC)

The RA array contains:

- The actual data of direction vector
- The actual data of colour values as required by CT.

Common element:

IL= 2

IA(1)= colour type = CT

RL= 3+*

RA(1)=x-value of direction vector(WC)

RA(2)=y-value of direction vector(WC)

RA(3)=z-value of direction vector(WC)

SL= 0

LSTR= ()

STR= ()

Individual element:

CASE colour type=PINDIR:

IA(2)=colour index

CASE colour type=PRGB or PCIE or PHSV or PHLS:

IA(2)= number of components of colour value = NCC

RA= element 4 through 3+NCC contain the colour values

DATREC parameters to build LIGHT SOURCE DATA RECORD for LSTYP = PPOSI:

The IA array contains:

- The colour type(CT)
- The actual data of colour index, if CT is indirect.
- The number of components of colour value(NCC)

The RA array contains:

- The actual data of direction vector
- The actual data of attenuation coefficients
- The actual data of colour values as required by CT.

Common element:

IL= 2

IA(1)= colour type = CT

RL= 5+*

RA(1)=x-value of direction vector(WC)

RA(2)=y-value of direction vector(WC)

RA(3)=z-value of direction vector(WC)

RA(4)=attenuation coefficient 1

RA(5)=attenuation coefficient 2

SL= 0

LSTR= ()

STR= ()

Individual element:

CASE colour type=PINDIR:

IA(2)=colour index

CASE colour type=PRGB or PCIE or PHSV or PHLS:

IA(2)= number of components of colour value = NCC

RA= element 6 through 5+NCC contain the colour values

DATREC parameters to build LIGHT SOURCE DATA RECORD for LSTYP = PSPOT:

The IA array contains:

- The colour type(CT)
- The actual data of colour index, if CT is indirect.
- The number of components of colour value(NCC)

The RA array contains:

- The actual data of light source position
- The actual data of direction vector of light source
- The actual data of concentration exponent
- The actual data of attenuation coefficients
- The actual data of spread angle
- The actual data of colour values as required by CT.

Common element:

IL= 2

IA(1)= colour type = CT

RL= 10+*

RA(1)=x-coordinate of light source position(WC)

RA(2)=y-coordinate of light source position(WC)

RA(3)=z-coordinate of light source position(WC)

RA(4)=x-value of light source direction(WC)

RA(5)=y-value of light source direction(WC)

RA(6)=z-value of light source direction(WC)

RA(7)= concentration exponent

RA(8)=attenuation coefficient 1

RA(9)=attenuation coefficient 2

RA(10)= spread angle

SL= 0

LSTR= ()

STR= ()

Individual element:

CASE colour type=PINDIR:

IA(2)=colour index

CASE colour type=PRGB or PCIE or PHSV or PHLS:

IA(2)= number of components of colour value = NCC

RA= element 11 through 10+NCC contain the colour values

SET DEPTH CUE REPRESENTATION

SUBROUTINE PSDCR(WKID,DCI,DCMODE,DQMIN,DQMAX,DCSFMI,DCSFMX,
*CTYPE,COLI,NCC,COLR)

Input Parameters:

INTEGER WKID

workstation identifier

INTEGER DCI

depth cue index

INTEGER DCMODE

depth cue mode
(PSUPPR,PALLOW)

REAL DQMIN,DQMAX

depth cue reference planes(NPC)

REAL DCSFMI,DCSFMX

depth cue scale factors

INTEGER CTYPE

depth cue colour type

INTEGER COLI

colour index

INTEGER NCC

number of components of colour value

REAL COLR(NCC)

colour values

SET COLOUR MAPPING REPRESENTATION

SUBROUTINE PSCMR(WKID,CMI,CMM,LDR,DATREC)

Input Parameters:

INTEGER WKID	workstation identifier
INTEGER CMI	colour mapping index
INTEGER CMM	colour mapping method
INTEGER LDR	length of data record array
CHARACTER*80 DATREC(LDR)	data record

DATREC parameters to build COLOUR MAPPING METHOD DATA RECORD
for CMM = PTRUE: no data record

DATREC parameters to build COLOUR MAPPING METHOD DATA RECORD
for CMM = PSUD:

The IA array contains:

- The colour model(CM)
- The number of components of colour value(NCC), same as the number of weight vector values
- The number of list of colours in the specified colour model(NLC)

The RA array contains:

- The actual data of weight vector
- The list of colour values. There are NLC colour values, each having as many components as required by CM.

IL= 3

IA(1)= colour model = CM

IA(2)= number of components of colour value, same as number of weight vector value = NCC

IA(3)= number of list of colours in the specified colour model = NLC

RL= NCC+NCC*NLC

RA= element 1 through NCC contain the weight vector

RA= element NCC+1 through NCC*NLC+NCC contain the colour value

example r1,g1,b1,r2,g2,b2,...

SL= 0

LSTR= ()

STR= ()

DATREC parameters to build COLOUR MAPPING METHOD DATA RECORD
for CMM = PSUDN:

The IA array contains:

- The colour model(CM)
- The number of components in the colour model(NCC)
- The array of end indices for list of colour coordinates(IXA)

The RA array contains:

- The list of colour coordinates.

IL= 2

IA(1)= colour model = CM

IA(2)= number of components in the colour model = NCC

IA= element 3 through NCC+2 contain the array of end indices for lists of colour coordinates

RL= IA(NCC+2)

RA=element 1 through IA(NCC+2) contain the lists of colour coordinates

example for colour model=PRGB:

RA element 1 through IA(3) contain red values;

RA element IA(3)+1 through IA(4) contain green values

RA element IA(4)+1 through IA(5) contain blue values

SL= 0

LSTR= ()

STR= ()

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 9593-1:1990/Amd 1:1995

13.4 Inquiry functions

13.4.1 Inquiry functions for workstation state list

INQUIRE POLYLINE REPRESENTATION PLUS

SUBROUTINE PQPLP(WKID,PLI,CCSBSZ,TYPE,MLDR,ERRIND,LTYPE,
*LWIDTH,CTYPE,COLI,NCC,COLR,PLSM,ACRI,LDR,DATREC)

Input Parameters:

INTEGER WKID	workstation identifier
INTEGER PLI	polyline index
INTEGER CCSBSZ	colour component specification buffer size
INTEGER TYPE	type of return value(PSET,PREALI)
INTEGER MLDR	dimension of curve approximation criteria data record array

Output Parameters:

INTEGER ERRIND	error indicator
INTEGER LTYPE	linetype
REAL LWIDTH	linewidth scale factor
INTEGER CTYPE	colour type
INTEGER COLI	colour index
INTEGER NCC	number of components of colour value
REAL COLR(CCSBSZ)	colour values
INTEGER PLSM	polyline shading method
INTEGER ACRI	curve approximation criteria type
INTEGER LDRCA	length of curve approximation criteria data record array
CHARACTER*80 DATREC(MLDR)	curve approximation criteria data record ¹⁴

INQUIRE POLYMARKER REPRESENTATION PLUS

SUBROUTINE POPMP(WKID,PMI,CCSBSZ,TYPE,ERRIND,MTYPE,MSZSF,CTYPE,
*COLI,NCC,COLR)

Input Parameters:

INTEGER WKID	workstation identifier
INTEGER PMI	polymarker index
INTEGER CCSBSZ	colour component specification buffer size
INTEGER TYPE	type of return value(PSET,PREALI)

Output Parameters:

INTEGER ERRIND	error indicator
INTEGER MTYPE	marker type
REAL MSZSF	marker scale factor
INTEGER CTYPE	colour type
INTEGER COLI	colour index
INTEGER NCC	number of components of colour value
REAL COLR(CCSBSZ)	colour values

¹⁴See SET CURVE APPROXIMATION CRITERIA for a description of the curve approximation criteria data records.

INQUIRE TEXT REPRESENTATION PLUS

SUBROUTINE PQTXP(WKID,TXI,CCSBSZ,TYPE,ERRIND,FONT,PREC,CHXP,
*CHSP,CTYPE,COLI,NCC,COLR)

Input Parameters:

INTEGER WKID	workstation identifier
INTEGER TXI	text index
INTEGER CCSBSZ	colour component specification buffer size
INTEGER TYPE	type of return value(PSET,PREALI)

Output Parameters:

INTEGER ERRIND	error indicator
INTEGER FONT	text font
INTEGER PREC	text precision(PSTRP,PCHARP,PSTRKP)
REAL CHXP	character expansion factor
REAL CHSP	character spacing
INTEGER CTYPE	colour type
INTEGER COLI	colour index
INTEGER NCC	number of components of colour value
REAL COLR(CCSBSZ)	colour values

INQUIRE INTERIOR REPRESENTATION PLUS

SUBROUTINE PQIP(WKID,II,CCSBSZ,TYPE,ERRIND,INTS,STYLI,CTYPE,COLI,
*NCC,COLR,ISM)

Input Parameters:

INTEGER WKID	workstation identifier
INTEGER II	interior index
INTEGER CCSBSZ	colour component specification buffer size
INTEGER TYPE	type of return value(PSET,PREALI)

Output Parameters:

INTEGER ERRIND	error indicator
INTEGER INTS	interior style
INTEGER STYLI	interior style index
INTEGER CTYPE	colour type
INTEGER COLI	colour index
INTEGER NCC	number of components of colour value
REAL COLR(CCSBSZ)	colour values
INTEGER ISM	interior shading method

INQUIRE EDGE REPRESENTATION PLUS

SUBROUTINE PQEDP(WKID,EDI,CCSBSZ,TYPE,ERRIND,EDFLAG,EDTYPE,
*EWIDTH,CTYPE,COLI,NCC,COLR)

Input Parameters:

INTEGER WKID	workstation identifier
INTEGER EDI	edge index
INTEGER CCSBSZ	colour component specification buffer size
INTEGER TYPE	type of return value(PSET,PREALI)

Output Parameters:

INTEGER ERRIND	error indicator
INTEGER EDFLAG	edge flag (POFF,PON)
INTEGER EDTYPE	edge type
REAL EWIDTH	edge scale factor
INTEGER CTYPE	colour type
INTEGER COLI	colour index
INTEGER NCC	number of components of colour value
REAL COLR(CCSBSZ)	colour values

INQUIRE LIST element OF DATA MAPPING INDICES

SUBROUTINE PQEDMI(WKID,N,ERRIND,OL,DMI)

Input Parameters:

INTEGER WKID	workstation identifier
INTEGER N	list element requested

Output Parameters:

INTEGER ERRIND	error indicator
INTEGER OL	number of data mapping bundle table entries
INTEGER DMI	Nth element of list of defined data mapping indices

INQUIRE DATA MAPPING REPRESENTATION

SUBROUTINE PQDMR(WKID,DMI,TYPE,MLDR,ERRIND,DMM,LDR,DATREC)

Input Parameters:

INTEGER WKID	workstation identifier
INTEGER DMI	data mapping index
INTEGER TYPE	type of return value(PSET,PREALI)
INTEGER MLDR	dimension of data record array

Output Parameters:

INTEGER ERRIND	error indicator
INTEGER DMM	data mapping method
INTEGER LDR	length of data record array
CHARACTER*80 DATREC(MLDR)	data mapping data record ¹⁵

¹⁵See SET DATA MAPPING METHOD for a description of the data mapping method data records.

INQUIRE LIST element OF REFLECTANCE INDICES

SUBROUTINE PQERFI(WKID,N,ERRIND,OL,RFI)

Input Parameters:

INTEGER WKID	workstation identifier
INTEGER N	list element requested

Output Parameters:

INTEGER ERRIND	error indicator
INTEGER OL	number of reflectance bundle table entries
INTEGER RFI	Nth element of list of defined reflectance indices

INQUIRE REFLECTANCE REPRESENTATIONSUBROUTINE PQRFR(WKID,RFI,TYPE,MLDR,ERRIND,RFM,RPTYPE,LDR,
*DATREC)*Input Parameters:*

INTEGER WKID	workstation identifier
INTEGER RFI	reflectance index
INTEGER TYPE	type of return value(PSET,PREALI)
INTEGER MLDR	dimension of data record array

Output Parameters:

INTEGER ERRIND	error indicator
INTEGER RFM	reflectance model
INTEGER RPTYPE	reflectance property type
INTEGER LDR	length of data record array
CHARACTER*80 DATREC(MLDR)	reflectance property colour value data record ¹⁶

INQUIRE LIST element OF PARAMETRIC SURFACE INDICES

SUBROUTINE PQEPSI(WKID,N,ERRIND,OL,PSI)

Input Parameters:

INTEGER WKID	workstation identifier
INTEGER N	list element requested

Output Parameters:

INTEGER ERRIND	error indicator
INTEGER OL	number of parametric surface table entries
INTEGER PSI	Nth element of list of defined parametric surface indices

¹⁶See SET REFLECTANCE PROPERTIES for a description of the reflectance properties data records.

INQUIRE PARAMETRIC SURFACE REPRESENTATION

SUBROUTINE PQPSR(WKID,PSI,TYPE,MLDRSA,MLDRPS,ERRIND,ACRI,LDRSA,
*DARECS,PSCH,LDRPS,DARECP)

Input Parameters:

INTEGER WKID	workstation identifier
INTEGER PSI	parametric surface bundle index
INTEGER TYPE	type of return value(PSET,PREALI)
INTEGER MLDRSA	dimension of surface approximation criteria data record array
INTEGER MLDRPS	dimension of parametric surface characteristics data record array

Output Parameters:

INTEGER ERRIND	error indicator
INTEGER ACRI	surface approximation criteria type
INTEGER LDRSA	length of surface approximation criteria data record
CHARACTER*80 DARECS(MLDRSA)	surface approximation criteria data record ¹⁷
INTEGER PSCH	parametric surface characteristics type
INTEGER LDRPS	length of parametric surface characteristics data record
CHARACTER*80 DARECP(MLDRPS)	parametric surface characteristics data record ¹⁸

INQUIRE PATTERN REPRESENTATION PLUS

SUBROUTINE PQPAP(WKID,PAI,CCSBSZ,TYPE,DIMX,DIMY,ERRIND,DX,DY,
*CTYPE,COLIA,NCC,COLRA)

Input Parameters:

INTEGER WKID	workstation identifier
INTEGER PAI	pattern index
INTEGER CCSBSZ	colour component specification buffer size
INTEGER TYPE	type of return value(PSET,PREALI)
INTEGER DIMX,DIMY	maximum pattern array dimension

Output Parameters:

INTEGER ERRIND	error indicator
INTEGER DX,DY	pattern array dimensions
INTEGER CTYPE	colour type
INTEGER COLIA(DIMX,DIMY)	colour index
INTEGER NCC	number of components of colour value
REAL COLRA(CCSBSZ)	colour values

¹⁷See SET SURFACE APPROXIMATION CRITERIA for a description of the surface approximation criteria data records.

¹⁸See SET PARAMETRIC SURFACE CHARACTERISTICS for a description of the parametric surface characteristics data records.

INQUIRE LIST element OF LIGHT SOURCE INDICES

SUBROUTINE PQELSI(WKID,N,ERRIND,OL,LSI)

Input Parameters:

INTEGER WKID	workstation identifier
INTEGER N	list element requested

Output Parameters:

INTEGER ERRIND	error indicator
INTEGER OL	number of light source table entries
INTEGER LSI	Nth element of list of defined light source indices

INQUIRE LIGHT SOURCE REPRESENTATION

SUBROUTINE PQLSR(WKID,LSI,TYPE,MLDR,ERRIND,LSTYP,LDR,DATREC)

Input Parameters:

INTEGER WKID	workstation identifier
INTEGER LSI	light source index
INTEGER TYPE	type of return value(PSET,PREALI)
INTEGER MLDR	dimension of data record array

Output Parameters:

INTEGER ERRIND	error indicator
INTEGER LSTYP	light source type
INTEGER LDR	length of data record array
CHARACTER*80 DATREC(MLDR)	data record ¹⁹

INQUIRE LIST element OF DEPTH CUE INDICES

SUBROUTINE PQEDCI(WKID,N,ERRIND,NCC,DCI)

Input Parameters:

INTEGER WKID	workstation identifier
INTEGER N	list element requested

Output Parameters:

INTEGER ERRIND	error indicator
INTEGER OL	number of depth cue table entries
INTEGER DCI	Nth element of list of defined depth cue indices

¹⁹See SET LIGHT SOURCE REPRESENTATION for a description of the light source data record.

INQUIRE DEPTH CUE REPRESENTATION

SUBROUTINE PQDCR(WKID,DCI,CCSBSZ,TYPE,ERRIND,DCMODE,DQMIN,
*DQMAX,DCSFMI,DCSFMX,CTYPE,COLI,NCC,COLR)

Input Parameters:

INTEGER WKID	workstation identifier
INTEGER DCI	depth cue index
INTEGER CCSBSZ	colour component specification buffer size
INTEGER TYPE	type of return value(PSET,PREAL)

Output Parameters:

INTEGER ERRIND	error indicator
INTEGER DCMODE	depth cue mode(PSUPPR,PALLOW)
REAL DQMIN,DQMAX	depth cue reference plane(NPC)
REAL DCSFMI,DCSFMX	depth cue scale factors
INTEGER CTYPE	colour type
INTEGER COLI	colour index
INTEGER NCC	number of components of colour value
REAL COLR(CCSBSZ)	colour values

INQUIRE COLOUR MAPPING STATE

SUBROUTINE PQCMS(WKID,CMM,MLDR,ERRIND,LDR,DATREC)

Input Parameters:

INTEGER WKID	workstation identifier
INTEGER CMM	colour mapping method
INTEGER MLDR	dimension of data record array

Output Parameters:

INTEGER ERRIND	error indicator
INTEGER LDR	length of data record array
CHARACTER*80 DATREC(MLDR)	data record

DATREC parameters to build COLOUR MAPPING DATA RECORD for CMM = PTRUE:

The IA array contains:

- The number of true colours available

The other array are empty.

IL= 1

IA(1)= number of true colours available

RL= 0

RA= ()

SL= 0

LSTR= ()

STR= ()

DATREC parameters to build COLOUR MAPPING DATA RECORD for CMM = PSUD:

The IA array contains:

- The number of pseudo colour entries available

The other array are empty.

IL= 1

IA(1)= number of pseudo colour entries available

RL= 0

RA= ()
 SL= 0
 LSTR= ()
 STR= ()

DATREC parameters to build COLOUR MAPPING DATA RECORD for CMM = PSUDN:
 No data record

INQUIRE LIST element OF COLOUR MAPPING INDICES

SUBROUTINE PQECMI(WKID,N,ERRIND,OL,CMI)

Input Parameters:

INTEGER WKID	workstation identifier
INTEGER N	list element requested

Output Parameters:

INTEGER ERRIND	error indicator
INTEGER OL	number of colour mapping table entries
INTEGER CMI	Nth element of list of defined colour mapping indices

INQUIRE COLOUR MAPPING REPRESENTATION

SUBROUTINE PQCMR(WKID,CMI,TYPE,MLDR,ERRIND,CMM,LDR,DATREC)

Input Parameters:

INTEGER WKID	workstation identifier
INTEGER CMI	colour mapping index
INTEGER TYPE	type of return value(PSET,PREALI)
INTEGER MLDR	dimension of data record array

Output Parameters:

INTEGER ERRIND	error indicator
INTEGER CMM	colour mapping method
INTEGER LDR	length of data record array
CHARACTER*80 DATREC(MLDR)	data record ²⁰

²⁰See SET COLOUR MAPPING REPRESENTATION for a description of the colour mapping data record.

13.4.2 Inquiry functions for workstation description table

INQUIRE DIRECT COLOUR MODEL FACILITIES

SUBROUTINE PQDCMF(WTYPE,N,ERRIND,NDCM,DCM)

Input Parameters:

INTEGER WTYPE	workstation type
INTEGER N	list element requested of direct colour model

Output Parameters:

INTEGER ERRIND	error indicator
INTEGER NDCM	number of available direct colour model
INTEGER DCM	Nth element of list of defined direct colour model

INQUIRE RENDERING COLOUR MODEL FACILITIES

SUBROUTINE PQRCMF(WTYPE,N,ERRIND,NRCM,RCM)

Input Parameters:

INTEGER WTYPE	workstation type
INTEGER N	list element requested of rendering colour model

Output Parameters:

INTEGER ERRIND	error indicator
INTEGER NRCM	number of available rendering colour model
INTEGER RCM	Nth element of list of defined rendering colour model

INQUIRE DYNAMICS OF WORKSTATION PLUS

SUBROUTINE PQDCWP(WTYPE,ERRIND,DMR,RFR,PSR,LSR,DCR,CMR)

Input Parameters:

INTEGER WTYPE	workstation type
---------------	------------------

Output Parameters:

INTEGER ERRIND	error indicator
INTEGER DMR	data mapping representation(PIRG,PIMM,PCBS)
INTEGER RFR	reflectance representation(PIRG,PIMM,PCBS)
INTEGER PSR	parametric surface representation (PIRG,PIMM,PCBS)
INTEGER LSR	light source representation(PIRG,PIMM,PCBS)
INTEGER DCR	depth cue representation(PIRG,PIMM,PCBS)
INTEGER CMR	colour mapping representation(PIRG,PIMM,PCBS)

INQUIRE POLYLINE FACILITIES PLUS

SUBROUTINE PQPLFP(WTYPE,NRLT,NRSM,ERRIND,NLT,LT,NLW,NOMLW,
*RLWMIN,RLWMAX,NSM,SM,NPPLI)

Input Parameters:

INTEGER WTYPE	workstation type
INTEGER NRLT	list of element requested of linetypes
INTEGER NRSM	list of element requested of shading method

Output Parameters:

INTEGER ERRIND	error indicator
INTEGER NLT	number of available linetypes
INTEGER LT	element NRLT of list of available linetypes
INTEGER NLW	number of available linewidths
REAL NOMLW	nominal linewidth
REAL RLWMIN,RLWMAX	range of linewidths
INTEGER NSM	number of available shading method
INTEGER SM	element NRSM of list of available shading method
INTEGER NPPLI	number of predefined polyline indices

INQUIRE PREDEFINED POLYLINE REPRESENTATION PLUS

SUBROUTINE PQPPLP(WTYPE,PLI,CCSBSZ,MLDR,ERRIND,LTYPE,LWIDTH,
*CTYPE,COLI,NCC,COLR,PLSM,ACRI,LDR,DATREC)

Input Parameters:

INTEGER WTYPE	workstation type
INTEGER PLI	predefined polyline index
INTEGER CCSBSZ	colour component specification buffer size
INTEGER MLDR	dimension of curve approximation criteria data record array

Output Parameters:

INTEGER ERRIND	error indicator
INTEGER LTYPE	linetype
REAL LWIDTH	linewidth scale factor
INTEGER CTYPE	colour type
INTEGER COLI	colour index
INTEGER NCC	number of components of colour value
REAL COLR(CCSBSZ)	colour values
INTEGER PLSM	polyline shading method
INTEGER ACRI	curve approximation criteria type
INTEGER LDR	length of data record array
CHARACTER*80 DATREC(MLDR)	curve approximation criteria data record ²¹

²¹See SET CURVE APPROXIMATION CRITERIA for a description of the curve approximation criteria data records.

INQUIRE PREDEFINED POLYMARKER REPRESENTATION PLUS

SUBROUTINE PQPPMP(WTYPE,PMI,CCSBSZ,ERRIND,MTYPE,MSZSF,
*CTYPE,COLI,NCC,COLR)

Input Parameters:

INTEGER WTYPE	workstation type
INTEGER PMI	predefined polymarker index
INTEGER CCSBSZ	colour component specification buffer size

Output Parameters:

INTEGER ERRIND	error indicator
INTEGER MTYPE	marker type
REAL MSZSF	marker scale factor
INTEGER CTYPE	colour type
INTEGER COLI	colour index
INTEGER NCC	number of components of colour value
REAL COLR(CCSBSZ)	colour values

INQUIRE PREDEFINED TEXT REPRESENTATION PLUS

SUBROUTINE PQPTXP(WTYPE,PTXI,CCSBSZ,ERRIND,FONT,PREC,CHXP,CHSP,
*CTYPE,COLI,NCC,COLR)

Input Parameters:

INTEGER WTYPE	workstation type
INTEGER PTXI	predefined text index
INTEGER CCSBSZ	colour component specification buffer size

Output Parameters:

INTEGER ERRIND	error indicator
INTEGER FONT	text font
INTEGER PREC	text precision(PSTRP,PCHARP,PSTRKP)
REAL CHXP	character expansion factor
REAL CHSP	character spacing
INTEGER CTYPE	colour type
INTEGER COLI	colour index
INTEGER NCC	number of components of colour value
REAL COLR(CCSBSZ)	colour values

INQUIRE INTERIOR FACILITIES PLUS

SUBROUTINE PQIFP(WTYPE,NI,NH,NRSM,ERRIND,NIS,IS,NHS,HS,NSM,
*SM,NPFAI)

Input Parameters:

INTEGER WTYPE	workstation type
INTEGER NI	list element of interior style requested
INTEGER NH	list element of hatch style requested
INTEGER NRSM	list element of shading method requested

Output Parameters:

INTEGER ERRIND	error indicator
INTEGER NIS	number of available interior styles
INTEGER IS	element NI of list of available interior styles
INTEGER NHS	number of available hatch style
INTEGER HS	element NH of list of available hatch styles
INTEGER NSM	number of available shading method
INTEGER SM	element NRSM of list of available shading method
INTEGER NPFAI	number of predefined interior indices

INQUIRE PREDEFINED INTERIOR REPRESENTATION PLUS

SUBROUTINE PQPIP(WTYPE,PII,CCSBSZ,ERRIND,INTS,STYLI,
*CTYPE,COLI,NCC,COLR,ISM)

Input Parameters:

INTEGER WTYPE	workstation type
INTEGER PII	predefined interior index
INTEGER CCSBSZ	colour component specification buffer size

Output Parameters:

INTEGER ERRIND	error indicator
INTEGER INTS	interior style
INTEGER STYLI	interior style index
INTEGER CTYPE	colour type
INTEGER COLI	colour index
INTEGER NCC	number of components of colour value
REAL COLR(CCSBSZ)	colour values
INTEGER ISM	interior shading method

INQUIRE PREDEFINED EDGE REPRESENTATION PLUS

SUBROUTINE PQPEDP(WTYPE,PEDI,CCSBSZ,ERRIND,EDFLAG,EDTYPE,
*EWIDTH,CTYPE,COLI,NCC,COLR)

Input Parameters:

INTEGER WTYPE	workstation type
INTEGER PEDI	predefined edge index
INTEGER CCSBSZ	colour component specification buffer size

Output Parameters:

INTEGER ERRIND	error indicator
INTEGER EDFLAG	edge flag (POFF,PON)
INTEGER EDTYPE	edge type
REAL EWIDTH	edge scale factor
INTEGER CTYPE	colour type
INTEGER COLI	colour index
INTEGER NCC	number of components of colour value
REAL COLR(CCSBSZ)	colour values

INQUIRE DATA MAPPING FACILITIES

SUBROUTINE PQDMF(WTYPE,N,ERRIND,NDM,DM,NPDAI)

Input Parameters:

INTEGER WTYPE	workstation type
INTEGER N	list element requested of data mapping methods

Output Parameters:

INTEGER ERRIND	error indicator
INTEGER NDM	number of available data mapping methods
INTEGER DM	Nth element of list of available data mapping methods
INTEGER NPDAI	number of predefined data mapping indices

INQUIRE PREDEFINED DATA MAPPING REPRESENTATION

SUBROUTINE PQPDMR(WTYPE,PDMI,MLDR,ERRIND,DMM,LDR,DATREC)

Input Parameters:

INTEGER WTYPE	workstation type
INTEGER PDMI	predefined data mapping index
INTEGER MLDR	dimension of data record array

Output Parameters:

INTEGER ERRIND	error indicator
INTEGER DMM	data mapping method
INTEGER LDR	length of data record array
CHARACTER*80 DATREC(MLDR)	data mapping data record ²²

INQUIRE REFLECTANCE FACILITIES

SUBROUTINE PQRFF(WTYPE,N,NRRFP,ERRIND,NRFM,RFM,NPRFI,NRFP,RFP)

Input Parameters:

INTEGER WTYPE	workstation type
INTEGER N	list element requested of reflectance models
INTEGER NRRFP	list of element requested of reflectance properties

Output Parameters:

INTEGER ERRIND	error indicator
INTEGER NRFM	number of available reflectance model
INTEGER RFM	Nth element of list of available reflectance models
INTEGER NPRFI	number of predefined reflectance indices
INTEGER NRFP	number of available reflectance properties
INTEGER RFP	element NRRFP of list of available reflectance properties

INQUIRE PREDEFINED REFLECTANCE REPRESENTATION

SUBROUTINE PQPRFR(WTYPE,PRFI,MLDR,ERRIND,RFM,RPTYPE,LDR,DATREC)

Input Parameters:

INTEGER WTYPE	workstation type
INTEGER PRFI	predefined reflectance index
INTEGER MLDR	dimension of data record array

Output Parameters:

INTEGER ERRIND	error indicator
INTEGER RFM	reflectance model
INTEGER RPTYPE	reflectance properties type
INTEGER LDR	length of data record array
CHARACTER*80 DATREC(MLDR)	data record ²³

²²See SET DATA MAPPING METHOD for a description of the data mapping data records.

²³See SET REFLECTANCE PROPERTIES for a description of the reflectance properties data records.

INQUIRE CURVE AND SURFACE FACILITIES

It has been broken into four related functions: INQUIRE CURVE FACILITIES, INQUIRE PARAMETRIC SURFACE FACILITIES, INQUIRE B-SPLINE SURFACE FACILITIES, and INQUIRE TRIMMING CURVE FACILITIES.

INQUIRE CURVE FACILITIES

SUBROUTINE PQCVF(WTYPE,N,ERRIND,MNUBSC,NCACT,CACT)

Input Parameters:

INTEGER WTYPE

workstation type

INTEGER N

list element requested of curve approximation
criteria types

Output Parameters:

INTEGER ERRIND

error indicator

INTEGER MNUBSC

maximum non-uniform b-spline curve order supported

INTEGER NCACT

number of available curve approximation criteria types

INTEGER CACT

Nth element of list of available curve
approximation criteria types

INQUIRE PARAMETRIC SURFACE FACILITIES

SUBROUTINE PQPSF(WTYPE,N,ERRIND,NPSCT,PSCT,NPPSI)

Input Parameters:

INTEGER WTYPE

workstation type

INTEGER N

list element requested of parametric surface
characteristics types

Output Parameters:

INTEGER ERRIND

error indicator

INTEGER NPSCT

number of available parametric surface characteristics

INTEGER PSCT

Nth element of list of available parametric surface
characteristics types

INTEGER NPPSI

number of predefined parametric surface indices

INQUIRE B-SPLINE SURFACE FACILITIES

SUBROUTINE PQBSSF(WTYPE,N,ERRIND,MNUBSS,NCAST,CAST)

Input Parameters:

INTEGER WTYPE

workstation type

INTEGER N

list element requested of surface approximation
criteria types*Output Parameters:*

INTEGER ERRIND

error indicator

INTEGER MNUBSS

maximum non-uniform b-spline surface order supported

INTEGER NCAST

number of available surface approximation criteria types

INTEGER CAST

Nth element of list of available surface
approximation criteria types**INQUIRE TRIMMING CURVE FACILITIES**

SUBROUTINE PQTCF(WTYPE,N,ERRIND,MTRIMC,NTCACT,TCACT)

Input Parameters:

INTEGER WTYPE

workstation type

INTEGER N

list element requested of trimming curve
approximation criteria types*Output Parameters:*

INTEGER ERRIND

error indicator

INTEGER MTRIMC

maximum trimming curve order supported

INTEGER NTCACT

number of available trimming curve approximation
criteria types

INTEGER TCACT

Nth element of list of available trimming curve
approximation criteria types

INQUIRE PREDEFINED PARAMETRIC SURFACE REPRESENTATION

SUBROUTINE PQPPSR(WTYPE,PPSI,MLDRSA,MLDRPS,ERRIND,ACRI,LDRSA,
*DARECS,PSCH,LDRPS,DARECP)

Input Parameters:

INTEGER WTYPE	workstation type
INTEGER PPSI	predefined parametric surface bundle index
INTEGER MLDRSA	dimension of surface approximation criteria data record array
INTEGER MLDRPS	dimension of parametric surface characteristics data record array

Output Parameters:

INTEGER ERRIND	error indicator
INTEGER ACRI	surface approximation criteria type
INTEGER LDRSA	length of surface approximation criteria data record
CHARACTER*80 DARECS(MLDRSA)	surface approximation criteria data record ²⁴
INTEGER PSCH	parametric surface characteristics type
INTEGER LDRPS	length of parametric surface characteristics data record
CHARACTER*80 DARECP(MLDRPS)	parametric surface characteristics data record ²⁵

INQUIRE PREDEFINED PATTERN REPRESENTATION PLUS

SUBROUTINE PQPPAP(WTYPE,PAI,CCSBSZ,DIMX,DIMY,ERRIND,
*DX,DY,CTYPE,COLIA,NCC,COLRA)

Input Parameters:

INTEGER WTYPE	workstation type
INTEGER PAI	predefined pattern index
INTEGER CCSBSZ	colour component specification buffer size
INTEGER DIMX,DIMY	maximum pattern array dimension

Output Parameters:

INTEGER ERRIND	error indicator
INTEGER DX,DY	pattern array dimensions
INTEGER CTYPE	colour type
INTEGER COLIA(DIMX,DIMY)	colour index
INTEGER NCC	number of components of colour value specification
REAL COLRA(CCSBSZ)	colour values

²⁴See SET SURFACE APPROXIMATION CRITERIA for a description of the surface approximation criteria data records.

²⁵See SET PARAMETRIC SURFACE CHARACTERISTICS for a description of the parametric surface characteristics data records.

INQUIRE LIGHT SOURCE FACILITIES

SUBROUTINE PQLSF(WTYPE,N,ERRIND,NLSTYP,LSTYP,MSNALS,NPLSI)

Input Parameters:

INTEGER WTYPE	workstation type
INTEGER N	list element requested of light source indices

Output Parameters:

INTEGER ERRIND	error indicator
INTEGER NLSTYP	number of available light source types
INTEGER LSTYP	Nth element of list of available light source types
INTEGER MSNALS	maximum number of simultaneously active non-ambient light source
INTEGER NPLSI	number of predefined light source indices

INQUIRE PREDEFINED LIGHT SOURCE REPRESENTATION

SUBROUTINE PQPLSR(WTYPE,PLSI,MLDR,ERRIND,LSTYP,LDR,DATREC)

Input Parameters:

INTEGER WTYPE	workstation type
INTEGER PLSI	predefined light source index
INTEGER MLDR	dimension of data record array

Output Parameters:

INTEGER ERRIND	error indicator
INTEGER LSTYP	light source type
INTEGER LDR	length of data record array
CHARACTER*80 DATREC(MLDR)	light source data record ²⁶

INQUIRE DEPTH CUE FACILITIES

SUBROUTINE PQDCF(WTYPE,N,ERRIND,NPDCI,NDCM,DCM)

Input Parameters:

INTEGER WTYPE	workstation type
INTEGER N	list element requested of depth cue modes

Output Parameters:

INTEGER ERRIND	error indicator
INTEGER NPDCI	number of predefined depth cue indices
INTEGER NDCM	number of depth cue modes
INTEGER DCM	Nth element of list of depth cue mode

²⁶See SET LIGHT SOURCE REPRESENTATION for a description of the light source data record.

INQUIRE PREDEFINED DEPTH CUE REPRESENTATION

SUBROUTINE PQPDCR(WTYPE,PDCI,CCSBSZ,ERRIND,DCMODE,DQMIN,DQMAX,
*DCSFMI,DCSFMX,CTYPE,COLI,NCC,COLR)

Input Parameters:

INTEGER WTYPE	workstation type
INTEGER PDCI	predefined depth cue index
INTEGER CCSBSZ	colour component specification buffer size

Output Parameters:

INTEGER ERRIND	error indicator
INTEGER DCMODE	depth cue mode(PSUPPR,PALLOW)
REAL DQMIN,DQMAX	depth cue reference planes(NPC)
REAL DCSFMI,DCSFMX	depth cue scale factors
INTEGER CTYPE	colour type
INTEGER COLI	colour index
INTEGER NCC	number of components of colour value
REAL COLR(CCSBSZ)	colour cvalues

INQUIRE COLOUR MAPPING FACILITIES

SUBROUTINE PQCMF(WTYPE,N,ERRIND,NCMTYP,CMTYP,NPCMI)

Input Parameters:

INTEGER WTYPE	workstation type
INTEGER N	list element requested of colour mapping indices

Output Parameters:

INTEGER ERRIND	error indicator
INTEGER NCMTYP	number of available colour mapping methods
INTEGER CMTYP	Nth element of list of available colour mapping methods
INTEGER NPCMI	number of predefined colour mapping indices

INQUIRE COLOUR MAPPING METHOD FACILITIES

SUBROUTINE PQCMMF(WTYPE,CMM,MLDR,ERRIND,LDR,DATREC)

Input Parameters:

INTEGER WTYPE	workstation type
INTEGER CMM	colour mapping method
INTEGER MLDR	dimension of data record array

Output Parameters:

INTEGER ERRIND	error indicator
INTEGER LDR	length of data record array
CHARACTER*80 DATREC(MLDR)	data record

DATREC parameters to build COLOUR MAPPING METHOD DATA RECORD
for CMM=PTRUE:

The IA array contains:

- The number of true colours available

The other array are empty.

IL= 1

IA(1)= number of true colours available

RL= 0

RA= ()

SL= 0

LSTR= ()

STR= ()

DATREC parameters to build COLOUR MAPPING METHOD DATA RECORD
for CMM=PSUD:

The IA array contains:

- The maximum number of pseudo colour entries

The other array are empty.

IL= 1

IA(1)= maximum number of pseudo colour entries

RL= 0

RA= ()

SL= 0

LSTR= ()

STR= ()

DATREC parameters to build COLOUR MAPPING METHOD DATA RECORD
for CMM= PSUDN: No data record

INQUIRE PREDEFINED COLOUR MAPPING REPRESENTATION

SUBROUTINE PQPCMR(WTYPE,PCMI,MLDR,ERRIND,CMM,LDR,DATREC)

Input Parameters:

INTEGER WTYPE	workstation type
INTEGER PCMI	predefined colour mapping index
INTEGER MLDR	dimension of data record array

Output Parameters:

INTEGER ERRIND	error indicator
INTEGER CMM	colour mapping method
INTEGER LDR	length of data record array
CHARACTER*80 DATREC(MLDR)	data record ²⁷

INQUIRE WORKSTATION STATE TABLE LENGTHS PLUS

SUBROUTINE PQWSLP(WTYPE,ERRIND,MDMBTE,MRFBTE,MPSBTE,MLSTE,
*MDCTE,MCMTE)

Input Parameters:

INTEGER WTYPE	workstation type
---------------	------------------

Output Parameters:

INTEGER ERRIND	error indicator
INTEGER MDMBTE	maximum number of data mapping bundle table entries
INTEGER MRFBTE	maximum number of reflectance bundle table entries
INTEGER MPSBTE	maximum number of parametric surface bundle table entries
INTEGER MLSTE	maximum number of light source table entries
INTEGER MDCTE	maximum number of depth cue table entries
INTEGER MCMTE	maximum number of colour mapping table entries

INQUIRE GENERALIZED DRAWING PRIMITIVE 3

SUBROUTINE PQGDP3(WTYPE,GDP,ERRIND,NBND,BNDL)

Input Parameters:

INTEGER WTYPE	workstation type
INTEGER GDP	3D GDP identifier

Output Parameters:

INTEGER ERRIND	error indicator
INTEGER NBND	number of sets of attributes used
INTEGER BNDL(7)	list of sets of attributes used (PPLATT,PPMATT,PTXATT,PINATT,PEDATT, ²⁸ PRFATT,PPSATT)

This function is defined in PHIGS part 1. Additional attributes are defined in PHIGS part 4. This binding shows those additional attributes.

²⁷See SET COLOUR MAPPING REPRESENTATION for a description of the colour mapping data record.

²⁸already defined in PHIGS

INQUIRE GENERALIZED DRAWING PRIMITIVE

SUBROUTINE PQGDP(WTYPE,GDP,ERRIND,NBND,BNDL)

Input Parameters:

INTEGER WTYPE	workstation type
INTEGER GDP	GDP identifier

Output Parameters:

INTEGER ERRIND	error indicator
INTEGER NBND	number of sets of attributes used
INTEGER BNDL(7)	list of sets of attributes used (PPLATT,PPMATT,PTXATT,PINATT,PEDATT, ²⁹ PRFATT,PPSATT)

This function is defined in PHIGS part 1. Additional attributes are defined in PHIGS part 4. This binding shows those additional attributes.

²⁹already defined in PHIGS

INQUIRE CURRENT ELEMENT TYPE AND SIZE

SUBROUTINE PQCETS(ERRIND,ELTYPE,IL,RL,SL)

Output Parameters:

INTEGER ERRIND

error indicator

INTEGER ELTYPE

element type

(PENIL,PEPL3,PEPL,PEPM3,PEPM,PETX3,PETX,
 PEATR3,PEATR,PEFA3,PEFA,PEFAS3,PEFAS,
 PECA3,PECA,PEGDP3,PEGDP,PEPLI,PEPMI,
 PETXI,PEII,PEEDI,PELN,PELWSC,PEPLCI,
 PEMK,PEMKSC,PEPMCI,PETXFN,PETXPR,
 PECHXP,PECHSP,PETXCI,PECHII,PECHUP,
 PETXP,PETXAL,PEATCH,PEATCU,PEATP,
 PEATAL,PEANST,PEIS,PEISI,PEICI,PEEDFG,
 PEEDT,PEEWS,PEEDCI,PEPA,PEPRPV,
 PEPARF,PEADS,PERES,PEIASF,
 PEHRID,PELMT3,PELMT,PEGMT3,PEGMT,
 PEMCV3,PEMCV,PEMCLI,PERMCV,PEVWI,
 PEEXST,PELB,PEAP,PEGSE,PEPKID,³⁰
 PEPLS3,PEFS3D,PEFSD,PECA3P,PESFS3,
 PESFSD,PETS3D,PETSD,PETST3,PETSTD,
 PEQM3D,PEQMD,PEBC3,PEBC3C,PEBS3,
 PEB3D,PEDMI,PERFI,PEBII,PEBDMI,
 PEBRFI,PEPRSI,PEPLC,PEPLSM,PEPMC,
 PETXC,PEFDM,PEFCM,PEIC,PEISM,
 PEDMM,PERFP,PERFM,PEBIS,PEBISI,
 PEBIC,PEBISM,PEBDMM,PEBRFP,PEBRFM,
 PELSS,PEEDC,PECAC,PESAC,PEPSC,
 PERCM,PEDPCI,PECM)

INTEGER IL

dimension of integer array

INTEGER RL

dimension of real array

INTEGER SL

dimension of character array

This function is defined in PHIGS part 1. Additional element types are defined in PHIGS part 4. This binding shows those additional element types.

³⁰ already defined in PHIGS

INQUIRE ELEMENT TYPE AND SIZE

SUBROUTINE PQETS(STRID,ELENUM,ERRIND,ELTYPE,IL,RL,SL)

Input Parameters:

INTEGER STRID	structure identifier
INTEGER ELENUM	element number

Output Parameters:

INTEGER ERRIND	error indicator
INTEGER ELTYPE	element type

(PENIL, PEPL3, PEPL, PEP3, PEP, PETX3, PETX, PEATR3, PEATR, PEFA3, PEFA, PEFAS3, PEFAS, PECA3, PECA, PEGDP3, PEGDP, PEPLI, PEPMI, PETXI, PEII, PEEDI, PELN, PELWSC, PEPLCI, PEMK, PEMKSC, PEP3, PETXFN, PETXPR, PECHXP, PECHSP, PETXCI, PECHH, PECHUP, PETXP, PETXAL, PEATCH, PEATCU, PEATP, PEATAL, PEANST, PEIS, PEISI, PEICI, PEEDFG, PEEDT, PEEWSC, PEEDCI, PEPA, PEPRPV, PEPARF, PEADS, PERES, PEIASF, PEHRID, PELMT3, PELMT, PEGMT3, PEGMT, PEMCV3, PEMCV, PEMCLI, PERMCV, PEVWI, PEEXST, PELB, PEAP, PEGSE, PEPKID,³¹ PEPLS3, PEFS3D, PEFSD, PECA3P, PESFS3, PESFSD, PETS3D, PETSD, PETST3, PETSTD, PEQM3D, PEQMD, PEB3, PEB3C, PEB3, PEB3D, PEDMI, PERFI, PEBII, PEBDMI, PEBRFI, PEPRSI, PEPLC, PEPLSM, PEP3, PETXC, PEFDM, PEF3, PEIC, PEISM, PEDMM, PERFR, PERFM, PEBIS, PEBISI, PEBIC, PEBISM, PEBDMM, PEBRFP, PEBRFM, PELSS, PEEDC, PECAC, PESAC, PEPSC, PERCM, PEDPCI, PECMI)

INTEGER IL	dimension of integer array
INTEGER RL	dimension of real array
INTEGER SL	dimension of character array

This function is defined in PHIGS part 1. Additional element types are defined in PHIGS part 4. This binding shows those additional element types.

³¹already defined in PHIGS

INQUIRE ELEMENT CONTENT

SUBROUTINE PQECO(STRID,ELENUM,IIL,IRL,ISL,ERRIND,IL,IA,RL,RA,SL,
*LSTR,STR)

Input Parameters:

INTEGER STRID	structure identifier
INTEGER ELENUM	element position
INTEGER IIL	dimension of integer array
INTEGER IRL	dimension of real array
INTEGER ISL	dimension of character array

Output Parameters:

INTEGER ERRIND	error indicator
INTEGER IL	number of integer entries
INTEGER IA(IIL)	array of containing integer entries
INTEGER RL	number of real entries
REAL RA(IRL)	array of containing real entries
INTEGER SL	number of character string entries
INTEGER LSTR(ISL)	length of each character string entry
CHARACTER*80 STR(ISL)	character string entries ³²

This function is defined in PHIGS part 1. Additional attributes are defined in PHIGS part 4. This binding shows those additional element types.

³²See INQUIRE CURRENT ELEMENT CONTENT for details on interpreting the information returned in the integer, real and character arrays.

INQUIRE CURRENT ELEMENT CONTENT

SUBROUTINE PQCECO(IIL,IRL,ISL,ERRIND,IL,IA,RL,RA,SL,LSTR,STR)

Input Parameters:

INTEGER IIL	dimension of integer array
INTEGER IRL	dimension of real array
INTEGER ISL	dimension of character array

Output Parameters:

INTEGER ERRIND	error indicator
INTEGER IL	number of integer entries
INTEGER IA(IIL)	array of containing integer entries
INTEGER RL	number of real entries
REAL RA(IRL)	array of containing real entries
INTEGER SL	number of character string entries
INTEGER LSTR(ISL)	length of each character string entry
CHARACTER*80 STR(ISL)	character string entries

Output parameters for STRUCTURE CONTENT DATA RECORD for
ELTYPE = PEPLS3:

The IA array contain:

- The start element number and the end element number of following data
 - vertex colour indices
 - vertex colour components
- If the optional data is not present, the value of the "start element number" is set to zero and the value of the "end element number" is set to -1.
- data per vertex flag
- The colour type
- The number of components of colour value
- The number of point list
- The array of end indices for point lists
- The vertex colour indices

The RA array contains:

- The coordinates of points
- The vertex colour components

$IL = 8 + IA(8) + (IA(2) - IA(1) + 1)$

IA(1) = start element number in IA of vertex colour indices

IA(2) = end element number in IA of vertex colour indices

IA(3) = start element number in RA of vertex colour components

IA(4) = end element number in RA of vertex colour components

IA(5) = data per vertex flag(PCD,PCDC)

IA(6) = colour type

IA(7) = number of colour components of colour value

IA(8) = number of point lists in polyline set 3 with colour

IA = element 9 through IA(8)+8 contain the array of end indices for point lists in polyline set 3 with data

IA = element IA(1) through IA(2) contain the vertex colour indices

RL = IA(IA(8)+8)*3

RA = element 1 through IA(IA(8)+8)*3 contain the coordinates of points

This function is defined in PHIGS part 1. Additional attributes are defined in PHIGS part 4. This binding shows those additional element types.

example x1,x2,...,y1,y2,...,z1,z2...

RA=element IA(3) through IA(4) contain the vertex colour components

example(colour type =PRGB) r1,g1,b1,r2,g2,b2,.....

SL= 0

LSTR= ()

STR= ()

Output parameters for STRUCTURE CONTENT DATA RECORD for
ELTYPE = PEFS3D:

The IA array contains:

- The start element number and the end element number of following data
 - edge data
 - vertex colour indices
 - vertex colour components
 - vertex normal data
 - vertex application-specific data

If the optional data is not present, the value of the "start element number" is set to zero and the value of the "end element number" is set to -1.

- The data per facet flag
- The data per edge flag
- The data per vertex flag
- The colour type
- The number of components of colour value(NCC)
- The number of point lists
- The length of application-specific data list per facet
- The length of application-specific data list per vertex
- The array of end indices for point lists
- The facet colour indices
- The edge data
- The vertex colour indices.

The RA array contains:

- The coordinates of points
- The facet colour components
- The facet normal data
- The facet application-specific data
- The vertex colour components
- The vertex normal data
- The vertex application-specific data

IL=19+IA(16)+(IA(2)-IA(1)+1)+(IA(4)-IA(3)+1)

IA(1)= start element number in IA of edge data

IA(2)= end element number in IA of edge data

IA(3)= start element number in IA of vertex colour indices

IA(4)= end element number in IA of vertex colour indices

IA(5)= start element number in RA of vertex colour components

IA(6)= end element number in RA of vertex colour components

IA(7)= start element number in RA of vertex normal data

IA(8)= end element number in RA of vertex normal data

IA(9)= start element number in RA of vertex application-specific data

IA(10)= end element number in RA of vertex application-specific data

IA(11)= data per facet flag(PFNO,PFC,PFN,PFD,PFCN,PFCD,PFND,PFCND)

IA(12)= data per edge flag(PENO,PEVF)

IA(13)= data per vertex flag

(PCD,PCDC,PCDN,PCDD,PCDCN,PCDCD,PCDND,PCDCND)

IA(14)= colour type
 IA(15)= number of components of colour value = NCC
 IA(16)= number of point lists in fill area set 3 with data
 IA(17)= length of application-specific data list per facet
 IA(18)= length of application-specific data list per vertex
 IA(19)= facet colour index
 IA=element 20 through IA(16)+19 contain the array of end indices for point lists in fill area set 3 with data
 IA=element IA(1) through IA(2) contain the edge data
 IA=element IA(3) through IA(4) contain the vertex colour indices
 $RL = IA(IA(16)+19)*3 + IA(15)+3 + IA(17) + (IA(6)-IA(5)+1) + (IA(8)-IA(7)+1) + (IA(10)-IA(9)-1)$
 RA=element 1 through IA(IA(16)+19)*3=NUM1 contain the coordinates of points
 example x1,x2,...y1,y2,...z1,z2...
 RA=element NUM1+1 through NUM1+NCC=NUM2 contain the facet colour components
 example(colour type =PRGB) r1,g1,b1,r2,g2,b2,.....
 RA=element NUM2+1 through NUM2+3=NUM3 contain the facet normal data
 RA=element NUM3+1 through NUM3+IA(17) contain the facet application-specific data
 RA=element IA(5) through IA(6) contain the vertex colour components
 RA=element IA(7) through IA(8) contain the vertex normal data
 example x1,x2,...y1,y2,...z1,z2...
 RA=element IA(9) through IA(10) contain the vertex application-specific data
 SL= 0
 LSTR= ()
 STR= ()

Output parameters for STRUCTURE CONTENT DATA RECORD for
ELTYPE = PEFSD:

The IA array contains:

- The start element number and the end element number of following data
 - edge data
 - vertex colour indices
 - vertex colour components
 - vertex normal data
 - vertex application-specific data

If the optional data is not present, the value of the "start element number" is set to zero and the value of the "end element number" is set to -1.

- The data per facet flag
- The data per edge flag
- The data per vertex flag
- The colour type
- The number of components of colour value(NCC)
- The number of point lists
- The length of application-specific data list per facet
- The length of application-specific data list per vertex
- The array of end indices for point lists
- The facet colour indices
- The edge data
- The vertex colour indices

The RA array contains:

- The coordinates of points
- The facet colour components
- The facet normal data
- The facet application-specific data

- The vertex colour components
- The vertex normal data
- The vertex application-specific data

$IL = 19 + IA(16) + (IA(2) - IA(1) + 1) + (IA(4) - IA(3) + 1)$

IA(1)= start element number in IA of edge data

IA(2)= end element number in IA of edge data

IA(3)= start element number in IA of vertex colour indices

IA(4)= end element number in IA of vertex colour indices

IA(5)= start element number in RA of vertex colour components

IA(6)= end element number in RA of vertex colour components

IA(7)= start element number in RA of vertex normal data

IA(8)= end element number in RA of vertex normal data

IA(9)= start element number in RA of vertex application-specific data

IA(10)= end element number in RA of vertex application-specific data

IA(11)= data per facet flag(PFNO,PFC,PFN,PFD,PFCN,PFCD,PFND,PECND)

IA(12)= data per edge flag(PENO,PEVF)

IA(13)= data per vertex flag

(PCD,PCDC,PCDN,PCDD,PCDCN,PCDCD,PCDND,PCDCND)

IA(14)= colour type

IA(15)= number of components of colour value = NCC

IA(16)= number of point lists in fill area set with data

IA(17)= length of application-specific data list per facet

IA(18)= length of application-specific data list per vertex

IA(19)= facet colour indices

IA=element 20 through IA(16)+19 contain the array of end indices for point lists in fill area set with data

IA=element IA(1) through IA(2) contain the edge data

IA=element IA(3) through IA(4) contain the vertex colour indices

$RL = IA(IA(16)+19)*2 + IA(15) + IA(17) + (IA(6) - IA(5) + 1) + (IA(8) - IA(7) + 1) + (IA(10) - IA(9) - 1)$

RA=element 1 through IA(IA(16)+19)*2=NUM1 contain the coordinates of points

example x1,x2,...y1,y2...

RA=element NUM1+1 through NUM1+NCC=NUM2 contain the facet colour components

example(colour type = PRGB) r1,g1,b1,r2,g2,b2,.....

RA=element NUM2+1 through NUM2+3=NUM3 contain the facet normal data

RA=element NUM3+1 through NUM3+IA(17) contain the facet application-specific data

RA=element IA(5) through IA(6) contain the vertex colour components

RA=element IA(7) through IA(8) contain the vertex normal data

example x1,x2,...y1,y2,...z1,z2...

RA=element IA(9) through IA(10) contain the vertex application-specific data

SL= 0

LSTR= ()

STR= ()

Output parameters for STRUCTURE CONTENT DATA RECORD for

ELTYPE = PECA3P:

The IA array contains:

- The number of columns(NC)
- The number of rows(NR)
- The colour type(CT)
- The number of components of colour value
- The list of colour indices. There are NC*NR colour indices, if CT is indirect.

The RA array contains:

- The cell parallelogram(P)
- The cell parallelogram(Q)
- The cell parallelogram(R)
- The list of colour values. There are $NCC \cdot NC \cdot NR$ colour values, that having as many components as required by CT.

Common element:

IL= 3+*

IA(1)= number of columns = NC

IA(2)= number of rows = NR

IA(3)= colour type = CT

IA(4)= number of components of colour value = NCC

RL= 9+*

RA=element 1 through 3 contain the cell parallelogram(P)

RA=element 4 through 6 contain the cell parallelogram(Q)

RA=element 7 through 9 contain the cell parallelogram(R)

SL= 0

LSTR= ()

STR= ()

Individual element:

CASE colour type=PINDIR:

IA=element 4 through $NC \cdot NR + 3$ contain colour indices

CASE colour type=PRGB or PCIE or PHSV or PHLS:

RA=element 10 through $NCC \cdot NC \cdot NR + 9$ contain the colour components

Output parameters for STRUCTURE CONTENT DATA RECORD for
ELTYPE = PESFS3:

The IA array contains:

- The start element number and the end element number of following data
 - facet colour indices
 - edge data
 - vertex colour indices
 - facet colour components
 - facet normal data
 - facet application-specific data
 - vertex colour components
 - vertex normal data
 - vertex application-specific data

If the optional data is not present, the value of the "start element number" is set to zero and the value of the "end element number" is set to -1.

- The data per facet flag
- The data per edge flag
- The data per vertex flag
- The colour type
- The number of components of colour value
- The number of fill area sets
- The number of points
- The length of application-specific data list per facet
- The length of application-specific data list per vertex
- The array of end indices of fill area indices for each fill area set
- The array of end indices of vertex indices for each fill area
- The vertex indices
- The facet colour indices
- The edge data

- The vertex colour indices
- The RA array contains:
- The coordinates of points
 - The facet colour components
 - The facet normal data
 - The facet application-specific data
 - The vertex colour components
 - The vertex normal data
 - The vertex application-specific data

$$IL = 27 + (IA(2) - IA(1) + 1) + (IA(4) - IA(3) + 1) + (IA(6) - IA(5) + 1) + IA(24) + IA(IA(24) + 27) + IA(IA(24) + 27) + IA(27 + IA(24) + IA(27 + IA(24)))$$

IA(1)= start element number in IA of facet colour indices

IA(2)= end element number in IA of facet colour indices

IA(3)= start element number in IA of edge data

IA(4)= end element number in IA of edge data

IA(5)= start element number in IA of vertex colour indices

IA(6)= end element number in IA of vertex colour indices

IA(7)= start element number in RA of facet colour components

IA(8)= end element number in RA of facet colour components

IA(9)= start element number in RA of facet normal data

IA(10)= end element number in RA of facet normal data

IA(11)= start element number in RA of facet application-specific data

IA(12)= end element number in RA of facet application-specific data

IA(13)= start element number in RA of vertex colour components

IA(14)= end element number in RA of vertex colour components

IA(15)= start element number in RA of vertex normal data

IA(16)= end element number in RA of vertex normal data

IA(17)= start element number in RA of vertex application-specific data

IA(18)= end element number in RA of vertex application-specific data

IA(19)= data per facet flag (PFNO, PFC, PFN, PFD, PFCN, PFCD, PFND, PFCND)

IA(20)= data per edge flag (PEN0, PEVF)

IA(21)= data per vertex flag

(PCD, PCDC, PCDN, PCDD, PCDCN, PCDCD, PCDND, PCDCND)

IA(22)= colour type

IA(23)= number of components of colour value

IA(24)= number of fill area sets in set of fill area sets 3 with data

IA(25)= number of points in set of fill area sets 3 with data

IA(26)= length of application-specific data list per facet

IA(27)= length of application-specific data list per vertex

IA=element 28 through IA(24)+27 contain the array of end indices of vertex indices

for each fill area set in set of fill area sets 3 with data

IA=element IA(24)+28 through IA(24)+27+IA(IA(24)+27)=NUM1 contain the array of

end indices for vertex indices in for each fill area in set of fill area sets 3 with data

IA=element NUM1+1 through IA(NUM1)+NUM1 contain the vertex indices

IA=element IA(1) through IA(2) contain the facet colour indices

IA=element IA(3) through IA(4) contain the edge data

IA=element IA(5) through IA(6) contain the vertex colour indices

RL= IA(25)*3+(IA(8)-IA(7)+1)+(IA(10)-IA(9)+1)+(IA(12)-IA(11)+1)+

(IA(14)-IA(13)+1)+(IA(16)-IA(15)+1)+(IA(18)-IA(17)+1)

RA=element 1 through IA(25)*3 contain the coordinates of points

example x1,x2,...,y1,y2,...,z1,z2...

RA=element IA(7) through IA(8) contain the facet colour components

example(colour type =PRGB) r1,g1,b1,r2,g2,b2,.....

RA=element IA(9) through IA(10) contain the facet normal data

example $x_1, x_2, \dots, y_1, y_2, \dots, z_1, z_2, \dots$

RA=element IA(11) through IA(12) contain the facet application-specific data

RA=element IA(13) through IA(14) contain the vertex colour components

RA=element IA(15) through IA(16) contain the vertex normal data

RA=element IA(17) through IA(18) contain the vertex application-specific data

SL= 0

LSTR= ()

STR= ()

Output parameters for STRUCTURE CONTENT DATA RECORD for

ELTYPE = PESFSD:

The IA array contains:

- The start element number and the end element number of following data
 - facet colour indices
 - edge data
 - vertex colour indices
 - facet colour components
 - facet normal data
 - facet application-specific data
 - vertex colour components
 - vertex normal data
 - vertex application-specific data

If the optional data is not present, the value of the "start element number" is set to zero and the value of the "end element number" is set to -1.

- The data per facet flag
- The data per edge flag
- The data per vertex flag
- The colour type
- The number of components of colour value
- The number of fill area sets
- The number of points
- The length of application-specific data list per facet
- The length of application-specific data list per vertex
- The array of end indices of vertex indices for each fill area set
- The array of end indices of vertex indices for each fill area
- The vertex indices
- The facet colour indices
- The edge data
- The vertex colour indices

The RA array contains:

- The coordinates of points
- The facet colour components
- The facet normal data
- The facet application-specific data
- The vertex colour components
- The vertex normal data
- The vertex application-specific data

$$IL = 27 + (IA(2) - IA(1) + 1) + (IA(4) - IA(3) + 1) + (IA(6) - IA(5) + 1) + IA(24) + IA(24) + 27 \\ + IA(27 + IA(24) + IA(27 + IA(24)))$$

IA(1)= start element number in IA of facet colour indices

IA(2)= end element number in IA of facet colour indices

IA(3)= start element number in IA of edge data

IA(4)= end element number in IA of edge data
 IA(5)= start element number in IA of vertex colour indices
 IA(6)= end element number in IA of vertex colour indices
 IA(7)= start element number in RA of facet colour components
 IA(8)= end element number in RA of facet colour components
 IA(9)= start element number in RA of facet normal data
 IA(10)= end element number in RA of facet normal data
 IA(11)= start element number in RA of facet application-specific data
 IA(12)= end element number in RA of facet application-specific data
 IA(13)= start element number in RA of vertex colour components
 IA(14)= end element number in RA of vertex colour components
 IA(15)= start element number in RA of vertex normal data
 IA(16)= end element number in RA of vertex normal data
 IA(17)= start element number in RA of vertex application-specific data
 IA(18)= end element number in RA of vertex application-specific data
 IA(19)= data per facet flag(PFNO,PFC,PFN,PFD,PFCN,PFCD,PFND,PFCDND)
 IA(20)= data per edge flag(PENO,PEVF)
 IA(21)= data per vertex flag
 (PCD,PCDC,PCDN,PCDD,PCDCN,PCDCD,PCDND,PCDCND)
 IA(22)= colour type
 IA(23)= number of components of colour value
 IA(24)= number of fill area sets in set of fill area sets with data
 IA(25)= number of points in set of fill area sets with data
 IA(26)= length of application-specific data list per facet
 IA(27)= length of application-specific data list per vertex
 IA=element 28 through IA(24)+27 contain the array of end indices of vertex indices
 for each fill area set in set of fill area sets with data
 IA=element IA(24)+28 through IA(24)+27+IA(IA(24)+27)=NUM1 contain the array of
 end indices for vertex indices in set of fill area sets with data
 IA=element NUM1+1 through IA(NUM1)+NUM1 contain the vertex indices
 IA=element IA(1) through IA(2) contain the facet colour indices
 IA=element IA(3) through IA(4) contain the edge data
 IA=element IA(5) through IA(6) contain the vertex colour indices
 RL= IA(25)*2+(IA(8)-IA(7)+1)+(IA(10)-IA(9)+1)+(IA(12)-IA(11)+1)+
 (IA(14)-IA(13)+1)+(IA(16)-IA(15)+1)+(IA(18)-IA(17)+1)
 RA=element 1 through IA(25)*2 contain the coordinates of points
 example x1,x2,...y1,y2,...
 RA=element IA(7) through IA(8) contain the facet colour components
 example(colour type =PRGB) r1,g1,b1,r2,g2,b2,.....
 RA=element IA(9) through IA(10) contain the facet normal data
 example x1,x2,...y1,y2,...z1,z2...
 RA=element IA(11) through IA(12) contain the facet application-specific data
 RA=element IA(13) through IA(14) contain the vertex colour components
 RA=element IA(15) through IA(16) contain the vertex normal data
 RA=element IA(17) through IA(18) contain the vertex application-specific data
 SL= 0
 LSTR= ()
 STR= ()

Output parameters for STRUCTURE CONTENT DATA RECORD for
ELTYPE = PETS3D:

The IA array contains:

- The start element number and the end element number of following data
 facet colour indices

edge data
 vertex colour indices
 facet colour components
 facet normal data
 facet application-specific data
 vertex colour components
 vertex normal data
 vertex application-specific data

If the optional data is not present, the value of the "start element number" is set to zero and the value of the "end element number" is set to -1.

- The data per facet flag
- The data per edge flag
- The data per vertex flag
- The colour type
- The number of components of colour value
- The number of triangles
- The number of points
- The length of application-specific data list per facet
- The length of application-specific data list per vertex
- The vertex indices
- The facet colour indices
- The edge data
- The vertex colour indices

The RA array contains:

- The coordinates of points
- The facet colour components
- The facet normal data
- The facet application-specific data
- The vertex colour components
- The vertex normal data
- The vertex application-specific data

$$IL=27+3*IA(24)+(IA(2)-IA(1)+1)+(IA(4)-IA(3)-1)+(IA(6)-IA(5)+1)$$

IA(1)= start element number in IA of facet colour indices

IA(2)= end element number in IA of facet colour indices

IA(3)= start element number in IA of edge data

IA(4)= end element number in IA of edge data

IA(5)= start element number in IA of vertex colour indices

IA(6)= end element number in IA of vertex colour indices

IA(7)= start element number in RA of facet colour components

IA(8)= end element number in RA of facet colour components

IA(9)= start element number in RA of facet normal data

IA(10)= end element number in RA of facet normal data

IA(11)= start element number in RA of facet application-specific data

IA(12)= end element number in RA of facet application-specific data

IA(13)= start element number in RA of vertex colour components

IA(14)= end element number in RA of vertex colour components

IA(15)= start element number in RA of vertex normal data

IA(16)= end element number in RA of vertex normal data

IA(17)= start element number in RA of vertex application-specific data

IA(18)= end element number in RA of vertex application-specific data

IA(19)= data per facet flag(PFNO,PFC,PFN,PFD,PFCN,PFCD,PFND,PFCND)

IA(20)= data per edge flag(PENO,PEVF)

IA(21)= data per vertex flag

(PCD,PCDC,PCDN,PCDD,PCDCN,PCDCD,PCDND,PCDCND)

IA(22)= colour type

IA(23)= number of components of colour value

IA(24)= number of triangles

IA(25)= number of points in triangle set 3 with data

IA(26)= length of application-specific data list per facet

IA(27)= length of application-specific data list per vertex

IA=element 28 through $3*IA(24)+27$ contain vertex indices

IA=element IA(1) through IA(2) contain the facet colour indices

IA=element IA(3) through IA(4) contain the edge data

IA=element IA(5) through IA(6) contain the vertex colour indices

RL= $IA(25)*3+(IA(8)-IA(7)+1)+(IA(10)-IA(9)+1)+(IA(12)-IA(11)+1)+$
 $(IA(14)-IA(13)+1)+(IA(16)-IA(15)+1)+(IA(18)-IA(17)+1)$

RA=element 1 through $IA(25)*3$ contain the coordinates of points

example $x_1, x_2, \dots, y_1, y_2, \dots, z_1, z_2, \dots$

RA=element IA(7) through IA(8) contain the facet colour components

example(colour type =PRGB) $r_1, g_1, b_1, r_2, g_2, b_2, \dots$

RA=element IA(9) through IA(10) contain the facet normal data

example $x_1, x_2, \dots, y_1, y_2, \dots, z_1, z_2, \dots$

RA=element IA(11) through IA(12) contain the facet application-specific data

RA=element IA(13) through IA(14) contain the vertex colour components

RA=element IA(15) through IA(16) contain the vertex normal data

RA=element IA(17) through IA(18) contain the vertex application-specific data

SL= 0

LSTR= ()

STR= ()

Output parameters for STRUCTURE CONTENT DATA RECORD for

ELTYPE = PETSD:

The IA array contains:

- The start element number and the end element number of following data

facet colour indices

edge data

vertex colour indices

facet colour components

facet normal data

facet application-specific data

vertex colour components

vertex normal data

vertex application-specific data

If the optional data is not present, the value of the "start element number" is set to zero and the value of the "end element number" is set to -1.

- The data per facet flag

- The data per edge flag

- The data per vertex flag

- The colour type

- The number of components of colour value

- The number of triangles

- The number of points

- The length of application-specific data list per facet

- The length of application-specific data list per vertex

- The vertex indices

- The facet colour indices

- The edge data

- The vertex colour indices
- The RA array contains:
- The coordinates of points
 - The facet colour components
 - The facet normal data
 - The facet application-specific data
 - The vertex colour components
 - The vertex normal data
 - The vertex application-specific data

$$II = 27 + 3 * IA(24) + (IA(2) - IA(1) + 1) + (IA(4) - IA(3) + 1) + (IA(6) - IA(5) + 1)$$

IA(1)= start element number in IA of facet colour indices

IA(2)= end element number in IA of facet colour indices

IA(3)= start element number in IA of edge data

IA(4)= end element number in IA of edge data

IA(5)= start element number in IA of vertex colour indices

IA(6)= end element number in IA of vertex colour indices

IA(7)= start element number in RA of facet colour components

IA(8)= end element number in RA of facet colour components

IA(9)= start element number in RA of facet normal data

IA(10)= end element number in RA of facet normal data

IA(11)= start element number in RA of facet application-specific data

IA(12)= end element number in RA of facet application-specific data

IA(13)= start element number in RA of vertex colour components

IA(14)= end element number in RA of vertex colour components

IA(15)= start element number in RA of vertex normal data

IA(16)= end element number in RA of vertex normal data

IA(17)= start element number in RA of vertex application-specific data

IA(18)= end element number in RA of vertex application-specific data

IA(19)= data per facet flag(PFNO,PFC,PFN,PFDP,PFCN,PFCD,PFND,PFCND)

IA(20)= data per edge flag(PENO,PEVE)

IA(21)= data per vertex flag

(PCD,PCDC,PCDN,PCDD,PCDCN,PCDCD,PCDND,PCDCND)

IA(22)= colour type

IA(23)= number of components of colour value

IA(24)= number of triangles

IA(25)= number of points in triangle set 3 with data

IA(26)= length of application-specific data list per facet

IA(27)= length of application-specific data list per vertex

IA=element 28 through $3 * IA(24) + 27$ contain vertex indices

IA=element IA(1) through IA(2) contain the facet colour indices

IA=element IA(3) through IA(4) contain the edge data

IA=element IA(5) through IA(6) contain the vertex colour indices

$RL = IA(25) * 2 + (IA(8) - IA(7) + 1) + (IA(10) - IA(9) + 1) + (IA(12) - IA(11) + 1) +$
 $(IA(14) - IA(13) + 1) + (IA(16) - IA(15) + 1) + (IA(18) - IA(17) + 1)$

RA=element 1 through $IA(25) * 2$ contain the coordinates of points

example $x_1, x_2, \dots, y_1, y_2, \dots$

RA=element IA(7) through IA(8) contain the facet colour components

example(colour type =PRGB) $r_1, g_1, b_1, r_2, g_2, b_2, \dots$

RA=element IA(9) through IA(10) contain the facet normal data

example $x_1, x_2, \dots, y_1, y_2, \dots, z_1, z_2, \dots$

RA=element IA(11) through IA(12) contain the facet application-specific data

RA=element IA(13) through IA(14) contain the vertex colour components

RA=element IA(15) through IA(16) contain the vertex normal data

RA=element IA(17) through IA(18) contain the vertex application-specific data

SL= 0

LSTR= ()

STR= ()

Output parameters for STRUCTURE CONTENT DATA RECORD for

ELTYPE = PETST3:

The IA array contains:

- The start element number and the end element number of following data
 - facet colour indices
 - edge data
 - vertex colour indices
 - facet colour components
 - facet normal data
 - facet application-specific data
 - vertex colour components
 - vertex normal data
 - vertex application-specific data

If the optional data is not present, the value of the "start element number" is set to zero and the value of the "end element number" is set to -1.

- The data per facet flag
- The data per edge flag
- The data per vertex flag
- The colour type
- The number of components of colour value
- The number of points
- The length of application-specific data list per facet
- The length of application-specific data list per vertex
- The facet colour indices
- The edge data
- The vertex colour indices

The RA array contains:

- The coordinates of points
- The facet colour components
- The facet normal data
- The facet application-specific data
- The vertex colour components
- The vertex normal data
- The vertex application-specific data

$IL=26+(IA(2)-IA(1)+1)+(IA(4)-IA(3)+1)+(IA(6)-IA(5)+1)$

IA(1)= start element number in IA of facet colour indices

IA(2)= end element number in IA of facet colour indices

IA(3)= start element number in IA of edge data

IA(4)= end element number in IA of edge data

IA(5)= start element number in IA of vertex colour indices

IA(6)= end element number in IA of vertex colour indices

IA(7)= start element number in RA of facet colour components

IA(8)= end element number in RA of facet colour components

IA(9)= start element number in RA of facet normal data

IA(10)= end element number in RA of facet normal data

IA(11)= start element number in RA of facet application-specific data

IA(12)= end element number in RA of facet application-specific data

IA(13)= start element number in RA of vertex colour components

IA(14)= end element number in RA of vertex colour components
 IA(15)= start element number in RA of vertex normal data
 IA(16)= end element number in RA of vertex normal data
 IA(17)= start element number in RA of vertex application-specific data
 IA(18)= end element number in RA of vertex application-specific data
 IA(19)= data per facet flag(PFNO,PFC,PFN,PFD,PFCN,PFCD,PFND,PFCND)
 IA(20)= data per edge flag(PENO,PEVF)
 IA(21)= data per vertex flag
 (PCD,PCDC,PCDN,PCDD,PCDCN,PCDCD,PCDND,PCDCND)
 IA(22)= colour type
 IA(23)= number of components of colour value
 IA(24)= number of points in triangle strip 3 with data
 IA(25)= length of application-specific data list per facet
 IA(26)= length of application-specific data list per vertex
 IA=element IA(1) through IA(2) contain the facet colour indices
 IA=element IA(3) through IA(4) contain the edge data
 IA=element IA(5) through IA(6) contain the vertex colour indices
 $RL = IA(24)*3 + (IA(8)-IA(7)+1) + (IA(10)-IA(9)+1) + (IA(12)-IA(11)+1) +$
 $(IA(14)-IA(13)+1) + (IA(16)-IA(15)+1) + (IA(18)-IA(17)+1)$
 RA=element 1 through IA(24)*3 contain the coordinates of points
 example x1,x2,...,y1,y2,...,z1,z2...
 RA=element IA(7) through IA(8) contain the facet colour components
 example(colour type =PRGB) r1,g1,b1,r2,g2,b2,.....
 RA=element IA(9) through IA(10) contain the facet normal data
 example x1,x2,...,y1,y2,...,z1,z2...
 RA=element IA(11) through IA(12) contain the facet application-specific data
 RA=element IA(13) through IA(14) contain the vertex colour components
 RA=element IA(15) through IA(16) contain the vertex normal data
 RA=element IA(17) through IA(18) contain the vertex application-specific data
 SL= 0
 LSTR= ()
 STR= ()

Output parameters for STRUCTURE CONTENT DATA RECORD for
ELTYPE = PETSTD:

The IA array contains:

- The start element number and the end element number of following data
 - facet colour indices
 - edge data
 - vertex colour indices
 - facet colour components
 - facet normal data
 - facet application-specific data
 - vertex colour components
 - vertex normal data
 - vertex application-specific data

If the optional data is not present, the value of the "start element number" is set to zero and the value of the "end element number" is set to -1.

- The data per facet flag
- The data per edge flag
- The data per vertex flag
- The colour type
- The number of components of colour value
- The number of points

- The length of application-specific data list per facet
- The length of application-specific data list per vertex
- The facet colour indices
- The edge data
- The vertex colour indices

The RA array contains:

- The coordinates of points
- The facet colour components
- The facet normal data
- The facet application-specific data
- The vertex colour components
- The vertex normal data
- The vertex application-specific data

$$IL = 26 + (IA(2) - IA(1) + 1) + (IA(4) - IA(3) + 1) + (IA(6) - IA(5) + 1)$$

IA(1)= start element number in IA of facet colour indices

IA(2)= end element number in IA of facet colour indices

IA(3)= start element number in IA of edge data

IA(4)= end element number in IA of edge data

IA(5)= start element number in IA of vertex colour indices

IA(6)= end element number in IA of vertex colour indices

IA(7)= start element number in RA of facet colour components

IA(8)= end element number in RA of facet colour components

IA(9)= start element number in RA of facet normal data

IA(10)= end element number in RA of facet normal data

IA(11)= start element number in RA of facet application-specific data

IA(12)= end element number in RA of facet application-specific data

IA(13)= start element number in RA of vertex colour components

IA(14)= end element number in RA of vertex colour components

IA(15)= start element number in RA of vertex normal data

IA(16)= end element number in RA of vertex normal data

IA(17)= start element number in RA of vertex application-specific data

IA(18)= end element number in RA of vertex application-specific data

IA(19)= data per facet flag(PFNO,PFC,PFN,PFD,PFCN,PFCD,PFND,PFCND)

IA(20)= data per edge flag(PENO,PEVF)

IA(21)= data per vertex flag

(PCD,PCDC,PCDN,PCDD,PCDCN,PCDCD,PCDND,PCDCND)

IA(22)= colour type

IA(23)= number of components of colour value

IA(24)= number of points in triangle strip 3 with data

IA(25)= length of application-specific data list per facet

IA(26)= length of application-specific data list per vertex

IA=element IA(1) through IA(2) contain the facet colour indices

IA=element IA(3) through IA(4) contain the edge data

IA=element IA(5) through IA(6) contain the vertex colour indices

$$RL = IA(24) * 2 + (IA(8) - IA(7) + 1) + (IA(10) - IA(9) + 1) + (IA(12) - IA(11) + 1) + (IA(14) - IA(13) + 1) + (IA(16) - IA(15) + 1) + (IA(18) - IA(17) + 1)$$

RA=element 1 through IA(24)*2 contain the coordinates of points

example x1,x2,...y1,y2,...

RA=element IA(7) through IA(8) contain the facet colour components

example(colour type =PRGB) r1,g1,b1,r2,g2,b2,.....

RA=element IA(9) through IA(10) contain the facet normal data

example x1,x2,...y1,y2,...z1,z2...

RA=element IA(11) through IA(12) contain the facet application-specific data

RA=element IA(13) through IA(14) contain the vertex colour components
 RA=element IA(15) through IA(16) contain the vertex normal data
 RA=element IA(17) through IA(18) contain the vertex application-specific data
 SL= 0
 LSTR= ()
 STR= ()

Output parameters for STRUCTURE CONTENT DATA RECORD for
ELTYPE = PEQM3D:

The IA array contains:

- The start element number and the end element number of following data
 - facet colour indices
 - edge data
 - vertex colour indices
 - facet colour components
 - facet normal data
 - facet application-specific data
 - vertex colour components
 - vertex normal data
 - vertex application-specific data

If the optional data is not present, the value of the "start element number" is set to zero and the value of the "end element number" is set to -1.

- The data per facet flag
- The data per edge flag
- The data per vertex flag
- The colour type
- The number of components of colour value
- The columns number of point dimension
- The rows number of point dimension
- The length of application-specific data list per facet
- The length of application-specific data list per vertex
- The facet colour indices
- The edge data
- The vertex colour indices

The RA array contains:

- The coordinates of points
- The facet colour components
- The facet normal data
- The facet application-specific data
- The vertex colour components
- The vertex normal data
- The vertex application-specific data

$IL = 27 + (IA(2) - IA(1) + 1) + (IA(4) - IA(3) + 1) + (IA(6) - IA(5) + 1)$

IA(1)= start element number in IA of facet colour indices

IA(2)= end element number in IA of facet colour indices

IA(3)= start element number in IA of edge data

IA(4)= end element number in IA of edge data

IA(5)= start element number in IA of vertex colour indices

IA(6)= end element number in IA of vertex colour indices

IA(7)= start element number in RA of facet colour components

IA(8)= end element number in RA of facet colour components

IA(9)= start element number in RA of facet normal data

IA(10)= end element number in RA of facet normal data

IA(11)= start element number in RA of facet application-specific data
 IA(12)= end element number in RA of facet application-specific data
 IA(13)= start element number in RA of vertex colour components
 IA(14)= end element number in RA of vertex colour components
 IA(15)= start element number in RA of vertex normal data
 IA(16)= end element number in RA of vertex normal data
 IA(17)= start element number in RA of vertex application-specific data
 IA(18)= end element number in RA of vertex application-specific data
 IA(19)= data per facet flag(PFNO,PFC,PFN,PFN,PCFN,PCFCD,PFND,PCFND)
 IA(20)= data per edge flag(PENO,PEVF)
 IA(21)= data per vertex flag
 (PCD,PCDC,PCDN,PCDD,PCDCN,PCDCD,PCDND,PCDCND)
 IA(22)= colour type
 IA(23)= number of components of colour value
 IA(24)= columns number of points dimension
 IA(25)= rows number of points dimension
 IA(26)= length of application-specific data list per facet
 IA(27)= length of application-specific data list per vertex
 IA=element IA(1) through IA(2) contain the facet colour indices
 IA=element IA(3) through IA(4) contain the edge data
 IA=element IA(5) through IA(6) contain the vertex colour indices
 $RL = IA(24) * IA(25) * 3 + (IA(8) - IA(7) + 1) + (IA(10) - IA(9) + 1) + (IA(12) - IA(11) + 1) +$
 $(IA(14) - IA(13) + 1) + (IA(16) - IA(15) + 1) + (IA(18) - IA(17) + 1)$
 RA=element 1 through $IA(24) * IA(25) * 3$ contain the coordinates of points
 example $x_1, x_2, \dots, y_1, y_2, \dots, z_1, z_2, \dots$
 RA=element IA(7) through IA(8) contain the facet colour components
 example(colour type =PRGB) $r_1, g_1, b_1, r_2, g_2, b_2, \dots$
 RA=element IA(9) through IA(10) contain the facet normal data
 example $x_1, x_2, \dots, y_1, y_2, \dots, z_1, z_2, \dots$
 RA=element IA(11) through IA(12) contain the facet application-specific data
 RA=element IA(13) through IA(14) contain the vertex colour components
 RA=element IA(15) through IA(16) contain the vertex normal data
 RA=element IA(17) through IA(18) contain the vertex application-specific data
 SL= 0
 LSTR= ()
 STR= ()

Output parameters for STRUCTURE CONTENT DATA RECORD for
ELTYPE = PEQMD:

The IA array contains:

- The start element number and the end element number of following data
 - facet colour indices
 - edge data
 - vertex colour indices
 - facet colour components
 - facet normal data
 - facet application-specific data
 - vertex colour components
 - vertex normal data
 - vertex application-specific data

If the optional data is not present, the value of the "start element number" is set to zero and the value of the "end element number" is set to -1.

- The data per facet flag
- The data per edge flag

- The data per vertex flag
- The colour type
- The number of components of colour value
- The columns number of point dimension
- The rows number of point dimension
- The length of application-specific data list per facet
- The length of application-specific data list per vertex
- The facet colour indices
- The edge data
- The vertex colour indices

The RA array contains:

- The coordinates of points
- The facet colour components
- The facet normal data
- The facet application-specific data
- The vertex colour components
- The vertex normal data
- The vertex application-specific data

$IL = 27 + (IA(2) - IA(1) + 1) + (IA(4) - IA(3) + 1) + (IA(6) - IA(5) + 1)$

IA(1)= start element number in IA of facet colour indices

IA(2)= end element number in IA of facet colour indices

IA(3)= start element number in IA of edge data

IA(4)= end element number in IA of edge data

IA(5)= start element number in IA of vertex colour indices

IA(6)= end element number in IA of vertex colour indices

IA(7)= start element number in RA of facet colour components

IA(8)= end element number in RA of facet colour components

IA(9)= start element number in RA of facet normal data

IA(10)= end element number in RA of facet normal data

IA(11)= start element number in RA of facet application-specific data

IA(12)= end element number in RA of facet application-specific data

IA(13)= start element number in RA of vertex colour components

IA(14)= end element number in RA of vertex colour components

IA(15)= start element number in RA of vertex normal data

IA(16)= end element number in RA of vertex normal data

IA(17)= start element number in RA of vertex application-specific data

IA(18)= end element number in RA of vertex application-specific data

IA(19)= data per facet flag (PFNO, PFC, PFN, PFD, PFCN, PFCD, PFND, PFCND)

IA(20)= data per edge flag (PEN, PEVF)

IA(21)= data per vertex flag

(PCD, PCDC, PCDN, PCDD, PCDCN, PCDCD, PCND, PCDCND)

IA(22)= colour type

IA(23)= number of components of colour value

IA(24)= columns number of points dimension

IA(25)= rows number of points dimension

IA(26)= length of application-specific data list per facet

IA(27)= length of application-specific data list per vertex

IA=element IA(1) through IA(2) contain the facet colour indices

IA=element IA(3) through IA(4) contain the edge data

IA=element IA(5) through IA(6) contain the vertex colour indices

$RL = IA(24) * IA(25) * 2 + (IA(8) - IA(7) + 1) + (IA(10) - IA(9) + 1) + (IA(12) - IA(11) + 1) +$

$(IA(14) - IA(13) + 1) + (IA(16) - IA(15) + 1) + (IA(18) - IA(17) + 1)$

RA=element 1 through IA(23)*IA(24)*2 contain the coordinates of points

example $x_1, x_2, \dots, y_1, y_2, \dots$

RA=element IA(7) through IA(8) contain the facet colour components

example(colour type =PRGB) $r_1, g_1, b_1, r_2, g_2, b_2, \dots$

RA=element IA(9) through IA(10) contain the facet normal data

example $x_1, x_2, \dots, y_1, y_2, \dots, z_1, z_2, \dots$

RA=element IA(11) through IA(12) contain the facet application-specific data

RA=element IA(13) through IA(14) contain the vertex colour components

RA=element IA(15) through IA(16) contain the vertex normal data

RA=element IA(17) through IA(18) contain the vertex application-specific data

SL= 0

LSTR= ()

STR= ()

Output parameters for STRUCTURE CONTENT DATA RECORD for
ELTYPE = PEBC3:

The IA array contains:

- The spline order
- The number of knots
- The rationality
- The number of control points

The RA array contains:

- The knots
- The parameter range limits
- The coordinates of points

If "rationality" is PNRAT, coordinates of points are PXA, PYA and PZA.

If "rationality" is PRAT, coordinates of points are PXA, PYA, PZA and PWA.

IL= 4

IA(1)= spline order

IA(2)= number of knots

IA(3)= rationality(PRAT,PNRAT)

IA(4)= number of control points

RL= IA(2)+2+*

RA=element 1 through IA(2) contain the knots

RA=element IA(2)+1 through IA(2)+2 contain the parameter range limits

first minimum parameter, second maximum parameter.

if rationality=PRAT

RA=element IA(2)+4 through IA(2)+2+IA(4)*4 contain the coordinates of points

example $x_1, x_2, \dots, y_1, y_2, \dots, z_1, z_2, \dots, w_1, w_2, \dots$

if rationality=PNRAT

RA=element IA(2)+3 through IA(2)+2+IA(4)*3 contain the coordinates of points

example $x_1, x_2, \dots, y_1, y_2, \dots, z_1, z_2, \dots$

SL= 0

LSTR= ()

STR= ()

Output parameters for STRUCTURE CONTENT DATA RECORD for
ELTYPE = PEBC3C:

The IA array contains:

- The spline order
- The number of knots
- The rationality
- The number of control points

The RA array contains:

- The knots
 - The parameter range limits
 - The coordinates of points
 - If "rationality" is PNRAT, coordinates of points are PXA, PYA and PZA.
 - If "rationality" is PRAT, coordinates of points are PXA, PYA, PZA and PWA.
- The STR array contains:
- The colour spline curve data record.

IL= 4

IA(1)= spline order

IA(2)= number of knots

IA(3)= rationality(PRAT,PNRAT)

IA(4)= number of control points

RL= IA(2)+2+*

RA=element 1 through IA(2) contain the knots

RA=element IA(2)+1 through IA(2)+2 contain the parameter range limits

if rationality=PRAT

RA=element IA(2)+4 through IA(2)+2+IA(4)*4 contain the coordinates of points

example x1,x2,...y1,y2,...z1,z2,...w1,w2,...

if rationality=PNRAT

RA=element IA(2)+3 through IA(2)+2+IA(4)*3 contain the coordinates of points

example x1,x2,...y1,y2,...z1,z2,...

SL= number of array elements used in data record

For i= 1 to SL

LSTR(i)= 80

STR= colour spline curve data record

Output parameters for STRUCTURE CONTENT DATA RECORD for
ELTYPE = PEBS3:

The IA array contains:

- The u spline order
- The v spline order
- The u number of knots
- The v number of knots
- The rationality
- The u number of control points
- The v number of control points

The RA array contains:

- The u knots
- The v knots
- The coordinates of points

If "rationality" is PNRAT, coordinates of points are PXA, PYA and PZA.

If "rationality" is PRAT, coordinates of points are PXA, PYA, PZA and PWA.

The STR array contains:

- The trimming curve data record

IL=7

IA(1)= u spline order

IA(2)= v spline order

IA(3)= number of knots in u

IA(4)= number of knots in v

IA(5)= rationality(PRAT,PNRAT)

IA(6)= u number of control points dimension

IA(7)= v number of control points dimension

$RL = IA(3) + IA(4) + *$
 RA=element 1 through IA(3) contain the u knots
 RA=element IA(3)+1 through IA(4)+IA(3) contain the v knots
 if rationality=PRAT
 RA=element IA(4)+IA(3)+1 through $4*IA(6)*IA(7)+IA(4)+IA(3)$ contain
 the coordinates of points
 example $x_1, x_2, \dots, y_1, y_2, \dots, z_1, z_2, \dots, w_1, w_2, \dots$
 if rationality=PNRAT
 RA=element IA(4)+IA(3)+1 through $3*IA(6)*IA(7)+IA(4)+IA(3)$ contain
 the coordinates of points
 example $x_1, x_2, \dots, y_1, y_2, \dots, z_1, z_2, \dots$
 SL= number of array elements used in trimming curve data record
 For i=1 to SL
 LSTR(i)= 80
 STR= trimming curve data record

Output parameters for STRUCTURE CONTENT DATA RECORD for
ELTYPE = PEBS3D:

The IA array contains:

- The u spline order
- The v spline order
- The u number of knots
- The v number of knots
- The rationality
- The u number of control points
- The v number of control points

The RA array contains:

- The u knots
 - The v knots
 - The coordinates of points
- If "rationality" is PNRAT, coordinates of points are PXA, PYA and PZA.
 If "rationality" is PRAT, coordinates of points are PXA, PYA, PZA and PWA.

The STR array contains:

- The trimming curve data record
- The colour spline surface data record
- The data spline surface data record

IL=7

IA(1)= spline order u

IA(2)= spline order v

IA(3)= number of knots in u

IA(4)= number of knots in v

IA(5)= rationality(PRAT,PNRAT)

IA(6)= u number of control points dimension

IA(7)= v number of control points dimension

$RL = IA(3) + IA(4) + *$

RA=element 1 through IA(3) contain the u knots

RA=element IA(3)+1 through IA(4)+IA(3) contain the v knots

if rationality=PRAT

RA=element IA(4)+IA(3)+1 through $4*IA(6)*IA(7)+IA(4)+IA(3)$ contain
the coordinates of points

example $x_1, x_2, \dots, y_1, y_2, \dots, z_1, z_2, \dots, w_1, w_2, \dots$

if rationality=PNRAT

RA=element IA(4)+IA(3)+1 through $3*IA(6)*IA(7)+IA(4)+IA(3)$ contain

the coordinates of points

example $x_1, x_2, \dots, y_1, y_2, \dots, z_1, z_2, \dots$

SI = number of array elements used in trimming curve data record +
number of array elements used in colour spline surface data record
number of array elements used in data spline surface data record

For $i=1$ to SL

LSTR(i) = 80

STR = trimming curve data record, colour spline surface data record and
data spline surface data record

Output parameters for STRUCTURE CONTENT DATA RECORD for
ELTYPE = PEDMI:

The IA array contains:

- The data mapping index

The other arrays are empty.

IL = 1

IA(1) = data mapping index

RL = 0

RA = ()

SL = 0

LSTR = ()

STR = ()

Output parameters for STRUCTURE CONTENT DATA RECORD for
ELTYPE = PERFI:

The IA array contains:

- The reflectance index

The other arrays are empty.

IL = 1

IA(1) = reflectance index

RL = 0

RA = ()

SL = 0

LSTR = ()

STR = ()

Output parameters for STRUCTURE CONTENT DATA RECORD for
ELTYPE = PEBII:

The IA array contains:

- The back interior index

The other arrays are empty.

IL = 1

IA(1) = back interior index

RL = 0

RA = ()

SL = 0

LSTR = ()

STR = ()

Output parameters for STRUCTURE CONTENT DATA RECORD for
ELTYPE = PEBDMI:

The IA array contains:

- The back data mapping index

The other arrays are empty.

IL= 1

IA(1)= back data mapping index

RL= 0

RA= ()

SL= 0

LSTR= ()

STR= ()

Output parameters for STRUCTURE CONTENT DATA RECORD for
ELTYPE = PEBRFI:

The IA array contains:

- The back reflectance index

The other arrays are empty.

IL= 1

IA(1)= back reflectance index

RL= 0

RA= ()

SL= 0

LSTR= ()

STR= ()

Output parameters for STRUCTURE CONTENT DATA RECORD for
ELTYPE = PEPRSI:

The IA array contains:

- The parametric surface index

The other arrays are empty.

IL= 1

IA(1)= parametric surface index

RL= 0

RA= ()

SL= 0

LSTR= ()

STR= ()

Output parameters for STRUCTURE CONTENT DATA RECORD for
ELTYPE = PEPLC:

The IA array contains:

- The colour type(CT)
- The number of components of colour value(NCC)
- The actual data of colour index, if CT is indirect.

The RA array contains:

- The actual data of colour component values as required by CT.

Common element:

IL= 2+*

IA(1)= colour type = CT

IA(2)= number of components of colour value = NCC

RL= *

SL= 0

LSTR= ()

STR= ()

Individual element:

CASE colour type=PINDIR:

IA(3)= colour index

CASE colour type=PRGB or PCIE or PHSV or PHLS:

RA= element 1 through NCC contain the colour components

Output parameters for STRUCTURE CONTENT DATA RECORD for
ELTYPE = PEPLSM:

The IA array contains:

- The polyline shading method

The other arrays are empty.

IL= 1

IA(1)= polyline shading method

RL= 0

RA= ()

SL= 0

LSTR= ()

STR= ()

Output parameters for STRUCTURE CONTENT DATA RECORD for
ELTYPE = PEPMC:

The IA array contains:

- The colour type(CT)

- The number of components of colour value(NCC)

- The actual data of colour index, if CT is indirect.

The RA array contains:

- The actual data of colour component values as required by CT.

Common element:

IL= 2+*

IA(1)= colour type = CT

IA(2)= number of components of colour value

RL= *

SL= 0

LSTR= ()

STR= ()

Individual element:

CASE colour type=PINDIR:

IA(3)= colour index

CASE colour type=PRGB or PCIE or PHSV or PHLS:

RA= element 1 through NCC contain the colour components

Output parameters for STRUCTURE CONTENT DATA RECORD for
ELTYPE = PETXC:

The IA array contains:

- The colour type(CT)

- The number of components of colour value(NCC)

- The actual data of colour index, if CT is indirect.

The RA array contains:

- The actual data of colour component values as required by CT.

Common element:

IL= 2+*

IA(1)= colour type = CT

IA(2)= number of components of colour value

RL= *

SL= 0

LSTR= ()

STR= ()

Individual element:

CASE colour type=PINDIR:

IA(3)= colour index

CASE colour type=PRGB or PCIE or PHSV or PHLS:

RA= element 1 through NCC contain the colour components

Output parameters for STRUCTURE CONTENT DATA RECORD for
ELTYPE = PEFDM:

The IA array contains:

- The distinguishing mode

The other arrays are empty.

IL= 1

IA(1)= distinguishing mode(POFF,PON)

RL= 0

RA= ()

SL= 0

LSTR= ()

STR= ()

Output parameters for STRUCTURE CONTENT DATA RECORD for
ELTYPE = PEFCM:

The IA array contains:

- The culling mode

The other arrays are empty.

IL= 1

IA(1)= culling mode(PNOFC,PBKFC,PFTFC)

RL= 0

RA= ()

SL= 0

LSTR= ()

STR= ()

Output parameters for STRUCTURE CONTENT DATA RECORD for
ELTYPE = PEIC:

The IA array contains:

- The colour type(CT)

- The number of components of colour value(NCC)

- The actual data of colour index, if CT is indirect.

The RA array contains:

- The actual data of colour component values as required by CT.

Common element:

IL= 2+*

IA(1)= colour type = CT

IA(2)= number of components of colour value

RL= *

SL= 0

LSTR= ()

STR= ()

Individual element:

CASE colour type=PINDIR:

IA(3)= colour index

CASE colour type=PRGB or PCIE or PHSV or PHLS:

RA= element 1 through NCC contain the colour components

Output parameters for STRUCTURE CONTENT DATA RECORD for

ELTYPE = PEISM:

The IA array contains:

- The interior shading mode

The other arrays are empty.

IL= 1

IA(1)= interior shading method

RL= 0

RA= ()

SL= 0

LSTR= ()

STR= ()

Output parameters for STRUCTURE CONTENT DATA RECORD for

ELTYPE = PEDMM:

The IA array contains:

- The data mapping method

The STR array contains:

- The data mapping data record

IL= 1

IA(1)= data mapping method

RL= 0

RA= ()

SL= length of data record array

FOR i=1 TO length of data record array

LSTR(i)= 80

STR= data mapping data record³³

Output parameters for STRUCTURE CONTENT DATA RECORD for

ELTYPE = PERFP:

The IA array contains:

- The properties type

The STR array contains:

- The reflectance properties data record

Common element:

IL= 1

IA(1)= properties type

³³See SET DATA MAPPING METHOD for a description of the data mapping method data data record.

RL= 0
RA()
SL= length of reflectance properties data record array
For i=1 to SL
LSTR(i)= 80
STR= reflectance properties data record

Output parameters for STRUCTURE CONTENT DATA RECORD for
ELTYPE = PERFM:

The IA array contains:

- The reflectance model

The other arrays are empty.

IL= 1
IA(1)= reflectance model
RL= 0
RA= ()
SL= 0
LSTR= ()
STR= ()

Output parameters for STRUCTURE CONTENT DATA RECORD for
ELTYPE = PEBIS:

The IA array contains:

- The interior style

The other arrays are empty.

IL= 1
IA(1)= interior style(PHOLLO,PSOLID,PPATTR,PPATCH,PISEMP)
RL= 0
RA= ()
SL= 0
LSTR= ()
STR= ()

Output parameters for STRUCTURE CONTENT DATA RECORD for
ELTYPE = PEBISI:

The IA array contains:

- The interior style index

The other arrays are empty.

IL= 1
IA(1)= interior style index
RL= 0
RA= ()
SL= 0
LSTR= ()
STR= ()

Output parameters for STRUCTURE CONTENT DATA RECORD for
ELTYPE = PEBIC:

The IA array contains:

- The colour type(CT)

- The number of components of colour value(NCC)

- The actual data of colour index, if CT is indirect.
- The RA array contains:
- The actual data of colour component values as required by CT.

Common element:

IL= 2+*

IA(1)= colour type = CT

IA(2)= number of components of colour value

RL= *

SL= 0

LSTR= ()

STR= ()

Individual element:

CASE colour type=PINDIR:

IA(3)= colour index

CASE colour type=PRGB or PCIE or PHSV or PHLS:

RA= element 1 through NCC contain the colour components

Output parameters for STRUCTURE CONTENT DATA RECORD for
ELTYPE = PEBISM:

The IA array contains:

- The interior shading method

The other arrays are empty.

IL= 1

IA(1)= interior shading method

RL= 0

RA= ()

SL= 0

LSTR= ()

STR= ()

Output parameters for STRUCTURE CONTENT DATA RECORD for
ELTYPE = PEBDMM:

The IA array contains:

- The data mapping method

The STR array contains:

- The data mapping data record

IL= 1

IA(1)= data mapping method

RL= 0

RA= ()

SL= length of data record array

FOR i=1 TO length of data record array

LSTR(i)= 80

STR= data mapping data record³⁴

Output parameters for STRUCTURE CONTENT DATA RECORD for
ELTYPE = PEBRFP:

The IA array contains:

³⁴See SET DATA MAPPING METHOD for a description of the data mapping method data data record.

- The properties type
- The STR array contains:
- The reflectance properties data record

IL= 1
 IA(1)= properties type
 RL= 0
 RA()
 SL= length of reflectance properties data record array
 For i=1 to SL
 LSTR(i)= 80
 STR= reflectance properties data record

Output parameters for STRUCTURE CONTENT DATA RECORD for
 ELTYPE = PEBRFM:
 The IA array contains:

- The reflectance model

The other arrays are empty.

IL= 1
 IA(1)= reflectance model
 RL= 0
 RA= ()
 SL= 0
 LSTR= ()
 STR= ()

Output parameters for STRUCTURE CONTENT DATA RECORD for
 ELTYPE = PELSS:
 The IA array contains:

- The number of activation indices(NAI)
- The list of activation indices
- The number of deactivation indices(NDI)
- The list of deactivation indices

The other arrays are empty.

IL= 1+*
 IA(1)= number of activation indices = NAI
 IA(2)= number of deactivation indices = NDI
 IA= element 3 through NAI+2 contain the activation list
 IA= element NAI+3 through NDI+NAI+2 contain the deactivation list
 RL= 0
 RA= ()
 SL= 0
 LSTR= ()
 STR= ()

Output parameters for STRUCTURE CONTENT DATA RECORD for
 ELTYPE = PEEDC:
 The IA array contains:

- The colour type(CT)
- The number of components of colour value
- The actual data of colour index, if CT is indirect.

The RA array contains:

- The actual data of colour component values as required by CT.

Common element:

IL= 2+*

IA(1)= colour type = CT

IA(2)= number of components of colour value

RL= *

SL= 0

LSTR= ()

STR= ()

Individual element:

CASE colour type=PINDIR:

IA(3)= colour index

CASE colour type= PRGB or PCIE or PHSV or PHLS:

RA= element 1 through NCC contain the colour components

Output parameters for STRUCTURE CONTENT DATA RECORD for
ELTYPE = PECAC:

The IA array contains:

- The curve approximation criteria type

The STR array contains:

- The curve approximation data record

IL= 1

IA(1)= curve approximation criteria type

RL= 0

RA=()

SL= length of curve approximation data record array

For i= 1 to SL

LSTR(i)= 80

STR= curve approximation data record

Output parameters for STRUCTURE CONTENT DATA RECORD for
ELTYPE = PESAC:

The IA array contains:

- The surface approximation criteria type

The STR array contains:

- The surface approximation data record

IL= 1

IA(1)= surface approximation criteria type

RL= 0

RA=()

SL= length of surface approximation data record array

For i= 1 to SL

LSTR(i)= 80

STR= surface approximation data record

Output parameters for STRUCTURE CONTENT DATA RECORD for
ELTYPE = PEPSC:

The IA array contains:

- The parametric surface characteristics type

The STR array contains:

- The parametric surface characteristics data record

IL= 1
IA(1)= parametric surface characteristics type
RL= 0
RA= ()
SL= length of data record array
FOR i=1 TO length of data record array
LSTR(i)= 80
STR= parametric surface characteristics data record³⁵

Output parameters for STRUCTURE CONTENT DATA RECORD for
ELTYPE = PERCM:

The IA array contains:

- The rendering colour model

The other arrays are empty.

IL= 1
IA(1)= rendering colour model
RL= 0
RA= ()
SL= 0
LSTR= ()
STR= ()

Output parameters for STRUCTURE CONTENT DATA RECORD for
ELTYPE = PEDPCI:

The IA array contains:

- The depth cue index

The other arrays are empty.

IL= 1
IA(1)= depth cue index
RL= 0
RA= ()
SL= 0
LSTR= ()
STR= ()

Output parameters for STRUCTURE CONTENT DATA RECORD for
ELTYPE = PECMI:

The IA array contains:

- The colour mapping index

The other arrays are empty.

IL= 1
IA(1)= colour mapping index
RL= 0
RA= ()
SL= 0
LSTR= ()
STR= ()

³⁵See SET PARAMETRIC SURFACE CHARACTERISTICS for a description of the parametric surface characteristics data record.

ELEMENT SEARCH

SUBROUTINE PELS(STRID,STRTEP,SRCDIR,EISN,EIS,EESN,EES,ERRIND,
*STATUS,FNDEP)

Input Parameters:

INTEGER STRID
INTEGER STRTEP
INTEGER SRCDIR
INTEGER EISN
INTEGER EIS(EISN)

structure identifier
start element position
search direction(PBWD,PFWDD)
number of elements in element inclusion set
element inclusion set

(PENIL,PEPL3,PEPL,PEPM3,PEPM,PETX3,PETX,
PEATR3,PEATR,PEFA3,PEFA,PEFAS3,PEFAS,
PECA3,PECA,PEGDP3,PEGDP,PEPLI,PEPMI,
PETXI,PEII,PEEDI,PELN,PELWSC,PEPLCI,
PEMK,PEMKSC,PEPMCI,PETXFN,PETXPR,
PECHXP,PECHSP,PETXCI,PECHL,PECHUP,
PETXP,PETXAL,PEATCH,PEATCU,PEATP,
PEATAL,PEANST,PEIS,PEISI,PEICI,PEEDFG,
PEEDT,PEEWSC,PEEDCI,PEPA,PEPRPV,
PEPARF,PEADS,PERES,PEIASF,
PEHRID,PELMT3,PELMT,PEGMT3,PEGMT,
PEMCV3,PEMCV,PEMCLI,PERMCV,PEVWI,
PEEXST,PELB,PEAP,PEGSE,PEPKID,³⁶
PEPLS3,PEFS3D,PEFSD,PECA3P,PESFS3,
PESFSD,PETS3D,PETSD,PETST3,PETSTD,
PEQM3D,PEQMD,PEBC3,PEBC3C,PEBS3,
PESS3D,PEDMI,PERFI,PEBII,PEBDMI,
PEBRFI,PEPRSI,PEPLC,PEPLSM,PEPMC,
PETXC,PEFDM,PEFCM,PEIC,PEISM,
PEDMM,PERFP,PERFM,PEBIS,PEBISI,
PEBIC,PEBISM,PEBDMM,PEBRFP,PEBRFM,
PELSS,PEEDC,PECAC,PESAC,PEPSC,
PERCM,PEDPCI,PECFMI)

INTEGER EESN
INTEGER EES(EESN)

number of elements in element exclusion set
element exclusion set
(enumerated type the same as that of element inclusion set)

Output Parameters:

INTEGER ERRIND
INTEGER STATUS
INTEGER FNDEP

error indicator
status indicator(PFAIL,PSUCC)
found element position

This function is defined in PHIGS part 1. Additional enumeration types are defined in PHIGS part 4. This binding shows those additional enumeration types.

³⁶already defined in PHIGS

14 Utility functions not defined in PHIGS and PHIGS PLUS

PACK COLOUR SPLINE CURVE

SUBROUTINE PPCSC (CSORD,CNKA,CKNOTS,CRTYPE,CTYPES,NCC,NCSCP,
*CSCP,MLDR,ERRIND,CSCLDR,CSCREC)

Input Parameters:

INTEGER CSORD	colour spline order
INTEGER CNKA	number of colour spline knots
REAL CKNOTS(CNKA)	colour spline knots
INTEGER CRTYPE	colour spline rationality (PRAT,PNRAT)
INTEGER CTYPES	colour type for colour spline
INTEGER NCC	number of colour components (count does not include homogeneous component in rational colour splines)
INTEGER NCSCP	number of colour spline control points
REAL CSCP(*)	colour spline control points
INTEGER MLDR	dimension of colour spline curve data record array

Output Parameters:

INTEGER ERRIND	error indicator (zero if no error)
INTEGER CSCLDR	number of array elements used in CSCREC
CHARACTER*80 CSCREC(MLDR)	colour spline curve data record

UNPACK COLOUR SPLINE CURVE

SUBROUTINE PUCSC (CSCLDR,CSCREC,ICNKA,INCSCP,ERRIND,CSORD,CNKA,
*CKNOTS,CRTYPE,CTYPES,NC,NCSCP,CSCP)

Input Parameters:

INTEGER CSCLDR	number of array elements used in CSCREC
CHARACTER*80 CSCREC(CSCLDR)	colour spline curve data record
INTEGER ICNKA	dimension of CKNOTS array
INTEGER INCSCP	dimension of CSCP array

Output Parameters:

INTEGER ERRIND	error indicator (zero if no error)
INTEGER CSORD	colour spline order
INTEGER CNKA	number of colour spline knots in CKNOTS array
REAL CKNOTS(ICNKA)	colour spline knots
INTEGER CRTYPE	colour spline rationality (PRAT,PNRAT)
INTEGER CTYPES	colour type for colour spline
INTEGER NC	number of colour components (count does not include homogeneous component in rational colour splines)
INTEGER NCSCP	number of colour spline control points
REAL CSCP(INCSCP)	colour spline control points

PACK TRIMMING CURVE

SUBROUTINE PPTC (INITFL,LOOPFL,TACRI,LDR,DATREC,TCVF,TSORD,
 *TNKA,TKNOTS,TPARL,TRTYPE,NTCCP,TPWUA,TPWVA,TPWWA,MLDR,
 *ERRIND,TCLDR,TCREC)

Input Parameters:

LOGICAL INITFL	data record initialization flag
LOGICAL LOOPFL	data record new loop flag
INTEGER TACRI	trimming curve approximation criteria type
INTEGER LDR	length of data record array for trimming curve approximation criteria
CHARACTER*80 DATREC(LDR)	data record for trimming curve approximation criteria ³⁷
INTEGER TCVF	trimming curve visibility flag (POFF,PON)
INTEGER TSORD	trimming curve spline order
INTEGER TNKA	number of spline knots in array
REAL TKNOTS(TNKA)	trimming curve spline knots
REAL TPARL(2)	trimming curve parameter range limits
INTEGER TRTYPE	trimming curve spline rationality (PRAT,PNRAT)
INTEGER NTCCP	number of trimming curve spline control points
REAL TPWUA(NTCCP)	trimming curve U control point components
REAL TPWVA(NTCCP)	trimming curve V control point components
REAL TPWWA(NTCCP)	trimming curve W control point components (unused if trimming curve is non-rational)
INTEGER MLDR	dimension of trimming curve data record

Output Parameters:

INTEGER ERRIND	error indicator (zero if no error)
INTEGER TCLDR	total number of array elements used in TCREC
CHARACTER*80 TCREC(MLDR)	trimming curve data record

³⁷See SET CURVE APPROXIMATION CRITERIA for description of the curve approximation criteria data recode.

UNPACK TRIMMING CURVE

SUBROUTINE PUTC(TCLDR,TCREC,ILOOP,ITCRV,MLDR,ITNKA,INTCCP,
 *ERRIND,NLOOP,NCURVE,TACRI,LDR,DATREC,TCVF,TSORD,TNKA,TKNOTS,
 *TPARL,TRTYPE,NTCCP,TPWUA,TPWVA,TPWWA)

Input Parameters:

INTEGER TCLDR	number of array elements used in TCREC
CHARACTER*80 TCREC(TCLDR)	trimming curve data record
INTEGER ILOOP	which loop
INTEGER ITCRV	which curve in loop
INTEGER MLDR	dimension of data record for trimming curve approximation criteria
INTEGER ITNKA	dimension of TKNOTS array
INTEGER INTCCP	dimension of TPWUA, TPWVA, and TPWWA arrays

Output Parameters:

INTEGER ERRIND	error indicator (zero if no error)
INTEGER NLOOP	Number of trimming loops
INTEGER NCURVE	Number of curves in current loop
INTEGER TACRI	trimming curve approximation criteria type
INTEGER LDR	number of array elements used in DATREC
CHARACTER*80 DATREC(MLDR)	data record for trimming curve approximation criteria ³⁸
INTEGER TCVF	trimming curve visibility flag (POFF,PON)
INTEGER TSORD	trimming curve spline order
INTEGER TNKA	number of trimming curve spline knots in TKNOTS array
REAL TKNOTS(ITNKA)	trimming curve spline knots
REAL TPARL(2)	trimming curve parameter range limits
INTEGER TRTYPE	trimming curve spline rationality (PRAT,PNRAT)
INTEGER NTCCP	number of trimming curve spline control points
REAL TPWUA(INTCCP)	trimming curve U control point components
REAL TPWVA(INTCCP)	trimming curve V control point components
REAL TPWWA(INTCCP)	trimming curve W control point components (unused if trimming curve is non-rational)

³⁸See SET CURVE APPROXIMATION CRITERIA for a description of the curve approximation criteria data recode.

PACK COLOUR SPLINE SURFACE

SUBROUTINE PPCSS (CUSORD,CVSORD,CUNKA,CVNKA,CUKNTS,CVKNTS,
 *CRTYPE,CTYPES,NCC,UNCSCP,VNCSCP,CSCP,MLDR,ERRIND,
 *CSSLDR,CSSREC)

Input Parameters:

INTEGER CUSORD	u colour spline order
INTEGER CVSORD	v colour spline order
INTEGER CUNKA	number of u spline knots in array
INTEGER CVNKA	number of v spline knots in array
REAL CUKNTS(CUNKA)	u colour spline knots
REAL CVKNTS(CVNKA)	v colour spline knots
INTEGER CRTYPE	colour spline rationality (PRAT,PNRAT)
INTEGER CTYPES	colour type for spline
INTEGER NCC	number of colour components (count does not include homogeneous component in rational colour splines)
INTEGER UNCSCP	u number of colour spline control points dimension
INTEGER VNCSCP	v number of colour spline control points dimension
REAL CSCP(*)	colour spline control points
INTEGER MLDR	dimension of colour spline surface data record array

Output Parameters:

INTEGER ERRIND	error indicator (zero if no error)
INTEGER CSSLDR	number of array elements used in CSSREC
CHARACTER*80 CSSREC(MLDR)	colour spline surface data record

UNPACK COLOUR SPLINE SURFACE

SUBROUTINE PUCSS (CSSLDR,CSSREC,ICUNKA,ICVNKA,ICNSCP,ERRIND,
 *CUSORD,CVSORD,CUNKA,CVNKA,CUKNTS,CVKNTS,CRTYPE,CTYPES,NCC,
 *UNCSCP,VNCSCP,CSCP)

Input Parameters:

INTEGER CSSLDR	number of array elements used in CSSREC
CHARACTER*80 CSSREC(CSSLDR)	colour spline surface data record
INTEGER ICUNKA	dimension of CUKNTS array
INTEGER ICVNKA	dimension of CVKNTS array
INTEGER ICNSCP	dimension of CSCP array

Output Parameters:

INTEGER ERRIND	error indicator (zero if no error)
INTEGER CUSORD	u colour spline order
INTEGER CVSORD	v colour spline order
INTEGER CUNKA	number of u spline knots in CUKNTS array
INTEGER CVNKA	number of v spline knots in CVKNTS array
REAL CUKNTS(ICUNKA)	u colour spline knots
REAL CVKNTS(ICVNKA)	v colour spline knots
INTEGER CRTYPE	colour spline rationality (PRAT,PNRAT)
INTEGER CTYPES	colour type for spline
INTEGER NCC	number of colour components (count does not include homogeneous component in rational colour splines)
INTEGER UNCSCP	u number of colour spline control points dimension
INTEGER VNCSCP	v number of colour spline control points dimension
REAL CSCP(UNCSCP)	colour spline control points

PACK DATA SPLINE SURFACE

SUBROUTINE PPDSS (INITFL,DATAFL,DUSORD,DVSORD,DUNKA,DVNKA,
 *DUKNTS,DVKNTS,DRTYPE,UNDSCP,UNDSCP,DDIMS,DSCP,MLDR,ERRIND,
 *DSSLDR,DSSREC)

Input Parameters:

LOGICAL INITFL	data record initialization flag
LOGICAL DATAFL	data record new data spline flag
INTEGER DUSORD	u data spline order
INTEGER DVSORD	v data spline order
INTEGER DUNKA	number of u spline knots in DUKNTS array
INTEGER DVNKA	number of v spline knots in DVKNTS array
REAL DUKNTS(DUNKA)	u data spline knots
REAL DVKNTS(DVNKA)	v data spline knots
INTEGER DRTYPE	data spline rationality (PRAT,PNRAT)
INTEGER UNDSCP	u number of data spline control points dimension
INTEGER UNDSCP	v number of data spline control points dimension
INTEGER DDIMS	data dimension for spline
REAL DSCP(*)	data spline control points
INTEGER MLDR	dimension of data spline surface data record array

Output Parameters:

INTEGER ERRIND	error indicator (zero if no error)
INTEGER DSSLDR	number of array elements used in DSSREC
CHARACTER*80 DSSREC(MLDR)	data spline surface data record

UNPACK DATA SPLINE SURFACE

SUBROUTINE PUDSS (DSSLDR,DSSREC,IDS,IDUNKA,IDVNKA,IDNSCP,ERRIND,
 *DUSORD,DVSORD,DUNKA,DVNKA,DUKNTS,DVKNTS,DRTYPE,UNDS CP,
 *UNDS CP,DDIMS,DSCP)

Input Parameters:

INTEGER DSSLDR	number of array elements used in DSSREC
CHARACTER*80 DSSREC(DSSLDR)	data record
INTEGER IDS	which data spline
INTEGER IDUNKA	dimension of DUKNTS array
INTEGER IDVNKA	dimension of DVKNTS array
INTEGER IDNSCP	dimension of DSCP array

Output Parameters:

INTEGER ERRIND	error indicator (zero if no error)
INTEGER DUSORD	u data spline order
INTEGER DVSORD	v data spline order
INTEGER DUNKA	number of u spline knots in array
INTEGER DVNKA	number of v spline knots in array
REAL DUKNTS(IDUNKA)	u data spline knots
REAL DVKNTS(IDVNKA)	v data spline knots
INTEGER DRTYPE	data spline rationality (PRAT,PNRAT)
INTEGER UNDS CP	u number of data spline control points dimension
INTEGER UNDS CP	v number of data spline control points dimension
INTEGER DDIMS	data dimension for spline
REAL DSCP(IDNSCP)	data spline control points

Annex A (informative) FORTRAN Examples

Add the following to AnnexA.

The following sample programs, using the PHIGS and PHIGS PLUS FORTRAN binding, illustrate the use of PHIGS and PHIGS PLUS functions.

Example 1:

```

C  PROGRAM SURF
C
C  DESCRIPTION:
C    This program draws a surface hollowed out by trimming curve.
C    Copyright 1992 O'Reilly and Associates, Inc. Permission to use, copy,
C    and modify this program is hereby granted, as long as this
C    copyright notice appears in each copy of the program source code.
C    Program adapted from C to Fortran for use as language binding example.
C
C  Define PHIGS constants.
C
C  INTEGER PNRAT, PHOLLO, PUBKCP
C  PARAMETER (PNRAT=0, PHOLLO=0, PUBKCP=1)
C  INTEGER PICPC, PCBKSA, PON
C  PARAMETER (PICPC=3, PCBKSA=2, PON=1)
C  INTEGER PPERFO
C  PARAMETER (PPERFO=1)
C
C  Define the surface data.
C
C  INTEGER USORD, VSORD
C  INTEGER UNKA, VNKA
C  INTEGER UNCP, VNCP
C  INTEGER RTYPE
C  REAL UKNOTS(6)/0.0,0.0,0.0,1.0,1.0,1.0/
C  REAL VKNOTS(8)/0.0,0.0,0.0,0.0,0.0,1.0,1.0,1.0/
C  REAL PXA(12)/0.0,0.3,0.6,0.9,
C  -      0.0,0.3,0.6,0.9,
C  -      0.0,0.3,0.6,0.9/
C  REAL PYA(12)/0.5,0.5,0.4,0.5,
C  -      0.6,1.0,0.5,0.3,
C  -      0.5,0.5,0.4,0.2/
C  REAL PZA(12)/0.0,0.0,0.0,0.0,
C  -      0.5,0.5,0.5,0.5,
C  -      1.0,1.0,1.0,1.0/
C  REAL PWA(12)/12*1.0/
C
C  Define the trimming curve data.
C
C  LOGICAL INITFL, LOOPFL
C  INTEGER TACRI, TCVF
C  INTEGER TSORD, TNKA, TRTYPE, NTCCP
C  REAL TKNOTS(12), TPWUA(9), TPWVA(9)
C  DATA TKNOTS(1), TKNOTS(2), TKNOTS(3), TKNOTS(4)/0.0,0.0,0.0,1.0/

```

DATA TKNOTS(5),TKNOTS(6),TKNOTS(7),TKNOTS(8)/1.0,2.0,2.0,3.0/
 DATA TKNOTS(9),TKNOTS(10),TKNOTS(11),TKNOTS(12)/3.0,4.0,4.0,4.0/
 DATA TPWUA(1),TPWUA(2),TPWUA(3)/0.5,0.68,0.68/
 DATA TPWUA(4),TPWUA(5),TPWUA(6)/0.68,0.5,0.32/
 DATA TPWUA(7),TPWUA(8),TPWUA(9)/0.32,0.32,0.5/
 DATA TPWVA(1),TPWVA(2),TPWVA(3)/0.32,0.32,0.5/
 DATA TPWVA(4),TPWVA(5),TPWVA(6)/0.68,0.68,0.68/
 DATA TPWVA(7),TPWVA(8),TPWVA(9)/0.5,0.32,0.32/
 REAL TPWWA/0.0/
 REAL TPARL(2)
 INTEGER TCLDR
 CHARACTER*80 TCREC(9)

C

INTEGER PSCTY
 INTEGER ACRI
 INTEGER ERRIND
 INTEGER IA(3),LDR,MLDR
 CHARACTER*80 DATREC

C

C Open PHIGS and a workstation.

C

CALL POPPH(99,-1)
 CALL POPWK(1,0,0)

C

C Open the structure.

C

CALL POPST(1)

C

C Select the view index for the surface.

C

CALL PSVWI(1)

C

C Hollow the surface.

C

CALL PSIS(PHOLLO)

C

C Set the parametric surface characteristics.

C

IL = 3
 IA(1) = PUBKCP
 IA(2) = 20
 IA(3) = 20
 MLDR = 1
 CALL PPREC(IL,IA,0,0,0,0,MLDR,ERRIND,LDR,DATREC)
 PSCTY = PICPC
 CALL PSPSC(PSCTY,LDR,DATREC)

C

C Set the surface approximation criteria.

C

IL = 2
 IA(1) = 10
 IA(2) = 10
 MLDR = 1
 CALL PPREC(IL,IA,0,0,0,0,MLDR,ERRIND,LDR,DATREC)

```

ACRI = PCBKSA
CALL PSSAC(ACRI,LDR,DATREC)
C
C   Display the edge of surface.
C
CALL PSEDFG(PON)
C
C   Set the first trimming curve
C
INITFL = .TRUE.
LOOPFL = .TRUE.
TACRI = PCBKCA
IL = 1
IA(1) = 10
MLDR = 1
CALL PPREC(IL,IA,0,0,0,0,MLDR,ERRIND,LDR,DATREC)
TCVF = PON
TSORD = 3
TNKA = 12
TPARL(1) = 0.0
TPARL(2) = 4.0
TRTYPE = PNRAT
NTCCP = 9
MLDR = 3
CALL PPTCV(INITFL,LOOPFL,TACRI,LDR,DATREC,TCVF,TSORD,TNKA,
-   TKNOTS,TPARL,TRTYPE,NTCCP,TPWUA,TPWVA,
-   TPWWA,MLDR,ERRIND,TCLDR,TCREC)
C
C   Set the second trimming curve
C
INITFL = .FALSE.
LOOPFL = .FALSE.
TACRI = PCBKCA
IL = 1
IA(1) = 10
MLDR = 1
CALL PPREC(IL,IA,0,0,0,0,MLDR,ERRIND,LDR,DATREC)
TCVF = PON
TSORD = 3
TNKA = 12
TKNOTS(1) = 0.0
TKNOTS(2) = 0.0
TKNOTS(3) = 0.0
TKNOTS(4) = 1.0
TKNOTS(5) = 1.0
TKNOTS(6) = 2.0
TKNOTS(7) = 2.0
TKNOTS(8) = 3.0
TKNOTS(9) = 3.0
TKNOTS(10) = 4.0
TKNOTS(11) = 4.0
TKNOTS(12) = 4.0
TPARL(1) = 0.0
TPARL(2) = 4.0

```