



INTERNATIONAL STANDARD ISO/IEC 9594-3:2008
TECHNICAL CORRIGENDUM 2

Published 2012-09-15

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION • МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ • ORGANISATION INTERNATIONALE DE NORMALISATION
INTERNATIONAL ELECTROTECHNICAL COMMISSION • МЕЖДУНАРОДНАЯ ЭЛЕКТРОТЕХНИЧЕСКАЯ КОМИССИЯ • COMMISSION ÉLECTROTECHNIQUE INTERNATIONALE

Information technology — Open Systems Interconnection — The Directory: Abstract service definition

TECHNICAL CORRIGENDUM 2

Technologies de l'information — Interconnexion de systèmes ouverts (OSI) — L'annuaire: Définition du service abstrait

RECTIFICATIF TECHNIQUE 2

Technical Corrigendum 2 to ISO/IEC 9594-3:2008 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 6, *Telecommunications and information exchange between systems*, in collaboration with ITU-T. The identical text is published as Rec. ITU-T X.511 (2008)/Cor.2 (04/2012).

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 9594-3:2008/COR2:2012

INTERNATIONAL STANDARD

RECOMMENDATION ITU-T

**Information technology – Open Systems Interconnection –
The Directory: Abstract service definition**

Technical Corrigendum 2

(covering resolution to defect reports 363, 364 and 367)

1) Correction of the defects reported in defect report 363

Update the second paragraph of clause 7.6.1 as shown:

A **contextSelection** is said to govern ~~an~~ one or more attribute types if any of the following conditions occur:

- the **ContextSelection** specifies **allContexts** (in which case all attribute values of all attribute types are selected);
- the **ContextSelection** data type has a **selectedContexts** component which includes a set of TypeAndContextAssertion data types where the ~~whose~~-type component specifies an attribute type, including its subtypes, that is governed by the contextAssertions component ~~the same as or a supertype of the attribute type~~; or
- the **ContextSelection** data type has a **selectedContexts** component which includes a **TypeAndContextAssertion** data type where the ~~whose~~-type is component specifies the object identifiers id-oa-allAttributeTypes.

2) Correction of the defects reported in defect report 364

In clause 12.7 and Annex A update **securityError** as shown:

```
securityError ERROR ::= {
  PARAMETER      OPTIONAL-PROTECTED { SET {
    problem      [0] SecurityProblem,
    spkmInfo     [1] SPKM-ERROR, OPTIONAL,
    COMPONENTS OF CommonResults } }
  CODE           id-errcode-securityError }
```

3) Correction of the defects reported in defect report 367

In clause 7.10 and in Annex A, delete the **attributeCertificationPath** component of the security parameters and mark the tag as not reusable.

Also in clause 7.10, delete the text associated with the **attributeCertificationPath** component.

Delete the last two sentences of the first paragraph of clause 8.1.1.

In clause 8.1.1 and in Annex A, delete the **attributeCertificationPath** component and mark the tag as not reusable.

In clause 8.1.2, replace the fourth paragraph with:

For the **strong** alternative, the specification for the parameters of **StrongCredential** are:

- the **certificate-path** component, if present, shall hold a certification path as specified by the CertificationPath data type as defined in clause 7.6 of ITU-T Rec. X.509 | ISO/IEC 9594-8;
- the **bind-token** component shall be signed and shall have the subcomponents as specified below; and
- the **name** component shall hold the distinguished name of the requestor.