

ISO

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION

ISO RECOMMENDATION R 104

BALL AND ROLLER BEARINGS
BOUNDARY DIMENSIONS

1st EDITION

April 1959

COPYRIGHT RESERVED

The copyright of ISO Recommendations and ISO Standards belongs to ISO Member Bodies. Reproduction of these documents, in any country, may be authorized therefore only by the national standards organization of that country, being a member of ISO.

For each individual country the only valid standard is the national standard of that country.

Printed in Switzerland

Also issued in French and Russian. Copies to be obtained through the national standards organizations.

BRIEF HISTORY

The ISO Recommendation R 104, *Ball and Rollers Bearings - Boundary Dimensions*, was drawn up by Technical Committee ISO/TC 4, *Ball and Roller Bearings*, the Secretariat of which is held by the Sveriges Standardiseringskommission (SIS).

The proposals drawn up by the ISO/TC 4 Secretariat for the subject-matter of this ISO Recommendation were discussed by the Technical Committee during its fourth meeting, held in Madrid, in May 1955, and during its fifth meeting, held in Vienna, in September 1956; they were adopted as a Draft ISO Recommendation.

On 15 November 1957, the Draft ISO Recommendation (No 154) was distributed to all the ISO Member Bodies and was approved by the following Member Bodies:

Austria	India	Spain
Bulgaria	Italy	Sweden
Burma	Japan	Switzerland
Canada	Netherlands	Union of
Finland	New Zealand	South-Africa
France	Poland	United Kingdom
Germany	Portugal	U.S.A.
Hungary	Romania	U.S.S.R.

No Member Body opposed the approval of the Draft.

The Draft ISO Recommendation was then submitted by correspondence to the ISO Council, which decided, in April 1959, to accept it as an ISO RECOMMENDATION.

BALL AND ROLLER BEARINGS

BOUNDARY DIMENSIONS

CONTENTS

1. Radial bearings (except tapered roller bearings)
Intermediate boundary dimensions

Symbols		4
1.1 Diameter series 8		4
1.2 Diameter series 9		5
1.3 Diameter series 0		5

2. Double-direction thrust bearings with flat seats
Boundary dimensions

Symbols		6
2.1 Diameter series 2 — Dimension series 22		7
2.2 Diameter series 3 — Dimension series 23		7
2.3 Diameter series 4 — Dimension series 24		8


1. RADIAL BEARINGS

(except tapered roller bearings)

INTERMEDIATE BOUNDARY DIMENSIONS

Symbols

- d = Bearing bore diameter
 D = Bearing outside diameter
 B = Bearing width (inner and outer rings)
 r = Inner and outer ring chamfer dimension (height and width)
 $r_{\min.}$ = Minimum chamfer dimension indicating the maximum shaft or housing fillet radius which the bearing corner will clear
 $r_{\max.}$ = Maximum chamfer dimension indicating the minimum shaft or housing shoulder which the bearing face must contact
 r_{nominal} = Nominal chamfer dimension



1.1 Diameter series 8

Dimensions in millimetres

Bore diameter <i>d</i>	Outside diameter <i>D</i>	Dimension series												
		08	18	28	38	48	58	68	08			18 — 68		
		Width <i>B</i>							Chamfer <i>r</i>					
									min.	max.	nomi- nal	min.	max.	nomi- nal
22	34	4	7	—	10	—	16	22	0.3	0.8	0.5	0.3	0.8	0.5
28	40	4	7	—	10	—	16	22	0.3	0.8	0.5	0.3	0.8	0.5
32	44	4	7	—	10	—	16	22	0.3	0.8	0.5	0.3	1	0.5

1.2 Diameter series 9

Dimensions in millimetres

Bore diameter <i>d</i>	Outside diameter <i>D</i>	Dimension series												
		09	19	29	39	49	59	69	09			19 — 69		
		Width <i>B</i>							Chamfer <i>r</i>					
									min.	max.	nomi- nal	min.	max.	nomi- nal
22	39	7	9	11	13	17	23	30	0.3	0.8	0.5	0.3	1	0.5
28	45	7	9	11	13	17	23	30	0.3	0.8	0.5	0.3	1	0.5
32	52	7	10	13	15	20	27	36	0.3	0.8	0.5	0.6	1.5	1

1.3 Diameter series 0

Dimensions in millimetres

Bore diameter <i>d</i>	Outside diameter <i>D</i>	Dimension series												
		00	10	20	30	40	50	60	00		10 — 60			
		Width <i>B</i>							Chamfer <i>r</i>					
									min.	max.	nomi- nal	min.	max.	nomi- nal
22	44	8	12	14	16	22	30	40	0.3	0.8	0.5	0.6	1.5	1
28	52	8	12	15	18	24	32	43	0.3	1	0.5	0.6	1.5	1
32	58	9	13	16	20	26	35	47	0.3	1	0.5	1	2.2	1.5

2. DOUBLE-DIRECTION THRUST BEARINGS WITH FLAT SEATS

BOUNDARY DIMENSIONS

Symbols

d = Maximum shaft shoulder diameter = bore diameter of small-bore washer of corresponding single-direction thrust bearing

d_1 = Bore diameter of centre washer

D = Outside diameter of large-bore washers = maximum outside diameter of centre washer

H = Bearing height

a = Thickness of centre washer

r = Chamfer dimension (height and width) of outside surface of large-bore washers

r_1 = Chamfer dimension (height and width) of bore of centre washer

$r_{\min.}, r_{1\min.}$ = Minimum chamfer dimension indicating the maximum shaft or housing fillet radius which the bearing corner will clear

$r_{\max.}, r_{1\max.}$ = Maximum chamfer dimension

$r_{\text{nominal}}, r_{1\text{nominal}}$ = Nominal chamfer dimension

