

ISO

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION

ISO RECOMMENDATION R 1580

SLOTTED PAN HEAD SCREWS

METRIC SERIES

1st EDITION

June 1970

COPYRIGHT RESERVED

The copyright of ISO Recommendations and ISO Standards belongs to ISO Member Bodies. Reproduction of these documents, in any country, may be authorized therefore only by the national standards organization of that country, being a member of ISO.

For each individual country the only valid standard is the national standard of that country.

Printed in Switzerland

Also issued in French and Russian. Copies to be obtained through the national standards organizations.

STANDARDSISO.COM : Click to view the full PDF of ISO/R 1580:1970

BRIEF HISTORY

The ISO Recommendation R 1580, *Slotted pan head screws – Metric series*, was drawn up by Technical Committee ISO/TC 2, *Bolts, nuts and accessories*, the Secretariat of which is held by the Deutscher Normenausschuss (DNA).

Work on this question led to the adoption of Draft ISO Recommendation No. 1580, which was circulated to all the ISO Member Bodies for enquiry in July 1968. It was approved, subject to a few modifications of an editorial nature, by the following Member Bodies :

Austria	Israel	South Africa, Rep. of
Belgium	Italy	Spain
Brazil	Japan	Sweden
Canada	Korea, Rep. of	Switzerland
Czechoslovakia	Netherlands	Thailand
Denmark	New Zealand	Turkey
Finland	Norway	U.A.R.
Germany	Poland	United Kingdom
Hungary	Portugal	U.S.A.
India	Romania	U.S.S.R.

The following Member Body opposed the approval of the Draft :

France

This Draft ISO Recommendation was then submitted by correspondence to the ISO Council, which decided to accept it as an ISO RECOMMENDATION.

STANDARDSISO.COM : Click to view the full PDF of ISO/R 1580:1970

SLOTTED PAN HEAD SCREWS

METRIC SERIES




1. SCOPE

This ISO Recommendation specifies dimensions of slotted pan head screws of the metric series and provides a system of standard lengths, i.e. recommended combinations of thread size, thread length and nominal length.




2. DIMENSIONS

Principal dimensions are given in Table 1, page 6. (Nominal lengths and thread lengths are given in section 3.) The thread sizes in parentheses should be avoided if possible.

NOTE. — According to the type of manufacturing process used, screw cutting or die-casting, the shape of the head may be cylindrical or tapered with a conicity of up to 5°.



shank diameter $\approx$ pitch diameter



shank diameter $\approx$ major diameter

TABLE 1 – Principal dimensions

Dimensions in millimetres

Thread size	<i>d</i>	2.5	3	(3.5)	4	(4.5)	5	6	8	10
<i>D</i>	h14	5	6	7	8	9	10	12	16	20
<i>k</i>	h13	1.5	1.8	2.1	2.4	2.7	3	3.6	4.8	6
<i>n</i>	Nominal value	0.6	0.8	0.8	1	1	1.2	1.6	2	2.5
	max.	0.80	1.00	1.00	1.20	1.20	1.51	1.91	2.31	2.81
	min.	0.66	0.86	0.86	1.06	1.06	1.26	1.66	2.06	2.56
<i>e</i>	min.	0.6	0.72	0.84	0.96	1.08	1.2	1.44	1.92	2.4
<i>t</i>	max.	0.9	1.08	1.26	1.44	1.62	1.8	2.16	2.88	3.6
	min.	0.6	0.72	0.84	0.96	1.08	1.2	1.44	1.92	2.4
<i>R</i> ₁	min.	0.1	0.1	0.1	0.2	0.2	0.2	0.25	0.4	0.4
<i>R</i> ₂	max.	1	1.2	1.4	1.6	1.8	2	2.5	3.2	4
<i>d</i> _a	max.	3.1	3.6	4.1	4.7	5.2	5.7	6.8	9.2	11.2
<i>a</i>	max.	0.9	1	1.2	1.4	1.5	1.6	2	2.5	3

NOTE. – For tolerance and symbols see ISO Recommendation R 286, *ISO System of limits and fits – Part 1 : General, tolerances and deviations*.