

ISO

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION

ISO RECOMMENDATION R 357

EXPRESSION OF THE POWER AND INTENSITY LEVELS OF SOUND OR NOISE

This ISO Recommendation is supplementary to
ISO Recommendation R 131 -

Expression of the Physical and Subjective Magnitudes of Sound or Noise

1st EDITION
December 1963

COPYRIGHT RESERVED

The copyright of ISO Recommendations and ISO Standards belongs to ISO Member Bodies. Reproduction of these documents, in any country, may be authorized therefore only by the national standards organization of that country, being a member of ISO.

For each individual country the only valid standard is the national standard of that country.

Printed in Switzerland

Also issued in French and Russian. Copies to be obtained through the national standards organizations.

BRIEF HISTORY

The ISO Recommendation R 357, *Expression of the Power and Intensity Levels of Sound or Noise*, was drawn up by Technical Committee ISO/TC 43, *Acoustics*, the Secretariat of which is held by the British Standards Institution (B.S.I.).

Work on this question by the Technical Committee began in 1960 and led, in 1961, to the adoption of a Draft ISO Recommendation.

In March 1962, this Draft ISO Recommendation (No. 504) was circulated to all the ISO Member Bodies for enquiry. It was approved by the following Member Bodies:

Australia	Denmark	New Zealand
Austria	Finland	Poland
Belgium	France	Portugal
Brazil	Germany	Switzerland
Burma	Hungary	Sweden
Canada	India	United Kingdom
Chile	Japan	U.S.A.
Czechoslovakia	Netherlands	U.S.S.R.
		Yugoslavia

No Member Body opposed the approval of the Draft.

The Draft ISO Recommendation was then submitted by correspondence to the ISO Council, which decided, in December 1963, to accept it as an ISO RECOMMENDATION.

EXPRESSION OF THE POWER AND INTENSITY LEVELS OF SOUND OR NOISE

This ISO Recommendation is supplementary to
ISO Recommendation R 131
Expression of the Physical and Subjective Magnitudes of Sound or Noise

1. SOUND POWER LEVEL

The sound power level of a sound or noise is expressed as

$$10 \log_{10} \frac{P}{P_0} \quad \text{in decibels, dB}$$

where P is the sound power in question, and
 P_0 is the reference sound power, expressed in the same units as P .

It is recommended that the value

$$10^{-12} \text{ W, that is, 1 picowatt (pW),}$$

be universally adopted as the reference sound power.

2. SOUND INTENSITY LEVEL

The sound intensity level of a sound or noise is expressed as

$$10 \log_{10} \frac{I}{I_0} \quad \text{in decibels, dB}$$

where I is the sound intensity in question, and
 I_0 is the reference sound intensity expressed in the same units as I .

It is recommended that for sound in air the value

$$10^{-12} \text{ W/m}^2, \text{ that is, } 1 \text{ pW/m}^2, \text{ also expressed as } 10^{-16} \text{ W/cm}^2,$$

be universally adopted as the reference sound intensity.