

TECHNICAL REPORT

**ISO/TR
15070**

First edition
1996-08-15

AMENDMENT 1
2005-05-01

Series 1 freight containers — Rationale for structural test criteria

AMENDMENT 1: Guidance on structural integrity

Conteneurs de la série 1 — Fondement des critères de résistance

AMENDEMENT 1: Lignes directrices pour l'intégrité de la structure



Reference number
ISO/TR 15070:1996/Amd.1:2005(E)

© ISO 2005

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

© ISO 2005

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

In exceptional circumstances, when a technical committee has collected data of a different kind from that which is normally published as an International Standard ("state of the art", for example), it may decide by a simple majority vote of its participating members to publish a Technical Report. A Technical Report is entirely informative in nature and does not have to be reviewed until the data it provides are considered to be no longer valid or useful.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

Amendment 1 to ISO/TR 15070:1996 was prepared by Technical Committee ISO/TC 104, *Freight containers*, Subcommittee SC 1, *General purpose containers*.

Series 1 freight containers — Rationale for structural test criteria

AMENDMENT 1: Guidance on structural integrity

Page 10, 4.8.2.1

In the first line of the first paragraph, replace “the ability of the floor” with “the ability of the whole surface of the floor”.

Page 13, after the content of 4.12.3

Add the following new text.

5 Prototype test criteria and sequence of tests

5.1 For 20 ft containers

See Table 2.

Table 2 — Prototype test criteria and sequence of tests for 20 ft containers

Sequence of tests	ISO test number	Test ^a	Dimensions check	Maximum allowable residual deformation mm
1		Dimensions check	To confirm that all dimensions are in accordance with ISO 668:1995	n/a
2	8	Floor strength: 7 260 kg		
2.1			Bottom side rails	3
2.2			Crossmembers	4
3	1	Stacking: 3 816 kN $1,8R - T$		
3.1			Corner post (horizontal dimensions)	2
3.2			Bottom side rails	3
3.3			Crossmembers	3

Table 2 (continued)

Sequence of tests	ISO test number	Test ^a	Dimensions check	Maximum allowable residual deformation mm
4	2	Lifting from top corner fittings: $2R - T$		
4.1			Bottom side rails	3
4.2			Crossmembers	3
5	3	Lifting from bottom corner fittings: $2R - T$		
5.1			Bottom side rails	3
5.2			Crossmembers	3
6	11	Lifting from fork-lift pockets: $1,6R - T$		
6.1			Bottom side rails	3
6.2			Crossmembers	3
7	4	Restraint (longitudinal)		
7.1			Vertically	3
7.2			Longitudinally	6
8	9	Rigidity (transverse)		
8.1			End frame ^{b,c} diagonally	10
9	10	Rigidity (longitudinal)		
9.1			Side frame at top fittings	6
10	5	End walls and doors		
10.1			Front end panel	7
10.2			Doors ^b	6
11	6	Strength of side walls		
11.1			Side panel	8
12	7	Strength of the roof		
12.1			Roof panel	4
15			After testing, maximum allowable residual deformation for crossmembers	7
NOTE 1 All dimensions are in accordance with ISO 668:1995.				
NOTE 2 After testing, no dimensions are allowed to be outside the planes of the corner-castings.				
^a T is the tare of the container.				
^b Deformation should not affect security and door operation.				
^c These values do not apply for one door off operation.				

5.2 For 40 ft containers

See Table 3.

Table 3 — Prototype test criteria and sequence of tests for 40 ft containers

Sequence of tests	ISO test number	Test ^a	Dimensions check	Maximum allowable residual deformation mm
1		Dimensions check	To confirm that all dimensions are in accordance with ISO 668:1995	n/a
2	8	Floor strength: 7 260 kg		
2.1			Bottom side rails	3
2.2			Crossmembers	4
2.3			Gooseneck	5
3	1	Stacking: 3 816 kN $1,8R - T$		
3.1			Corner post (horizontal dimensions)	2
3.2			Bottom side rails	3
3.3			Crossmembers	3
4	2	Lifting from top corner fittings: $2R - T$		
4.1			Bottom side rails	3
4.2			Crossmembers	3
5	3	Lifting from bottom corner fittings: $2R - T$		
5.1			Bottom side rails	3
5.2			Crossmembers	3
6	11	Lifting from fork-lift pockets: $1,6R - T$		
6.1			Bottom side rails	n/a
6.2			Crossmembers	n/a
7	4	Restraint (longitudinal)		
7.1			Vertically	4
7.2			Longitudinally	10

Table 3 (continued)

Sequence of tests	ISO test number	Test ^a	Dimensions check	Maximum allowable residual deformation mm
8	9	Rigidity (transverse)		
8.1			End frame ^{b,c} diagonally	10
9	10	Rigidity (longitudinal)		
9.1			Side frame at top fittings	9
10	5	End walls and doors		
10.1			Front end panel	7
10.2			Doors ^b	6
11	6	Strength of side walls		
11.1			Side panel	8
12	7	strength of the roof		
12.1			roof panel	4
14	13	Waterproofness ^d	all areas	n/a
15			After testing, maximum allowable residual deformation for crossmembers	6
NOTE 1 All dimensions are in accordance with ISO 668:1995.				
NOTE 2 After testing, no dimensions are allowed to be outside the planes of the corner-castings.				
^a <i>T</i> is the tare of the container.				
^b Deformation should not affect security and door operation.				
^c These values do not apply for one door off operation.				
^d The container should allow no water ingress.				

Pages 13 and 14

Change the numbering of Clause 5 and subclauses 5.1, 5.1.1, 5.1.2 and 5.2 to 6, 6.1, 6.1.1, 6.1.2 and 6.2, respectively.