

S A E

AERONAUTICAL INFORMATION

REPORT

NO. 26

NUMBER 70-90, 70L-90, 80-100 AND 80L-100 PROPELLER SHAFT ENDS
DUAL ROTATION (PROPELLER SUPPLIED BEARING)



May 1, 1949

REAFFIRMED

5/95-

PREPARED BY

Committee E-21, Standard Components for Aircraft Engines
and
Committee P-6, Propeller Standards

SOCIETY OF AUTOMOTIVE ENGINEERS, INC.
29 West 39th Street, New York, N. Y.

SAENORM.COM : Click to view the full PDF of air26

Section 7C of the SAE Technical Board rules provides that: "All technical reports, including standards approved and practices recommended are advisory only. Their use by anyone engaged in industry or trade is entirely voluntary. There is no agreement to adhere to any SAE standard or recommended practice, and no commitment to conform to or be guided by any technical report. In formulating and approving technical reports, the Board and its Committees will not investigate or consider patents which may apply to the subject matter. Prospective users of the report are responsible for protecting themselves against liability for infringement of patents."

NUMBER 70-90, 70L-90, 80-100 AND 80L-100 PROPELLER SHAFT ENDS

DUAL ROTATION (PROPELLER SUPPLIED BEARING)

INTRODUCTION

1. PURPOSE:

- 1.1 The purpose of this report is to preserve for record purposes the dimensions for the No. 70-90, 70L-90, 80-100 and 80L-100 dual rotation propeller shaft ends, which have been deleted from Aeronautical Recommended Practice ARP 375.

2. BACKGROUND:

- 2.1 Aeronautical Recommended Practice ARP 375, initially issued November 1, 1948, included dimensions and data for No. 70-90, 70L-90, 80-100 and 80L-100 dual rotation shafts. The 70-90 and 70L-90 shafts were intended for use with engines of 8,000 to 12,000 HP. However, at about this time it became apparent that the 70 and 70L shafts in these combinations were critically loaded due to gyroscopic and LXP continuous bending moments being encountered in modern high-speed high wing-loading aircraft. Therefore, dimensions for the 80-90 shafts were developed for inclusion in the revised ARP 375. Since it appeared that the 70-90, 70L-90, 80-100 and 80L-100 shafts would not be used, it was decided to delete them from ARP 375 and include them in an Aeronautical Information Report.
- 2.2 Although SAE Committees E-21 and P-6 had established the designations 70-90 for the shafts having a P dimension of 23.250 and 70L-90 for the shafts having a P dimension of 29.250, the Air Force and Navy in issuing AND10152, Shaft Ends - Propeller, revision 1, chose to show only the combination with the P dimension of 29.250 and to designate this as 70-90. In view of the previous correspondence, layouts, etc., which showed this combination as the 70L-90, the tables included herein do not agree with AND10152 in this regard, but retain the original designation from ARP 375. The above is noted to prevent future confusion concerning these particular shaft designations.

THIS REPORT WAS PREPARED BY

Committee E-21, Standard Components for Aircraft Engines
G. N. Cole, Chairman
Pratt & Whitney Aircraft

G. Carvelli Wright Aeronautical Corp.	F. H. Norriss Westinghouse Electric Corp. Aviation Gas Turbine Div.
C. C. DePew Ranger Aircraft Engines	E. M. Phillips General Electric Company Aircraft Gas Turbine Div.
C. J. McDowall Allison Division General Motors Corp.	F. J. Wiegand Wright Aeronautical Corp.

Committee P-6, Propeller Standards
R. P. Lambeck, Chairman
Hamilton Standard Propellers

J. H. Sheets Curtiss-Wright Corp. Propeller Division	H. C. Treseder Aeroproducts Division General Motors Corp.
--	---

APPROVED BY SAE AERONAUTICS COMMITTEE

Arthur Nutt, Chairman

Arthur E. Raymond Douglas Aircraft Co., Inc.	Erle Martin Hamilton Standard Propellers
J. B. Johnson USAF Air Materiel Command	C. E. Mines
R. D. Kelly United Air Lines, Inc.	Wright A. Parkins Pratt & Whitney Aircraft
W. C. Lawrence American Airlines System	

CONCENTRICITY NOTES:

WITH EITHER SHAFT MOUNTED ON DIA G AND REAR BEARING SURFACE, DIA H, KK (APPLIES TO OUTBOARD SHAFTS ONLY) AND OTHER BEARING SURFACES, SHALL BE CONCENTRIC WITHIN .001 FIR, THREAD T- PITCH DIA S SHALL BE CONCENTRIC WITHIN .005 FIR, AND DIA Z ON INVOLUTE SPLINES SHALL BE CONCENTRIC WITHIN .002 FIR.

WITH SHAFTS UNSUPPORTED BY PROPELLER BEARING, DIA KK ON OUTBOARD SHAFT AND DIA G ON INBOARD SHAFT SHALL BE CONCENTRIC WITHIN .048 FIR.

DIA H ON INBOARD SHAFT AND DIA HH SHALL BE CONCENTRIC WITHIN .007 FIR.

ENGINE MFR TO PROVIDE OIL SEAL BETWEEN SHAFTS, AND BETWEEN INBOARD SHAFT AND ENGINE NOSE

SURFACE MUST BE FREE FROM HOLES OR SLOTS.

SHOULDER NEED NOT BE INTEGRAL WITH SHAFT.

SURFACE MUST BE SQUARE WITH DIA KK WITHIN .002 FIR. SELF ALIGNING NON-INTEGRAL

SHOULDERS SHALL BE CHECKED WHEN HELD RIGIDLY IN PLACE. FOR INSPECTION PURPOSES

IT IS PERMISSIBLE TO ADJUST PARTS BY THE APPLICATION OF NORMAL

ALIGNING FORCES TO MEET THIS REQUIREMENT

TAPER NOTE:

SURFACE AT DIA G AND H NOT TO TAPER MORE THAN .0005 PER INCH OF LENGTH

ENGINE MANUFACTURER TO PLUG

SHAFT TO PREVENT LEAKAGE IN

EITHER DIRECTION UNDER 12 INCH HEAD

OF SAE NO.10 OIL. FRONT SURFACES

OF PLUG TO BE WITHIN THIS LENGTH

8 SLOTS EQUALLY SPACED CIRCUMFERENTIALLY WITHIN .010 OF TRUE LOCATION.

THREAD T NS, PITCH DIA S

SEE ALSO FIG.2

CENTER OPTIONAL WITH MFR

DRILL W THRU 8 HOLES

EQUALLY SPACED

CIRCUMFERENTIALLY WITHIN

.010 OF TRUE LOCATION

ENGINE PARTS, AND ENGINE MOUNTED ACCESSORIES OR SAE ACCESSORY CLEARANCE ENVELOPES IF AVAILABLE, NOT TO EXTEND OUTBOARD OF THIS LINE

SURFACE MUST BE SQUARE WITH DIA H OF INBOARD SHAFT WITHIN .015 FIR, AND FREE FROM HOLES OR SLOTS OTHER THAN THOSE SPECIFIED

ENCLOSED SPACE EXCEPT FOR THAT SHOWN ON FIG.3 RESERVED FOR ENGINE NOSE MFR, BOLTS, CAP SCREWS OR STUDS OPTIONAL WITH MFR

SURFACE MUST BE SQUARE WITH DIA H OF INBOARD SHAFT WITHIN .005 FIR, AND FREE FROM HOLES OR SLOTS

SEE FIG.3

DIM. ZZ

RELATIVE

RADIAL CLEAR-

ANCE BETWEEN

SHAFTS

0.16 TO .022

0.062 MIN

0.062 MAX R

0.500 MAX R

2.000 MAX R

PP SS

LL

EE

VV

DD

MM

HH

GG

0.072 MAX

ENVELOPE

RADIUS

PERMITTED

IN THESE

CORNERS

0.062 MIN

DO NOT PAINT

THESE

SURFACES

FF

CHAMFER 45°x.030

AA


QQ

* REFERENCE LINE FOR DIMENSIONS

L DIM. APPLIES ONLY WHEN C DIA IS LESS THAN G DIA. SEE ALSO FIG.2

FIG. 1

* DIMENSIONS, DIMENSION LETTERS AND NOTES ARE FOR BOTH SHAFTS AS APPLICABLE



SECTION AA

ARROWS INDICATE REQUIRED

DIRECTION OF ROTATION. SHAFT GEAR

RATIOS ARE TO BE IDENTICAL.

THREAD UNDERCUT OPTIONAL.

THREADING METHOD OPTIONAL

BREAK SHARP EDGES .016

UNLESS OTHERWISE SPECIFIED

ALLOWABLE TOLERANCE ON:-

LINEAR DIMENSIONS ±.01

ANGULAR DIMENSIONS ±2°

LET	TOLERANCE		70 — 90		70L — 90		80 — 100		80L — 100	
	OUT-BOARD SHAFT	IN-BOARD SHAFT	INVOLUTE SPLINES	INVOLUTE SPLINES	INVOLUTE SPLINES	INVOLUTE SPLINES	INVOLUTE SPLINES	INVOLUTE SPLINES	INVOLUTE SPLINES	INVOLUTE SPLINES
A	+0.000	-.005	5.539	7.554	5.539	7.554	6.411	8.667	6.411	8.667
B	MAX		5.294	7.294	5.294	7.294	6.151	8.313	6.151	8.313
C	+0.000	-.020	5.179	7.179	5.179	7.179	6.036	8.199	6.036	8.199
D	+0.000	-.0030	.2233	.2234	.2233	.2234	.2233	.2607	.2233	.2607
E	+0.000	-.004	5.120	7.120	5.120	7.120	5.995	8.120	5.995	8.120
F	+0.000	-.005	4.938	6.938	4.938	6.938	5.812	7.938	5.812	7.938
G	+0.000	-.002	5.156	7.156	5.156	7.156	6.011	8.174	6.011	8.174
H	+0.000	-.002	5.562	7.570	5.562	7.570	6.426	8.682	6.426	8.682
I	±.020	±.025	14.188	3.312	20.188	3.312	15.875	3.500	23.875	3.500
J	±.030	±.040	14.688	3.812	20.688	3.812	16.375	4.000	24.375	4.000
K	±.020	—	19.062	8.000	25.062	8.000	21.500	9.000	29.500	9.000
L	±.020	—	—	—	—	—	—	—	—	—
M	+0.000	+0.010	21.235	11.610	27.235	11.610	24.485	13.735	32.485	13.735
N	±.010	-.030	22.610	13.110	28.610	13.110	25.860	15.235	33.860	15.235
O	±.015	—	23.000	—	29.000	—	26.312	—	34.312	—
P	±.020	—	23.250	14.062	29.250	14.062	26.562	15.875	34.562	15.875
Q	±.020	—	21.125	11.500	27.125	11.500	24.375	13.625	32.375	13.625
R	MAX		2.030	3.030	2.030	3.030	2.030	3.030	2.030	3.030
R	MIN		1.125	1.125	1.125	1.125	1.125	1.125	1.125	1.125
r	+0.030	-.000	.062	.062	.062	.062	.062	.062	.062	.062
S	+0.0000	-.0030	—	—	—	—	—	—	—	—
S	+0.0000	-.0050	5.0418	—	5.0418	—	5.9168	—	5.9168	—
S	+0.0000	-.0080	—	7.0418	—	7.0418	—	8.0418	—	8.0418
T	—	—	5.125-8	7.125-8	5.125-8	7.125-8	6.000-8	8.125-8	6.000-8	8.125-8
U	±.030	—	.250	.250	.250	.250	.250	.250	.250	.250
V	APPROX	—	.068	.068	.068	.068	.068	.080	.068	.080
W	—	—	.2656	—	.2656	—	.2656	—	.2656	—
X	—	—	38	52	38	52	44	51	44	51
Y	—	—	7/16	7/16	7/16	7/16	7/16	7/16	7/16	6/12
Z	THEO	—	5.4286	7.4286	5.4286	7.4286	6.2857	8.5000	6.2857	8.5000
AA	±.030	—	14.125	—	14.125	—	15.938	—	15.938	—
BB	MAX	—	.094	—	.094	—	.094	—	.094	—
CC	±.020	—	6.000	—	6.000	—	6.000	—	6.000	—
DD	—	—	8.750	—	8.750	—	10.000	—	10.000	—
EE	MAX	—	1.000	—	1.000	—	1.000	—	1.000	—
FF	—	—	.312	—	.312	—	.375	—	.375	—
GG	MIN	—	11.375	—	11.375	—	13.000	—	13.000	—
HH	±.001	—	14.373	—	14.373	—	15.248	—	15.248	—
JJ	±.005	—	4.375	—	4.375	—	5.156	—	5.156	—
KK	±.0005	—	5.5908 (142MM BRG)	—	5.5908 (142MM BRG)	—	6.4567 (164MM BRG)	—	6.4567 (164MM BRG)	—
LL	MIN	—	4.000	—	4.000	—	4.000	—	4.000	—
MM	MAX	—	9.125	—	9.125	—	10.875	—	10.875	—
NN	MIN	—	6.250	—	6.250	—	7.125	—	7.125	—
PP	MIN	—	45°	—	45°	—	45°	—	45°	—
QQ	±.025	—	.938	—	.938	—	1.062	—	1.062	—
RR	—	—	—	6.750	—	6.750	—	7.750	—	7.750
SS	MIN	—	.500	—	.500	—	.500	—	.500	—
TT	±.030	—	3.000	—	3.000	—	3.000	—	3.000	—
UU	—	—	—	6.875	—	6.875	—	7.875	—	7.875
VV	MAX	—	14.250	—	14.250	—	15.125	—	15.125	—

INBOARD AXIAL DIMENSIONS ARE FROM THRUST NUT

M DIM. MAX LIMIT GIVES MIN FULL THREAD

* MINUS VALUE DEPENDS ON METHOD OF THREADING AND THD RUNOUT RELATION TO SHOULDER Q TO OBTAIN DIM. FOR FULL NUMBER OF PITCHES, WHEN DESIRED, DEDUCT BASIC M FROM BASIC N

M DIM. DOES NOT APPLY WHEN UNDERCUT IS USED

UNLESS OTHERWISE SPECIFIED

ALLOWABLE TOLERANCE ON:-
 LINEAR DIMENSIONS ±.01
 ANGULAR DIMENSIONS ±.2°

TABLE FOR FIG. 1 AND 2