

AEROSPACE MATERIAL SPECIFICATION

SAE AMS3373/2

REV. B

Issued 1981-11
Revised 1987-07
Reaffirmed 2001-01
Stabilized 2012-01

Superseding AMS3373/2A

Compound, Silicone Rubber, Insulating and Sealing
Oil and Reversion Resistant, Medium Viscosity, Room Temperature Cure

RATIONALE

This document has been determined to contain basic and stable technology which is not dynamic in nature.

STABILIZED NOTICE

This document has been declared "Stabilized" by SAE G-9, Aerospace Sealing Committee, and will no longer be subjected to periodic reviews for currency. Users are responsible for verifying references and continued suitability of technical requirements. Newer technology may exist.

SAENORM.COM : Click to view the full PDF of AMS3373-2B

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

Copyright © 2012 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)
Tel: +1 724-776-4970 (outside USA)
Fax: 724-776-0790
Email: CustomerService@sae.org
http://www.sae.org

SAE WEB ADDRESS:

**SAE values your input. To provide feedback
on this Technical Report, please visit
<http://www.sae.org/technical/standards/AMS3373/2B>**

1. SCOPE:

1.1 Form:

This specification covers an elastomeric silicone insulating and sealing compound, supplied as a two-component system. The compound may be either an addition- or a condensation-cure type.

1.2 Application:

Primarily for use as a resilient potting or encapsulant where medium viscosity, oil resistance, closed mold capability, and hydrolytic stability are desired.

2. APPLICABLE DOCUMENTS:

See AMS 3373.

3. TECHNICAL REQUIREMENTS:

3.1 Basic Specification:

The complete requirements for procuring the product described herein shall consist of this document and the latest issue of the basic specification, AMS 3373.

3.2 Material:

Shall be as specified in AMS 3373.

3.3 Properties:

The compound, mixed in accordance with manufacturer's instructions and cured as specified in the basic specification, shall conform to the following requirements, determined in accordance with test methods listed in AMS 3373 and herein: