

WRENCH PADS FOR FLUID FITTINGS MACHINED FROM ALTERNATE SHAPES OF MATERIAL

(THIS IS A DESIGN STANDARD, NOT TO BE USED AS A PART NUMBER)

SCOPE: THIS AEROSPACE STANDARD PROVIDES ALTERNATE DIMENSIONS AND SHAPES FOR FLUID FITTING BODIES MACHINED FROM BAR STOCK, OVERSIZE FORGINGS OR OTHER APPROVED ALTERNATE MATERIALS.

REFERENCES: FITTINGS PER MIL-F-18280, MIL-F-5509, AS1576 AND OTHER STANDARDS (SEE PAGE 8).

- REQUIREMENTS:**
1. REMOVE ALL BURRS AND BREAK ALL SHARP EDGES.
 2. ALL MACHINED SURFACES SHALL BE SMOOTH TO 125 MICROINCHES R_a MAX PER ANSI B46.1.
 3. ALL DIMENSIONS ARE IN INCHES. TOLERANCES UNLESS OTHERWISE SPECIFIED: DECIMALS $\pm .016$; ANGLES $\pm 5^\circ$.
 4. SLIGHT FLATS ON C DIA OF TRANSITION ZONE SHALL NOT BE CAUSE FOR REJECTION.
 5. ON ELBOWS AND TEES, 45° MILLING CUTS ARE TO BE MADE AS SHOWN TO REDUCE WEIGHT ON SIZE 8 AND LARGER STANDARD FITTINGS, SIZE 10 AND LARGER REDUCED ENVELOPE FITTINGS, AND SIZE 6 AND LARGER INTERNALLY THREADED FITTINGS.


TABLE 1 STANDARD FITTING DIMENSIONS

(SEE FIGURE 1)



TUBE SIZE	TUBE O.D.	A	B	C DIA	E $\pm .008$	H RAD	U RAD
-02	1/8	.312	-	.312	.156	.062	.062
-03	3/16	.375	-	.375	.188		
-04	1/4	.438	-	.438	.219		
-05	5/16	.500	-	.500	.250	.094	.094
-06	3/8	.562	-	.562	.281		
-08	1/2	.750	.221	.750	.375		
-10	5/8	.875	.257	.875	.438	.125	.125
-12	3/4	1.062	.312	1.062	.531		
-16	1	1.312	.386	1.312	.656		
-20	1-1/4	1.625	.478	1.625	.812		
-24	1-1/2	1.875	.551	1.875	.938		
-32	2	2.562	.754	2.562	1.281		.188

SAE Technical Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.




ELBOW, 45° BULKHEAD



ELBOW, 90°


.060/.120
RAD TYP
AT CORNERS

X-X




ELBOW, 90° BULKHEAD

X-X




TEE

X-X




TEE, BULKHEAD ON RUN

X-X



TEE, BULKHEAD ON SIDE

X-X



CROSS

X-X

TABLE II REDUCED ENVELOPE FITTING DIMENSIONS
(SEE FIGURE I)

TUBE SIZE	TUBE O.D.	A	B	C DIA	E ±.008	H RAD	U RAD
-04	1/4	.390	-	.350	.195	.062	.062
-06	3/8	.453	-	.453	.226	.094	.094
-08	1/2	.577	-	.577	.288		
-10	5/8	.702	.206	.702	.351		
-12	3/4	.890	.261	.890	.445		
-16	1	1.140	.334	1.140	.570	.125	.125
-20	1 1/4	1.290	.379	1.290	.645		

TABLE III
FLARED TO HOSE AND HOSE TO HOSE FITTINGS
(SEE FIGURE I)

DASH NO.	HOSE I.D.	TUBE O.D.	A	B	E ±.008
4	1/4	1/4	.438	-	.219
6	3/8	3/8	.562	-	.281
8	1/2	1/2	.750	.221	.375
10	5/8	5/8	.875	.257	.438
12	3/4	3/4	1.062	.312	.531
16	1	1	1.312	.386	.656
20	1-1/4	1-1/4	1.625	.478	.812
24	1-1/2	1-1/2	1.875	.551	.938

TABLE IV WELD FITTING DIMENSIONS
(SEE FIGURE II)

SIZE	TUBE O.D.	A	B	E ±.008
-04	1/4	.390	-	.195
-05	5/16	.453	-	.226
-06	3/8	.453	-	.226
-08	1/2	.577	-	.288
-10	5/8	.702	.206	.351
-12	3/4	.890	.261	.445
-16	1	1.140	.334	.570
-20	1 1/4	1.290	.379	.645

FIGURE II
WELD FITTINGS




FIGURE III
FITTINGS WITH INTERNAL SCREW THREADS




TABLE V INTERNAL SCREW THREAD FITTING DIMENSIONS
(SEE FIGURE III)

TUBE SIZE	TUBE O.D.	THREAD SIZE REF	A	B	C DIA	E ±.008
-04	1/4	.4375	.750	-	.688	.375
-05	5/16	.5000	.750	-	.750	.375
-06	3/8	.5625	.812	.239	.813	.406
-08	1/2	.7500	1.062	.313	1.062	.531
-10	5/8	.8750	1.188	.349	1.188	.594
-12	3/4	1.0625	1.438	.423	1.438	.719
-16	1	1.3125	1.688	.496	1.688	.844
-20	1 1/4	1.6250	2.000	.588	2.000	1.000

FIGURE IV
FITTINGS WITH INTERNAL PIPE THREADS

AS 1376








TABLE VI
INTERNAL PIPE THREAD FITTING DIMENSIONS
(SEE FIGURE IV)

DASH NUMBER *	PIPE THREAD SIZE REF.	A	B	C DIA	E ±.008	W
-1	1/8	.625	-	.578	.312	.063
-2	1/4	.813	-	.781	.406	
-3	3/8	.938	.276	.922	.469	.094
-4	1/2	1.188	.349	1.156	.594	
-6	3/4	1.375	.404	1.359	.688	.125
-8	1	1.750	.515	1.688	.875	
-10	1 1/4	2.156	.634	2.125	1.078	.156

*DASH NUMBER IS PIPE SIZE IN 1/8 INCHES

FIGURE V
MULTIPLE CONNECTOR AND UNIVERSAL FITTINGS
(BANJO FITTINGS)




TABLE VII MULTIPLE CONNECTOR AND
UNIVERSAL FITTING DIMENSIONS (SEE FIGURE V)

TUBE SIZE	TUBE O.D.	A	B	E ±.008
-04	1/4	.812	.238	.406
-05	5/16	.812	.238	.406
-06	3/8	1.000	.293	.500
-08	1/2	1.188	.348	.594
-10	5/8	1.375	.403	.688
-12	3/4	1.688	.494	.844
-16	1	2.062	.604	1.031