


SAE Executive Standards Committee Rules provide that: " This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

REV. A			FEDERAL SUPPLY CLASS
AS1486™	RATIONALE THIS TECHNICAL REPORT IS BEING STABILIZED BECAUSE IT COVERS TECHNOLOGY, PRODUCTS, OR PROCESSES WHICH ARE MATURE AND NOT LIKELY TO CHANGE IN THE FORESEEABLE FUTURE. STABILIZED NOTICE THIS DOCUMENT HAS BEEN DECLARED "STABILIZED" BY SAE G-3, AEROSPACE COUPLINGS, FITTINGS, HOSE, TUBING ASSEMBLIES COMMITTEE AND WILL NO LONGER BE SUBJECTED TO PERIODIC REVIEWS FOR CURRENCY. USERS ARE RESPONSIBLE FOR VERIFYING REFERENCES AND CONTINUED SUITABILITY OF TECHNICAL REQUIREMENTS. NEWER TECHNOLOGY MAY EXIST.		
		For more information on this standard, visit https://www.sae.org/standards/content/AS1486A/	THIRD ANGLE PROJECTION 
CUSTODIAN: G-3		PROCUREMENT SPECIFICATION:	
	AEROSPACE STANDARD HOSE ASSEMBLY, SEMI-RIGID, LOW PRESSURE, FLARELESS, POTABLE WATER, 45° TO 45°		AS1486™ REV. A

SAENORM.COM : Click to view the full PDF of as1486a

ISSUED 1979-04 REAFFIRMED 2013-01 STABILIZED 2024-01




FIGURE 1

TABLE I

HOSE ASSEMBLY NO. AND SIZE CODE	HOSE ASSY. SIZE (REF)	THREAD T PER MIL-S-8879 (REF)	A MAX	B GAGE DIA BASIC	C MIN DIA THRU 4	D		E MAX	F HEX ACROSS FLATS (REF)	HOSE I.D. MIN.	HOSE O.D.	
						MIN	MAX				MIN.	MAX.
AS1486E	1/4	.4375-20 UNJF-38	1.80	.2930	.174	.33	.39	.67	.56	.199	.34	.37
AS1486G	3/8	.5625-18 UNJF-38	2.16	.4120	.291	.42	.48	.82	.69	.310	.47	.50
AS1486H	1/2	.7500-16 UNJF-38	2.51	.5600	.409	.47	.53	1.03	.88	.396	.59	.62
AS1486J	5/8	.8750-14 UNJF-38	2.84	.6730	.495	.57	.63	1.18	1.00	.610	.79	.82
AS1486K	3/4	1.0625-12 UNJ-38	3.17	.8100	.646	.62	.67	1.47	1.25	.735	.91	.94
AS1486M	1	1.3125-12 UNJ-38	3.80	1.0620	.898	.76	.82	1.75	1.50	.985	1.16	1.19

TABLE II

HOSE ASSEMBLY LENGTH	AVAILABLE INCREMENTS	TOLERANCE
UNDER 18 INCHES	(NOT LESS THAN) .125 INCH	(PLUS OR MINUS) .125 INCH
18 TO 36 INCHES	(NOT LESS THAN) .250 INCH	(PLUS OR MINUS) .250 INCH
36 TO 50 INCHES	(NOT LESS THAN) .500 INCH	(PLUS OR MINUS) .500 INCH
OVER 50 INCHES	(NOT LESS THAN) 1.000 INCH	(PLUS OR MINUS) 1 PER CENT

TABLE III

HOSE SIZE (REF)	MAXIMUM WEIGHTS	
	HOSE LBS/INCH	STANDARD END FITTING (LBS) EACH
04	.003	
06	.005	
08	.008	
10	.010	
12	.014	
16	.018	




FIGURE II