

SAE Technical Board rules provide that: "All technical reports, including standards approved and practices recommended, are advisory only. Their use by anyone engaged in industry or trade is entirely voluntary. There is no agreement to adhere to any SAE standard or recommended practice, and no commitment to conform to be guided by any technical report. In formulating and approving technical reports, the Board and its Committees will not investigate or consider patents which may apply to the subject matter. Prospective users of the report are responsible for protecting themselves against liability for infringement of patents."

AS154




FIGURE 1

TABLE I

HOSE ASSEMBLY NO. AND SIZE CODE	HOSE ASSEMBLY SIZE REF	THREAD T PER MIL-G-8879 REF	I.D. MIN	A1 MAX	A2 MAX	B WITH DIA TYP	C DIA MAX WITHOUT SLEEVING	D		E HEX REF
								MIN	MAX	
AS154-04	1/4	.4375-20UMJF-3B	.212	1.24	2.08	.141	.69	.280	.451	.56
AS154-06	3/8	.5625-18UMJF-3B	.298	1.48	2.29	.250	.80	.370	.563	.69
AS154-08	1/2	.7500-16UMJF-3B	.391	1.69	2.61	.360	.97	.430	.645	.88
AS154-10	5/8	.8750-14UMJF-3B	.485	1.77	3.09	.455	1.11	.510	.666	1.00
AS154-12	3/4	1.0625-12UMJF-3B	.602	1.95	3.44	.568	1.38	.590	.720	1.25
AS154-16	1	1.3125-12UMJF-3B	.852			.760	1.66			1.50

TABLE II

HOSE ASSEMBLY LENGTH	AVAILABLE INCREMENTS	TOLERANCE
UNDER 18 INCHES	(NOT LESS THAN) 1/8 INCH	(PLUS OR MINUS) .125 INCH
18 TO 36 INCHES	(NOT LESS THAN) 1/4 INCH	(PLUS OR MINUS) .250 INCH
36 TO 50 INCHES	(NOT LESS THAN) 1/2 INCH	(PLUS OR MINUS) .500 INCH
OVER 50 INCHES	(NOT LESS THAN) 1 INCH	(PLUS OR MINUS) 1 PERCENT

TABLE III

SLEEVING CODE OR HOSE	TYPE OF SLEEVING OR HOSE	HOSE OR SLEEVE O.D. MAX HOSE SIZE						TEMPERATURE LIMIT
		1/4	3/8	1/2	5/8	3/4	1	
NONE	HOSE ONLY	.410	.540	.640	.745	.990		400°F
A	TUBULAR ABRASION (TFE)	.580	.678	.800	.850	1.184		400°F
B	SPIRAL ABRASION	.508	.612	.754	.847	1.080		275°F
C	FIRE SLEEVE	.875	.940	1.100	1.230	1.480		400°F
D	INTEGRAL ABRASION	.500	.625	.708	.832	1.112		400°F
E	SHRINK ABRASION (FEP)	.470	.600	.700	.805	1.050		400°F
F	SHRINK ABRASION (POLYOLEFIN)	.470	.610	.700	.815	1.050		275°F

PREPARED BY SAE COMMITTEE G-3, AEROSPACE FITTINGS, HOSE AND TUBING ASSEMBLIES

Society of Automotive Engineers, Inc.
400 COMMONWEALTH DRIVE, WARRENDALE, PA 15096

AEROSPACE STANDARD
HOSE ASSEMBLY, NON METALLIC-3000 PSI, TFE
FLARED, STRAIGHT TO 45°, LIGHTWEIGHT.

AS154

SH 1 OF 3

TABLE IV

HOSE SIZE (REF)	MAXIMUM WEIGHTS						STANDARD END FITTING (LBS) EACH	
	HOSE LBS/INCH	SPIRAL SLEEVE LBS/INCH	TFE SLEEVE LBS/INCH	FIRE SLEEVE LBS/INCH	FIRE SLEEVE CLAMPS (LBS) EACH		STRAIGHT	45°
04	.010	.001	.003	.010	.025		.063	.075
06	.015	.002	.003	.014	.025		.106	.121
08	.021	.003	.004	.016	.025		.181	.207
10	.028	.003	.004	.017	.026		.260	.306
12	.055	.004	.006	.022	.026		.438	.566
16								

TABLE V

HOSE SIZE	LENGTH (INCHES)
04	
06	2.00 ± .25
08	
10	2.50 ± .25
12	
16	3.00 ± .25




FIGURE 2

CONSTRUCTION AND PERFORMANCE: THESE HOSE ASSEMBLIES SHALL MEET THE CONSTRUCTION AND PERFORMANCE REQUIREMENTS OF AS 1339. FITTINGS SHALL BE PERMANENTLY ATTACHED TO THE HOSE.

RATED OPERATING CHARACTERISTICS: SEE AS 1339.

MATERIALS: HOSE AND FITTINGS-PER AS1339.
 TUBULAR ABRASION SLEEVE (TFE) - BLACK, EXTRUDED SEAMLESS TFE TUBING PER AS 1291.
 SPIRAL ABRASION SLEEVE - BLACK, NYLON COIL PER AS1294.
 FIRESLEEVE - ASBESTOS, IMPREGNATED WITH SILICON RUBBER PER AS1072 "SIL" CODED.
 INTEGRAL ABRASION SLEEVE - BLACK, INTEGRALLY BONDED SILICON/TFE COMPOSITE.
 SHRINK ABRASION SLEEVE (FEP) - TRANSLUCENT, SHRINKABLE FEP TUBING PER MIL-I-23053/11.
 SHRINK ABRASION SLEEVE (POLYOLEFIN) - BLACK, SHRINKABLE POLYOLEFIN TUBING PER AMS 3587 OR MIL-R-46846 TYPE 5.

MARKING: THE HOSE ASSEMBLIES SHALL HAVE ALL IDENTIFICATION MARKING AS REQUIRED BY AS1339, PERMANENTLY MARKED ON A PERMANENT STAINLESS STEEL BAND NOT MORE THAN 1.0 INCH WIDE OR ON THE END FITTING. THE CHARACTERS SHALL BE A MINIMUM OF 1/16 INCH HIGH. THE BAND SHALL BE SO DESIGNED AS TO REMAIN TIGHT ON THE HOSE TO PREVENT RELATIVE MOVEMENT AND RESULTANT CHAFING AND OF SUFFICIENT STRENGTH TO PREVENT REMOVAL BY HAND.

PREPARED BY SAE COMMITTEE G-3, AEROSPACE FITTINGS, HOSE AND TUBING ASSEMBLIES

AEROSPACE STANDARD

HOSE ASSEMBLY, NONMETALLIC-3000 PSI, TFE,
FLARED, STRAIGHT TO 45°, LIGHTWEIGHT,

AS154

SH 2 OF 3