

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

SAE AS154701
THRU AS155000

FEDERAL SUPPLY CLASS
5307

RATIONALE

AS154701 HAS BEEN REAFFIRMED TO COMPLY WITH THE SAE FIVE-YEAR REVIEW POLICY.

NOTICE

THIS DOCUMENT HAS BEEN TAKEN DIRECTLY FROM U.S. MILITARY SPECIFICATION AN154701 THRU AN155000 REV. 2, NOTICE 1 AND CONTAINS ONLY MINOR EDITORIAL AND FORMAT CHANGES REQUIRED TO BRING IT INTO CONFORMANCE WITH THE PUBLISHING REQUIREMENTS OF SAE TECHNICAL STANDARDS. THE INITIAL RELEASE OF THIS DOCUMENT IS INTENDED TO REPLACE AN154701 THRU AN155000 REV. 2, NOTICE 1. ANY PART NUMBERS ESTABLISHED BY THE ORIGINAL SPECIFICATION REMAIN UNCHANGED.


THE ORIGINAL MILITARY SPECIFICATION WAS ADOPTED AS AN SAE STANDARD UNDER THE PROVISIONS OF THE SAE TECHNICAL STANDARDS BOARD (TSB) RULES AND REGULATIONS (TSB 001) PERTAINING TO ACCELERATED ADOPTION OF GOVERNMENT SPECIFICATIONS AND STANDARDS. TSB RULES PROVIDE FOR (A) THE PUBLICATION OF PORTIONS OF UNREVISED GOVERNMENT SPECIFICATIONS AND STANDARDS WITHOUT CONSENSUS VOTING AT THE SAE COMMITTEE LEVEL, AND (B) THE USE OF THE EXISTING GOVERNMENT SPECIFICATION OR STANDARD FORMAT.

UNDER DEPARTMENT OF DEFENSE POLICIES AND PROCEDURES, ANY QUALIFICATION REQUIREMENTS AND ASSOCIATED QUALIFIED PRODUCTS LISTS ARE MANDATORY FOR DOD CONTRACTS. ANY REQUIREMENT RELATING TO QUALIFIED PRODUCTS LISTS (QPL'S) HAS NOT BEEN ADOPTED BY SAE AND IS NOT PART OF THIS SAE TECHNICAL DOCUMENT.

SAENORM.COM : Click to view the full PDF of as154701

SAE values your input. To provide feedback
on this Technical Report, please visit
<http://www.sae.org/technical/standards/AS154701>

THIRD ANGLE PROJECTION



CUSTODIAN: E-25

PROCUREMENT SPECIFICATION: NONE

SAE Aerospace
An SAE International Group

AEROSPACE STANDARD

STUD – STEPPED, 2 DIA ENGAGEMENT
.250-20 X .190-32

SAE AS154701
THRU AS155000
SHEET 1 OF 3


Copyright 2012 SAE International
All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)
Fax: 724-776-0790

Tel: +1 724-776-4970 (outside USA)
Email: CustomerService@sae.org

SAE WEB ADDRESS: <http://www.sae.org>

ISSUED 1999-04 REAFFIRMED 2012-11



UNDERSIZE AND OVERSIZE IDENTIFICATION		-.003	STANDARD	+0.003	+0.006	+0.009	+0.012
		(-3)	○	3	6	9	12
C	1/	.245-.250	.245-.250	.245-.250	.245-.250	.245-.259	.245-.259
PD BEFORE PLATING		.2183-.2193	.2183-.2223	.2243-.2253	.2273-.2283	.2303-.2313	.2333-.2343
PD AFTER PLATING		.2188-.2203	.2218-.2233	.2248-.2263	.2278-.2293	.2308-.2323	.2338-.2353
PD LEAD THREAD		.2125-.2145	.2165-.2175	.2185-.2205	.2215-.2235	.2245-.2265	.2275-.2295
L	B	PART NUMBER	PART NUMBER	PART NUMBER	PART NUMBER	PART NUMBER	PART NUMBER
1.000	.375	AN154719	AN154720	AN154721	AN154722	AN154723	AN154724
1.062	.438	AN154725	AN154726	AN154727	AN154728	AN154729	AN154730
1.125	.500	AN154731	AN154732	AN154733	AN154734	AN154735	AN154736
1.188	.500	AN154737	AN154738	AN154739	AN154740	AN154741	AN154742
1.250	.500	AN154743	AN154744	AN154745	AN154746	AN154747	AN154748
1.312	.500	AN154749	AN154750	AN154751	AN154752	AN154753	AN154754
1.375	.500	AN154755	AN154756	AN154757	AN154758	AN154759	AN154760
1.438	.500	AN154761	AN154762	AN154763	AN154764	AN154765	AN154766
1.500	.500	AN154767	AN154768	AN154769	AN154770	AN154771	AN154772
1.562	.500	AN154773	AN154774	AN154775	AN154776	AN154777	AN154778
1.625	.500	AN154779	AN154780	AN154781	AN154782	AN154783	AN154784
1.688	.500	AN154785	AN154786	AN154787	AN154788	AN154789	AN154790
1.750	.500	AN154791	AN154792	AN154793	AN154794	AN154795	AN154796
1.812	.500	AN154797	AN154798	AN154799	AN154800	AN154801	AN154802

1/ PITCH DIAMETERS OF BOTH THREADED ENDS SHALL BE CONCENTRIC WITHIN .006 FIR.

NOTES:

1. MATERIAL: STEEL AMS 6322 (AMS 6320 MATERIAL MAY ALSO BE USED FOR THIS PART UNTIL JANUARY 1, 1957).