


REV.
C

AS1716

FEDERAL SUPPLY CLASS
4730

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.



CUSTODIAN: SAE G-3/G-3A


PROCUREMENT SPECIFICATION: /3/ AS1710

SAE The Engineering Society
For Advancing Mobility
Land Sea Air and Space®
INTERNATIONAL
400 Commonwealth Drive, Warrendale, PA 15096-0001

AEROSPACE STANDARD

FERRULE, COUPLING, FLEXIBLE, VARIABLE
CAVITY, THREADED, FERRULE TUBE END

THIRD ANGLE PROJECTION



AS1716
SHEET 1 OF 3

**REV.
C**

AS1716	REV. C
--------	-----------

TABLE 1 - FERRULE DIMENSIONS AND WEIGHTS

BASIC NO. AS1716	(TUBE O.D.)	A /11/	B + .000/- .005	C	D /12/	E ± .005	F + .005/- .000	G	H PLCS	J PLCS	K /13/	L	LB/EA MAX
08	.500	.686	.625	.592	.504	.483	.035	.555	4	4	.010	.045/.035	.006
10	.625	.811	.750	.717	.630	.609	.035	.555	4	4	.010	.045/.035	.008
12	.750	.989	.891	.859	.755	.734	.040	.555	4	4	.010	.045/.035	.011
16	1.000	1.265	1.142	1.109	1.005	.984	.040	.579	4	4	.010	.045/.035	.014
20	1.250	1.515	1.392	1.359	1.256	1.235	.040	.579	4	4	.010	.045/.035	.017
24	1.500	1.785	1.642	1.600	1.506	1.480	.040	.685	5	5	.010	.045/.035	.024
28	1.750	2.035	1.892	1.850	1.756	1.730	.040	.685	5	5	.010	.045/.035	.029
32	2.000	2.308	2.145	2.100	2.006	1.980	.060	.685	5	5	.010	.045/.035	.035
36	2.250	2.558	2.395	2.350	2.257	2.220	.060	.692	5	5	.010	.045/.035	.039
40	2.500	2.808	2.645	2.600	2.507	2.465	.060	.692	5	5	.010	.065/.055	.042
44	2.750	3.058	2.895	2.850	2.757	2.715	.060	.692	5	5	.010	.065/.055	.049
48	3.000	3.308	3.145	3.100	3.007	2.965	.060	.692	5	5	.010	.065/.055	.052
56	3.500	3.820	3.645	3.600	3.509	3.467	.060	.722	5	5	.016	.065/.055	.063
64	4.000	4.329	4.154	4.110	4.009	3.975	.060	.722	5	5	.016	.065/.055	.069
72	4.500	4.830	4.655	4.610	4.509	4.475	.060	.770	6	6	.024	.090/.080	.090
80	5.000	5.330	5.155	5.110	5.009	4.975	.075	.966	8	8	.024	.090/.080	.114
88	5.500	5.830	5.655	5.610	5.511	5.475	.075	.966	8	8	.024	.090/.080	.124