

SAE Executive Standards Committee Rules provide that: " This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

REV. A
AS1868™

FEDERAL SUPPLY CLASS
4720

RATIONALE

THIS TECHNICAL REPORT IS BEING STABILIZED BECAUSE IT COVERS TECHNOLOGY, PRODUCTS, OR PROCESSES WHICH ARE MATURE AND NOT LIKELY TO CHANGE IN THE FORESEEABLE FUTURE.


STABILIZED NOTICE

THIS DOCUMENT HAS BEEN DECLARED "STABILIZED" BY SAE G-3, AEROSPACE COUPLINGS, FITTINGS, HOSE, TUBING ASSEMBLIES COMMITTEE AND WILL NO LONGER BE SUBJECTED TO PERIODIC REVIEWS FOR CURRENCY. USERS ARE RESPONSIBLE FOR VERIFYING REFERENCES AND CONTINUED SUITABILITY OF TECHNICAL REQUIREMENTS. NEWER TECHNOLOGY MAY EXIST.

SAENORM.COM : Click to view the full PDF of as1868a

For more information on this standard, visit
<https://www.sae.org/standards/content/AS1868A/>

THIRD ANGLE PROJECTION



CUSTODIAN: G-3/G-3D

PROCUREMENT SPECIFICATION: MIL-H-8795



AEROSPACE STANDARD

HOSE ASSEMBLY, RUBBER, FLARELESS,
FIELD ATTACHABLE FITTING, 90° TO 90°

AS1868™

REV.
A

Copyright © 2024 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, or used for text and data mining, AI training, or similar technologies, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)
Fax: 724-776-0790

Tel: +1 724-776-4970 (outside USA)
Email: CustomerService@sae.org

SAE WEB ADDRESS: <http://www.sae.org>

ISSUED 1987-04 REAFFIRMED 2013-01 STABILIZED 2024-09




FIGURE 1

TABLE 1

HOSE SIZE DASH NUMBER	HOSE ASSEMBLY SIZE REF.	THREAD T PER MIL-S-8879 REF.	HOSE I.D. MIN.	HOSE O.D. MAX.	A MAX.	B GAGE DIA. BASIC	E /1/ MAX.	F HEX REF.
-03	.125	.3750-24 UNJF-3B	.125	.476		.2340	.627	.50
-04	.188	.4375-20 UNJF-3B	.188	.539	1.86	.2930	.690	.56
-05	.250	.5000-20 UNJF-3B	.250	.601	2.08	.3500	.752	.62
-06	.313	.5625-18 UNJF-3B	.313	.695	2.24	.4120	.877	.69
-08	.406	.7500-16 UNJF-3B	.406	.789	2.66	.5600	1.016	.88
-10	.500	.8750-14 UNJF-3B	.500	.945	2.94	.6730	1.235	1.00
-12	.625	1.0625-12 UNJ-3B	.625	1.101	3.86	.8100	1.360	1.25
-16	.875	1.3125-12 UNJ-3B	.875	1.265	3.67	1.0620	1.546	1.50
-20	1.125	1.6250-12 UNJ-3B	1.125	1.531	3.88	1.3160	1.921	1.81
-24	1.375	1.8750-12 UNJ-3B	1.375	1.781		1.5650	2.124	2.12

TABLE 2

SIZE CODE	D		C MIN. DIA. THRU
	MIN.	MAX.	
-03			.073
-04	.73	.85	.123
-05	.88	1.00	.170
-06	.99	1.11	.232
-08	1.03	1.15	.350
-10	1.25	1.37	.450
-12	1.89	2.01	.575
-16	2.18	2.30	.781
-20	2.22	2.34	1.015
-24			1.250

TABLE 3

HOSE ASSEMBLY LENGTH	AVAILABLE INCREMENTS	TOLERANCE
UNDER 18 INCHES	(NOT LESS THAN) .125 INCH	(PLUS OR MINUS) .125 INCH
18 TO 36 INCHES	(NOT LESS THAN) .250 INCH	(PLUS OR MINUS) .250 INCH
36 TO 50 INCHES	(NOT LESS THAN) .500 INCH	(PLUS OR MINUS) .500 INCH
OVER 50 INCHES	(NOT LESS THAN) 1.000 INCH	(PLUS OR MINUS) 1 PERCENT