

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.


REV. A			FEDERAL SUPPLY CLASS 4730	
	AS21913			
NOTICE THIS DOCUMENT HAS BEEN TAKEN DIRECTLY FROM U.S. MILITARY SPECIFICATION MS21913E, NOTICE 1 AND CONTAINS ONLY MINOR EDITORIAL AND FORMAT CHANGES REQUIRED TO BRING IT INTO CONFORMANCE WITH THE PUBLISHING REQUIREMENTS OF SAE TECHNICAL STANDARDS. THE INITIAL RELEASE OF THIS DOCUMENT IS INTENDED TO REPLACE MS21913E, NOTICE 1. ANY PART NUMBERS ESTABLISHED BY THE ORIGINAL SPECIFICATION REMAIN UNCHANGED. THE ORIGINAL MILITARY SPECIFICATION WAS ADOPTED AS AN SAE STANDARD UNDER THE PROVISIONS OF THE SAE TECHNICAL STANDARDS BOARD (TSB) RULES AND REGULATIONS (TSB 001) PERTAINING TO ACCELERATED ADOPTION OF GOVERNMENT SPECIFICATIONS AND STANDARDS. TSB RULES PROVIDE FOR (A) THE PUBLICATION OF PORTIONS OF UNREVISED GOVERNMENT SPECIFICATIONS AND STANDARDS WITHOUT CONSENSUS VOTING AT THE SAE COMMITTEE LEVEL, AND (B) THE USE OF THE EXISTING GOVERNMENT SPECIFICATION OR STANDARD FORMAT. UNDER DEPARTMENT OF DEFENSE POLICIES AND PROCEDURES, ANY QUALIFICATION REQUIREMENTS AND ASSOCIATED QUALIFIED PRODUCTS LISTS ARE MANDATORY FOR DOD CONTRACTS. ANY REQUIREMENT RELATING TO QUALIFIED PRODUCTS LISTS (QPL'S) HAS NOT BEEN ADOPTED BY SAE AND IS NOT PART OF THIS SAE TECHNICAL DOCUMENT.				
CUSTODIAN: SAE G-3/G-3B		PROCUREMENT SPECIFICATION: AS18280		
 SAE The Engineering Society For Advancing Mobility Land Sea Air and Space® 400 Commonwealth Drive, Warrendale, PA 15096-0001		AEROSPACE STANDARD PLUG, FLARELESS TUBE		AS21913 SHEET 1 OF 3
				REV. A

SAENORM.COM : Click to view the full PDF of as21913a

ISSUED 1998-03 REVISED 2001-03

REV.
A

AS21913



DASH NO.	TUBE OD	THREAD T MIL-S-8879	A -3/64 +0	B	C	WT LB MAX		
						STEEL	AL ALLOY	TI ALLOY
-2	1/8	.3125-24UNJF-3A	3/8	9/16	.438	.014	.005	.008
-3	3/16	.3750-24UNJF-3A	7/16	39/64	.500	.017	.006	.009
-4	1/4	.4375-20UNJF-3A	1/2	41/64	.563	.020	.007	.011
-5	5/16	.5000-20UNJF-3A	1/2	43/64	.625	.026	.010	.015
-6	3/8	.5625-18UNJF-3A	9/16	23/32	.688	.033	.012	.019
-8	1/2	.7500-16UNJF-3A	5/8	27/32	.812	.067	.024	.038
-10	5/8	.8750-14UNJF-3A	11/16	63/64	.938	.107	.038	.061
-12	3/4	1.0625-12UNJ-3A	1-1/16	1-1/32	1.125	.174	.062	.100
-16	1	1.3125-12UNJ-3A	1-1/8	1-1/16	1.375	.245	.091	.141
-20	1-1/4	1.6250-12UNJ-3A	5/8	1-3/32	1.688	.390	.150	.225
-24(b)	1-1/2	1.8750-12UNJ-3A	23/32	1-3/32	2.000	.540	.192	.311
-32(b)	2	2.5000-12UNJ-3A	11/16	1-3/32	2.625	.965	.354	.556

(b) DRILL POINT NOT PERMITTED ON -24 AND -32 SIZES, HOLE SHALL BE FLAT BOTTOMED IN ACCORDANCE WITH DIMENSION A.

FOR DESIGN FEATURE PURPOSES, THIS STANDARD TAKES PRECEDENCE OVER PROCUREMENT DOCUMENTS REFERENCED HEREIN. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BID.