

SAE-AS27641

ADOPTION NOTICE

SAE-AS27641, "Bearings, Ball, Airframe, Anti-friction, Intermediate Duty," was adopted on 23 July 1998, for use by the Department of Defense (DoD). Proposed changes by DoD activities must be submitted to the DoD Adopting Activity: Commander, Naval Air Warfare Center Aircraft Division, Code 414100B120-3, Highway 547, Lakehurst, NJ 08733-5100. DoD activities may obtain copies of this standard from the Standardization Document Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111-5094. The private sector and other government agencies may purchase copies from SAE, 400 Commonwealth Drive, Warrendale, PA 15096-0001.

SAE-AS27641 should be used instead of MS27641F, which was canceled on 23 July 1998.

Custodians:

Army - AV

Navy - AS

Air Force - 99

Adopting Activity

Navy - AS

(Project 3110-1085)

Review Activities:

Army - AR, AT, MI

Navy - SH

Air Force - 84

DLA - GS

AMSC N/A

FSC 3110

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Submitted for recognition as an American National Standard

Form Approved
OMB No. 0704-0188

AS27641

NOTICE

THIS DOCUMENT HAS BEEN TAKEN DIRECTLY FROM U.S. MILITARY SPECIFICATION MS27641F AND CONTAINS ONLY MINOR EDITORIAL AND FORMAT CHANGES REQUIRED TO BRING IT INTO CONFORMANCE WITH THE PUBLISHING REQUIREMENTS OF SAE TECHNICAL STANDARDS. THE INITIAL RELEASE OF THIS DOCUMENT IS INTENDED TO REPLACE MS27641F. ANY PART NUMBERS ESTABLISHED BY THE ORIGINAL SPECIFICATION REMAIN UNCHANGED.

THE ORIGINAL MILITARY SPECIFICATION WAS ADOPTED AS AN SAE STANDARD UNDER THE PROVISIONS OF THE SAE TECHNICAL STANDARDS BOARD (TSB) RULES AND REGULATIONS (TSB 001) PERTAINING TO ACCELERATED ADOPTION OF GOVERNMENT SPECIFICATIONS AND STANDARDS. TSB RULES PROVIDE FOR (A) THE PUBLICATION OF PORTIONS OF UNREVISED GOVERNMENT SPECIFICATIONS AND STANDARDS WITHOUT CONSENSUS VOTING AT THE SAE COMMITTEE LEVEL, AND (B) THE USE OF THE EXISTING GOVERNMENT SPECIFICATION OR STANDARD FORMAT.

ANY MATERIAL RELATING TO QUALIFIED PRODUCT LISTS HAS NOT BEEN ADOPTED BY SAE. THIS MATERIAL WAS PART OF THE ORIGINAL MILITARY SPECIFICATION AND IS REPRINTED HERE FOR HISTORIC REFERENCE ONLY.

SAENORM.COM : Click to view the full PDF of as27641

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user." SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

ISSUED 1998-04

PREPARED BY AIRFRAME CONTROL BEARINGS GROUP (ACBG)



AEROSPACE STANDARD

BEARING, BALL, AIRFRAME,
ANTI-FRICTION, INTERMEDIATE DUTY

AS27641
SHEET 1 OF 3

Copyright 1998 Society of Automotive Engineers, Inc.
All rights reserved.

Printed in the U.S.A.

QUESTIONS REGARDING THIS DOCUMENT:
TO PLACE A DOCUMENT ORDER:

(724) 772-8510
(724) 776-4970

FAX: (724) 776-0243
FAX Distributed under license from the IHS Archive

SAE WEB ADDRESS: <http://www.sae.org>

AS27641




TABLE I. DIMENSIONS AND LOADS

MS DASH NO.	øB	øD	W	H	øA	E	C	RADIAL LIMIT LOAD RATING LBS	THRUST LIMIT LOAD RATING LBS	5/ RADIAL LOAD RATING (LBS.) FOR AVERAGE LIFE OF 10,000 COMPLETE 90° CYCLES		WEIGHT POUNDS (APPROX)	MAXIMUM STARTING TORQUE (INCH-OZ)
	BORE	OUTSIDE DIAMETER	WIDTH INNER	WIDTH OUTER	SHOULDER DIAMETER	4/ INNER RING CORNER CHAMFER	3/ OUTER RING CORNER CHAMFER						
	2/ 1/ 2/	1/ 2/	1/ 1/	1/ 1/	INNER RING (APPROX)	+015 -000	+015 -000						
	+0.000 -0.005	+0.000 -0.005	+0.000 -0.005	+0.000 -0.005									
-3	.1900	.6250	.297	.234	.297	.005	.016	1560	700	1500	1250	.01	1.0
-4	.2500	.7500	.281	.219	.380			1880	900	1690	1450	.02	1.5
-5	.3125	.8125	.297	.234	.415			2190	1000	1820	1600	.02	1.5
-6	.3750	.8750	.313	.250	.495			2500	1100	1920	1710	.03	2.0
-8	.5000	1.1250	.375	.313	.616			3910	1700	2870	2550	.05	2.5
-10	.6250	1.3750	.406	.344	.768	.015	.032	6700	3000	4980	4360	.08	3.0
-12	.7500	1.6250	.437	.375	.919			8790	3900	5980	5320	.13	3.0
-16	1.0000	2.0000	.500	.438	1.241			11900	5200	7070	6400	.22	4.0
-20	1.2500	2.2500	.500	.438	1.478			13800	6100	7400	6810	.26	5.0

1/ DIMENSIONS TO BE MET AFTER PLATING.

2/ OUT-OF-ROUND TOLERANCES: BORE: +.0002, -.0007; OUTER DIA: +.0005, -.0010.

3/ 45° CHAMFER OR A RADIUS GIVING APPROXIMATELY THE SAME GRIP FOR STAKING THE BEARING IN THE HOUSING WILL BE ACCEPTABLE.

4/ 45° CHAMFER OR A RADIUS GIVING APPROXIMATELY THE SAME FILLET CLEARANCE WILL BE ACCEPTABLE.

5/ CASE I = LOAD FIXED WITH RESPECT TO OUTER RING.

CASE II = LOAD FIXED WITH RESPECT TO INNER RING.

6/ THESE RATINGS ARE FOR OPERATION UP TO 250°F. FOR OPERATION UP TO 350°F, THE RATINGS SHALL BE REDUCED BY 20%.

(F) DENOTES CHANGES