

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.


REV. C	FEDERAL SUPPLY CLASS 5310	
	RATIONALE THIS STANDARD IS TO BE CANCELLED AND SUPERSEDED BY AS6146. CANCELLATION NOTICE THIS TECHNICAL REPORT HAS BEEN DECLARED "CANCELLED" AS OF SEPTEMBER, 2020 AND HAS BEEN SUPERSEDED BY AS6146. BY THIS ACTION, THIS DOCUMENT WILL REMAIN LISTED IN THE RESPECTIVE INDEX, IF APPLICABLE. CANCELLED TECHNICAL REPORTS ARE AVAILABLE FROM SAE. UNLESS OTHERWISE SPECIFIED, PART INVENTORY MANUFACTURED TO PREVIOUS REVISIONS OF THE APPLICABLE DRAWING OR SPECIFICATION MAY BE PROCURED AND USED UNTIL STOCK IS DEPLETED.	
AS3067™	SAENORM.COM : Click to view the full PDF of as3067c	
For more information on this standard, visit https://www.sae.org/standards/content/AS3067C/		THIRD ANGLE PROJECTION 
CUSTODIAN: E-25		PROCUREMENT SPECIFICATION: NONE
	AEROSPACE STANDARD NUT, SELF-LOCKING, DOUBLE HEXAGON, REDUCED ENVELOPE, AS7251	AS3067™ REV. C

TABLE 1B

IDENTIFICATION NUMBER	F Inch	F (mm)	G Inch	G (mm)	L Inch	L (mm)	M Inch	M (mm)
AS3067-08	.045-.060	1.15-1.52	.164-.194	4.17- 4.92	.164-.184	4.17- 4.67	.229	5.81
AS3067-09	.045-.060	1.15-1.52	.190-.220	4.83- 5.58	.190-.210	4.83- 5.33	.262	6.65
AS3067-10	.045-.060	1.15-1.52	.250-.280	6.35- 7.11	.250-.270	6.35- 6.85	.326	8.28
AS3067-11	.060-.075	1.53-1.90	.312-.342	7.93- 8.68	.312-.332	7.93- 8.43	.392	9.95
AS3067-12	.070-.090	1.78-2.28	.375-.405	9.53-10.28	.375-.395	9.53-10.03	.458	11.63
AS3067-13	.080-.100	2.04-2.54	.438-.468	11.13-11.88	.438-.458	11.13-11.63	.588	14.93
AS3067-14	.100-.120	2.54-3.04	.500-.535	12.70-13.58	.500-.520	12.70-13.20	.654	16.61
AS3067-15	.110-.130	2.80-3.30	.562-.597	14.28-15.16	.562-.582	14.28-14.78	.720	18.28

TABLE 1C

IDENTIFICATION NUMBER	N Inch	N (mm)	P Inch	P (mm)	S Inch	S (mm)	Y Inch	Y (mm)	Z Inch	Z (mm)	HARDNESS ROCKWELL	APPROX MASS lb/100	APPROX MASS kg/100
AS3067-08	.005-.020	0.13-0.50	.090	2.28	.135-.175	3.43- 4.44	.004	0.10	.005	0.12	C39-46	.17	0.077
AS3067-09	.005-.030	0.13-0.76	.095	2.41	.150-.190	3.81- 4.82	.004	0.10	.006	0.15	C39-46	.22	0.100
AS3067-10	.005-.030	0.13-0.76	.110	2.79	.190-.235	4.83- 5.96	.005	0.12	.007	0.17	C38-46	.41	0.186
AS3067-11	.005-.035	0.13-0.88	.130	3.30	.220-.270	5.59- 6.85	.005	0.12	.008	0.20	C38-46	.70	0.318
AS3067-12	.005-.040	0.13-1.01	.150	3.81	.270-.330	6.86- 8.38	.005	0.12	.009	0.22	C38-46	.99	0.449
AS3067-13	.005-.040	0.13-1.01	.150	3.81	.270-.330	6.86- 8.38	.006	0.15	.010	0.25	C38-46	1.51	0.685
AS3067-14	.005-.060	0.13-1.52	.180	4.57	.335-.405	8.51-10.28	.006	0.15	.012	0.30	C38-46	2.35	1.066
AS3067-15	.005-.070	.013-1.77	.195	4.95	.380-.460	9.66-11.68	.007	0.17	.014	0.35	C38-46	3.67	1.665

TABLE 1D

IDENTIFICATION NUMBER	VENDOR NUMBER
AS3067-08	LH11973-86
AS3067-09	LH11973-3
AS3067-10	LH11973-4
AS3067-11	LH11973-5
AS3067-12	LH11973-6
AS3067-13	LH11973-7
AS3067-14	LH11973-8
AS3067-15	LH11973-9



AEROSPACE STANDARD

NUT, SELF-LOCKING, DOUBLE HEXAGON,
REDUCED ENVELOPE, AS7251

AS3067™
SHEET 2 OF 3

**REV.
C**