


SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

REV. E	FEDERAL SUPPLY CLASS 4730	
	RATIONALE THIS NONCURRENT STANDARD HAS BEEN STABILIZED. STABILIZED NOTICE THIS DOCUMENT HAS BEEN DECLARED "STABILIZED" BY THE SAE E-25 GENERAL STANDARDS FOR AEROSPACE AND PROPULSION SYSTEMS COMMITTEE AND WILL NO LONGER BE SUBJECTED TO PERIODIC REVIEWS FOR CURRENCY. USERS ARE RESPONSIBLE FOR VERIFYING REFERENCES AND CONTINUED SUITABILITY OF TECHNICAL REQUIREMENTS. NEWER TECHNOLOGY MAY EXIST.	
AS3075	SAENORM.COM : Click to view the full PDF of as3075e	
CUSTODIAN: E-25		THIRD ANGLE PROJECTION 
SAE values your input. To provide feedback on this Technical Report, please visit http://www.sae.org/technical/standards/AS3075E		ISSUED 1974-04 NONCURRENT 1998-02 REAF. NONC. 2003-10 REVISED 2007-02 STABILIZED 2014-12
AEROSPACE STANDARD GASKET - 37° FLARED TUBE FITTING, NICKEL, AMS5553		AS3075
		REV. E




FIGURE 1

INACTIVE - SEE NOTE 9



AEROSPACE STANDARD

GASKET - 37° FLARED TUBE FITTING,
NICKEL, AMS5553

AS3075
SHEET 1 OF 3

REV.
E

TABLE 1

AS IDENT NUMBER	NOM TUBE OD in	NOM TUBE OD (mm)	A DIA in	A DIA (mm)	B in	B (mm)	C DIA in	C DIA (mm)	T in	T (mm)	APPROX MASS lb PER 100	APPROX MASS kg PER 100	VENDOR NUMBER
AS3075-02	0.125	3.18	0.103-0.118	2.62-2.99	0.045-0.060	1.15-1.52	0.245-0.250	6.23-6.35	0.004-0.006	0.102-0.152	0.017	0.008	VSF1015N2B
AS3075-03	0.188	4.78	0.166-0.181	4.22-4.59	0.045-0.060	1.15-1.52	0.307-0.312	7.80-7.92	0.004-0.006	0.102-0.152	0.021	0.010	VSF1015N3B
AS3075-04	0.250	6.35	0.213-0.228	5.42-5.79	0.060-0.075	1.53-1.90	0.359-0.364	9.12-9.24	0.004-0.006	0.102-0.152	0.028	0.013	VSF1015N4B
AS3075-05	0.312	7.92	0.275-0.290	6.99-7.36	0.060-0.075	1.53-1.90	0.421-0.426	10.70-10.82	0.004-0.006	0.102-0.152	0.035	0.016	VSF1015N5B
AS3075-06	0.375	9.52	0.338-0.353	8.59-8.96	0.060-0.075	1.53-1.90	0.476-0.481	12.10-12.21	0.004-0.006	0.102-0.152	0.040	0.018	VSF1015N6B
AS3075-07	0.438	11.13	0.401-0.416	10.19-10.56	0.060-0.075	1.53-1.90	0.539-0.544	13.70-13.81	0.004-0.006	0.102-0.152	0.088	0.040	VSF1015N7B
AS3075-08	0.500	12.70	0.446-0.461	11.33-11.70	0.080-0.095	2.04-2.41	0.654-0.659	16.62-16.73	0.009-0.011	0.229-0.279	0.151	0.069	VSF1015N8B
AS3075-09	0.562	14.27	0.529-0.544	13.44-13.81	0.080-0.095	2.04-2.41	0.722-0.727	18.34-18.46	0.009-0.011	0.229-0.279	0.171	0.078	VSF1015N9B
AS3075-10	0.625	15.88	0.562-0.577	14.28-14.65	0.090-0.105	2.29-2.66	0.767-0.772	19.49-19.60	0.009-0.011	0.229-0.279	0.181	0.082	VSF1015N10B
AS3075-11	0.688	17.48	0.625-0.640	15.88-16.25	0.090-0.105	2.29-2.66	0.882-0.887	22.41-22.52	0.009-0.011	0.229-0.279	0.229	0.104	VSF1015N11B
AS3075-12	0.750	19.05	0.687-0.702	17.45-17.83	0.090-0.105	2.29-2.66	0.938-0.943	23.83-23.95	0.009-0.011	0.229-0.279	0.283	0.128	VSF1015N12B
AS3075-14	0.875	22.22	0.826-0.841	20.99-21.36	0.090-0.105	2.29-2.66	1.070-1.075	27.18-27.30	0.009-0.011	0.229-0.279	0.303	0.138	VSF1015N14B
AS3075-16	1.000	25.40	0.936-0.951	23.78-24.15	0.110-0.125	2.80-3.17	1.188-1.193	30.18-30.30	0.009-0.011	0.229-0.279	0.362	0.164	VSF1015N16B
AS3075-18	1.125	28.58	1.046-1.061	26.57-26.94	0.060-0.075	1.53-1.90	1.375-1.380	34.93-35.05	0.009-0.011	0.229-0.279	0.457	0.207	VSF1015N18B
AS3075-20	1.250	31.75	1.175-1.190	29.85-30.22	0.110-0.125	2.80-3.17	1.501-1.506	38.13-38.25	0.009-0.011	0.229-0.279	0.546	0.248	VSF1015N20B
AS3075-24	1.500	38.10	1.410-1.425	35.82-36.19	0.110-0.125	2.80-3.17	1.750-1.755	44.45-44.57	0.009-0.011	0.229-0.279	0.662	0.301	VSF1015N24B
AS3075-28	1.750	44.45	1.680-1.695	42.68-43.05	0.110-0.125	2.80-3.17	2.125-2.130	53.98-54.10	0.009-0.011	0.229-0.279	0.982	0.446	VSF1015N28B
AS3075-32	2.000	50.80	1.913-1.928	48.60-48.97	0.110-0.125	2.80-3.17	2.375-2.380	60.33-60.45	0.009-0.011	0.229-0.279	1.068	0.485	VSF1015N32B



AEROSPACE STANDARD

GASKET - 37° FLARED TUBE FITTING,
NICKEL, AMS5553AS3075
SHEET 2 OF 3REV.
E