

SAE Executive Standards Committee Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

REV.
A


AS3098™

FEDERAL SUPPLY CLASS
5305

RATIONALE


REVISE THREAD TO AS8879, REVISE LEAD THREAD CHAMFER, ADD RUNOUT REQUIREMENT TO BEARING FACE DIAMETER, ADD EDGE DISTANCE EXCEPTION ON HEAD MARKING, ADD SURFACE TEXTURE REQUIREMENT TO WRENCH FLATS, ADD AS3062 FOR THREAD RUNOUT TO FIGURE 1, UPDATE FPI REQUIREMENTS, UPDATE SURFACE TEXTURE NOTE AND REFERENCES, DELETE METRIC DIMENSIONS, ADD NOTE FOR THE DISPOSITION OF EXISTING INVENTORY, FIGURE 1 REDRAWN, GENERAL EDITORIAL UPDATES.

AS3098A HAS BEEN REAFFIRMED TO COMPLY WITH THE SAE FIVE-YEAR REVIEW POLICY.



For more information on this standard, visit
<https://www.sae.org/standards/content/AS3098A/>

THIRD ANGLE PROJECTION



CUSTODIAN: E-25

PROCUREMENT SPECIFICATION: AS7477



AEROSPACE STANDARD

(R) SCREW, MACHINE - HEXAGON HEAD, PD SHANK,
CRES AMS5731 (UNS S66286), .164-36 UNJF-3A

AS3098™
SHEET 1 OF 2

REV.
A

Copyright © 2024 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, or used for text and data mining, AI training, or similar technologies, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)
Fax: 724-776-0790

Tel: +1 724-776-4970 (outside USA)
Email: CustomerService@sae.org

SAE WEB ADDRESS: <http://www.sae.org>

ISSUED 1979-07 REVISED 2019-02 REAFFIRMED 2024-04