

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."



REV.
A

TABLE 1 - PART NUMBERS AND DIMENSIONS L, G, K, AND APPROX MASS

PART NUMBER	L	G MIN	K MAX	APPROX MASS LB/100
AS3107-11	.802- .822	.060	.182	.96
AS3107-12	.865- .885	.123	.245	1.00
AS3107-13	.928- .948	.186	.308	1.04
AS3107-14	.990-1.010	.248	.370	1.08
AS3107-15	1.052-1.072	.310	.432	1.12
AS3107-16	1.115-1.135	.373	.495	1.16
AS3107-17	1.178-1.198	.436	.558	1.20
AS3107-18	1.240-1.260	.489	.620	1.24
AS3107-19	1.302-1.322	.560	.682	1.28
AS3107-20	1.365-1.385	.623	.745	1.32
AS3107-21	1.428-1.448	.686	.808	1.36
AS3107-22	1.490-1.510	.748	.870	1.40
AS3107-23	1.552-1.572	.810	.932	1.45
AS3107-24	1.615-1.635	.873	.995	1.49
AS3107-25	1.678-1.698	.936	1.058	1.53
AS3107-26	1.740-1.760	.998	1.120	1.57
AS3107-27	1.802-1.822	1.060	1.182	1.61
AS3107-28	1.865-1.885	1.123	1.245	1.65
AS3107-29	1.928-1.948	1.186	1.308	1.69
AS3107-30	1.990-2.010	1.248	1.370	1.73
AS3107-31	2.115-2.135	1.373	1.495	1.81
AS3107-32	2.240-2.260	1.498	1.620	1.89
AS3107-33	2.365-2.385	1.623	1.745	1.97
AS3107-34	2.490-2.510	1.748	1.870	2.06
AS3107-35	2.615-2.635	1.873	1.995	2.14
AS3107-36	2.740-2.760	1.998	2.120	2.22
AS3107-37	2.865-2.885	2.123	2.245	2.30
AS3107-38	2.990-3.010	2.248	2.370	2.38
AS3107-39	3.115-3.135	2.373	2.495	2.46
AS3107-40	3.240-3.260	2.498	2.620	2.54
AS3107-41	3.365-3.385	2.623	2.745	2.63
AS3107-42	3.490-3.510	2.748	2.870	2.71
AS3107-43	3.615-3.635	2.873	2.995	2.79
AS3107-44	3.740-3.760	2.998	3.120	2.87
AS3107-45	3.865-3.885	3.123	3.245	2.95

NOTES:

- FOR PART NUMBERS AS3107-11 THRU AS3107-14 DATUM **A** SHALL REPLACE DATUM **B**.
- MATERIAL: CORROSION RESISTANT STEEL AMS5731 (COMPOSITION SIMILAR TO UNS S66286).
- PROCUREMENT SPECIFICATION: AS7477.
- FLUORESCENT PENETRANT INSPECTION PER ASTM E1417/E1417M, TYPE 1, SENSITIVITY LEVEL 2 MIN.
- SURFACE TEXTURE: SYMBOLS PER ASME Y14.36M. REQUIREMENTS PER ASME B46.1. UNLESS OTHERWISE SPECIFIED, SURFACES TO BE 125 MICROINCHES Ra EXCEPT UPSET HEAD.

	AEROSPACE STANDARD	AS3107 SHEET 2 OF 3	REV. A
	(R) BOLT, MACHINE - HEXAGON HEAD, DRILLED 1 HOLE, PD SHANK, CRES AMS5731 (UNS S66286), .1900-32 UNJF-3A		