

TABLE 1 - PART NUMBERS AND DIMENSIONS

PART NUMBER	L	G MIN	K MAX	APPROX MASS LB/100
AS3114-11	.802-.822	.100	.182	1.08
AS3114-12	.865-.885	.163	.245	1.12
AS3114-13	.928-.948	.286	.308	1.16
AS3114-14	.990-1.010	.288	.370	1.20
AS3114-15	1.052-1.072	.350	.432	1.24
AS3114-16	1.115-1.135	.413	.495	1.28
AS3114-17	1.178-1.198	.476	.558	1.32
AS3114-18	1.240-1.260	.538	.620	1.36
AS3114-19	1.302-1.322	.600	.682	1.40
AS3114-20	1.365-1.385	.663	.745	1.44
AS3114-21	1.428-1.448	.726	.808	1.48
AS3114-22	1.490-1.510	.788	.870	1.53
AS3114-23	1.552-1.572	.850	.932	1.57
AS3114-24	1.615-1.635	.913	.995	1.61
AS3114-25	1.678-1.698	.976	1.058	1.65
AS3114-26	1.740-1.760	1.038	1.120	1.69
AS3114-27	1.802-1.822	1.100	1.182	1.73
AS3114-28	1.865-1.885	1.163	1.245	1.77
AS3114-29	1.928-1.948	1.226	1.308	1.81
AS3114-30	1.990-2.010	1.288	1.370	1.85
AS3114-31	2.115-2.135	1.413	1.495	1.93
AS3114-32	2.240-2.260	1.538	1.620	2.01
AS3114-33	2.365-2.385	1.663	1.745	2.10
AS3114-34	2.490-2.510	1.788	1.870	2.18
AS3114-35	2.615-2.635	1.913	1.995	2.26
AS3114-36	2.740-2.760	2.038	2.120	2.34
AS3114-37	2.865-2.885	2.163	2.245	2.42
AS3114-38	2.990-3.010	2.288	2.370	2.50
AS3114-39	3.115-3.135	2.413	2.495	2.58
AS3114-40	3.240-3.260	2.538	2.620	2.67
AS3114-41	3.365-3.385	2.663	2.745	2.75
AS3114-42	3.490-3.510	2.788	2.870	2.83
AS3114-43	3.615-3.635	2.913	2.995	2.91
AS3114-44	3.740-3.760	3.038	3.120	2.99
AS3114-45	3.865-3.885	3.163	3.245	3.07

1/ FOR SHORT BOLTS THREADED TO HEAD, REFER TO AS9583.

	AEROSPACE STANDARD	AS3114™ SHEET 2 OF 3	REV. B
	BOLT, MACHINE - HEXAGON HEAD, DRILLED 6 HOLES, PD SHANK, CRES UNS S66286, .1900-32 UNJF-3A		