

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

REV. B	FEDERAL SUPPLY CLASS 5970	
	RATIONALE THIS DOCUMENT WAS TAKEN DIRECTLY FROM U.S. MILITARY SPECIFICATION MS3117E AND IS IN NEED OF EXTENSIVE REVISION. IT IS HEREBY BEING CANCELLED AND INCLUDED IN AS85049 CONNECTOR ACCESSORY SPECIFICATION CONSIDERING THEY ARE USED IN CONJUNCTION WITH ACCESSORIES AS SPECIFIED IN AS85049. THIS DOCUMENT WILL BE SUPERSEDED BY AS85049/141. CANCELLATION NOTICE THIS DOCUMENT HAS BEEN DECLARED "CANCELLED" AS OF AUGUST 2008 AND HAS BEEN SUPERSEDED BY AS85049/141. BY THIS ACTION, THIS DOCUMENT WILL REMAIN LISTED IN THE NUMERICAL SECTION OF THE AEROSPACE STANDARDS INDEX NOTING THAT IT IS SUPERSEDED BY AS85049/141.	
CUSTODIAN: SAE AE-8/AE-8C1		PROCUREMENT SPECIFICATION: MIL-I-81765(AS)
	AEROSPACE STANDARD BOOTS, HEAT-SHRINKABLE, STRAIN-RELIEF, RIGHT ANGLE	SAE AS31171 SHEET 1 OF 5 SUPERSEDED BY AS85049/141
		REV. B

SAENORM.COM : Click to view the full PDF of as31171b

NOTICE

THIS DOCUMENT HAS BEEN TAKEN DIRECTLY FROM U.S. MILITARY SPECIFICATION MS3117E AND CONTAINS ONLY MINOR EDITORIAL AND FORMAT CHANGES REQUIRED TO BRING IT INTO CONFORMANCE WITH THE PUBLISHING REQUIREMENTS OF SAE TECHNICAL STANDARDS. THE INITIAL RELEASE OF THIS DOCUMENT IS INTENDED TO REPLACE MS3117E. ANY PART NUMBERS ESTABLISHED BY THE ORIGINAL SPECIFICATION REMAIN UNCHANGED.


THE ORIGINAL MILITARY SPECIFICATION WAS ADOPTED AS AN SAE STANDARD UNDER THE PROVISIONS OF THE SAE TECHNICAL STANDARDS BOARD (TSB) RULES AND REGULATIONS (TSB 001) PERTAINING TO ACCELERATED ADOPTION OF GOVERNMENT SPECIFICATIONS AND STANDARDS. TSB RULES PROVIDE FOR (A) THE PUBLICATION OF PORTIONS OF UNREVISED GOVERNMENT SPECIFICATIONS AND STANDARDS WITHOUT CONSENSUS VOTING AT THE SAE COMMITTEE LEVEL, AND (B) THE USE OF THE EXISTING GOVERNMENT SPECIFICATION OR STANDARD FORMAT.

ANY MATERIAL RELATING TO QUALIFIED PRODUCT LISTS HAS NOT BEEN ADOPTED BY SAE. THIS MATERIAL WAS PART OF THE ORIGINAL MILITARY SPECIFICATION AND IS REPRINTED HERE FOR HISTORIC REFERENCE ONLY.


SAENORM.COM : Click to view the full PDF of as311716

 An SAE International Group	AEROSPACE STANDARD	SAE AS31171 SHEET 2 OF 5 SUPERSEDED BY AS85049/141	REV. B
	BOOTS, HEAT-SHRINKABLE, STRAIN-RELIEF, RIGHT ANGLE		


AS SUPPLIED




AS RECOVERED



AS SUPPLIED



AS RECOVERED



DASH NO.	BOOTS FOR BACKSHELLS (REF)		H. DIA.		J. DIA.			P ±.25	R ±.10	S ±.06	T ±.004	HW ±20%	JW ±20%
	MS3416 STYLE G	MS3158	SUPP. MIN.	REC. MAX.	SUPPLIED MIN. MAT'L A, B	SUPPLIED MIN. MAT'L C	REC. MAX. MAT'L A, B & C						
-01	-	-3, -8	.88	.45	.88	.55	.25	4.14	.73	.47	.040	.06	.045
-02	-3, -8	-10	1.01	.59	1.01	.63	.29	4.88	.78	.47	.040	.06	.045
-03	-10	-12, -14	1.16	.74	1.16	.72	.33	5.76	.82	.47	.040	.07	.045
-04	-12, -14	-16, -18	1.34	.90	1.34	.84	.38	6.78	.86	.47	.040	.07	.045
-05	-16, -18	-20	1.47	1.16	1.47	.91	.41	7.29	.96	.47	.065	.08	.045
-06	-20, -22	-22, -24 -61	1.72	1.34	1.72	1.07	.48	8.41	1.08	.47	.065	.08	.045
-07	-24, -61	-28	1.97	1.62	1.97	1.24	.56	8.84	1.16	.47	.065	.09	.055
-08	-28, -32	-32, -36	2.47	1.85	2.47	1.54	.69	8.95	1.31	.63	.080	.10	.055
-09	-36	-40	2.73	2.35	2.73	1.70	.77	9.19	1.38	.63	.080	.10	.055
-10	-40, -44 -48	-44, -48	3.22	2.64	3.22	2.01	.90	9.33	1.75	.63	.080	.10	.055
-11	-	-3, -8	.92	.41	.92	.47	.22	1.08	.89	-	.040	.05	.05
-12	-3, -8	-10	1.12	.56	1.12	.58	.26	1.65	1.07	-	.040	.06	.06
-13	-10	-12, -14	1.22	.70	1.22	.63	.28	1.84	1.22	-	.040	.07	.07
-14	-12, -14	-16, -18	1.42	.88	1.42	.73	.33	2.20	1.38	-	.040	.07	.07
-15	-16, -18	-20, -22	1.68	1.11	1.68	.87	.39	2.71	1.73	-	.065	.08	.08
-16	-20, -22 -24, -61	-24, -28 -61	2.04	1.38	2.04	1.39	.62	3.84	2.08	-	.065	.13	.13
-17	-28, -32	-32, -36	2.60	1.75	2.60	1.80	.80	4.81	2.60	-	.080	.15	.15
-18	-36, -40 -44, -48	-40, -44 -48	3.22	2.38	3.22	2.25	1.00	5.90	3.30	-	.080	.16	.16

SAENORM.COM : Click to view the full PDF of AS31171