

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.


REV.
B

AS3118™

FEDERAL SUPPLY CLASS
5306


RATIONALE

FIGURE REDRAWN TO AS1132 STANDARD, USAGE NOTE ADDED, SPECS UPDATED.



For more information on this standard, visit
<https://www.sae.org/standards/content/AS3118B>

THIRD ANGLE PROJECTION



CUSTODIAN: E-25

PROCUREMENT SPECIFICATION: AS7477



AEROSPACE STANDARD

(R) BOLT, MACHINE - HEXAGON HEAD,
DRILLED 6 HOLES, PD SHANK,
AMS5731, UNS S66286, .4375-20 UNJF-3A

AS3118™
SHEET 1 OF 3

REV.
B

TABLE 1 - DIMENSIONS

PART NUMBER /3/	L	G MIN	K MAX	APPROX MASS LB/100
AS3118-14	1.312	.030	.188	8.29
AS3118-15	1.375	.090	.250	8.52
AS3118-16	1.438	.153	.312	8.75
AS3118-17	1.500	.215	.375	8.98
AS3118-18	1.562	.277	.438	9.21
AS3118-19	1.625	.340	.500	9.45
AS3118-20	1.688	.403	.562	9.68
AS3118-21	1.750	.465	.625	9.91
AS3118-22	1.812	.527	.688	10.14
AS3118-23	1.875	.590	.750	10.37
AS3118-24	1.938	.653	.812	10.60
AS3118-25	2.000	.715	.875	10.83
AS3118-26	2.125	.840	1.000	11.29
AS3118-27	2.250	.965	1.125	11.76
AS3118-28	2.375	1.090	1.250	12.22
AS3118-29	2.500	1.215	1.375	12.68
AS3118-30	2.625	1.340	1.500	13.14
AS3118-31	2.750	1.465	1.625	13.61
AS3118-32	2.875	1.590	1.750	14.07
AS3118-33	3.000	1.715	1.875	14.53
AS3118-34	3.125	1.840	2.000	14.99
AS3118-35	3.250	1.965	2.125	15.45
AS3118-36	3.375	2.000	2.250	15.92
AS3118-37	3.500	2.215	2.375	16.38
AS3118-38	3.625	2.340	2.500	16.84
AS3118-39	3.750	2.465	2.625	17.30
AS3118-40	3.875	2.590	2.750	17.76
AS3118-41	4.000	2.715	2.875	18.23
AS3118-42	4.125	2.840	3.000	18.69
AS3118-43	4.250	2.965	3.125	19.15
AS3118-44	4.375	3.090	3.250	19.61
AS3118-45	4.500	3.215	3.375	20.08
AS3118-46	4.625	3.340	3.500	20.54
AS3118-47	4.750	3.465	3.625	21.00
AS3118-48	4.875	3.590	3.750	21.46
AS3118-49	5.000	3.715	3.875	21.92
AS3118-50	5.125	3.840	4.000	22.39
AS3118-51	5.250	3.965	4.125	22.85
AS3118-52	5.375	4.090	4.250	23.31
AS3118-53	5.500	4.215	4.375	23.77
AS3118-54	5.625	4.340	4.500	24.23
AS3118-55	5.750	4.465	4.625	24.69
AS3118-56	5.875	4.590	4.750	25.16
AS3118-57	6.000	4.715	4.875	25.62