

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions




TABLE 1 - DIMENSIONS

PART NUMBER /1/	L	G MIN	K MAX	APPROX MASS LB/100
AS3120-15	1.552-1.572	.030	.188	15.96
AS3120-16	1.615-1.635	.079	.250	16.35
AS3120-17	1.678-1.698	.142	.312	16.74
AS3120-18	1.740-1.760	.204	.375	17.13
AS3120-19	1.802-1.822	.266	.438	17.52
-				
AS3120-20	1.865-1.885	.329	.500	17.91
AS3120-21	1.928-1.948	.392	.562	18.30
AS3120-22	1.990-2.010	.454	.625	18.69
AS3120-23	2.115-2.135	.579	.750	19.47
AS3120-24	2.240-2.260	.704	.875	20.25
-				
AS3120-25	2.365-2.385	.829	1.000	21.03
AS3120-26	2.490-2.510	.954	1.125	21.81
AS3120-27	2.615-2.635	1.079	1.250	22.59
AS3120-28	2.740-2.760	1.204	1.375	23.37
AS3120-29	2.865-2.885	1.329	1.500	24.15
-				
AS3120-30	2.990-3.010	1.454	1.625	24.93
AS3120-31	3.115-3.135	1.579	1.750	25.71
AS3120-32	3.240-3.260	1.704	1.875	26.48
AS3120-33	3.365-3.385	1.829	2.000	27.26
AS3120-34	3.490-3.510	1.954	2.125	28.04
-				
AS3120-35	3.615-3.635	2.079	2.250	28.82
AS3120-36	3.740-3.760	2.204	2.375	29.60
AS3120-37	3.865-3.885	2.329	2.500	30.38
AS3120-38	3.990-4.010	2.454	2.625	31.16
AS3120-39	4.115-4.135	2.579	2.750	31.94
-				
AS3120-40	4.240-4.260	2.704	2.875	32.72
AS3120-41	4.365-4.385	2.829	3.000	33.50
AS3120-42	4.490-4.510	2.954	3.125	34.28
AS3120-43	4.615-4.635	3.079	3.250	35.06
AS3120-44	4.740-4.760	3.204	3.375	35.84
-				
AS3120-45	4.865-4.885	3.329	3.500	36.62
AS3120-46	4.990-5.010	3.454	3.625	37.40
AS3120-47	5.115-5.135	3.579	3.750	38.18
AS3120-48	5.240-5.260	3.704	3.875	38.96
AS3120-49	5.365-5.385	3.829	4.000	39.74
-				
AS3120-50	5.490-5.510	3.954	4.125	40.52
AS3120-51	5.615-5.635	4.079	4.250	41.30
AS3120-52	5.740-5.760	4.204	4.375	42.08
AS3120-53	5.775-5.795	4.329	4.500	42.86
AS3120-54	5.990-6.010	4.454	4.625	43.64



AEROSPACE STANDARD

BOLT, MACHINE - HEXAGON HEAD,
DRILLED 6 HOLES, PD SHANK,
UNS S66286, .5625-18 UNJF-3A

AS3120™
SHEET 2 OF 3

REV.
B