

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SSUED 1976-04	REAFFIRMED 2006-10	REVISED 2015-08
---------------	--------------------	-----------------

TABLE 1 - DIMENSIONS

PART NUMBER	L	K	B MAX	C MIN	APPROX MASS LB/100
AS3144-04	2.240 - 2.260	.834 - .854	.742	.642	12.82
AS3144-05	2.365 - 2.385	.959 - .979	.867	.767	13.43
AS3144-06	2.490 - 2.510	1.084 - 1.104	.975	.875	14.04
AS3144-07	2.615 - 2.635	1.209 - 1.229	.975	.875	14.64
AS3144-08	2.740 - 2.760	1.334 - 1.354	.975	.875	15.25
AS3144-09	2.865 - 2.885	1.459 - 1.479	.975	.875	15.86
AS3144-10	2.990 - 3.010	1.584 - 1.604	.975	.875	16.47
AS3144-11	3.115 - 3.135	1.709 - 1.729	.975	.875	17.08
AS3144-12	3.240 - 3.260	1.834 - 1.854	.975	.875	17.69
AS3144-13	3.365 - 3.385	1.959 - 1.979	.975	.875	18.30
AS3144-14	3.490 - 3.510	2.084 - 2.104	.975	.875	18.91
AS3144-15	3.615 - 3.635	2.209 - 2.229	.975	.875	19.52
AS3144-16	3.740 - 3.760	2.334 - 2.354	.975	.875	20.13
AS3144-17	3.865 - 3.885	2.459 - 2.479	.975	.875	20.74
AS3144-18	3.990 - 4.010	2.584 - 2.604	.975	.875	21.35
AS3144-19	4.115 - 4.135	2.709 - 2.729	.975	.875	21.96
AS3144-20	4.240 - 4.260	2.834 - 2.854	.975	.875	22.57
AS3144-21	4.365 - 4.385	2.959 - 2.979	.975	.875	23.18
AS3144-22	4.490 - 4.510	3.084 - 3.104	.975	.875	23.79
AS3144-23	4.615 - 4.635	3.209 - 3.229	.975	.875	24.40
AS3144-24	4.740 - 4.760	3.334 - 3.354	.975	.875	25.01
AS3144-25	4.865 - 4.885	3.459 - 3.479	.975	.875	25.62
AS3144-26	4.990 - 5.010	3.584 - 3.604	.975	.875	26.23
AS3144-27	5.115 - 5.135	3.709 - 3.729	.975	.875	26.84
AS3144-28	5.240 - 5.260	3.834 - 3.854	.975	.875	27.45
AS3144-29	5.365 - 5.385	3.959 - 3.979	.975	.875	28.06
AS3144-30	5.490 - 5.510	4.084 - 4.104	.975	.875	28.67
AS3144-31	5.615 - 5.635	4.209 - 4.229	.975	.875	29.28
AS3144-32	5.740 - 5.760	4.334 - 4.354	.975	.875	29.89
AS3144-33	5.865 - 5.885	4.459 - 4.479	.975	.875	30.50
AS3144-34	5.990 - 6.010	4.584 - 4.604	.975	.875	31.11
AS3144-35	6.115 - 6.135	4.709 - 4.729	.975	.875	31.72
AS3144-36	6.240 - 6.260	4.834 - 4.854	.975	.875	32.33

NOTES:

1. MATERIAL: CORROSION AND HEAT RESISTANT STEEL AMS5731.
2. PROCUREMENT SPECIFICATION: AS7477 REQUIREMENTS RELATED TO BOLT HEADS NOT APPLICABLE.
3. SURFACE TEXTURE: REQUIREMENTS PER ASME B46.1, SYMBOLS PER ASME Y14.36M.
4. FLUORESCENT PENETRANT INSPECTION PER ASTM E1417/E1417M TYPE I, SENSITIVITY LEVEL 2.
5. BREAK SHARP EDGES .003 TO .015, UNLESS OTHERWISE SPECIFIED.
6. DIMENSIONS IN INCHES.
7. DIMENSIONS AND TOLERANCING: ANSI Y14.5M-1982 (ASME PUBLICATION).
8. MARK PART NUMBER PER AS478-37.
9. DO NOT USE UNASSIGNED PART NUMBERS.

	AEROSPACE STANDARD	AS3144™ SHEET 2 OF 3	REV. A
	(R) STUD, STEPPED 2.5 DIA ENGAGEMENT, PD SHANK, AMS5731, .5625-18 UNJF-3A X .500-20 UNJF-3A		