

TABLE 1 - PART NUMBERS AND DIMENSIONS

PART NO.	L	G MIN	K MAX	APPROX. MASS LB/100	PART NO.	L	G MIN	K MAX	APPROX. MASS LB/100
AS3150-03	.838-.858	.105	.198	2.31	AS3150-45	3.462-3.482	2.729	2.822	7.01
AS3150-04	.900-.920	.167	.260	2.42	AS3150-46	3.525-3.545	2.792	2.885	7.12
AS3150-05	.962-.982	.229	.322	2.53	AS3150-47	3.588-3.608	2.855	2.948	7.24
AS3150-06	1.025-1.045	.292	.385	2.64	AS3150-48	3.650-3.670	2.917	3.010	7.35
AS3150-07	1.088-1.108	.355	.448	2.76	AS3150-49	3.712-3.732	2.979	3.072	7.46
AS3150-08	1.150-1.170	.417	.510	2.87	AS3150-50	3.775-3.795	3.042	3.135	7.57
AS3150-09	1.212-1.232	.479	.572	2.98	AS3150-51	3.838-3.858	3.105	3.198	7.68
AS3150-10	1.275-1.295	.542	.635	3.09	AS3150-52	3.900-3.920	3.167	3.260	7.79
AS3150-11	1.338-1.358	.605	.698	3.21	AS3150-53	3.962-3.982	3.229	3.322	7.90
AS3150-12	1.400-1.420	.667	.760	3.32	AS3150-54	4.025-4.045	3.292	3.385	8.02
AS3150-13	1.462-1.482	.729	.822	3.43	AS3150-55	4.088-4.108	3.355	3.448	8.13
AS3150-14	1.525-1.545	.792	.885	3.54	AS3150-56	4.150-4.170	3.417	3.510	8.24
AS3150-15	1.588-1.608	.855	.948	3.64	AS3150-57	4.212-4.232	3.479	3.572	8.36
AS3150-16	1.650-1.670	.917	1.010	3.75	AS3150-58	4.275-4.295	3.542	3.635	8.47
AS3150-17	1.712-1.732	.979	1.072	3.86	AS3150-59	4.338-4.358	3.605	3.698	8.58
AS3150-18	1.775-1.795	1.042	1.135	3.98	AS3150-60	4.400-4.420	3.667	3.760	8.69
AS3150-19	1.838-1.858	1.105	1.198	4.09	AS3150-61	4.462-4.482	3.729	3.822	8.80
AS3150-20	1.900-1.920	1.167	1.260	4.20	AS3150-62	4.525-4.545	3.792	3.885	8.92
AS3150-21	1.962-1.982	1.229	1.322	4.32	AS3150-63	4.588-4.608	3.855	3.948	9.03
AS3150-22	2.025-2.045	1.292	1.385	4.43	AS3150-64	4.650-4.670	3.917	4.010	9.14
AS3150-23	2.088-2.108	1.355	1.448	4.54	AS3150-65	4.712-4.732	3.979	4.072	9.24
AS3150-24	2.150-2.170	1.417	1.510	4.65	AS3150-66	4.775-4.795	4.042	4.135	9.37
AS3150-25	2.212-2.232	1.479	1.572	4.76	AS3150-67	4.838-4.858	4.105	4.198	9.48
AS3150-26	2.275-2.295	1.542	1.635	4.88	AS3150-68	4.900-4.920	4.167	4.260	9.58
AS3150-27	2.338-2.358	1.605	1.698	4.99	AS3150-69	4.962-4.982	4.229	4.322	9.69
AS3150-28	2.400-2.420	1.667	1.760	5.10	AS3150-70	5.025-5.045	4.292	4.385	9.80
AS3150-29	2.462-2.482	1.729	1.822	5.22	AS3150-71	5.088-5.108	4.355	4.448	9.92
AS3150-30	2.525-2.545	1.792	1.885	5.33	AS3150-72	5.150-5.170	4.417	4.510	10.03
AS3150-31	2.588-2.608	1.855	1.948	5.44	AS3150-73	5.212-5.232	4.479	4.572	10.14
AS3150-32	2.650-2.670	1.917	2.010	5.55	AS3150-74	5.275-5.295	4.542	4.635	10.25
AS3150-33	2.712-2.732	1.979	2.072	5.66	AS3150-75	5.338-5.358	4.605	4.698	10.37
AS3150-34	2.775-2.795	2.042	2.135	5.77	AS3150-76	5.400-5.420	4.667	4.760	10.48
AS3150-35	2.838-2.858	2.105	2.198	5.89	AS3150-77	5.462-5.482	4.729	4.822	10.59
AS3150-36	2.900-2.920	2.167	2.260	6.00	AS3150-78	5.525-5.545	4.792	4.885	10.70
AS3150-37	2.962-2.982	2.229	2.322	6.11	AS3150-79	5.588-5.608	4.855	4.948	10.81
AS3150-38	3.025-3.045	2.292	2.385	6.22	AS3150-80	5.650-5.670	4.917	5.010	10.92
AS3150-39	3.088-3.108	2.355	2.448	6.34					
AS3150-40	3.150-3.170	2.417	2.510	6.45					
AS3150-41	3.212-3.232	2.479	2.572	6.56					
AS3150-42	3.275-3.295	2.542	2.635	6.67					
AS3150-43	3.238-3.258	2.605	2.698	6.78					
AS3150-44	3.400-3.420	2.667	2.760	6.90					