

Copyright © 2021 SAE International
All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER:	Tel: 877-606-7323 (inside USA and Canada)	Tel: +1 724-776-4970 (outside USA)	
	Fax: 724-776-0790	Email: CustomerService@sae.org	SAE WEB ADDRESS: http://www.sae.org

TABLE 1

PART NUMBER	L	G MIN	K MAX	APPROX MASS LB/100	PART NUMBER	L	G MIN	K MAX	APPROX MASS LB/100
AS3161-03	.984	.088	.198	4.88	AS3161-41	3.358	2.462	2.572	12.46
AS3161-04	1.046	.150	.260	5.09	AS3161-42	3.471	2.525	2.635	12.66
AS3161-05	1.108	.212	.322	5.27	AS3161-43	3.484	2.588	2.698	12.86
AS3161-06	1.171	.275	.385	5.48	AS3161-44	3.546	2.650	2.760	13.06
AS3161-07	1.234	.338	.448	5.68	AS3161-45	3.608	2.712	2.822	13.25
AS3161-08	1.296	.400	.510	5.88	AS3161-46	3.671	2.775	2.885	13.46
AS3161-09	1.358	.462	.572	6.07	AS3161-47	3.734	2.838	2.948	13.65
AS3161-10	1.421	.525	.635	6.28	AS3161-48	3.796	2.900	3.010	13.86
AS3161-11	1.484	.588	.698	6.48	AS3161-49	3.858	2.962	3.072	14.06
AS3161-12	1.546	.650	.760	6.68	AS3161-50	3.921	3.025	3.135	14.25
AS3161-13	1.608	.712	.822	6.88	AS3161-51	3.984	3.088	3.198	14.46
AS3161-14	1.671	.775	.885	7.08	AS3161-52	4.046	3.150	3.260	14.65
AS3161-15	1.734	.838	.948	7.28	AS3161-53	4.108	3.212	3.322	14.84
AS3161-16	1.796	.900	1.010	7.48	AS3161-54	4.171	3.275	3.385	15.05
AS3161-17	1.858	.962	1.072	7.68	AS3161-55	4.234	3.338	3.448	15.26
AS3161-18	1.921	1.025	1.135	7.87	AS3161-56	4.296	3.400	3.510	15.45
AS3161-19	1.984	1.088	1.198	8.08	AS3161-57	4.358	3.462	3.572	15.65
AS3161-20	2.046	1.150	1.260	8.27	AS3161-58	4.421	3.525	3.635	15.85
AS3161-21	2.108	1.212	1.322	8.47	AS3161-59	4.484	3.588	3.698	16.05
AS3161-22	2.171	1.275	1.385	8.67	AS3161-60	4.546	3.650	3.760	16.25
AS3161-23	2.234	1.338	1.448	8.87	AS3161-61	4.608	3.712	3.822	16.45
AS3161-24	2.296	1.400	1.510	9.07	AS3161-62	4.671	3.775	3.885	16.65
AS3161-25	2.358	1.462	1.572	9.27	AS3161-63	4.714	3.838	3.948	16.85
AS3161-26	2.421	1.525	1.635	9.48	AS3161-64	4.796	3.900	4.010	17.04
AS3161-27	2.484	1.588	1.698	9.67	AS3161-65	4.858	3.962	4.072	17.25
AS3161-28	2.546	1.650	1.760	9.86	AS3161-66	4.921	4.025	4.135	17.44
AS3161-29	2.608	1.712	1.822	10.07	AS3161-67	4.984	4.088	4.198	17.65
AS3161-30	2.671	1.775	1.885	10.27	AS3161-68	5.046	4.150	4.260	17.85
AS3161-31	2.734	1.838	1.948	10.47	AS3161-69	5.108	4.212	4.322	18.04
AS3161-32	2.796	1.900	2.010	10.67	AS3161-70	5.171	4.275	4.385	18.25
AS3161-33	2.858	1.962	2.072	10.86	AS3161-71	5.234	4.388	4.448	18.44
AS3161-34	2.921	2.025	2.135	11.07	AS3161-72	5.296	4.400	4.510	18.63
AS3161-35	2.984	2.088	2.198	11.27	AS3161-73	5.358	4.462	4.572	18.84
AS3161-36	3.046	2.150	2.260	11.46	AS3161-74	5.421	4.525	4.635	19.05
AS3161-37	3.108	2.212	2.322	11.66	AS3161-75	5.484	4.588	4.698	19.24
AS3161-38	3.171	2.275	2.385	11.86	AS3161-76	5.546	4.650	4.760	19.44
AS3161-39	3.234	2.338	2.448	12.06					
AS3161-40	3.296	2.400	2.510	12.26					



AEROSPACE STANDARD

BOLT, MACHINE - DOUBLE HEXAGON EXTENDED
WASHER HEAD, DRILLED, CLOSE TOLERANCE
SHANK, AMS4967, .5000-20 UNJF-3A

AS3161™
SHEET 2 OF 3

REV.
B