


SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."



REV.
C

TABLE 1 - PART NUMBERS AND DIMENSIONS

PART NO.	L	N MIN	M MAX	APPROX. MASS LB/100	PART NO.	L	N MIN	M MAX	APPROX. MASS LB/100
AS3250-03	.302 - .322	.025	.092	.59	AS3250-25	1.678 - 1.698	.936	1.058	1.52
AS3250-04	.365 - .385	.025	.092	.63	AS3250-26	1.740 - 1.760	.998	1.120	1.56
AS3250-05	.428 - .448	.025	.092	.68	AS3250-27	1.802 - 1.822	1.060	1.182	1.60
AS3250-06	.490 - .510	.025	.092	.72	AS3250-28	1.865 - 1.885	1.123	1.245	1.64
AS3250-07	.552 - .572	.025	.092	.76	AS3250-29	1.928 - 1.948	1.186	1.308	1.68
AS3250-08	.615 - .635	.025	.092	.80	AS3250-30	1.990 - 2.010	1.248	1.370	1.73
AS3250-09	.678 - .698	.025	.092	.84	AS3250-31	2.115 - 2.135	1.373	1.495	1.82
AS3250-10	.740 - .760	.025	.120	.88	AS3250-32	2.240 - 2.260	1.498	1.620	1.90
AS3250-11	.802 - .822	.060	.183	.92	AS3250-33	2.365 - 2.385	1.623	1.745	1.98
AS3250-12	.865 - .885	.123	.245	.97	AS3250-34	2.490 - 2.510	1.748	1.870	2.07
AS3250-13	.928 - .948	.186	.308	1.01	AS3250-35	2.615 - 2.635	1.873	1.995	2.15
AS3250-14	.990 - 1.010	.248	.370	1.05	AS3250-36	2.740 - 2.760	1.998	2.120	2.23
AS3250-15	1.052 - 1.072	.310	.432	1.09	AS3250-37	2.865 - 2.885	2.123	2.245	2.33
AS3250-16	1.115 - 1.135	.373	.495	1.14	AS3250-38	2.990 - 3.010	2.248	2.370	2.41
AS3250-17	1.178 - 1.198	.436	.558	1.18	AS3250-39	3.115 - 3.135	2.373	2.495	2.49
AS3250-18	1.240 - 1.260	.498	.620	1.23	AS3250-40	3.240 - 3.260	2.498	2.620	2.57
AS3250-19	1.302 - 1.322	.560	.682	1.27	AS3250-41	3.365 - 3.385	2.623	2.745	2.66
AS3250-20	1.365 - 1.385	.623	.745	1.31	AS3250-42	3.490 - 3.510	2.748	2.870	2.74
AS3250-21	1.428 - 1.448	.686	.808	1.35	AS3250-43	3.615 - 3.635	2.873	2.995	2.82
AS3250-22	1.490 - 1.510	.748	.870	1.39	AS3250-44	3.740 - 3.760	2.998	3.120	2.92
AS3250-23	1.552 - 1.572	.810	.932	1.43	AS3250-45	3.865 - 3.885	3.123	3.245	3.00
AS3250-24	1.615 - 1.635	.873	.995	1.47					