


SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."



REV.
D

TABLE 1 - PART NUMBERS AND DIMENSIONS

PART NO.	L	N MIN	M MAX	APPROX. MASS LB/100	PART NO.	L	N MIN	M MAX	APPROX. MASS LB/100
AS3252-04	.490 - .510	.025	.108	1.91	AS3252-34	2.740 - 2.760	1.732	1.875	6.19
AS3252-05	.552 - .572	.025	.108	2.03	AS3252-35	2.865 - 2.885	1.857	2.000	6.43
AS3252-06	.615 - .635	.025	.108	2.15	AS3252-36	2.990 - 3.010	1.982	2.125	6.66
AS3252-07	.678 - .698	.025	.108	2.26	AS3252-37	3.115 - 3.135	2.107	2.250	6.90
AS3252-08	.740 - .760	.025	.108	2.39	AS3252-38	3.240 - 3.260	2.232	2.375	7.14
AS3252-09	.802 - .822	.025	.108	2.50	AS3252-39	3.365 - 3.385	2.357	2.500	7.37
AS3252-10	.865 - .885	.025	.108	2.63	AS3252-40	3.490 - 3.510	2.482	2.625	7.61
AS3252-11	.928 - .948	.025	.108	2.74	AS3252-41	3.615 - 3.635	2.607	2.750	7.85
AS3252-12	.990 - 1.010	.025	.125	2.87	AS3252-42	3.740 - 3.760	2.732	2.875	8.09
AS3252-13	1.052 - 1.072	.044	.188	2.98	AS3252-43	3.865 - 3.885	2.857	3.000	8.33
AS3252-14	1.115 - 1.135	.107	.250	3.09	AS3252-44	3.990 - 4.010	2.982	3.125	8.56
AS3252-15	1.178 - 1.198	.170	.312	3.22	AS3252-45	4.115 - 4.135	3.107	3.250	8.80
AS3252-16	1.240 - 1.260	.232	.375	3.33	AS3252-46	4.240 - 4.260	3.232	3.375	9.04
AS3252-17	1.302 - 1.322	.294	.438	3.46	AS3252-47	4.365 - 4.385	3.357	3.500	9.28
AS3252-18	1.365 - 1.385	.357	.500	3.57	AS3252-48	4.490 - 4.510	3.482	3.625	9.51
AS3252-19	1.428 - 1.448	.420	.562	3.70	AS3252-49	4.615 - 4.635	3.607	3.750	9.75
AS3252-20	1.490 - 1.510	.482	.625	3.81	AS3252-50	4.740 - 4.760	3.732	3.875	9.99
AS3252-21	1.552 - 1.572	.544	.688	3.93	AS3252-51	4.865 - 4.885	3.857	4.000	10.22
AS3252-22	1.615 - 1.635	.607	.750	4.05	AS3252-52	4.990 - 5.010	3.982	4.125	10.46
AS3252-23	1.678 - 1.698	.670	.812	4.16	AS3252-53	5.115 - 5.135	4.107	4.250	10.70
AS3252-24	1.740 - 1.760	.732	.875	4.29	AS3252-54	5.240 - 5.260	4.232	4.375	10.94
AS3252-25	1.802 - 1.822	.794	.938	4.40	AS3252-55	5.365 - 5.385	4.357	4.500	11.18
AS3252-26	1.865 - 1.885	.857	1.000	4.53	AS3252-56	5.490 - 5.510	4.482	4.625	11.42
AS3252-27	1.928 - 1.948	.920	1.062	4.64	AS3252-57	5.615 - 5.635	4.607	4.750	11.66
AS3252-28	1.990 - 2.010	.982	1.125	4.76	AS3252-58	5.740 - 5.760	4.732	4.875	11.89
AS3252-29	2.115 - 2.135	1.107	1.250	5.00	AS3252-59	5.865 - 5.885	4.857	5.000	12.13
AS3252-30	2.240 - 2.260	1.232	1.375	5.23	AS3252-60	5.990 - 6.010	4.982	5.125	12.37
AS3252-31	2.365 - 2.385	1.357	1.500	5.47					
AS3252-32	2.490 - 2.510	1.482	1.625	5.71					
AS3252-33	2.615 - 2.635	1.607	1.750	5.95					