



INCH	MILLIMETER	INCH	MILLIMETER	INCH	MILLIMETER	INCH	MILLIMETER
.002	0.05	.006	0.15	.012	0.30	.054	1.37
.003	0.08	.009	0.23	.029	0.74	.121	3.07
.005	0.13	.010	0.25	.033	0.84		

BIN CODE	A DIA	B DIA MAX	C DIA	D DIA	E DIA	F DIA	H	J	K REF	L CHAM	M MIN	N	P	R
190	.033 (0.84)	.060 (1.52)	.0615 (1.56)	.0200 (0.51) .0180 (0.46)	.0480 (1.22) .0465 (1.18)	.017 (0.43) .013 (0.33)			.327 (8.31)	.006 (0.15) .003 (0.08)	.130 (3.30)	.166 (4.22) .158 (4.01)		.035 (0.89) .033 (0.84)
191	.031 (0.79)		.0600 (1.52)	.0355 (0.90) .0335 (0.85)		.022 (0.56) .018 (0.46)	.175 (4.45) .160 (4.06)	.170 (4.32) .160 (4.06)					.137 (3.48) .120 (3.05)	
192	.044 (1.12) .042 (1.07)	.076 (1.93)	.094 (2.39) .091 (2.31)	.048 (1.22) .046 (1.17)	.070 (1.78) .068 (1.73)	.027 (0.69) .023 (0.58)			.349 (8.86)	.010 (0.25) .005 (0.13)	.150 (3.81)	.188 (4.78) .180 (4.57)		
193	.066 (1.68) .064 (1.63)	.108 (2.74)	.130 (3.30) .127 (3.23)	.068 (1.73) .066 (1.68)	.103 (2.62) .101 (2.57)									.055 (1.40) .053 (1.35)
605	.100 (2.54) .097 (2.46)	.168 (4.27)	.171 (4.34) .168 (4.27)	.102 (2.59) .096 (2.44)	.152 (3.86) .148 (3.76)	.030 (0.76) .019 (0.48)	.220 (5.59) .205 (5.21)	.215 (5.46) .205 (5.21)	.446 (11.33)	.016 (0.41) .005 (0.13)	.176 (4.47)	.240 (6.10) .230 (5.84)	.187 (4.75) .170 (4.32)	

TABLE 3 - DESIGN CHARACTERISTICS

BIN CODE	COLOR BANDS			MATING END SIZE	WIRE BARREL SIZE	TYPE	CLASS
	1ST	2ND	3RD				
1/ 190	BROWN	WHITE	BLACK	22	28	A	B
191	BROWN	WHITE	BROWN	22	22		
192	BROWN	WHITE	RED	20	20		
193	BROWN	WHITE	ORANGE	16	16		
605	BLUE	BLACK	GREEN	12	12		

1/ SEE APPLICATION NOTE.

TABLE 4 - TOOLS

BIN CODE	BASIC CRIMPING TOOL	POSITIONER	INSTALLING TOOL (REF) 1/	REMOVAL TOOL (REF) 1/
-190	M22520/7-01	M22520/7-11	M81969/14-01 M81969/8-01 M81969/8-301	M81969/14-01 M81969/8-02 M81969/8-302
-191			M81969/14-01 M81969/8-03 M81969/8-303	M81969/14-01 M81969/8-04 M81969/8-304
-192		M22520/7-12	M81969/14-10 M81969/8-05 M81969/8-205 M81969/8-305	M81969/14-10 M81969/8-06 M81969/8-206 M81969/8-306
-193		M22520/7-13	M81969/14-03 M81969/8-07 M81969/8-207 M81969/8-307	M81969/14-03 M81969/8-08 M81969/8-208 M81969/8-308
-605	M22520/1-01	M22520/1-18	M81969/8-09 M81969/8-309 M81969/8-209 M81969/16-03	M81969/8-10 M81969/8-310 M81969/8-210 M81969/16-03

1/ SEE THE APPLICATION NOTE FOR THE APPLICABLE PRODUCT SPECIFICATION.

TABLE 5 - CONTACT RESISTANCE

ENGAGING END SIZE	WIRE SIZE RANGE	TEST CURRENT (AMPERES)	MAXIMUM VOLTAGE DROP (MILIVOLTS)		
			25 °C ± 3 °C	25 °C ± 3 °C AFTER CONDITIONING	200 °C +3 °C, - 0 °C
22	28	1.5	60	70	100
	32	1.0	95	105	135
22	22	5.0	70	80	120
	26	2.0	60	70	100
20	20	7.5	55	65	95
	24	3.0	45	55	80
16	16	13.0	50	60	85
	20	7.5	45	55	80
12	12 1/	23.0	60	70	100
	14	17.0	55	65	95

1/ SILVER PLATED WIRE.

TABLE 6 - CONTACT ENGAGEMENT AND SEPERATION FORCE

SOCKET ENGAGING END SIZE	TEST PIN DIAMETER	
	MIN +.0001, -.0000	MAX +.0000, -.0001
22	.0295	.0305
20	.0395	.0405
16	.0615	.0625
12	.0935	.0945

	AEROSPACE STANDARD	AS39029™/22 SHEET 3 OF 5	REV. E
	CONTACTS, ELECTRICAL, CONNECTOR, SOCKET, CRIMP REMOVABLE (FOR AS81714 TERMINAL JUNCTION SYSTEM SERIES II)		

TABLE 7 - PROBE DAMAGE

SOCKET ENGAGING END SIZE	TEST PROBE DIAMETER	BENDING MOMENT	
		DEPTH OF INSERTION	MOMENT (MAX IN-LB)
22	.0305	.105	.10
	.0295	.095	
20	.0405	.135	.25
	.0395		
16	.0625	.125	.37
	.0615		
12	.0935	.185	.55
	.0945	.175	

TABLE 8 - TENSILE STRENGTH

WIRE BARRELL SIZE	WIRE SIZE (AWG)	AXIAL LOAD (POUNDS)				1/ MAXIMUM RECOMMENDED CRIMP BARREL GROWTH PER DIA
		SILVER OR TIN PLATED COPPER WIRE		NICKEL PLATED COPPER WIRE		
		INITIAL CONDITION VALUES	THERMAL CONDITION VALUES	INITIAL CONDITION VALUES	THERMAL CONDITION VALUES	
28	28	2.7	2	1.7	1.28	.0015
	32	1.0	.75	1.0	.75	
22	22	12.0	7.5	8.0	6	
	26	5.0	4	3.0	2.5	
20	20	20.0	14	10.0	7.5	.0030
	24	8.0	6	6.0	4.5	
16	16	50.0	37	29.0	21	.0050
	20	20.0	14	10.0	7.5	
12	12	100.0	85	65.0	55	.0070
	14	60.0	52	34.0	30	

1/ UNTIL A TEST METHOD IS DEFINED FOR VERIFICATION, THE MAXIMUM GROWTH DIAMETER WILL REMAIN A RECOMMENDATION RATHER THAN A REQUIREMENT.

TABLE 9 - PART NUMBER

AS39029 PART NUMBER	BIN CODE	SUPERSEDED PART NUMBER(S)
M39029/22-190	190	M39029/22-22-28 M39029/15-22-28
M39029/22-191	191	M39029/22-22-22 M39029/15-22-22
M39029/22-192	192	M39029/22-20-20
M39029/22-193	193	M39029/22-16-16
M39029/22-605	605	AIR FORCE LOGISTIC COMMAND B2070520-2-1

REQUIREMENTS: ALL REQUIREMENTS SHALL CONSIST OF THIS DOCUMENT AND THE LATEST ISSUE OF AS39029.

1. DESIGN:

CONTACTS SHALL BE DESIGNED IN ACCORDANCE WITH FIGURES 1 AND 2 AND TABLES 2 AND 3. DIMENSIONS ARE IN INCHES. DIMENSIONS SHOWN APPLY AFTER PLATING. DIMENSION "M" IS THE DISTANCE BETWEEN REAR OF CONTACT SHOULDER AND POINT AT WHICH A GAGE PIN, OF SAME BASIC DIAMETER AS MATING PIN CONTACT AND A SQUARE FACE, FIRST ENGAGES SOCKET CONTACT SPRING MEMBER. THE MAXIMUM ALLOWABLE GAP BETWEEN THE HOOD AND BODY OF THE CONTACT IS .010 INCH. AXIAL CONCENTRICITY: ALL DIAMETERS TO BE CONCENTRIC WITHIN .004 FIM EXCEPT AS NOTED.

2. TOOLS:

TOOLS REQUIRED FOR CRIMPING CONTACTS TO WIRE/CABLE AND THE INSTALLING/REMOVAL FROM THE CONNECTOR SHALL BE IN ACCORDANCE WITH TABLE 4.

3. PART NUMBERS:

CONTACT PART NUMBERS SHALL BE IN ACCORDANCE WITH TABLE 9. SUPERSEDED PART NUMBERS ARE AS SPECIFIED.

	AEROSPACE STANDARD		AS39029™/22 SHEET 4 OF 5	REV. E
	CONTACTS, ELECTRICAL, CONNECTOR, SOCKET, CRIMP REMOVABLE (FOR AS81714 TERMINAL JUNCTION SYSTEM SERIES II)			