

SAE Executive Standards Committee Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

REV.
C

AS39029™/59


FEDERAL SUPPLY CLASS
5999

RATIONALE

LIMITED SCOPE REVISION IS REQUIRED TO CORRECT THE DOCUMENT FEDERAL SUPPLY CLASS (FSC) NUMBER; IT SHOULD BE 5999 RATHER THAN 5935.


NOTICE

THE COMPLETE REQUIREMENTS FOR PROCURING THE PRODUCT DESCRIBED HEREIN SHALL CONSIST OF THIS DOCUMENT AND THE LATEST ISSUE OF AS39029.



For more information on this standard, visit
<https://www.sae.org/standards/content/AS39029/59C/>

THIRD ANGLE PROJECTION



CUSTODIAN: AE-8C1

PROCUREMENT SPECIFICATION: AS39029



AEROSPACE STANDARD

CONTACTS, ELECTRICAL CONNECTOR, SOCKET,
CRIMP REMOVABLE, SHIELDED, SIZE 8
(FOR MIL-DTL-38999 SERIES I, III, AND IV CONNECTORS)

AS39029™/59
SHEET 1 OF 7

REV.
C

Copyright © 2021 SAE International
All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)
Fax: 724-776-0790

Tel: +1 724-776-4970 (outside USA)
Email: CustomerService@sae.org

SAE WEB ADDRESS: <http://www.sae.org>

ISSUED 2000-07 REVISED 2021-02




FIGURE 1 - CONNECTOR CONTACT (CONTINUED)




FIGURE 2 - INSULATOR EXPANDER TOOL

	AEROSPACE STANDARD	AS39029™/59 SHEET 2 OF 7	REV. C
	CONTACTS, ELECTRICAL CONNECTOR, SOCKET, CRIMP REMOVABLE, SHIELDED, SIZE 8 (FOR MIL-DTL-38999 SERIES I, III, AND IV CONNECTORS)		

TABLE 1 - FIGURE 1 AND 2 METRIC EQUIVALENTS

INCHES	MILLIMETERS	INCHES	MILLIMETERS	INCHES	MILLIMETERS	INCHES	MILLIMETERS
.001	0.03	.031	0.79	.155	3.94	.286	7.26
.002	0.05	.0355	0.90	.165	4.19	.290	7.37
.003	0.08	.051	1.30	.186	4.72	.314	7.98
.005	0.13	.053	1.35	.198	5.03	.380	9.65
.006	0.15	.075	1.91	.2180	5.54	.405	10.29
.014	0.36	.090	2.29	.219	5.56	.420	10.67
.015	0.38	.106	2.69	.221	5.61	.442	11.23
.019	0.48	.125	3.18	.242	6.15	.562	14.27
.020	0.51	.141	3.58	.263	6.68	.625	15.88
.027	0.69	.151	3.84	.274	6.96		




FIGURE 3 - VIBRATION ENVELOPE



AEROSPACE STANDARD

CONTACTS, ELECTRICAL CONNECTOR, SOCKET,
CRIMP REMOVABLE, SHIELDED, SIZE 8
(FOR MIL-DTL-38999 SERIES I, III, AND IV CONNECTORS)

AS39029™/59
SHEET 3 OF 7

REV.
C

TABLE 2 - DESIGN CHARACTERISTICS

BIN CODE	COLOR BANDS			CONTACT CAVITY SIZE	CABLES ACCOMMODATED	TYPE	CLASS
	1ST	2ND	3RD				
366	ORANGE	BLUE	BLUE	8	M17/095-RG180	D	B

TABLE 3 - TOOLS

BIN CODE	INSTALLING TOOL	REMOVAL TOOL	INSULATOR EXPANDER TOOL (CRIMP ONLY) ^{1/}
366	M81969/8-13	M81969/14-12 M81969/8-14	SEE MANUFACTURER'S ASSEMBLY INSTRUCTIONS

^{1/} INSULATOR EXPANDER TOOL KIT MUST BE USED TO ASSEMBLE REAR INSULATOR OVER CONTACT WHEN THE INNER CONTACT IS INSTALLED BY CRIMPING MEANS ALONE.

TABLE 4 - TOOLS (INNER CONTACT AND SHIELD CRIMP SLEEVE TOOLS)

BIN CODE	INNER CONTACT TOOLING ^{1/}		SHIELD CRIMP SLEEVE TOOLING	
	BASIC CRIMPING TOOL	CONTACT POSITIONER	BASIC CRIMPING TOOL	DIE PART OR IDENTIFYING NO.
366	M22520/2-01	M22520/2-31	M22520/5-01 M22520/10-01	M22520/5-05 DIE CLOSURE B M22520/10-07 DIE CLOSURE B

^{1/} MAY BE SOLDERED IN ACCORDANCE WITH MANUFACTURER'S ASSEMBLY INSTRUCTIONS.

TABLE 5 - LOW SIGNAL LEVEL CONTACT RESISTANCE (INNER CONTACT ONLY)

BIN CODE	CABLE ACCOMMODATED	MAXIMUM CONTACT RESISTANCE (MILLIOHMS)	
		INITIAL	AFTER CONDITIONING
366	M17/095-RG180	120	144

TABLE 6 - CONTACT RESISTANCE

BIN CODE	CONTACT	CABLE ACCOMMODATED	TEST CURRENT (AMPERES)	MAXIMUM VOLTAGE DROP (MILLIVOLTS)		
				25 °C +3 °C, -0 °C		200 °C +3 °C, -0 °C
				MAX	AFTER CONDITIONING	
					MAX	
366	INNER	M17/095-RG180	1	120	144	204
	OUTER		12	60	72	102

TABLE 7 - CONTACT ENGAGEMENT AND SEPARATION FORCES

TEST PIN DIAMETER (INCHES)	INITIAL			AFTER CONDITIONING		
	MINIMUM SEPARATION FORCE (OZ)	MAXIMUM AVERAGE ENGAGEMENT FORCE (OZ)	MAXIMUM ENGAGEMENT FORCE (OZ)	MINIMUM SEPARATION FORCE (OZ)	MAXIMUM AVERAGE ENGAGEMENT FORCE (OZ)	MAXIMUM ENGAGEMENT FORCE (OZ)
.2190 +.0002 -.0000	N/A	N/A	48	N/A	N/A	60
.2170 +.0000 -.0002	4	N/A	N/A	2	N/A	N/A

TABLE 8 - CRIMP TENSILE STRENGTH

BIN CODE	CABLE ACCOMMODATED	AXIAL LOAD (POUNDS MINIMUM)	
		INNER CONTACT	OUTER CONTACT
366	M17/095-RG180	3.5	25

TABLE 9 - DIELECTRIC WITHSTANDING VOLTAGE

ALTITUDE	TEST VOLTAGES, AC RMS
SEA LEVEL 50000 FEET	1300 250

TABLE 10 - PART NUMBER

BIN CODE	PART NUMBER	SUPERSEDED PART NUMBER
366	M39029/59-366	MS27535

REQUIREMENTS: ALL REQUIREMENTS SHALL CONSIST OF THIS DOCUMENT AND THE LATEST ISSUE OF AS39029.

1. DESIGN:

CONTACTS SHALL BE DESIGNED IN ACCORDANCE WITH FIGURE 1 AND TABLE 2. DIMENSIONS ARE IN INCHES. DIMENSIONS SHOWN APPLY AFTER PLATING. OPERATING TEMPERATURE RANGE: -65 °C (-85 °F) TO 200 °C (392 °F). THE OUTER CONTACT MATES WITH A .2180 ± .0010 DIAMETER PIN, THE SPRING DESIGN IS OPTIONAL. THE .090 MAXIMUM DIMENSION TO ENGAGEMENT IN FIGURE 1 IS MEASURED WITH A .2180 DIAMETER BASIC SQUARE ENDED PIN. MANUFACTURER'S RECOMMENDED ASSEMBLY INSTRUCTIONS SHALL BE SHIPPED WITH UNIT PACKAGE.

2. TOOLS:

TOOLS REQUIRED FOR CRIMPING CONTACTS TO THE WIRE/CABLE AND THE INSTALLING/REMOVAL FROM THE CONNECTOR SHALL BE IN ACCORDANCE WITH TABLES 3 AND 4. THE EXPANDER TOOL SOURCING INFORMATION SHALL BE PROVIDED BY THE CONTACT MANUFACTURER WITH THE UNIT PACKAGE. SEE FIGURE 2 FOR EXPANDER TOOL DETAILS.

3. PART NUMBERS:

CONTACT PART NUMBERS SHALL BE IN ACCORDANCE WITH TABLE 10. SUPERSEDING PART NUMBERS ARE AS SPECIFIED.

4. MATERIALS:

MATERIALS SHALL BE IN ACCORDANCE WITH AS39029.

	AEROSPACE STANDARD	AS39029™/59 SHEET 5 OF 7	REV. C
	CONTACTS, ELECTRICAL CONNECTOR, SOCKET, CRIMP REMOVABLE, SHIELDED, SIZE 8 (FOR MIL-DTL-38999 SERIES I, III, AND IV CONNECTORS)		