

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

REV.
C

AS4687

FEDERAL SUPPLY CLASS
4730

RATIONALE

THIS DOCUMENT HAS BEEN REAFFIRMED TO COMPLY WITH THE SAE 5-YEAR REVIEW POLICY.




FIGURE 1 - ELBOW ASSEMBLY, 90°





FIGURE 2 - INSTALLATION, RETAINED NUT AND RETAINING WIRE

THIRD ANGLE PROJECTION



CUSTODIAN: SAE G-3/G-3B

PROCUREMENT SPECIFICATION: /4/ AS4444

SAE Aerospace
An SAE International Group

AEROSPACE STANDARD

FITTING ASSEMBLY, ELBOW, 90°, FLARELESS AND
SHORT FLARELESS, REDUCER, RETAINED NUT

AS4687
SHEET 1 OF 4

**REV.
C**

Copyright 2007 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)
Fax: 724-776-0790

Tel: 724-776-4970 (outside USA)
Email: CustomerService@sae.org

SAE WEB ADDRESS: <http://www.sae.org>

ISSUED 1992-07 REVISED 1997-03 REAFFIRMED 2007-08

REV.
C

AS4687

TABLE 1 - DIMENSIONS AND WEIGHTS

BASIC NO. AS4687 /10/ /18/ SIZE CODE	D	H	J + .005/- .020	LB/EA MAX ALUM	LB/EA MAX CRES	LB/EA MAX Ti
20	.517	.124	1.375	.332	.964	.560
24	.614	.156	1.688	.502	1.430	.828

(R) TABLE 2 - WIRE INSERTION DEPTH

PORT SIZE	(NOMINAL TUBE SIZE)	C
04	.250	.076
05	.312	.076
06	.375	.084
08	.500	.095
10	.625	.114
12	.750	.150
16	1.000	.176
20	1.250	.247
24	1.500	.287

TABLE 3 - LEG LENGTH A

SIZE OF PORT #2	FORGING SIZE /10/ 20	FORGING SIZE /10/ 24
04	1.424	1.549
05	1.424	1.549
06	1.440	1.565
08	1.533	1.658
10	1.596	1.721
12	1.659	1.784
16	1.659	1.784
20	1.678	1.577
24	--	1.803

TABLE 4 - LEG LENGTH B

SIZE OF PORT #1	FORGING SIZE /10/ 20	FORGING SIZE /10/ 24
04	1.401	1.526
05	1.453	1.578
06	1.514	1.639
08	1.611	1.736
10	1.690	1.815
12	1.679	1.804
16	1.727	1.852
20	1.603	1.728
24	--	1.756

TABLE 5 - TUBE SIZE AND CORRESPONDING THREADS

PORT SIZE	(NOMINAL TUBE SIZE)	T THREAD PER MIL-S-8879 CLASS 3B
04	.250	.4375-20UNJF
05	.312	.5000-20UNJF
06	.375	.5625-18UNJF
08	.500	.7500-16UNJF
10	.625	.8750-14UNJF
12	.750	1.0625-12UNJ
16	1.000	1.3125-12UNJ
20	1.250	1.5625-12UNJ
24	1.500	1.8125-12UNJ

NOTES:

/1/ MATERIAL:

a. CODE LETTER T:

- (1) BODY: TYPE 6AL-4V TITANIUM ALLOY PER AMS 4928
- (2) NUT: CODE LETTER T OF AS4702 OR AS1790 REFERENCE (TYPE 6AL-4V TITANIUM ALLOY)
- (3) WIRE: PER AS4701 OR AS1791 REFERENCE (CLASS 302 OR 305 CORROSION RESISTANT STEEL)

b. CODE LETTER V:

- (1) BODY: TYPE 15-5PH CORROSION RESISTANT STEEL PER AMS 5659
- (2) NUT: CODE LETTER V OF AS4702 OR AS1790 REFERENCE (TYPE 15-5PH CORROSION RESISTANT STEEL)
- (3) WIRE: PER AS4701 OR AS1791 REFERENCE (CLASS 302 OR 305 CORROSION RESISTANT STEEL)

c. CODE LETTER W:

- (1) BODY: TYPE 7075-T73 ALUMINUM ALLOY FORGING PER AMS 4141 OR TYPE 7075-T7351 ALUMINUM ALLOY BAR PER AMS 4124
- (2) NUT: CODE LETTER W OF AS4702 OR AS1790 REFERENCE (TYPE 7075-T73 ALUMINUM ALLOY)
- (3) WIRE: PER AS4701 OR AS1791 REFERENCE (CLASS 302 OR 305 CORROSION RESISTANT STEEL)

2. HEAT TREAT:

a. MATERIAL CODE LETTER T:

- (1) BODY, NUT, AND WIRE: NONE

b. MATERIAL CODE LETTER V:

- (1) BODY: HEAT TREAT TO CONDITION H-1075 PER AMS 2759/3
- (2) NUT: MATERIAL CODE LETTER V OF AS4702 OR AS1790 REFERENCE (HEAT TREAT TO CONDITION H-1075)
- (3) WIRE: NONE

c. MATERIAL CODE LETTER W:

- (1) BODY, NUT, AND WIRE: NONE

/3/ FINISH:

a. MATERIAL CODE LETTER T:

- (1) BODY: FLUORIDE PHOSPHATE CONVERSION COAT PER AMS 2486
- (2) NUT: CODE LETTER T OF AS4702 OR AS1790 WITH SUFFIX N REFERENCE (FLUORIDE PHOSPHATE CONVERSION COAT AND COAT WITH SOLID FILM LUBRICANT ON ID)
- (3) WIRE: PER AS4701 OR AS1791 REFERENCE (PASSIVATE AND COAT WITH SOLID FILM LUBRICANT)

b. MATERIAL CODE LETTER V:

- (1) BODY:
 - (a) V CODE PARTS TO BE PASSIVATED ONLY WILL HAVE NO FINISH CODE LETTER AFTER THE PART NUMBER. THE FINISH WILL BE: PASSIVATE PER QQ-P-35, TYPE II OR VIII.
 - (b) V CODE PARTS TO BE CADMIUM PLATED ONLY WILL HAVE THE FINISH CODE LETTER "P" AFTER THE SIZE CODE IN THE PART NUMBER. THE FINISH WILL BE: CADMIUM PLATE PER QQ-P-416, TYPE II, CLASS 2.
- (2) NUT: CODE LETTER V OF AS4702 OR AS1790 REFERENCE
 - (a) NO FINISH CODE LETTER AT END OF PART NUMBER: PASSIVATE AND COAT WITH SOLID FILM LUBRICANT ON ID
 - (b) FINISH CODE LETTER P AT END OF PART NUMBER: CADMIUM PLATE
- (3) WIRE: PER AS4701 OR AS1791 REFERENCE (PASSIVATE AND COAT WITH SOLID FILM LUBRICANT)