

Society of Automotive Engineers, Inc.
TWO PENNSYLVANIA PLAZA, NEW YORK, N. Y. 10001

AEROSPACE STANDARD AS 473B


FLANGE-ACCESSORY, 10" BOLT CIRCLE

Issued 11-15-57


Revised 2-28-63

BOLT CLEARANCE MIN 1.375
PREFERRED 1.750

ACCESSORY SHALL BE CAPABLE OF SATISFACTORY OPERATION WITH THE PITCH DIAMETER CENTER OF DRIVE SPLINE DISPLACED TO A MAXIMUM .006 IN ANY DIRECTION FROM THE CENTER DEFINED BY THE A PILOT DIAMETER AND OUT OF SQUARE WITH MOUNTING FACE WITHIN .001 INCH/INCH OF INDICATED DIA FIR. SPLINE SHAFT SHALL BE RETAINED IN THE ACCESSORY WHEN THE LATTER IS REMOVED FROM THE POWER SOURCE



PILOT DIA A 8.996
8.992
SHALL BE CONCENTRIC WITH AXIS OF ROTATION WITHIN .008 FULL INDICATOR READING



POWER RATINGS

FLANGE TYPE	SPLINE PD	(a) MAX HP VARIABLE SPEED	(b) MAX HP BASED ON 6000 RPM CONSTANT SPEED	(b) MAX HP BASED ON 8000 RPM CONSTANT SPEED	O RING SIZE CROSS SECTION .135-.143	
					ID ACTUAL	OD NOMINAL
A	0.800	30 (15 KVA)	65 (40 KVA)	95 (60 KVA)	0.728-0.740	1.000
B	1.200	85 (40 KVA)	190 (120 KVA)	250 (160 KVA)	1.103-1.115	1.375
C	1.625	190 (90 KVA)	250 (160 KVA)		1.478-1.490	1.750
D	1.875	250 (120 KVA)			1.724-1.744	2.000
E	2.000	335 (160 KVA)			1.849-1.869	2.125

- (a) HP INCLUDES COMBINED EFFICIENCY OF 64% FOR AC GENERATORS AND CONSTANT SPEED TRANSMISSION.
(b) HP INCLUDES EFFICIENCY OF 85% FOR AC GENERATORS.

THE NOMINAL USE OF THIS FLANGE IS FOR AC AND DC AIRCRAFT GENERATORS, CONSTANT SPEED TRANSMISSIONS (DRIVES), AND HIGH SPEED FLUID POWER PUMPS.

THE STATIC TORSIONAL STRENGTH OF THE ACCESSORY DRIVE SHAFT SHALL NOT EXCEED 5 TIMES THE FULL LOAD TORQUE RATING OF THE ACCESSORY AT MINIMUM RATED SPEED. (FOR AC GENERATORS, FULL LOAD IS BASED ON UNITY POWER FACTOR).

THE ACCESSORY SHALL OPERATE SATISFACTORILY WITH OIL LEAKAGE FROM THE DRIVE INTO THE PILOT COMPARTMENT NOT EXCEEDING 2 CC PER HOUR.

IN THE EVENT OF A SHEAR SECTION FAILURE, THE ACCESSORY SHALL BE DESIGNED TO PREVENT DISENGAGEMENT OF THE DRIVE SPLINE COMPONENT. REMOVE ALL BURRS AND SHARP EDGES.

DIMENSIONS IN INCHES. UNLESS OTHERWISE SPECIFIED, TOLERANCES: DECIMALS $\pm .010$, ANGLES $\pm 2^\circ$.

THIS DRAWING AND THE APPLICABLE ACCESSORY SPECIFICATIONS, TOGETHER, COMPLETELY DEFINE THE DESIGN REQUIREMENTS.

FOR EXHAUST SHROUD MOUNTING SURFACES ON AIR COOLED AC AND DC GENERATORS, SEE A/P 554 AND 555.

SURFACE ROUGHNESS SYMBOL $\sqrt{\text{ }}$, AS 291 (AA).

THIS IS A DESIGN STANDARD AND IS NOT TO BE USED AS A PART NUMBER.

FOR DETAILS OF MATING DRIVE, SEE AS 470.

FOR DETAILS OF SLOTTED MOUNTING HOLE FLANGE, SEE AS 474.

FOR DETAILS OF O RING SEALED MOUNTING FLANGE, SEE AS 481.

Section 8.3 of the SAE Technical Board rules provides that: "All technical reports, including standards approved and practices recommended, are advisory only. Their use by anyone engaged in industry or trade is entirely voluntary. There is no agreement to adhere to any SAE standard or recommended practice, and no commitment to conform to or be guided by any technical report. In formulating and approving technical reports, the Board and its Committees will not investigate or consider patents which may apply to the subject matter. Prospective users of the report are responsible for protecting themselves against liability for infringement of patents."