

AS4774

SAE Technical Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and the applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.




FIGURE 1 - DUCT WITH CUFF ENDS




FIGURE 2 - CUFF END




FIGURE 3 - CUT ENDS


TABLE 1 - PERFORMANCE CRITERIA

OPERATING TEMPERATURE, °F	MAXIMUM PRESSURE, psi	R /5/ BEND RADIUS MIN	HOSE LEAKAGE, SCFM/FT/IN DIA	JOINT LEAKAGE, /8/ SCFM/IN DIA
-65 TO +250	1	.75 X DIA	.015	.1

TABLE 2 - SIZES, LENGTHS, AND WEIGHTS

HOSE INSIDE DIAMETER	HOSE LENGTH MINIMUM	HOSE LENGTH MAXIMUM	MAXIMUM BODY WEIGHT, LB/IN/IN DIA	MAXIMUM CUFF WEIGHT, LB/IN DIA
4.00 TO 6.00	4.00	240.00	.0035	.010
6.25 TO 8.00	4.00	240.00	.0040	.014
8.25 TO 10.00	4.00	240.00	.0040	.015
10.25 TO 12.00	4.00	240.00	.0042	.016

THIRD ANGLE PROJECTION



CUSTODIAN: SAE 6-3/G-3D

PROCUREMENT SPECIFICATION: /1D/ AS1501

SAE The Engineering Society
For Advancing Mobility
Land Sea Air and Space
INTERNATIONAL
400 Commonwealth Drive, Warrendale, PA 15096-0001

AEROSPACE STANDARD

HOSE, AIR DUCT, FLEXIBLE,
SILICONE-COATED FABRIC, 1 psi,
EXTERNAL NYLON HELIX, SELF-EXTINGUISHING

AS4774

SHEET 1 OF 2