

REV.
B

AS5239

FEDERAL SUPPLY CLASS
4730

RATIONALE

MATERIAL OPTION FOR 15-5PH CORROSION RESISTANT STEEL HAS BEEN ADDED. UPDATES.





FIGURE 1 - FITTING, ADAPTER

TABLE 1 - DIMENSIONS

BASIC NO. AS5239 /15/ SIZE CODE	(NOMINAL TUBE SIZE)	T THREAD PER AS8879 CLASS 3A	A	B ±.010	C ±.031	D	E
02	.125	.3125-24 UNJF	1.531	.542	.938	.062	.093
03	.188	.3750-24 UNJF	1.625	.605	THRU	.125	.125
04	.250	.4375-20 UNJF	1.750	.668	1.094	.172	.187
05	.312	.5000-20 UNJF	1.781	.730	THRU	.234	.234
06	.375	.5625-18 UNJF	1.891	.792	THRU	.297	.297
08	.500	.7500-16 UNJF	2.125	.980	1.344	.391	.422
10	.625	.8750-14 UNJF	2.375	1.103	1.469	.484	.500
12	.750	1.0625-12 UNJ	2.656	1.353	1.594	.609	.656
16	1.000	1.3125-12 UNJ	2.688	1.603	1.594	.845	.875
20	1.250	1.6250-12 UNJ	2.734	1.853	1.594	1.080	1.093
24	1.500	1.8750-12 UNJ	2.875	2.099	1.594	1.314	1.344
32	2.000	2.5000-12 UNJ	3.562	2.724	2.000	1.784	1.813

SAE values your input. To provide feedback
on this Technical Report, please visit
<http://www.sae.org/technical/standards/AS5239B>

THIRD ANGLE PROJECTION



CUSTODIAN: G-3/G-3B

PROCUREMENT SPECIFICATION: AS18280 /4/



AEROSPACE STANDARD

FITTING, ADAPTER, BULKHEAD,
FLARELESS TO FLARED

AS5239
SHEET 1 OF 4

REV.
B

TABLE 1A - DIMENSIONS AND WEIGHTS

BASIC NO. AS5239 /15/ SIZE CODE	H	LB/EA APPROX REF AL	LB/EA APPROX REF STEEL	LB/EA APPROX REF TI
02	.552- .565	.0140	.0403	.0222
03	.615- .628	.0196	.0564	.0311
04	.678- .691	.0247	.0710	.0391
05	.740- .753	.0313	.0899	.0496
06	.802- .815	.0396	.114	.0627
08	.990-1.003	.0708	.203	.112
10	1.113-1.128	.0988	.284	.157
12	1.363-1.380	.161	.462	.255
16	1.613-1.630	.214	.616	.340
20	1.863-1.880	.313	.899	.496
24	2.109-2.135	.394	1.13	.624
32	2.734-2.760	.895	2.57	1.42

NOTES:

NOTICE

THIS DOCUMENT REFERENCES A PART WHICH CONTAINS CADMIUM AS A PLATING MATERIAL. CONSULT LOCAL OFFICIALS IF YOU HAVE QUESTIONS CONCERNING CADMIUM'S USE.

/1/ MATERIAL:

- a. DASH AS CODE LETTER - TYPE 4130 ALLOY STEEL BAR PER AMS6370. /2/
- b. CODE LETTER D - TYPE 2024-T6 ALUMINUM ALLOY BAR PER AMS-QQ-A-225/6 OR AMS4339 OR TYPE 2024-T851 ALUMINUM ALLOY BAR PER AMS-QQ-A-225/6.
- c. CODE LETTER J - TYPE 304 CORROSION RESISTANT STEEL BAR PER AMS5639.
- d. CODE LETTER K - TYPE 316 CORROSION RESISTANT STEEL BAR PER AMS5648.
- e. CODE LETTER R - TYPE 321 CORROSION RESISTANT STEEL BAR PER AMS5645.
- f. CODE LETTER T - TYPE 6AL-4V TITANIUM ALLOY BAR PER AMS4928.
- g. CODE LETTER V - TYPE 15-5PH CORROSION RESISTANT STEEL BAR PER AMS5659. /2/
- h. CODE LETTER W - TYPE 7075-T73 ALUMINUM ALLOY BAR PER AMS-QQ-A-225/9 OR TYPE 7075-T7351 ALUMINUM ALLOY BAR PER AMS4124.

/2/ HEAT TREATMENT:

- a. DASH AS MATERIAL CODE LETTER - SEE HARDNESS REQUIREMENT PER PROCUREMENT SPECIFICATION.
- b. MATERIAL CODE LETTERS D AND W - SEE ELECTRICAL CONDUCTIVITY AND HARDNESS REQUIREMENT PER PROCUREMENT SPECIFICATION.
- c. MATERIAL CODE LETTER V - HEAT TREAT TO CONDITION H-1075 PER AMS2759/3.
- d. OTHER MATERIAL CODE LETTERS - NONE.

	AEROSPACE STANDARD	AS5239 SHEET 2 OF 4	REV. B
	FITTING, ADAPTER, BULKHEAD, FLARELESS TO FLARED		

3. FINISH:

- a. DASH AS MATERIAL CODE LETTER - CADMIUM PLATE PER AMS-QQ-P-416, TYPE II, CLASS 2 AND COAT WITH A LIGHT FILM OF OIL PER PROCUREMENT SPECIFICATION.
- b. MATERIAL CODE LETTER D - ANODIZE PER MIL-A-8625, TYPE II, CLASS 2, DYE GREEN, DUPLEX SEAL PER PROCUREMENT SPECIFICATION.
- c. MATERIAL CODE LETTER J, K, AND R - PASSIVATE PER AMS2700 PER PROCUREMENT SPECIFICATION.
- e. MATERIAL CODE LETTER T - ANODIZE PER AMS2488 OR FLUORIDE PHOSPHATE CONVERSION COAT PER AMS2486 WITH COLOR PER PROCUREMENT SPECIFICATION.
- e. MATERIAL CODE LETTER V:
 - (1) PASSIVATE PER AMS2700, TYPE 2 OR 8.
 - (2) SUFFIX FINISH CODE LETTER "P": CADMIUM PLATE PER AMS-QQ-P-416, TYPE II, CLASS 2.
- f. MATERIAL CODE LETTER W - ANODIZE PER MIL-A-8625, TYPE II, CLASS 2, DYE BROWN, DUPLEX SEAL PER PROCUREMENT SPECIFICATION.

/4/ PROCUREMENT SPECIFICATION: AS18280 EXCEPT AS SPECIFIED ON THIS STANDARD. PRODUCT SUPPLIED TO THIS SPECIFICATION SHALL BE MANUFACTURED BY AN ACCREDITED MANUFACTURER AS LISTED IN THE PERFORMANCE REVIEW INSTITUTE (PRI) QUALIFIED PRODUCTS LIST PRI-QPL-AS18280 FOR THIS STANDARD. SEE <http://www.eAuditNet.com> FOR CURRENT QPL ONLINE.

NOTE: PRI-QPL LIMITATION - WITH REVISION A OF THIS STANDARD THE PROCUREMENT SPECIFICATION HAS BEEN CHANGED FROM AS4444 FOR 5000 PSI TO AS18280 FOR 3000 PSI. USERS OF THIS FITTING FOR 5000 PSI APPLICATIONS PER AS4444 ARE ADVISED TO CONTROL SOURCE APPROVAL BY STANDARD PAGE SUPPLEMENT OR SIMILAR MEANS.

/5/ IDENTIFICATION AT LOCATION SHOWN: MARK PER AS478 CLASS C OR D OR METHOD 7A3, 15A3, OR 15B.

- a. FOR SIZE 06 AND SMALLER: MANUFACTURER'S NAME, CAGE CODE OR TRADEMARK, LETTER "AS" AND MATERIAL CODE LETTER.
- b. FOR SIZE 08 AND LARGER: MANUFACTURER'S NAME, CAGE CODE OR TRADEMARK, BASIC PART NUMBER AND MATERIAL CODE LETTER.

6. INTENDED USE:

- a. THIS STANDARD IS THE FUNCTIONAL EQUIVALENT OF MS21900 AND IS INTENDED TO BE SUITABLE AS A REPLACEMENT STANDARD.
- b. CLEANING OF ALUMINUM ALLOY AND CORROSION RESISTANT STEEL FITTINGS IN ACCORDANCE WITH ARP1176 (CODE LETTER "A") IS REQUIRED FOR OXYGEN SYSTEMS TO AVOID FIRE DUE TO PARTICLES OR OTHER CONTAMINANTS.

/7/ THE INTERNAL DIAMETER SHALL END IN A CONICAL END OF 110 DEGREES MINIMUM INCLUDED ANGLE.

/8/ THE HEX CORNERS MAY BE ROUNDED PER ARP1942.

/9/ SUFFIX LETTER A: CODE A ALUMINUM AND CORROSION RESISTANT STEEL PARTS USED IN OXYGEN SYSTEMS SHALL BE CLEANED AND PACKAGED IN ACCORDANCE WITH ARP1176 CATEGORY 2 FOR ALUMINUM AND CATEGORY 1C FOR CORROSION RESISTANT STEEL.

10. INTERPRETATION OF DRAWING PER AS4296.

11. SURFACE TEXTURE: SYMBOLS PER ASME Y14.36M. REQUIREMENTS PER ASME B46.1. UNLESS OTHERWISE SPECIFIED, MACHINED SURFACES TO BE 125 MICROINCHES Ra. SURFACES OF HEX FLATS MAY BE 250 MICROINCHES Ra.

	AEROSPACE STANDARD	AS5239 SHEET 3 OF 4	REV. B
	FITTING, ADAPTER, BULKHEAD, FLARELESS TO FLARED		