

REV.
A

AS5954

FEDERAL SUPPLY CLASS
4720





FIGURE 1- FLARELESS HOSE ASSEMBLY, STRAIGHT TO 90° ELBOW



THIRD ANGLE PROJECTION



CUSTODIAN: SAE G-3/G-3D

PROCUREMENT SPECIFICATION: /2/ AS5951

SAE Aerospace
An SAE International Group

AEROSPACE STANDARD

HOSE ASSEMBLY, POLYTETRAFLUOROETHYLENE,
PARA ARAMID REINFORCED, 275 °F, 5080 PSI,
FLARELESS, TITANIUM FITTINGS, STRAIGHT TO 90°

AS5954
SHEET 1 OF 6

**REV.
A**

TABLE 1 - HOSE AND FITTING DIMENSIONS

BASIC HOSE ASSEMBLY NO. AS5954 SIZE CODE	SIZE	/14/ FITTING TYPE	REF THREAD PER AS8879	HOSE ID	A1 MAX	A2 MAX	REF B GAGE BASIC	C/7/ FITTING DIA. MIN.	REF D1	REF D2	E MAX	REF F HEX	G MIN	G MAX	STRAIGHT FITTING BALL SIZE MIN THRU 7/16 IN	ELBOW FITTING BALL SIZE MIN THRU 7/16 IN
E	.250	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--
E	.250	S	4375-28UNJEF-3B	.212	1.92	2.06	.2930	.133	.16	.055	.58	.56	.74	.87	.120	.113
E	.250	E	.5625-24UNJEF-3B	.212	2.02	2.12	.4120	.133	.16	.055	.58	.69	.81	.94	.120	.113
G	.375	R	.4375-28UNJEF-3B	.298	2.12	2.21	.2930	.133	.16	.055	.75	.56	.74	.87	.120	.113
G	.375	S	.5625-24UNJEF-3B	.298	2.16	2.27	.4120	.226	.16	.055	.75	.69	.81	.94	.203	.192
G	.375	E	.7500-20UNJEF-3B	.298	2.29	2.36	.5600	.226	.19	.066	.75	.88	.99	1.12	.203	.192
H	.500	R	.5625-24UNJEF-3B	.391	2.38	2.49	.4120	.226	.16	.055	.88	.69	.81	.94	.203	.192
H	.500	S	.7500-20UNJEF-3B	.391	2.51	2.58	.5600	.330	.19	.066	.88	.88	.99	1.12	.297	.281
H	.500	E	.8750-20UNJEF-3B	.391	2.58	2.65	.6730	.330	.20	.066	.88	1.00	1.14	1.34	.297	.281
J	.625	R	.7500-20UNJEF-3B	.485	3.02	3.09	.5600	.330	.19	.066	1.00	.88	.99	1.12	.297	.281
J	.625	S	.8750-20UNJEF-3B	.485	3.09	3.16	.6730	.410	.20	.066	1.00	1.00	1.14	1.34	.369	.349
J	.625	E	1.0625-18UNJEF-3B	.485	3.34	3.28	.8100	.410	.23	.066	1.00	1.25	1.33	1.55	.369	.349
K	.750	R	.8750-20UNJEF-3B	.602	3.90	3.95	.6730	.410	.20	.066	1.30	1.00	1.14	1.34	.369	.349
K	.750	S	1.0625-18UNJEF-3B	.602	3.96	4.06	.8100	.510	.23	.066	1.30	1.25	1.33	1.55	.459	.434
K	.750	E	1.3125-16UNJ-3B	.602	4.07	4.47	1.0620	.510	.30	.066	1.30	1.50	1.57	1.77	.459	.434
M	1.000	R	1.0625-18UNJEF-3B	.852	4.36	4.47	.8100	.510	.23	.066	1.70	1.25	1.33	1.55	.459	.434
M	1.000	S	1.3125-16UNJ-3B	.852	4.48	4.86	1.0620	.750	.30	.066	1.70	1.50	1.57	1.77	.675	.638
M	1.000	E	--	--	--	--	--	--	--	--	--	--	--	--	--	--

TABLE 2 - HOSE OR SLEEVE OUTSIDE DIAMETERS /10/
(DIAMETERS ARE MAXIMUM UNLESS OTHERWISE NOTED)

SLEEVE CODE	SLEEVE MATERIAL	TEMP LIMIT °F	SIZE	SIZE	SIZE	SIZE	SIZE	SIZE	SIZE
-	(-) INDICATES HOSE ONLY NO SLEEVE (REF)	275	.420-.590	.525-.760	.750-.925	.870-.985	.980-1.180	1.264-1.580	
G	FIRE SLEEVE (AS1072 SIL-FG) (5 MIN) /11/ /12/ /13/	275	.97	1.15	1.38	1.5	1.75	2.06	
F	ABRASION SLEEVE SHRINK-ON (POLYOLEFIN AS1073-CODE B) /18/	275	.65	.83	.99	1.06	1.26	1.67	

TABLE 3 - HOSE ASSEMBLY LENGTH TOLERANCES

HOSE ASSEMBLY LENGTH	TOLERANCE
UNDER 18 in	±125 in
18 TO 36 in EXCLUSIVE	±250 in
36 TO 50 in EXCLUSIVE	±500 in
50 in AND OVER	±1%

REV. A		TABLE 4 - WEIGHTS /19/									
		HOSE OR SLEEVE CODE	HOSE, PART OR SLEEVE	UNITS	SIZE .250	SIZE .375	SIZE .500	SIZE .625	SIZE .750	SIZE 1.000	
AS5954	-		HOSE ONLY	LB/IN	.010	.014	.020	.023	.032	.055	
	G		FIRESLEEVE AS1072 (5 min PER AS1055)	LB/IN	.016	.019	.028	.029	.037	.041	
	F		PROTECTIVE SLEEVE, SHRINK-ON (POLYOLEFIN AS1073, CODE B) /18/	LB/IN	.002	.003	.003	.003	.005	.007	
	NONE		FIRESLEEVE CLAMP	LB/EA	.019	.019	.019	.024	.024	.028	
	NONE		FITTING END (STRAIGHT) /14/	R	LB/EA	---	.091	.137	.221	.539	1.038
				S	LB/EA	.057	.102	.162	.247	.592	1.084
				E	LB/EA	.068	.127	.188	.300	.638	---
	NONE		FITTING END (90°) /14/	R	LB/EA	---	.118	.173	.274	.665	1.291
				S	LB/EA	.072	.129	.198	.300	.718	1.337
				E	LB/EA	.095	.163	.241	.426	.891	---
	NOTES:										
1. MATERIALS:											
a. HOSE AND FITTINGS - PER AS5951.											
b. THE COLLARS MAY BE STAINLESS STEEL.											
c. SLEEVES - SEE APPLICABLE STANDARDS, TABLE 2.											
/2/ PRODUCT SUPPLIED TO THIS SPECIFICATION SHALL BE ASSEMBLED BY AN ACCREDITED MANUFACTURER OR ASSEMBLING DISTRIBUTOR LISTED IN THE PERFORMANCE REVIEW INSTITUTE (PRI) QUALIFIED PRODUCTS LIST FOR PRI-QPL-AS5951 FOR THIS STANDARD. SEE http://www.pri.sae.org/QPL/AS5951.pdf FOR CURRENT QPL ONLINE. NOTE THAT MANUFACTURERS AND ASSEMBLING DISTRIBUTORS ARE ACCREDITED BY PART NUMBER, SIZE AND MATERIAL ON THE PRI-QPL-AS5951.											
3. CONSTRUCTION AND PERFORMANCE PER AS5951. FITTINGS SHALL BE PERMANENTLY ATTACHED TO HOSE.											
4. OPERATING CHARACTERISTICS PER AS5951.											
/5/ MARKING: MARKING SHALL BE PER AS5951 ON A STAINLESS STEEL BAND NOT OVER 1.0 IN WIDE OR ON THE COLLAR. IF A BAND IS USED, IT SHALL BE LOCATED OVER THE COLLAR. THE CHARACTERS SHALL BE A MINIMUM OF .06 IN HIGH. THE BAND SHALL BE SO DESIGNED AS TO REMAIN TIGHT ON THE COLLAR TO PREVENT RELATIVE MOVEMENT AND SHALL BE OF SUFFICIENT STRENGTH TO PREVENT REMOVAL BY HAND. MARKING BAND SHALL BE COVERED WITH TRANSPARENT POLYOLEFIN SHRINK SLEEVE PER AS1073 CODE A.											
		AEROSPACE STANDARD					AS5954 SHEET 4 OF 6		REV. A		
		HOSE ASSEMBLY, POLYTETRAFLUOROETHYLENE, PARA ARAMID REINFORCED, 275 °F, 5080 PSI, FLARELESS, TITANIUM FITTINGS, STRAIGHT TO 90°									